CURIOSITY-DRIVEN UNSUPERVISED DATA COLLECTION FOR OFFLINE REINFORCEMENT LEARNING

ABSTRACT

In offline reinforcement learning (RL), while the majority of efforts are focusing on engineering sophisticated learning algorithms given a fixed dataset, very few works have been carried out to improve the dataset quality itself. More importantly, it is even challenging to collect a task-agnostic dataset such that the offline RL agent can learn multiple skills from it. In this paper, we propose a **C**uriosity-driven **U**nsupervised **D**ata **C**ollection (CUDC) method to improve the data collection process. Specifically, we quantify the agent's internal belief to estimate the probability of the k-step future states being reachable from the current states. Different from existing approaches that implicitly assume limited feature space with fixed environment steps, CUDC is capable of adapting the number of environment steps to explore. Thus, the feature representation can be substantially diversified with the dynamics information. With this adaptive reachability mechanism in place, the agent can navigate itself to collect higher-quality data with curiosity. Empirically, CUDC surpasses existing unsupervised methods in sample efficiency and learning performance in various downstream offline RL tasks of the DeepMind control suite.

1 INTRODUCTION

Deep reinforcement learning has demonstrated remarkable breakthroughs in games, robotics, and navigation in complex environments (Kiran et al., 2021; Singh et al., 2022; Sun et al., 2022a). For online RL, agents constantly update the policy to acquire different skills through active interactions with the environments. However, online RL is impractical in many real-world environments as direct interactions with the environments might be expensive or dangerous (Kiran et al., 2021; Singh et al., 2022). In recent years, offline RL has become a promising research area to cope with limited interactions, where agents learn a policy exclusively from previously-collected experiences stored in a fixed dataset (Levine et al., 2020; Kostrikov et al., 2021; Fujimoto & Gu, 2021).

In view of the growing popularity of offline RL, the majority of current research focuses on model-centric practices by successively developing new algorithms (Kumar et al., 2020; Janner et al., 2021; Matsushima et al., 2021; Emmons et al., 2022; Kumar et al., 2022). Despite the rapid progress in these algorithmic advances, their performances are inevitably limited by the quality of the pre-collected dataset itself. Recently, the concept of data-centric approaches has become critical in the machine learning community, emphasizing the importance of improving the training data quality over algorithmic advances (Ng, 2021; Motamedi et al., 2021; Patel et al., 2022). Motivated by this, the offline RL research community attempts to eye on ways of engineering the training data (Prudencio et al., 2022). To focus on more useful data, one solution is to exploit the sample importance with sampling (Zhang et al., 2020) or re-weighting (Wu et al., 2021). Different from this approach, we aim to collect a higher-quality dataset that can be directly used for offline RL agents.

More importantly, it is even more desirable yet challenging to collect a task-agnostic dataset such that offline RL agents are able to extract effective policies for multiple downstream tasks. To analyze and understand these challenges, ExORL (Yarats et al., 2022) empirically shows that unsupervised RL methods are superior to supervised methods to collect the exploratory data that allows even vanilla off-policy RL algorithms to effectively learn offline and acquire different skills. Nevertheless, the existing methods learn the feature representation by pre-defining a fixed number of environment steps between current states and future states, which limits the diversity in feature representation.

As we observe that fixing the environment step limits the feature space and results in low-quality dataset, it is desired to enhance feature representation by exploiting the reachability from current state to more distant future states. Although existing works of reachability analysis have been introduced in RL (Savinov et al., 2019; Péré et al., 2018; Ivanovic et al., 2019; Yu et al., 2022), these approaches are however not directly applicable. For example, Savinov et al. (2019) only considers the reachability in a binary case, and it requires extensive comparisons to the stored embeddings in memory. Moreover, the reachability in goal space exploration requires kernel density estimation, increasing the computational cost substantially. Different from these approaches, we propose a **C**uriosity-driven **U**nsupervised **D**ata **C**ollection (CUDC) method with a novel reachability module. Inspired by the fact that human curiosity can enhance the learning process by motivating human beings on the novel knowledge that is beyond ones' perception (Rossing & Long, 1981; Markey & Loewenstein, 2014; Sun et al., 2022b), CUDC facilitates the agent to collect a dataset curiously without any task-specific reward. In particular, we define the reachability module to characterize the probability of a k-step future state being reachable from the current state, with no episodic memory required. This module allows the agent to automatically determine the number of environment steps to explore without directly modeling the feature space density, where the feature representation can be incorporated with the information of dynamics. Compared with the existing unsupervised methods, it avoids relying on the fixed feature space by gradually expanding to more distant future states. With the enhanced representation learning, a mixed intrinsic reward encourages curious exploration towards more meaningful state-action space as well as the under-learned states. As a result, the collected dataset can lead to improved sample efficiency and better performances in downstreabelongs to noveltym offline RL tasks.

Our contributions can be summarized as follows. 1) We are the first to introduce reachability for improving data collection in offline RL, which is defined in a more efficient way and can enable the agent to navigate curiosity-driven learning coherently. 2) We empirically show that adapting the number of environment steps to perform increasingly challenging future state prediction can enhance feature representation with information of the dynamics, thereby improving the collected dataset quality. 3) With the learned state and action representations, CUDC additionally incentivizes the agent to explore diverse state-action space as well as the under-learned states with high prediction errors through a mixed intrinsic reward and regularization. 4) Under the ExORL (Yarats et al., 2022) setting, CUDC outperforms the other unsupervised methods to collect the dataset that can be learned offline in multiple downstream tasks of the DeepMind control suite (Tassa et al., 2018).

2 RELATED WORKS

Reachability in RL   Savinov et al. (2019) constructed a reachability network to estimate how many environment steps to take for reaching a particular state. It intrinsically rewards the agent to explore the state that is unreachable i.e., takes more than a fixed threshold step, from other states in memory. However, it only takes the binary case of reachability into consideration and is quite inefficient when comparing the similarity with all stored states in memory. In the goal exploration tasks, Péré et al. (2018) defined the reachability of a goal with an estimated density and proposed to sample increasingly difficult goals to reach during exploration. Although the goal space can be learned in an unsupervised manner other than in a specifically engineered way, its sampling process requires a kernel density estimator, increasing the computational cost substantially. Following the similar idea, BARC (Ivanovic et al., 2019) adapts the initial state distribution gradually from easy-to-reach to challenging-to-reach goals. As a result, agents can perform well even in a hard robotic control task. Recently, RCRL (Yu et al., 2022) has shown that leveraging reachability analysis (Hsu et al., 2021) can help learn an optimal safe policy by expanding the limited conservative feasible set to the largest feasible set of the state space.

Curiosity-Driven RL   Curiosity-driven RL intrinsically encourages agents to explore the task environment in a human-like way, which is of vital importance when the task-specific rewards are sparse or absent (Aubret et al., 2019; Sun et al., 2022b). The main type of curiosity-driven RL is to incorporate an intrinsic reward that self-motivates agents to explore based on various aspects of the state, such as novelty (Bellemare et al., 2016), entropy (Seo et al., 2021; Liu & Abbeel, 2021b), reachability (Savinov et al., 2019), prediction errors (Pathak et al., 2017; Berseth et al., 2020), complexity (Campero et al., 2020), and uncertainty (Pathak et al., 2019; Sekar et al., 2020; Li et al.,

2021). Another type of curiosity-driven RL is to prioritize the experience replay towards under-explored states (Schaul et al., 2016; Zhao & Tresp, 2019; Brittain et al., 2019; Jiang et al., 2021). However, the curiosity mechanism can be further exploited and introduced into other components of RL for exploration, as shown in CCLF (Sun et al., 2022a). Therefore, we propose to curiously adapt the environment step to explore more distant future states, enhancing the learned representation space. Meanwhile, our method regularizes the Q-learning by assigning the importance weights through a curiosity weight to focus more on under-learned tuples.

Unsupervised Data Collection   ExORL (Yarats et al., 2022) evaluates 9 unsupervised data collection algorithms, demonstrating a superior capability over supervised methods for multi-task offline learning. In particular, knowledge-driven models of ICM (Pathak et al., 2017), Disagreement (Pathak et al., 2019), and RND (Burda et al., 2019) encourage agents to explore by maximizing the prediction errors of the states. Data-driven models of APT (Liu & Abbeel, 2021b) and ProtoRL (Yarats et al., 2021) incentivize to uniformly explore the entire state space. By leveraging some prior information, competence-based models of DIAYN (Eysenbach et al., 2019), SMM (Lee et al., 2019) and APS (Liu & Abbeel, 2021a) encourage agents to learn diverse skills. However, all these methods are not tailored for data collection; instead, they were originally proposed for online pretraining and fine-turning at task learning process as evaluated in the URLB benchmark (Laskin et al., 2021). Moreover, their feature space is limited by relying on a fixed environment step k between the current state and future state. Concurrently, Explore2Offline (Lambert et al., 2022) leverages the intrinsic model predictive control to simulate trajectories and their resulting predicted intrinsic rewards, but it does not consider the sample importance while updating the policy.

3   CURIOSITY-DRIVEN UNSUPERVISED DATA COLLECTION (CUDC)

3.1   PROBLEM SETTING

We consider the problem of multi-task offline learning with three main steps of data collection, reward relabeling, and downstream offline learning as described in both ExORL(Yarats et al., 2022) and Explore2Offline (Lambert et al., 2022). In the data collection phase, the exploratory agent (data collector) has the access to a Markov Decision Process (MDP) environment with a state of the environment $s \in \mathcal{S}$, an action $a \in \mathcal{A}$ based on a policy $\pi(s)$, a transition probability $p(s'|s, a)$ mapping from the current state s and action a to the next state s', a reward r, and a discount factor $\gamma \in [0, 1)$ weighting future rewards. In particular, the exploratory agent online interacts with the environment and stores the unlabeled tuples (s, a, s') in the dataset $\mathcal{D}$. The second phase is to relabel the collected dataset $\mathcal{D}$ using the given reward function about the downstream task $r(s, a)$ for each tuple. It transfers information from task-agnostic exploration to downstream tasks. The last step is to perform multiple downstream tasks with an offline RL agent on the labeled dataset. In this paper, we focus on the most challenging part of this problem setting, which is the task-agnostic data collection and we evaluate the quality of the collected dataset in multiple downstream tasks.

Figure 1: Curiosity-driven Unsupervised Data Collection (CUDC): The diagram on the left illustrates the framework of CUDC. A batch of transition tuples is sampled from the accumulated dataset, and then the reachability between the k-step future and current states is measured by agent's internal belief. The reachability module outputs the mixed intrinsic reward to encourage diverse exploration. Meanwhile, it also outs a curiosity weight to adapt the environment steps and regularize the backbone RL. Therefore, the agent curiously collects new data until dataset capacity is reached. The diagram on the right shows how the agent measures and updates its internal belief on the probability of the k-step future states being reachable from the current states.

3.2 FRAMEWORK OVERVIEW

In this section, we propose a **C**uriosity-driven **U**nsupervised **D**ata **C**ollection (CUDC) method, which employs DDPG (Lillicrap et al., 2015) as the base RL algorithm for the exploratory agent. As shown in Figure 1 (right), a novel reachability module is constructed to measure the probability of a k-step future state being reachable from the current state. With this module in place, the exploratory agent is encouraged to diversely explore by a mixed intrinsic reward, and meanwhile regularize the critic-actor update to focus more on under-learned tuples. Most importantly, the number of environment steps is adaptively increased to incorporate the dynamics information in feature representation. As a result, the exploration becomes more diverse. More details are listed in Algorithm 1.

3.3 THE REACHABILITY MODULE

In ExORL(Yarats et al., 2022), the existing unsupervised methods assume the limited feature space by implicitly fixing the environment step k between current and future states. To diversity the feature representation, a natural choice is to employ the reachability analysis that can adjust the environment step k during exploration. However, the existing implementations of reachability are not desired due to the limited capability by binary classification of reachable states (Savinov et al., 2019), or costly density estimation of goal space (Péré et al., 2018). As these approaches are not practical in the offline RL setting, we define the reachability in CUDC by the self-supervised estimation on the probability of a k-step future state s_{t_i+k} being reachable from the current state, with no expensive density estimation or manual labelling required. s_{t_i}. As a result, the proposed method can enhance feature representation when expanding the feature space through an adaptive environment step. In fact, this motivation has been shown effective in the other works of reachability, such as constrained RL (Yu et al., 2022) and robotics (Ivanovic et al., 2019).

Given a batch of unlabeled tuples $(s_{t_i}, a_{t_i}, s_{t_i+k}, k)_{i=1}^n$, we first encode the state features $z_{s_{t_i}} = \phi_s(s_{t_i}), z_{s_{t_i+k}} = \phi_s(s_{t_i+k})$ and action feature $z_{a_{t_i}} = \phi_a(a_{t_i})$ with a state encoder $\phi_s(\cdot)$ and an action encoder $\phi_a(\cdot)$, and perform the one-hot encoding for the environment step k. To facilitate the reachability analysis, a forward dynamic network $\hat{z}_{s_{t_i+k}} = f_s(z_{s_{t_i}}, z_{a_{t_i}}, k; \theta_s)$ is constructed, which takes the inputs of $z_{s_{t_i}}, z_{a_{t_i}}$, and the encoded k to predict the future state feature $\hat{z}_{s_{t_i+k}}$, fully exploiting the information of dynamics. It can be updated by an l_2 norm loss of $||z_{s_{t_i+k}} - \hat{z}_{s_{t_i+k}}||_2$. In addition, we want to enforce $\hat{z}_{s_{t_i+k}}$ to match with its own $z_{s_{t_i+k}}$ as much as possible, while keeping apart from the other future states within the same batch. The intuition is that each future state should be most reachable from its own current state. Therefore, the reachability module can estimate the probability of s_{t_i+k} being reachable from s_{t_i} by

$$l_i = \frac{\exp(h(\hat{z}_{s_{t_i+k}})^T W \bar{h}(\bar{z}_{s_{t_i+k}}))}{\exp(h(\hat{z}_{s_{t_i+k}})^T W \bar{h}(\bar{z}_{s_{t_i+k}})) + \sum_{j=1, j \neq i}^n \exp(h(\hat{z}_{s_{t_i+k}})^T W \bar{h}(\bar{z}_{s_{t_j+k}}))} \tag{1}$$

where n is the batch size, $h(\cdot)$ is a deterministic projection function, W is a hidden weight to compute the similarity between the two projections, and $\bar{h}(\cdot)$ as well as $\bar{z}(\cdot)$ are respectively the momentum-based moving average of the projection and state feature to ensure consistency and stability (He et al., 2020). In this way, this reachability network can be updated by the loss of $\mathcal{L}_{\text{reach}} = -\sum_{i=1}^n \log l_i$ in a self-supervised way without maunal labeling.

To further improve the representation learning, the reachability module also includes two inverse models for predicting action feature $\hat{z}_{a_{t_i}}$ and environment step $\hat{k}$. Similar to ICM (Pathak et al., 2017) and Disagreement (Pathak et al., 2019), we define $\hat{z}_{a_{t_i}} = f_a(z_{s_{t_i}}, z_{s_{t_i+k}}, k; \theta_a)$ with a backward loss of $||z_{a_{t_i}} - \hat{z}_{a_{t_i}}||_2$, which ensures the encoded features are robust to environment variations that are uncontrollable by the agent. For the inverse model of the environment step, $\hat{k} = f_k(z_{s_{t_i}}, z_{s_{t_i+k}}; \theta_k)$ characterizes the prediction with a distribution $\mathbb{P}(k)$. It is updated through a cross-entropy loss, which enables the encoders to capture the dynamics information in the encoded features.

The agent can therefore update its internal belief in a self-supervised manner without any expensive labeling process compared to supervised learning. More importantly, we can allow the environment step to adapt during learning, rather than relying on a fixed hyperparameter in many existing unsupervised methods. It is of vital importance as the feature representations of both states and actions

become more informative and robust when adjusting the environment step. Meanwhile, this module is also capable of computing a curiosity weight w_i for each tuple i as

$$w_i = 1 - l_i \in [0, 1]. \tag{2}$$

Intuitively, a large value of w_i means that the agent mistakenly believes the true future state is unreachable from the current state, which induces high curiosity due to the conflict with agent's current internal belief. It further indicates that this under-learned transition tuple contains novel information, and the encoders are not capable of extracting meaningful features yet. With this reachability module in place, we can enable the agent to perform the task-agnostic dataset collection in a curious manner. Detailed curiosity-driven learning is illustrated in the next subsection.

3.4 CURIOSITY-DRIVEN LEARNING

It should be noted that reachability in previous works is only incorporated as an intrinsic reward to encourage diverse exploration. In contrast, our proposed CUDC extends the reachability to more stages of learning. Firstly, it adapts the number of environment steps to explore, enhancing feature representation with the dynamics information of more distant future states. Secondly, it incorporates a mixed intrinsic reward to encourage effective exploration with the expanded feature space. Lastly, it regularizes the critic-actor update for the DDPG algorithm by utilizing the curiosity weights to focus more on under-learned tuples. Different from the 8 existing methods evaluated in ExORL that only utilize intrinsic rewards as curiosity, our CUDC extends curiosity-driven learning to different RL components, improving the data collection process coherently.

3.4.1 ENHANCE FEATURE REPRESENTATION WITH ADAPTIVE ENVIRONMENT STEPS

It is worth noting that all 8 methods discussed in ExORL limit the autonomy of feature space by expecting the agent to reach the future states in exactly 3 steps. Recent works on online pre-training RL such as SPR (Schwarzer et al., 2020) and SGI (Schwarzer et al., 2021) predict agent's own latent state representations multiple steps into the future, addressing the challenge of sample efficiency. However, this approach requires iterative predictions by calling the forward dynamic network for k times. In contrast, CUDC can automatically adjust the environment step k to directly perform the k-step future state estimation in the proposed reachability module, without increasing the computational complexity substantially. To expand the feature space by leveraging the dynamics information, our main idea is to keep the reachability estimation increasingly challenging with an adaptive environment step.

In particular, we adaptively adjust the number of enviroment steps k by encouraging curiosity, i.e., k is increased by 1 if the agent is not curious enough for the current reachability analysis. For this purpose, we set a threshold C_w for low curiosity and a threshold C_k for the proportion of tuples with low curiosity. Thus, the agent will adapt k when $\frac{\sum_i^n \mathbf{1}[w_i < C_w]}{n} > C_k$. The intuition is that the agent should be encouraged to explore further based on the reachability, when they are no longer curious about the majority of tuples within the same batch. As a result, the feature representation can be enhanced by learning the dynamics of more distant future states. With the expanded feature space, the data collection is performed towards more informative and diverse features. It should be noted that there are many possible ways to vary the environment step such as sampling from a probabilistic distribution. For this reason, an ablation study is also conducted to validate the effectiveness of the proposed curiosity-driven method, compared to other sampling-based methods.

3.4.2 INCORPORATE A MIXED INTRINSIC REWARD

CUDC employs a mixed intrinsic reward of state-action entropy and prediction error of future states. On one hand, the existing methods of APT (Liu & Abbeel, 2021b) and RE3 (Seo et al., 2021) have shown that agents can be encouraged to explore the state space more uniformly, by utilizing the particle-based k-nearest neighbors state entropy as an intrinsic reward. This is consistent with the entropy maximization principle (Beirlant et al., 1997; Singh et al., 2003). However, we believe that the agent should diversely explore not only the state space, but also the action space. Therefore, CUDC extends state embedding to state-action embedding and we prove that the k-nearest neighbor entropy estimation in the state-action representation space can be used for entropy maximization.

Algorithm 1 Implementation of the proposed CUDC

Initialize parameters of encoders ϕ_s and ϕ_a, forward dynamic network f_s, inverse models f_a and f_k, projection h, critic Q, policy π, hidden weight W, and the environment step k
Initialize the task-agnostic dataset $\mathcal{D} = \emptyset$

  for each timestep t **do**
    // COLLECT TRANSITIONS
    Interact with the environment using the policy $a_t \sim \pi(s_t)$ and observe s_{t+1}
    $\mathcal{D} \cup (s_t, a_t, s_{t+1}) \to \mathcal{D}$
    // UPDATE INTERNAL BELIEF OF REACHABILITY
    Sample a minibatch $\{(s_{t_i}, a_{t_i}, s_{t_i+k}, k)\}_{i=1}^n \sim \mathcal{D}$
    for each tuple i in the minibatch **do**
      Encode the state and action, and predict the $t_i + k$'s future state feature $\hat{z}_{s_{t_i+k}}$
      Evaluate the curiosity weight w_i according to Equation (2)
      Compute the intrinsic reward r_i using w_i by Equation (3)
    end for
    Update the internal belief of reachability module
    //ADAPT THE ENVIRONMENT STEP TO PREDICT
    if $\frac{1}{n}\sum_i^n \mathbf{1}[\mathrm{w_i} < \mathrm{C_w}] > C_k$ **then**
      Increase the environment step $k = k + 1$
    end if
    //REGULARIZE CRITIC-ACTOR UPDATE
    Update the critic Q with regularization by Equation (4)
    Update the actor π with regularization
    Perform the momentum update for $\bar{h}$ and $\bar{z}$
  end for

Lemma 3.1. *Let $u = (z_s, z_a)$ represent the state-action representation. The particle-based entropy $\mathcal{H}(u)$ is proportional to a K-nearest neighbor (K-NN) distance,*

$$\mathcal{H}(u) \propto \sum_{i=1}^n \log ||u_i - u_i^{K\text{-}NN}||_2.$$

Following the same idea to treat each tuple as a particle (Liu & Abbeel, 2021b; Seo et al., 2021), we formulate an intrinsic reward to estimate the particle-based entropy, $r_\mathcal{H}(s_{t_i}, a_{t_i}) = \log(\frac{1}{N_K}\sum ||u_i - u_i^{K\text{-}NN}||_2 + 1)$ where $u_i = (\phi_s(s_{t_i}), (\phi_a(a_{t_i}))$ and N_K is the number of K-NN. As the encoded features are constantly updated to capture the dynamics of more distant future states in the reachability module, the proposed $r_\mathcal{H}$ can lead to a more diverse state-action space exploration, where the state-of-the-art off-policy RL algorithm SAC (Haarnoja et al., 2018) has also shown that exploration through a discounted maximum-policy (actor)-entropy term is more effective.

On the other hand, the prediction errors of future states are often employed as the intrinsic reward to incentivize the agent to explore surprising states that are beyond their exceptions (Pathak et al., 2017; Burda et al., 2018). CUDC additionally integrates the prediction error $r_\mathcal{E}(s_{t_i}, a_{t_i}) = ||z_{s_{t_i+k}} - \hat{z}_{s_{t_i+k}}||_2$ in the intrinsic reward as well, where the reachability module is conveniently re-used without additional networks. Finally, the mixed intrinsic reward in CUDC is given by

$$r_i(s_{t_i}, a_{t_i}) = r_\mathcal{H}(s_{t_i}, a_{t_i}) + \alpha r_\mathcal{E}(s_{t_i}, a_{t_i}) + \beta, \tag{3}$$

where α controls the prioritization of under-learned state exploration and β is a constant for numerical stability.

3.4.3 REGULARIZE THE CRITIC-ACTOR UPDATE

Furthermore, CUDC adaptively regularizes the backbone DDPG algorithm to focus more on under-learned tuples, by utilizing the curiosity weight w_i. In particular, $w = (w_1, w_2, \cdots, w_n)$ quantitatively describes the curiosity weight on each transition tuple, which can be seamlessly used to characterize the sample importance and regularize both critic and actor updates. Therefore, we can perform the Q-learning in DDPG by minimizing the following objective,

$$\mathbb{E}_{(s,a,s')\sim\mathcal{D}}\left[w\left(Q(s,a) - (r_i(s,a) + \gamma Q_{\text{target}}(s', \pi(s')))\right)^2\right]. \tag{4}$$

Meanwhile, the policy can be updated by maximizing $\mathbb{E}_{(s,a,s')\sim\mathcal{D}}\left[wQ(s,\pi(s))\right]$. In this way, CUDC facilitates the agent to adapt the learning process in a self-supervised manner in the sense that the regularization is controlled by the conceptualized curiosity to exploit sample importance.

4 EXPERIMENTAL RESULTS

Environments We evaluate the proposed CUDC on continuous control tasks with state observations in the DeepMind control suite (Tassa et al., 2018), which consists of 12 downstream tasks across 3 main challenging domains: Walker, Quadruped, and Jaco Arm. Walker is a controllable entity with locomotion-related balancing controls, where it can learn walking, running, flipping and standing. Quadruped is a passively stable body in a more challenging 3D environment to learn various locomotion skills of walking, running, standing, and jumping. Jaco Arm is 6 degree-of-freedom robotic arm with a three-finger gripper for object manipulation, where the downstream tasks require it to reach different positions. Note that PointMass Maze is not included since most baseline methods in ExORL have already demonstrated excellent performances.

Baseline Models We compare CUDC against state-of-the-art unsupervised methods across all three categories as benchmarked in ExORL, i.e., a knowledge-driven baseline of ICM (Pathak et al., 2017), data-driven baselines of APT (Liu & Abbeel, 2021b) and ProtoRL (Yarats et al., 2021), and a competence-driven baseline of APS (Liu & Abbeel, 2021a). Meanwhile, a random data collector is also included, which collects the data by performing randomly sampled actions. The other four methods discussed in ExORL are excluded since their performance are less competitive. We set the same hyperparameters and model architecture as reported in ExORL. To demonstrate that all proposed components play important roles in the performance, we also compare four versions of CUDC as follows. $\text{CUDC}_{\text{vary}}^{\text{ICM}}$ and $\text{CUDC}_{\text{vary}}^{\text{APT}}$: adapting the environment step k by the intrinsic rewards based on the original ICM and APT methods. $\text{CUDC}_{\text{reward}}$: extending to state-action entropy with a mixed intrinsic reward based on $\text{CUDC}_{\text{vary}}^{\text{APT}}$. $\text{CUDC}_{\text{reach}}$: adding the full reachability module without regularization based on $\text{CUDC}_{\text{reward}}$. The detailed implementation and differences from the full model are summarized in Appendix A.

Model Training and Evaluation To impose model stability during learning, we restrict the environment step k to be increased from 3 to 6 and set the upper and lower bounds for the regularization weights to ensure stability. For further details regarding the network implementation and hyperparameter setting of the proposed CUDC, readers can refer to Appendix A. During data collection, all methods are trained using a DDPG (Lillicrap et al., 2015) agent as the backbone for fairness. They interact with 3 domain environments in the absence of extrinsic rewards for 1M steps. For the main results, a total of 90 datasets (6 algorithms $\times$ 3 main tasks $\times$ 5 seeds) are collected. After that, relabeling is performed for each downstream task on the collected dataset. During the evaluation, a TD3 (Fujimoto et al., 2018) agent learns offline from each relabeled dataset for 500K steps. We report the performance score at 100K step for sample efficiency and at 500K step for learning performance.

Main Results on 12 Downstream Tasks As shown in Figure 2, no single baseline method can greatly improve the dataset quality for all domains. In contrast, the dataset collected by CUDC is capable of boosting the offline agent's learning performances at 500K step in all 12 downstream tasks across 3 challenging domains, as highlighted in Table 1. Specifically, CUDC outperforms the competence-based method (APS) in the Walker domain by 6%, outperforms the data-based method (APT) in the Quadruped domain by 51%, and outperforms the knowledge-based method (ICM) in the Jaco Arm domain by 10%. As for the sample efficiency, it can be observed in Figure 2 that CUDC leads to the best sample efficiency with a significant margin on 3 downstream tasks of Quadruped. In the easy domain of Walker, CUDC can help the offline agent to converge faster in 3 downstream tasks. However, the sample efficiency in the hardest domain of Jaco Arm is not desirable. It might be caused by too much complexity in this most challenging environment, increasing the difficulty of reachablility analysis.

Effects of Adapting the k-Step We empirically show that adapting the environment steps to explore more distant future states can certainly help to enhance the feature representation, and thereby improve the data collection process. By comparing the results in Figure 3, $\text{CUDC}_{\text{vary}}^{\text{ICM}}$ has outper-

Table 1: Main results of the offline RL agent on 12 downstream tasks across 3 main domains. The proposed CUDC collects a more useful dataset such that offline RL agents can improve sample efficiency (100K) in 9 out of 12 downstream tasks and achieve better learning performance (500K) in all 12 downstream tasks.

100K Step Score	Random	APS	ProtoRL	ICM	APT	CUDC
Walker, Walk	190±153	652±227	532±332	503±258	548±338	**827±64**
Walker, Flip	175±136	590±77	610±95	530±59	579±51	**615±66**
Walker, Run	53±25	368±77	332±81	233±111	372±40	**381±37**
Walker, Stand	401±295	923±76	831±318	797±312	878±101	**984±11**
Quadruped, Walk	135±101	206±25	153±119	**338±211**	248±22	**338±147**
Quadruped, Run	145±96	183±17	121±31	210±63	249±24	**256±133**
Quadruped, Stand	271±105	334±148	193±78	585±301	524±153	**618±311**
Quadruped, Jump	223±60	237±83	150±89	466±208	391±127	**483±222**
Jaco Arm, Reach Top Left	5±4	63±40	68±49	**88±78**	42±77	54±60
Jaco Arm, Reach Top Right	49±37	**119±64**	76±39	99±73	51±67	32±59
Jaco Arm, Reach Bottom Left	35±31	87±74	76±75	**101±46**	30±43	74±89
Jaco Arm, Reach Bottom Right	49±46	100±75	85±66	113±89	92±42	**121±79**

500K Step Score	Random	APS	ProtoRL	ICM	APT	CUDC
Walker, Walk	198±266	845±38	826±67	802±67	799±73	**893±34**
Walker, Flip	303±195	561±121	645±150	534±218	591±77	**717±41**
Walker, Run	62±24	369±33	386±38	261±142	384±20	**393±11**
Walker, Stand	519±312	949±24	954±17	868±73	890±139	**971±7**
Quadruped, Walk	77±53	169±38	177±181	231±107	363±141	**425±76**
Quadruped, Run	102±52	179±52	77±36	165±89	198±57	**349±80**
Quadruped, Stand	162±96	335±80	127±111	343±133	464±144	**637±188**
Quadruped, Jump	152±74	261±71	99±51	242±108	329±85	**574±74**
Jaco Arm, Reach Top Left	59±75	129±26	138±52	166±54	41±29	**212±11**
Jaco Arm, Reach Top Right	81±54	152±82	166±19	195±36	95±32	**214±17**
Jaco Arm, Reach Bottom Left	91±68	103±74	100±68	**216±16**	101±56	**218±7**
Jaco Arm, Reach Bottom Right	107±56	197±33	149±69	**229±8**	131±33	**229±6**

Figure 2: Learning curves of the offline RL agent on the task-agnostic dataset collected by different methods. The proposed CUDC demonstrates superior capability of improving the sample efficiency and learning performances of the offline RL agent.

formed ICM significantly, with on average $1.25\times$ sample efficiency at 100K step and $1.16\times$ offline learning performance at 500K step. Similarly, $\text{CUDC}_{\text{vary}}^{\text{APT}}$ obtains respectively $1.12\times$ and $1.04\times$ scores at 100K and 500K steps across 4 downstream tasks, compared with APT. We note that the standard deviation increases a bit, which might be caused by the introduced complexity of more distant future state when improving the learned representation. Thus, it is desirable to find an adaptive way to smooth this process, e.g., by incorporating the other proposed components inherently.

Effectiveness of the Other Proposed Components We additionally incorporate the mixed intrinsic reward to $\text{CUDC}_{\text{vary}}^{\text{APT}}$ as $\text{CUDC}_{\text{reward}}$, and it further improves both sample-efficiency and learning capability of the offline RL agent, shown in Table 4 and Figure 3. As the new intrinsic reward en-

Figure 3: The performance score evaluated at 100K and 500K steps in 4 downstream tasks of Walker. All four versions of CUDC perform better than ICM and APT.

courages a more uniform exploration on the state-action space and focuses more on under learned states, the performance at 100K is inevitably unstable, with a 67% increase of standard deviation. Therefore, it is necessary to leverage the proposed reachability module as agent's internal belief and facilitate the data collection. By comparing $\text{CUDC}_{\text{reach}}$ with $\text{CUDC}_{\text{reward}}$, the dataset collected by $\text{CUDC}_{\text{reach}}$ stabilizes the offline learning process by reducing 48% and 25% of standard deviation at 100K and 500K steps. However, its performance scores slightly decrease in 2 tasks. To address this problem, the full model further regularizes the critic-actor update with a curiosity weight, compared with $\text{CUDC}_{\text{reach}}$. It achieves the best performances with minimum standard deviation at 500K step. It can be concluded that all components play important roles to collect a useful dataset for improving the downstream task learning and resolving instability on offline RL agents.

Figure 4: Learning curves of the offline RL agent on 4 downstream tasks of Walker. The adaptive environment step proposed in CUDC performs better than the other two sampling in 3 out of 4 downstream tasks.

Adjusting the Environment Step in Different Ways   One may wonder how the feature representation improves with different ways of adjusting the environment step k in the reachability module. Thus, we explicitly conduct an ablation study on the Walker domain by sampling k uniformly (Uniform) from 3 to 6 and normally (Normal) with an increasing mean. It can be observed in Figure 4 that Uniform performs the worst in all 4 tasks as it cannot adapt the environment step to enhance the representation learning. At 500K step, it only achieves 85% overall learning capability with 300% increase in the standard deviation, compared to CUDC. Normal to some extent adapts the environment step through an increasing mean, and it even outperforms CUDC in the Flip task. However, its overall performance is still 4.5% weaker than CUDC and its standard deviation is 128% higher than CUDC, indicating the instability issue. Overall, the curious way proposed in CUDC is the best and it is interesting to investigate more adaptive ways in the future.

5 CONCLUSION

We propose CUDC, a curiosity-driven unsupervised data collection method to improve the dataset quality for offline RL agents in the multi-task setting. A reachability module is introduced, quantifying agent's internal belief of estimating the probability of a k-step future state being reachable form the current state. Substantially, CUDC can enhance feature representation by adaptively allowing the agent to explore more distant future states in the reachability module. Empirically, CUDC demonstrates superior data collection capability with improved sample efficiency and better performances in downstream multi-task offline learning. We also present this work with insightful empirical evidence of effective data collection methods for future research.

REFERENCES

Arthur Aubret, Laetitia Matignon, and Salima Hassas. A survey on intrinsic motivation in reinforcement learning. *arXiv preprint arXiv:1908.06976*, 2019.

Jan Beirlant, Edward J Dudewicz, László Györfi, Edward C Van der Meulen, et al. Nonparametric entropy estimation: An overview. *International Journal of Mathematical and Statistical Sciences*, 6(1):17–39, 1997.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. *NeurIPS*, 29:1471–1479, 2016.

Glen Berseth, Daniel Geng, Coline Manon Devin, Nicholas Rhinehart, Chelsea Finn, Dinesh Jayaraman, and Sergey Levine. Smirl: Surprise minimizing reinforcement learning in unstable environments. In *International Conference on Learning Representations*, 2020.

Marc Brittain, Josh Bertram, Xuxi Yang, and Peng Wei. Prioritized sequence experience replay. *arXiv preprint arXiv:1905.12726*, 2019.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. In *International Conference on Learning Representations*, 2018.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *Seventh International Conference on Learning Representations*, pp. 1–17, 2019.

Andres Campero, Roberta Raileanu, Heinrich Kuttler, Joshua B Tenenbaum, Tim Rocktäschel, and Edward Grefenstette. Learning with amigo: Adversarially motivated intrinsic goals. In *International Conference on Learning Representations*, 2020.

Scott Emmons, Benjamin Eysenbach, Ilya Kostrikov, and Sergey Levine. Rvs: What is essential for offline rl via supervised learning? In *International Conference on Learning Representations*, 2022.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2019.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. *Advances in neural information processing systems*, 34:20132–20145, 2021.

Scott Fujimoto, Herke Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *International conference on machine learning*, pp. 1587–1596. PMLR, 2018.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Kai Chieh Hsu, Vicenç Rubies-Royo, Claire J Tomlin, and Jaime F Fisac. Safety and liveness guarantees through reach-avoid reinforcement learning. In *17th Robotics: Science and Systems, RSS 2021*. MIT Press Journals, 2021.

Boris Ivanovic, James Harrison, Apoorva Sharma, Mo Chen, and Marco Pavone. Barc: Backward reachability curriculum for robotic reinforcement learning. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 15–21. IEEE, 2019.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. *Advances in neural information processing systems*, 34:1273–1286, 2021.

Minqi Jiang, Edward Grefenstette, and Tim Rocktäschel. Prioritized level replay. In *ICML*, pp. 4940–4950. PMLR, 2021.

B Ravi Kiran, Ibrahim Sobh, Victor Talpaert, Patrick Mannion, Ahmad A Al Sallab, Senthil Yoga-mani, and Patrick Pérez. Deep reinforcement learning for autonomous driving: A survey. *IEEE Transactions on Intelligent Transportation Systems*, 2021.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In *International Conference on Machine Learning*, pp. 5774–5783. PMLR, 2021.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:1179–1191, 2020.

Aviral Kumar, Joey Hong, Anikait Singh, and Sergey Levine. Should i run offline reinforcement learning or behavioral cloning? In *International Conference on Learning Representations*, 2022.

Nathan Lambert, Markus Wulfmeier, William Whitney, Arunkumar Byravan, Michael Bloesch, Vib-havari Dasagi, Tim Hertweck, and Martin Riedmiller. The challenges of exploration for offline reinforcement learning. *arXiv preprint arXiv:2201.11861*, 2022.

Michael Laskin, Denis Yarats, Hao Liu, Kimin Lee, Albert Zhan, Kevin Lu, Catherine Cang, Lerrel Pinto, and Pieter Abbeel. Urlb: Unsupervised reinforcement learning benchmark. *arXiv preprint arXiv:2110.15191*, 2021.

Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric Xing, Sergey Levine, and Ruslan Salakhutdi-nov. Efficient exploration via state marginal matching. *arXiv preprint arXiv:1906.05274*, 2019.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *ArXiv e-prints*, pp. arXiv–1607, 2016.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tuto-rial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Kevin Li, Abhishek Gupta, Ashwin Reddy, Vitchyr H Pong, Aurick Zhou, Justin Yu, and Sergey Levine. Mural: Meta-learning uncertainty-aware rewards for outcome-driven reinforcement learning. In *ICML*, pp. 6346–6356, 2021.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

Hao Liu and Pieter Abbeel. Aps: Active pretraining with successor features. In *International Conference on Machine Learning*, pp. 6736–6747. PMLR, 2021a.

Hao Liu and Pieter Abbeel. Behavior from the void: Unsupervised active pre-training. *Advances in Neural Information Processing Systems*, 34:18459–18473, 2021b.

Amanda Markey and George Loewenstein. Curiosity. *International handbook of emotions in edu-cation*, pp. 238–255, 2014.

Tatsuya Matsushima, Hiroki Furuta, Yutaka Matsuo, Ofir Nachum, and Shixiang Gu. Deployment-efficient reinforcement learning via model-based offline optimization. In *ICLR*, 2021.

Mohammad Motamedi, Nikolay Sakharnykh, and Tim Kaldewey. A data-centric approach for train-ing deep neural networks with less data. *arXiv preprint arXiv:2110.03613*, 2021.

Andrew Ng. A chat with andrew on mlops: From model-centric to data-centric ai, 2021.

Hima Patel, Shanmukha Guttula, Ruhi Sharma Mittal, Naresh Manwani, Laure Berti-Equille, and Abhijit Manatkar. Advances in exploratory data analysis, visualisation and quality for data centric ai systems. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 4814–4815, 2022.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International conference on machine learning*, pp. 2778–2787. PMLR, 2017.

Deepak Pathak, Dhiraj Gandhi, and Abhinav Gupta. Self-supervised exploration via disagreement. In *International conference on machine learning*, pp. 5062–5071. PMLR, 2019.

Alexandre Péré, Sébastien Forestier, Olivier Sigaud, and Pierre-Yves Oudeyer. Unsupervised learning of goal spaces for intrinsically motivated goal exploration. In *International Conference on Learning Representations*, 2018.

Rafael Figueiredo Prudencio, Marcos ROA Maximo, and Esther Luna Colombini. A survey on offline reinforcement learning: Taxonomy, review, and open problems. *arXiv preprint arXiv:2203.01387*, 2022.

Boyd E Rossing and Huey B Long. Contributions of curiosity and relevance to adult learning motivation. *Adult Education*, 32(1):25–36, 1981.

Nikolay Savinov, Anton Raichuk, Damien Vincent, Raphael Marinier, Marc Pollefeys, Timothy Lillicrap, and Sylvain Gelly. Episodic curiosity through reachability. In *International Conference on Learning Representations*, 2019.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *ICLR (Poster)*, 2016.

Max Schwarzer, Ankesh Anand, Rishab Goel, R Devon Hjelm, Aaron Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. In *International Conference on Learning Representations*, 2020.

Max Schwarzer, Nitarshan Rajkumar, Michael Noukhovitch, Ankesh Anand, Laurent Charlin, R Devon Hjelm, Philip Bachman, and Aaron C Courville. Pretraining representations for data-efficient reinforcement learning. *Advances in Neural Information Processing Systems*, 34:12686–12699, 2021.

Ramanan Sekar, Oleh Rybkin, Kostas Daniilidis, Pieter Abbeel, Danijar Hafner, and Deepak Pathak. Planning to explore via self-supervised world models. In *ICML*, pp. 8583–8592. PMLR, 2020.

Younggyo Seo, Lili Chen, Jinwoo Shin, Honglak Lee, Pieter Abbeel, and Kimin Lee. State entropy maximization with random encoders for efficient exploration. In *International Conference on Machine Learning*, pp. 9443–9454. PMLR, 2021.

Bharat Singh, Rajesh Kumar, and Vinay Pratap Singh. Reinforcement learning in robotic applications: a comprehensive survey. *Artificial Intelligence Review*, 55(2):945–990, 2022.

Harshinder Singh, Neeraj Misra, Vladimir Hnizdo, Adam Fedorowicz, and Eugene Demchuk. Nearest neighbor estimates of entropy. *American journal of mathematical and management sciences*, 23(3-4):301–321, 2003.

Chenyu Sun, Hangwei Qian, and Chunyan Miao. Cclf: A contrastive-curiosity-driven learning framework for sample-efficient reinforcement learning. In *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence, IJCAI-22*, pp. 3444–3450, 7 2022a. Main Track.

Chenyu Sun, Hangwei Qian, and Chunyan Miao. From psychological curiosity to artificial curiosity: Curiosity-driven learning in artificial intelligence tasks. *arXiv preprint arXiv:2201.08300*, 2022b.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

Yue Wu, Shuangfei Zhai, Nitish Srivastava, Joshua M Susskind, Jian Zhang, Ruslan Salakhutdinov, and Hanlin Goh. Uncertainty weighted actor-critic for offline reinforcement learning. In *International Conference on Machine Learning*, pp. 11319–11328. PMLR, 2021.

Denis Yarats, Rob Fergus, Alessandro Lazaric, and Lerrel Pinto. Reinforcement learning with prototypical representations. In *International Conference on Machine Learning*, pp. 11920–11931. PMLR, 2021.

Denis Yarats, David Brandfonbrener, Hao Liu, Michael Laskin, Pieter Abbeel, Alessandro Lazaric, and Lerrel Pinto. Don't change the algorithm, change the data: Exploratory data for offline reinforcement learning. *arXiv preprint arXiv:2201.13425*, 2022.

Dongjie Yu, Haitong Ma, Shengbo Li, and Jianyu Chen. Reachability constrained reinforcement learning. In *International Conference on Machine Learning*, pp. 25636–25655. PMLR, 2022.

Ruiyi Zhang, Bo Dai, Lihong Li, and Dale Schuurmans. Gendice: Generalized offline estimation of stationary values. *arXiv preprint arXiv:2002.09072*, 2020.

Rui Zhao and Volker Tresp. Curiosity-driven experience prioritization via density estimation. *arXiv preprint arXiv:1902.08039*, 2019.

A CUDC Implementation and Hyperparameter Setting

A.1 Implementation Details

A.1.1 CUDC

In the reachability module of CUDC shown in Figure 1, the state encoder ϕ_s is a 1-layer MLP with the ReLU activation. Subsequently, the output is passed to a single normalized fully-connected layer by LayerNorm (Lei Ba et al., 2016) with the tanh nonlinearity applied at the end. The target encoder is momentum updated from the state encoder to obtain $\bar{z}$. The action encoder ϕ_a is a 3-layer MLP with the ReLU activation. For the forward network f_s and the backward networks f_a and f_k, they are 2-layer MLP with the ReLU activation. The projection network h is a 2-layer MLP with hidden size of 128 and output size of 64, followed by LayerNorm. $\bar{h}$ is also momentum updated from h.

A.1.2 CUDC$_{\text{VARY}}^{\text{ICM}}$ and CUDC$_{\text{VARY}}^{\text{APT}}$

CUDC$_{\text{vary}}^{\text{ICM}}$ and CUDC$_{\text{vary}}^{\text{APT}}$ are two variants of the proposed CUDC. Given the implementation of ICM and APT in ExORL (Yarats et al., 2022), we added the forward network f_s and backward network f_k in order to let these models learn more feature representations with the dynamics information. Therefore, the environment step k can be adapted in a similar way as in CUDC. k is increased by 1 if the proportion of tuples with low intrinsic rewards is greater than a threshold, i.e. $\frac{\sum_i^n \mathbf{1}[r_i < C_r]}{n} > C_k$. In this way, we can investigate the effects of adapting environment step on two unsupervised baseline methods.

A.1.3 CUDC$_{\text{REWARD}}^{\text{APT}}$

CUDC$_{\text{reward}}^{\text{APT}}$ is a variant of the proposed CUDC. Given the implementation of CUDC$_{\text{vary}}^{\text{APT}}$ in the previous subsection, we extended the state entropy to state-action entropy and meanwhile add a prediction error of the k-step future state as formulated in Equation (3). Therefore, agent can be encouraged to explore more diverse state-action space while focusing on the under states with high prediction errors. In this way, we can investigate the effects of the proposed mixed intrinsic reward.

A.1.4 CUDC$_{\text{REACH}}^{\text{APT}}$

CUDC$_{\text{reach}}^{\text{APT}}$ is a variant of the proposed CUDC. Given the implementation of CUDC$_{\text{reward}}^{\text{APT}}$ in the previous subsection, we incorporated the full reachability module with the reachable network. As a result, the adaptive update of the environment step can be facilitated by the curiosity weight w outputted by the reachability module and the enhanced representation learning can be carried out in a self-supervised manner. Compared with the full CUDC model, CUDC$_{\text{reach}}^{\text{APT}}$ has disabled the regularization of the critic-actor update. In this way, we can investigate the effects of the proposed reachability module.

A.2 Hyperparameter Setting

A.2.1 Data Collection

We provide a full set of common hyperparameters used in baselines as welll as CUDC in Table 2, which closely follows the same settings from ExORL (Yarats et al., 2022) and URLB (Laskin et al., 2021).

For the other hyperparameter used in CUDC, they are listed in Table 3.

It should be noted that Explore2Offline (Lambert et al., 2022) is a concurrent work for data collection, but its source code is not available at the moment.

A.2.2 Offline RL

For the offline RL agent, we follow the findings reported in ExORL that even the vanilla off-policy RL algorithm of TD3 (Fujimoto et al., 2018) can outperform the carefully designed offline RL algorithms when the collected dataset is of high quality. Thus, we implement an offline RL of TD3

Table 2: Common hyperparameter setting for the unsupervised data collection methods

Hyperparameter	Value
Observation type	states
Replay buffer Size	10^6
Action repetitions	1
Seed frames	4000
Batch size	1024
Discount factor	0.99
Optimizer	Adam
Learning rate	10^{-4}
Non-linearity	ReLU
Agent update frequency	2
Critic target EMA rate	0.01
Hidden dimention	1024
Exploration stddev clip	0.3
Exploration stddev value	0.2

Table 3: Hyperparameter setting for the proposed CUDC

Hyperparameter	Value
Environment step range	3, 4, 5, 6
State representation dimension	512
Actor representation dimension	64
MLP hidden dimension for action encoder	64 for action encoder
MLP hidden dimension	128 for projection
Projection dimension	64
Regularization clip	[0.2, 2] for Walker
	[0.2, 1] for Quadruped
	[0.9, 1] for Jaco Arm
Intrinsic reward weights (α, β)	$(10^{-3}, 10^{-2})$ for Walker
	$(10^{-4}, 10^{-2})$ for Quadruped
	$(100, 0)$ for Jaco Arm
K-NN	12
Threshold C_w	0.02 for Walker and Quadruped
	0.01 for Jaco Arm
Threshold C_k	512

to evaluate the quality of the collected dataset. The detailed implementation and hyperparamter settings can be found in ExORL.

B PROOF OF LEMMA 3.1

Proof. It has been shown in APT Liu & Abbeel (2021b) that the particle-based entropy estimator of the state representation z can be derived as

$$\mathcal{H}(z) = -\frac{1}{n}\sum_{i=1}^{n}\log\frac{K}{nv_i^K} + b(K) \propto \sum_{i=1}^{n}\log v_i^K \tag{5}$$

where $b(K)$ represents a bias correlation and v_i^K indicates the volume of the hypersphere with a radius of $||z_i - z_i^{\text{K-NN}}||$ between the z_i and its K-th nearest neighbor $z_i^{\text{K-NN}}$.

By substituting $v_i^K = \frac{||z_i - z_i^{\text{K-NN}}||\pi^{n_z/2}}{\Gamma(n_z/2+1)}$ where Γ is a gamma function and n_z is the dimension of z, we can obtain

$$\mathcal{H}(z) \propto \sum_{i=1}^{n}\log||z_i - z_i^{\text{K-NN}}||_2. \tag{6}$$

Let $u = (z_s, z_a)$ represent the state-action representation and we can further substitute $z = u$ into Equation (6) to obtain

$$\mathcal{H}(u) \propto \sum_{i=1}^{n}\log||u_i - u_i^{\text{K-NN}}||_2. \tag{7}$$

□

C ADDITIONAL RESULTS AND DISCUSSIONS

We present the performance scores of the four variants of CUDC at 100K and 500K steps in Table 4. Moreover, the detailed learning curves of the offline RL agent on 4 downstream tasks are shown in Figure 7. It can be concluded that adapting the environment step to reach more distant k-step future can substantially improve both sample efficiency and learning capabilities. Moreover, all proposed components facilitated by the proposed reachability module are necessarily important to yield the improvement. As a result, the full CUDC model further addressed the instability issue to obtain the minimum standard deviation among all methods.

Table 4: Performance scores (mean & standard deviation) of four versions of CUDC at 100K and 500K environment steps. The full model outperforms other versions on 3 out of 4 tasks in sample efficiency (100K) and all four tasks in learning performance (500K) regimes, across 5 random seeds.

100K Step Score	ICM	CUDC$_{\text{vary}}^{\text{ICM}}$	APT	CUDC$_{\text{vary}}^{\text{APT}}$	CUDC$_{\text{reward}}$	CUDC$_{\text{reach}}$	CUDC
Walker, Walk	503±258	686±46	548±338	785±56	796±85	811±69	**827±64**
Walker, Flip	530±59	589±82	579±51	542±173	601±156	570±71	**615±66**
Walker, Run	233±111	320±26	372±40	**387±19**	385±69	370±40	381±37
Walker, Stand	797±312	909±88	878±101	936±69	950±40	**983±11**	**984±11**
500K Step Score	ICM	CUDC$_{\text{vary}}^{\text{ICM}}$	APT	CUDC$_{\text{vary}}^{\text{APT}}$	CUDC$_{\text{reward}}$	CUDC$_{\text{reach}}$	CUDC
Walker, Walk	802±67	822±52	799±73	820±71	824±52	849±36	**893±34**
Walker, Flip	534±218	665±32	591±77	674±77	666±53	679±41	**717±41**
Walker, Run	261±142	336±115	384±20	370±38	**394±43**	375±27	393±11
Walker, Stand	868±73	927±74	890±139	916±78	**970±12**	969±11	971±7

Figure 6 and Figure 7 show the full results on the 12 downstream tasks across 3 domains. Figure 8 summarizes the overall performances in 3 domains. They demonstrate that our proposed methods significantly outperform the baseline methods in 3 downstream tasks of Walker and 3 downstream tasks of Quadruped. However, in the hardest domain of Jaco Arm, the learning sample efficiency becomes poor in 3 downstream tasks although its learning performance at 500K step catches up with the best baseline method of ICM. We explain this by the fact that our method can introduce more complexity and challenges for the agent whenever adapting the environment step to learn a better representation. However, as Jaco Arm is indeed the most challenging domain, the introduced

Figure 5: Full results of learning curves on full 12 downstream tasks with the task-agnostic dataset collected by different versions of the proposed CUDC. They are capbable of improving both sample efficiency at 100K step and learning capbilities at 500K steps, compared to the baselines of ICM and APT. All proposed components work inherently to collect the high quality dataset for offline learning.

complexity cannot be fully coped with this environment. Thus, the poor performance in sample efficiency can occur, and it is interesting to further study on how to cope with hard domain environments in the future works.

Figure 6: Full results of the average performance score evaluated at 100K and 500K steps for the offline RL agent on each downstream task. CUDC significantly improves the sample-efficiency in 9 out 12 tasks at 100K step and learning performances in all 12 tasks at 500K step.

Finally, we plot how our proposed method adapts the environment steps during data collection in the Walker domain, as shown in Figure 9. It can be observed that agents take around 450K step to learn and adjust the environment step from $k = 3$ to $k = 4$. Then, it takes around just 200K steps to increase from $k4$ to $k = 5$. Finally, it takes more than 400K steps to reach $k = 6$. This increasing behavior implies that at the early phase of training, we should not inject a too challenging k value. Once the agent has learned enough dynamics information, they are able to learn quickly on more challenging reachability analysis. However, after a certain stage ($)k = 5$ in this domain), the learning becomes too difficult for the agent. Therefore, it is interesting to further adapt this over-difficult knowledge in the future works as well.

Figure 7: Learning curves of the offline RL agent on full 12 downstream tasks with the task-agnostic dataset collected by different methods. The proposed CUDC demonstrates superior capability of improving the sample-efficiency and learning performances of the offline RL agent in the domains of Walker and Quadruped.

Figure 8: The overall offline learning performance across 3 domains. CUDC consistently leads to significant improvement in offline agent's performance at 500K step in all 3 domains on average.

Figure 9: The adaptive increase of the environment step for future state prediction. It is averaged by 5 random runs in the Walker domain, where the k-step is limited to change from 3 to 6.