Beyond Easy Wins: A Text Hardness-Aware Benchmark for LLM-generated Text Detection

Abstract

We present a novel evaluation paradigm for AI text detectors that prioritizes real-world and equitable assessment. Current approaches predominantly report conventional metrics like AUROC, overlooking that even modest false positive rates constitute a critical impediment to practical deployment of detection systems. Furthermore, real-world deployment necessitates predetermined threshold configuration, making detector stability (i.e. the maintenance of consistent performance across diverse domains and adversarial scenarios), a critical factor. These aspects have been largely ignored in previous research and benchmarks. Our benchmark, **SHIELD**, addresses these limitations by integrating both reliability and stability factors into a unified evaluation metric designed for practical assessment. Furthermore, we introduce a lightweight, model-agnostic humanification framework featuring a controllable hardness parameter that systematically steers the AI text distribution toward human authorship to rigorously stress-test AI text detectors. By evaluating these humanified samples through our designed metric paradigm, any critical deficiency in either a detector's localized reliability or cross-scenario stability is immediately exposed. (Data and code will be available upon acceptance).

1 Introduction

Despite large language models' (LLMs) beneficial applications, they expose new potential avenues for malicious exploitation. Such harmful practices include, but are not limited to, automated disinformation dissemination (Vykopal et al., 2024), academic plagiarism and cheating (Cotton et al., 2024; Wahle et al., 2022), and the fabrication of deceptive reviews (Chiang et al., 2023). The subtlety of distinguishing recurring patterns in LLM-generated text renders human classification efforts scarcely better than chance (Uchendu et al., 2021;

Clark et al., 2021; Dou et al., 2022). Consequently, research emphasis has shifted toward the development of automatic detection tools. However, prior research notes several limitations that significantly undermine their robustness and reliability. Most prominently, their inability to generalize to out-of-distribution cases leads to failures when analyzing texts generated by unseen models or characterized by unfamiliar stylistic nuances (Kuznetsov et al., 2024; Lai et al., 2024). Furthermore, detector efficacy is significantly diminished through minimal perturbations, text length modifications, or the application of adversarial techniques (Zhou et al., 2024; Huang et al., 2024) including paraphrasing (Cheng et al., 2025; Fang et al., 2025; Hu et al., 2023; Huang et al., 2025), stylistic transformation, and intentional insertion of errors (Dugan et al., 2024). In efforts to improve detector robustness, most existing studies predominantly report conventional metrics, such as accuracy (Kuznetsov et al., 2024), F1-score (Liu et al., 2025; Wu et al., 2025; Guo et al., 2024a), and AUROC (Wu et al., 2025; Liu et al., 2025; Yu et al., 2024b; Su et al., 2023; Mitchell et al., 2023; Bao et al., 2023) when assessing performance under diverse adversarial attacks. However, this evaluation paradigm manifests several critical limitations in real-world assessment of detectors. Primarily, **even modest false positive rates (FPR) are fundamentally unacceptable in LLM text detection contexts.** For instance, in academic integrity applications, where the objective is to ensure fairness by identifying instances of academic dishonesty, misclassification of legitimately authored student work introduces significant procedural inequity by penalizing students undeservedly. Consequently, some researchers have transitioned toward reporting true positive rates (TPR) at fixed FPR (e.g. 1%) (Hans et al., 2024; Yang et al., 2023). However, despite this shift, additional unresolved issues remain. When deployed in real-world applications, detection systems re-

quire configuration with a predetermined threshold, independent of the generative provenance of examined text. Within this practical framework, **quantifying detector stability** through analysis of **threshold dynamics** across diverse adversarial conditions becomes critically important, a dimension that previous studies have largely overlooked. To get a taste of why traditional metrics are insufficient, we show the performance of several key detectors using traditional metrics. Global aggregators like AUROC and Gini trigger an equivalence illusion, scoring Fast-DetectGPT (Bao et al., 2023) and Binoculars (Hans et al., 2024) identically and completely masking their disparate low-FPR capabilities. While a localized snapshot like TPR@1%FPR (T@1%F) surfaces this specific gap, it deceptively ranks the worst-performing model, Rank (Gehrmann et al., 2019), above Binoculars. F_{β} score generates a highly distorted impression by positioning the Rank detector at near-parity with Fast-DetectGPT due to over-optimization on an unanchored validation point, while Matthews Correlation Coefficient (MCC) remains blind to distribution volatility, ranking Rank higher than Binoculars despite Binoculars possessing superior threshold consistency. Our framework resolves these blind spots by isolating strict, localized low-FPR discrimination and directly quantifying threshold shifting under cross-domain variance. By integrating these dimensions into a unified metric, our proposed metric heavily penalizes models with critical single-dimension vulnerabilities to deliver an operationally robust deployment ranking.

In addition, we present a model-agnostic and lightweight framework designed to steer LLM-generated texts toward more human-like word distributions across calibrated difficulty gradients. This humanification process spans multiple hardness levels, and specifically target vulnerabilities in zero-shot detection approaches (Mitchell et al., 2023; Bao et al., 2023). Rather than being limited to evaluating performance across shifting macro conditions such as varying generative models or writing styles, our framework introduces structured, fine-grained difficulty gradients to systematically stress-test systems. By progressively diminishing detection signals while maintaining semantic coherence, it provides increasingly sophisticated evaluation scenarios that advance detector robustness assessment and illuminate the fundamental limitations of detection approaches through our newly designed metrics. In essence, this paper offers a broader and more real-world evaluation framework that pushes detection efforts "**beyond easy wins**"!

The core contributions of this paper are the following:

- We formulate a novel evaluation paradigm that integrates both detector performance and stability while specifically penalizing elevated FPRs, thus ensuring fair and rigorous comparative assessments.

- We develop an effective lightweight generation framework that produces LLM-generated texts with controlled difficulty gradients to systematically evaluate detectors' performance.

2 Related work

2.1 LLM-generated text detection

Detection of LLM-generated text falls into three principal categories: **watermarking** (Kirchenbauer et al., 2023; Liu and Bu, 2024; Panaitescu-Liess et al., 2025), **supervised techniques** (Guo et al., 2024a,b; Abassy et al., 2024; Yu et al., 2024a), and **zero-shot approaches** (Hans et al., 2024; Ma and Wang, 2024; Yang et al., 2023; Bao et al., 2023). **Watermarking** embeds imperceptible signals during text generation. These approaches fail to protect unknowing third-party users and are susceptible to paraphrasing attacks (Fernandez et al., 2026; Pang et al., 2024). **Supervised techniques** train classifiers atop encoder-based backbones like RoBERTa (Liu et al., 2021) using annotated corpora. These approaches manifest considerable performance deterioration when applied to out-of-distribution contexts. **Zero-shot methods** operate without training requirements, exploiting LM generative mechanisms through statistical indicators including log-likelihood (Gehrmann et al., 2019), perplexity (Hans et al., 2024), token rank (Gehrmann et al., 2019; Su et al., 2023), and entropy (Lavergne et al., 2008). Many approaches require generating alternative text versions to detect statistical deviations (Mitchell et al., 2023; Yang et al., 2023), a computationally intensive process. This issue is

Table 1: The real-world deployment paradox.

Detector	Traditional metrics					Ours		
	AUROC	Gini	MCC	T@1%F	F_{β}	W-A	SFD	URSS
Fast-DetectGPT	0.92	0.84	0.66	0.63	0.97	0.74	0.61	0.45
Binoculars	0.92	0.84	0.22	0.12	0.24	0.60	0.43	0.26
LRR	0.74	0.47	0.32	0.21	0.32	0.37	0.27	0.10
Rank	0.70	0.40	0.24	0.14	0.92	0.30	0.31	0.09

Table 2: Comparative analysis of LLM-generated text detection benchmarks.

Benchmark name	Human samples	LLM samples	Num of Styles	Multiple LLMs	Hardness Levels?	Fair Metric?
BUST(Cornelius et al., 2024)	3.2k	22k	3	✓	✗	✗
DetectRL(Wu et al., 2024)	11.2k	11.2k	4	✓	✗	✗
ESPERANTO(Ayoobi et al., 2025)	36k	36k	4	✓	✗	✗
HC3(Guo et al., 2023)	59k	27k	1	✗	✗	✗
MAGE(Li et al., 2024)	154k	295k	7	✓	✗	✗
M4GT-Bench(Wang et al., 2024)	65k	88k	6	✓	✗	✗
MGTBench(He et al., 2024)	3k	18k	3	✓	✗	✗
RAID(Dugan et al., 2024)	15k	509k	8	✓	✗	✗
SHIELD (Ours)	87.5k	612.5k	7	✓	✓	✓

mitigated through reducing required revisions, and efficient sampling methods (Bao et al., 2023; Su et al., 2023).

2.2 Benchmarks for LLM text detection

The literature presents multiple benchmarks for evaluating LLM-generated text detection, each with varying characteristics in scale, diversity, and evaluation methodology (Uchendu et al., 2021; Yu et al., 2025; Pudasaini et al., 2025). RAID (Dugan et al., 2024) systematically examines robustness across multiple decoding strategies. MAGE (Li et al., 2024) extends evaluation capabilities across a broader spectrum of LLMs. DetectRL (Wu et al., 2024) focuses on vulnerability assessment through implementation of adversarial attacks and perturbations. M4GT-Bench (Wang et al., 2024) contributes a multilingual evaluation framework, and HC3 (Guo et al., 2023) compiles one of the largest ChatGPT-centric datasets available. Despite these significant contributions, current benchmarks commonly lack samples with structured difficulty gradients and principled metrics that ensure fairness in practical comparisons. Our benchmark, **SHIELD**, represents the first benchmark to incorporate humanified samples with graduated hardness levels. Furthermore, SHIELD pioneers a fairness-aware evaluation methodology, thus filling critical gaps in the current evaluation paradigm. Table 2 provides a comparative analysis of our proposed benchmark against existing benchmarks in English. The comparison covers critical aspects including pre-attack dataset size, diversity of writing styles, utilization of multiple LLMs, structured hardness levels, and the presence of fairness-oriented evaluation metrics.

3 SHIELD benchmark: data creation, humanification process, and metric design

This section introduces the methodology underlying our benchmark **SHIELD** (**S**calable **H**ardness-**I**nformed **E**valuation of **LL**M **D**etectors).

3.1 Data creation

To compile a comprehensive dataset capable of unmasking cross-field threshold volatility, a critical operational vulnerability hidden by traditional metrics, SHIELD incorporates seven diverse writing styles: **semi-formal** discourse from Medium posts, **journalistic** reporting from news sources, **evaluative** content from Amazon reviews, **question-answering** text from Reddit's ELI5, **scientific** writing from arXiv abstracts, **partisan-persuasion** reporting from pink slime, and **expository** documentation from Wikipedia. Please refer to Appendix A.1 for additional data characteristics. To obtain the LLM-generated counterparts, we deployed seven models: Llama3.2-1b, Llama3.2-3b, Llama3.1-8b (Grattafiori et al., 2024), Mistral-7b (Jiang et al., 2023), Qwen-7b (Bai et al., 2023), Gemma2-2b, and Gemma2-9b (Mesnard et al., 2024) for rephrasing of human-written texts. Additional specifications regarding models and prompting are detailed in Appendix A.2. To guarantee human authorship, the dataset comprises exclusively pre-2021 data, predating the emergence of LLMs. The SHIELD dataset contains 87.5k human-written documents and 612.5k LLM-generated samples before the application of adversarial techniques or humanization processes. Complete statistical details are presented in Appendix A.3.

3.2 Fairness-oriented evaluation metric

To expose the cross-field threshold volatility hidden by traditional global metrics, we partition our evaluation framework into two operational dimensions: localized reliability (performance) and cross-scenario threshold stability.

3.2.1 Reliability and performance metric

AUROC neglects consideration of practical operational threshold regions. It uniformly weights the entire ROC curve, including high-FPR regions that are impractical for real-world deployment of AI-text detection systems. It also fails to capture performance instability, that is, significant changes in TPR or FPR due to small threshold adjustments. To more precisely evaluate the reliability of AI-text detection systems, we introduce weighted-AUROC (W-AUROC), defined as the expectation of TPR over a non-uniform probability distribution $p(t)$ across FPR,

$$\text{W-AUROC} = \mathbb{E}_{t \sim p(t)}[\text{TPR}(t)] \quad (1)$$

where the weighting function is given by, $p(t) = \frac{1}{\mathcal{Z}} exp(-kt)$, with decay parameter $k > 0$ and normalization constant $\mathcal{Z} = \frac{1 - exp(-k)}{k}$. To determine the decay parameter k, we set the exponential weighting function $exp(-k.\text{FPR})$ to decay to 50% of its initial value at FPR$=0.05$. This decision is inspired by prior works in AI-text detection that routinely report TPR at a fixed FPR of less than 5% as a key performance indicator, reflecting its status as a standard deployment-level operating point. This constraint yields $k = 20 \, ln2$.

3.2.2 Stability under FPR deviation (SFD)

To assess stability across different scenarios, we compute the standard deviation of FPR at decision thresholds determined by Youden's J statistic (Youden, 1950) on ROC curve. Our selection of FPR as the target variable stems from two considerations: 1) the threshold determination in each detection system is intrinsically dependent on scoring function values with ranges varying between methods, 2) this approach enables direct penalization of significant FPR fluctuations for stability assessment, as substantial FPR variability constitutes unacceptable performance in AI-text detection frameworks. For each detection system and across M evaluation scenarios (e.g., generative models, attack types, or writing styles), we extract the threshold t_i^* that maximizes $J(t) = \text{TPR}(t) - \text{FPR}(t)$ for each scenario i, and record the corresponding $\text{FPR}_i^* = \text{FPR}_i(t_i^*)$,

$$t_i^* = \arg \max_t \left[\text{TPR}_i(t) - \text{FPR}_i(t) \right] \quad (2)$$

The standard deviation of these optimal FPRs across all M scenarios is calculated and denoted as σ_{FPR}. Finally, we define the stability metric as,

$$\text{SFD} = exp(-\lambda.\sigma_{\text{FPR}}) \quad (3)$$

where $\lambda > 0$ is a tunable hyperparameter controlling the sensitivity to instability. Lower standard deviation in FPR results in higher stability scores, with perfect stability ($\sigma_{\text{FPR}} = 0$) yielding a maximum value of 1. To determine a principled value for the decay parameter λ, we calibrate it so that a moderate but practically noticeable instability in FPRs corresponds to a mid-range stability score. Therefore, we set it such that the stability score reduces to 0.5 when the standard deviation σ_{FPR} reaches 0.1. This yields $\lambda = 10 \, ln2$.

We adopt a multiplicative formulation to combine W-AUROC (performance) and SFD (stability) into a single unified reliability-stability score (URSS),

$$\text{URSS} = \left(\frac{1}{M} \sum_{i=1}^{M} \text{W-AUROC}_i \right).\text{SFD} \quad (4)$$

Multiplication enforces a **non-compensatory relationship**: a high W-AUROC cannot mask poor stability, and conversely, robust stability does not necessarily indicate high discrimination capability. This reflects real-world deployment requirements, where even a highly accurate detector is unusable if unstable, and vice versa.

3.3 Hardness-aware humanification process

The core hypothesis of our approach is to replace words that strongly indicate LLM authorship with words indicative of human authorship. Initially, we quantify each word's impact on authorship inference by the following scoring function:

$$MI_i = \sum_x P(x, w_i) log(\frac{P(x|w_i)}{P(x)}) \quad (5)$$

where x represents authorship, and the mutual information (MI) quantifies the extent to which observing the word w_i shifts our probabilistic belief regarding the text's authorship. This scoring is performed by the ranker module illustrated in Figure 1(a). Subsequently, we partition the vocabulary into two subsets: AI-associated $\mathbb{A}$, and human-associated $\mathbb{H}$ vocabularies based on their usage frequencies f_i. This separation reflects whether a word predominantly contributes to the distribution of AI- or human-written texts. For humanification of text, we implement three strategies: **a) Random meaning-preserving mutation (RMM)**, **b) AI-flagged word swap (AWS)**, and **c) Recursive humanification loop (RHL)**. Please see Appendix B for a sample of humanified text.

3.3.1 Random meaning-preserving mutation

This approach simulates scenarios wherein malicious users substitute random words to circumvent detection or when $\mathbb{A}$ and $\mathbb{H}$ are inaccessible. Figure 1.b illustrates this process. Let $\mathcal{D} = [w_1, ..., w_n]$ be an AI-generated text consisting of a sequence of words. We define $\mathcal{S} \subset \mathcal{D}$ as the set of non-stop words, $\mathcal{S} = \{w_i \in \mathcal{D} | w_i \notin \text{StopWords}\}$. Next, we randomly sample a subset $\mathcal{M} \subset \mathcal{S}$ such that $|\mathcal{M}| = \lfloor p.|S| \rfloor$, with p representing the sampling ratio. Then, we construct a masked version $\mathcal{D}^{mask} = \text{Mask}(\mathcal{D}, \mathcal{M})$ by replacing each word

$w_i \in \mathcal{M}$ in $\mathcal{D}$ with the special token <mask>. $\mathcal{D}^{mask}$ is fed into a masking language model $\mathbf{f_{MLM}}$ which outputs a ranked list of predictions $\mathbf{f_{MLM}^{(i)}}(\mathcal{D}^{mask})$ at each masked position i. For each i, the first candidate $\hat{w}_i$ with highest rank is selected such that it differs from original word in $\mathcal{D}$, $\hat{w}_i \neq w_i$. Finally, the edited text $\mathcal{D}^{edit}$ is produced by replacing each $w_i \in \mathcal{M}$ with the corresponding $\hat{w}_i$:

$$\mathcal{D}^{edit} = \mathbf{Replace}(\mathcal{D}, \{(w_i, \hat{w}_i)\}_{w_i \in \mathcal{M}}) \quad (6)$$

3.3.2 AI-flagged word swap

The second strategy, depicted in Figure 1(c), leverages $\mathbb{A}$ and $\mathbb{H}$ to substitute AI-indicative words with human-characteristic alternatives. Without loss of generality, let $\mathcal{S}' = \mathbf{Sort}(\mathcal{S}, \mathrm{MI}_{\mathbb{A}}) = [w_{(1)}, w_{(2)}, ..., w_{(|\mathcal{S}|)}]$ such that $\mathrm{MI}_{\mathbb{A}}(w_{(1)}) \geq \mathrm{MI}_{\mathbb{A}}(w_{(2)}) \geq ... \geq \mathrm{MI}_{\mathbb{A}}(w_{(|\mathcal{S}|)})$. Here, $\mathcal{S}'$ is the set $\mathcal{S}$ reordered in descending order based on MI scores with respect to the $\mathbb{A}$. To construct set $\mathcal{M}$, we extract the top $p\%$ of words from $\mathcal{S}'$,

$$\mathcal{M} = \{w_{(i)} \in \mathcal{S}' | 1 \leq i \leq \lfloor p.|\mathcal{S}| \rfloor\} \quad (7)$$

The parameter p acts as a tunable knob that controls the hardness level of the humanified text. The words in $\mathcal{M}$ undergo masking in the initial text. $\mathbf{f_{MLM}}$ then predicts candidate replacements for each masked position. For each masked position i, we select the word with the highest score in $\mathbb{H}$,

$$\hat{w}_i = \underset{w \in \mathbf{f_{MLM}^{(i)}}(\mathcal{D}^{\mathbf{mask}})}{\arg\max} \mathrm{MI}_{\mathbb{H}}(w) \quad (8)$$

The edited text $\mathcal{D}^{edit}$ is derived similarly as Equation 6.

3.3.3 Recursive humanification loop

Figure 1(d) shows the third strategy which extends second strategy (AWS) through implementation of a recursive refinement. Let $\mathcal{D}^{(0)}$ be the original AI text. We define the recursive editing process for R rounds. At each round $r \in \{1, 2, ..., R\}$, the set of non-stop words are formed,

$$\mathcal{S}^{(r-1)} = \{w_i \in \mathcal{D}^{(r-1)} | w_i \notin \mathrm{StopWords}\} \quad (9)$$

Subsequently, words are ordered according to $\mathrm{MI}_{\mathbb{A}}$ scores,

$$\mathcal{S}'^{(r-1)} = \mathbf{Sort}(\mathcal{S}^{(r-1)}, \mathrm{MI}_{\mathbb{A}})$$
$$= [w_{(1)}^{(r-1)}, w_{(2)}^{(r-1)}, ..., w_{(|\mathcal{S}|)}^{(r-1)}] \quad (10)$$

(a)

(b)

(c)

(d)

Figure 1: Humanification strategies based on the ranked vocabularies $\mathbb{A}$ and $\mathbb{H}$ produced by the Ranker in (a). (b) Random meaning-preserving mutation (RMM), (c) AI-flagged word swap (AWS), (d) Recursive humanification loop (RHL).

A fixed proportion $p = p_o$ (set at 10%) of words with maximal scores are selected for masking,

$$\mathcal{M}^{(r)} = \{w_{(i)}^{(r-1)} \in \mathcal{S}'^{(r-1)} | 1 \leq i \leq \lfloor p_o.|\mathcal{S}| \rfloor\} \quad (11)$$

$\mathbf{f_{MLM}}$ predicts the masked words in $D^{mask\,(r)}$, which is obtained by $\mathbf{Mask}(D^{(r-1)}, \mathcal{M}^{(r)})$. For each masked position i, we choose the word with the highest score in $\mathbb{H}$,

$$\hat{w}_i^{(r)} = \underset{w \in \mathbf{f_{MLM}^{(i)}}(\mathcal{D}^{\mathbf{mask},\,(\mathbf{r})})}{\arg\max} \mathrm{MI}_{\mathbb{H}}(w) \quad (12)$$

Then the edited document for round r is:

$$\mathcal{D}^{(r)} = \mathbf{Replace}(\mathcal{D}^{(r-1)}, \{(w_i, \hat{w}_i^{(r)})\}_{w_i \in \mathcal{M}^{(r)}}) \quad (13)$$

The final humanified text is $\mathcal{D}^{edit} = \mathcal{D}^{(R)}$. The parameter R acts as a controllable knob to adjust the hardness level of the resulting text, with larger values yielding increasingly human-like phrasing.

Figure 2: Radar charts of comparing detectors in different writing styles across all generative models.

4 Experiments and discussion

In this section, we organize our experiments and discussion around four core questions: 1) **Why are traditional metrics insufficient** for evaluating detectors in real-world settings? 2) **How effectively does our proposed humanification process stress-test zero-shot detectors** to highlight their vulnerabilities? 3) **How does humanification process affect text quality**? and 4) **Why zero-shot detectors fail?** We evaluate six zero-shot detectors, Binoculars (Hans et al., 2024), Fast-DetectGPT (Bao et al., 2023), LRR (Su et al., 2023), Log-Likelihood, Log-Rank, and Rank (Gehrmann et al., 2019), along with a supervised model, Radar (Hu et al., 2023), to examine the comparative **vulnerability of zero-shot methods**. Further information on the detectors used can be found in Appendix C.

4.1 Why are traditional metrics NOT enough?

As demonstrated by the empirical contradictions outlined in Table 1, traditional metrics, ranging from global curve aggregators like the Gini coefficient to localized or single-threshold snapshots like MCC, F_{β}, and T@1%F fail to precisely rank text detectors for real-world deployment due to their systemic inability to balance localized reliability with domain threshold stability. Nevertheless, for the remainder of the empirical evaluation in this paper, we select AUROC to serve as the primary baseline representative for conventional metrics. This choice is motivated by its near-universal ubiquity in prior text detection literature. For each writing style, we compare detectors across all generative models using the original LLM-generated texts (without humanification). The resulting radar charts are presented in Figure 2 (Please refer to Appendix D for radar charts of different LLMs across all writing styles). While traditional AUROC can exaggerate the superiority of a detector, our proposed framework reveals an illuminating truth. AUROC may obscure cases where detectors perform equivalently in practice. In contrast, URSS effectively exposes equivalences by

examining performance parity within operationally low FPR regions and assessing stability. For instance, in the Reddit chart, although Radar exhibits a substantially higher AUROC than Rank, both achieve identical URSS, highlighting their practical equivalence. Conversely, there are cases where detectors achieve similar AUROC scores, yet one outperforms the other in low-FPR operational regions while also exhibiting greater threshold stability. **Such multidimensional superiority is entirely masked when relying solely on the conventional AUROC metric**. Representative cases include Rank vs. Log-Rank and Log-Rank vs. Log-Likelihood in the Medium chart, and Binoculars vs. Fast-DetectGPT across News, Wikipedia, Medium, and Review charts. Despite significant disparities in either W-AUROC or SFD, identical AUROC across detectors can cause a misleading impression of equivalence. This potentially results in **suboptimal choices for real-world deployment**. Such patterns are seen in Fast-DetectGPT vs. Rank and Log-Likelihood vs. Log-Rank on arXiv, Log-Rank vs. Log-Likelihood in Reddit, and Rank vs. Log-Likelihood in Wikipedia. URSS suggests that **meaningful performance equivalency** between detectors can only be established through comprehensive evaluation that simultaneously considers both operational region sensitivity and cross-scenario stability. For example, in the Wikipedia chart, URSS observes that Log-Likelihood has slightly lower W-AUROC but higher SFD than Log-Rank, and assigns them equal scores, reflecting fairness when each method excels in one dimension and the trade-off is not substantial.

A significant observation from our experiments is that methods exhibiting severe deficiencies in any critical performance dimension are heavily penalized, acknowledging that such limitations undermine real-world deployment potential. This evaluation principle is exemplified by Binoculars which, while achieving the highest AUROC and second-highest W-AUROC scores, was ultimately positioned last in the Reddit writing style analysis

Table 3: Performance of detectors under paraphrasing (baseline), RMM, AWS, and RHL strategies.

LLM → Detector ↓ Metric (%) →	Gemma2 9b				Llama3.1 8b				Mistral 7b				Qwen 7b			
	AUC	W-A	SFD	URSS	AUC	W-A	SFD	URSS	AUC	W-A	SFD	URSS	AUC	W-A	SFD	URSS
Paraphrase (baseline)																
Binoculars	93.8	69.9	47.0	32.9	95.4	74.0	55.2	40.9	90.6	59.4	46.2	27.4	85.5	35.2	42.5	14.9
Fast-DetectGPT	93.1	74.7	60.7	45.3	94.6	80.3	60.5	48.6	89.2	62.1	62.1	38.6	91.7	76.2	81.2	61.8
Log-Likelihood	77.6	28.7	41.2	11.8	82.2	36.1	41.8	15.1	64.8	16.6	22.8	3.8	66.0	18.0	42.6	7.7
Log-Rank	77.6	30.1	47.3	14.3	82.5	38.6	44.5	17.2	63.3	15.7	20.8	3.3	65.6	18.1	37.6	6.8
LRR	76.2	34.0	58.4	19.9	81.5	45.1	55.5	25.0	58.5	13.5	16.9	2.3	62.5	17.8	27.2	4.8
Radar	76.7	34.2	17.6	6.0	79.8	42.3	14.8	6.3	71.0	25.5	15.9	4.0	83.7	50.7	21.1	10.7
Rank	75.9	35.6	49.3	17.5	76.3	36.8	57.1	21.0	62.0	16.9	16.3	2.8	59.3	18.1	16.0	2.9
Random meaning-preserving mutation (RMM)																
Binoculars	77.9	35.4	35.1	12.4	83.6	44.7	43.8	19.6	73.9	28.9	53.0	15.3	77.7	30.4	46.2	14.1
Fast-DetectGPT	77.0	37.8	35.8	13.5	82.2	47.8	46.3	22.1	71.7	27.2	45.8	12.5	83.5	50.4	52.8	26.6
Log-Likelihood	34.4	4.7	5.9	0.3	41.2	8.4	6.2	0.5	26.1	2.2	4.0	0.1	31.3	4.8	8.1	0.4
Log-Rank	36.9	5.4	7.3	0.4	44.2	9.6	6.9	0.7	27.6	2.2	4.5	0.1	32.9	4.8	7.6	0.4
LRR	50.4	9.6	11.8	1.1	58.5	16.4	10.3	1.7	39.4	3.4	8.9	0.3	43.1	5.4	5.7	0.3
Radar	89.0	52.4	34.0	17.8	88.1	52.3	27.8	14.5	83.7	41.9	24.8	10.4	89.4	60.7	29.9	18.2
Rank	48.4	7.0	9.5	0.7	50.1	8.4	9.2	0.8	39.7	2.8	6.7	0.2	38.8	3.3	6.0	0.2
AI-flagged word swap (AWS)																
Binoculars	81.6	45.4	54.4	24.7	81.9	46.1	37.2	17.2	78.6	41.2	57.4	23.6	73.2	31.3	42.6	13.3
Fast-DetectGPT	83.1	45.9	31.0	14.2	83.3	49.6	36.3	18.0	79.5	37.7	37.8	14.3	78.5	42.5	43.1	18.3
Log-Likelihood	21.5	2.5	4.3	0.1	25.0	4.7	5.3	0.3	16.1	1.3	3.7	0.0	18.8	2.7	18.4	0.5
Log-Rank	22.7	2.7	4.3	0.1	26.4	5.1	5.3	0.3	16.7	1.2	4.0	0.0	18.8	2.4	13.6	0.3
LRR	32.6	4.0	7.8	0.3	36.1	6.8	4.9	0.3	24.7	1.4	4.3	0.1	22.3	1.7	3.7	0.1
Radar	85.9	47.6	30.0	14.3	82.3	40.3	26.1	10.5	80.4	39.0	19.0	7.4	86.0	52.3	26.5	13.9
Rank	46.1	4.9	10.3	0.5	46.5	5.5	10.5	0.6	39.5	2.4	11.9	0.3	31.3	2.0	5.7	0.1
Recursive humanization loop (RHL)																
Binoculars	75.8	32.2	59.3	19.1	78.0	36.2	40.0	14.5	75.0	32.3	63.4	20.5	72.6	26.6	44.9	11.9
Fast-DetectGPT	76.5	30.9	50.2	15.5	78.2	37.3	42.4	15.8	74.8	27.1	50.2	13.6	77.4	36.7	61.0	22.4
Log-Likelihood	17.5	0.6	3.5	0.0	21.6	1.8	3.8	0.1	12.4	0.5	3.3	0.0	17.2	1.9	8.3	0.2
Log-Rank	20.2	0.8	3.7	0.0	24.5	2.4	4.2	0.1	14.4	0.5	3.2	0.0	18.3	1.8	6.7	0.1
LRR	36.4	3.3	11.6	0.4	40.6	6.4	5.8	0.4	29.4	1.1	10.9	0.1	27.6	1.7	3.6	0.1
Radar	85.4	43.9	34.5	15.1	81.8	37.9	27.0	10.2	79.9	33.9	27.1	9.2	86.6	51.2	30.9	15.8
Rank	45.1	4.4	8.8	0.4	45.1	4.5	9.0	0.4	39.0	1.7	7.2	0.1	32.6	1.9	4.5	0.1

based on URSS metric due to its exceptionally poor stability.

4.2 Effectiveness of humanification strategies

Table 3 shows the impact of different strategies on detector performance across all writing styles, using the largest LLM model from each family evaluated in this study. Corresponding results for smaller models are available in Appendix D. To enhance readability, all metrics are reported as percentages. The baseline consists of original LLM-generated texts (specifically paraphrased texts without humanification). Zero-shot detectors suffer marked average URSS degradation of 41%, 62%, 97%, 96%, 92%, and 95% in **RMM**; 27%, 66%, 98%, 98%, 98%, and 95% in **AWS**; and 38%, 65%, 99%, 99%, 97%, and 97% in **RHL**, corresponding to Binoculars, Fast-DetectGPT, Log-Likelihood, Log-Rank, LRR, and Rank, respectively. This demonstrates that without devising robustness enhancements, **zero-shot detectors fail to withstand word-level humanification**, resulting in severe performance loss. Interestingly, even though AWS and RHL introduce more complex humanification than RMM, our experiments reveal that multiple detectors demonstrate similarly compromised URSS performance under the simpler RMM. For instance, Log-Likelihood's URSS drops to 0.1 under RMM for Mistral 7b, nearly equivalent to its 0.0 under AWS and RHL. This observation indicates that

zero-shot detectors depend on fragile token-level statistical signatures that collapse under even modest perturbations. This vulnerability becomes particularly concerning considering that RMM more closely approximates natural user editing behaviors, rendering these detection systems unreliable in practical deployment scenarios. This limitation exacerbates the previously documented challenge of generative model dependency (Wu et al., 2024), as further evidenced in Table 3, which demonstrates significant variation in URSS metrics across different LLMs when subjected to identical strategies.

4.3 Text quality and strategy knob calibration

To verify that our humanification strategies systematically alter token distributions rather than merely injecting destructive linguistic noise, we evaluate text quality after edits by measuring fluency and contextual meaning preservation. Fluency is quantified by perplexity (PPL) using "Llama-3.1-8b-Instruct" model, while contextual meaning preservation is captured by cosine similarity mapping over an embedding space ("all-MiniLM-L6-v2" model), see Figure 3 and Figure 4. **RMM** preserves text quality up to $p = 40\%$. At this limit, semantic similarity remains high (≥ 0.86) and perplexity inflation is strictly controlled ($PPL \leq 15.5$). Exceeding $p = 40\%$ triggers rapid linguistic degradation, bounding the valid operational window to $p \in [10\%, 40\%]$. **AWS** drives a steeper perplexity

acceleration than RMM ($PPL = 22$ at $p = 40\%$). However, it maintains strong contextual meaning (similarity ≥ 0.89) before suffering a severe semantic collapse at higher intervals. This limits the valid operational range for high-fidelity targeted token erasure to $p \in [10\%, 40\%]$. **RHL** demonstrates distribution convergence, shifting initially at $R = 5$ (similarity $= 0.9$, $PPL = 17$) before plateauing. Between $R = 20$ and $R = 40$, perplexity (≈ 25) and similarity (≈ 0.74) lock asymptotically as token mutations cease. This establishes $R \in [5, 20]$ as the optimal operational window for stress-testing detectors before distribution stabilization.

4.4 Why zero-shot detectors fail

To uncover why zero-shot detectors fail, we compare the top two detectors (Fast-DetectGPT and Binoculars) under RMM and AWS strategies. Cross-referencing URSS with semantic similarity uncovers an operational paradox: **targeted statistical erasure degrades detector efficacy far more aggressively than random perturbations, despite preserving higher semantic similarity**. As illustrated in Figure 5, Fast-DetectGPT experiences a severe overall performance collapse under AWS, with its URSS plunging from 31.3% at $p = 10\%$ down to 12.8% at $p = 40\%$. In contrast, under RMM, its URSS drops more gradually from 36.2% to 20.5%. We observe an identical vulnerability pattern in Binoculars, where AWS forces a steep URSS reduction from 20.4% down to a critical failure point of 8.4%, outstripping the degradation caused by RMM (23.0% to 11.5%). According to Figure 4, we discover that AWS consistently maintains superior semantic fidelity to the baseline text than RMM. This unmasks the root cause of zero-shot detector vulnerability: these systems are fundamentally blind to semantic coherence or textual meaning. Instead, their mathematical foundations rely entirely on highly fragile, localized statistical signature, such as the conditional probability curvature leveraged by Fast-DetectGPT or the autoregressive proxy model perplexity ratios computed by Binoculars. By selectively swapping out the high-leverage, low-entropy tokens that language models preferentially over-generate, AWS successfully erases these mathematical artifacts and flattens the probability space. Because zero-shot models cannot evaluate text through a holistic semantic lens, this targeted token erasure breaks their underlying distributional assumptions, triggering catastrophic performance and threshold failures.

Figure 3: perplexity score after edits.

Figure 4: semantic similarity score after edits.

Figure 5: Comparison of URSS degradation under RMM and AWS.

5 Conclusion

In this work, we presented SHIELD, a comprehensive benchmark advancing the fair evaluation of AI text detectors under realistic deployment scenarios. We demonstrated that traditional metrics, ranging from AUROC and Gini to MCC, TPR at fixed FPR, and F_β, trigger an "equivalence illusion" by masking cross-domain threshold volatility and localized low-FPR constraints. SHIELD addresses these blind spots via the Unified reliability-stability Score (URSS), combining localized reliability with cross-scenario threshold stability. Rather than being limited to evaluating performance across shifting macro conditions such as varying generative models or writing styles, our framework introduces structured, fine-grained difficulty gradients to systematically stress-test AI test detectors. Our experiments expose a vital operational paradox: targeted token erasure degrades zero-shot detectors far more aggressively than random mutations, despite maintaining superior semantic fidelity. This unmasks the root failure of zero-shot methodologies, their fundamental blindness to holistic text meaning and total dependence on fragile, localized statistical signatures. By breaking these underlying distributional assumptions, our benchmark triggers catastrophic performance and threshold failures. Ultimately, SHIELD provides a rigorous adversarial environment to stress-test text forensic systems, pushing detection capabilities "beyond easy wins".

Limitations

Several constraints merit acknowledgment within our experimental framework. Primarily, our investigation was confined to monolingual English text analysis, precluding examination of multilingual detection scenarios that represent increasingly important deployment contexts given the global nature of AI text generation. This linguistic limitation potentially restricts the generalizability of our findings to diverse language environments. Additionally, the inherently dynamic nature of LLM development presents a significant temporal constraint; as generative architectures evolve through version updates and architectural innovations, their statistical signatures undergo corresponding transformations, necessitating periodic collection of representative text samples to maintain benchmark currency and relevance. Furthermore, budgetary constraints confined our experimental protocol to open-source models, resulting in the exclusion of closed-source systems including ChatGPT and Claude. The inclusion of these commercial platforms would enhance the comprehensiveness of our evaluation framework, particularly considering their extensive deployment and potentially distinctive generative characteristics that may present unique challenges to detection methodologies.

Ethical considerations

This investigation aims to evaluate the robustness of contemporary AI-text detection methods against adversarial manipulations. The proliferation of LLM-generated content and its potential for malicious applications necessitates robust detection mechanisms to serve as effective countermeasures against synthetic text deception. Vulnerabilities in these detection frameworks could precipitate significant complications in computational forensics and information verification processes. Consequently, this research endeavors to provide detection system engineers with rigorous adversarial testing frameworks for comprehensive validation of their algorithmic approaches against sophisticated evasion techniques. We explicitly stipulate that the methodologies and results documented in this study are intended exclusively for detection system improvement and validation, and not for circumvention of existing detection systems.

Acknowledgments

We utilized AI strictly for grammar correction, proofreading, and improving phrasing. All underlying ideas, experimental methodologies, and empirical findings presented in this paper are exclusively the work of the authors.

References

Mervat Abassy, Kareem Elozeiri, Alexander Aziz, Minh Ngoc Ta, Raj Vardhan Tomar, Bimarsha Adhikari, Saad El Dine Ahmed, Yuxia Wang, Osama Mohammed Afzal, Zhuohan Xie, Jonibek Mansurov, Ekaterina Artemova, Vladislav Mikhailov, Rui Xing, Jiahui Geng, Hasan Iqbal, Zain Muhammad Mujahid, Tarek Mahmoud, Akim Tsvigun, and 5 others. 2024. LLM-DetectAIve: a tool for fine-grained machine-generated text detection. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 336–343, Miami, Florida, USA. Association for Computational Linguistics.

Navid Ayoobi, Lily Knab, Wen Cheng, David Pantoja, Hamidreza Alikhani, Sylvain Flamant, Jin Kim, and Arjun Mukherjee. 2025. Esperanto: Evaluating synthesized phrases to enhance robustness in ai detection for text origination. In *Proceedings of the 36th ACM Conference on Hypertext and Social Media*, HT '25, page 1–10, New York, NY, USA. Association for Computing Machinery.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, and 1 others. 2023. Qwen technical report. *arXiv preprint arXiv:2309.16609*.

Guangsheng Bao, Yanbin Zhao, Zhiyang Teng, Linyi Yang, and Yue Zhang. 2023. Fast-detectgpt: Efficient zero-shot detection of machine-generated text via conditional probability curvature. *arXiv preprint arXiv:2310.05130*.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. 2020. Longformer: The long-document transformer. *arXiv:2004.05150*.

Yize Cheng, Vinu Sankar Sadasivan, Mehrdad Saberi, Shoumik Saha, and Soheil Feizi. 2025. Adversarial paraphrasing: A universal attack for humanizing ai-generated text. In *Advances in Neural Information Processing Systems*, volume 38, pages 47591–47622. Curran Associates, Inc.

Hung-Yun Chiang, Yi-Syuan Chen, Yun-Zhu Song, Hong-Han Shuai, and Jason S. Chang. 2023. Shilling black-box review-based recommender systems through fake review generation. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '23, page 286–297, New York, NY, USA. Association for Computing Machinery.

Elizabeth Clark, Tal August, Sofia Serrano, Nikita Haduong, Suchin Gururangan, and Noah A. Smith. 2021. All that's 'human' is not gold: Evaluating human evaluation of generated text. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 7282–7296, Online. Association for Computational Linguistics.

Colin B Clement, Matthew Bierbaum, Kevin P O'Keeffe, and Alexander A Alemi. 2019. On the use of arxiv as a dataset. *arXiv preprint arXiv:1905.00075*.

Joseph Cornelius, Oscar Lithgow-Serrano, Sandra Mitrovic, Ljiljana Dolamic, and Fabio Rinaldi. 2024. BUST: Benchmark for the evaluation of detectors of LLM-generated text. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8029–8057, Mexico City, Mexico. Association for Computational Linguistics.

Debby R. E. Cotton, Peter A. Cotton, and J. Reuben Shipway. 2024. Chatting and cheating: Ensuring academic integrity in the era of chatgpt. *Innovations in Education and Teaching International*, 61(2):228–239.

Yao Dou, Maxwell Forbes, Rik Koncel-Kedziorski, Noah A. Smith, and Yejin Choi. 2022. Is GPT-3 text indistinguishable from human text? scarecrow: A framework for scrutinizing machine text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7250–7274, Dublin, Ireland. Association for Computational Linguistics.

Liam Dugan, Alyssa Hwang, Filip Trhlík, Andrew Zhu, Josh Magnus Ludan, Hainiu Xu, Daphne Ippolito, and Chris Callison-Burch. 2024. RAID: A shared benchmark for robust evaluation of machine-generated text detectors. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12463–12492, Bangkok, Thailand. Association for Computational Linguistics.

Angela Fan, Yacine Jernite, Ethan Perez, David Grangier, Jason Weston, and Michael Auli. 2019. ELI5: Long form question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3558–3567, Florence, Italy. Association for Computational Linguistics.

Hao Fang, Jiawei Kong, Tianqu Zhuang, Yixiang Qiu, Kuofeng Gao, Bin Chen, Shu-Tao Xia, Yaowei Wang, and Min Zhang. 2025. Your language model can secretly write like humans: Contrastive paraphrase attacks on LLM-generated text detectors. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 8585–8602, Suzhou, China. Association for Computational Linguistics.

Pierre Fernandez, Tom Sander, Hady Elsahar, Hongyan Chang, Tomáš Souček, Valeriu Lacatusu, Tuan Tran, Sylvestre-Alvise Rebuffi, and Alexandre Mourachko. 2026. How good is post-hoc watermarking with language model rephrasing? *Preprint*, arXiv:2512.16904.

Sebastian Gehrmann, Hendrik Strobelt, and Alexander Rush. 2019. GLTR: Statistical detection and visualization of generated text. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 111–116, Florence, Italy. Association for Computational Linguistics.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Biyang Guo, Xin Zhang, Ziyuan Wang, Minqi Jiang, Jinran Nie, Yuxuan Ding, Jianwei Yue, and Yupeng Wu. 2023. How close is chatgpt to human experts? comparison corpus, evaluation, and detection. *arXiv preprint arXiv:2301.07597*.

Hanxi Guo, Siyuan Cheng, Xiaolong Jin, Zhuo Zhang, Kaiyuan Zhang, Guanhong Tao, Guangyu Shen, and Xiangyu Zhang. 2024a. Biscope: Ai-generated text detection by checking memorization of preceding tokens. In *Advances in Neural Information Processing Systems*, volume 37, pages 104065–104090. Curran Associates, Inc.

Xun Guo, Shan Zhang, Yongxin He, Ting Zhang, Wanquan Feng, Haibin Huang, and Chongyang Ma. 2024b. Detective: Detecting ai-generated text via multi-level contrastive learning. In *Advances in Neural Information Processing Systems*, volume 37, pages 88320–88347. Curran Associates, Inc.

Abhimanyu Hans, Avi Schwarzschild, Valeriia Cherepanova, Hamid Kazemi, Aniruddha Saha, Micah Goldblum, Jonas Geiping, and Tom Goldstein. 2024. Spotting llms with binoculars: zero-shot detection of machine-generated text. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org.

Xinlei He, Xinyue Shen, Zeyuan Chen, Michael Backes, and Yang Zhang. 2024. Mgtbench: Benchmarking machine-generated text detection. In *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*, CCS '24, page 2251–2265, New York, NY, USA. Association for Computing Machinery.

Benjamin D. Horne and Maurício Gruppi. 2024. Nelaps: A dataset of pink slime news articles for the study of local news ecosystems. *Proceedings of the International AAAI Conference on Web and Social Media*, 18(1):1958–1966.

Xiaomeng Hu, Pin-Yu Chen, and Tsung-Yi Ho. 2023. Radar: Robust ai-text detection via adversarial learning. In *Advances in Neural Information Processing Systems*, volume 36, pages 15077–15095. Curran Associates, Inc.

Guanhua Huang, Yuchen Zhang, Zhe Li, Yongjian You, Mingze Wang, and Zhouwang Yang. 2024. Are AI-generated text detectors robust to adversarial perturbations? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6005–6024, Bangkok, Thailand. Association for Computational Linguistics.

Junjie Huang, Ruiquan Zhang, Jinsong Su, and Yidong Chen. 2025. TempParaphraser: "heating up" text to evade AI-text detection through paraphrasing. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 31554–31573, Suzhou, China. Association for Computational Linguistics.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *Preprint*, arXiv:2310.06825.

John Kirchenbauer, Jonas Geiping, Yuxin Wen, Jonathan Katz, Ian Miers, and Tom Goldstein. 2023. A watermark for large language models. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 17061–17084. PMLR.

Kristian Kuznetsov, Eduard Tulchinskii, Laida Kushnareva, German Magai, Serguei Barannikov, Sergey Nikolenko, and Irina Piontkovskaya. 2024. Robust AI-generated text detection by restricted embeddings. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 17036–17055, Miami, Florida, USA. Association for Computational Linguistics.

Zhixin Lai, Xuesheng Zhang, and Suiyao Chen. 2024. Adaptive ensembles of fine-tuned transformers for llm-generated text detection. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pages 1–7.

Thomas Lavergne, Tanguy Urvoy, and François Yvon. 2008. Detecting fake content with relative entropy scoring. In *Proceedings of the 2008 International Conference on Uncovering Plagiarism, Authorship and Social Software Misuse - Volume 377*, PAN'08, page 27–31, Aachen, DEU. CEUR-WS.org.

Yafu Li, Qintong Li, Leyang Cui, Wei Bi, Zhilin Wang, Longyue Wang, Linyi Yang, Shuming Shi, and Yue Zhang. 2024. MAGE: Machine-generated text detection in the wild. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 36–53, Bangkok, Thailand. Association for Computational Linguistics.

Runheng Liu, Heyan Huang, Xingchen Xiao, and Zhijing Wu. 2025. Zero-shot detection of llm-generated text via implicit reward model. In *Advances in Neural Information Processing Systems*, volume 38, pages 167683–167709. Curran Associates, Inc.

Yepeng Liu and Yuheng Bu. 2024. Adaptive text watermark for large language models. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org.

Zhuang Liu, Wayne Lin, Ya Shi, and Jun Zhao. 2021. A robustly optimized bert pre-training approach with post-training. In *Chinese Computational Linguistics*, pages 471–484, Cham. Springer International Publishing.

Shixuan Ma and Quan Wang. 2024. Zero-shot detection of LLM-generated text using token cohesiveness. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 17538–17553, Miami, Florida, USA. Association for Computational Linguistics.

Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, and 1 others. 2024. Gemma: Open models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*.

Eric Mitchell, Yoonho Lee, Alexander Khazatsky, Christopher D. Manning, and Chelsea Finn. 2023. Detectgpt: zero-shot machine-generated text detection using probability curvature. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org.

Jianmo Ni, Jiacheng Li, and Julian McAuley. 2019. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 188–197, Hong Kong, China. Association for Computational Linguistics.

Michael-Andrei Panaitescu-Liess, Zora Che, Bang An, Yuancheng Xu, Pankayaraj Pathmanathan, Souradip Chakraborty, Sicheng Zhu, Tom Goldstein, and Furong Huang. 2025. Can watermarking large language models prevent copyrighted text generation and hide training data? *Proceedings of the AAAI Conference on Artificial Intelligence*, 39(23):25002–25009.

Qi Pang, Shengyuan Hu, Wenting Zheng, and Virginia Smith. 2024. No free lunch in llm watermarking: Trade-offs in watermarking design choices. *arXiv preprint arXiv:2402.16187*.

Shushanta Pudasaini, Luis Miralles, David Lillis, and Marisa Llorens Salvador. 2025. Benchmarking AI text detection: Assessing detectors against new datasets, evasion tactics, and enhanced LLMs. In *Proceedings of the 1stWorkshop on GenAI Content Detection (GenAIDetect)*, pages 68–77, Abu Dhabi, UAE. International Conference on Computational Linguistics.

Jinyan Su, Terry Zhuo, Di Wang, and Preslav Nakov. 2023. DetectLLM: Leveraging log rank information for zero-shot detection of machine-generated text. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12395–12412, Singapore. Association for Computational Linguistics.

Adaku Uchendu, Zeyu Ma, Thai Le, Rui Zhang, and Dongwon Lee. 2021. TURINGBENCH: A benchmark environment for Turing test in the age of neural text generation. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2001–2016, Punta Cana, Dominican Republic. Association for Computational Linguistics.

Ivan Vykopal, Matúš Pikuliak, Ivan Srba, Robert Moro, Dominik Macko, and Maria Bielikova. 2024. Disinformation capabilities of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14830–14847, Bangkok, Thailand. Association for Computational Linguistics.

Jan Philip Wahle, Terry Ruas, Frederic Kirstein, and Bela Gipp. 2022. How large language models are transforming machine-paraphrase plagiarism. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 952–963, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Yuxia Wang, Jonibek Mansurov, Petar Ivanov, Jinyan Su, Artem Shelmanov, Akim Tsvigun, Osama Mohammed Afzal, Tarek Mahmoud, Giovanni Puccetti, Thomas Arnold, Alham Aji, Nizar Habash, Iryna Gurevych, and Preslav Nakov. 2024. M4GT-bench: Evaluation benchmark for black-box machine-generated text detection. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3964–3992, Bangkok, Thailand. Association for Computational Linguistics.

Junchao Wu, Runzhe Zhan, Derek F. Wong, Shu Yang, Xuebo Liu, Lidia S. Chao, and Min Zhang. 2025. Who wrote this? the key to zero-shot LLM-generated text detection is GECScore. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 10275–10292, Abu Dhabi, UAE. Association for Computational Linguistics.

Junchao Wu, Runzhe Zhan, Derek F. Wong, Shu Yang, Xinyi Yang, Yulin Yuan, and Lidia S. Chao. 2024. Detectrl: Benchmarking llm-generated text detection in real-world scenarios. In *Advances in Neural Information Processing Systems*, volume 37, pages 100369–100401. Curran Associates, Inc.

Xianjun Yang, Wei Cheng, Yue Wu, Linda Petzold, William Yang Wang, and Haifeng Chen. 2023. Dna-gpt: Divergent n-gram analysis for training-free detection of gpt-generated text. *arXiv preprint arXiv:2305.17359*.

WJ Youden. 1950. Index for rating diagnostic tests. *Cancer*, 3(1):32–35.

Sungduk Yu, Man Luo, Avinash Madusu, Vasudev Lal, and Phillip Howard. 2025. Is your paper being reviewed by an llm? a new benchmark dataset and approach for detecting ai text in peer review. *arXiv preprint arXiv:2502.19614*.

Xiao Yu, Kejiang Chen, Qi Yang, Weiming Zhang, and Nenghai Yu. 2024a. Text fluoroscopy: Detecting LLM-generated text through intrinsic features. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 15838–15846, Miami, Florida, USA. Association for Computational Linguistics.

Xiao Yu, Yuang Qi, Kejiang Chen, Guoqiang Chen, Xi Yang, Pengyuan Zhu, Xiuwei Shang, Weiming Zhang, and Nenghai Yu. 2024b. Dpic: Decoupling prompt and intrinsic characteristics for llm generated text detection. In *Advances in Neural Information Processing Systems*, volume 37, pages 16194–16212. Curran Associates, Inc.

Ying Zhou, Ben He, and Le Sun. 2024. Humanizing machine-generated content: Evading AI-text detection through adversarial attack. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 8427–8437, Torino, Italia. ELRA and ICCL.

A Dataset

A.1 Data domains

Medium: We utilized the Medium Articles dataset curated by Fabio Chiusano, hosted on Hugging Face [1]. This dataset consists of more than 190k English-language articles from Medium.com, each containing textual and metadata fields, including title, body, URL, authorship, timestamp, and tags. We randomly selected a subset of 12.5k articles with word counts between 400 and 2000 that were published before 2021.

News: We curated a collection of 200k news articles from reputable news agency websites, including ABC News, Al Jazeera, American Press, Associated Press News, CBS News, CNN, NBC News, Reuters, and The Guardian. From this corpus, we randomly sampled 12.5k articles with lengths ranging from 250 to 2000 words. The selected articles span diverse topical domains such as politics, science, social issues, religion, technology, sports, and culture. All articles were published prior to the advent of modern LLMs.

Reviews: We utilized the Amazon Reviews dataset collected by (Ni et al., 2019), which comprises over 233 million customer reviews spanning from 1996 to October 2018. This large-scale dataset includes rich metadata, such as review text, star ratings, helpfulness scores, and product attributes (e.g., category, brand, price, and image features). For our benchmark, we randomly sampled 12.5k reviews from various product categories, retaining only those with 30 or more words.

Reddit: To build the Reddit component of our dataset, we extracted question–answer pairs from the ELI5 subreddit, following a collection strategy similar to (Fan et al., 2019). We restricted the dataset to answers with lengths between 400 and 2000 words, all posted before 2021. A final sample of 12.5k answers was randomly selected for inclusion in our benchmark.

arXiv: We utilized the arXiv dataset introduced by (Clement et al., 2019), which contains over 1.5 million preprint articles spanning disciplines such as physics, mathematics, and computer science. Each article includes metadata such as title, abstract, authors, categories, and citation data. To construct our dataset, we randomly sampled 12.5k abstracts with word counts ranging from 150 to 500, limited to publications before 2021.

Pink slime: We employed the NELA-PS dataset introduced by (Horne and Gruppi, 2024), which encompasses 7.9 million articles from 1093 local news sources, commonly referred to as "pink slime" journalism, spanning from March 2021 to January 2024. These outlets generate content that mimics legitimate local journalism in structure and presentation while frequently advancing partisan narratives. From this corpus, we sampled 12.5k articles published in 2021, with document lengths constrained to 250-2000 words.

Wikipedia We utilized the Plain Text Wikipedia 2020-11 dataset accessible through Kaggle [2]. This corpus comprises a comprehensive Wikipedia dump of 23 GB, containing articles spanning diverse topics and domains. From this dataset, we randomly sampled 12.5k articles, each with a word count between 400 and 2000, for inclusion in our benchmark.

A.2 Utilized LLMs and input prompts

A.2.1 Models

We employed seven distinct open-source large language models and their instruction-tuned variants sourced from the Hugging Face repository: **Llama3.2-1b**, **Llama3.2-3b**, **Llama3.1-8b**, **Mistral-7b**, **Qwen-7b**, **Gemma2-2b**, and **Gemma2-9b**.

Llama3.1-8b: The Llama 3.1-8b-Instruct model is an instruction-tuned variant of Meta's 8B-parameter LLM from the Llama 3.1 series, optimized for dialogue and assistant-like tasks. It is fine-tuned using supervised fine-tuning (SFT) and reinforcement learning with human feedback (RLHF), enhancing its ability to align with human preferences and generate helpful, and safe responses. The model supports up to 128k token context lengths and employs Grouped-Query Attention (GQA), rotary positional embeddings (RoPE), and SwiGLU activations to improve scalability and inference efficiency. Trained on over 15T tokens of publicly available data, it supports multilingual capabilities across several major languages and demonstrates strong performance in reasoning, text, and code generation tasks.

Llama3.2-1b and **Llama3.2-3b:** The Llama 3.2-1b-Instruct and Llama 3.2-3b-Instruct models are instruction-tuned variants of Meta's Llama 3.2 series, comprising 1.23 billion and 3.21 billion pa-

[1] https://huggingface.co/datasets/fabiochiu/medium-articles

[2] https://www.kaggle.com/datasets/ltcmdrdata/plain-text-wikipedia-202011

rameters respectively. Both models are optimized for multilingual dialogue applications, including tasks like agentic retrieval and summarization, and have demonstrated superior performance compared to many open-source and proprietary chat models on standard industry benchmarks. They employ an auto-regressive transformer architecture enhanced with GQA for improved inference scalability and support a context length of up to 128k tokens. Trained on up to 9 trillion tokens of publicly available online data, these models support multiple languages such as English, German, French, Italian, Portuguese, Hindi, Spanish, and Thai.

Mistral-7b: We utilized Mistral-7b-Instruct-v0.3 model, that is an instruction-tuned variant of Mistral AI's 7.25b-parameter language model, designed to excel in a wide range of natural language processing tasks. This version introduces several enhancements over its predecessors, including an expanded vocabulary of 32,768 tokens and support for the v3 tokenizer, which improves its ability to handle complex text inputs. The v0.3 instruction-tuned variant has been specifically optimized through reinforcement learning from RLHF techniques to better follow user instructions and generate more helpful responses. Despite its relatively compact size compared to models with hundreds of billions of parameters, Mistral-7b-Instruct-v0.3 demonstrates competitive performance across various benchmarks, including reasoning, coding, and language understanding tasks.

Qwen-7b: The DeepSeek-R1-Distill-Qwen-7b model is a 7.62b-parameter instruction-tuned language model developed by DeepSeek AI, based on the Qwen2.5 architecture. It was fine-tuned using reinforcement learning and SFT techniques, leveraging reasoning data generated by the larger DeepSeek-R1 model. This training approach enhances the model's capabilities in reasoning, mathematics, and coding tasks. The model supports a context length of up to 128k tokens, enabling it to handle extensive inputs effectively.

Gemma2-2b and **Gemma2-9b:** The Gemma family, developed by Google, includes the Gemma2-2b-instruct and Gemma2-9b-instruct models, which are instruction-tuned variants of the base Gemma models. These models are part of Google's effort to provide lightweight, high-performing open models, drawing from the same research and technology used to create the Gemini models. Both models are decoder-only large language models, available in English, and are designed to be versatile for various

applications, including text generation, conversational AI, and summarization.

A.2.2 Prompts

We employed LLMs in their chat-based configurations to generate AI texts across multiple writing styles. Each data domain received tailored prompts to elicit appropriate responses. For the "pink slime" data, we supplemented prompts with definitional context to ensure semantic alignment. To preserve comparability in length, the LLMs were instructed to produce outputs approximately equal in word count to the corresponding human-written text (denoted as <N>). Moreover, in the Amazon Reviews, Reddit, Pink slime, and Wikipedia datasets, we incorporated the respective titles, product name, post title, news headline, or document title, into the input prompt to enhance coherence and topical relevance. Below, we detail the specific prompts used to condition LLM outputs across the various writing styles examined in this work.

Medium:

```
[{'role': 'system', 'content': 'You
are a blog writer in Medium website.
You paraphrase the Medium article I
give you in about <N> words as if you
are the original author, maintaining
the same ideas and tone while using
your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>'},]
```

News:

```
[{'role': 'system', 'content': 'You
are a journalist working for a
reputable news agency. You paraphrase
the news article I give you in about
<N> words as if you are the original
writer, maintaining the same ideas and
tone while using your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

Amazon reviews:

```
[{'role': 'system', 'content': 'You
are an Amazon customer. You paraphrase
the review I give you about a product
with title <TITLE> in about <N> words as
if you are the original review writer,
maintaining the same ideas and tone
while using your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

Reddit:

```
[{'role': 'system', 'content': 'You
are a Reddit user.  You paraphrase
the Reddit post with title <TITLE> I
give you in about <N> words as if you
are the original Reddit post writer,
maintaining the same ideas and tone
while using your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

arXiv:

```
[{'role': 'system', 'content': 'You
are a scientific paper writer.  You
paraphrase the abstract of a scientific
paper I give you in about <N> words
as if you are the original author,
maintaining the same ideas and tone
while using your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

Pink slime:

```
[{'role': 'system', 'content': 'Pink
slime journalism is a practice in
which American news outlets, or fake
partisan operations masquerading as
such, publish poor-quality news reports
which appear to be local news. You are
a pink slime journalist. You paraphrase
the pink slime article I give you about
a subject with title <TITLE> in about
<N> words as if you are the original
article writer, maintaining the same
ideas and tone while using your own
words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

Wikipedia:

```
[{'role': 'system', 'content': 'You
are a Wikipedia writer. You paraphrase
the article I give you about a subject
with title <TITLE> in about <N> words as
if you are the original article writer,
maintaining the same ideas and tone
while using your own words.'},
{'role': 'user', 'content': 'The
article is <HUMAN TEXT>"},]
```

A.3 Dataset statistics

Table 4 reports the number of text samples included in our benchmark for each LLM evaluated. The "Human" column denotes the number of collected human-written texts. The "Paraphrased" column corresponds to the original LLM-generated outputs without humanification. The "Humanified" column indicates the number of paraphrased samples that were modified using the humanification strategies specified in the corresponding rows. Additionally, Figure 6 illustrates the word count distributions of human-written texts and LLM-generated paraphrased outputs for each writing style, aggregated across all LLMs used in this study.

B Text samples

For masked word prediction within our MLM framework, we employed the Longformer-base-4096 architecture developed by the Allen Institute for AI (Beltagy et al., 2020). In this section, we provide exemplar texts demonstrating the three humanification strategies employed in our methodology. The words enclosed in brackets and highlighted in red represent words predicted by the MLM architecture, which subsequently replaced their corresponding precedent words in the paraphrased text. Text highlighted in blue represents the baseline AI-paraphrased content prior to humanification processing.

B.1 Sample humanified text from RMM strategy

The White House is escalating its efforts to persuade Congress to approve limited [military] strikes [action] against Syria, as President Obama faces a formidable challenge in convincing lawmakers to back a new military campaign in the Middle East. The president has been personally engaging with skeptical lawmakers over the weekend, delivering [making] a tailored pitch to Democrats and Republicans who remain undecided or open [close] to

Table 4: Data statistics for each LLM utilized.

Dataset →	Medium			News			Amazon reviews			Reddit		
Strategy ↓	Human	Paraphrased	Humanified	Human	Paraphrased	Humanified	Human	Paraphrased	Humanified	Human	Paraphrased	Humanified
Paraphrasing	3000	3000	—	3000	3000	—	3000	3000	—	3000	3000	—
RMM @ p=10%	500	500	500	500	500	500	500	500	500	500	500	500
RMM @ p=20%	500	500	500	500	500	500	500	500	500	500	500	500
RMM @ p=40%	500	500	500	500	500	500	500	500	500	500	500	500
RMM @ p=60%	500	500	500	500	500	500	500	500	500	500	500	500
RMM @ p=80%	500	500	500	500	500	500	500	500	500	500	500	500
RMM @ p=100%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=10%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=20%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=40%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=60%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=80%	500	500	500	500	500	500	500	500	500	500	500	500
AWS @ p=100%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=5%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=15%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=20%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=25%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=30%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=35%	500	500	500	500	500	500	500	500	500	500	500	500
RHL @ R=40%	500	500	500	500	500	500	500	500	500	500	500	500

Dataset →	arXiv			Pink slime			Wikipedia					
Strategy ↓	Human	Paraphrased	Humanified	Human	Paraphrased	Humanified	Human	Paraphrased	Humanified			
Paraphrasing	3000	3000	—	3000	3000	—	3000	3000	—			
RMM @ p=10%	500	500	500	500	500	500	500	500	50			
RMM @ p=20%	500	500	500	500	500	500	500	500	500			
RMM @ p=40%	500	500	500	500	500	500	500	500	500			
RMM @ p=60%	500	500	500	500	500	500	500	500	500			
RMM @ p=80%	500	500	500	500	500	500	500	500	500			
RMM @ p=100%	500	500	500	500	500	500	500	500	50			
AWS @ p=10%	500	500	500	500	500	500	500	500	50			
AWS @ p=20%	500	500	500	500	500	500	500	500	500			
AWS @ p=40%	500	500	500	500	500	500	500	500	500			
AWS @ p=60%	500	500	500	500	500	500	500	500	500			
AWS @ p=80%	500	500	500	500	500	500	500	500	500			
AWS @ p=100%	500	500	500	500	500	500	500	500	50			
RHL @ R=5%	500	500	500	500	500	500	500	500	500			
RHL @ R=15%	500	500	500	500	500	500	500	500	500			
RHL @ R=20%	500	500	500	500	500	500	500	500	500			
RHL @ R=25%	500	500	500	500	500	500	500	500	500			
RHL @ R=30%	500	500	500	500	500	500	500	500	500			
RHL @ R=35%	500	500	500	500	500	500	500	500	500			
RHL @ R=40%	500	500	500	500	500	500	500	500	500			

reconsidering their opposition to military action.

According to White House officials, Obama's argument [case] centers on the dual imperative of both moral responsibility and national security interest. The president believes that the United States has a critical obligation to respond to the devastating chemical weapons attack [attacks] in Syria, which has left countless civilians, including children, dead or injured. This perspective is underscored by a series of disturbing videos, obtained by ABC News, which were shown to lawmakers in a classified briefing [session] last week.

These graphic images, which depict the harrowing aftermath of the chemical attack [attacks], are being used by the administration to make a powerful [compelling] case to Congress and the American public. Secretary of State John Kerry, who has been leading the charge to build international support [consensus] for military action, referenced the videos in a speech in Paris on Saturday, emphasizing the atrocities committed by the Syrian [Assad] regime against its own people [citizens].

Kerry's impassioned plea, which highlighted the tragic fate of innocent civilians, including children, is a stark reminder [illustration] of the human cost of inaction. As he noted, the use of chemical weapons in the middle of the night, when people [children] should have been sleeping safely in their beds, is an unconscionable act that demands [warrants] a response from the international community [body].

The administration is aware that it faces a tough sell in convincing Congress to approve military action, with a recent ABC News survey indicating deep opposition among lawmakers. However, officials remain hopeful that they can build a coalition of 60 [enough] Democrats and Republicans to overcome the threat of a filibuster and secure approval for the military strike.

In a bid to build support [consensus], Vice President Biden is hosting a dinner for over a dozen Republican senators on Sunday night, with the guest

list including several key lawmakers who have expressed reservations about military action. The administration is also counting on the support [endorsement] of retired General David Petraeus, a respected figure in military circles, who has publicly urged lawmakers to back the military strike.

As the vote on the military strike looms in the Senate as early as Wednesday, the White House is stepping [speeding] up its efforts to persuade lawmakers to support [back] the president's plan. Obama will make his case to the American public in a series of interviews with network television anchors [stations] on Monday, followed by a televised address on Tuesday. The outcome of this high-stakes debate will have far-reaching [wide-reaching] implications for the United States and its role in the Middle East, and the White House is leaving [left] no stone unturned in its bid to secure approval for military action.

B.2 Sample humanified text from AWS strategy

Pleased with the affordable [good] price and adorable [good] design[[look], I've been using this cardigan for work over the past few months. However [but], I've noticed minor [some] issues [things] where my arms have caused small fabric balls to form, which can be a bit bothersome but not entirely unexpected [bad] for a budget-friendly [work-type] item. Sizing has been an issue [problem] for me, as I often [have] find [that] cardigans in my size still gape open. If you're larger-chested [big-chested] like me, I'd suggest sizing up for a better fit. Despite [Besides] these concerns [things], I might [have] still purchase [get] more due [because] to the low cost, but a higher-quality [higher-cut] garment might [do] offer [get] better longevity [looks].

B.3 Sample humanified text from RHL strategy

I'm feeling [really] so hurt [upset] and confused after our last conversation. I said I was sorry and wanted to make amends [up], but he's now acting like I'm the one who's done him wrong. I don't see how I deserve [want] to be treated [loved] this way, especially [just] when I've been trying [able] to be understanding [kind] and accommodating [loving]. Our relationship was pretty [so] intense [good] from the start, and we were monogamous pretty [very] quickly. However [unfortunately], he refused [wanted] to acknowledge [believe] that we were in a real relationship for a few months, which was confusing and frustrating [annoying]. He had high expectations [opinion] of me, and I felt like I had to constantly prove [explain] myself to him. I've never [only] cheated on anyone before, and I thought I was able to handle [explain] myself around [in] people with good intentions [reason]. One of the things that really bothered me was how he would belittle [tell] me about my male friends. He would get [be] upset if I spent time with them or made plans with them, and he would even get [be] angry if I didn't include them in everything. I felt like he was conditioning me into isolation, and it was suffocating [annoying]. There were a lot [couple] of fights in our relationship, and many of them were petty [stupid]. Like the time he thought I smelled [was] of cologne [stupid] and swore [that] I had just slept with someone [her]. Or the time he came over and claimed [said] there were tire marks [nuts] in his parking [sweet] spot, even though [if] it was just a dirt [back] road. It was like he was looking for any excuse to get [be] upset. I also [really] felt like he was playing games with me. Like the time I told him I was lazy [sick] and didn't want to drive [go] to my friends' house, and he got upset because I didn't spend the night [time] with him. Or the time he broke up with me and then said we weren't in a relationship, even though [if] we had been hanging out and talking. It was like he was trying [able] to manipulate [trick] me into feeling [being] guilty [stupid] or responsible [sorry] for his own emotions [faults]. But the thing that really hurt [upset] me was when he introduced me to his ex-girlfriend [girl-friends] as his friend, and then acted like I was the one who had done him wrong. He said I was "fucking with his heart and emotions [mind]," and that I needed to earn [lose] his trust. It was like he was trying [out] to make me feel [look] like I was the problem [one], even though [if] I had done nothing wrong. I feel [felt] like I'm losing [wasting] my mind, to be honest [fair]. I'm trying [attempting] to be understanding [kind] and accommodating [sweet], but it feels [was] like he's not giving me any space or trust. I'm starting [beginning] to wonder [think] if I'm just not good enough for him, or if he's just not willing [able] to work through our issues [shit] together. Do I deserve [have] to be treated [left] this way?

C Detectors

Binoculars (Hans et al., 2024) is a zero-shot, model-agnostic method for detecting machine-generated text that requires no training data. It operates by comparing the perplexity of a text as evaluated by two language models: an "observer" model and a "performer" model. The observer computes the perplexity of the text directly, while the performer generates next-token predictions, which are then evaluated by the observer to compute cross-perplexity. The ratio of perplexity to cross-perplexity serves as a strong indicator of whether the text is human- or machine-generated.

Fast-DetectGPT (Bao et al., 2023) is a zero-shot method, building upon the principles of DetectGPT. It introduces the concept of conditional probability curvature to distinguish between human- and AI-authored content. The method operates by sampling alternative word choices for a given text and evaluating the conditional probabilities using a language model. By analyzing the curvature of these probabilities, Fast-DetectGPT identifies AI text.

LRR (Log-Likelihood Log-Rank Ratio) (Su et al., 2023) is a zero-shot approach. It combines two statistical measures: the log-likelihood, which assesses the absolute confidence of a language model in predicting a sequence, and the log-rank, which evaluates the relative ranking of the predicted tokens. By computing the ratio of these two measures, LRR captures nuanced differences between human-written and LLM-generated text.

Log-Likelihood (Gehrmann et al., 2019) calculates the log-probability of each token in a text sequence using a language model, assessing how predictable each word is within its context. In this framework, human-written text typically exhibits a mix of high- and low-probability tokens, reflecting natural linguistic variability. In contrast, LLM-generated text often contains a higher proportion of high-probability tokens, indicating more predictable word choices.

Rank (Gehrmann et al., 2019) evaluates the predictability of each token in a text by determining its rank within the language model's probability distribution. Tokens that consistently appear among the top-ranked predictions indicate higher predictability, a characteristic often associated with LLM-generated text. Analyzing the distribution of these token ranks assists in distinguishing between human-authored and AI-generated content.

Log-Rank (Gehrmann et al., 2019) enhances the performance of Rank method by applying a logarithmic transformation to the rank of each token within a language model's predicted probability distribution.

RADAR(Hu et al., 2023) is a framework designed to enhance the detection of AI-generated text, particularly against paraphrased content that often evades traditional detectors. It employs an adversarial training approach involving two components: a paraphraser and a detector. The paraphraser aims to rewrite AI-generated text to resemble human-authored content, thereby challenging the detector's ability to identify machine-generated text. Conversely, the detector is trained to distinguish between human-written and AI-generated texts.

D Additional results

Figure 7 shows the radar charts of comparing detectors for each LLM across all writing styles. Table 5 shows the impact of different strategies on detector performance across all writing styles for smaller models from each family evaluated in this study.

Figure 6: Word count distribution of human-written and LLM-generated texts aggregated across all LLMs. "All" represents all samples across both writing styles and LLMs.

Figure 7: Radar charts of comparing detectors in different generative models across all writing styles.

Table 5: Performance of detectors under paraphrasing (baseline), RMM, AWS, and RHL strategies.

LLM →	Gemma2 2b				Llama3.2 1b				Llama3.2 3b			
Detector ↓ Metric (%) →	AUC	W-A	SFD	URSS	AUC	W-A	SFD	URSS	AUC	W-A	SFD	URSS
Paraphrase (baseline)												
Binoculars	97.3	84.0	57.6	48.4	85.8	33.1	47.3	15.7	93.6	63.4	64.0	40.6
Fast-DetectGPT	96.8	87.6	60.6	53.0	86.4	64.7	58.2	37.7	93.3	75.4	56.2	42.4
Log-Likelihood	86.6	40.1	45.2	18.1	75.9	33.9	51.8	17.6	78.5	30.8	42.4	13.0
Log-Rank	88.1	46.1	63.0	29.0	76.7	36.9	58.9	21.7	79.1	33.3	41.3	13.7
LRR	89.5	61.7	54.3	33.5	77.0	42.9	58.2	24.9	79.1	41.0	54.7	22.5
Radar	83.1	49.6	16.1	8.0	74.2	36.6	14.7	5.4	78.7	38.9	17.3	6.7
Rank	79.4	42.7	58.8	25.1	69.1	29.2	62.8	18.3	73.6	32.7	56.8	18.6
Random meaning-preserving mutation (RMM)												
Binoculars	89.6	58.6	40.3	23.6	80.2	29.2	50.9	14.8	82.8	39.8	50.1	19.9
Fast-DetectGPT	88.9	63.2	50.8	32.1	80.1	46.9	57.8	27.1	81.8	45.8	49.2	22.5
Log-Likelihood	48.0	10.5	8.5	0.9	42.5	11.7	11.8	1.4	38.2	6.8	6.0	0.4
Log-Rank	52.2	12.9	9.3	1.2	45.7	13.3	18.4	2.5	41.0	7.8	7.6	0.6
LRR	67.6	25.5	14.5	3.7	59.6	20.0	13.2	2.6	55.3	13.8	10.7	1.5
Radar	91.7	63.1	49.3	31.1	86.2	50.9	28.9	14.7	88.8	53.1	30.9	16.4
Rank	55.7	11.5	13.2	1.5	50.2	8.5	9.6	0.8	48.7	7.4	9.7	0.7
AI-flagged word swap (AWS)												
Binoculars	88.4	59.5	49.7	29.6	76.0	28.1	32.2	9.1	81.7	43.5	36.5	15.9
Fast-DetectGPT	89.0	62.3	45.8	28.5	78.2	43.2	49.7	21.4	83.1	47.9	43.0	20.6
Log-Likelihood	29.5	5.9	6.0	0.3	25.7	7.0	13.1	0.9	22.2	3.4	4.8	0.2
Log-Rank	31.9	6.6	5.5	0.4	26.9	7.3	16.2	1.2	23.5	3.6	4.2	0.2
LRR	45.1	10.9	7.2	0.8	34.5	7.9	5.2	0.4	33.5	5.2	4.1	0.2
Radar	89.0	56.6	35.5	20.1	79.8	38.1	24.4	9.3	83.5	43.1	25.7	11.1
Rank	50.5	7.0	12.5	0.9	42.4	4.9	7.0	0.3	44.6	4.6	10.3	0.5
Recursive humanization loop (RHL)												
Binoculars	86.8	51.1	52.5	26.8	73.2	23.5	51.9	12.2	78.3	35.1	40.9	14.4
Fast-DetectGPT	86.8	55.1	50.6	27.9	75.0	34.3	53.5	18.4	78.9	37.7	45.2	17.0
Log-Likelihood	28.3	3.5	4.3	0.2	22.9	4.6	12.5	0.6	20.0	1.7	3.3	0.1
Log-Rank	31.9	4.4	4.7	0.2	25.3	5.1	12.5	0.6	22.7	2.1	3.5	0.1
LRR	49.8	10.1	11.4	1.2	38.9	7.2	6.8	0.5	38.4	5.1	6.9	0.3
Radar	89.0	54.3	41.5	22.5	80.4	37.5	27.2	10.2	83.1	40.5	26.3	10.7
Rank	50.4	6.7	13.8	0.9	41.4	3.8	6.6	0.2	43.8	4.0	7.7	0.3