Probing and Controlling Self-Reflection in Language Models

Abstract

Self-reflection—the ability of a large language model (LLM) to revisit, evaluate, and revise its own reasoning—has recently emerged as a powerful behavior enabled by reinforcement learning with verifiable rewards (RLVR). While self-reflection correlates with improved reasoning accuracy, its origin and underlying mechanisms remain poorly understood. In this work, *we first show that self-reflection is not exclusive to RLVR fine-tuned models: it already emerges, albeit rarely, in pretrained models.* To probe this latent ability, we introduce Reflection-Inducing Probing, a method that injects reflection-triggering reasoning traces from fine-tuned models into pretrained models. This intervention raises self-reflection frequency of Qwen2.5 from 0.6% to 38.9%, revealing a hidden capacity for reflection. Moreover, our analysis of internal representations shows that both pretrained and fine-tuned models maintain hidden states that distinctly separate self-reflective from non-reflective contexts. Leveraging this observation, *we then construct a self-reflection vector, a direction in activation space associated with self-reflective reasoning.* By manipulating this vector, we enable bidirectional control over the self-reflective behavior for both pretrained and fine-tuned models. Experiments across multiple reasoning benchmarks show that enhancing these vectors improves reasoning performance by up to 13.7, while suppressing them reduces computational cost, providing a flexible mechanism to navigate the trade-off between reasoning quality and efficiency without requiring additional training. Our findings further our understanding of self-reflection and support a growing body of work showing that understanding model internals can enable precise behavioral control.

1 Introduction

Reinforcement Learning with Verifiable Rewards (RLVR) has emerged as a powerful technique for enhancing the reasoning abilities of large language models (LLMs), enabling learning from outcome-level feedback across diverse tasks (Xu et al., 2025; WANG et al., 2025; Mroueh, 2025). In a nutshell, RLVR optimizes for end-task success, enabling models to autonomously explore and discover novel reasoning strategies at scale without relying on explicit supervised signals from human expertise (Zhao et al., 2025b; Ferrag et al., 2025; Su et al., 2025). Notably, it has been reported (Guo et al., 2025; Liu et al., 2025c; Zeng et al., 2025) that such training induces new emergent behaviors, such as self-reflection—the ability of a model to revisit, evaluate, and revise its prior outputs. For instance, the DeepSeek-R1 report (Guo et al., 2025) highlights that RLVR-trained models often generate tokens such as "wait", interpreted as signals of internal deliberation or critique.

At the same time, a growing body of work raises an important question: does RLVR truly incentivize new reasoning capabilities beyond those already present in the base pretrained model, or does it primarily elicit and amplify latent behaviors through training and decoding strategies (Yue et al., 2025)? This ongoing debate calls for a more principled understanding of what is genuinely learned versus what is revealed. In this work, we focus on one such behavior—self-reflection—as a concrete lens to study this question.

Despite these observations of self-reflection emerging under RLVR, it remains unclear whether such behaviors are genuinely induced by RLVR or arise from latent capabilities in the base model, and more fundamentally, why and how such reflective behaviors emerge. Answering this question is crucial for understanding the foundations of reasoning in LLMs and guiding future methods for enhancing their performance. Moreover, empirical studies have shown that reflection correlates with more accurate and robust reasoning (Zuo et al.,

Figure 1: The overall pipeline of our method. **Left:** We identify self-reflection behavior in LLMs by using LLM-as-a-judge to locate self-reflection tokens (e.g., *wait*), and extract the corresponding Reflection-Inducing Tokens (RIT) and Non-Reflection-Inducing Tokens (NIT) from their context (see 4.2 for definitions). **Middle:** Hidden state analysis reveals that both $\mathcal{A}_{\tt pt}$ and $\mathcal{A}_{\tt ft}$ exhibit clear geometric separation between reflection and non-reflection states, indicating that $\mathcal{A}_{\tt pt}$ retains latent self-reflection capacity despite its low surface-level reflection rate (0.6%). Transplanting pre-reflection responses from $\mathcal{A}_{\tt ft}$ into $\mathcal{A}_{\tt pt}$ confirms this capacity, boosting its self-reflection rate to 38.9%. **Right:** Leveraging RIT and NIT hidden states collected from both models, we construct a self-reflection vector and apply linear steering. Positive steering strength improves task performance, while negative steering yields more concise responses, demonstrating bidirectional control over the self-reflection behavior.

2025; Yue et al., 2025; Liu et al., 2024a), and that prompting models to explicitly "wait" or reflect can further improve performance with test-time computing. However, this benefit may come at a cost: reflection can increase inference time, introduce unnecessary verbosity, and reduce computational efficiency (Yang et al., 2025b; Renze & Guven, 2024; Sui et al., 2025). These findings highlight not only the need to understand self-reflection in LLMs, but also the importance of controlling it to balance reasoning quality and efficiency. These gaps motivate this work to study the following research questions:

Is self-reflection a novel behavior induced by RLVR, or does it already emerge during pretraining? Can we control self-reflection in LLMs to balance performance and computational efficiency?

Contribution In this work, we provide affirmative answers to both questions. First, we compare the reasoning behaviors of pretrained models and fine-tuned models (either via RLVR or distillation), and verify that self-reflection is already present in the pretrained model, albeit at a much lower frequency. Next, we analyze the hidden representations associated with reflective versus non-reflective reasoning, and find that they exhibit distinct activation patterns. Furthermore, we show that the degree of self-reflection can be modulated by a single direction in the representation space. Our contribution can be summarized as follows.

- **Self-Reflection already emerges during pretraining:** We demonstrate that self-reflection capabilities naturally exist in pretrained models and are not solely artifacts of RLVR.[1] However, the frequency of such behavior is extremely low—for example, only 0.6% as shown in Figure 1. To isolate the model's capacity for self-reflection from its general reasoning ability, we propose a method, called *reflection-inducing probing*, that inserts reasoning traces—specifically, those that trigger self-reflection in a fine-tuned reasoning model—into the input of the pretrained model, and then measures whether the latter produces reflection in response. Using reflection-inducing probing, we observe that the pretrained model exhibits reflection with a frequency of 38.9%, significantly higher than the baseline of 0.6%, though still lower than

---

[1]However, whether self-reflection should be interpreted as genuine metacognitive capability remains further investigation and is beyond the scope of this paper.

the fine-tuned model (which is almost 100%). Through comparative analysis of hidden representations, we show that pretrained models maintain internal structures that distinguish reflective behavior from non-reflective contexts—similar to fine-tuned models—further suggesting that pretrained models already possess self-reflection capabilities.

- **The degrees of self-reflection can be modulated by a single direction:** Motivated by the separability of reflective and non-reflective contexts in the hidden representation space, we use the method of difference-in-means (Rimsky et al., 2024) to construct a *self-reflection direction*, enabling control over self-reflection behavior for both pretrained and fine-tuned models. Our experiments demonstrate that this control mechanism offers a tunable trade-off between accuracy and efficiency: enhancing reflection improves accuracy on benchmarks by up to 13.7%, while suppressing it reduces output length by up to 32% without significant performance degradation. We further show that this direction transfers robustly across diverse tasks—including mathematical and scientific reasoning—highlighting its universality as a shared, task-agnostic mechanism.

2 Related Work

2.1 Features as Directions

Extracting feature directions, often derived from contrastive pairs of inputs, is an established technique for analyzing and manipulating neural network representations (Rimsky et al., 2024; Burns et al., 2022; Zou et al., 2023). It is widely recognized that adding such feature vectors to the model's residual stream can modify its behavior, although the optimal intervention points and specific methodologies remain areas of active research (Von Rütte et al., 2024; Jorgensen et al., 2023).

Several studies suggest that activation-space directions can capture semantic features more effectively than neurons (Geiger et al., 2024; Park et al., 2023; Bolukbasi et al., 2016). These directions can be identified using methods ranging from sparse autoencoders (Huben et al., 2024) to simple contrastive estimators such as Difference-in-Means, which has shown stronger performance in model steering (Arditi et al., 2024; Wu et al., 2025). The broader linear representation hypothesis has also motivated successful interventions for behavioral control (Shao et al., 2023; Belrose et al., 2023; Feng et al., 2025; Zhu et al., 2025). Nevertheless, we do not assume that all behaviors are single-directional; linear directions should be viewed as a useful first-order approximation, while some behaviors may require richer structures such as subspaces or manifolds.

2.2 Self-Reflection in Language Models

The concept of self-reflection in language models has gained increasing attention as a mechanism for improving reasoning quality and alignment. Recent studies (Lightman et al., 2024; Madaan et al., 2023; Puerto et al., 2024; Zelikman et al., 2022; Lightman et al., 2023; Li et al., 2025) have explored how prompting models to generate intermediate reflections, critiques, or alternative solutions can improve final outputs in tasks such as math problem solving, programming, and factual reasoning. While many of these techniques are implemented at the prompting level or through chain-of-thought scaffolding, they suggest that self-reflection is a powerful tool for enhancing reasoning. Notably, these methods often induce substantial increases in generation length and latency, raising questions about the trade-off between deliberation and efficiency (Yang et al., 2025b; Yi & Wang, 2025; Chen et al., 2024; Team et al., 2025). This places reflection control within the broader literature on test-time computation (Ai et al., 2025; Huang et al., 2025). Concurrent work such as (Wang et al., 2025) studies over-reflection from the surface-token perspective, showing that suppressing explicit markers such as "wait" can reduce unnecessary deliberation.

Related work further shows that RLVR can enhance reasoning performance by encouraging reflection through outcome-based feedback (Shah et al., 2025; Shinn et al., 2023; Wang et al., 2025; Xu et al., 2025). Empirically, models such as DeepSeek-R1 exhibit improved reasoning ability with emergent self-reflective behaviors (Guo et al., 2025; Liu et al., 2025b). However, concurrent studies suggest that RLVR may amplify latent capabilities already acquired during pretraining, rather than introducing fundamentally new ones (Shah et al., 2025; Yue et al., 2025). Our work complements this view by showing that self-reflection is a broadly distributed latent feature of LLMs, already encoded in hidden states even without explicit reflection training, and can be

selectively enhanced or suppressed through simple vector interventions. This enables lightweight control of reflective behavior, including the mitigation of over-reflection, without additional training.

3 Preliminary

3.1 Transformer Layer

Decoder-only transformers (Liu et al., 2018) map input tokens $\mathbf{t} = (t_1, t_2, \ldots, t_n) \in \mathcal{V}^n$ to output probability distributions over the vocabulary $\mathcal{V}$. Let $\mathbf{h}_i^{(\ell)} \in \mathbb{R}^d$ denote the residual stream activation (also referred to as the hidden state) of the i-th token at the ℓ-th layer, where d is the dimensionality of the hidden state. Each of the L transformer layers applies a sequence of attention and MLP to update the residual stream:

$$\widetilde{\mathbf{h}}_i^{(\ell)} = \mathbf{h}_i^{(\ell)} + \text{Attn}^{(\ell)}(\mathbf{h}_{1:i}^{(\ell)}), \quad \mathbf{h}_i^{(\ell+1)} = \widetilde{\mathbf{h}}_i^{(\ell)} + \text{MLP}^{(\ell)}(\tilde{\mathbf{h}}_i^{(\ell)}). \tag{1}$$

The final hidden state is then projected to a probability distribution over the vocabulary $\mathcal{V}$ using an unembedding matrix followed by a softmax function.

3.2 Self-Reflection

Recent work has shown that large language models (LLMs), even when pretrained purely on next-token prediction, demonstrate surprising levels of reasoning ability (Mondorf & Plank, 2024; Liu et al., 2024b; Wang et al., 2023). However, this capability can be significantly enhanced through fine-tuning on reasoning tasks using either reinforcement learning with verifiable rewards (RLVR) or supervised learning with distilled responses from reasoning models trained from RLVR (Liu et al., 2025a; Wang et al., 2024; Zhao et al., 2025a). We denote the pretrained model as $\mathcal{A}_{\texttt{pt}}$, and its fine-tuned variant as $\mathcal{A}_{\texttt{ft}}$.

A notable emergent behavior observed in fine-tuned models $\mathcal{A}_{\texttt{ft}}$ is self-reflection—the model's ability to internally evaluate, critique, or revise its own reasoning process. Unlike standard reasoning, which involves generating a direct solution to a task, self-reflection introduces an intermediate meta-cognitive step where the model pauses or backtracks to reconsider its prior outputs. This behavior is often marked by explicit tokens such as "wait," which have been shown to correlate with improved reasoning outcomes (Li et al., 2024; Liu et al., 2025c; Yeo et al., 2025).

Importantly, self-reflection is not limited to any specific model architecture, observed across both proprietary models (Jaech et al., 2024) and open-source systems (Guo et al., 2025; OLMo et al., 2024; Yang et al., 2025a), indicating that it may be a general emergent property of optimizing for complex reasoning objectives. Although phrases such as "wait" are often treated as markers of self-reflection, recent work shows that a model may generate such expressions as superficial discourse patterns, without actually revising its prior reasoning (Wang et al., 2025). For this reason, we do not define self-reflection using a fixed set of tokens alone. Instead, we use an LLM-as-a-judge (Gu et al., 2024) to evaluate complete responses and determine whether they exhibit self-reflective behavior. When self-reflection is present, we further distinguish between responses that merely contain surface-level reflection and those that demonstrate genuine reconsideration of prior reasoning. This procedure allows us to move beyond token matching and obtain a broader grounded characterization of self-reflection. Further details are provided in Section 6.3.

4 Self-Reflection Already Emerges During Pretraining

In this section, we conduct a systematic analysis of self-reflection behavior in pretrained models $\mathcal{A}_{\texttt{pt}}$ and fine-tuned reasoning models $\mathcal{A}_{\texttt{ft}}$. Using the MATH500 dataset (Hendrycks et al., 2021) as our evaluation benchmark, we compare their reasoning trajectories. We first show that self-reflection emerges naturally in pretrained models, although it appears at a substantially lower frequency than in post-trained reasoning models. We then analyze hidden-state representations and find that even pretrained models implicitly encode and distinguish between self-reflective and non-self-reflective states, despite rarely expressing reflective behavior explicitly in their outputs.

4.1 Probing Self-Reflection in Pretrained Models

To investigate whether self-reflection emerges intrinsically in $\mathcal{A}_{\texttt{pt}}$, rather than being solely a byproduct of fine-tuning strategies such as RLVR, we examined the behavior of $\mathcal{A}_{\texttt{pt}}$ on mathematical reasoning tasks using the MATH500 benchmark. Figure 1 (middle) highlights the contrast in self-reflection frequency between $\mathcal{A}_{\texttt{pt}}$ and $\mathcal{A}_{\texttt{ft}}$ models, alongside the clear geometric separation of their hidden states into reflection and non-reflection clusters. Even in the absence of task-specific supervision, $\mathcal{A}_{\texttt{pt}}$ exhibited spontaneous self-reflective behavior in a small but non-negligible fraction of cases—approximately 0.6%. These instances are characterized by explicit reconsideration or revision of prior reasoning steps. For details on how we identify self-reflection instances, please see Section 6.3. While the self-reflection tokens differ somewhat from those typically observed in RLVR-trained models, their reflective nature is still discernible. These findings suggest that self-reflection is not solely acquired through fine-tuning, but rather emerges as a latent capability within the $\mathcal{A}_{\texttt{pt}}$, one that is infrequently activated but nonetheless present.

Reflection-Inducing Probing by Injecting CoT from $\mathcal{A}_{\texttt{ft}}$ into $\mathcal{A}_{\texttt{pt}}$ However, the extremely low frequency of self-reflection in $A_{\texttt{pt}}$ makes it challenging to analyze systematically and to develop methods (which will be studied in the next section) for controlling such behavior. To address this challenge, we propose a probing method, termed *reflection-inducing probing*, that isolates the model's capacity for self-reflection from its general reasoning ability. The key idea is to decouple reasoning competence from reflective behavior by inserting reasoning traces generated by the fine-tuned model $\mathcal{A}_{\texttt{ft}}$ into the input of the pretrained model $\mathcal{A}_{\texttt{pt}}$, and then measuring whether $\mathcal{A}_{\texttt{pt}}$ generates reflection in response.

Formally, given a question q, we use the fine-tuned model $\mathcal{A}_{\texttt{ft}}$ to generate a sequence of reasoning tokens:

$$\mathcal{A}_{\texttt{ft}}(q) = (\underbrace{r_1}_{\text{pre-reflection}}, \underbrace{\texttt{reflection}}_{\text{explicit signal}}, \underbrace{r_2}_{\text{post-reflection}})$$

where r_1 denotes the initial chain-of-thought leading up to an explicit reflection token (e.g., "wait"), and r_2 represents the revised or continued reasoning after reflection. We then construct a new prompt by inserting r_1 (the pre-reflection reasoning) into the input of $\mathcal{A}_{\texttt{pt}}$, and evaluate whether $\mathcal{A}_{\texttt{pt}}$ independently produces a reflection token at the appropriate point. This setup ensures that both models operate on similar reasoning contexts, eliminating confounding differences in reasoning capability. By comparing the frequency and consistency of self-reflection under this controlled setting, we can more directly assess whether reflective behavior is present in the pretrained model and to what extent it is amplified by fine-tuning. The frequency of generating reflection with reflection-inducing probing is reported in Figure 1.

Self-Reflection emerges naturally in pretrained models albeit with much lower frequency $\mathcal{A}_{\texttt{pt}}$ exhibits clear self-reflective behavior in 38.9% of these cases, a dramatic increase from its baseline rate. This differential response demonstrates that while $\mathcal{A}_{\texttt{pt}}$ rarely produces overt reflection markers in standard contexts, it possesses latent self-reflection capabilities that can be activated by appropriate contextual triggers. These findings strongly suggest that self-reflection mechanisms are encoded during pretraining, rather than being exclusively developed through reinforcement learning. With 38.9% self-reflection cases, the subsequent section analyzes the hidden state representations of these self-reflective behaviors to provide further insights.

4.2 Hidden State Representations of Self-Reflection

To further investigate the emergence of self-reflection, we analyze the internal representations of the model when it decides to generate reflection versus when it does not. Specifically, we focus on the hidden states associated with reasoning tokens that immediately precede the generation of a reflection token (e.g., "wait"), and compare them to those that do not lead to reflection.

Since both the pretrained model $\mathcal{A}_{\texttt{pt}}$ and the fine-tuned one $\mathcal{A}_{\texttt{ft}}$ exhibit self-reflection behaviors, we use $\mathcal{A}$ to denote a generic model (either pretrained or fine-tuned), which will be specified in context. Given a question q, suppose the model $\mathcal{A}$ generates a sequence of reasoning tokens that includes self-reflection. Let $r = \mathcal{A}(q) = (r_1, \texttt{reflection}, r_2)$, where r_1 precedes the reflection token and r_2 follows it. Due to the auto-regressive nature of transformer models, the information from the question q and the reasoning tokens

r_1 is aggregated into the hidden representation of the final token in r_1, which is then used by the last layer to predict the next token—the reflection token. For convenience, we refer to the final token in r_1 as a *reflection-inducing token (RIT)*, though its hidden state captures information from the entire preceding context (q, r_1). Reflection-inducing tokens often coincide with sentence-final punctuation (e.g., ".", "!", or closing brackets) or specific markers such as "But". Now with a slight abuse of notation, let $h^{(\ell)}_{\text{reflection-inducing}}(q, r)$ denote the ℓ-th layer hidden state of a model at $\mathcal{A}$ corresponding to the reflection-inducing token. We collect all such hidden states from model outputs that contain reflection tokens into the following set

$$\mathbb{H}^{(\ell)}_{\texttt{reflect}} = \left\{ h^{(\ell)}_{\text{reflection-inducing}}(q, r) \in \mathbb{R}^d \right\}. \tag{2}$$

To study the properties of hidden states associated with self-reflection, we contrast this set with representations from cases where the model *does not* generate reflection. Specifically, to eliminate the confounding effect of token surface form, we extract hidden states from tokens that share the same form as reflection-inducing tokens (e.g., sentence-final punctuation), but which do not lead to self-reflection in the subsequent responses (within 20 tokens in the experiments). For notational convenience, we refer to these as *non-reflection-inducing tokens*, and denote their corresponding hidden states as $h^{(\ell)}_{\text{non-reflection-inducing (NIT)}}(q, r)$. We collect such non-reflection-inducing into the following set

$$\mathbb{H}^{(\ell)}_{\texttt{non}-\texttt{reflect}} = \left\{ h^{(\ell)}_{\text{non-reflection-inducing}}(q, r) \in \mathbb{R}^d \right\}. \tag{3}$$

This design ensures a fair comparison by controlling for the surface form of the reflection-inducing token, ensuring that any differences in hidden representations are attributable to the model's decision to reflect.

For $\mathcal{A}_{\texttt{pt}}$ models, which rarely generate self-reflective outputs, we use the method of reflection-inducing probing by injecting CoT from $\mathcal{A}_{\texttt{ft}}$ into $\mathcal{A}_{\texttt{pt}}$ to elicit reflective behavior. To visualize these high-dimensional representations, we employ principal component analysis (PCA) for dimensionality reduction, projecting the hidden states into a 2D space. Figure 1 presents the visualizations for the 15th layer (out of 28 total layers) for both models, with more layers presented in Appendix B.

Our analysis reveals a pattern: **both models show clear separation between self-reflection and nonself-reflection states**. While this separation is expected in $\mathcal{A}_{\texttt{ft}}$, which was explicitly trained to exhibit self-reflective behavior, the equally distinct clustering in $\mathcal{A}_{\texttt{pt}}$ is remarkable. Despite rarely generating explicit self-reflection tokens in its outputs, $\mathcal{A}_{\texttt{pt}}$ maintains internal representations that clearly distinguish between self-reflective and nonself-reflective contexts. This finding provides strong evidence that self-reflection capabilities develop during pretraining, with models encoding these patterns in their hidden state representations even when they rarely manifest in generated text. We will exploit this internal structure to develop methods for controlling self-reflection in the next section.

5 Controlling Self-Reflection in Language Models

In this section, we introduce our approach for identifying and manipulating self-reflection vectors in LLMs. Building on our finding in the last section that hidden representations distinctly separate self-reflective from non-reflective contexts, we construct self-reflection vectors, directions in activation space associated with self-reflective reasoning. We then demonstrate how these vectors can be used to bidirectionally control self-reflection behavior, either enhancing it to improve reasoning accuracy or suppressing it to reduce computational overhead. Through extensive evaluation across multiple mathematical reasoning benchmarks, we show that our method significantly outperforms strong baselines while offering flexible control over the performance-efficiency trade-off. Finally, we examine the cross-domain transferability of these vectors, revealing their potential as universal controls for self-reflection across diverse reasoning tasks.

5.1 Extract Self-Reflection Vectors

To identify the self-reflection vector in the residual stream activations, we compute the difference between the activations of self-reflective and nonself-reflective contexts. This technique, known as difference-in-means,

Figure 2: Analysis of self-reflection vectors in DeepSeek-R1-1.5B. **Left**: cosine similarity between reflection vectors across datasets and their similarity to the "wait" token. **Middle**: Effect of steering strength α on performance and response length on MATH500 injected at layer 14. **Right:** Effect of injecting the self-reflection vector at different layers of DeepSeek-R1 1.5B ($\alpha = 0.03$) on Pass@1 and response length for MATH-500.

effectively isolates key feature directions, as demonstrated in prior work (Rimsky et al., 2024; Arditi et al., 2024; Wu et al., 2025), motivating our application of this approach to the self-reflection domain. As in Section 4, we focus on the hidden state of reflection-inducing token, positing that this state encodes the model's transition into self-reflection reasoning.

For each layer $\ell \in \{1, \ldots, L\}$, we compute the mean hidden states in the reflection set $\mathbb{H}^{(\ell)}_{\texttt{reflect}}$ and non-reflection set $\mathbb{H}^{(\ell)}_{\texttt{non-reflect}}$, using 100 examples for each set, as

$$\boldsymbol{\mu}^{(\ell)}_{\texttt{reflect}} = \text{mean}(\mathbb{H}^{(\ell)}_{\texttt{reflect}}), \quad \boldsymbol{\mu}^{(\ell)}_{\texttt{non-reflect}} = \text{mean}(\mathbb{H}^{(\ell)}_{\texttt{non-reflect}}), \tag{4}$$

and then construct the self-reflection vector as the difference-in-means vector $\boldsymbol{v}^{(\ell)} = \boldsymbol{\mu}^{(\ell)}_{\texttt{reflect}} - \boldsymbol{\mu}^{(\ell)}_{\texttt{non-reflect}}$, which captures both the direction along which self-reflective and nonself-reflective activations diverge, and the magnitude of that divergence.

5.2 Model Interventions for Controlling Trade-off between Reasoning and Efficiency

To actively modulate a model's tendency to reflect, motivated by the linear representation hypothesis and prior work (Arditi et al., 2024), we apply simple linear interventions based on the self-reflection vector $\boldsymbol{v}^{(\ell)}$ from the ℓ-th layer, which is expected to capture the direction in representation space most associated with self-reflection. Specifically, we modify each residual stream $\boldsymbol{h}^{(\ell)}$ at the ℓ-th layer in (1) according to

$$\widehat{\boldsymbol{h}}^{(\ell)} = \boldsymbol{h}^{(\ell)} + \alpha \boldsymbol{v}^{(\ell)} \left\langle \boldsymbol{h}^{(\ell)}, \boldsymbol{v}^{(\ell)} \right\rangle, \tag{5}$$

where $\widehat{\boldsymbol{h}}^{(\ell)}$ replaces $\boldsymbol{h}^{(\ell)}$ as the input to the next layer, and the α controls the intervention strength. Here, $\left\langle \boldsymbol{h}^{(\ell)}, \boldsymbol{v}^{(\ell)} \right\rangle$ is a scalar projection coefficient measuring how strongly the current hidden state aligns with the self-reflection direction. When $\alpha > 0$, the self-reflection behavior is enhanced; when $\alpha < 0$, it is suppressed.

Ablation study on α To illustrate the effect of the linear intervention method for controlling self-reflection, we conduct an ablation study by varying the self-reflection steering strength α from -1.0 to 1.0, injecting the reflection vector at layer 14 in DeepSeek-R1-1.5B on the MATH-500 benchmark. The result is shown in Figure 2. Negative α values shorten responses, reducing average token length, while preserving accuracy. In contrast, positive α both lengthens responses, and boosts performance, peaking at $\alpha=0.03$ with a 12% performance gain in Pass@1, before declining at larger values due to over-reflection. This clear trade-off underscores α as a practical knob for balancing verbosity against reasoning depth. Further ablation detail on the effect of the injection layer is provided in Section 6.5.

5.3 Experimental Results

We evaluate our self-reflection control mechanism along three complementary dimensions: **reasoning ability**, **reasoning efficiency**, and **reasoning quality preservation**. For reasoning ability and efficiency,

Model	Method	MATH-500		AIME 2024		GPQA Diamond	
		Pass@1 ↑	LEN ↓	Pass@1 ↑	LEN ↓	Pass@1 ↑	LEN ↓
$\mathcal{A}_{\texttt{ft}}$ **Models**							
DeepSeek-R1-1.5B	Vanilla	84.1	4755	29.2	6118	14.0	4250
	BF	85.5	10122	30.0	8986	14.8	8210
	SR Enhanced	**87.4**	9458	**33.5**	8132	**18.9**	7496
	SR Suppressed	83.2	**3716**	27.3	**5229**	13.8	**3795**
DeepSeek-R1-7B	Vanilla	92.7	3585	55.8	4558	27.1	3696
	BF	93.1	7111	54.5	9629	32.0	5802
	SR Enhanced	**93.5**	8959	**58.2**	5684	**34.6**	6513
	SR Suppressed	91.2	**2439**	52.9	**3319**	26.5	**3120**
OLMo2-13B	Vanilla	41.8	3075	7.2	3753	15.2	2645
	BF	43.2	4891	10.2	4894	17.0	3714
	SR Enhanced	**47.9**	4574	**11.7**	4941	**19.1**	3490
	SR Suppressed	40.8	**2106**	6.5	**2656**	13.7	**1375**
OLMo3-7B-Think	Vanilla	94.5	7351	61.6	7212	47.6	8301
	BF	95.0	8251	62.3	9856	48.0	10543
	SR Enhanced	**95.4**	7690	**65.3**	9653	**51.2**	10015
	SR Suppressed	94.2	**4822**	61.3	**5201**	47.0	**5544**
$\mathcal{A}_{\texttt{pt}}$ **Models**							
Qwen2.5-1.5B	Vanilla	27.5 ± 1.3	$\mathbf{1515 \pm 242}$	0.2 ± 0.0	$\mathbf{544 \pm 98}$	5.7 ± 0.7	$\mathbf{702 \pm 40}$
	BF	29.6 ± 1.4	3993 ± 312	0.1 ± 0.2	4517 ± 428	5.0 ± 0.8	1389 ± 205
	SR Enhanced	$\mathbf{36.9 \pm 2.3}$	1836 ± 174	$\mathbf{6.1 \pm 1.7}$	2525 ± 233	$\mathbf{6.8 \pm 0.9}$	814 ± 96
Qwen2.5-7B	Vanilla	44.8 ± 1.9	$\mathbf{1294 \pm 15}$	3.9 ± 0.4	$\mathbf{2285 \pm 297}$	16.2 ± 0.6	$\mathbf{598 \pm 143}$
	BF	46.0 ± 1.1	3986 ± 351	5.3 ± 0.9	4526 ± 401	$\mathbf{16.9 \pm 1.2}$	1639 ± 188
	SR Enhanced	$\mathbf{56.6 \pm 2.7}$	2671 ± 214	$\mathbf{16.1 \pm 2.4}$	2941 ± 265	14.8 ± 1.5	1816 ± 203
Llama 3.1-8B	Vanilla	44.0 ± 2.4	$\mathbf{1613 \pm 189}$	3.5 ± 0.4	$\mathbf{1653 \pm 124}$	30.9 ± 1.2	$\mathbf{1914 \pm 351}$
	BF	40.1 ± 1.8	3771 ± 294	2.9 ± 0.8	3912 ± 377	26.1 ± 1.9	5031 ± 462
	SR Enhanced	$\mathbf{57.7 \pm 2.1}$	2887 ± 241	$\mathbf{16.5 \pm 2.6}$	2974 ± 286	$\mathbf{34.1 \pm 1.7}$	3995 ± 355

Table 1: Performance on mathematical and scientific reasoning benchmarks across $\mathcal{A}_{\texttt{ft}}$ and $\mathcal{A}_{\texttt{pt}}$ models. We compare **Vanilla** (no intervention), **BF** (budget forcing via "wait" token insertion), and our method **SR Enhanced/SR Suppressed** (applying positive or negative α to amplify or suppress self-reflection during inference). For $\mathcal{A}_{\texttt{pt}}$ models, we report only **SR Enhanced**, since self-reflection triggers it only rarely. Pass@1 denotes accuracy (higher is better), and LEN denotes average generation length (lower is better). We use 10% of the data as a validation set to select the optimal α in Eq. 5.

we report Pass@1 and average response length on two mathematical reasoning benchmarks, MATH-500 (Hendrycks et al., 2021) and AIME 2024, as well as one scientific QA benchmark, GPQA Diamond (Rein et al., 2024). To assess whether steering self-reflection alters the semantic quality of the reasoning process itself, we additionally evaluate the generated chains using ROSCOE-SS (Golovneva et al., 2023), which measures semantic agreement across reasoning steps using `facebook/roscoe-512-roberta-base` embeddings.

Experiments are conducted on both $\mathcal{A}_{\texttt{pt}}$ and $\mathcal{A}_{\texttt{ft}}$. For $\mathcal{A}_{\texttt{pt}}$ models, we use Qwen2.5-1.5B, Qwen2.5-7B and Llama 3.1 8B (Grattafiori et al., 2024; Yang et al., 2024). For $\mathcal{A}_{\texttt{ft}}$, we evaluate DeepSeek-R1 1.5B and 7B, OLMo-2-13B-Instruct and OLMo3-7B-Think (Guo et al., 2025; OLMo et al., 2024; Olmo et al., 2025). All evaluations use greedy decoding. For $\mathcal{A}_{\texttt{pt}}$ models, we report the mean and standard deviation across steering vectors constructed from CoT traces generated by four different $\mathcal{A}_{\texttt{ft}}$ models. For $\mathcal{A}_{\texttt{ft}}$ models, we use a fixed validation-selected steering configuration and report point estimates.

We compare three inference strategies: **Vanilla**, which uses standard decoding without intervention; **BF** (Budget Forcing), which encourages reflection by appending a "wait" token to generations shorter than 8196 tokens (Guo et al., 2025; Muennighoff et al., 2025); and **SR Enhanced/SR Suppressed**, our method that perturbs hidden states using self-reflection vectors scaled by a coefficient α (positive for enhancement, negative for suppression). Since $\mathcal{A}_{\texttt{ft}}$ models can frequently trigger self-reflection, we evaluate both enhancement and suppression for them; in contrast, $\mathcal{A}_{\texttt{pt}}$ models exhibit such behavior only rarely, so we report SR enhancement only. We use 10% of the data as a validation set to select the optimal α in Eq. 5. Table 1 reports

Setting	DeepSeek-R1-1.5B	DeepSeek-R1-7B	OLMo2-13B	OLMo3-7B-Think	Qwen2.5-1.5B	Qwen2.5-7B	Llama 3.1-8B
Vanilla	0.562	**0.589**	**0.537**	**0.594**	0.518	0.541	**0.576**
SR Enhanced	0.558	0.586	0.534	0.589	**0.523**	**0.549**	0.561
SR Suppressed	**0.565**	0.577	0.533	0.591	\	\	\

Table 2: ROSCOE-SS scores on MATH500 across all models. Higher is better. We compare **Vanilla** and our method **SR Enhanced/SR Suppressed**. For $\mathcal{A}_{\mathtt{pt}}$ models, we report only **SR Enhanced**, since self-reflection is triggered only rarely and suppression is therefore less informative.

reasoning ability and efficiency, while Table 2 evaluates whether these interventions preserve the semantic quality of the reasoning chain.

Key Findings. Our results highlight four major insights. First, SR Enhancement improves reasoning performance across most evaluated datasets and model sizes. For example, Qwen2.5 7B's performance on MATH-500 jumps by 11.8 percentage points (from 44.8% to 56.6%), and DeepSeek-R1 variants enjoy similar boosts when employing reflection-enhanced decoding. Furthermore, this performance gain is also accompanied by a noticeable increase in response length, suggesting that longer responses can be beneficial when tackling more challenging reasoning tasks.

Second, SR Suppression offers fine-grained control over computational cost. It consistently reduces output length while preserving most of the model's accuracy. Notably, DeepSeek-R1-7B reduces average token length from 3585 to 2439 on MATH-500 with only a minor drop in Pass@1, which remains above 91%.

Third, these effects demonstrate strong generalizability across training paradigms and model families. The observed improvements hold for both $\mathcal{A}_{\mathtt{ft}}$ models (e.g., DeepSeek-R1, OLMO) and $\mathcal{A}_{\mathtt{pt}}$ models (e.g., Qwen2.5, Llama3.1). We also observe a performance drop for Qwen2.5-7B on GPQA Diamond under SR Enhanced. This suggests that for knowledge-intensive tasks, excessive self-reflection may not always be beneficial, especially when additional deliberation does not provide new factual evidence.

Fourth, self-reflection steering does not show a clear degradation in ROSCOE-SS. Across model families, the scores remain broadly comparable to the vanilla setting, suggesting that our intervention can modulate reflective behavior without obviously degrading the generated reasoning traces under this metric. Since ROSCOE-SS is only a proxy for reasoning-trace quality, we treat this result as a complementary diagnostic.

Building on this generalizability, we emphasize the practical value of inference-time control over latent self-reflection dynamics. Unlike rigid interventions such as budget forcing, our method affords semantically grounded, continuous modulation of a model's internal self-reflection, enabling a tunable trade-off between performance and efficiency, especially in resource-constrained settings.

6 Further Analyses of Self-Reflection Vectors

6.1 Transferability of Self-Reflection Vectors

To investigate the transferability of self-reflection vectors across different reasoning domains, we evaluated whether vectors extracted from the GPQA Diamond dataset could be effectively transferred to mathematical reasoning tasks in MATH500. We compute the cosine similarity between self-reflection vectors extracted from different domains (MATH500 and GPQA Diamond), and between these vectors and the embedding of the token "wait" in DeepSeek-R1-Distill-Qwen-1.5B. For tokenizers containing multiple subword tokens for "wait", we report the average cosine similarity along with its variance. The results are plotted in Figure 2.

Model	Setting	PASS@1	Len
1.5B	SR Enhanced	86.4	7781
	SR Suppressed	82.6	3684
7B	SR Enhanced	93.0	6007
	SR Suppressed	91.0	2992

Table 3: Performance on MATH500 when applying self-reflection vectors extracted from GPQA Diamond to DeepSeek-R1 models.

Our analysis revealed remarkable consistency in the neural signatures of self-reflection across these distinct domains. Specifically, vectors extracted from GPQA and MATH500 exhibit high cosine similarity, suggesting that the internal representation of reflective

Model	Onset Token	Evidence Quote
DeepSeek-R1-1.5B	`wait`	"Wait, that cannot be right because I double-counted ..."
DeepSeek-R1-7B	`wait`	"Wait, let me re-check the sign here ..."
OLMo2-13B	`But`	"But this step assumes independence, which is not valid ..."
OLMo3-7B-Think	`hold`	"Hold on, I should recompute from the definition ..."
Qwen2.5-1.5B	`wait`	"Wait, I need to verify whether the carry term is correct ..."
Qwen2.5-7B	`hmm`	"Hmm, that earlier conclusion does not follow from the equation ..."
Llama 3.1-8B	`wait`	"Wait, I made an invalid simplification in the previous step ..."

Table 5: Self-reflection examples for each model. For each model, we report one reflection token identified by the judge together with a short supporting quote from a response labeled as `GENUINE_SELF_REFLECTION`.

states is largely domain-invariant. Notably, these self-reflection vectors are substantially different from the embedding of the token "wait", indicating that they encode deeper semantic properties of reflective behavior rather than surface-level cues.

Further, we evaluate the performance of self-reflection vectors derived from GPQA-Diamond on MATH500 using our proposed intervention method, SR-Enhanced/Suppressed, and present the results in Table 3. Notably, we observe similar performance gains to those seen with in-domain self-reflection vectors, as reported in Table 1. This cross-domain transfer demonstrates that the reflective mechanism captures a generalizable cognitive pattern rather than being confined to task-specific reasoning strategies. Together, these findings suggest that LLMs develop a unified internal representation of self-reflection, one that can be leveraged across tasks without the need for domain-specific fine-tuning.

6.2 Comparison of Different Methods

To validate our choice of the difference-in-means approach for generating steering vectors, we conduct a comparative analysis against alternative feature-extraction techniques. We consider four variants: (i) a difference-in-means direction with the projected update used in the main paper, (ii) a difference-in-means direction with additive steering, (iii) a standard PCA direction, and (iv) contrastive PCA (Abid et al., 2018). All methods are evaluated under identical settings.

Table 4: Comparison of feature-extraction methods and steering methods for constructing the self-reflection vector on DeepSeek-R1 1.5B.

Method	SR Enhanced		SR Suppressed	
	PASS@1 ↑	LEN ↓	PASS@1 ↑	LEN ↓
Difference-in-means	**87.4**	**9458**	**83.2**	**3716**
↪ Additive Steering	86.0	9845	83.0	3639
PCA	84.3	10074	79.1	3912
Contrastive PCA	84.7	9876	80.6	4078

The evaluation was performed under identical intervention settings for both the enhancement and suppression of the target behavior. The quantitative results are shown in Table 4. The data indicate that the difference-in-means approach achieves the highest task performance in both scenarios, yielding superior PASS@1 scores while maintaining reasonable lengths.

This empirical finding aligns with insights from recent work in mechanistic interpretability (Wu et al., 2025). These studies suggest that for the specific goal of causal steering of model behavior, simple directional vectors derived from differences often outperform other techniques, thereby motivating our choice of the difference-in-means approach.

6.3 Identifying Self-Reflection Instances

To identify self-reflection in language model outputs, we use an LLM-as-a-judge procedure instead of relying solely on a fixed set of keywords. We define a response as exhibiting genuine self-reflection only when the model explicitly revisits its earlier reasoning and performs a meaningful check, correction, backtrack, revision, or re-derivation. This criterion is intentionally stricter than keyword matching: discourse markers

such as `wait`, `hold on`, or `let me think` are not considered sufficient unless they are followed by substantive reconsideration of prior reasoning.

Given a question-response pair, the judge assigns one of three labels: `NO_REFLECTION`, `SURFACE_REFLECTION`, or `GENUINE_SELF_REFLECTION`. For responses labeled as `GENUINE_SELF_REFLECTION`, the judge further identifies all self-reflection occurrences in the response. For each occurrence, the judge returns (i) the reflection phrase, (ii) the corresponding reflection token, and (iii) a short evidence quote. This allows us to recover the full set of self-reflection points within a generation, rather than restricting analysis to only the first reflective turn. The full judge prompt is provided in Appendix C.

We apply this procedure to model outputs on the MATH500 benchmark, using a maximum generation length of 8196 tokens. Final labels and self-reflection tokens are determined by the judge rather than by the presence of any single keyword. To provide qualitative intuition, Table 5 presents one representative example for each model, together with a reflection token identified by the judge and a short supporting quote. As a complementary analysis, we also examine the surface tokens associated with self-reflection in Table 6. We find that the specific tokens are not identical across models, but they exhibit substantial overlap. In particular, markers such as `wait`, and

Model	Top-5 Reflection Onset Tokens
DeepSeek-R1-1.5B	`wait`, `but`, `hold`, `hmm`, `actually`
DeepSeek-R1-7B	`wait`, `but`, `hold`, `so`, `actually`
OLMo2-13B	`but`, `wait`, `however`, `hold`, `actually`
OLMo3-7B-Think	`hold`, `wait`, `but`, `hmm`, `actually`
Qwen2.5-1.5B	`wait`, `hmm`, `but`, `hold`, `actually`
Qwen2.5-7B	`hmm`, `wait`, `but`, `actually`, `hold`
Llama 3.1-8B	`wait`, `but`, `hold`, `actually`, `hmm`

Table 6: Top-5 most frequent reflection onset tokens for each model, as identified by the judge on responses labeled `GENUINE_SELF_REFLECTION`.

`actually` recur across multiple model families, suggesting that genuine reflective revision is often expressed through a partially shared set of surface cues, despite model-specific variation.

6.4 Linear Separability of Self-Reflection States

To quantify whether self-reflection states are linearly encoded in model representations, we train a linear SVM at each layer to distinguish reflection-inducing tokens from non–reflection-inducing tokens in Qwen2.5-1.5B and DeepSeek-R1-Distill-Qwen-1.5B. The classifier is trained on 10% of the hidden states and evaluated on the remaining 90%.

As shown in Figure 3, test accuracy exceeds 99% across all layers for both models. This result indicates that reflection-inducing and non–reflection-inducing tokens are almost perfectly linearly separable in the original hidden-state space, suggesting that self-reflection is represented as a robust latent direction rather than a weak or diffuse signal.

Notably, this linear structure also appears in Qwen2.5-1.5B, which produces very few explicit self-reflection tokens. This finding supports our claim that self-reflection is encoded internally even in models that rarely express it overtly, and is therefore not tied only to surface markers or a specific training recipe.

Figure 3: Linear-probe test accuracy of a linear SVM trained to distinguish reflection-inducing tokens from non–reflection-inducing tokens at each layer of DeepSeek-R1-Distill-Qwen-1.5B and Qwen2.5-1.5B. Accuracy exceeds 99% across all layers for both models, indicating near-perfect linear separability.

This linear separability also helps explain the effectiveness of our steering method: the intervention acts along an existing representational axis that already distinguishes reflective from non-reflective states, allowing it to amplify or suppress self-reflection by leveraging an emergent internal structure. Complementary PCA visualizations in Appendix B provide a qualitative view of the same geometric pattern.

6.5 Ablation Study

We determine the injection configuration using a two-stage selection procedure. First, for each candidate layer ℓ, we conduct a grid search over the steering coefficient $\alpha \in [-1.0, 1.0]$ to identify the value that yields the best validation performance. This search covers both positive and negative directions, corresponding respectively to enhancing and suppressing self-reflective behavior. Second, after identifying effective scales, we compare candidate injection layers to determine where the model is most receptive to intervention.

Ablation on Steering Strength α. We first examine the effect of steering magnitude by varying α from -1.0 to 1.0 while fixing the injection layer to layer 14 of DeepSeek-R1-1.5B. The results are shown in Figure 2. Overall, the relationship between α and performance is clearly asymmetric: moderate positive values are beneficial, whereas overly large magnitudes in either direction are harmful.

For negative α, the intervention suppresses the self-reflection direction. In this regime, response length decreases substantially, indicating reduced deliberative reasoning. Notably, moderate negative values shorten outputs without causing a large drop in Pass@1, suggesting that part of the model's reflective behavior may be verbose rather than essential. For positive α, the model is pushed further along the self-reflection direction. Small positive values improve Pass@1 and generally increase response length, indicating that stronger reflective reasoning can help the model revise faulty intermediate steps. However, this benefit is not monotonic. Performance peaks around $\alpha = 0.03$, after which larger positive values begin to hurt both answer quality and efficiency. Taken together, these results suggest that self-reflection is most useful when it is moderately amplified rather than maximized.

Effect of Injection Layer. We then isolate the role of layer choice by fixing $\alpha = 0.03$ and injecting the self-reflection vector at each layer of DeepSeek-R1-1.5B on MATH-500 (Figure 2). We observe a clear layer dependence: performance improves most strongly when the intervention is applied at middle layers, with layer 14 giving the best overall result.

This pattern suggests that self-reflection is most effectively modulated at intermediate stages of computation. When injected into early layers, the steering signal has to pass through many subsequent transformations, which can dilute or overwrite its effect before it influences the final reasoning trajectory. As a result, early-layer interventions produce only limited gains. In contrast, injecting into very late layers places the perturbation close to token generation, where it is less able to reshape the latent reasoning process and more likely to act as a superficial bias on next-token prediction.

The strong performance of middle-layer injection is consistent with the view that these layers encode higher-level reasoning dynamics in a form that is both semantically meaningful and still causally effective for downstream computation (Jiang et al., 2025; Skean et al., 2025). Intervening at this stage allows the model to revise or strengthen its internal reflective proc ess before the final answer is produced.

7 Conclusion

In this paper, we demonstrated that self-reflection in large language models is an emergent capability that develops during pretraining rather than being uniquely induced by reinforcement learning techniques. Through contrastive analysis of hidden state representations, we revealed that even models with minimal explicit reflection behavior maintain internal neural signatures that distinguish self-reflective contexts. By exploiting these representations, we developed an intervention method that enables bidirectional control over self-reflection, providing a flexible mechanism to navigate the performance-efficiency trade-off without requiring additional training. This work primarily focuses on understanding the internal representations underlying self-reflection and leveraging them for controllable behavior. There remain several important directions for future work. Our method requires users to decide in advance whether to enhance or suppress reflection, rather than adapting to task difficulty automatically. It also requires white-box access to internal activations, limiting its use for closed-source or API-only models. Moreover, our experiments are limited to models up to 13B parameters, leaving it open whether reflection vectors behave similarly in larger models. We leave adaptive control, restricted-access settings, and larger-scale evaluation to future work.

References

Abubakar Abid, Martin J Zhang, Vivek K Bagaria, and James Zou. Exploring patterns enriched in a dataset with contrastive principal component analysis. *Nature communications*, 9(1):2134, 2018.

Rui Ai, Yuqi Pan, David Simchi-Levi, Milind Tambe, and Haifeng Xu. Beyond majority voting: Llm aggregation by leveraging higher-order information. *arXiv preprint arXiv:2510.01499*, 2025.

Andy Arditi, Oscar Balcells Obeso, Aaquib Syed, Daniel Paleka, Nina Rimsky, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=pH3XAQME6c.

Nora Belrose, David Schneider-Joseph, Shauli Ravfogel, Ryan Cotterell, Edward Raff, and Stella Biderman. LEACE: Perfect linear concept erasure in closed form. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=awIpKpwTwF.

Tolga Bolukbasi, Kai-Wei Chang, James Y Zou, Venkatesh Saligrama, and Adam T Kalai. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Advances in neural information processing systems*, 29, 2016.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. *ArXiV*, 2022.

Qiguang Chen, Libo Qin, Jiaqi WANG, Jingxuan Zhou, and Wanxiang Che. Unlocking the capabilities of thought: A reasoning boundary framework to quantify and optimize chain-of-thought. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=pC44UMwy2v.

Jiahai Feng, Stuart Russell, and Jacob Steinhardt. Monitoring latent world states in language models with propositional probes. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=0yvZm2AjUr.

Mohamed Amine Ferrag, Norbert Tihanyi, and Merouane Debbah. Reasoning beyond limits: Advances and open problems for llms. *arXiv preprint arXiv:2503.22732*, 2025.

Atticus Geiger, Zhengxuan Wu, Christopher Potts, Thomas Icard, and Noah Goodman. Finding alignments between interpretable causal variables and distributed neural representations. In *Causal Learning and Reasoning*, pp. 160–187. PMLR, 2024.

Olga Golovneva, Moya Peng Chen, Spencer Poff, Martin Corredor, Luke Zettlemoyer, Maryam Fazel-Zarandi, and Asli Celikyilmaz. ROSCOE: A suite of metrics for scoring step-by-step reasoning. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=xYlJRpzZtsY.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, et al. A survey on llm-as-a-judge. *The Innovation*, 2024.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *NeurIPS*, 2021.

Audrey Huang, Adam Block, Qinghua Liu, Nan Jiang, Akshay Krishnamurthy, and Dylan J Foster. Is best-of-n the best of them? coverage, scaling, and optimality in inference-time alignment. *arXiv preprint arXiv:2503.21878*, 2025.

Robert Huben, Hoagy Cunningham, Logan Riggs Smith, Aidan Ewart, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=F76bwRSLeK.

Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai o1 system card. *arXiv preprint arXiv:2412.16720*, 2024.

Jiachen Jiang, Yuxin Dong, Jinxin Zhou, and Zhihui Zhu. From compression to expression: A layerwise analysis of in-context learning. *arXiv preprint arXiv:2505.17322*, 2025.

Ole Jorgensen, Dylan Cope, Nandi Schoots, and Murray Shanahan. Improving activation steering in language models with mean-centring. *arXiv preprint arXiv:2312.03813*, 2023.

Dacheng Li, Shiyi Cao, Tyler Griggs, Shu Liu, Xiangxi Mo, Eric Tang, Sumanth Hegde, Kourosh Hakhamaneshi, Shishir G Patil, Matei Zaharia, et al. Llms can easily learn to reason from demonstrations structure, not content, is what matters! *arXiv preprint arXiv:2502.07374*, 2025.

Yanhong Li, Chenghao Yang, and Allyson Ettinger. When hindsight is not 20/20: Testing limits on reflective thinking in large language models. *arXiv preprint arXiv:2404.09129*, 2024.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*, 2023.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=v8L0pN6EOi.

Fengyuan Liu, Nouar AlDahoul, Gregory Eady, Yasir Zaki, Bedoor AlShebli, and Talal Rahwan. Self-reflection outcome is sensitive to prompt construction. *arXiv preprint arXiv:2406.10400*, 2024a.

Peter J Liu, Mohammad Saleh, Etienne Pot, Ben Goodrich, Ryan Sepassi, Lukasz Kaiser, and Noam Shazeer. Generating wikipedia by summarizing long sequences. *arXiv preprint arXiv:1801.10198*, 2018.

Qianchu Liu, Sheng Zhang, Guanghui Qin, Timothy Ossowski, Yu Gu, Ying Jin, Sid Kiblawi, Sam Preston, Mu Wei, Paul Vozila, Tristan Naumann, and Hoifung Poon. X-reasoner: Towards generalizable reasoning across modalities and domains, 2025a. URL https://arxiv.org/abs/2505.03981.

Zichen Liu, Changyu Chen, Chao Du, Wee Sun Lee, and Min Lin. Oat: A research-friendly framework for llm online alignment, 2024b.

Zichen Liu, Changyu Chen, Wenjun Li, Tianyu Pang, Chao Du, and Min Lin. There may not be aha moment in r1-zero-like training — a pilot study. https://oatllm.notion.site/oat-zero, 2025b. Notion Blog.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding r1-zero-like training: A critical perspective. *arXiv preprint arXiv:2503.20783*, 2025c.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=S37hOerQLB.

Philipp Mondorf and Barbara Plank. Beyond accuracy: Evaluating the reasoning behavior of large language models - a survey. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=Lmjgl2n11u.

Youssef Mroueh. Reinforcement learning with verifiable rewards: Grpo's effective loss, dynamics, and success amplification. *arXiv preprint arXiv:2503.06639*, 2025.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettle-moyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. s1: Simple test-time scaling, 2025. URL https://arxiv.org/abs/2501.19393.

Team OLMo, Pete Walsh, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Shane Arora, Akshita Bhagia, Yuling Gu, Shengyi Huang, Matt Jordan, et al. 2 olmo 2 furious. *arXiv preprint arXiv:2501.00656*, 2024.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, Pradeep Dasigi, Robert Berry, Saumya Malik, Saurabh Shah, Scott Geng, Shane Arora, Shashank Gupta, Taira Anderson, Teng Xiao, Tyler Murray, Tyler Romero, Victoria Graf, Akari Asai, Akshita Bhagia, Alexander Wettig, Alisa Liu, Aman Rangapur, Chloe Anastasiades, Costa Huang, Dustin Schwenk, Harsh Trivedi, Ian Magnusson, Jaron Lochner, Jiacheng Liu, Lester James V. Miranda, Maarten Sap, Malia Morgan, Michael Schmitz, Michal Guerquin, Michael Wilson, Regan Huff, Ronan Le Bras, Rui Xin, Rulin Shao, Sam Skjonsberg, Shannon Zejiang Shen, Shuyue Stella Li, Tucker Wilde, Valentina Pyatkin, Will Merrill, Yapei Chang, Yuling Gu, Zhiyuan Zeng, Ashish Sabharwal, Luke Zettlemoyer, Pang Wei Koh, Ali Farhadi, Noah A. Smith, and Hannaneh Hajishirzi. Olmo 3, 2025. URL https://arxiv.org/abs/2512.13961.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *In the 36th Annual ACM Symposium on User Interface Software and Technology (UIST '23)*, UIST '23, New York, NY, USA, 2023. Association for Computing Machinery.

Haritz Puerto, Tilek Chubakov, Xiaodan Zhu, Harish Tayyar Madabushi, and Iryna Gurevych. Fine-tuning with divergent chains of thought boosts reasoning through self-correction in language models, 2024. URL https://openreview.net/forum?id=u4whlT6xKO.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*, 2024. URL https://openreview.net/forum?id=Ti67584b98.

Matthew Renze and Erhan Guven. Self-reflection in llm agents: Effects on problem-solving performance. *arXiv preprint arXiv:2405.06682*, 2024.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering llama 2 via contrastive activation addition. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15504–15522, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.828. URL https://aclanthology.org/2024.acl-long.828/.

Darsh J Shah, Peter Rushton, Somanshu Singla, Mohit Parmar, Kurt Smith, Yash Vanjani, Ashish Vaswani, Adarsh Chaluvaraju, Andrew Hojel, Andrew Ma, et al. Rethinking reflection in pre-training. *arXiv preprint arXiv:2504.04022*, 2025.

Shun Shao, Yftah Ziser, and Shay B. Cohen. Gold doesn't always glitter: Spectral removal of linear and nonlinear guarded attribute information. In Andreas Vlachos and Isabelle Augenstein (eds.), *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pp. 1611–1622, Dubrovnik, Croatia, May 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.eacl-main.118. URL https://aclanthology.org/2023.eacl-main.118/.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36: 8634–8652, 2023.

Oscar Skean, Md Rifat Arefin, Dan Zhao, Niket Nikul Patel, Jalal Naghiyev, Yann LeCun, and Ravid Shwartz-Ziv. Layer by layer: Uncovering hidden representations in language models. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=WGXb7UdvTX.

Yi Su, Dian Yu, Linfeng Song, Juntao Li, Haitao Mi, Zhaopeng Tu, Min Zhang, and Dong Yu. Expanding rl with verifiable rewards across diverse domains. *arXiv preprint arXiv:2503.23829*, 2025.

Yang Sui, Yu-Neng Chuang, Guanchu Wang, Jiamu Zhang, Tianyi Zhang, Jiayi Yuan, Hongyi Liu, Andrew Wen, Shaochen Zhong, Hanjie Chen, et al. Stop overthinking: A survey on efficient reasoning for large language models. *arXiv preprint arXiv:2503.16419*, 2025.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, et al. Kimi k1. 5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*, 2025.

Dimitri Von Rütte, Sotiris Anagnostidis, Gregor Bachmann, and Thomas Hofmann. A language model's guide through latent space. *arXiv preprint arXiv:2402.14433*, 2024.

Chenlong Wang, Yuanning Feng, Dongping Chen, Zhaoyang Chu, Ranjay Krishna, and Tianyi Zhou. Wait, we don't need to" wait"! removing thinking tokens improves reasoning efficiency. *arXiv preprint arXiv:2506.08343*, 3, 2025.

Hongru WANG, Deng Cai, Wanjun Zhong, Shijue Huang, Jeff Z. Pan, Zeming Liu, and Kam-Fai Wong. Self-reasoning language models: Unfold hidden reasoning chains with few reasoning catalyst. In *Workshop on Reasoning and Planning for Large Language Models*, 2025. URL https://openreview.net/forum?id=p4wXiD8FX1.

Shuhe Wang, Shengyu Zhang, Jie Zhang, Runyi Hu, Xiaoya Li, Tianwei Zhang, Jiwei Li, Fei Wu, Guoyin Wang, and Eduard Hovy. Reinforcement learning enhanced llms: A survey. *arXiv preprint arXiv:2412.10400*, 2024.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=1PL1NIMMrw.

Yiping Wang, Qing Yang, Zhiyuan Zeng, Liliang Ren, Lucas Liu, Baolin Peng, Hao Cheng, Xuehai He, Kuan Wang, Jianfeng Gao, et al. Reinforcement learning for reasoning in large language models with one training example. *arXiv preprint arXiv:2504.20571*, 2025.

Zhengxuan Wu, Aryaman Arora, Atticus Geiger, Zheng Wang, Jing Huang, Dan Jurafsky, Christopher D Manning, and Christopher Potts. Axbench: Steering llms? even simple baselines outperform sparse autoencoders. *arXiv preprint arXiv:2501.17148*, 2025.

Fengli Xu, Qianyue Hao, Zefang Zong, Jingwei Wang, Yunke Zhang, Jingyi Wang, Xiaochong Lan, Jiahui Gong, Tianjian Ouyang, Fanjin Meng, et al. Towards large reasoning models: A survey of reinforced reasoning with large language models. *arXiv preprint arXiv:2501.09686*, 2025.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jing Zhou, Jingren Zhou, Junyang Lin, Kai Dang, Keqin Bao, Kexin Yang, Le Yu, Lianghao Deng, Mei Li, Min Xue, Mingze Li, Pei Zhang, Peng Wang, Qin Zhu, Rui Men, Ruize Gao, Shixuan Liu, Shuang Luo, Tianhao Li, Tianyi Tang, Wenbiao Yin, Xingzhang Ren, Xinyu Wang, Xinyu Zhang, Xuancheng Ren, Yang Fan, Yang Su, Yi-Chao Zhang, Yinger Zhang, Yu Wan, Yuqiong Liu, Zekun Wang, Zeyu

Cui, Zhenru Zhang, Zhipeng Zhou, and Zihan Qiu. Qwen3 technical report. 2025a. URL https://api.semanticscholar.org/CorpusID:278602855.

Chenxu Yang, Qingyi Si, Yongjie Duan, Zheliang Zhu, Chenyu Zhu, Zheng Lin, Li Cao, and Weiping Wang. Dynamic early exit in reasoning models. *arXiv preprint arXiv:2504.15895*, 2025b.

Edward Yeo, Yuxuan Tong, Xinyao Niu, Graham Neubig, and Xiang Yue. Demystifying long chain-of-thought reasoning in LLMs. In *ICLR 2025 Workshop on Navigating and Addressing Data Problems for Foundation Models*, 2025. URL https://openreview.net/forum?id=AgtQlhMQOV.

Jingyang Yi and Jiazheng Wang. Shorterbetter: Guiding reasoning models to find optimal inference length for efficient reasoning. *arXiv preprint arXiv:2504.21370*, 2025.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*, 2025.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. STar: Bootstrapping reasoning with reasoning. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=_3ELRdg2sgI.

Weihao Zeng, Yuzhen Huang, Qian Liu, Wei Liu, Keqing He, Zejun Ma, and Junxian He. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *arXiv preprint arXiv:2503.18892*, 2025.

Andrew Zhao, Yiran Wu, Yang Yue, Tong Wu, Quentin Xu, Matthieu Lin, Shenzhi Wang, Qingyun Wu, Zilong Zheng, and Gao Huang. Absolute zero: Reinforced self-play reasoning with zero data. *arXiv preprint arXiv:2505.03335*, 2025a.

Jiaxing Zhao, Xihan Wei, and Liefeng Bo. R1-omni: Explainable omni-multimodal emotion recognition with reinforcement learning. *arXiv preprint arXiv:2503.05379*, 2025b.

Xudong Zhu, Mohammad Mahdi Khalili, and Zhihui Zhu. Abstopk: Rethinking sparse autoencoders for bidirectional features. *arXiv preprint arXiv:2510.00404*, 2025.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

Yuxin Zuo, Kaiyan Zhang, Shang Qu, Li Sheng, Xuekai Zhu, Biqing Qi, Youbang Sun, Ganqu Cui, Ning Ding, and Bowen Zhou. Ttrl: Test-time reinforcement learning. *arXiv preprint arXiv:2504.16084*, 2025.

A   Implementation Details

For the $\mathcal{A}_{ft}$ models, we adopted a specialized prompting strategy that incorporates the explicit token `<think>` to elicit self-reflective reasoning and promote internal deliberation.

In contrast, for the $\mathcal{A}_{pt}$ models, we employed the same prompt template but omitted the `<think>` token. This design allowed us to isolate and assess the specific influence of `<think>` on eliciting reflective behaviors and its downstream impact, as Qwen models do not natively rely on such explicit triggers.

Unless otherwise noted, we set the maximum generation length to 32,784 tokens to support complex multi-step reasoning and avoid premature truncation. All experiments were conducted on a computing cluster equipped with 8 NVIDIA A5000 GPUs.

B   PCA Visualization of Self-Reflection States

To complement the quantitative linear-probe results in the main text, we apply PCA to hidden states extracted from Qwen2.5-1.5B and DeepSeek-R1-Distill-Qwen-1.5B. Figure 1 shows the PCA projection of the 15th-layer representations, while Figures 4 and 5 provide additional layer-wise visualizations for both models.

Across layers, reflection-inducing and non–reflection-inducing tokens form two elongated clusters that become increasingly separated along the first principal component. In very early layers there is still some overlap, but from middle layers onward a clear margin emerges, and by the deepest layers the two groups are well separated in both model families.

These PCA visualizations are consistent with the linear-probe results reported in the main text, providing a low-dimensional illustration of the same underlying geometric structure: self-reflection corresponds to a direction in representation space that becomes progressively more organized across depth.

C   LLM-as-a-Judge Pipeline for Identifying Self-Reflection

Judge model and labels. We use `Gemini-3-Flash` as the LLM judge with its default decoding configuration. For each example, the judge receives the full question and the full model response, and is instructed to return a JSON object with one of three labels: NO_REFLECTION, SURFACE_REFLECTION, or GENUINE_SELF_REFLECTION. For vector construction and reflection-rate analysis, we binarize these labels by treating GENUINE_SELF_REFLECTION as reflective and merging NO_REFLECTION and SURFACE_REFLECTION as non-reflective.

Judge validation.

To validate whether the LLM judge can identify self-reflection, we construct a small manually labeled validation set with 50 examples. The positive set contains 25 responses manually selected from `RLHFlow/Deepseek-MATH500-Test` that exhibit genuine self-reflection, while the negative set contains the first 25 examples from

Validation set	# Ex.	Run 1	Run 2	Run 3
MATH500-SR	25	25	25	24
FineWeb-Edu	25	25	25	25

Table 7: Judge validation over three repeated runs. Entries report the number of correct labels.

`HuggingFaceFW/fineweb-edu`, which are ordinary web-text passages and are labeled as non-reflective. We run the judge three times on each example using the same prompt and default `Gemini-3-Flash` configuration. As shown in Table 7, the judge correctly labels all negative examples in all runs and correctly labels 25, 25, and 24 of the 25 positive examples; the only error is one positive example labeled as `SURFACE_REFLECTION` in the third run. This lightweight validation suggests that the judge is robust for our use case.

Judge prompt.   The full prompt used for identifying self-reflection instances is shown below.

Figure 4: PCA visualization of hidden states from the Qwen2.5-1.5B model across 14 layers.

Figure 5: PCA visualization of hidden states from the DeepSeek-R1-Distill-Qwen-1.5B model across 14 layers.

Prompt for identifying self-reflection instances

```
You are evaluating whether a model response exhibits genuine self-reflection.

Definition:
Genuine self-reflection means that the model explicitly reconsiders, questions, checks,
backtracks on, or revises its earlier reasoning.  This must go beyond superficial discourse
markers such as "wait", "hold on", or "let me think".  A response counts as genuine
self-reflection only if there is evidence that the model revisits prior reasoning and
meaningfully changes, re-evaluates, or re-derives it.

Label the response as one of:
- NO_REFLECTION: no reflective behavior
- SURFACE_REFLECTION: contains reflection-like phrases, but no substantive reconsideration of
prior reasoning
- GENUINE_SELF_REFLECTION: explicitly revisits prior reasoning and meaningfully re-evaluates,
revises, or corrects it

Instructions:
1.  Read the full question and full response.
2.  Focus on behavior, not keywords alone.
3.  Do not classify as genuine self-reflection unless the response refers back to earlier
reasoning and performs a meaningful check, correction, backtrack, or revision.
4.  Prefer precision over recall.
5.  If the response is labeled as GENUINE_SELF_REFLECTION, identify all reflection occurrences
in the response, not just the first one.
6.  For each reflection occurrence, return the reflection phrase, the corresponding reflection
token, and a short evidence quote.
7.  If there is no genuine self-reflection, return an empty list for "reflection_instances".

Return JSON only:
{
"label":  "NO_REFLECTION | SURFACE_REFLECTION | GENUINE_SELF_REFLECTION",
"confidence":  0.0--1.0,
"reflection_instances":  [
{
"reflection_phrase":  "...",
"reflection_token":  "...",
"evidence_quote":  "..."
}
]
}

Question:
{question}

Response:
{response}
```

D   Broader Impact

This work provides an interpretable way to modulate self-reflection at inference time using an activation
direction and a scalar coefficient. This may help allocate reasoning effort more selectively, improving efficiency
on simple queries while preserving the option to increase deliberation on harder or higher-risk tasks.

However, reflection control also has dual-use risks. Suppressing reflection may reduce a model's tendency
to verify intermediate steps, reconsider mistakes, or perform informal safety checks, which is concerning

in domains such as medicine, law, and finance. Conversely, enhancing reflection may produce longer and more convincing rationalizations without necessarily improving correctness. Because activation-level steering changes the model's internal tendency to reflect in a way that may not be visible to users, it may also affect how users perceive model reliability. Therefore, reflection steering should be used conditionally and evaluated not only for accuracy and length, but also for calibration, robustness, and safety behavior.

E   Projected Steering as State-Dependent Adaptive Control

We further discuss why projected steering can be more effective than a fixed additive intervention. Recall that our intervention is defined as

$$\widehat{\boldsymbol{h}}^{(\ell)} = \boldsymbol{h}^{(\ell)} + \alpha \left\langle \boldsymbol{h}^{(\ell)}, \boldsymbol{v}^{(\ell)} \right\rangle \boldsymbol{v}^{(\ell)} = \boldsymbol{h}^{(\ell)} + \alpha_{\text{eff}}(\boldsymbol{h}) \boldsymbol{v}^{(\ell)}, \qquad \alpha_{\text{eff}}(\boldsymbol{h}) = \alpha \left\langle \boldsymbol{h}^{(\ell)}, \boldsymbol{v}^{(\ell)} \right\rangle. \qquad (6)$$

Thus, projected steering can be interpreted as a simple state-dependent adaptive intervention: the effective steering strength is not a fixed constant, but varies with the current hidden state.

This differs from additive steering, which applies the same perturbation $\alpha \boldsymbol{v}^{(\ell)}$ at every position regardless of whether the current token is reflection-relevant. In contrast, projected steering increases the intervention when the hidden state already contains a strong component along the reflection direction, and decreases it when this component is weak. In this sense, the scalar projection acts as a lightweight adaptive gain.

F   Representative Self-Reflection Example from Qwen2.5-7B

We show a representative self-reflection example from Qwen2.5-7B. The highlighted phrase marks the point where the model explicitly checks its own intermediate answer, which is the behavior labeled as self-reflection in our analysis.

Representative self-reflection example from Qwen2.5-7B

We need to convert the rectangular coordinate point $(0, 3)$ into polar coordinates. In rectangular coordinates, a point is written as (x, y), while in polar coordinates, the same point is written as (r, θ), where r is the distance from the origin and θ is the angle measured counterclockwise from the positive x-axis. The problem also tells us that the answer should satisfy $r > 0$ and $0 \leq \theta < 2\pi$, so we need to choose the standard polar representation with a positive radius and an angle in this interval.
For the point $(0, 3)$, we have
$$x = 0, \qquad y = 3.$$

The radius r is computed using
$$r = \sqrt{x^2 + y^2}.$$

Substituting $x = 0$ and $y = 3$, we get

$$r = \sqrt{0^2 + 3^2} = \sqrt{9} = 3.$$

So the radius is 3. This makes sense geometrically because the point $(0, 3)$ is exactly 3 units above the origin.
Now we need to find the angle θ. Usually, we can use

$$\tan \theta = \frac{y}{x}.$$

However, in this case $x = 0$, so $\frac{y}{x}$ is undefined. That means we should not blindly use the arctangent formula. Instead, we should think about the location of the point geometrically.
The point $(0, 3)$ has $x = 0$ and $y > 0$, so it lies on the positive y-axis. The angle from the positive x-axis to the positive y-axis is
$$\frac{\pi}{2}.$$

Therefore, the angle should be

$$\theta = \frac{\pi}{2}.$$

Let me check that carefully. If the polar coordinates are

$$\left(3, \frac{\pi}{2}\right),$$

then converting back to rectangular coordinates should give the original point. The conversion formulas are

$$x = r\cos\theta, \qquad y = r\sin\theta.$$

Using $r = 3$ and $\theta = \frac{\pi}{2}$, we get

$$x = 3\cos\frac{\pi}{2} = 3 \cdot 0 = 0,$$

and

$$y = 3\sin\frac{\pi}{2} = 3 \cdot 1 = 3.$$

So the rectangular coordinates become

$$(0, 3),$$

which exactly matches the original point.

Let me also make sure there is no issue with the required angle range. The problem requires

$$0 \le \theta < 2\pi.$$

The angle $\frac{\pi}{2}$ is in this interval, since it is greater than 0 and less than 2π. Also, the radius $r = 3$ is positive, so it satisfies $r > 0$.

Wait, another possible angle that gives an x-coordinate of 0 is $\frac{3\pi}{2}$, but that angle points downward along the negative y-axis. If we used

$$\theta = \frac{3\pi}{2},$$

then

$$x = 3\cos\frac{3\pi}{2} = 0,$$

but

$$y = 3\sin\frac{3\pi}{2} = -3.$$

That would give the point $(0, -3)$, not $(0, 3)$. So $\frac{3\pi}{2}$ is not correct for this point.

Thus, the correct angle is $\frac{\pi}{2}$, and the correct radius is 3. Therefore, the polar coordinates of the point $(0, 3)$ are

$$\boxed{\left(3, \frac{\pi}{2}\right)}.$$

G Additional Diagnostics

Figure 6a shows that the steering strength α provides direct control over reflection frequency. For the fine-tuned model, reflection is already frequent at $\alpha = 0$; positive steering further increases it, while negative steering reduces but does not fully remove it. For the pretrained model, reflection is rare without steering, but positive α can substantially elicit it. This supports the view that self-reflection is a latent behavior that can be continuously modulated by the learned direction.

Figure 6b tests whether our linear separability result is driven by simple surface-level confounds. On DeepSeek-R1-7B, probes for question-vs.-statement and long-vs.-short contrasts remain close to chance across layers, unlike the near-perfect self-reflection probe. This suggests that the self-reflection direction

(a) Reflection rate under different steering strengths.

(b) Linear-probe accuracy for control contrasts.

Figure 6: Additional diagnostic analyses for self-reflection steering. **(a)** Reflection rate as a function of steering strength α for DeepSeek-R1-Distill-Qwen-1.5B and Qwen2.5-1.5B. **(b)** Linear-probe test accuracy on DeepSeek-R1-7B for two generic control contrasts, question vs. statement and long vs. short, across layers. The question vs. statement contrast uses 100 examples and probes the final-token activation of each sentence. The long vs. short contrast uses another 100 examples and probes the final-token activation of each response, with long responses defined as generations longer than 4K tokens and short responses as the remaining generations.

is not merely capturing generic syntax or response length, but a more specific latent state associated with reflective revision.