Automatically Composing Representation Transformations as a Means for Generalization

Michael B. Chang
Electrical Engineering and Computer Science
University of California, Berkeley, USA
mbchang@berkeley.edu

Abhishek Gupta
Electrical Engineering and Computer Science
University of California, Berkeley, USA
abhigupta@berkeley.edu

Sergey Levine
Electrical Engineering and Computer Science
University of California, Berkeley
svlevine@eecs.berkeley.edu

Thomas L. Griffiths
Psychology and Cognitive Science
Princeton University, USA
tomg@princeton.edu

Abstract

A generally intelligent learner should generalize to more complex tasks than it has previously encountered, but the two common paradigms in machine learning – either training a separate learner per task or training a single learner for all tasks – both have difficulty with such generalization because they do not leverage the compositional structure of the task distribution. This paper introduces the *compositional problem graph* as a broadly applicable formalism to relate tasks of different complexity in terms of problems with shared subproblems. We propose the *compositional generalization problem* for measuring how readily old knowledge can be reused and hence built upon. As a first step for tackling compositional generalization, we introduce the *compositional recursive learner*, a domain-general framework for learning algorithmic procedures for composing representation transformations, producing a learner that reasons about what computation to execute by making analogies to previously seen problems. We show on a symbolic and a high-dimensional domain that our compositional approach can generalize to more complex problems than the learner has previously encountered, whereas baselines that are not explicitly compositional do not.

1 Introduction

This paper seeks to tackle the question of how to build machines that leverage prior experience to solve more complex problems than they have previously encountered. How does a learner represent prior experience? How does a learner apply what it has learned to solve new problems? Motivated by these questions, this paper aims to formalize the idea of, as well as to develop an understanding of the machinery for, *compositional generalization* in problems that exhibit compositional structure. The solutions for such problems can be found by composing in sequence a small set of reusable partial solutions, each of which tackles a subproblem of a larger problem. The central contributions of this paper are to frame the shared structure across multiple tasks in terms of a *compositional problem graph*, propose *compositional generalization* as an evaluation scheme to test the degree a learner can apply previously learned knowledge to solve new problems, and introduce the *compositional recursive learner*, a domain-general framework[1] for sequentially composing representation transformations that each solve a subproblem of a larger problem.

The key to our approach is recasting the problem of generalization as a problem of learning algorithmic procedures over representation transformations. A solution to a (sub)problem is a transformation between its input and output representations, and a solution to a larger problem composes

---

[1]https://github.com/mbchang/crl

these subsolutions together. Therefore, representing and leveraging prior problem-solving experience amounts to learning a set of reusable primitive transformations and their means of composition that reflect the structural properties of the problem distribution.

This paper introduces the compositional recursive learner (CRL), a framework for learning both these transformations and their composition together with sparse supervision, taking a step beyond other approaches that have assumed either pre-specified transformation or composition rules (Sec. 5). CRL learns a modular recursive program that iteratively re-represents the input representation into more familiar representations it knows how to compute with. In this framework, a transformation between representations is encapsulated into a *computational module*, and the overall program is the sequential combination of the inputs and outputs of these modules, whose application are decided by a *controller*.

What sort of training scheme would encourage the spontaneous specialization of the modules around the compositional structure of the problem distribution? First, exposing the learner to a diverse distribution of compositional problems would help it pattern-match across problems to distill out common functionality that it can capture in its modules for future use. Second, constraining the model class of these modules guides them to capture the structure of the problem distribution; without such constraints the learner can easily overfit to the empirical training distribution and fail to generalize to harder problems in a combinatorially large problem space. Third, training the learner with a curriculum encourages the learner to build off old solutions to solve new problems by re-representing the new problem into one it knows how to solve, rather than learning from scratch.

How should the learner learn to use these modules to exploit the compositional structure of the problem distribution? The application of a sequence of modules can be likened to the execution trace of the program that CRL automatically constructs, where a computation is the application of a module to the output of a previous computation. The automatic construction of the program can be formulated as the solution to a sequential decision-making problem in a meta-level Markov decision process (MDP) (Hay et al., 2014), where the state space is the learner's internal states of computation and the action space is the set of modules. Under this formulation, the controller can implement loops and recursion, and it can also decide on which part of the current state of computation to apply a module.

Our experiments on solving multilingual arithmetic problems and recognizing spatially transformed MNIST digits show that the above proposed training scheme prescribes a type of *reformulation*: re-representing a new problem in terms of other problems by implicitly making an *analogy* between their solutions. We also show that our *meta-reasoning* approach for deciding what modules to execute achieves better generalization to more complex problems than monolithic learners that are not explicitly compositional.

2 COMPOSITIONAL GENERALIZATION

> *Solving a problem simply means representing it so as to make the solution transparent.*

(SIMON, 1988)

Humans navigate foreign cities and understand novel conversations despite only observing a tiny fraction of the true distribution of the world. Perhaps they can extrapolate in this way because the world contains compositional structure, such that solving a novel problem is possible by composing previously learned partial solutions in a novel way to fit the context.

With this perspective, we propose the concept of *compositional generalization*, adding to the standard learning theory paradigm additional assumptions that are tailored for studying generalization in the compositional context. The key assumption of compositional generalization is that harder problems are made of easier problems. The problems from the training and test sets share the same primitive subproblems, but differ in the manner and complexity with which these subproblems are combined. Therefore, problems in the test set can be solved by combining solutions learned from the training set in novel ways.

Definition. Let a *problem* P be a pair (X_{in}, X_{out}), where X_{in} and X_{out} are random variables that respectively correspond to the input and output representations of the problem. Let the distribution

of X_{in} be r_{in} and the distribution of X_{out} be r_{out}. To solve a particular problem $P = p$ is to transform $X_{in} = x_{in}$ into $X_{out} = x_{out}$. A composite problem $p_a = p_b \circ p_c$ is that for which it is possible to solve by first solving p_c and then solving p_b with the output of p_c as input. p_b and p_c are subproblems with respect to p_a. The space of compositional problems form a *compositional problem graph*, whose nodes are the representation distributions r. A problem is described as pair of nodes between which the learner must learn to construct an edge or a path to transform between the two representations.

Characteristics. First, there are many ways in which a problem can be solved. For example, translating an English expression to a Spanish one can be solved directly by learning such a transformation, or a learner could make an *analogy* with other problems by first translating English to French, and then French to Spanish as intermediate subproblems. Second, sometimes a useful (although not only) way to solve a problem is indicated by the *recursive* structure of the problem itself: solving the arithmetic expression $3 + 4 \times 7$ modulo 10 can be decomposed by first solving the subproblem $4 \times 7 = 8$ and then $3 + 8 = 1$. Third, because a problem is just an (input, output) pair, standard problems in machine learning fit into this broadly applicable framework. For example, for a supervised classification problem, the input representation can be an image and the output representation a label, and intermediate subproblems can be transforming some intermediate representations to other intermediate representations. Sec. 4 demonstrates CRL on all three of the above examples.

Broad Applicability. Problems in supervised, unsupervised, and reinforcement learning can all be viewed under the framework of transformations between representations. What we gain from the compositional problem graph perspective is a methodological way to relate together different problems of various forms and complexity, which is especially useful in a lifelong learning setting: the knowledge required to solve one problem is composed of the knowledge required to solve subproblems seen in the past in the context of different problems. For example, we can view latent variable reinforcement learning architectures such as (Ha & Schmidhuber, 2018; Nair et al., 2018) as simultaneously solving an image reconstruction problem and an action prediction problem, both of which share the same subproblem of transforming a visual observation into a latent representation. Lifelong learning, then, can be formulated as continuing to make more connections between nodes in the compositional problem graph, gradually expanding the frontier of nodes explored. Sec. 4 describes how CRL takes advantage of this compositional formulation in a multi-task zero-shot generalization setup to solve new problems by re-using computations learned from solving past problems.

Evaluation. To evaluate a learner's capacity for compositional generalization, we introduce two challenges. The first is to generalize to problems with different subproblem combinations from what the learner has seen. The second is to generalize to problems with longer subproblems combinations than the learner has seen. Evaluating a learner's capability for compositional generalization is one way to measure how readily old knowledge can be reused and hence built upon.

3 A LEARNER THAT PROGRAMS ITSELF

This paper departs from the popular *representation-centric* view of knowledge (Bengio et al., 2013) and instead adopts a *computation-centric* view of knowledge: our goal is to encapsulate useful functionality shared across tasks into specialized *computational modules* – atomic function operators that perform transformations between representations. This section introduces the compositional recursive learner (CRL), a framework for training modules to capture primitive subproblems and for composing together these modules as subproblem solutions to form a path between nodes of the compositional problem graph.

3.1 COMPOSITIONAL RECURSIVE LEARNER

The CRL framework consists of a controller π, a set of modules $m \in M$, and an evaluator E. Training CRL on a diverse compositional problem distribution produces a modular recursive program that is trained to transform the input X_{in} into its output X_{out}, the corresponding samples of which are drawn from pairs of nodes in the compositional problem graph. In this program, the controller looks at the current state x_i of the program and chooses a module m to apply to the state. The evaluator executes the module on that state to produce the next state x_{i+1} of the program. X_{in} is the initial state of the program, $\hat{X}_{out}$ is the last, and the intermediate states X_i of the execution trace

Figure 1: **Compositional recursive learner (CRL):** *top-left*: CRL is a symbiotic relationship between a controller and evaluator: the controller selects a function m given an intermediate representation x and the evaluator applies m on x to create a new representation. *bottom-left*: CRL learns dynamically learns the structure of a program customized for its problem, and this program can be viewed as a finite state machine. *right*: A series of computations in the program is equivalent to a traversal through the Meta-MDP, where functions can be reused across different stages of computation, allowing for recursive computation.

correspond to the other representations produced and consumed by the modules. The controller can choose to re-use modules across different program executions to solve different problems, making it straightforward to re-use computation learned from solving other problems to solve the current one. The controller can also choose to reuse modules several times within the same program execution, which produces recursive behavior.

3.2 DECIDING WHICH COMPUTATIONS TO EXECUTE

The sequential decision problem that the controller solves can be formalized as a meta-level Markov decision process (meta-MDP) (Hay et al., 2014), whose state space corresponds to the intermediate states of computation X, whose action space corresponds to the modules M, and whose transition model corresponds to the evaluator E. The symbiotic relationship among these components is shown in Fig. 1. In the *bounded* version of CRL (Sec. 4.2), the meta-MDP has a finite horizon whose length is determined by the complexity of the current problem. In the *unbounded* version of CRL (Sec. 4.1), the program itself determines when to halt when the controller selects the the HALT signal. When the program halts, in both versions the current state of computation is produced as output $\hat{x}_{out}$, and CRL receives a terminal reward that reflects how $\hat{x}_{out}$ matches the desired output x_{out}. The unbounded CRL also incurs a cost for every computation it executes to encourage it to customize its complexity to the problem.

Note the following key characteristics of CRL. First, unlike standard reinforcement learning setups, the state space and action space can vary in dimensionality across and within episodes because CRL trains on problems of different complexity, reducing more complex problems to simpler ones (Sec. 4.1). Second, because the meta-MDP is internal to CRL, the controller shapes the meta-MDP by choosing which modules get trained and the meta-MDP in turn shapes the controller through its non-stationary state-distribution, action-distribution, and transition function. Thus CRL simultaneously designs and solves reinforcement learning problems "in its own mind," whose dynamics depend just as much on the intrinsic complexity of the problem as well as the current problem-solving capabilities of CRL.

3.3 Making Analogies in the Compositional Problem Graph

The solution that we want CRL to discover lies between two extremes, both of which have their own drawbacks. One extreme is where CRL learns a module specialized for every pair of nodes in the compositional problem graph, and the other is where CRL only learns one module for all pairs of nodes. Both extremes yield a horizon-one meta-MDP and are undesirable for compositional generalization in a lifelong learner: the former does not re-use past knowledge and the latter cannot flexibly continuously learn without suffering from negative transfer.

We want to encourage the modules to capture the most primitive subproblems, such that they can be composed as atomic computations for other problems. In our experiments, we use domain knowledge to restrict the representation vocabulary and the function class of the modules. Constraining each module to learn only a simple transformation gives them a local view on the global problem, thereby forcing the controller to compose the modules together to generalize. Because the the space of subproblem compositions is combinatorially large, we use a curriculum to encourage solutions for the simpler subproblems to converge somewhat before introducing more complex problems, for which CRL can learn to solve by composing together the modules that had been trained on simpler problems. Lastly, to encourage the controller to generalize to new node combinations it has not seen, we train on a diverse distribution of compositional problems, such that the controller does not overfit to any one problem. This encourages controller to make analogies between problems during training by re-using partial solutions learned while solving other problems. Our experiments show that this analogy-making ability helps with compositional generalization because the controller solves new or more complex subproblem combinations by re-using modules that it learned during training.

4 Experiments

To evaluate compositional generalization, we select disjoint subsets of node pairs for training and evaluating the learner. Evaluating on problems distinct from those in training tests the learner's ability to *apply* what it has learned, rather than directly performing a simple nearest-neighbor lookup. To demonstrate the broad applicability of the compositional graph, we consider the structured symbolic domain of multilingual arithmetic and the underconstrained and high-dimensional domain of transformed-MNIST classification. We compare CRL with "monolithic" architectures that directly map input to output without explicit modularity.

In our experiments, the controller and modules begin as randomly initialized neural networks. After the program halts, a loss is computed by comparing the current state of computation with the desired output. The loss is backpropagated through the modules, which are trained with Adam (Kingma & Ba, 2014). The controller receives a sparse reward derived from the loss at the end of the computation, and a small cost for each computational step. The model is trained with proximal policy optimization (Schulman et al., 2017).

4.1 Multilingual Arithmetic

This experiment evaluates the unbounded CRL in a multi-objective, variable-length input, symbolic reasoning multi-task setting. A task is to simplify an arithmetic expression expressed in a *source* language, encoded as variable-length sequences of one-hot tokens, and produce the answer modulo 10 in a given *target* language. To evaluate compositional generalization, we test whether, after having trained on 46200 examples of 2, 3, 4, 5-length expressions ($2.76 \cdot 10^{-4}$ of the training distribution) involving 20 of the $5 \times 5 = 25$ pairs of five languages, the learner can generalize to 5-length and 10-length expressions involving the other five held-out language pairs (problem space: $4.92 \cdot 10^{15}$ problems). To handle the multiple target languages, the CRL controller receives a one-hot token for the target language at every computational step additional to the arithmetic expression. The CRL modules consist of reducers and translators, which do not know the target language and so can only make local progress on the global problem. Reducers transform a consecutive window of three tokens into one token, and translators transform all tokens in a sequence by the same transformation. The CRL controller also selects where in the arithmetic expression to apply a reducer. We trained by gradually increasing the complexity of arithmetic expressions from length two to length five.

Quantitive results in Fig. 2 show that CRL achieves significantly better compositional generalization than an RNN baseline (Cho et al., 2014) trained to directly map the expression to its answer, even

(a) Training   (b) Different subproblem combinations   (c) More complex subproblem combinations

Figure 2: **Multilingual Arithmetic (Quantitative).** CRL generalizes significantly better than the RNN, which, even with ten times more data, does not generalize to 10-length multilingual arithmetic expressions. Pretraining the RNN on domain-specific auxiliary tasks does not help the 10-length case, highlighting a limitation of using monolithic learners for compositional problems. By comparing CRL with a version trained without a curriculum ("No Curr": blue), we see the benefit of slowly growing the complexity of problems throughout training, although this benefit does not transfer to the RNN. The vertical black dashed line indicates at which point all the training data has been added when CRL is trained with a curriculum (red). The initial consistent rise of the red training curve before this point shows CRL exhibits forward transfer (Lopez-Paz et al., 2017) to expressions of longer length. Generalization becomes apparent only after a million iterations after all the training data has been added. **(b, c)** only show accuracy on the expressions with the maximum length of those added so far to the curriculum. "1e4" and "1e5" correspond to the order of magnitude of the number of samples in the dataset, of which 70% are used for training. 10, 50, and 90 percentiles are shown over 6 runs.

Figure 3: **Multilingual Arithmetic (Qualitative).** A randomly selected execution trace for generalizing to length-10 expressions. The input is $0 - 6 + 1 + 7 \times 3 \times 6 - 3 + 7 - 7 \times 7$ expressed in Pig Latin. The desired output is *seis*, which is the value of the expression, 6, expressed in Spanish. Each step of computation is labeled A - L, which is reflected in the finite state machine view on the right. The purple modules are reducers and the pink modules are translators. The input to a module is highlighted and the output of the module is underlined. The controller learns order of operations. The reducer m_9 always reduces to numerals and reducer m_{10} always reduces to English terms. The task-agnostic nature of the modules forces them to learn transformations that the controller would commonly reuse across problems. Even if the problem may not be compositionally structured, such as translating Pig Latin to Spanish, CRL learns to design a compositional solution (Pig Latin to Numerals to Spanish) from previous experience (Pig Latin to Numerals and Numerals to Spanish) in order to generalize: it first reduces the Pig Latin expression to a numerical evaluation, and then translates that to its Spanish representation using the translator m_6. Note that all of this computation is happening internally to the learner, which computes on softmax distributions over the vocabulary; for visualization we show the token of the distribution with maximum probability.

when the RNN has been pretrained or receives 10x more data. Fig. 8 shows that CRL achieves about 60% accuracy for extrapolating to 100-term problems (problem space: $4.29 \cdot 10^{148}$).

The curriculum-based training scheme encourages CRL to designs its own edges and paths to connect nodes in the compositional problem graph, solving harder problems with the solutions from simpler ones. It also encourages its internal representations to mirror the external representations it observes in the problem distribution, even though it has no direct supervision to do so. However, while this is often the case, qualitative results in Fig. 3 show that CRL also comes up with its own *internal* language – hybrid representations that mix different external representations together – to construct compositional solutions during for novel problems. Rather than learn translators and reducers that are specific to single input and single output language pair as we had expected, the modules, possibly due to their nonlinear nature, tended to learn operations specific to the output language only.

Figure 4: **Left:** For multilingual arithmetic, blue denotes the language pairs for training and red denotes the language pairs helf out for evaluation in Fig 2b,c. **Center:** For transformed MNIST classification, blue denotes the length-2 transformation combinations that produced the input for training, red denotes the length-2 transformation combinations held out for evaluation. Not shown are the more complex length-3 transformation combinations (scale then rotate then translate) we also tested on. **Right:** For transformed MNIST classification, each learner performs better than the others in a different metric: the CNN performs best on the training subproblem combinations, the STN on different subproblem combinations of the same length as training, and CRL on longer subproblem combinations than training. Whereas CRL performs comparably with the others in the former two metrics, the $\sim 40\%$ gap between CRL and the others for more complex image transformations is significant.

4.2 IMAGE TRANSFORMATIONS

This experiment demonstrates the bounded CRL in a single-objective, latent-structured, high-dimensional multi-task setting. A task is to classify an MNIST digit, where the MNIST digit has been randomly translated (left, right, up, down), rotated (left, right), and scaled (small, big). Suppose CRL has knowledge of what untransformed MNIST digits look like; is it possible that CRL can learn to compose appropriate spatial affine transformations in sequence to convert the transformed MNIST digit into a "canonical" one, such that it can use a pre-trained classifier to classify it? To reformulate a scenario to one that is more familar is characteristic of compositional generalization humans: humans view an object at different angles yet understand it is the same object; they may have an accustomed route to work, but can adapt to a detour if the route is blocked. To evaluate compositional generalization, we test whether, having trained on images produced by combinations of two spatial transformations, CRL can can generalize to different length-2 combinations as well as length-3 combinations. A challenge in this domain is that the compositional structure is latent, rather than apparent in the input for the learner to exploit.

CRL is initialized with four types of modules: a Spatial Transformer Network (STN) (Jaderberg et al., 2015) parametrized to only rotate, an STN that only scales, an STN that only translates, and an identity function. All modules are initialized to perform the identity transformation, such that symmetry breaking (and their eventual specialization) is due to the stochasticity of the controller.

Quantitative results in Fig. 4 show that CRL achieves significantly better compositional generalization than both finetuning the convolutional neural network (Springenberg et al., 2014) pretrained classifier and training an affine-STN as a pre-processor to the classifier. Both baselines perform better than CRL on the training set. Note that in Fig. 5 the sequence of transformations CRL performs are not necessarily the reverse of those that generated the original input.

5 RELATED WORK

Our work is one of a small growing body of work bridging reformulation and metareasoning with deep learning; our emphasis on learning algorithmic procedures as a means for generalization departs from work that seeks to learn shared representations; we show the benefit of hierarchical learning in low data regimes; we demonstrate a fully disentangled self-organizing neural network where both the transformations and the means of their combination are learned with sparse supervision,

Figure 5: **Image Transformations:** CRL reasonably applies a sequence of modules to transform a transformed MNIST digit into canonical position, even for digits that have been transformed different and longer compositions of generative transformations. Consider (d): the generative transformations were "scale big" then "translate right," so the correct inversion should be "translate left" then "scale small." However, CRL chose to equivalently "scale small" and then "translate left." m_0 is constrained to output the sine and cosine of a rotation angle, m_1 is constrained to output the scaling factor, and m_2 through $m_1 3$ are constrained to output spatial translations. Some modules like m_2 and m_6 learn to translate up, some like m_3 and m_{10} learn to translate down, some like m_7 learn to shift right, and some like m_{13} learn to shift left. CRL also creatively uses m_0 to scale, as in (e) and (f), even though its original parametrization of outputting sine and cosine is biased towards rotation.

a step beyond prior work. We hope this paper provides a point of unification among these areas through which further connections can be strengthened.

Reformulation and cognitive development: *Reformulation*, or re-representing a problem to make it easier to solve, dates back at least to the 1960s (Holte & Choueiry, 2003; Simon, 1969; Anderson, 1990), but is relatively unexplored in deep learning. CRL's ability to dynamically re-represent a new problem in the language of previous problems is an initial step towards bridging the idea of re-representation with deep learning. How the primitive transformations for such re-representation are acquired relates to the study of representational change in cognitive science. The simultaneous optimization over the the continuous function parameters and their discrete compositional structure in CRL can be seen as an attempt to build a learner that emulates in a limited sense the interplay between abstract and concrete knowledge that is hypothesized to characterize cognitive development: abstract structural priors serve as a scaffolding within which concrete, domain-specific learning takes place (Spelke, 1990; Pinker, 1994), but domain-specific learning about the continuous semantics of the world can also provide feedback to update the more discrete structural priors (Gopnik & Wellman, 2012; Carey, 2015).

Combinatorial generalization through metareasoning: To solve out-of-distribution problems, both metalearning and metareasoning approaches assume that the new problem shares regularities

with previous problems but take different perspectives on how to exploit those regularities. The metalearning framework (Thrun & Pratt, 2012; Schmidhuber, 1987) seeks to learn a learner that can learn quickly on the new problem. CRL departs from this paradigm by taking a metareasoning approach (Russell & Wefald, 1991; Hay et al., 2014), where the learner reasons about its own knowledge and computations to solve the new problem. Much recent metalearning work (Finn et al., 2017; Nichol et al., 2018; Ravi & Larochelle, 2016; Andrychowicz et al., 2016; Grant et al., 2018; Mishra et al., 2018; Lake et al., 2015; Frans et al., 2017; Gupta et al., 2018b;a; Srinivas et al., 2018) focuses on domains where achieving zero-shot generalization is unclear and follow a common paradigm which assumes that the shared representation of monolithic architectures (with the exception of concurrent work (Alet et al., 2018)) can be shaped by the diversity of tasks in the training distribution as good initializations for future learning. But for combinatorial generalization, monolithic architectures may itself be a barrier to zero-shot generalization: our experiments suggest that such architectures are significantly less data efficient than compositional modular approaches. In these cases it may be possible to extract enough structure during training to generalize out-of-distribution without learning at all. Indeed, the monolithic/shared-representation paradigm can be improved in two complementary ways. The first, advocated in contemporaneous work (Battaglia et al., 2018), focuses on learning more structured representations of entities and relations with graph networks. The second, the focus of this paper, focuses on learning structured algorithmic procedures that can implement recursion and composition of partial solutions that operate on state representations. Instead of learning an algorithm to learn, the learner can learn an algorithm to reason: casting the generalization problem as an algorithm design problem is a growing hypothesis for the mechanism with which humans can generalize to new scenarios (Griffiths et al., 2015; Callaway et al., 2017; Lieder et al., 2017). Our work is one of a small but growing community (Hamrick et al., 2017; Graves, 2016; Oh et al., 2017) linking metareasoning with deep learning.

Compositional neural program induction: Compositional approaches (as opposed to memory-augmented (Graves et al., 2014; Sukhbaatar et al., 2015; Joulin & Mikolov, 2015; Grefenstette et al., 2015; Kurach et al., 2015; Andrychowicz et al., 2016; Graves et al., 2016) or monolithic (Zaremba & Sutskever, 2014; Kaiser & Sutskever, 2015) approaches for learning programs) to the challenge of discovering reusable primitive transformations and their means of composition generally fall into two categories. The first assumes pre-specified transformations and learns the structure (from dense supervision on execution traces to sparse-rewards) (Reed & De Freitas, 2015; Cai et al., 2017; Xu et al., 2017; Chen et al., 2017; Ganin et al., 2018; Bunel et al., 2018; Feser et al., 2016; Džeroski et al., 2001; Zaremba et al., 2016). The second learns the transformations but pre-specifies the structure (Devin et al., 2017; Andreas et al., 2016; Riedel et al., 2016). These approaches are respectively analogous to our hardcoded-functions and hardcoded-controller ablations in Fig. 6. (Zaremba & Sutskever, 2014) noted the challenge of learning the individual operators and how to combine them; our paper can be considered a candidate to address this challenge. The closest work in this respect to ours is (Gaunt et al., 2016) which assumes a differentiable interpreter grounded in source code; we take a different perspective of learning algorithms through re-representations, which enables our method to adapt on-line to new problem classes. Our perspective comes with its own challenges; without grounding in source code, the concept of a `for`-loop is implicit in the controller, rather than an explicit concept that can exist independently of the data, which is desirable for constructing more complex programs.

Self-organizing learners, disentanglement, hierarchical learning: Research on self-organizing learners (Schmidhuber, 1987; Dechter et al., 2013; Schmidhuber, 2009; 2012) has so far been relatively theoeretical; CRL is a synthesis of recent work in disentanglement and hierarchical learning that attempts to bring this old idea closer to reality. Just as the motivation behind disentangled representations (Whitney et al., 2016; Kulkarni et al., 2015; Chen et al., 2016; Thomas et al., 2017; Bengio et al., 2013) is to uncover the latent factors of variation, the motivation behind disentangled programs is to uncover the latent organization of a task. Finding such structure is important for generalization because it shields various parts of the representation or program from changing when one component changes. For example, (Hinton et al., 2018; Rosenbaum et al., 2018; Fernando et al., 2017) have begun to examine how to *route* through an fixed architecture to encapsulate computation, but the hard limitation that prevents fixed architectures from scaling to problems with complexity beyond that which they were trained is their limited number of computation steps. A parallel line of work runs through the hierarchical reinforcement learning (HRL) literature (Barto & Mahadevan, 2003), with recent work (Bacon et al., 2017; Kulkarni et al., 2016; Frans et al., 2017; Vezhnevets et al., 2017; Nachum et al., 2018) attempting to learn both lower-level policies as well

as a higher-level policy that calls them. Several works have investigated the conditions in which hierarchy is useful for humans (Botvinick et al., 2009; Solway et al., 2014; Sanborn et al., 2018); our experiments show that the hierarchical structure of CRL is more useful than the flat structure of the RNN for low-data compositional problems. The fast-weights (FW) literature (Schmidhuber, 1992; Ba et al., 2016) is also related to the idea of selecting different weights at different steps of computation, but with a different motivation for learning context-dependent associative memory (Hopfield, 1982; Willshaw et al., 1969; Kohonen, 1972; Anderson & Hinton, 2014; Ha et al., 2016), with the exception of (Schlag & Schmidhuber, 2017). By combining adaptive computation time (Graves, 2016) with routing, CRL synthesizes all of these above ideas by dynamically composing learned reusable subnetworks together as fully disentangled programs, taking a step towards making the topology of the computation graph self-organizing as well.

6 DISCUSSION

This paper sought to tackle the question of how to build machines that leverage prior experience to solve more complex problems than they have seen. This paper makes three contributions towards the solution. First, we formalized the compositional problem graph as a language for studying compositionally-structured problems of different complexity that can be applied on various problems in machine learning. Second, we introduced the compositional generalization evaluation scheme for measuring how readily old knowledge can be reused and hence built upon. Third, we presented the compositional recursive learner, a domain-general framework for learning a set of reusable primitive transformations and their means of composition that reflect the structural properties of the problem distribution.

Griffiths et al. (2019) argued that the efficient use cognitive resources in humans may also explain their ability to generalize, and this paper provides evidence that reasoning about what computation to execute by making analogies to previously seen problems achieves significantly higher compositional generalization than non-compositional monolithic learners. Because problems in supervised, unsupervised, and reinforcement learning can all be expressed under the framework of transformations between representations in the compositional problem graph, we hope that our work motivates further research for tackling the compositional generalization problem in many other domains to accelerate the long-range generalization capabilities that are characteristic of general-purpose learning machines.

ACKNOWLEDGMENTS

The authors would like to thank Alyosha Efros, Dinesh Jayaraman, Pulkit Agrawal, Jason Peng, Erin Grant, Rachit Dubey, Thanard Kurutach, Parsa Mahmoudieh, Aravind Srinivas, Fred Callaway, Justin Fu, Ashvin Nair, Marvin Zhang, Shubham Tulsiani, Peter Battaglia, Jessica Hamrick, Rishabh Singh, Feras Saad, Kai-I Shan, and others in the Berkeley Artificial Intelligence Research Lab for helpful feedback, discussions, and support. The authors are grateful for computing support from Amazon, NVIDIA, and Google. This work was supported in part by the Berkeley EECS Department Fellowship for first-year Ph.D. students, travel funding from Bloomsbury AI, contract number FA8650-18-2-7832 from the Defence Advanced Research Projects Agency (DARPA) under the Lifelong Learning Machines program, contract number FA9550-18-1-0077 from the Air Force Office of Scientific Research (AFOSR), and the National Science Foundation (NSF) Graduate Research Fellowship Program. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of DARPA, AFOSR, or the NSF.

REFERENCES

Ferran Alet, Tomás Lozano-Pérez, and Leslie P Kaelbling. Modular meta-learning. *arXiv preprint arXiv:1806.10166*, 2018.

James A Anderson and Geoffrey E Hinton. Models of information processing in the brain. In *Parallel models of associative memory*, pp. 33–74. Psychology Press, 2014.

John Robert Anderson. The adaptive character of thought. chapter 5, pp. 191–230. Psychology Press, 1990.

Jacob Andreas, Marcus Rohrbach, Trevor Darrell, and Dan Klein. Neural module networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 39–48, 2016.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in Neural Information Processing Systems*, pp. 3981–3989, 2016.

Jimmy Ba, Geoffrey E Hinton, Volodymyr Mnih, Joel Z Leibo, and Catalin Ionescu. Using fast weights to attend to the recent past. In *Advances in Neural Information Processing Systems*, pp. 4331–4339, 2016.

Pierre-Luc Bacon, Jean Harb, and Doina Precup. The option-critic architecture. In *AAAI*, pp. 1726–1734, 2017.

Andrew G Barto and Sridhar Mahadevan. Recent advances in hierarchical reinforcement learning. *Discrete event dynamic systems*, 13(1-2):41–77, 2003.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

Matthew M Botvinick, Yael Niv, and Andrew C Barto. Hierarchically organized behavior and its neural foundations: a reinforcement learning perspective. *Cognition*, 113(3):262–280, 2009.

Rudy Bunel, Matthew Hausknecht, Jacob Devlin, Rishabh Singh, and Pushmeet Kohli. Leveraging grammar and reinforcement learning for neural program synthesis. *arXiv preprint arXiv:1805.04276*, 2018.

Jonathon Cai, Richard Shin, and Dawn Song. Making neural programming architectures generalize via recursion. *arXiv preprint arXiv:1704.06611*, 2017.

Frederick Callaway, Falk Lieder, Paul Krueger, and Thomas L Griffiths. Mouselab-mdp: A new paradigm for tracing how people plan. 2017.

Susan Carey. 15 why theories of concepts should not ignore the problem of acquisition. *The conceptual mind: New directions in the study of concepts*, pp. 415, 2015.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Advances in Neural Information Processing Systems*, pp. 2172–2180, 2016.

Xinyun Chen, Chang Liu, and Dawn Song. Learning neural programs to parse programs. *arXiv preprint arXiv:1706.01284*, 2017.

Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Eyal Dechter, Jonathan Malmaud, Ryan P Adams, and Joshua B Tenenbaum. Bootstrap learning via modular concept discovery. In *IJCAI*, pp. 1302–1309, 2013.

Coline Devin, Abhishek Gupta, Trevor Darrell, Pieter Abbeel, and Sergey Levine. Learning modular neural network policies for multi-task and multi-robot transfer. In *Robotics and Automation (ICRA), 2017 IEEE International Conference on*, pp. 2169–2176. IEEE, 2017.

Sašo Džeroski, Luc De Raedt, and Kurt Driessens. Relational reinforcement learning. *Machine learning*, 43(1-2):7–52, 2001.

SM Ali Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, Geoffrey E Hinton, et al. Attend, infer, repeat: Fast scene understanding with generative models. In *Advances in Neural Information Processing Systems*, pp. 3225–3233, 2016.

Chrisantha Fernando, Dylan Banarse, Charles Blundell, Yori Zwols, David Ha, Andrei A Rusu, Alexander Pritzel, and Daan Wierstra. Pathnet: Evolution channels gradient descent in super neural networks. *arXiv preprint arXiv:1701.08734*, 2017.

John K Feser, Marc Brockschmidt, Alexander L Gaunt, and Daniel Tarlow. Differentiable functional program interpreters. *arXiv preprint arXiv:1611.01988*, 2016.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. *arXiv preprint arXiv:1703.03400*, 2017.

Kevin Frans, Jonathan Ho, Xi Chen, Pieter Abbeel, and John Schulman. Meta learning shared hierarchies. *arXiv preprint arXiv:1710.09767*, 2017.

Yaroslav Ganin, Tejas Kulkarni, Igor Babuschkin, S.M. Ali Eslami, and Orial Vinyals. Synthesizing programs for images using reinforced adversarial learning. *arXiv preprint arXiv:1804.01118*, 2018.

Alexander L Gaunt, Marc Brockschmidt, Nate Kushman, and Daniel Tarlow. Differentiable programs with neural libraries. *arXiv preprint arXiv:1611.02109*, 2016.

Alison Gopnik and Henry M Wellman. Reconstructing constructivism: Causal models, bayesian learning mechanisms, and the theory theory. *Psychological bulletin*, 138(6):1085, 2012.

Erin Grant, Chelsea Finn, Sergey Levine, Trevor Darrell, and Thomas Griffiths. Recasting gradient-based meta-learning as hierarchical bayes. *arXiv preprint arXiv:1801.08930*, 2018.

Alex Graves. Adaptive computation time for recurrent neural networks. *arXiv preprint arXiv:1603.08983*, 2016.

Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. *arXiv preprint arXiv:1410.5401*, 2014.

Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538 (7626):471, 2016.

Edward Grefenstette, Karl Moritz Hermann, Mustafa Suleyman, and Phil Blunsom. Learning to transduce with unbounded memory. In *Advances in Neural Information Processing Systems*, pp. 1828–1836, 2015.

Thomas L Griffiths, Falk Lieder, and Noah D Goodman. Rational use of cognitive resources: Levels of analysis between the computational and the algorithmic. *Topics in cognitive science*, 7(2): 217–229, 2015.

Thomas L Griffiths, Fred Callaway, Michael B Chang, Erin Grant, Paul M Krueger, and Falk Lieder. Doing more with less: Meta-reasoning and meta-learning in humans and machines. *Current Opinion in Behavioral Sciences*, 01 2019.

Abhishek Gupta, Benjamin Eysenbach, Chelsea Finn, and Sergey Levine. Unsupervised meta-learning for reinforcement learning. *arXiv preprint arXiv:1806.04640*, 2018a.

Abhishek Gupta, Russell Mendonca, YuXuan Liu, Pieter Abbeel, and Sergey Levine. Meta-reinforcement learning of structured exploration strategies. *arXiv preprint arXiv:1802.07245*, 2018b.

David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. *arXiv preprint arXiv:1609.09106*, 2016.

Jessica B Hamrick, Andrew J Ballard, Razvan Pascanu, Oriol Vinyals, Nicolas Heess, and Peter W Battaglia. Metacontrol for adaptive imagination-based optimization. *arXiv preprint arXiv:1705.02670*, 2017.

Nicholas Hay, Stuart Russell, David Tolpin, and Solomon Eyal Shimony. Selecting computations: Theory and applications. *arXiv preprint arXiv:1408.2048*, 2014.

Geoffrey Hinton, Nicholas Frosst, and Sara Sabour. Matrix capsules with em routing. 2018.

Robert C Holte and Berthe Y Choueiry. Abstraction and reformulation in artificial intelligence. *Philosophical Transactions of the Royal Society of London B: Biological Sciences*, 358(1435): 1197–1204, 2003.

John J Hopfield. Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the national academy of sciences*, 79(8):2554–2558, 1982.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, et al. Spatial transformer networks. In *Advances in neural information processing systems*, pp. 2017–2025, 2015.

Armand Joulin and Tomas Mikolov. Inferring algorithmic patterns with stack-augmented recurrent nets. In *Advances in neural information processing systems*, pp. 190–198, 2015.

Łukasz Kaiser and Ilya Sutskever. Neural gpus learn algorithms. *arXiv preprint arXiv:1511.08228*, 2015.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Teuvo Kohonen. Correlation matrix memories. *IEEE transactions on computers*, 100(4):353–359, 1972.

Tejas D Kulkarni, William F Whitney, Pushmeet Kohli, and Josh Tenenbaum. Deep convolutional inverse graphics network. In *Advances in Neural Information Processing Systems*, pp. 2539–2547, 2015.

Tejas D Kulkarni, Karthik Narasimhan, Ardavan Saeedi, and Josh Tenenbaum. Hierarchical deep reinforcement learning: Integrating temporal abstraction and intrinsic motivation. In *Advances in neural information processing systems*, pp. 3675–3683, 2016.

Karol Kurach, Marcin Andrychowicz, and Ilya Sutskever. Neural random-access machines. *arXiv preprint arXiv:1511.06392*, 2015.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Falk Lieder, Frederick Callaway, Sayan Gul, Paul M Krueger, and Thomas L Griffiths. Learning to select computations. *arXiv preprint arXiv:1711.06892*, 2017.

David Lopez-Paz et al. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems*, pp. 6467–6476, 2017.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. 2018.

Volodymyr Mnih, Nicolas Heess, Alex Graves, et al. Recurrent models of visual attention. In *Advances in neural information processing systems*, pp. 2204–2212, 2014.

Ofir Nachum, Shane Gu, Honglak Lee, and Sergey Levine. Data-efficient hierarchical reinforcement learning. *arXiv preprint arXiv:1805.08296*, 2018.

Ashvin V Nair, Vitchyr Pong, Murtaza Dalal, Shikhar Bahl, Steven Lin, and Sergey Levine. Visual reinforcement learning with imagined goals. In *Advances in Neural Information Processing Systems*, pp. 9209–9220, 2018.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th international conference on machine learning (ICML-10)*, pp. 807–814, 2010.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *CoRR, abs/1803.02999*, 2018.

Junhyuk Oh, Satinder Singh, Honglak Lee, and Pushmeet Kohli. Zero-shot task generalization with multi-task deep reinforcement learning. *arXiv preprint arXiv:1706.05064*, 2017.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. In *NIPS-W*, 2017.

S Pinker. Baby born talkingdescribes heaven. *The language instinct: How the mind creates language*, pp. 265–301, 1994.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. 2016.

Scott Reed and Nando De Freitas. Neural programmer-interpreters. *arXiv preprint arXiv:1511.06279*, 2015.

Sebastian Riedel, Matko Bosnjak, and Tim Rocktäschel. Programming with a differentiable forth interpreter. *CoRR, abs/1605.06640*, 2016.

Clemens Rosenbaum, Tim Klinger, and Matthew Riemer. Routing networks: Adaptive selection of non-linear functions for multi-task learning. *International Conference on Learning Representations*, 2018.

Stuart Russell and Eric Wefald. Principles of metareasoning. *Artificial intelligence*, 49(1-3):361–395, 1991.

S Sanborn, D Bourgin, M Chang, and T Griffiths. Representational efficiency outweighs action efficiency in human program induction. In *Proceedings of the 40th annual Cognitive Science Society*, July 2018.

Imanol Schlag and Jürgen Schmidhuber. Gated fast weights for on-the-fly neural program generation. In *NIPS Metalearning Workshop*, 2017.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook*. PhD thesis, Technische Universität München, 1987.

Jürgen Schmidhuber. Learning to control fast-weight memories: An alternative to dynamic recurrent networks. *Neural Computation*, 4(1):131–139, 1992.

Jürgen Schmidhuber. Ultimate cognition à la gödel. *Cognitive Computation*, 1(2):177–193, 2009.

Jürgen Schmidhuber. Self-delimiting neural networks. *arXiv preprint arXiv:1210.0118*, 2012.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Herbert A Simon. The sciences of the artificial. *Cambridge, MA*, pp. 132, 1969.

Herbert A Simon. The science of design: Creating the artificial. *Design Issues*, pp. 67–82, 1988.

Alec Solway, Carlos Diuk, Natalia Córdova, Debbie Yee, Andrew G Barto, Yael Niv, and Matthew M Botvinick. Optimal behavioral hierarchy. *PLoS computational biology*, 10(8):e1003779, 2014.

Elizabeth S Spelke. Principles of object perception. *Cognitive science*, 14(1):29–56, 1990.

Jost Tobias Springenberg, Alexey Dosovitskiy, Thomas Brox, and Martin Riedmiller. Striving for simplicity: The all convolutional net. *arXiv preprint arXiv:1412.6806*, 2014.

Aravind Srinivas, Allan Jabri, Pieter Abbeel, Sergey Levine, and Chelsea Finn. Universal planning networks. *arXiv preprint arXiv:1804.00645*, 2018.

Sainbayar Sukhbaatar, Jason Weston, Rob Fergus, et al. End-to-end memory networks. In *Advances in neural information processing systems*, pp. 2440–2448, 2015.

Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. In *Advances in neural information processing systems*, pp. 3104–3112, 2014.

Valentin Thomas, Jules Pondard, Emmanuel Bengio, Marc Sarfati, Philippe Beaudoin, Marie-Jean Meurs, Joelle Pineau, Doina Precup, and Yoshua Bengio. Independently controllable features. *arXiv preprint arXiv:1708.01289*, 2017.

Sebastian Thrun and Lorien Pratt. *Learning to learn*. Springer Science & Business Media, 2012.

Alexander Sasha Vezhnevets, Simon Osindero, Tom Schaul, Nicolas Heess, Max Jaderberg, David Silver, and Koray Kavukcuoglu. Feudal networks for hierarchical reinforcement learning. *arXiv preprint arXiv:1703.01161*, 2017.

William F Whitney, Michael Chang, Tejas Kulkarni, and Joshua B Tenenbaum. Understanding visual concepts with continuation learning. *arXiv preprint arXiv:1602.06822*, 2016.

David J Willshaw, O Peter Buneman, and Hugh Christopher Longuet-Higgins. Non-holographic associative memory. *Nature*, 1969.

Danfei Xu, Suraj Nair, Yuke Zhu, Julian Gao, Animesh Garg, Li Fei-Fei, and Silvio Savarese. Neural task programming: Learning to generalize across hierarchical tasks. *arXiv preprint arXiv:1710.01813*, 2017.

Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. Show, attend and tell: Neural image caption generation with visual attention. In *International Conference on Machine Learning*, pp. 2048–2057, 2015.

Wojciech Zaremba and Ilya Sutskever. Learning to execute. *arXiv preprint arXiv:1410.4615*, 2014.

Wojciech Zaremba, Tomas Mikolov, Armand Joulin, and Rob Fergus. Learning simple algorithms from examples. In *International Conference on Machine Learning*, pp. 421–429, 2016.

A DATA

Numerical arithmetic (Sec. D.1): The dataset contains arithmetic expressions of k terms where the terms are integers $\in [0, 9]$ and the operators are $\in \{+, \times, -\}$. The number of possible problems is $(10^k)(3^{k-1})$. The learner sees $5810/(2.04 \cdot 10^{14}) = 2.85 \cdot 10^{-11}$ of the training distribution. The number of possible problems in the extrapolation set is $(10^{20})(3^{19}) = 1.16 \cdot 10^{29}$. An input expression is a sequence of one-hot vectors of size 13.

# Terms	Prob. Space	# Train Samples	Frac. of Prob. Space
2	$(10^2)(3^1) = 3 \cdot 10^2$	210	$7 \cdot 10^{-1}$
3	$(10^3)(3^2) = 9 \cdot 10^3$	700	$7.78 \cdot 10^{-2}$
4	$(10^4)(3^3) = 2.7 \cdot 10^5$	700	$2.6 \cdot 10^{-3}$
5	$(10^5)(3^4) = 8.1 \cdot 10^6$	700	$8.64 \cdot 10^{-5}$
6	$(10^6)(3^5) = 2.43 \cdot 10^8$	700	$2.88 \cdot 10^{-6}$
7	$(10^7)(3^6) = 7.29 \cdot 10^9$	700	$9.60 \cdot 10^{-8}$
8	$(10^8)(3^7) = 2.19 \cdot 10^{11}$	700	$3.20 \cdot 10^{-9}$
9	$(10^9)(3^8) = 6.56 \cdot 10^{12}$	700	$1.07 \cdot 10^{-10}$
10	$(10^{10})(3^9) = 1.97 \cdot 10^{14}$	700	$3.56 \cdot 10^{-12}$
Total	$2.04 \cdot 10^{14}$	5810	$2.85 \cdot 10^{-11}$

Table 1: Numerical Arithmetic Dataset

Multilingual arithmetic (Sec. 4.1): The dataset contains arithmetic expressions of k terms where the terms are integers $\in [0, 9]$ and the operators are $\in \{+, \cdot, -\}$, expressed in five different languages. With 5 choices for the source language and target language, the number of possible problems is $(10^k)(3^{k-1})(5^2)$. In training, each source language is seen with 4 target languages and each target language is seen with 4 source languages: 20 pairs are seen in training and 5 pairs are held out for testing. The learner sees $46200/(1.68 \cdot 10^8) = 2.76 \cdot 10^{-4}$ of the training distribution. The entire space of possible problems in the extrapolation set is $(10^{10})(3^9)(5^2) = 4.92 \cdot 10^{15}$ out of which we draw samples from the 5 held-out language pairs $\big((10^{10})(3^9)(5) = 9.84 \cdot 10^{14}$ possible$\big)$. An input expression is a sequence of one-hot vectors of size $13 \times 5 + 1 = 66$ where the single additional element is a STOP token (for training the RNN).

# Terms	Prob. Space	Train Prob. Space	# Train Samples	Frac. of Train Dist.	Frac. of Prob. Space
2	$(10^2)(3^1)(25) = 7.5 \cdot 10^3$	$(10^2)(3^1)(20) = 6 \cdot 10^3$	$210 \cdot 20 = 4.2 \cdot 10^3$	$7 \cdot 10^{-1}$	$5.6 \cdot 10^{-1}$
3	$(10^3)(3^2)(25) = 2.25 \cdot 10^5$	$(10^3)(3^2)(20) = 1.8 \cdot 10^5$	$700 \cdot 20 = 1.4 \cdot 10^4$	$7.78 \cdot 10^{-2}$	$6.22 \cdot 10^{-2}$
4	$(10^4)(3^3)(25) = 6.75 \cdot 10^6$	$(10^4)(3^3)(20) = 5.4 \cdot 10^6$	$700 \cdot 20 = 1.4 \cdot 10^4$	$2.6 \cdot 10^{-3}$	$2.07 \cdot 10^{-3}$
5	$(10^5)(3^4)(25) = 2.02 \cdot 10^8$	$(10^5)(3^4)(20) = 1.62 \cdot 10^8$	$700 \cdot 20 = 1.4 \cdot 10^4$	$8.64 \cdot 10^{-5}$	$6.91 \cdot 10^{-5}$
Total	$2.09 \cdot 10^8$	$1.68 \cdot 10^8$	46200	$2.76 \cdot 10^{-4}$	$2.21 \cdot 10^{-4}$

Table 2: Multilingual Arithmetic Dataset

Spatially transformed MNIST (Sec. 4.2): The generative process for transforming the standard MNIST dataset to the input the learner observes is described as follows. We first center the 28x28 MNIST image in a 42x42 black background. We have three types of transformations to apply to the image: scale, rotate, and translate. We can scale big or small. We can rotate left or right. We can translate left, right, up, and down, but the degree to which we translate depends on the size of the object: we translate the digit to the edge of the image, so smaller digits get translated more than large digits. In total there are $2 + 2 + 4 \times 3 = 16$ individual transformation operations used in the generative process. Because some transformation combinations are commutative, we defined an ordering with which we will apply the generative transformations: scale then rotate then translate. For length-2 compositions of generative transformations, there are scale-small-then-translate (1×4), scale-big-then-translate (1×4), rotate-then-translate (2×4), and scale-then-rotate (2×2). We randomly choose 12 of these 16 for training, 2 for validation, 2 for test, as shown in Figure 4. For length-3 compositions of generative transformations, there are scale-small-then-rotate-then-translate $(1 \times 2 \times 4)$ and scale-big-then-rotate-then-translate $(1 \times 2 \times 4)$. All 16 were held out for evaluation.

B LEARNER DETAILS

All learners are implemented in PyTorch (Paszke et al., 2017) and we will make the code and data available online.

B.1 ARITHMETIC

Baseline: The RNN is implemented as a sequence-to-sequence (Sutskever et al., 2014) GRU (Cho et al., 2014).

CRL Controller: The controller consists of a policy network and a value function, each implemented as GRUs that read in the input expression. The value function outputs a value estimate for the current expression. For the numerical arithmetic task, the policy network first selects a reducer and then conditioned on that choice selects the location in the input expression to apply the reducer. For the multilingual arithmetic task, the policy first samples whether to halt, reduce, or translate, and then conditioned on that choice (if it doesn't halt) it samples the reducer (along with an index to apply it) or translator.

CRL Modules: The reducers are initialized as a two-layer feedforward network with ReLU non-linearities (Nair & Hinton, 2010). The translators are a linear weight matrices.

B.2 IMAGE TRANSFORMATIONS

Baselines: The CNN is a variant of an all-convolutional network (Springenberg et al., 2014) fully convolutional network. This was also used as the pre-trained image classifier. The affine-STN predicts all 6 learnable affine parameters as in Jaderberg et al. (2015).

CRL Controller: The controller consists of a policy network and a value function, each implemented as CNNs.

CRL Modules: The rotate-STN's localization network is constrained to output the sine and cosine of a rotation angle, the scale-STN's localization network is constrained to output the scaling factor, and the translate-STN's localization network is constrained to output spatial translations

C EXPERIMENT DETAILS

C.1 ARITHMETIC

Training procedure: The training procedure for the controller follows the standard Proximal Policy Optimization training procedure, where the learner samples a set of episodes, pushes them to a replay buffer, and every k episodes updates the controller based on the episodes collected. Independently, every k' episodes we consolidate those k' episodes into a batch and use it to train the functions. We found via a grid search $k = 1024$ and $k' = 256$. Through an informal search whose heuristic was performance on the training set, we settled on updating the curriculum of CRL every 10^5 iterations and updating the curriculum of the RNN every $5 \cdot 10^4$ iterations.

Domain-specific nuances: In the case that HALT is called to early, CRL treats it as a no-op. Similarly, if a reduction operator is called when there is only one token in the expression, the learner also treats it as a no-op. There are other ways around this domain-specific nuance, such as to always halt whenever HALT is called but only do backpropagation from the loss if the expression has been fully reduced (otherwise it wouldn't make sense to compute a loss on an expression that has not been fully reduced). The way we interpret these "invalid actions" is analogous to a standard practice in reinforcement learning of keeping an agent in the same state if it walks into a wall of a maze.

Symmetry breaking: We believe that the random initialization of the functions and the controller breaks the symmetry between the functions. For episodes 0 through k the controller still has the same random initial weights, and for episodes 0 through k' the functions still have the same random initial weights. Because of the initial randomness, the initial controller will select certain functions more than others for certain inputs; similarly initially certain functions will perform better than others for certain inputs. Therefore, after k iterations, the controller's parameters will update in a direction that will make choosing the functions that luckily performed better for certain inputs more

(a) Training Accuracy   (b) Test Accuracy   (c) Extrapolation Accuracy

Figure 6: **Numerical math task.** We compare our learner with the RNN baseline. As a sanity check, we also compare with a version of our learner which has a hardcoded controller (HCC) and a learner which has hardcoded functions (HCF) (in which case the controller is restricted to select windows of 3 with an operator in the middle, but this is not the case in general). All models perform well on the training set. Only our method and its HCC, HCF modifications generalize to the testing and extrapolation set. The RNN requires 10 times more data to generalize to the testing and extrapolation set. For (b, c) we only show accuracy on the expressions with the maximum length of those added so far to the curriculum. "1e3" and "1e4" correspond to the order of magnitude of the number of samples in the dataset, of which 70% are used for training. 10, 50, and 90 percentiles are shown over 6 runs.

likely; similarly, after k' iterations, the functions' parameters will update in a direction that will make them better for the inputs they have been given. So gradually, functions that initially were slightly better at certain inputs will become more specialized towards those inputs and they will also get selected more for those inputs.

Training objective: The objective of the composition of functions is to minimize the negative log likelihood of the correct answer to the arithmetic problem. The objective of the controller is to maximize reward. It receives a reward of 1 if the token with maximum log likelihood is that of the correct answer, 0 if not, and -0.01 for every computation step it takes. The step penalty was found by a scale search over $\{-1, -0.1, -0.01, -0.001\}$ and -0.01 was a penalty that we found balanced accuracy and computation time to a reasonable degree during training. There is no explicit feedback on what the transformations should be and on how they are composed.

D   ADDITIONAL EXPERIMENTS

D.1   NUMERICAL MATH

The input is a numerical arithmetic expression (e.g. $3 + 4 \times 7$) and the desired output (e.g. 1) is the evaluation of the expression modulo 10. The input and output have the same type. In our experiments we train on a curriculum of length-2 expressions to length-10 expressions, adding new expressions to an expanding dataset over the course of training in a lifelong learning fashion. The first challenge is to learn from this limited data (only 6510 training expressions) to generalize well to unseen length-10 expressions in the test set ($\approx 2^{14}$ possible). The second challenge is to extrapolate from this limited data to length-20 expressions ($\approx 10^{29}$ possible).

Expressions are represented as sequences of one-hot vectors. The functions ("reducers") used in CRL reduce a length k expression to a length $k - 3$ one: the controller chooses a window of 3 terms in the expression, and the reducer transforms that into a softmax distribution over a single term in the vocabulary. This process is repeated until the expression is reduced to one term, at which point the expression persists until the controller HALTs. Choosing to attend to a subset of the input is not domain-specific; this strategy is applicable in many settings (Mnih et al., 2014; Eslami et al., 2016; Xu et al., 2015). We compare with an RNN architecture (Chung et al., 2014) directly trained to map input to output.

Results: Interestingly, though the RNN eventually generalizes to different 10-length expressions and extrapolates to 20-length expressions (yellow in Fig. 6) with 10 times more data as CRL, it completely overfits when given the same amount of data (gray). In contrast, CRL (red) does not overfit, generalizing significantly better to both the 10-length and 20-length test sets. We believe

(a) Pathological Train   (b) Pathological Test   (c) Different numbers of functions

Figure 7: **Variations:** The minimum number of reducers and translators that can solve the multilingual math problems is 1 and m respectively, where m is the number of languages. This is on an extrapolation task, which has more terms *and* different language pairs. (a, b): Four reducers and zero translators (red) is a pathological choice of functions that causes CRL to overfit, but it does not when translators are provided. (c) In the non-pathological cases, regardless of the number of functions, the learner metareasons about the resources it has to customize its computation to the problem. 10, 50, and 90 percentiles are shown over 6 runs.

that the modular disentangled structure in CRL biases it to cleave the problem distribution at its joints, yielding this 10-fold reduction in sample complexity relative to the RNN.

Indeed, we found that the controller naturally learned windows centered around operators (e.g. $2+3$ rather than $\times 4-$), suggesting that it has discovered semantic role of these primitive two-term expressions by pattern-matching common structure across arithmetic expressions of different lengths. Note that CRL's extrapolation accuracy here is not perfect compared to (Cai et al., 2017): but what we believe is noteworthy is that CRL achieves such high extrapolation accuracy with only sparse supervision, *without* the step-by-step supervision on execution traces, the stack-based model of execution, and hardcoded transformations.

D.2   VARIATIONS

Here we study the effect of varying the number of functions available to our learner. Fig. 7a, 7b highlights a particular pathological choice of functions that causes CRL to overfit. If CRL uses four reducers and zero translators (red), it is not surprising that it fails to generalize to the test set: recall that each source language is only seen with four target languages during training with one held out; each reducer can just learn to reduce to one of the four target languages. What is interesting though is that when we add five translators to the four reducers (blue), we see certain runs achieve 100% generalization, even though CRL need not use the translators at all in order to fit the training set. That the blue training curve is slightly faster than the red offers a possible explanation: it may be harder to find a program where each reducer can reduce any source language to their specialized target language, and easier to find programs that involve steps of re-representation (through these translators), where the solution to a new problem is found merely by re-representing that problem into a problem that learner is more familiar with. The four-reducers-five-translators could have overfitted completely like the four-reducers-zero-translators case, but it consistently does not.

Indeed, we find that when we vary the number of reducers in $\{1, 3\}$ and the number of translators in $\{5, 8\}$ in Fig. 7c, the extrapolation performance is consistent across the choices of different numbers of functions, suggesting that CRL is quite robust to the number of functions in non-pathological cases.

D.3   HOW FAR CAN WE PUSH EXTRAPOLATION?

The extrapolation accuracy from 6 to 100 terms after training on a curriculum from 2 to 5 terms (46200 examples) on the multilingual arithmetic task (Sec. 4.1). The number of possible 100-term problems is $(10^{100})(3^{99})(5^2) = 4.29 \cdot 10^{148}$ and CRL achieves about 60% accuracy on these problems; a random guess would be 10%.

Figure 8: Multilingual Extrapolation

D.4 EXECUTION TRACES: FUNCTION SELECTION

(a) Validation Execution Traces (b) Test Execution Traces (c) Extrapolation Execution Traces

Figure 9: **Multilingual Arithmetic Execution Traces**

Fig. 9 compares the execution traces of CRL on the validation, test, and extrapolation sets after training. The language pairs in the test and extrapolation sets are the same, and the language pairs among training, validation, and test are disjoint.

D.5 EXECUTION TRACES: EXAMPLES

Here are two randomly selected execution traces from the numerical arithmetic extrapolation task (train on 10 terms, extrapolate to 20 terms), where CRL's accuracy hovers around 80%. These expressions are derived from the internal representations of CRL, which are softmax distributions over the vocabulary (except for the first expression, which is one-hot because it is the input). The expressions here show the maximum value for each internal representation.

This is a successful execution. The input is `6*1*3-4+6*0*0+1-7-3+3+3*4+1+1+3+3+6+2+7` and the correct answer is `3`. Notice that the order in which controller applies its functions does not strictly follow the order of operations but respects the rules of order of operations: for example, it may decide to perform addition (A) before multiplication (B) if it doesn't affect the final answer.

```
6*1*3-4+6*0*0+1-7-3+3+3*4+1+1+3+3+6+2+7      # 3 * 4 = 2
6*1*3-4+6*0*0+1-7-3+3+2+1+1+3+3+6+2+7        # 3 + 2 = 5
6*1*3-4+6*0*0+1-7-3+5+1+1+3+3+6+2+7          # 1 - 7 = 4
6*1*3-4+6*0*0+4-3+5+1+1+3+3+6+2+7            # 0 * 0 = 0
6*1*3-4+6*0+4-3+5+1+1+3+3+6+2+7              # 4 - 3 = 1
6*1*3-4+6*0+1+5+1+1+3+3+6+2+7                # 1 + 3 = 4
6*1*3-4+6*0+1+5+1+4+3+6+2+7                  # 5 + 1 = 6
6*1*3-4+6*0+1+6+4+3+6+2+7                    # 1 + 6 = 7
6*1*3-4+6*0+7+4+3+6+2+7                      # 2 + 7 = 9
6*1*3-4+6*0+7+4+3+6+9                        # 3 + 6 = 9
6*1*3-4+6*0+7+4+9+9                          # 6 * 0 = 0      ----------------------------------------
6*1*3-4+0+7+4+9+9                            # tried to HALT  everything above this line is extrapolation
6*1*3-4+0+7+4+9+9                            # 9 + 9 = 8      (A)
6*1*3-4+0+7+4+8                              # 1 * 3 = 3      (B)
6*3-4+0+7+4+8                                # 0 + 7 = 7
6*3-4+7+4+8                                  # 6 * 3 = 8
8-4+7+4+8                                    # 8 - 4 = 4
4+7+4+8                                      # 4 + 7 = 1
1+4+8                                        # 1 + 4 = 5
5+8                                          # 5 + 8 = 3
3                                            # HALT
END
```

This is an unsuccessful execution trace.
The input is `5+6-4+5*7*3*3*8*0*1-4+6-3*5*3+6-0+0-4-6` and the correct answer is `0`. Notice that it tends to follow of order of operations by doing multiplication first, although it does make mistakes (D), which in this case was the reason for its incorrect answer. Note that CRL never receives explicit feedback about its mistakes on what its functions learn to do or the order in which it applies them; it only receives a sparse reward signal at the very end. Although (C) was a calculation mistake, it turns out that it does not matter because the subexpression would be multiplied by 0 anyways.

```
5+6-4+5*7*3*3*8*0*1-4+6-3*5*3+6-0+0-4-6      # 3 * 8 = 4
5+6-4+5*7*3*4*0*1-4+6-3*5*3+6-0+0-4-6        # 0 - 4 = 6
5+6-4+5*7*3*4*0*1-4+6-3*5*3+6-0+6-6          # 5 * 7 = 5
```

```
5+6-4+5*3*4*0*1-4+6-3*5*3+6-0+6-6      # 3 * 4 = 4 (mistake)       (C)
5+6-4+5*4*0*1-4+6-3*5*3+6-0+6-6        # tried to HALT
5+6-4+5*4*0*1-4+6-3*5*3+6-0+6-6        # 5 * 4 = 0
5+6-4+0*0*1-4+6-3*5*3+6-0+6-6          # 6 - 6 = 0
5+6-4+0*0*1-4+6-3*5*3+6-0+0            # 6 - 3 = 3                 (D: order of operations mistake)
5+6-4+0*0*1-4+3*5*3+6-0+0              # tried to HALT
5+6-4+0*0*1-4+3*5*3+6-0+0              # tried to HALT
5+6-4+0*0*1-4+3*5*3+6-0+0              # tried to HALT
5+6-4+0*0*1-4+3*5*3+6+0                # 3 * 5 = 5
5+6-4+0*0*1-4+5*3+6+0                  # 0 * 1 = 0
5+6-4+0*1-4+5*3+6+0                    # 5 * 3 = 5                 ----------------------------------------
5+6-4+0*1-4+5+6+0                      # 0 * 1 = 0                 everything above this line is extrapolation
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # tried to HALT
5+6-4+0-4+5+6+0                        # 6 + 0 = 0
5+6-4+0-4+5+6                          # 5 + 6 = 1
5+6-4+0-4+1                            # 0 - 4 = 6
5+6-4+6+1                              # 5 + 6 = 1
1-4+6+1                                # 1 - 4 = 7
7+6+1                                  # 7 + 6 = 3
3+1                                    # 3 + 1 = 4
4                                      # HALT
END
```