Rigorous Agent Evaluation: An adversarial approach to uncover catastrophic failures

Abstract

This paper addresses the problem of evaluating learning systems in safety critical domains such as autonomous driving, where failures can have catastrophic consequences. To this end, we focus on two problems: searching for scenarios when learned agents fail and the related problem of assessing their probability of failure. The standard method for agent evaluation in reinforcement learning, Vanilla Monte Carlo, can severely underestimate agent failure probabilities, leading to the deployment of unsafe agents. In our experiments, we observe this even after allocating equal compute to training and evaluation. To address this shortcoming, we draw upon the rare event probability estimation literature and propose an *adversarial evaluation* approach. Our approach focuses evaluation on difficult scenarios that are selected adversarially, while still providing unbiased estimates of failure probabilities. To do this, we propose a continuation approach to learning a failure probability predictor. This leverages data from related agents to overcome issues of data sparsity and allows the adversary to reuse data gathered for training the agent. We demonstrate the efficacy of adversarial evaluation on two complex reinforcement learning domains (humanoid control and simulated driving). Experimental results show that our methods can find catastrophic failures and estimate failures rates of agents multiple orders of magnitude faster (hours instead of days) than standard evaluation schemes.

1 Introduction

How can we ensure machine learning systems do not make catastrophic mistakes? While machine learning systems have shown impressive results across a variety of domains (Krizhevsky et al., 2012; Mnih et al., 2015; Silver et al., 2017), they may also perform extremely poorly on particular inputs, often in unexpected ways (Szegedy et al., 2013). As we start deploying these systems, it is important that we can reliably evaluate the risk of failure. This is particularly important for safety critical domains like autonomous driving where the negative consequences of a single mistake can overwhelm the positive benefits of typical operation of the policy. The paradigm of empirical risk minimization handles these cases poorly: although such failures have very large losses, their rarity leads them to be ignored by the empirical risk estimator which works with finite number of samples.

Limitations of random testing. For concreteness, consider a self-driving car company that decides that the cost of a single accident where the car is at fault outweighs the benefits of 100 million miles of faultless operation. The standard approach in machine learning is to estimate expected return via the sample mean on independent samples from the data distribution (frequently a test set). In the case of tightly bounded rewards, these sample estimates are guaranteed to quickly converge to the true expected return. However, for rare but catastrophic failures, this may be prohibitively inefficient. In our current example, any policy with a failure probability greater than $\epsilon = 10^{-8}$ per mile has negative expected reward. In other words, it would be better to not deploy the car. The key technical challenge here is that to achieve reasonable confidence that the autonomous vehicle crashes with probability below $1e\text{--}8$, the manufacturer would need to test-drive the car for at least $1e8$ miles. The general problem we point to is that, for standard statistical evaluation, attaining confidence that the failure rate of a policy is below ϵ requires at least $1/\epsilon$ episodes (e.g., Section 4.2 in Bucklew (2004)).

Our Contributions. To overcome the above-mentioned problems, we develop a novel *adversarial evaluation* approach. The central motivation behind our algorithmic choices is the fact that real-

world evaluation is typically dominated by the cost of running the agent in the real-world and/or human supervision. In the self-driving car example, both issues are present: testing requires both operating a physical car, and a human test driver behind the wheel. The overarching idea is thus to screen out situations that are unlikely to be problematic, and focus the evaluation efforts on the most difficult situations. The difficulty arises in identifying these situations – since failures are rare, there is little signal to drive optimization. To address this problem, we introduce a *continuation approach* to learning a *failure probability predictor* (FPP), which estimates the probability the agent fails given some initial conditions. The idea is to leverage data from less robust agents, which can provide a stronger signal for learning to identify potentially problematic situations. In our implementation, this also allows the algorithm to reuse data gathered for training the agent, saving time and resources during evaluation. We note that adversarial testing is a well-established idea (see Section 5), but typically requires either a dense optimization signal or expert domain knowledge. We avoid these stumbling blocks by relying on the FPP, which can thus be viewed as guiding the adversarially acting evaluator.

We look at two settings where the FPP can be used. In the simplest setting, *failure search*, the problem is to efficiently find inputs (initial conditions) that cause failures (Section 2.1). This task has many uses. First, an adversary that solves this task efficiently allows one to identify and debug potentially unsafe policies. Second, as has been done previously in the supervised learning literature, efficient adversaries can be used for adversarial training, by folding the states causing failures back into the training algorithm (Madry et al., 2017). The second setting, *risk estimation*, is the problem of efficiently estimating the failure probability of an agent (Section 2.2), which also has a simple application to efficiently selecting the most reliable agent from a finite set (Section 4.3).

Empirically, we demonstrate dramatic improvements in efficiency through adversarial testing on two domains (simulated driving and humanoid locomotion) which have been used for reinforcement learning research. In summary, we present 4 key contributions:

1. We formulate the problem of adversarial agent evaluation in the context where failures are rare but catastrophic. We introduce two versions of the problem: *failure search* to efficiently find a catastrophic trajectory produced by a policy and *risk estimation* to reliably estimate the failure probability for a policy.

2. We empirically demonstrate the limitations of standard random testing in our environments. We observe that with random testing, the cost of reliably obtaining a single adversarial state exceeds the entire cost of training, and reliably estimating risk is several times more expensive than training.

3. We describe a continuation approach for learning *failure probability predictors* even when failures are rare. We develop algorithms applying failure probability predictors to failure search, risk estimation, and model selection.

4. We extensively evaluate our method on simulated driving and humanoid locomotion domains. Using adversarial evaluation, we find failures with 198 and 3100 times fewer samples respectively. On humanoid, we bring the cost of reliable risk estimation down to a practical budget.

2 PROBLEM FORMULATION

We first introduce our notation. Recall that we are interested in reliability assessment of a trained agent. We assume that the experimenter who performs the reliability assessment can run an *experiment* (equivalently, a rollout or episode) with the trained agent given some initial condition $x \in \mathcal{X}$, the outcome of which is a random failure indicator $C = c(x, Z)$ where $Z \sim P_Z$ for some probability distribution P_Z over some set $\mathcal{Z}$ and where $c : \mathcal{X} \times \mathcal{Z} \to \{0, 1\}$. In particular, C is binary and $C = 1$ indicates a "catastrophic failure". The interpretation of Z is that it collects all sources of randomness due to the agent and the environment. Unlike the case of x, Z is neither observed, nor controllable by the experimenter. We are interested in the agent's performance on the environment distribution over initial conditions $X \sim P_X$, which we assume can be sampled quickly.[1]

---

[1] To minimize jargon, we omit standard conditions on the spaces and functions that permit the use of the language of probabilities.

In the real-world, evaluating c requires running the agent in the real-world and/or human supervision, which generally dominate the cost of evaluating neural networks. It is thus assumed that evaluating c on the pair (x, Z) is costly. In Section 4.1, we show that even on relatively cheap simulated environments, the cost of simulating environments dominates costs of evaluating neural networks.

2.1 FAILURE SEARCH

The objective of *failure search* is to find a catastrophic failure of the agent. Algorithms that search for failures, which we will call *adversaries*, can specify initial conditions x, observe the outcome C of running the agent on x and return as soon as $C = 1$. An adversary can choose the initial conditions in any order and is also allowed to randomize. Thus, for the first round an adversary could choose $X_1 \sim P_1(\cdot)$, run an experiment from X_1 and then observe $C_1 = c(X_1, Z_1)$. If $C_1 = 1$, the algorithm returns. In round $t > 1$, the adversary can choose $X_t \sim P_t(\cdot | X_1, \ldots, X_{t-1})$, observe $C_t = c(X_t, Z_t)$, return if $C_t = 1$ and continue to round $t + 1$ otherwise. Here, $Z_t \sim P_Z$, independently of the history $(X_1, \ldots, X_t, Z_1, \ldots, Z_{t-1})$. The *naive adversary* evaluates the agent on samples from P_X until observing a failure. We assess adversaries by the expected number of episodes, or the expected time elapsed, until returning a failure case.

To design a more efficient adversary, the experimenter is allowed to collect *historical data* of the form $(X'_1, \theta_1, C'_1), \ldots, (X'_n, \theta_n, C'_n)$ *while they are training their agent.* Here, the initial condition X'_t and $\theta_t \in \Theta$ are chosen by the training procedure, where θ_t encodes information about the agent used in round t to generate the observation $C'_t = c(X'_t, Z'_t)$, where the distribution of Z'_t is also affected by the choice of the agent for this round.

2.2 RISK ESTIMATION

Let P_X be a probability distribution over $\mathcal{X}$: as in the previous section, P_X reflects the user's beliefs of how likely each initial condition (e.g., initial state) will be encountered in practice. Given this probability distribution, the *failure probability* of the trained agent is

$$p = \mathbb{E}[c(X, Z)],$$

where $X \sim P_X$ and $Z \sim P_Z$ are independent of each other. A typical goal is to estimate p up to a fixed *relative accuracy* with high probability. Given some $\rho > 1$, $\delta \in (0, 1)$, an algorithm is said to be (ρ, δ) correct if the estimate $\hat{P}$ produced belongs to the $[p/\rho, p\rho]$ interval with probability at least $1 - \delta$. When $\hat{P}$ belongs to the said interval, we say that it is a ρ-approximation of p.

Again, it is assumed that the algorithm that estimates p can draw samples from P_X at a small cost. The algorithm has also access to the historic data described previously and can use it to decide whether to run an expensive experiment from the initial condition drawn from P_X. The *naive estimator* draws samples from P_X and runs experiments from these and takes the average of the observed outcomes until the desired accuracy is achieved or the budget available for experimentation is exhausted. This is known as the vanilla Monte Carlo (VMC) method in the literature. The efficiency of an algorithm will be measured by the total number of experiments it runs.

3 APPROACH

In this section we describe our approach to the two problems outlined above. A common feature of our proposed solutions is that they use the historic data to estimate the function $f_* : \mathcal{X} \to [0, 1]$ that returns the probability of seeing a failure given a initial condition:

$$f_*(x) = \mathbb{P}(c(x, Z) = 1), \qquad x \in \mathcal{X},$$

where $Z \sim P_Z$. We propose to learn an approximation $f \approx f_*$, $f : \mathcal{X} \to [0, 1]$, which we call a *failure probability predictor* (FPP). Specifics of our approach to learning f is in Section 3.3. As f will be chosen so that the cost of evaluating f for any given input will be negligible compared to running an experiment, the idea will be to use f to save on the cost of experimentation. Our solutions build on the *certainty equivalence* approach: First, we uncover how f_* (if available) could be used to solve our problems. In cases of certainty equivalence, we would simply plug in f in place of f_*. We however modify this by introducing additional heuristics whose purpose is to reduce sensitivity to the mismatch between f and f_*.

3.1 Failure Search

When f_* is known, the optimal adversary has a particularly simple form (proof left to the reader):

Proposition 3.1. *The adversary that minimizes the expected number of rounds until failure evaluates the agent repeatedly on an instance $x_* \in \mathcal{X}$ that maximizes $f_* : \mathcal{X} \to [0, 1]$.*

Having access to $f \approx f_*$, a natural approach is to evaluate the agent on $\arg\max_x f(x)$. There are two problems with this: *(i)* a maximizer may be hard to find and *(ii)* there is no guarantee that the maximizer of f will give a point where f_* is large. One way to increase the robustness of this procedure is to sample n initial conditions from P_X, pick the initial condition from this set where f is the largest, and run an experiment from the found initial condition. We repeat this process with new sampled initial conditions until we find a catastrophic failure. The pseudocode is included in Appendix B as Algorithm 2 (FPP Adversary).

3.2 Risk estimation using FPPs

The failure probability estimation method uses importance sampling (IS) (e.g., Section 4.2, Bucklew 2004) where the distribution P_X is replaced by a *proposal distribution Q*. For $t \in [n]$, the proposal distribution is used to generate random initial condition $X_t \sim Q$, then an experiment is performed to generate $C_t = c(X_t, Z_t)$, where, given $(X_1, Z_1, \ldots, X_{t-1}, Z_{t-1}, X_t)$, the distribution of Z_t is P_Z. The failure probability p is estimated using the sample mean

$$\hat{P} = \frac{1}{n} \sum_{t=1}^{n} W_t \, c(X_t, Z_t),$$

where $W_t = \frac{p_X(X_t)}{q(X_t)}$ is the *importance weight* of the t-th sample. Here, p_X denotes the density of P_X and q denotes the density of Q.[2] Let $U_t = W_t c(X_t, Z_t)$. As is well-known, under the condition that $p_X(x) f^*(x) = 0$ whenever $q(x) = 0$, we have that $\mathbb{E}[U_t] = p$, and hence $\mathbb{E}[\hat{P}] = p$. Given that $\hat{P}$ is unbiased for any proposal distribution, one natural objective is to choose a proposal distribution which minimizes the variance of the estimator $\hat{P}$.

Proposition 3.2. *For $f : \mathcal{X} \to [0, 1]$ such that $P_X(f^{1/2}) := \int f^{1/2}(x') P_X(dx') > 0$ let Q_f be defined as the distribution over $\mathcal{X}$ whose density q_f is*

$$q_f(x) = \frac{f^{1/2}(x) p_X(x)}{P_X(f^{1/2})}.$$

Then, the variance minimizing proposal distribution Q^* is Q_{f_*}.

The (standard) proof of this and the next proposition can be found in Appendix A. Note that from the definition of Q_f it follows that $\frac{p_X(x)}{q_f(x)} = f^{-1/2}(x) P_X(f^{1/2})$ when $q_f(x) > 0$.

The above result motivates us to suggest using the distribution Q_f as the proposal distribution of an IS estimator. Note that the choice of f (as long as it is bounded away from zero) only influences the efficiency of the method, but not its correctness. It remains to specify how to sample from Q_f and how to calculate the importance weights. For sampling from Q_f, we propose to use the *rejection sampling method* (Section 1.2.2, Bucklew 2004) with the proposal distribution chosen to be P_X: First, $X \sim P_X$ is chosen, which is accepted by probability $f^{1/2}(X)$. This is repeated until a sample is accepted:

Proposition 3.3. *Rejection sampling as described produces a sample from Q_f.*

To increase the robustness of the sampling procedure against errors introduced by $f \neq f_*$, we introduce a "hyperparameter" $\alpha > 0$ so that q_f is redefined to be proportional to f^α. Note that $\alpha = 1/2$ is what our previous result suggests. However, if f is overestimated, a larger value of α may work better, while if f is underestimated, a smaller value of α may work better. The pseudocode of the full procedure is given as Algorithm 1.

---

[2]Here, we implicitly assume that these measures have a density with respect to a common measure. As it turns out, this is not a limiting assumption, but this goes beyond the scope of the present article.

Algorithm 1 FPP-guided risk estimator (FPP estimator)

Input: FPP f, budget $T \in \mathbb{N}$ and tuning parameter $\alpha > 0$
Returns: Failure probability estimate $\hat{P}$
Initialize $S \leftarrow 0$
for $t = 1$ **to** T **do**
    repeat
        Sample proposal instance $X_t \sim P_X$
        Accept X_t with probability $f^\alpha(X_t)$
    until accepting initial condition X_t
    Evaluate the agent on X_t and observe $C_t = c(X_t, Z_t)$
    $S \leftarrow S + C_t / f^\alpha(X_t)$
end for
Compute normalization constant $Z \leftarrow \frac{1}{m} \sum_{i=1}^m f^\alpha(X_i')$ for $X_i' \sim P_X, m \gg T$
return $\hat{P} \leftarrow ZS/T$

3.3 A Continuation Approach to Learning FPPs

Since f_* gives probabilities, an approximation to f_* can be learned by setting up an appropriate binary classification problem when the observed failure indicator is used as the target label. In this work we use neural networks for this purpose, trained using the standard cross-entropy loss. The naive approach involves first collecting a dataset $(X_1, C_1), \ldots, (X_n, C_n)$ by evaluating the agent of interest on random problem instances $X \sim P_X$, then using this data to fit f.

Instead, we propose a *continuation approach*, in which f is trained on a family of related agents rather than a single agent. This has two key benefits. First, this allows us to leverage the wealth of data which is already collected while training the agent. Second, we shall see that, with random testing, the cost of observing a single failure for the final agent can approach the total cost of training. In these cases, the increased failure rates of earlier agents can provide an essential boost to the "signal" in the learning procedure.

Recall that the historical data collected during training takes the form $(X_1', \theta_1, C_1'), \ldots, (X_n', \theta_n, C_n')$ where X_t' is the initial condition in iteration t of training, and θ_t characterizes essential features of the agent's policy used to collect the failure indicator C_t'. The idea is to augment the input space of the neural network from $\mathcal{X}$ to $\mathcal{X} \times \Theta$, training the network to predict $\mathbb{P}(C_t' = 1 | X_t', \theta_t)$. In the simplest implementation, θ_t merely encodes the training iteration t. In many common off-policy RL methods, additional stochasticity is used in the policy at training time to encourage exploration. In these cases, we also use θ_t to encode the degree of stochasticity in the policy.

To some extent, we are relying on generalization in the FPP to address the data sparsity issue. After all, if the naive approach does not observe any failures for the agent of interest, the continuation approach almost certainly does not either. We now provide a simple toy example to discuss in which ways we rely on generalization of the FPP, and other ways in which we do not.

Example. Suppose the true FPP f_* factorizes as $f_*(x, \theta) = g_*(x)h_*(\theta)$. Suppose we have two agents described by θ_1, θ_2, such that the latter agent is significantly more robust, i.e., $h^*(\theta_1)/h^*(\theta_2) = r \gg 1$. Then, if learning requires a fixed number of positive examples to reach a particular accuracy, the continuation approach learns g, the state-dependent component, r times faster than the naive approach, since it receives r times as many positive examples.

On the other hand, accurately learning $h(\theta_2)$ is difficult, since positive examples on θ_2 are rare. However, even when h is learned inaccurately, this FPP is still useful for both failure search and risk estimation. Concretely, if two FPPs $f_1(x, \theta) = g(x)h_1(\theta), f_2(x, \theta) = g(x)h_2(\theta)$ differ only in h, then *both the adversaries and estimators induced by f_1 and f_2 are equivalent*. This is apparent, since when θ is held constant to θ_2 for the agent of interest, f_1 and f_2 only differ by a multiplicative constant $h_1(\theta_2)/h_2(\theta_2)$, which factors out when performing the adversarial search, and defining the proposal distribution for risk estimation.

Discussion. Of course, this strict factorization does not hold exactly in practice. However, we use this example to illustrate two points. First, for both failure search and risk estimation, it is the shape

Domain	FPP Cost	VMC Cost	PR Cost	Acceleration Factor
Driving	3/5/11	200/1000/2700	—*	65/198/250
Humanoid	19/33/56	60K/110K/180K	9K/10K/220K*	2100/3100/3800

Table 1: **Failure search.** We show cost for different adversaries to find an adversarial problem instance, measured by the expected number of episodes. Each column reports the min, median, and max over evaluations of 5 separate agents. In the median case, the FPP adversary finds adversarial inputs with 198x fewer episodes than random testing on Driving and 3100x fewer on Humanoid (Acceleration Factor).

of the learned FPP $f(\theta, s)$ which matters more than its magnitude. Particularly in failure search, even changes to the shape of f are fine, so long as the argmax of f does not change. Second, it captures the intuition that the FPP may learn the underlying structure of difficult states, i.e. $g(s)$, on policies where positive examples are less scarce. Further, using flexible parameterizations for f, such as neural networks, still allow f to represent interactions between θ and s, provided there is sufficient data to learn these regularities. Of course, if failure modes of the test policy of interest look nothing like the failure modes observed during training, the FPP approach is insufficient. However, we show that in the domains we study, this approach works quite well.

4 EXPERIMENTS

We run experiments on two standard reinforcement learning domains, which we describe briefly here. Full details on the environments and agent training procedures are provided in Appendix D.

In the *Driving* domain, the agent controls a car in the TORCS simulator (Wymann et al., 2000) and is rewarded for forward progress without crashing. An initial condition of a simulation run is defined by the shape of the track, which is sampled from a procedurally defined distribution P_X. We define a failure as any collision with a wall. We use an Asynchronous Actor-Critic agent as in (Espeholt et al., 2018), using environment settings from (Mnih et al., 2016) which reproduces the original results on TORCS.

In the *Humanoid* domain, the agent controls a 21-DoF humanoid body in the MuJoCo simulator Todorov et al. (2012); Tassa et al. (2018), and is rewarded for standing without falling. The initial condition of an experiment is defined by a standing joint configuration, which is sampled from a fixed distribution. We define a catastrophic failure as any state where the humanoid has fallen, i.e. the head height is below a fixed threshold. We use a distributed distributional deterministic policy gradient (D4PG) agent, following hyperparameters from Barth-Maron et al. (2018) which reproduces the original results on the humanoid tasks.

4.1 FAILURE SEARCH

We first compare three adversaries by the number of episodes required to find an initial condition that results in a trajectory that ends with a failure. Our purpose is to illustrate our claim that a naive evaluation can lead to a false sense of safety. The adversaries evaluated are the naive (VMC) and the FPP adversaries introduced in Section 3.1, as well as an adversary that we call the *prioritized replay* (PR) adversary. This latter adversary runs experiments starting from all initial conditions that were used during training and which led to failures during training, most recent first. This is perhaps the simplest alternative to the naive adversary: its appeal is its ease of implementation. Additional details on all adversaries are provided in Appendix D. The results are summarized in Table 1.

Discussion of FPP adversary. The FPP adversary is multiple orders of magnitude more efficient than the random adversary. In particular, we note that on Humanoid, for the VMC adversary to have over a 95% chance of detecting a single failure, we would require over $300,000$ episodes, exceeding the cost of training, which used less than $300,000$ episodes[3]. In practice, evaluation is often run for

---

[3]The number of failures is distributed $Bin(N, p)$ and in the median case, for $p = 1/110,000$, $N = 300,000$, we have $(1-p)^N > 0.05$.

much less time than training, and in these cases, the naive approach would very often lead to the mistaken impression that such failure modes do not exist.

We observe similar improvements in pure wall-clock time. On the Driving domain, finding a failure requires 6.4 hours on average for the random adversary, compared to 7.6 minutes on average for the FPP adversary. Even including the model training time of 5 minutes, the FPP adversary is 31 times faster. Similarly, on the Humanoid domain, the random adversary requires 77 hours on average, compared to 6 minutes for the FPP adversary, and a 61-fold speedup after including FPP training time of 70 minutes. These numbers underscore the point that even in relatively cheap, simulated environments, the cost of environment interactions dominate the cost of learning models and using them for optimization.

Discussion of Prioritized Replay adversary. We believe this is the first adversary practitioners should use, as it often provides much better efficiency than random testing, with minimal implementational overhead. The main limitation is that in some cases, the prioritized replay adversary may *never* detect failures, even if they exist. In particular, an agent may learn to handle the particular problem instances on which it was trained, without eliminating all possible failures. In these cases (this occurred once on Humanoid), we fall back to the VMC adversary after trying all the problem instances which caused failures at training. On the Driving domain, because we use a form of adversarial training for the agent, very few (< 20) of the training problem instances have support under P_X. Since none of these resulted in failures, the PR adversary would immediately fall back to the VMC adversary.

Discussion of adversarial testing. We believe the dramatic speed-ups resulting from the use of an appropriate adversary underscore the importance and benefits of adversarial testing. Already, in the Humanoid domain, the cost of finding a single adversarial state without adversarial testing approaches the entire training cost, and as real-world applications require increasingly reliable systems, the benefits of adversarial testing will increase. We further note that even for current reinforcement learning algorithms, the cost of obtaining a single failing input without an adversary presents a major obstacle to training increasingly reliable systems, since there is no optimization pressure to improve the policy on those inputs.

4.2 RISK ESTIMATION

We now compare approaches for risk estimation. Again, the purpose is to illustrate the claim that a naive approach may often be too inefficient to give rise to non-vacuous quantitative answers with reasonable resources, while better alternatives can deliver such answers. In particular, we compare the FPP estimator of Section 3.2 to the vanilla Monte Carlo estimator (VMC). For comparison purposes, we run each estimator multiple times and report the fraction of cases when the obtained estimates fail to fall in the $(p/3, 3p)$ interval, where p is the failure probability to be estimated. This provides a fairly accurate estimate of the probability of $\hat{P}$ failing to be a $\rho = 3$-approximation of p.[4] Results are summarized in Fig. 1. In Appendix D.3 we include plots for other choices of ρ, to show that the results are not sensitive to ρ.

Discussion. At the confidence level $1 - \delta = 0.95$, on the Driving domain, the FPP estimator needs only 750 experiments to achieve a 3-approximation, while the VMC estimator needs $11,000$ experiments for the same. This means that here the FPP estimator requires 14 times less environment interaction. Similarly, on the Humanoid domain, at the confidence level $1 - \delta = 0.95$, the FPP estimator requires $15,000$ experiments to achieve a 3-approximation, while the VMC estimator requires $5.1e5$ experiments, a 34-fold improvement.

We note that these numbers demonstrate that the FPP also has good *coverage*, i.e. it samples from all possible failures, since if any failure conditions were vastly undersampled, the variance of the FPP estimator would explode due to the importance weight term. Coverage and efficiency are complementary. While failure search merely requires the adversary identify a single failure, efficient risk estimation requires the adversary to sample from all possible failures.

---

[4]Here, p was measured separately by running the VMC estimator for $5e6$ episodes on Driving and $2e7$ episodes on Humanoid, so that 2 standard errors lies within 5% relative error on Driving, and 20% on Humanoid.

Figure 1: The figure shows the reliability of the FPP and VMC estimators. The x axis shows the number of evaluation episodes, while the y axis shows the probability that $\hat{P}$ does not belong to the interval $(p/3, 3p)$. This probability is obtained by repeating the evaluation multiple times and plotting the fraction of these runs when the estimate is outside of the target interval. The FPP estimator reliably approaches ground truth dramatically faster than the VMC estimator. We show error bars of 2 standard errors, which are difficult to see on the Driving domain, since we can afford to run sufficiently many trials that standard errors are near zero.

4.3 APPLICATION TO IDENTIFYING MORE RELIABLE AGENTS

The improved efficiency of the FPP estimator has many benefits. One application is to identify the most reliable agent from a fixed finite set.

For this illustration, we compare 50 Humanoid agents, spaced evenly over the course of training (excluding the beginning of training, when the agent has a high failure rate). We compare the choices made when the failure probability estimation is performed with the VMC estimator versus the FPP estimator. For this simple illustration, we estimate each agent's failure probability using the same number of experiments. The selected policy at each point in time is the policy with the lowest estimated risk. If a tie happens, the choice can be arbitrary among the top policies.

Fig. 2 summarizes the results. When using VMC, on average 36 out of 50 policies have never failed by the end of the evaluation process. Thus, VMC was not able to rank 36 out of the 50 policies and the experimenter would be forced to choose one of these with no further information about their reliability. On the other hand, the FPP estimator quickly produces failures for the weak policies, and is able to select a policy which

Figure 2: **Model selection**: We plot the expected number of episodes until failure, i.e. $1/p$ where p is the probability of failure, for the best policy selected by the FPP vs. VMC estimators. The error bars show the min/max over 5 random seeds, while the solid lines correspond to the averaged failure probability. The VMC estimator largely maintains a uniform distribution over many of the policies, whereas the FPP estimator quickly eliminates the worst policies.

is over 3 times more robust (this estimate is conservative – see Appendix X). This can be viewed as an extremely naive form of adversarial training, where the model is selected from a discrete set of options rather than a high-dimensional parameter space. We use this example to highlight the recurring theme that random testing can be highly inefficient – failing to identify the best policies even after $500,000$ episodes (longer than training time) – while adversarial testing greatly improves efficiency.

5 BACKGROUND AND RELATED WORK

Adversarial examples. This work is in part motivated by research on adversarial examples, which points to the fact that machine learning systems that perform very well on average may nonetheless

perform extremely poorly on particular *adversarial inputs*, often in surprising ways (Szegedy et al., 2013; Goodfellow et al., 2014). Unlike previous work on adversarial examples in reinforcement learning (Huang et al., 2017; Lin et al., 2017), we do not allow adversaries to generate inputs outside the distribution on which the agent is trained.

Almost all work on adversarial examples has focused on L_p norm balls in the image domain. Numerous recent papers have questioned the practical value of norm ball robustness, when so many other forms of adversarial perturbations exist (Gilmer et al., 2018; Engstrom et al., 2017; Schott et al., 2018). However, moving beyond the norm ball specification has been difficult, because without very tight constraints on the adversary, human evaluation is necessary to determine the ground truth labels (see Brown et al. (2018); Song et al. (2018) for recent work in this direction).

In this context, we believe simulated reinforcement learning environments provide a valuable testbed for researchers interested in adversarial examples - the ground truth is provided by the simulator. Undoubtedly, new techniques will be necessary both for attacks (efficiently searching for failures, as we do here) and defenses (training models which never make catastrophic mistakes), but we believe that current research on adversarial examples can be effectively leveraged towards this challenge. We hope the domains and problem formulations presented here drive research on adversarial examples beyond norm balls, and towards training and testing models consistent with global specifications.

Our work bears similarities to Werpachowski et al. (2018) who use adversarial examples with an importance weighting correction to detect test set overfitting in the context of classification. Our aims share similarities to recent proposals for testing components of autonomous vehicle systems (Shalev-Shwartz et al., 2017; Dreossi et al., 2017; Tian et al., 2018). We believe these approaches are complementary and should be developed in parallel: these works focus on components-level specifications (e.g. vision systems should be robust to weather conditions, controllers should maintain safe distances) while here, we focus on testing the entire agent end-to-end for system-level specifications.

Rare event estimation. We draw upon a rich literature on rare event simulation/probability estimation (e.g., Bucklew 2004; Rubino & Tuffin 2009; Rubinstein & Kroese 2017). In fact, importance sampling (IS) is one of the workhorses of this field. The closest to our approach from this field are the so-called *adaptive importance sampling methods* where data collected from an initial proposal distribution is used to adjust it to maximize sampling efficiency, in two or even more stages (e.g., Rubinstein 1997; Rubinstein & Kroese 2017; Li et al. 2013). These methods suffer from the problem that the cost of adaptation is not controlled. A recent work has addressed this issue in the case when the goal is to compete with the best of finitely many proposal distributions (Neufeld et al., 2014). Our method is also a two-stage method, but with the important distinction that data collection happens before the evaluation phase even starts, hence the cost of adaptation appears less acutely. Our approach is different from previous works in that, to better reflect the practicalities of RL tasks, we explicitly separate controllable randomness (i.e., initial conditions, simulator parameters) from randomness that is neither controllable, nor observable (environment and agent randomness). As we show, this has implications on the form of the minimum-variance proposal distribution. In addition, unlike IS methods that we are aware of, our method does not need access to the likelihood of individual experiment outcomes.

In robotics, the assessment of the safety of motion control algorithms has been recognized as a critical aspect of their real-world deployment. In a recent paper, extending the work of Janson et al. (2018), Schmerling & Pavone (2017) proposed to use an adaptive mixture importance sampling algorithm to quantify the collision probability for an LQR controller with EKF state estimation applied to non-linear systems with a full rigid-body collision model. The method, which is based on adjusting the parameters of the noise distributions, is illustrated on an airplane model with 8 state variables and 3-dimensional control. Unlike our method, this work needs an analytic model of the environment.

Learning highly reliable agents. While in this work we primarily focus on agent evaluation, rather than training, we note recent work on safe reinforcement learning (see García & Fernández, 2015, for a review). These approaches typically rely on strong knowledge of the transition dynamics (Moldovan & Abbeel, 2012), or assumptions about the accuracy of a learned model (Berkenkamp et al., 2017; Akametalu et al., 2014), and we believe are complementary to adversarial testing, which can be viewed as a mechanism for checking whether such assumptions in fact hold. We provide a longer discussion of this literature in Appendix E.

6 CONCLUSION AND FUTURE WORK

We believe efficient reliability assessment is an important question if ML systems are to be used in situations with the potential for catastrophic failures. In this work, we argued that standard approaches to evaluating RL agents are highly inefficient in detecting rare, catastrophic failures, which can create a false sense of safety. We believe the approach and results here strongly demonstrate that adversarial testing can play an important role in assessing and improving agents, but are only scratching the surface. We hope this works lays the groundwork for future research into evaluating and developing robust, deployable agents.

REFERENCES

Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. *arXiv preprint arXiv:1705.10528*, 2017.

Anayo K Akametalu, Shahab Kaynama, Jaime F Fisac, Melanie Nicole Zeilinger, Jeremy H Gillula, and Claire J Tomlin. Reachability-based safe learning with gaussian processes. In *CDC*, pp. 1424–1431. Citeseer, 2014.

Eitan Altman. *Constrained Markov decision processes*, volume 7. CRC Press, 1999.

Gabriel Barth-Maron, Matthew W Hoffman, David Budden, Will Dabney, Dan Horgan, Alistair Muldal, Nicolas Heess, and Timothy Lillicrap. Distributed distributional deterministic policy gradients. *arXiv preprint arXiv:1804.08617*, 2018.

Felix Berkenkamp, Matteo Turchetta, Angela Schoellig, and Andreas Krause. Safe model-based reinforcement learning with stability guarantees. In *Advances in Neural Information Processing Systems*, pp. 908–918, 2017.

Tom Brown, Nicholas Carlini, Chiyuan Zhang, Catherine Olsson, Paul Christiano, and Ian Goodfellow. Unrestricted adversarial examples. 2018.

James Antonio Bucklew. *Introduction to Rare Event Simulation*. Springer New York, 2004.

Yinlam Chow, Ofir Nachum, Edgar Duenez-Guzman, and Mohammad Ghavamzadeh. A lyapunov-based approach to safe reinforcement learning. *arXiv preprint arXiv:1805.07708*, 2018.

Tommaso Dreossi, Alexandre Donzé, and Sanjit A Seshia. Compositional falsification of cyber-physical systems with machine learning components. In *NASA Formal Methods Symposium*, pp. 357–372. Springer, 2017.

Logan Engstrom, Dimitris Tsipras, Ludwig Schmidt, and Aleksander Madry. A rotation and a translation suffice: Fooling cnns with simple transformations. *arXiv preprint arXiv:1712.02779*, 2017.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Volodymir Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. *arXiv preprint arXiv:1802.01561*, 2018.

Jordan Frank, Shie Mannor, and Doina Precup. Reinforcement learning in the presence of rare events. In *ICML*, pp. 336–343, 2008.

Javier García and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16:1437–1480, 2015. URL http://jmlr.org/papers/v16/garcia15a.html.

Justin Gilmer, Ryan P Adams, Ian Goodfellow, David Andersen, and George E Dahl. Motivating the rules of the game for adversarial example research. *arXiv preprint arXiv:1807.06732*, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Dan Horgan, John Quan, David Budden, Gabriel Barth-Maron, Matteo Hessel, Hado Van Hasselt, and David Silver. Distributed prioritized experience replay. *arXiv preprint arXiv:1803.00933*, 2018.

Sandy Huang, Nicolas Papernot, Ian Goodfellow, Yan Duan, and Pieter Abbeel. Adversarial attacks on neural network policies. *arXiv preprint arXiv:1702.02284*, 2017.

Lucas Janson, Edward Schmerling, and Marco Pavone. Monte carlo motion planning for robot trajectory optimization under uncertainty. In *Robotics Research*, pp. 343–361. Springer, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Wentao Li, Zhiqiang Tan, and Rong Chen. Two-stage importance sampling with mixture proposals. *Journal of the American Statistical Association*, 108(504):1350–1365, 2013.

Yen-Chen Lin, Zhang-Wei Hong, Yuan-Hong Liao, Meng-Li Shih, Ming-Yu Liu, and Min Sun. Tactics of adversarial attack on deep reinforcement learning agents. *arXiv preprint arXiv:1703.06748*, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Ajay Mandlekar, Yuke Zhu, Animesh Garg, Li Fei-Fei, and Silvio Savarese. Adversarially robust policy learning: Active construction of physically-plausible perturbations. In *IROS*, pp. 3932–3939. IEEE, 2017.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016.

Teodor Mihai Moldovan and Pieter Abbeel. Safe exploration in markov decision processes. *arXiv preprint arXiv:1205.4810*, 2012.

James. Neufeld, András György, Dale Schuurmans, and Csaba Szepesvári. Adaptive Monte Carlo via bandit allocation. In *ICML*, pp. 1944–1952, 2014.

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. *CoRR*, abs/1710.06537, 2017. URL `http://arxiv.org/abs/1710.06537`.

Lerrel Pinto, Marcin Andrychowicz, Peter Welinder, Wojciech Zaremba, and Pieter Abbeel. Asymmetric actor critic for image-based robot learning. *CoRR*, abs/1710.06542, 2017. URL `http://arxiv.org/abs/1710.06542`.

Alexander Pritzel, Benigno Uria, Sriram Srinivasan, Adria Puigdomenech, Oriol Vinyals, Demis Hassabis, Daan Wierstra, and Charles Blundell. Neural episodic control. *arXiv preprint arXiv:1703.01988*, 2017.

Gerardo Rubino and Bruno Tuffin (eds.). *Rare Event Simulation using Monte Carlo Methods*. John Wiley & Sons, 2009.

Reuven Y Rubinstein. Optimization of computer simulation models with rare events. *European Journal of Operational Research*, 99(1):89–112, 1997.

Reuven Y. Rubinstein and Dirk P. Kroese. *Simulation and the Monte Carlo method*. Wiley, 3 edition, 2017.

Edward Schmerling and Marco Pavone. Evaluating trajectory collision probability through adaptive importance sampling for safe motion planning. In *Robotics: Science and Systems 2017*, 2017.

Lukas Schott, Jonas Rauber, Wieland Brendel, and Matthias Bethge. Robust perception through analysis by synthesis. *arXiv preprint arXiv:1805.09190*, 2018.

Shai Shalev-Shwartz, Shaked Shammah, and Amnon Shashua. On a formal model of safe and scalable self-driving cars. *arXiv preprint arXiv:1708.06374*, 2017.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354, 2017.

Yang Song, Rui Shu, Nate Kushman, and Stefano Ermon. Generative adversarial examples. *arXiv preprint arXiv:1805.07894*, 2018.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

Yuchi Tian, Kexin Pei, Suman Jana, and Baishakhi Ray. Deeptest: Automated testing of deep-neural-network-driven autonomous cars. In *Proceedings of the 40th International Conference on Software Engineering*, pp. 303–314. ACM, 2018.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *Intelligent Robots and Systems (IROS), 2012 IEEE/RSJ International Conference on*, pp. 5026–5033. IEEE, 2012.

Matej Vecerík, Todd Hester, Jonathan Scholz, Fumin Wang, Olivier Pietquin, Bilal Piot, Nicolas Heess, Thomas Rothörl, Thomas Lampe, and Martin A Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *CoRR, abs/1707.08817*, 2017.

Roman Werpachowski, András György, and Csaba Szepesvári. Detecting overfitting using adversarial examples. *arXiv*, 2018.

Bernhard Wymann, Eric Espié, Christophe Guionneau, Christos Dimitrakakis, Rémi Coulom, and Andrew Sumner. Torcs, the open racing car simulator. *Software available at http://torcs. source-forge. net*, 4:6, 2000.

Yuke Zhu, Ziyu Wang, Josh Merel, Andrei A. Rusu, Tom Erez, Serkan Cabi, Saran Tunyasuvunakool, János Kramár, Raia Hadsell, Nando de Freitas, and Nicolas Heess. Reinforcement and imitation learning for diverse visuomotor skills. *CoRR, abs/1802.09564*, 2018.

A   PROOFS FOR SECTION 3.2

We start with the proof of Proposition 3.2. Let $U_t = W_t c(X_t, Z_t)$ where $W_t = p_X(X_t)/q(X_t)$. Under the condition that $p_X(x)f(x) = 0$ whenever $q(x) = 0$, $\mathbb{E}[U_t] = p$, hence $\mathbb{E}[\hat{P}] = p$.

Since $U_1, \ldots, U_n$ are independent and identically distributed, $\text{Var}[\hat{P}] = \text{Var}[U_t]/n$ for any $t \in [n]$. Hence, the variance of $\hat{P}$ is minimized when the variance of U_t is minimized. Since $\mathbb{E}[U_t] = p$, this variance is minimized when $\mathbb{E}[U_t^2] = \mathbb{E}[W_t^2 c(X_t, Z_t)] = \mathbb{E}[(W_t f_*^{1/2}(X_t))^2]$ is minimized, where we used the definition of f_* and that c is binary-valued. However, this is nothing but the second moment of the importance sampling estimator that uses the proposal distribution Q to estimate $\int P_X(dx) f_*^{1/2}(x)$. As is well known, this is minimized by the proposal distribution whose density with respect to P_X is proportional to $f_*^{1/2}$, leading to the desired claim.

Next, we prove Proposition 3.3, which stated that the rejection sampling procedure that accepts a random instance $X \sim P_X$ with probability $f^{1/2}(X)$ produces a sample from Q_f. Let U be uniformly distributed on the $[0, 1]$ interval and independent of X. Clearly, the probability that a sample produced by rejection sampling falls into a set $A \subset \mathcal{X}$ is $\mathbb{P}(X \in A | U \leq f^{1/2}(X))$. Now,

$$\mathbb{P}(X \in A | U \leq f^{1/2}(X)) = \frac{\mathbb{P}(X \in A, U \leq f^{1/2}(X))}{\mathbb{P}(U \leq f^{1/2}(X))} = \frac{\int_A \mathbb{P}(U \leq f^{1/2}(x)) P_X(x)}{\mathbb{P}(U \leq f^{1/2}(X))}$$

$$= \frac{\int_A f^{1/2}(x) P_X(x)}{\mathbb{P}(U \leq f^{1/2}(X))}.$$

Since $\mathbb{P}(X \in \cdot | U \leq f^{1/2}(X))$ is a probability measure on $\mathcal{X}$, it follows that the unconditional acceptance probability satisfies $\mathbb{P}(U \leq f^{1/2}(X)) = \int_{\mathcal{X}} f^{1/2}(x) P_X(x)$, thus showing that the distribution of accepted points is Q_f as required.

B   PSEUDOCODE FOR FPP ADVERSARY

Algorithm 2 FPP-guided Search (FPP adversary)

Input: Sample size n
repeat
    Collect random initial conditions $S = \{X_1, \ldots, X_n\}$ where $X_i \sim P_X, i \in [n]$
    Select $X = \arg\max_{x \in S} f(x)$
    Run an experiment to generate outcome $C = c(X, Z)$
until $C = 1$

C   AGENT TRAINING DETAILS

C.1   ENVIRONMENTS

For the *Driving* domain, we use the TORCS 3D car racing game (Wymann et al., 2000) with settings corresponding to the "Fast car, no bots" setting in Mnih et al. (2016). At each step, the agent receives an 15-dimensional observation vector summarizing its position, velocity, and the local geometry of the track. The agent receives a reward proportional to its velocity along the center of the track at its current position, while collisions with a wall terminate the episode and provide a large negative reward.

Each problem instance is a track shape, parameterized by a 12-dimensional vector encoding the locations and curvatures of waypoints specifying the track. Problem instances are sampled by randomly sampling a set of waypoints from a fixed distribution, and rejecting any tracks with self-intersections.

For the *Humanoid* domain, we use the Humanoid Stand task from Tassa et al. (2018). At each step, the agent receives a 67-dimensional observation vector summarizing its joint angles and velocities, and the locations of various joints in Cartesian coordinates. The agent receives a reward proportional

to its head height. If the head height is below 0.7m, the episode is terminated and the agent receives a large negative reward.

Each problem instance is defined by an initial standing pose. To define this distribution, we sample $1e5$ random trajectories from a separately trained D4PG agent. We sample a random state from these trajectories, ignoring the first 10 seconds of each trajectory, as well as any trajectories terminating in failure, to ensure all problem instances are feasible. Together, we obtain $6e7$ problem instances, so it is unlikely that any problem instance at train or test time has been previously seen.

C.2 AGENTS

We now describe the agents we used for evaluation on each task. The focus of this work is not on training agents, and hence we leave the agents fixed for all experiments. However, we did make some modifications to decrease agent failure probabilities, as we are most interested in whether we can design effective adversaries when failures are rare, and thus there is not much learning signal to guide the adversary.

On Driving, we use an asynchronous batched implementation of Advantage Actor-Critic, using a V-trace correction, following Espeholt et al. (2018), and using the same hyperparameters. The agent is trained for $1e9$ actor steps, which takes 4 hours distributed over 100 CPU workers and a single GPU learner. Since episodes are at most 3600 steps, this equates to roughly $270e3$ episodes. At test time, we take the most likely predicted action, rather than sampling, as we found it decreased the failure probability by roughly half. Additionally, we used a hand-crafted form of adversarial training by training on a more difficult distribution of track shapes, with sharper turns than the original distribution, since this decreased failure probability roughly 20-fold.

On Humanoid, we use a D4PG agent, using the same hyperparameters as Barth-Maron et al. (2018). The agent is trained for $4e6$ learner steps, which corresponds to between $250e6$ and $300e6$ actor steps, which takes 8 hours distributed over 32 CPU workers and a single GPU learner. Since episodes are at most 1000 steps, this equates to roughly $275e3$ episodes. We use different exploration rates on actors, as in Horgan et al. (2018), with noise drawn from a normal distribution with standard deviation σ evenly spaced from 0.0 to 0.4. We additionally use demonstrations from the agent described in the previous section, which was used for defining the initial pose distribution, following Vecerík et al. (2017). In particular, we use 1000 demonstration trajectories, and use demonstration data for half of each batch to update both the critic and policy networks. This results in a roughly 4-fold improvement in the failure rate.

D EXPERIMENTAL DETAILS

D.1 FPP DETAILS

When constructing the training datasets, we ignore the beginning of training during which the agent fails very frequently. This amounts to using the last $150,000$ episodes of data on Driving and last $200,000$ on Humanoid. To include information about the training iteration of the agent, we simply include a single real value, the current training iteration divided by the maximum number of training iterations. Similarly, for noise applied to the policy, we include the amount of noise divided by the maximum amount of noise. These are all concatenated before applying the MLP. We train both FPP models to minimize the cross-entropy loss, with the Adam optimizer (Kingma & Ba, 2014), for $20,000$ and $40,000$ iterations on Driving and Humanoid respectively, which requires 4.5 and 50 minutes respectively on a single GPU.

On Driving, the FPP architecture uses a 4-layer MLP with 32 hidden units per layer and a single output, with a sigmoid activation to convert the output to a probability. On Humanoid, since failures of the most robust agents are very rare, we use a simplified Differentiable Neural Dictionary architecture (Pritzel et al., 2017) to more effectively leverage the limited number of positive training examples. In particular, to classify an input x, the model first retrieves the $K = 32$ nearest neighbors and their corresponding labels (x_i, y_i) from the training set. The final prediction is then a weighted average $(b + \sum_{i:y_i=1} w_i)/(2b + \sum_i w_i)$, where b is a learned pseudocount, which allows the model to make uncertain predictions when all weights are close to 0. To compute weights w_i, each point is embedded by a 1-layer MLP f into 16 dimensions, and the weight of each neighbor

Sample size n	$n_0/10$ Cost	$n_0/10$ Speedup	n_0 Cost	$10n_0$ Cost	$10n_0$ Speedup
Driving	4/23/61	0.18/0.22/0.59	3/5/11	2/3/6	1.1/1.7/2.4
Humanoid	57/173/220	0.16/0.23/0.28	19/33/56	7/11/25	1.8/2.4/3.1

Table 2: **Adversary hyperparameter sensitivity analysis.** We show the performance of Algorithm 2 for varying values of the sample size parameter n. The middle column shows results for $n = n_0$, the value we used in our experiments, and we compare to a factor of 10 larger and smaller. Costs represent expected number of episodes until a failure, and speedups are relative to when $n = n_0$. As before, each cell shows min, median, and max values across 5 agents. On both domains, applying greater optimization pressure improves results.

is computed $w_i = \kappa(f(x), f(x_i))$, where κ is a Gaussian kernel, $\kappa(x, y) = exp(\|x - y\|_2^2 /2)$. We tried different hyperparameters for the number of MLP layers on Driving, and the number of neighbors on Humanoid, and selected based on a held-out test set using data collected during training. In particular, to match real-world situations, we did not select hyperparameters based on either failure search or risk estimation experiments.

D.2 FAILURE SEARCH

We ran the VMC adversary for $5e6$ experiments for each agent. The expected cost is simply $1/p$, where p is the fraction of experiments resulting in failures. For the FPP adversary, we ran $2e4$ experiments for each agent, since failures are more common, so less experiments are necessary to estimate the failure probabilities precisely. For the PR adversary, the adversary first selected problem instances which caused failures on the actor with the least noise, most recent first, followed by the actor with the second least noise, and so on. We also tried a version which did not account for the amount of noise and simply ran the most recent failures first, which was slightly worse.

For the failure search experiments on the Humanoid domain, we always evaluate the best version of each agent according to the FPP model selection procedure from Section 4.3. We chose this because we are most interested in whether we can design effective adversaries when failures are rare, and simply choosing the final agent is ineffective, as discussed in Appendix D.4.

We now discuss the sample size parameter n in Algorithm 2. As discussed, using larger values of n applies more selection pressure in determining which problem instances to run experiments on, while using smaller values of n draws samples from a larger fraction of $\mathcal{X}$, and thus provides some robustness to inaccuracies in the learned f. Of course, other more sophisticated approaches may be much more effective in producing samples from diverse regions of $\mathcal{X}$, but we only try this very simple approach. For our experiments, we use $n = 1000$ for Driving and $n = 10000$ for Humanoid. We did not perform any hyperparameter selection on n, in order to match the real-world setting where the experimenter has only a fixed budget of experiments, and wishes to find a single failure. However, we include additional experiments to study the robustness of the FPP adversary to the choice of n. These are summarized in Table 2.

We observe that on both domains, applying greater optimization pressure improves results, over the default choices for n we used. However, relative to the improvements over the VMC adversary, these differences are small, and the FPP adversary is dramatically faster than the VMC adversary for all choices of n we tried.

D.3 RISK ESTIMATION DETAILS

In our paper, we showed that the FPP estimator can estimate the failure probability of an agent much faster than the VMC estimator. In particular, we showed in both the Driving and Humanoid domains that our estimator requires an order of magnitude less episodes to achieve a 3-approximation at any given confidence level. In general, we may be interested in a ρ-approximation, that is we might want the estimates to fall in the range $(p/\rho, p\rho)$ where p is the probability of failure that we wish to measure. One might ask whether our results are sensitive to the choice of ρ. In other words, did we select $\rho = 3$ so that our results look good? To address this concern, we include results for lower

Figure 3: This figure shows the reliability of the FPP and VMC estimators for various choices of $r = \rho$. As before, the x axis shows the number of evaluation episodes. The y-axis shows the probability that $\hat{P}$ does not belong in the interval $(p/r, pr)$. The probability is obtained by running the evaluation multiple times, and we include error bars of 2 standard errors. Note that the curves are not smooth especially for the VMC estimator. This is not because of the uncertainty in the plots but is a property of ρ-estimators when the sample size is small, that is on the order of $1/p$. For such sample sizes, increasing the sample size does not monotonically improve the estimator's accuracy.

and higher choices of ρ. We see that the FPP estimator performs significantly better than the VMC estimator across choices of ρ.

D.4 MODEL SELECTION

Measuring ground truth failure probabilities. In Figure 4, we show the "ground truth" failure probabilities used for computing model robustness in Figure 2. Each bar represents a version of the agent at a different point in training, starting from step $5e5$, and taking a new version every $7e4$ learner steps (so that there are 50 agents in total). Failure probabilities are computed by taking the fraction of experiments resulting in failures, using $160,000$ experiments per agent. As in Figure 2, we show robustness $(1/p)$ rather than failure probabilities, so that it is easier to see differences between the most robust models. Robustness should be interpreted as the expected number of experiments until seeing a failure. Thus, when we report robustness in Figure 2 for averages over multiple agents, we first average the failure probabilities of these agents, before applying the reciprocal, which represents the expected number of experiments until failure, if the agent is randomly selected from that set.

We note that the failure probabilities we report after model selection in Figure 2 are conservative, for two reasons. First, for the two agents which did not fail in our ground truth measurements, we use a failure probability of $1/160,000$ rather than 0. Second, because our ground truth measurements are only noisy measurements of the true failure probability for each agent, it is possible that even an optimal model selection algorithm would not pick the optimal agent according to our ground truth measurements. We could run the ground truth measurements for longer, but already, this required $160,000 * 50 = 8e6$ experiments, or 231 CPU-days. Nonetheless, even with these conservative estimates, the FPP estimator showed significant improvements over using the VMC estimator for model selection.

Non-monotonicity of robustness over training. Finally, we note that the robustness is not monotonically increasing, and thus simply taking the last agent (or randomly choosing from the last

Figure 4: We show the robustness for agents taken from different points in training. The failure probability of each agent is estimated using $160,000$ experiments with VMC. Note that the robustness does not improve monotonically, and that simply choosing the final agent would not provide a robust agent.

few) would be a worse model selection strategy than uniform exploration with the FPP estimator. This differs from the standard setting in deep reinforcement learning, with tightly bounded rewards, where expected return usually (roughly) monotonically increases over the course of training. As discussed in Sections 1 and 5, when the agent is optimized using VMC, failures are observed very rarely, and thus the optimization process does not effectively decrease the failure probability, which is consistent with the non-monotonicity we observe here.

E EXTENDED RELATED WORK

Learning highly reliable agents. Our results also indicate that learning highly reliable agents will likely require a significant departure from some of current practices. In particular, since for highly reliable systems failure events are extremely rare, any technique that uses vanilla Monte Carlo (that is, perhaps 99% of the current RL literature) is ought to fail to provide the necessary guarantees. This is a problem that has been studied in the simulation optimization literature, but so far it has received only little attention in the RL community (e.g., Frank et al. 2008).

The training time equivalent of our setting can be viewed as a special case of Constrained MDPs (Altman, 1999), where a cost of 1 is incurred at the final state of a catastrophic trajectory. While recent work has adapted deep reinforcement learning techniques to handle constraints, these address situations where costs are observed frequently, and the objective is to keep expected costs below some threshold (Achiam et al., 2017; Chow et al., 2018) as opposed to avoiding costs entirely, and are not designed to specifically satisfy constraints when violations would be caused by rare events. This suggests a natural extension to the rare failures case using the techniques we develop here. Related work in safe reinforcement learning (see García & Fernández, 2015, for a review) tries to avoid catastrophic failures either during learning or deployment. Approaches for safe exploration typically rely on strong knowledge of the transition dynamics (Moldovan & Abbeel, 2012), or assumptions about the accuracy of a learned model (Berkenkamp et al., 2017; Akametalu et al., 2014), and we believe are complementary to adversarial testing approaches, which make weak assumptions, but also do not provide guarantees. Finally, there has been significant recent interest in training controllers that are robust to system misspecification by exposing them to pre-specified or adversarially constructed noise applied e.g. to observation or system dynamics (Peng et al., 2017; Pinto et al., 2017; Zhu et al., 2018; Mandlekar et al., 2017)