FLOW GENERATOR MATCHING

ABSTRACT

In the realm of Artificial Intelligence Generated Content (AIGC), flow-matching models have emerged as a powerhouse, achieving success due to their robust theoretical underpinnings and solid ability for large-scale generative modeling. These models have demonstrated state-of-the-art performance, but their brilliance comes at a cost. The process of sampling from these models is notoriously demanding on computational resources, as it necessitates the use of multi-step numerical ordinary differential equations (ODEs). Against this backdrop, this paper presents a novel solution with theoretical guarantees in the form of Flow Generator Matching (FGM), an innovative approach designed to accelerate the sampling of flow-matching models into a one-step generation, while maintaining the original performance. On the CIFAR10 unconditional generation benchmark, our one-step FGM model achieves a new record Fréchet Inception Distance (FID) score of 3.08 among few-step flow-matching-based models, outperforming original 50-step flow-matching models. Furthermore, we use the FGM to distill the Stable Diffusion 3, a leading text-to-image flow-matching model based on the MM-DiT architecture. The resulting MM-DiT-FGM one-step text-to-image model demonstrates outstanding industry-level performance. When evaluated on the GenEval benchmark, MM-DiT-FGM has delivered remarkable generating qualities, rivaling other multi-step models in light of the efficiency of a single generation step.

1 INTRODUCTIONS

Over the past decade, deep generative models have achieved remarkable advancements across various applications including data generation (Karras et al., 2020b; 2022; Nichol & Dhariwal, 2021; Oord et al., 2016; Ho et al., 2022; Poole et al., 2022; Hoogeboom et al., 2022; Kim et al., 2022), density estimation (Kingma & Dhariwal, 2018; Chen et al., 2019), and image editing (Meng et al., 2021; Couairon et al., 2022). These models have notably excelled in producing high-resolution, text-driven data such as images (Rombach et al., 2022; Saharia et al., 2022; Ramesh et al., 2022; 2021; Luo, 2024), videos (Ho et al., 2022; Brooks et al., 2024), audios (Evans et al., 2024), and others (Zhang et al., 2024; Xue et al., 2023; Luo & Zhang, 2024; Luo et al., 2023b; Zhang et al., 2023; Feng et al., 2023; Deng et al., 2024; Luo et al., 2024c; Geng et al., 2024b; Wang et al., 2024; Pokle et al., 2022), pushing the boundaries of Artificial Intelligence Generated Content (AIGC).

Among the spectrum of deep generative models, flow-matching models (FMs) have emerged as particularly potent, showcasing robust performance in applications like likelihood computation (Grathwohl et al., 2018; Chen et al., 2018) and text-conditional image synthesis(Esser et al., 2024; Liu et al., 2023). Flow models utilize neural networks to parametrize a continuous-time transportation field, establishing a bijective mapping between real data and random prior noises. They are trained to learn conditional vector fields using flow-matching methods (Lipman et al., 2022b; Albergo & Vanden-Eijnden, 2022; Liu et al., 2022; Neklyudov et al., 2023). The flexible parametrization and relative ease of training make FMs versatile across various datasets and applications.

However, despite their strengths, FMs still have severe drawbacks. Primarily, sampling from FMs involves multiple evaluations of the deep neural network, leading to computational inefficiencies. This limitation restricts their broader application, especially in scenarios where efficiency is paramount. Therefore fast sampling from flow models is important though challenging.

Step-wise distillation has emerged as a viable strategy to mitigate the computational inefficiencies associated with iterative sampling processes in deep generative models, particularly for accelerating

Figure 1: Qualitative Evaluation of one-step samples from MM-DiT-FGM. Prompts used in this figure can be found in the Appendix B.2.1.

diffusion models' sampling mechanisms into more efficient one-step models (Luo et al., 2023a; Salimans & Ho, 2022; Song et al., 2023; Gu et al., 2023a; Fan et al., 2023; Fan & Lee, 2023; Aiello et al., 2023; Watson et al., 2022). While distillation has proven effective in these contexts, the application of such techniques to flow models, has not yet been thoroughly investigated. Besides, since the flow matching does not imply marginal probability densities or score functions as diffusion models do, how to introduce a probabilistic distillation approach for FMs remains challenging.

In this paper, we bridge this gap by presenting *flow generator matching* (FGM), a probabilistic framework for the one-step distillation of flow models. FGM streamlines the sampling process of flow models, making it computationally efficient as a one-step generator, while maintaining high fidelity to the original model's output. Our approach is validated against several benchmarks, such as image generation on the CIFAR10 dataset and large-scale text-to-image generation. On both tasks, we demonstrated very strong performance with only one-step generation. Besides, our experiment on distilling text-to-image flow models shows remarkable performances, marking a new record for one-step text-to-image generation of flow-based models. In conclusion, our exploration not only expands the understanding of distillation techniques but also enhances the practical utility of flow models, particularly in scenarios where quick and efficient sampling is crucial.

2 RELATED WORKS

Diffusion Distillation. Diffusion distillation (Luo, 2023) is an active research line aiming to accelerate diffusion model sampling using distillation techniques. There are mainly three lines of approaches to distill pre-trained diffusion models to obtain solid few-step models. The first line is the distribution matching method. Luo et al. (2024a) first explore diffusion distillation by minimizing the Integral KL divergence. Yin et al. (2024b) extended this concept by incorporating a data regression loss to enhance performance. Zhou et al. (2024) investigated distillation by focusing on minimizing the Fisher divergence, while Luo et al. (2024b) applied a general score-based divergence to the distillation process. Many other approaches have also studied distribution matching distillation (Nguyen & Tran, 2024; Yuda Song, 2024; Heek et al., 2024; Xie et al., 2024; Xiao et al., 2021; Xu et al., 2024). In this paper, our approach is related to distribution matching distillation. However, how to properly apply distribution matching distillation in the regime of flow models is technically difficult. The second line is the so-called trajectory distillation, which aims to use few-step models to learn the diffusion model's trajectory (Luhman & Luhman, 2021; Salimans & Ho, 2022; Geng et al., 2024a; Meng et al., 2022). Other works use the self-consistency of the diffusion model's trajectory to learn few-step models (Song et al., 2023; Kim et al., 2023; Song & Dhariwal, 2023; Liu et al., 2024; Gu et al., 2023b; Geng et al., 2024b; Salimans et al., 2024).

Acceleration of Flow Matching Models. In recent years, there have been efforts to accelerate the sampling process of flow-matching models, most current work focuses on straightening the trajectories of ordinary differential equations (ODEs). ReFlow (Liu et al., 2022) replaces the arbitrary coupling of noise and data originally used for training flow matching with a deterministic coupling generated by a teacher model, enabling the model to learn a rectified flow from the data. CFM (Yang et al., 2024) shares a similar concept with consistency models but differs by applying consistency constraints to the velocity field space instead of the sample space. This approach also serves as a form of regularization aimed at straightening the trajectories of ODEs. Though these works have demonstrated decent accelerations, they are essentially different from our proposed FGM. The FGM is built upon a probabilistic perspective that guarantees the generator distribution matches the teacher FM by minimizing the flow-matching objective. Besides, as we show in Section 5.1, the FGM outperforms the mentioned methods with significant margins.

3 BACKGROUNDS

Flow-matching Models. Let $\mathbb{R}^d$ represent the data space with data points $\boldsymbol{x} = (\boldsymbol{x}^1, \ldots, \boldsymbol{x}^d) \in \mathbb{R}^d$. Let $q_1(\boldsymbol{x}_1)$ be a simple noise distribution while $q_0(\boldsymbol{x}_0)$ is the data distribution. Let $\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$ be a known conditional vector field that implies the conditional probabilistic transition $q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$. The marginal distribution densities $q_t(\boldsymbol{x}_t)$ form a path that links noise distribution $q_1(\boldsymbol{x}_1)$ and data distribution $q_0(\boldsymbol{x}_0)$, i.e. $q_1(\boldsymbol{x}|\boldsymbol{x}_0) = q_1(\boldsymbol{x})$ and $q_0(\boldsymbol{x}|\boldsymbol{x}_0) = \delta(\boldsymbol{x} - \boldsymbol{x}_0)$. Then, one can further define a corresponding marginal vector field (3.2) that translates particles drawn from noise distributions to obtain samples following the data distribution,

$$q_t(\boldsymbol{x}_t) = \int q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)q_0(\boldsymbol{x}_0)\mathrm{d}\boldsymbol{x}_0 \tag{3.1}$$

$$\boldsymbol{u}_t(\boldsymbol{x}_t) = \int \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)q_0(\boldsymbol{x}_0)}{q_t(\boldsymbol{x}_t)}\mathrm{d}\boldsymbol{x}_0. \tag{3.2}$$

Let $\boldsymbol{v}_\theta(\cdot, \cdot)$ be a vector field parametrized by a deep neural network. The goal of flow matching is to train $\boldsymbol{v}_\theta(\cdot, \cdot)$ to approximate the marginal flow $\boldsymbol{u}_t(\cdot)$ by minimizing the objective (3.3):

$$\mathcal{L}_{FM}(\theta) := \mathbb{E}_{t, \boldsymbol{x}_t \sim q_t(\boldsymbol{x}_t)}\|\boldsymbol{v}_\theta(\boldsymbol{x}_t, t) - \boldsymbol{u}_t(\boldsymbol{x}_t)\|^2. \tag{3.3}$$

Although (3.3) represents the optimal target for optimization, the lack of the explicit expression about $\boldsymbol{u}_t(\boldsymbol{x}_t)$ renders the computation impractical. To address this challenge, Lipman et al. (2022a) introduced flow-matching, a tractable alternative objective of (3.3). Lipman et al. (2022a) shows that one can minimize a simpler yet equivalent objective (3.4):

$$\mathbb{E}_{\substack{t, \boldsymbol{x}_0 \sim q_0(\boldsymbol{x}_0), \\ \boldsymbol{x}_t \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}} \|\boldsymbol{v}_\theta(\boldsymbol{x}_t, t) - \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\|^2, \tag{3.4}$$

with $\boldsymbol{x}_t$ is sampled from $q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$. The main insight of flow-matching is that the tractable objective (3.4) shares the same θ gradient as (3.3).

Practical Instance of Flow Matching Models. In this paper, we especially consider a widely used flow matching model, the rectified flow (ReFlow) (Liu et al., 2022; Albergo & Vanden-Eijnden, 2022) as a specific instance. Our theory and algorithms for the general flow-matching model share the same concepts as the ones based on ReFlow. The ReFlow defines the conditional vector field as

$$\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) = \frac{\boldsymbol{x}_0 - \boldsymbol{x}_t}{1 - t}. \tag{3.5}$$

This results in a simple training objective as

$$\mathcal{L}_{ReFlow}(\theta) = \mathbb{E}_{\substack{t, \boldsymbol{x}_0 \sim q_0(\boldsymbol{x}_0), \boldsymbol{x}_1 \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{I}), \\ \boldsymbol{x}_t = (1-t)\boldsymbol{x}_0 + t\boldsymbol{x}_1}} \|\boldsymbol{v}_\theta(\boldsymbol{x}_t, t) - (\boldsymbol{x}_1 - \boldsymbol{x}_0)\|_2^2 \tag{3.6}$$

The ReFlow objective (3.6) can be interpreted as using a neural network $\boldsymbol{v}_\theta(\boldsymbol{x}_t, t)$ to predict the direction from noises to data samples. In experiment Sections 5.1, we pretrain a flow model in-house using the ReFlow objective (3.6). In Section 5.2, the Stable Diffusion 3 model is also trained with the ReFlow objective.

4 FLOW GENERATOR MATCHING

In this section, we introduce Flow Generator Matching (FGM), a general method tailored for the one-step distillation of flow-matching models. We begin by defining problem setup and notations. Then we introduce our matching objective function and how FGM minimizes this objective. Finally, we compare FGM with existing flow distillation approaches, highlighting the empirical and theoretical advantages of our methods.

4.1 PROBLEM SETUPS

Problem Formulation. Our framework is built upon a pre-trained flow-matching model that accurately approximates the marginal vector field $\boldsymbol{u}_t(\boldsymbol{x}_t)$. The flow $\boldsymbol{u}_t(\boldsymbol{x}_t)$ bridges the noise and data distribution. We also know the conditional transition $q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$ which implies $\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$. Assume the pre-trained flow matching model provides a sufficiently good approximation of data distribution, i.e., q_0 is the ground truth data distribution.

Our goal is to train a one-step generator model g_θ, which directly transports a random noise $\boldsymbol{z} \sim p_z$ to obtain a sample $\boldsymbol{x}_0 = g_\theta(\boldsymbol{z})$. Let $p_{\theta,0}$ denote the distribution of the student model over the generated sample $\boldsymbol{x}$, and $p_{\theta,t}$ denote the marginal probability path transitioned with $q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$, i.e.,

$$p_{\theta,t}(\boldsymbol{x}_t) = \int q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)d\boldsymbol{x}_0$$

This student marginal probability path implicitly induces a flow vector field $\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)$ generating the path, which is unknown yet intractable.

Intractable Objective. One-step flow generator matching aims to let the student distribution $p_{\theta,0}$ match the data distribution q_0. For this, we consider matching the marginal vector field $\boldsymbol{v}_{\theta,t}$ with the pre-trained one $\boldsymbol{u}_t$ such that the distributions $p_{\theta,0}$ and q_0 can match with one another.

In this section, we define the objective for flow generator matching. Based on previous discussions, our goal is to minimize the expected L^2 distance between the implicit vector field $\boldsymbol{v}_{\theta,t}$ and the pre-trained flow model's vector field $\boldsymbol{u}_t$, which writes

$$\mathcal{L}_{FM}(\theta) := \mathbb{E}_{t, \boldsymbol{x}_t \sim p_{\theta,t}} \|\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) - \boldsymbol{u}_t(\boldsymbol{x}_t)\|^2 \tag{4.1}$$

$$= \mathbb{E}_{\substack{t, \boldsymbol{z} \sim p_z(\boldsymbol{z}), \boldsymbol{x}_0 = g_\theta(\boldsymbol{z}), \\ \boldsymbol{x}_t \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}} \|\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) - \boldsymbol{u}_t(\boldsymbol{x}_t)\|^2 \tag{4.2}$$

Notice that the sample $\boldsymbol{x}_t$ is dependent on the parameter θ. We may use $\boldsymbol{x}_t(\theta)$ to emphasize such a parameter reliance if necessary.

It is clear to see that the $\mathcal{D}_{FM}(p_{\theta,0}, q_0) = 0$ if and only if all induced vector fields meet, i.e. $\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) = \boldsymbol{u}_t(\boldsymbol{x}_t)$ a.s. $p_{\theta,t}$. Therefore it induces that $p_t(\boldsymbol{x}_t) = q_t(\boldsymbol{x}_t)$, a.s. $p_{\theta,t}$, which shows that the two distributions $p_{\theta,0}(\boldsymbol{x}_0) = q_0(\boldsymbol{x}_0)$, a.s. $p_{\theta,0}$ that match with one anther. Unfortunately, though minimizing objective (4.1) leads to a strong one-step generator, it is intractable because we do not know the relation between $\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)$ and the generator distribution $p_{\theta,0}$. In the next paragraph, we will bring our main contribution: a tractable yet equivalent training objective as (4.1) with theoretical guarantees.

4.2 TRACTABLE OBJECTIVE

Our goal is to optimize the parameter θ to minimize the objective (4.1). However, the implicit vector field $\boldsymbol{v}_{\theta,t}$ is unknown yet intractable. Therefore it is impossible to directly minimize the objective. However, by taking the gradient of the loss function (4.1) over θ, we have

$$\frac{\partial}{\partial\theta}\mathcal{L}_{FM}(\theta) = \frac{\partial}{\partial\theta}\mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\boldsymbol{x}_t}\left\{\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2\right\}\frac{\partial\boldsymbol{x}_t(\theta)}{\partial\theta} - 2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$= \text{Grad}_1(\theta) + \text{Grad}_1(\theta). \tag{4.3}$$

Where $\text{Grad}_1(\theta)$ and $\text{Grad}_2(\theta)$ are defined with

$$\text{Grad}_1(\theta) = \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\boldsymbol{x}_t}\left\{\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2\right\}\frac{\partial\boldsymbol{x}_t(\theta)}{\partial\theta}\right\}, \tag{4.4}$$

$$\text{Grad}_2(\theta) = \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{-2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}. \tag{4.5}$$

The gradients in (4.3) consider all derivatives concerning the parameter θ. We put the detailed derivation in Appendix A.1.

Notice that the first gradient $\text{Grad}_1(\theta)$ can be obtained if we stop the θ-gradient for $\boldsymbol{v}_{\theta,t}(\cdot)$, i.e. $\boldsymbol{v}_{\text{sg}[\theta],t}(\cdot)$. This results in an alternative loss function whose gradient coincides with $\text{Grad}_1(\theta)$,

$$\mathcal{L}_1(\theta) = \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t)\|_2^2\right\}$$

$$= \mathbb{E}_{\substack{t,\boldsymbol{z}\sim p_z,\boldsymbol{x}_0=g_\theta(\boldsymbol{z}),\\\boldsymbol{x}_t\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t)\|_2^2\right\} \tag{4.6}$$

However, the second gradient (4.5) involves an intractable term $\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\cdot)$. For the student generator, we only have efficient samples from the conditional probability path, but the vector field $\boldsymbol{v}_{\theta,t}(\cdot)$ along with its θ gradient is unknown. Fortunately, in this paper we have the following Theorem 4.2, allowing for a more tractable θ-gradient of the student vector field. Before that, we need to first introduce a novel Flow Product Identity in Theorem 4.1, which is one of our contributions.

Theorem 4.1 (Flow Product Identity). Let $\mathbf{f}(\cdot,\theta)$ be a vector-valued function, using the notations in Section 4.1, under mild conditions, the identity holds:

$$\mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) = \mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\\boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) \tag{4.7}$$

We put the proof of Flow Product Identity 4.1 in Appendix A.2.

Next, we show that we can introduce an equivalent tractable loss function that has the same parameter gradient as the intractable loss (4.1) in Theorem 4.2.

Theorem 4.2. If distribution $p_{\theta,t}$ satisfies some wild regularity conditions, then we have for all θ-parameter free vector-valued function $\boldsymbol{u}_t(\cdot)$, the equation holds for all parameter θ:

$$\mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\left\{-2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$= \frac{\partial}{\partial\theta}\mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\\boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t)\right\}^T\left\{\boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t) - \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\right\}\right\} \tag{4.8}$$

We put the detailed proof in Appendix A.3. The identity (4.8) shows that the expectation of the intractable gradient $\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}$ can be traded with a tractable expectation with differentiable samples from the student model.

It is a direct result of the identity (4.8) that the gradient $\text{Grad}_2(\theta)$ coincides with the following tractable loss function (4.9) with a stop-graident operation sg imposed on θ in the generator vector,

$$\mathcal{L}_2(\theta) = \mathbb{E}_{\substack{t,\boldsymbol{z}\sim p_z,\boldsymbol{x}_0=g_\theta(\boldsymbol{z}),\\\boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t)\right\}^T\left\{\boldsymbol{v}_{\text{sg}[\theta],t}(\boldsymbol{x}_t) - \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\right\}\right\}. \tag{4.9}$$

Algorithm 1: Flow Generator Matching Algorithm for training one-step Generators.

Input: pre-trained flow matching model $\boldsymbol{u}_t(\cdot)$, one-step generator g_θ, prior distribution p_z,
online flow model $\boldsymbol{v}_\psi(\cdot)$, time $t \in \mathcal{U}[0, 1]$, and conditional transition $q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$.

while *not converge* **do**

freeze θ, update ψ using SGD by minimizing the flow matching loss

$$\mathcal{L}_{FM}(\psi) = \mathbb{E}_{\substack{t, \boldsymbol{z} \sim p_z, \boldsymbol{x}_0 = g_\theta(\boldsymbol{z}), \\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}} \|\boldsymbol{v}_\psi(\boldsymbol{x}_t, t) - \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\|_2^2.$$

freeze ψ, update θ using SGD with by minimizing the FGM loss (4.10):

$$\mathcal{L}_{FGM}(\theta) = \mathcal{L}_1(\theta) + \mathcal{L}_2(\theta)$$

$$\mathcal{L}_1(\theta) = \mathbb{E}_{\substack{t, \boldsymbol{z} \sim p_z, \boldsymbol{x}_0 = g_\theta(\boldsymbol{z}), \\ \boldsymbol{x}_t \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}} \left\{ \|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta], t}(\boldsymbol{x}_t)\|_2^2 \right\} \qquad (4.11)$$

$$\mathcal{L}_2(\theta) = \mathbb{E}_{\substack{t, \boldsymbol{z} \sim p_z, \boldsymbol{x}_0 = g_\theta(\boldsymbol{z}), \\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}} \left\{ 2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\text{sg}[\theta], t}(\boldsymbol{x}_t)\}^T \{\boldsymbol{v}_{\text{sg}[\theta], t}(\boldsymbol{x}_t) - \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\} \right\}$$
$$(4.12)$$

end
return θ, ψ.

Putting together (4.6) and (4.9) in terms of (4.3), we have an equivalent loss to minimize the original objective, that is

$$\mathcal{L}_{FGM}(\theta) = \mathcal{L}_1(\theta) + \mathcal{L}_2(\theta), \qquad (4.10)$$

with $\mathcal{L}_1(\theta)$ and $\mathcal{L}_2(\theta)$ defined in (4.6) and (4.9). This gives rise to the proposed Flow Generator Matching (FGM) objective by minimizing the loss function (4.10). Algorithm 1 summarizes the pseudo algorithm of the flow generator matching by distilling the pre-trained flow matching model into a one-step student generator.

Differences From Diffusion Distillations The FGM gets inspiration from one-step diffusion distillation by minimizing the distribution divergences (Luo et al., 2024a; Zhou et al., 2024; Luo et al., 2024b), however, the resulting theory is essentially different from those of one-step diffusion distillation. The most significant difference between FGM and one-step diffusion distillation is that the flow matching does not imply an explicit modeling of either the probability density as the diffusion models do. Therefore, the definitions of distribution divergences can not be applied to flow models as well as its distillation. However, the FGM overcomes such an issue by directly working with the flow-matching objective instead of distribution divergence. The main insight is that our proposed explicit-implicit gradient equivalent theory bypasses the intractable flow-matching objective, resulting in strong practical algorithms with theoretical guarantees. We think Theorem 4.2 may also bring novel contributions to other future studies on flow-matching models.

Comparison with Other Flow Distillation Methods There are few existing works that try to accelerate flow models to single-step or few-step generative models. The consistency flow matching (CFM) (Yang et al., 2024) is a most recent work that distills pre-trained flow models into one or two-step models. Though CFM has shown decent results, it is different from our FGM in both theoretical and practical aspects. First, the theory behind CFM is built on the trajectory consistency of flow models, which is directly generalized from consistency models(Song et al., 2023; Song & Dhariwal, 2023; Geng et al., 2024b). On the contrary, our FGM is motivated by starting from flow-matching objectives, trying to train the one-step generator's implicit flow with the ground truth teacher flow, with theoretical guarantees. On the practical aspects, on CIFAR10 generation, we show that our trained one-step FGM models archive a new SoTA FID of 3.08 among flow-based models, outperforming CFM's best 2-step generation result with an FID of 5.34. Such strong empirical performance marks the FGM as a solid solution for accelerating flow-matching models on standard benchmarks. Besides the toyish CIFAR10 generation, in Section 5.2 we also use FGM to distill

leading large-scale text-to-image flow models, obtaining a very robust one-step text-to-image model with almost no performance declines.

5 EXPERIMENTS

We conducted experiments to evaluate the effectiveness and flexibility of FGM. Our experiments cover the standard evaluation benchmark, unconditional CIFAR10 image generation, and large-scale text-to-image generation using Stable Diffusion 3 (SD3) (Esser et al., 2024). These experiments demonstrate the FGM's capability to build efficient one-step generators while maintaining high-quality samples.

5.1 ONE-STEP CIFAR10 GENERATION

Experiment Settings. We first evaluated the effectiveness of FGM on the CIFAR10 dataset (Krizhevsky et al., 2014), the standard testbed for generative model performances. We pre-train flow matching models on CIFAR10 conditional and unconditional generation using ReFlow objective (3.6). We refer to the neural network architecture used for EDM model(Karras et al., 2022). We train both conditional and unconditional models with a batch size of 512 for 20000k images, the resulting in-house-trained flow model shows a CIFAR10 unconditional FID of 2.52 with 300 generation steps, which is slightly worse than the original ReFlow model (Liu et al., 2022) which has an FID of 2.58 using 127 generation steps. However, in Table 1, we find such a slightly worse model does not influence the distillation of a strong one-step generator.

These flow models serve as the teacher models for flow generator matching (FGM). Then we apply FGM to distill one-step generators from flow models. We assess the quality of generated images via Frechet Inception Distance (FID) (Heusel et al., 2017). Lower FID scores indicate higher sample quality and diversity.

Notice that loss (4.11) and loss (4.12) together composite a full parameter gradient of the FGM loss. We find two losses works great for toyish 2D dataset generations using only Multi-layer perceptions. In practice, we find that using loss (4.11) on CIFAR10 models leads to instability, which is a similar observation as Poole et al. (2022) that the condition number of its Jacobian term might be ill-posed. Therefore we do not use loss (4.11) when training and observing good performances. Training details and hyperparameters are shown in Appendix B.1.

Initialize Generator with Pretrained Flow Models Inspired by techniques in diffusion distillation, we initialize the one-step generator with the pre-trained flow models. Recall the flow model's training objective (3.6), the pre-trained flow model $\boldsymbol{v}_\theta(\boldsymbol{x}_t, t)$ approximately predict the direction from random noise to data. Therefore, we use the pre-trained flow to construct our one-step generator. Particularly, we construct the one-step generator with

$$\widehat{\boldsymbol{x}}_0 = (1 - t^*)^* \boldsymbol{z} + t^* \boldsymbol{v}_\theta(t^* \boldsymbol{z}, t^*), \boldsymbol{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}). \tag{5.1}$$

The θ is the learnable parameter of the generator, while the t^* is a pre-determined optimal timestep.

Quantitative Evaluations. We evaluate each model with the Fretchet Inception Distance (FID) (Heusel et al., 2017), which is a golden standard for evaluating image generation results on the CIFAR10 dataset. Table 1 and Table 2 summarize the FIDs of generative models on CIFAR10 datasets. On unconditional generation, our teacher flow model has an FID of 3.67 and 2.93 with 50 and 100 generation steps respectively. However, our one-step FGM model achieves an FID of **3.08** using only one generation step, outperforming the teacher model with 50 generation steps with a significant margin of **16%**. On CIFAR10 conditional generation, our one-step FGM model has an FID of **2.58**, outperforming the teacher flow with 100 generation steps which have an FID of **2.87**. In conclusion, our results on CIFAR10 generation benchmarks demonstrate the superior performance of FGM in that it can outperform the multi-step teacher flow model with significant margins.

The CIFAR-10 generation tasks are much toyish. In Section 5.2, we perform experiments to train large-scale one-step text-to-image generators by distilling from top-performing transformer-based flow models for text-to-image generation. In the next section, we show that the one-step T2I generator distilled by FGM demonstrates state-of-the-art results over other industry-level models.

Table 1: Unconditional sample quality on CIFAR-10. † means method we reproduced.

FAMILY	METHOD	NFE (↓)	FID (↓)
DIFFUSION & GAN	DDPM (Ho et al., 2020)	1000	3.17
	DD-GAN(T=2) (Xiao et al., 2021)	2	4.08
	KD Luhman & Luhman (2021)	1	9.36
	TDPM (Zheng et al., 2023)	1	8.91
	DFNO (Zheng et al., 2022)	1	4.12
	STYLEGAN2-ADA (Karras et al., 2020a)	1	2.92
	STYLEGAN2-ADA+DI (Luo et al., 2023a)	1	2.71
	EDM (Karras et al., 2022)	35	1.97
	EDM (Karras et al., 2022)	15	5.62
	PD (Salimans & Ho, 2022)	2	5.13
	CD (Song et al., 2023)	2	2.93
	GET (Geng et al., 2024a)	1	6.91
	CT (Song et al., 2023)	1	8.70
	iCT-DEEP (Song & Dhariwal, 2023)	2	2.24
	Diff-Instruct (Luo et al., 2023a)	1	4.53
	DMD (Yin et al., 2024b)	1	3.77
	CTM (Kim et al., 2023)	1	1.98
	CTM (Kim et al., 2023)	2	**1.87**
	SiD ($\alpha = 1.0$) (Zhou et al., 2024)	1	1.92
	SiD ($\alpha = 1.2$) (Zhou et al., 2024)	1	2.02
	DI†	1	3.70
FLOW-BASED	1-ReFlow (+distill) (Liu et al., 2022)	1	6.18
	2-ReFlow (+distill) (Liu et al., 2022)	1	4.85
	3-ReFlow (+distill) (Liu et al., 2022)	1	5.21
	CFM (Yang et al., 2024)	2	5.34
	FLOW	100	**2.93**
	FLOW	50	3.67
	FGM (OURS)	1	3.08

Table 2: Class-conditional sample quality on CIFAR10 dataset. † means method we reproduced.

FAMILY	METHOD	NFE (↓)	FID (↓)
DIFFUSION & GAN	BigGAN (Brock et al., 2019)	1	14.73
	BigGAN+Tune (Brock et al., 2019)	1	8.47
	STYLEGAN2 (Karras et al., 2020b)	1	6.96
	MultiHinge (Kavalerov et al., 2021)	1	6.40
	FQ-GAN (Zhao et al., 2020)	1	5.59
	STYLEGAN2-ADA (Karras et al., 2020a)	1	2.42
	STYLEGAN2-ADA+DI (Luo et al., 2023a)	1	2.27
	STYLEGAN2 + SMaRt (Xia et al., 2023)	1	2.06
	STYLEGAN-XL (Sauer et al., 2022)	1	1.85
	STYLESAN-XL (Takida et al., 2023)	1	**1.36**
	EDM (Karras et al., 2022)	35	1.82
	EDM (Karras et al., 2022)	20	2.54
	EDM (Karras et al., 2022)	10	15.56
	EDM (Karras et al., 2022)	1	314.81
	GET (Geng et al., 2024a)	1	6.25
	Diff-Instruct (Luo et al., 2023a)	1	4.19
	DMD (w.o. reg) (Yin et al., 2024b)	1	5.58
	DMD (w.o. KL) (Yin et al., 2024b)	1	3.82
	DMD (Yin et al., 2024b)	1	2.66
	CTM (Kim et al., 2023)	1	1.73
	CTM (Kim et al., 2023)	2	1.63
	GDD (Zheng & Yang, 2024)	1	1.58
	GDD-I (Zheng & Yang, 2024)	1	1.44
	SiD ($\alpha = 1.0$) (Zhou et al., 2024)	1	1.93
	SiD ($\alpha = 1.2$) (Zhou et al., 2024)	1	1.71
FLOW-BASED	**FLOW**	100	2.87
	FLOW	50	3.66
	FGM (OURS)	1	**2.58**

5.2 TEXT-TO-IMAGE GENERATION

Experiments Settings. Our goal in this section is to use FGM to train strong one-step text-to-image generators by distillation from leading flow-matching models. For our text-to-image experiments, we selected Stable Diffusion 3 Medium as our teacher model. This model adopts a novel architecture called MMDiT, which enhances performance in image quality, typography, complex prompt understanding, and resource efficiency. For the dataset, we utilized the Aesthetics 6.25+ prompts dataset along with its recaption prompts and sam-recaption data from Chen et al. (2023) for training, comprising approximately 2 million entries. This extensive dataset significantly improves our model's ability to generate high-quality images. Similar to our observation in CIFAR10 generation, we find loss (4.11) leads to unstable training dynamic, therefore we also abandon it when training text-to-image models.

Quantitative Evaluations. We followed the evaluation metrics used for Stable Diffusion 3 technical report (Esser et al., 2024), and we referenced GenEval metrics to more comprehensively assess the model's response to complex input texts. For the evaluations we conduct, we utilize the configuration recommended by the authors. Our distilled model demonstrates promising results, remaining competitive with other models that require multiple generation steps, even when using only a single generation step.

Qualitative Evaluations. In this study, we conducted qualitative evaluations of our proposed distillation approach to analyze its performance. Figure 2 showcases several sample outputs, comparing our teacher model, Hyper-SD3(Ren et al., 2024), and Flash-SD3(Chadebec et al., 2024) methods. The results demonstrate high visual quality, particularly in detail and color reproduction, even with only a single generation step. Especially, the one-step MM-DiT-FGM shows aesthetic lightning on each generated image. Compared to existing distillation methods, our model achieves comparable generation quality at a significantly lower cost. Such an advantage makes the FGM plausible in applications when real-time interactions are strictly needed.

Integration of GAN Loss. It is clear that the pure FGM algorithm 1 does not rely on any image data when training. In recent years, many studies have shown that incorporating GAN loss into distillation is beneficial for improving high-frequency details on generated images (Yin et al., 2024a; Sauer et al., 2023; 2024). Therefore, we also incorporate a GAN loss with FGM for training one-step text-to-image models and find benefits.

During the training process, we observed that in certain intervals of noise schedules where FGM is inefficient, the GAN loss can provide effective gradients to improve the quality of the model's

| SD3 (28 steps) | Hyper-SD3 (4 steps) | Flash-SD3 (4 steps) | Ours (1 step) |

Figure 2: The visual comparison between our **MM-DiT-FGM** and other methods. From left to right, the **first column** is 28-step SD3 model(Esser et al., 2024), the **second column** is the 4-step Hyper-SD3 model(Ren et al., 2024), the **third column** is the 4-step Flash-SD3 model(Chadebec et al., 2024). The prompts for these images are provided in B.2.1

outputs. Therefore, we believe that a significant advantage of GAN loss is its ability to compensate for the inefficiencies of FGM training in certain noise schedules, thereby complementing our loss.

6 CONCLUSION

In this paper, we introduce flow-generator matching (FGM), a strong probabilistic one-step distillation approach for flow-matching models. We establish the theoretical foundations of FGM. We also validate the strong empirical performances of FGM on both one-step CIFAR10 generation and large-scale one-step text-to-image generation.

Though FGM has a solid theoretical foundation as well as strong empirical performances, it still has limitations. The first limitation is that currently the FGM still requires an additional flow model that is used for approximating the generator-induced flow vectors. This requirement asks for additional memory costs for distillation and potentially brings challenges when pre-trained flow models and the

FGM-1Step CIFAR10 Cond, FID=2.58   Flow-50Step CIFAR10 Cond, FID=3.66   **FGM-1Step CIFAR10 Uncond, FID=3.08**   Flow-50Step CIFAR10 Uncond, FID=3.67

Figure 3: Visualizations of generated samples from FGM-1step models and 50-step teacher flow models on CIFAR10 datasets. On both conditional and unconditional generation, FGM-1step models outperform 50-step teacher flow models.

| | | Objects | | | | | Color | |
Model	Overall	Single	Two	Counting	Colors	Position	Attribution	NFEs
minDALL-E(Zeqiang et al., 2023)	0.23	0.73	0.11	0.12	0.37	0.02	0.01	-
SD v1.5(Rombach et al., 2022)	0.43	0.97	0.38	0.35	0.76	0.04	0.06	50
PixArt-alpha(Chen et al., 2023)	0.48	*0.98*	0.50	0.44	0.80	0.08	0.07	40
SD v2.1(Rombach et al., 2022)	0.50	*0.98*	0.51	0.44	0.85	0.07	0.17	50
DALL-E 2	0.52	0.94	0.66	0.49	0.77	0.10	0.19	-
SDXL(Podell et al., 2023)	0.55	*0.98*	0.74	0.39	0.85	0.15	0.23	50
SDXL Turbo (Sauer et al., 2023)	0.55	**1.00**	0.72	0.49	0.80	0.10	0.18	1
IF-XL	0.61	0.97	0.74	**0.66**	0.81	0.13	0.35	100
DALL-E 3(James Betker et al., 2023)	0.67	0.96	0.87	0.47	0.83	**0.43**	*0.45*	-
SD3†(Esser et al., 2024),	**0.70**	0.99	**0.88**	0.60	0.85	0.30	**0.59**	28
Hyper-SD3†(Ren et al., 2024)	0.63	**1.00**	0.74	0.56	*0.84*	0.22	0.42	4
Flash-SD3†(Chadebec et al., 2024)	0.67	0.99	0.77	*0.59*	**0.86**	*0.28*	0.54	4
Ours	*0.65*	**1.00**	*0.82*	0.58	0.83	0.20	0.46	1

Table 3: **GenEval metrics**. Our distilled model closely matches the performance of the teacher model SD3 (depth=24) on GenEval (Ghosh et al., 2024). Same as Esser et al. (2024) we highlight the **best**, second best, and *third best* entries. (†indicates that the metrics were evaluated by us.)

generators are of large model sizes. Secondly, the FGM is a purely image-data-free approach, which means that it does not need real image data when distilling. However, as a well-known argument, consistently incorporating high-quality image data is important to improve the performances of text-to-image generative models. We hope that future works will explore how to integrate data into the distillation process.

REFERENCES

Emanuele Aiello, Diego Valsesia, and Enrico Magli. Fast inference in denoising diffusion models via mmd finetuning. *ArXiv*, abs/2301.07969, 2023.

Michael S Albergo and Eric Vanden-Eijnden. Building normalizing flows with stochastic interpolants. *arXiv preprint arXiv:2209.15571*, 2022.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1xsqj09Fm.

Tim Brooks, Bill Peebles, Connor Holmes, Will DePue, Yufei Guo, Li Jing, David Schnurr, Joe Taylor, Troy Luhman, Eric Luhman, Clarence Ng, Ricky Wang, and Aditya Ramesh. Video generation models as world simulators. 2024. URL https://openai.com/research/video-generation-models-as-world-simulators.

Clement Chadebec, Onur Tasar, Eyal Benaroche, and Benjamin Aubin. Flash diffusion: Accelerating any conditional diffusion model for few steps image generation. *arXiv preprint arXiv:2406.02347*, 2024.

Junsong Chen, Jincheng Yu, Chongjian Ge, Lewei Yao, Enze Xie, Yue Wu, Zhongdao Wang, James Kwok, Ping Luo, Huchuan Lu, et al. Pixart-α: Fast training of diffusion transformer for photorealistic text-to-image synthesis. *arXiv preprint arXiv:2310.00426*, 2023.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural Ordinary Differential Equations. In *Advances in neural information processing systems*, pp. 6571–6583, 2018.

Ricky TQ Chen, Jens Behrmann, David K Duvenaud, and Jörn-Henrik Jacobsen. Residual flows for invertible generative modeling. In *Advances in Neural Information Processing Systems*, pp. 9916–9926, 2019.

Guillaume Couairon, Jakob Verbeek, Holger Schwenk, and Matthieu Cord. Diffedit: Diffusion-based semantic image editing with mask guidance. *ArXiv*, abs/2210.11427, 2022.

Wei Deng, Weijian Luo, Yixin Tan, Marin Biloš, Yu Chen, Yuriy Nevmyvaka, and Ricky TQ Chen. Variational schr\" odinger diffusion models. *arXiv preprint arXiv:2405.04795*, 2024.

Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first International Conference on Machine Learning*, 2024.

Zach Evans, Julian D Parker, CJ Carr, Zack Zukowski, Josiah Taylor, and Jordi Pons. Stable audio open. *arXiv preprint arXiv:2407.14358*, 2024.

Ying Fan and Kangwook Lee. Optimizing ddpm sampling with shortcut fine-tuning. *ArXiv*, abs/2301.13362, 2023.

Ying Fan, Olivia Watkins, Yuqing Du, Hao Liu, Moonkyung Ryu, Craig Boutilier, P. Abbeel, Mohammad Ghavamzadeh, Kangwook Lee, and Kimin Lee. Dpok: Reinforcement learning for fine-tuning text-to-image diffusion models. *ArXiv*, abs/2305.16381, 2023.

Yasong Feng, Weijian Luo, Yimin Huang, and Tianyu Wang. A lipschitz bandits approach for continuous hyperparameter optimization. *arXiv preprint arXiv:2302.01539*, 2023.

Zhengyang Geng, Ashwini Pokle, and J Zico Kolter. One-step diffusion distillation via deep equilibrium models. *Advances in Neural Information Processing Systems*, 36, 2024a.

Zhengyang Geng, Ashwini Pokle, William Luo, Justin Lin, and J Zico Kolter. Consistency models made easy. *arXiv preprint arXiv:2406.14548*, 2024b.

Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. Geneval: An object-focused framework for evaluating text-to-image alignment. *Advances in Neural Information Processing Systems*, 36, 2024.

Will Grathwohl, Ricky TQ Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. In *International Conference on Learning Representations*, 2018.

Jiatao Gu, Shuangfei Zhai, Yizhe Zhang, Lingjie Liu, and Joshua M. Susskind. Boot: Data-free distillation of denoising diffusion models with bootstrapping. *ArXiv*, abs/2306.05544, 2023a.

Jiatao Gu, Shuangfei Zhai, Yizhe Zhang, Lingjie Liu, and Joshua M Susskind. Boot: Data-free distillation of denoising diffusion models with bootstrapping. In *ICML 2023 Workshop on Structured Probabilistic Inference {\&} Generative Modeling*, 2023b.

Jonathan Heek, Emiel Hoogeboom, and Tim Salimans. Multistep consistency models. *arXiv preprint arXiv:2403.06807*, 2024.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local Nash equilibrium. In *Advances in Neural Information Processing Systems*, pp. 6626–6637, 2017.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Jonathan Ho, Tim Salimans, Alexey Gritsenko, William Chan, Mohammad Norouzi, and David J Fleet. Video diffusion models. *arXiv preprint arXiv:2204.03458*, 2022.

Emiel Hoogeboom, Vıctor Garcia Satorras, Clément Vignac, and Max Welling. Equivariant diffusion for molecule generation in 3d. In *International Conference on Machine Learning*, pp. 8867–8887. PMLR, 2022.

Li Jing James Betker, Gabriel Goh et al. Improving image generation with better captions, 2023. URL https://cdn.openai.com/papers/dall-e-3.pdf. Available as PDF.

Tero Karras, Miika Aittala, Janne Hellsten, Samuli Laine, Jaakko Lehtinen, and Timo Aila. Training generative adversarial networks with limited data. *Advances in Neural Information Processing Systems*, 33, 2020a.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8110–8119, 2020b.

Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In *Proc. NeurIPS*, 2022.

Ilya Kavalerov, Wojciech Czaja, and Rama Chellappa. A multi-class hinge loss for conditional gans. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 1290–1299, 2021.

Dongjun Kim, Chieh-Hsin Lai, Wei-Hsiang Liao, Naoki Murata, Yuhta Takida, Toshimitsu Uesaka, Yutong He, Yuki Mitsufuji, and Stefano Ermon. Consistency trajectory models: Learning probability flow ode trajectory of diffusion. *arXiv preprint arXiv:2310.02279*, 2023.

Heeseung Kim, Sungwon Kim, and Sungroh Yoon. Guided-tts: A diffusion model for text-to-speech via classifier guidance. In *International Conference on Machine Learning*, pp. 11119–11133. PMLR, 2022.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10215–10224. 2018.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. The CIFAR-10 Dataset. *online: http://www. cs. toronto. edu/kriz/cifar. html*, 55, 2014.

Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *ArXiv*, abs/2210.02747, 2022a.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022b.

Hongjian Liu, Qingsong Xie, Zhijie Deng, Chen Chen, Shixiang Tang, Fueyang Fu, Zheng-jun Zha, and Haonan Lu. Scott: Accelerating diffusion models with stochastic consistency distillation. *arXiv preprint arXiv:2403.01505*, 2024.

Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. *arXiv preprint arXiv:2209.03003*, 2022.

Xingchao Liu, Xiwen Zhang, Jianzhu Ma, Jian Peng, et al. Instaflow: One step is enough for high-quality diffusion-based text-to-image generation. In *The Twelfth International Conference on Learning Representations*, 2023.

Eric Luhman and Troy Luhman. Knowledge distillation in iterative generative models for improved sampling speed. *arXiv preprint arXiv:2101.02388*, 2021.

Weijian Luo. A comprehensive survey on knowledge distillation of diffusion models. *arXiv preprint arXiv:2304.04262*, 2023.

Weijian Luo. Diff-instruct++: Training one-step text-to-image generator model to align with human preferences. *arXiv preprint arXiv:2410.18881*, 2024.

Weijian Luo and Zhihua Zhang. Data prediction denoising models: The pupil outdoes the master, 2024. URL https://openreview.net/forum?id=wYmcfur889.

Weijian Luo, Tianyang Hu, Shifeng Zhang, Jiacheng Sun, Zhenguo Li, and Zhihua Zhang. Diff-instruct: A universal approach for transferring knowledge from pre-trained diffusion models. *ArXiv*, abs/2305.18455, 2023a.

Weijian Luo, Hao Jiang, Tianyang Hu, Jiacheng Sun, Zhenguo Li, and Zhihua Zhang. Training energy-based models with diffusion contrastive divergences. *arXiv preprint arXiv:2307.01668*, 2023b.

Weijian Luo, Tianyang Hu, Shifeng Zhang, Jiacheng Sun, Zhenguo Li, and Zhihua Zhang. Diff-instruct: A universal approach for transferring knowledge from pre-trained diffusion models. *Advances in Neural Information Processing Systems*, 36, 2024a.

Weijian Luo, Zemin Huang, Zhengyang Geng, J Zico Kolter, and Guo-Jun Qi. One-step diffusion distillation through score implicit matching. *arXiv preprint arXiv:2410.16794*, 2024b.

Weijian Luo, Boya Zhang, and Zhihua Zhang. Entropy-based training methods for scalable neural implicit samplers. *Advances in Neural Information Processing Systems*, 36, 2024c.

Chenlin Meng, Yang Song, Jiaming Song, Jiajun Wu, Jun-Yan Zhu, and Stefano Ermon. Sdedit: Image synthesis and editing with stochastic differential equations. *arXiv preprint arXiv:2108.01073*, 2021.

Chenlin Meng, Ruiqi Gao, Diederik P Kingma, Stefano Ermon, Jonathan Ho, and Tim Salimans. On distillation of guided diffusion models. *arXiv preprint arXiv:2210.03142*, 2022.

Kirill Neklyudov, Rob Brekelmans, Daniel Severo, and Alireza Makhzani. Action matching: Learning stochastic dynamics from samples. In *International conference on machine learning*, pp. 25858–25889. PMLR, 2023.

Thuan Hoang Nguyen and Anh Tran. Swiftbrush: One-step text-to-image diffusion model with variational score distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Alex Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. *arXiv preprint arXiv:2102.09672*, 2021.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*, 2016.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.

Ashwini Pokle, Zhengyang Geng, and J Zico Kolter. Deep equilibrium approaches to diffusion models. *Advances in Neural Information Processing Systems*, 35:37975–37990, 2022.

Ben Poole, Ajay Jain, Jonathan T Barron, and Ben Mildenhall. Dreamfusion: Text-to-3d using 2d diffusion. *arXiv preprint arXiv:2209.14988*, 2022.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pp. 8821–8831. PMLR, 2021.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Yuxi Ren, Xin Xia, Yanzuo Lu, Jiacheng Zhang, Jie Wu, Pan Xie, Xing Wang, and Xuefeng Xiao. Hyper-sd: Trajectory segmented consistency model for efficient image synthesis. *arXiv preprint arXiv:2404.13686*, 2024.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S Sara Mahdavi, Rapha Gontijo Lopes, et al. Photorealistic text-to-image diffusion models with deep language understanding. *arXiv preprint arXiv:2205.11487*, 2022.

Tim Salimans and Jonathan Ho. Progressive distillation for fast sampling of diffusion models. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=TIdIXIpzhoI.

Tim Salimans, Thomas Mensink, Jonathan Heek, and Emiel Hoogeboom. Multistep distillation of diffusion models via moment matching. *arXiv preprint arXiv:2406.04103*, 2024.

Axel Sauer, Katja Schwarz, and Andreas Geiger. Stylegan-xl: Scaling stylegan to large diverse datasets. *ACM SIGGRAPH 2022 Conference Proceedings*, 2022.

Axel Sauer, Dominik Lorenz, Andreas Blattmann, and Robin Rombach. Adversarial diffusion distillation. *arXiv preprint arXiv:2311.17042*, 2023.

Axel Sauer, Frederic Boesel, Tim Dockhorn, Andreas Blattmann, Patrick Esser, and Robin Rombach. Fast high-resolution image synthesis with latent adversarial diffusion distillation. *arXiv preprint arXiv:2403.12015*, 2024.

Yang Song and Prafulla Dhariwal. Improved techniques for training consistency models. *arXiv preprint arXiv:2310.14189*, 2023.

Yang Song, Prafulla Dhariwal, Mark Chen, and Ilya Sutskever. Consistency models. *arXiv preprint arXiv:2303.01469*, 2023.

Yuhta Takida, Masaaki Imaizumi, Takashi Shibuya, Chieh-Hsin Lai, Toshimitsu Uesaka, Naoki Murata, and Yuki Mitsufuji. San: Inducing metrizability of gan with discriminative normalized linear layer. *arXiv preprint arXiv:2301.12811*, 2023.

Yifei Wang, Weimin Bai, Weijian Luo, Wenzheng Chen, and He Sun. Integrating amortized inference with diffusion models for learning clean distribution from corrupted images. *arXiv preprint arXiv:2407.11162*, 2024.

Daniel Watson, William Chan, Jonathan Ho, and Mohammad Norouzi. Learning fast samplers for diffusion models by differentiating through sample quality. In *International Conference on Learning Representations*, 2022.

Mengfei Xia, Yujun Shen, Ceyuan Yang, Ran Yi, Wenping Wang, and Yong-jin Liu. Smart: Improving gans with score matching regularity. *arXiv preprint arXiv:2311.18208*, 2023.

Zhisheng Xiao, Karsten Kreis, and Arash Vahdat. Tackling the generative learning trilemma with denoising diffusion gans. In *International Conference on Learning Representations*, 2021.

Sirui Xie, Zhisheng Xiao, Diederik P Kingma, Tingbo Hou, Ying Nian Wu, Kevin Patrick Murphy, Tim Salimans, Ben Poole, and Ruiqi Gao. Em distillation for one-step diffusion models, 2024. URL https://arxiv.org/abs/2405.16852.

Yanwu Xu, Yang Zhao, Zhisheng Xiao, and Tingbo Hou. Ufogen: You forward once large scale text-to-image generation via diffusion gans. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8196–8206, 2024.

Shuchen Xue, Mingyang Yi, Weijian Luo, Shifeng Zhang, Jiacheng Sun, Zhenguo Li, and Zhi-Ming Ma. SA-solver: Stochastic adams solver for fast sampling of diffusion models. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=f6a9XVFYIo.

Ling Yang, Zixiang Zhang, Zhilong Zhang, Xingchao Liu, Minkai Xu, Wentao Zhang, Chenlin Meng, Stefano Ermon, and Bin Cui. Consistency flow matching: Defining straight flows with velocity consistency. *arXiv preprint arXiv:2407.02398*, 2024.

Tianwei Yin, Michaël Gharbi, Taesung Park, Richard Zhang, Eli Shechtman, Fredo Durand, and William T Freeman. Improved distribution matching distillation for fast image synthesis. *arXiv preprint arXiv:2405.14867*, 2024a.

Tianwei Yin, Michaël Gharbi, Richard Zhang, Eli Shechtman, Fredo Durand, William T Freeman, and Taesung Park. One-step diffusion with distribution matching distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6613–6623, 2024b.

Xuanwu Yin Yuda Song, Zehao Sun. Sdxs: Real-time one-step latent diffusion models with image conditions. *arxiv*, 2024.

Lai Zeqiang, Zhu Xizhou, Dai Jifeng, Qiao Yu, and Wang Wenhai. Mini-dalle3: Interactive text to image by prompting large language models. *arXiv preprint arXiv:2310.07653*, 2023.

Boya Zhang, Weijian Luo, and Zhihua Zhang. Purify++: Improving diffusion-purification with advanced diffusion models and control of randomness. *arXiv preprint arXiv:2310.18762*, 2023.

Boya Zhang, Weijian Luo, and Zhihua Zhang. Enhancing Adversarial Robustness via Score-Based Optimization. *Advances in Neural Information Processing Systems*, 36, 2024.

Yang Zhao, Chunyuan Li, Ping Yu, Jianfeng Gao, and Changyou Chen. Feature quantization improves gan training. *arXiv preprint arXiv:2004.02088*, 2020.

Bowen Zheng and Tianming Yang. Diffusion models are innate one-step generators. *arXiv preprint arXiv:2405.20750*, 2024.

Hongkai Zheng, Weili Nie, Arash Vahdat, Kamyar Azizzadenesheli, and Anima Anandkumar. Fast sampling of diffusion models via operator learning. *arXiv preprint arXiv:2211.13449*, 2022.

Huangjie Zheng, Pengcheng He, Weizhu Chen, and Mingyuan Zhou. Truncated diffusion probabilistic models and diffusion-based adversarial auto-encoders. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=HDxgaKk956l.

Mingyuan Zhou, Huangjie Zheng, Zhendong Wang, Mingzhang Yin, and Hai Huang. Score identity distillation: Exponentially fast distillation of pretrained diffusion models for one-step generation. In *International Conference on Machine Learning*, 2024.

A   THEORIES

A.1   PROOF OF EQUATION 4.3

Proof. We prove the equation (4.3) of our loss gradient:

$$\frac{\partial}{\partial\theta}\mathcal{L}_{FM}(\theta) = \frac{\partial}{\partial\theta}\mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\theta}\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2\right\}$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\{\frac{\partial\boldsymbol{u}_t(\boldsymbol{x}_t)}{\partial\boldsymbol{x}_t}\cdot\frac{\partial\boldsymbol{x}_t}{\partial\theta} - (\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) + \frac{\partial\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)}{\boldsymbol{x}_t}\cdot\frac{\partial\boldsymbol{x}_t}{\partial\theta})\}\right\}$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\{\frac{\partial\boldsymbol{u}_t(\boldsymbol{x}_t)}{\partial\boldsymbol{x}_t}\cdot\frac{\partial\boldsymbol{x}_t}{\partial\theta} - \frac{\partial\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)}{\partial\boldsymbol{x}_t}\cdot\frac{\partial\boldsymbol{x}_t}{\partial\theta}\} - 2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\frac{\partial}{\partial\boldsymbol{x}_t}\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}\cdot\frac{\partial\boldsymbol{x}_t}{\partial\theta} - 2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$= \mathbb{E}_{t,\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\boldsymbol{x}_t}\{\|\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\|_2^2\}\frac{\partial\boldsymbol{x}_t}{\partial\theta} - 2\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\}^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$\tag{A.1}$$

$\square$

A.2   PROOF OF THEOREM 4.1

Recall the definition of $p_{\theta,t}$ and $\boldsymbol{v}_{\theta,t}$:

$$p_{\theta,t}(\boldsymbol{x}_t) = \int q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)\mathrm{d}\boldsymbol{x}_0 \tag{A.2}$$

$$\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) = \int \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)}{p_{\theta,t}(\boldsymbol{x}_t)}\mathrm{d}\boldsymbol{x}_0. \tag{A.3}$$

We may use $\mathbf{f}$ for short. We have

$$\mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\mathbf{f}^T\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) = \mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\mathbf{f}^T\int \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)}{p_{\theta,t}(\boldsymbol{x}_t)}\mathrm{d}\boldsymbol{x}_0 \tag{A.4}$$

$$= \int p_{\theta,t}(\boldsymbol{x}_t)\mathbf{f}^T\int \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)}{p_{\theta,t}(\boldsymbol{x}_t)}\mathrm{d}\boldsymbol{x}_0\mathrm{d}\boldsymbol{x}_t \tag{A.5}$$

$$= \int\int \mathbf{f}^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)p_{\theta,0}(\boldsymbol{x}_0)\mathrm{d}\boldsymbol{x}_0\mathrm{d}\boldsymbol{x}_t \tag{A.6}$$

$$= \mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\mathbf{f}^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) \tag{A.7}$$

A.3   PROOF OF THEOREM 4.2

Proof. Let us take θ gradient on both sides of (4.7), and then we have

$$\mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\theta}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) + \mathbf{f}(\boldsymbol{x}_t,\theta)^T\frac{\partial}{\partial\theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\} + \mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\frac{\partial}{\partial\boldsymbol{x}_t}\left\{\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}\frac{\partial\boldsymbol{x}_t}{\partial\theta}$$

$$\tag{A.8}$$

$$= \mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\frac{\partial}{\partial\theta}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) + \mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\frac{\partial}{\partial\boldsymbol{x}_t}\left[\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\right]\frac{\partial\boldsymbol{x}_t}{\partial\theta}\right.$$

$$\left.+ \mathbf{f}(\boldsymbol{x}_t,\theta)^T\frac{\partial}{\partial\boldsymbol{x}_0}\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{\partial\boldsymbol{x}_0}{\partial\theta}\right\}$$

Notice that one can have

$$\mathbb{E}_{\boldsymbol{x}_t\sim p_{\theta,t}}\left\{\frac{\partial}{\partial\theta}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\right\}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t) = \mathbb{E}_{\substack{\boldsymbol{x}_0\sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0\sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\frac{\partial}{\partial\theta}\mathbf{f}(\boldsymbol{x}_t,\theta)^T\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)$$

by substituting $\mathbf{f}(\boldsymbol{x}_t, \theta)$ with $\frac{\partial}{\partial \theta}\mathbf{f}(\boldsymbol{x}_t, \theta)$ in equation (4.7).

This allows us to cancel out the corresponding terms from equation (A.8), and we have

$$\mathbb{E}_{\boldsymbol{x}_t \sim p_{\theta,t}}\left\{\mathbf{f}(\boldsymbol{x}_t, \theta)^T \frac{\partial}{\partial \theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\} + \mathbb{E}_{\boldsymbol{x}_t \sim p_{\theta,t}}\frac{\partial}{\partial \boldsymbol{x}_t}\left\{\mathbf{f}(\boldsymbol{x}_t, \theta)^T \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}\frac{\partial \boldsymbol{x}_t}{\partial \theta} \tag{A.9}$$

$$= \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\frac{\partial}{\partial \boldsymbol{x}_t}\left[\mathbf{f}(\boldsymbol{x}_t, \theta)^T \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\right]\frac{\partial \boldsymbol{x}_t}{\partial \theta} + \mathbf{f}(\boldsymbol{x}_t, \theta)^T \frac{\partial}{\partial \boldsymbol{x}_0}\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)\frac{\partial \boldsymbol{x}_0}{\partial \theta}\right\}$$

This gives rise to

$$\mathbb{E}_{\boldsymbol{x}_t \sim p_{\theta,t}}\left\{\mathbf{f}(\boldsymbol{x}_t, \theta)^T \frac{\partial}{\partial \theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\} \tag{A.10}$$

$$= \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\frac{\partial}{\partial \boldsymbol{x}_t}\left[\mathbf{f}(\boldsymbol{x}_t, \theta)^T\left\{\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) - \boldsymbol{v}_\theta(\boldsymbol{x}_t, t)\right\}\right]\frac{\partial \boldsymbol{x}_t}{\partial \theta} + \mathbf{f}(\boldsymbol{x}_t, \theta)^T \frac{\partial \boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}{\partial \boldsymbol{x}_0}\frac{\partial \boldsymbol{x}_0}{\partial \theta}\right\}$$

We now define the following loss function

$$\mathcal{L}_2(\theta) = \mathbb{E}_{\substack{\boldsymbol{x}_0 \sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\mathbf{f}(\boldsymbol{x}_t, \mathrm{sg}[\theta])^T\left\{\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) - \boldsymbol{v}_{\mathrm{sg}[\theta],t}(\boldsymbol{x}_t)\right\}\right\} \tag{A.11}$$

with $\mathbf{f}(\boldsymbol{x}_t, \theta) = -2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$. Its gradient becomes

$$\mathbb{E}_{\boldsymbol{x}_t \sim p_{\theta,t}}\left\{-2\left\{\boldsymbol{u}_t(\boldsymbol{x}_t) - \boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}^T \frac{\partial}{\partial \theta}\boldsymbol{v}_{\theta,t}(\boldsymbol{x}_t)\right\}$$

$$= \frac{\partial}{\partial \theta}\mathbb{E}_{\substack{\boldsymbol{x}_0 \sim p_{\theta,0},\\ \boldsymbol{x}_t|\boldsymbol{x}_0 \sim q_t(\boldsymbol{x}_t|\boldsymbol{x}_0)}}\left\{\mathbf{f}(\boldsymbol{x}_t, \mathrm{sg}[\theta])^T\left\{\boldsymbol{u}_t(\boldsymbol{x}_t|\boldsymbol{x}_0) - \boldsymbol{v}_{\mathrm{sg}[\theta]}(\boldsymbol{x}_t, t)\right\}\right\} \tag{A.12}$$

by applying the above result in (A.10). This completes the proof of Theorem 4.1, and shows the gradient of $\mathcal{L}_2(\theta)$ coincides with $\mathrm{Grad}_2(\theta)$.

$\square$

B ADDITIONAL EXPERIMENTAL DETAILS

B.1 CIFAR-10

Hyper-parameters Please note that prior to distilling our one-step flow matching models, we first pre-trained multi-step flow matching models on CIFAR-10 using the ReFlow objective. All experimental details can be found in Table 4.

When distilling our one-step model, we use a logit-normal distribution $\pi(0, 2)$. Larger variance allows the training to cover a wider range of noise levels, which provides better stability for the training process. Excessively high noise level can lead to a decline in the quality of the generated images, while excessively low noise can easily result in mode collapse issues.

Table 4: Experimental details on CIFAR-10.

Training Details	CIFAR-10 Uncond	CIFAR-10 Cond	CIFAR-10 Uncond (1 Step)	CIFAR-10 Cond (1 Step)
Training Kimg	20000	20000	20000	20000
Batch size	512	512	512	512
Optimizer ($\boldsymbol{v}_\psi$)	Adam	Adam	Adam	Adam
Optimizer (g_θ)	Adam	Adam	Adam	Adam
Learning rate ($\boldsymbol{v}_\psi$)	2e-5	2e-5	2e-5	2e-5
Learning rate (g_θ)	2e-5	2e-5	2e-5	2e-5
betas ($\boldsymbol{v}_\psi$)	(0, 0.999)	(0, 0.999)	(0, 0.999)	(0, 0.999)
betas (g_θ)	(0, 0.999)	(0, 0.999)	(0, 0.999)	(0, 0.999)
EMA decay rate	0.999	0.999	0.999	0.999

B.2 TEXT-TO-IMAGE

Hyper-parameters We detail the hyperparameters used in the distillation of our text-to-image models, specifically for both the one-step generator and the online flow model. Both models are trained in BF16 precision using the Adam optimizer with the following settings: $\beta_1 = 0, \beta_2 = 0.999, \epsilon = 1.0 \times 10^{-6}$, and a learning rate of 5.0×10^{-6}. For both the FGM loss and the flow matching loss, we sample timestep $t \in [0,1]$, following the Esser et al. (2024) using a logit-normal distribution as the timestep density function. The FGM loss employs $\pi(2.4, 1.0)$, while the flow matching loss uses $\pi(-1.0, 2.0)$. During the generator training phase, the GAN loss weight is set to 1×10^{-2}, whereas for the discriminator training, it is set to 5×10^{-2}. Additionally, we apply a loss scaling factor of 100 for the generator, and the entire model is trained with a batch size of 192.

Training Details During the training of the generator, we employed classifier-free guidance for inference on the teacher model when calculating $\mathcal{L}_2(\theta)$. To prevent artifacts in the output caused by an excessively high guidance scale, we opted for a more stable guidance scale of 4.0. To further reduce memory consumption, we pre-encoded the prompts dataset into embeddings. For the negative prompts used in classifier-free guidance, we used empty text for encoding and storage. Additionally, by applying Fully Sharded Data Parallel (FSDP) across the teacher model, online flow model, and generator, we achieved a batch size of 4 with a gradient accumulation of 6, ultimately allowing us to reach a batch size of 192 on 8xH800-80G.

Discriminator Design For the design of the discriminator's network architecture, we drew on previous work (Yin et al., 2024a), using the online flow model itself as a feature extractor for images, supplemented by a lightweight convolutional network as the classification head to differentiate between the distributions of noisy real data and generated data. However, unlike Yin et al. (2024a), the teacher model we chose does not have an explicit encoder structure. As a result, we output the hidden states from different layers of the transformer and found that the shallow features, specifically those from layer 2, better reflect the content of the image compared to deeper layers. Thus, we empirically selected this layer's features as the input for the subsequent classification head. Additionally, as mentioned earlier, we discovered that GAN can perform well in certain noise ranges where FGM is inefficient. Therefore, another distinction from Yin et al. (2024a) is our different design for the noise schedules used for FGM and GAN loss. The former primarily samples in high-noise ranges, while the latter focuses on sampling in lower-noise ranges. GAN training is conducted on a synthetic dataset containing approximately 500K high-quality images at a resolution of 1024px. Texts and images have also been pre-encoded and stored to reduce computational load during training.

Model Parameterization The standard flow-matching model for generating data from noise can be represented in EDM formulation as follows:

$$\widehat{\boldsymbol{x}}_0 = c_{\text{skip}} \cdot \boldsymbol{z} - c_{\text{out}} \cdot \boldsymbol{v}_\theta(c_{\text{in}} \cdot \boldsymbol{z}, c_{\text{noise}}(t)), \quad \boldsymbol{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}) \tag{B.1}$$

Generally, the conventional choices for one-step generator are $t = t^* = 1, c_{\text{skip}} = 1, c_{\text{out}} = t^*, c_{\text{in}} = 1$ and $c_{\text{noise}}(t) = t^*$. However, in practice, we identified two empirical modifications to these parameters that can further enhance the model's generation performance.

First, regarding the choice of t^*, since we need to inherit weights from the teacher model, selecting t^* effectively means choosing a specific v_{θ, t^*} from a family of models with shared parameters $v_{\theta, t}$. To optimize our initialization weights, we can select the model that performs best for one-step generation within this family. Given a simple hyperparameter search, we noticed that $t^* = 0.97$ is a good choice.

Second, we examined the input scaling factor c_{in}. While the standard choice is $c_{\text{in}} = 1$, we noticed during our training that the generated results consistently contained some small noise and blurriness that were difficult to eliminate. After multiple tuning attempts, we suspected that the variance of the model input was too large. We decided to slightly reduce the input variance and chose $c_{\text{in}} = 0.8$. Consequently, we derived our final model parameterization:

$$\widehat{\boldsymbol{x}}_0 = \boldsymbol{z} - 0.97 \cdot \boldsymbol{v}_\theta(0.8 \cdot \boldsymbol{z}, 0.97)), \quad \boldsymbol{z} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}) \tag{B.2}$$

Our Evaluation Settings In our evaluation, we evaluated several other models on GenEval(Ghosh et al., 2024), including SD3-Medium(Esser et al., 2024), Hyper-SD3(Ren et al., 2024), and Flash-SD3Chadebec et al. (2024). All evaluations were conducted at a resolution of 1024px, generating

four samples for each prompt from the original GenEval paper. We utilized the inference parameters recommended by the authors for these models. Specifically, for SD3, we use a guidance scale of 7.0, generating images in 28 steps.For Hyper-SD3, we applied a guidance scale of 3.0 and a LoRA scale of 0.125, performing 4 steps of inference to generate the evaluation images. For Flash-SD3, we set the guidance scale to 0.0 and also used 4 sampling steps. Finally, we automatically calculated the corresponding metrics using the scripts provided by GenEval.

B.2.1 EVALUATION PROMPTS

Prompts used in Figure 1

- *blurred landscape, close-up photo of man, 1800s, dressed in t-shirt.*
- *Seasoned fisherman portrait, weathered skin etched with deep wrinkles, white beard, piercing gaze beneath a fisherman's hat, softly blurred dock background accentuating rugged features, captured under natural light, ultra-realistic, high dynamic range photo.*
- *Portrait of a Young Woman.*
- *an old woman, Eyes Wide Open, Siena International Photo Awards.*
- *A 4k dslr image of a lemur wearing a red magician hat and a blue coat performing magic tricks with cards in a garden.*
- *A bird is perched on a flower, captured in close-up.*
- *border collie surfing a small wave, with a mountain on background.*
- *A photorealistic illustration of a galloping cheetah in an open field, splashing through puddles on wet ground. Dark clouds loom overhead, with a few trees in the background. The image features vibrant colors and a 35mm film aesthetic.*
- *Winter landscape of tree on the edge of the river on a foggy morning.*
- *View of Perth City skyline at dusk.*
- *Chinese landschap aquarel.*
- *Australian landscape oil paintings by graham gercken for Fall paintings easy.*
- *Pin for Later: Prepare For Your Jaw to Drop After Seeing 2015's Top Photos Stormy Porthcawl.*
- *Crater Lake, in Oregon, is one of the snowiest isolated places in United States. We went to spend the night at the edge of the crater and between two snow storms, we had the lights show!*
- *Ginkaku-ji Temple in Kyoto.*

Prompts used in Figure 2

- *Luminous Beings Are We painting by Stephen Andrade Gallery1988 Star Wars Art Awakens Yoda*
- *Delightful Fall Landscape Wallpapers*
- *Russian Blue cat exploring a garden, surrounded by vibrant flowers.*
- *A young girl walks across a field, head down, wearing a communion gown.*

B.2.2 MORE SAMPLES

C ABLATION STUDY

C.1 GENERATOR INITIALIZATION

C.2 TRAINING WITH REGRESSION LOSS

D IMAGE QUALITY IMPROVEMENT BY FURTHER TRAINING

Figure 4: Unconditional samplers from 1-step FGM model on CIFAR10.

Figure 5: Conditional samplers from 1-step FGM model on CIFAR10.

Figure 6: We choose several $t^* = [0.00, 0.25, 0.50, 0.75, 1.00]$ to train from scratch on 512-px. As t^* decreases, the structural integrity of the images tends to deteriorate.

After 1 Step Optimization   **After 250 Step Optimization**

Figure 7: We conduct two experiments on an early checkpoints, one training with both loss $\mathcal{L}_1 + \mathcal{L}_2$, another training with only $\mathcal{L}_2$, our results show that simply apply the extra regression loss $\mathcal{L}_1$ quickly degrade the performance.

Previous   **More Steps**   **Previous**   **More Steps**

Figure 8: This suggests the checkerboard artifacts can be substantially mitigated, and the overall image quality can also be enhanced with more extensive training.