PRIMA: PLANNER-REASONER INSIDE A MULTI-TASK REASONING AGENT

ABSTRACT

We consider the problem of multi-task reasoning (MTR), where an agent can solve multiple tasks via (first-order) logic reasoning. This capability is essential for human-like intelligence due to its strong generalizability and simplicity for handling multiple tasks. However, a major challenge in developing effective MTR is the intrinsic conflict between reasoning capability and efficiency. An MTR-capable agent must master a large set of "skills" to tackle diverse tasks, but executing a particular task at the inference stage requires only a small subset of immediately relevant skills. How can we maintain broad reasoning capability but efficient specific-task performance? To address this problem, we propose a Planner-Reasoner framework capable of state-of-the-art MTR capability and high efficiency. The Reasoner models shareable (first-order) logic deduction rules, from which the Planner selects a subset to compose into efficient reasoning paths. The entire model is trained in an end-to-end manner using deep reinforcement learning, and experimental studies over a variety of domains validate its effectiveness. [1]

1 INTRODUCTION

Multi-task learning (MTL) (Zhang & Yang, 2021; Zhou et al., 2011) demonstrates superior sample complexity and generalizability compared with the conventional "one model per task" style to solve multiple tasks. Recent research has additionally leveraged the great success of deep learning (LeCun et al., 2015) to empower learning deep multi-task models (Zhang & Yang, 2021; Crawshaw, 2020). Deep MTL models either learn a common multi-task feature representation by sharing several bottom layers of deep neural networks (Zhang et al., 2014; Liu et al., 2015; Zhang et al., 2015a; Mrksic et al., 2015; Li et al., 2015), or learn task-invariant and task-specific neural modules (Shinohara, 2016; Liu et al., 2017) via generative adversarial networks (Goodfellow et al., 2014). Although MTL is successful in many applications, a major challenge is the often impractically large MTL models. Although still smaller than piling up all models across different tasks, existing MTL models are significantly larger than a single model for tackling a specific task. This results from the intrinsic conflict underlying all MTL algorithms: balancing *across-task generalization capability* to perform different tasks with *single-task efficiency* in executing a specific task. On one hand, good generalization ability requires an MTL agent to be equipped with a large set of skills that can be combined to solve many different tasks. On the other hand, solving one particular task does not require all these skills. Instead, the agent needs to compose only a (small) subset of these skills into an efficient solution for a specific task. This conflict often hobbles existing MTL approaches.

This paper focuses on multi-task reasoning (MTR), a subarea of MTL that uses logic reasoning to solve multiple tasks. MTR is ubiquitous in human reasoning, where humans construct different reasoning paths for multiple tasks from the *same* set of reasoning skills. Conventional deep learning, although capable of strong expressive power, falls short in reasoning capabilities (Bengio, 2019). Considerable research has been devoted to endowing deep learning with logic reasoning abilities, the results of which include Deep Neural Reasoning (Jaeger, 2016), Neural Logic Reasoning (Besold et al., 2017; Bader et al., 2004; Bader & Hitzler, 2005), Neural Logic Machines (Dong et al., 2019), and other approaches (Besold et al., 2017; Bader et al., 2004; Bader & Hitzler, 2005). However, these approaches consider only single-task reasoning rather than a multi-task setting, and applying

---

[1]The code will be released after acceptance.

Figure 1: An example from the `AdjacentToRed` task and its formulation as a logical reasoning problem.

existing MTL approaches to learning these neural reasoning models leads to the same conflict between *across-task generalization capability* and *single-task efficiency*.

To strike a balance between reasoning capability and efficiency in MTR, we develop a ***Planner-Reasoner architecture Inside a Multi-task reasoning Agent*** (PRIMA) (Section 2), wherein the reasoner defines a set of neural logic operators for modeling reusable reasoning meta-rules ("skills") across tasks (Section 2.2). When defining the logic operators, we focus on first-order logic because of its simplicity and wide applicability to many reasoning problems, such as automated theorem proving (Fitting, 2012; Gallier, 2015) and knowledge-based systems (Van Harmelen et al., 2008). A separate planner module activates only a small subset of the meta-rules necessary for a given task and composes them into a deduction process (Section 2.3). Thus, our planner-reasoner architecture features the dual capabilities of *composing* and *pruning* a logic deduction process, achieving a graceful capability-efficiency trade-off in MTR (Section 2.4). The model architecture is trained in an end-to-end manner using deep reinforcement learning (Section 3), and experimental results on several benchmarks demonstrate that this framework leads to a more principled predicate space search and reduces reasoning complexity (Section 4). We discuss related works in Section 5, and conclude our paper in Section 6.

2   PLANNER-REASONER FOR MULTI-TASK REASONING

This section proposes the Planner-Reasoner framework for MTR. To that end, we first formally state the logic reasoning problem in Section 2.1, and then in Sections 2.2 and 2.3, we describe the ***Planner-Reasoner Inside a Single Reasoning Agent*** (PRISA) framework. This is a planner-reasoner architecture, which is a neural-logic architecture for traversing the first-order predicate space. Typically, logical reasoning can be reduced to *learning to search for a reasoning path with logical operators and then derive a logical consequence from premises*. Therefore, a reasoning problem can be addressed in two steps: (i) constructing the elementary logical operators and (ii) selecting a reasoning path that chains these logical operators together. This key observation motivates the Reasoner (Section 2.2) and Planner (Section 2.3) modules in our framework. In Section 2.4, the PRISA framework is extended to the MTR setting, which results in the ***Planner-Reasoner Inside a Multi-task Reasoning Agent*** (PRIMA) framework.

2.1   PROBLEM FORMULATION

Logic reasoning   We begin with a brief introduction of the logic reasoning problem. Specifically, we consider a special variant of the First-Order Logic (FOL) system, which only consists of *individual variables*, *constants* and up to r-ary *predicate variables*. That is, we do not consider *functions* that map individual variables/constants into *terms*. An r-ary predicate $p(x_1, \ldots, x_r)$ can be considered as a relation between r constants, which takes the value of `True` or `False`. An atom $p(x_1, \cdots, x_r)$ is an r-ary predicate with its arguments $x_1, \cdots, x_r$ being either variables or constants. A *well-defined formula* in our FOL system is a logical expression that is composed from atoms, logical connectives (e.g., negation $\neg$, conjunction $\wedge$, disjunction $\vee$, implication $\leftarrow$), and possibly existential $\exists$ and universal $\forall$ quantifiers according to certain formation rules (see Andrews (2002) for the details). In particular, the quantifiers $\exists$ and $\forall$ are only allowed to be applied to individual variables in FOL. In Fig. 1, we give an example from the `AdjacentToRed` task (Graves et al., 2016) and show how it could be formulated as a logical reasoning problem. Specifically, we are given a random graph along with the *properties* (i.e., the color) of the nodes and the *relations* (i.e., connectivity) between nodes. In our context, each node i in the graph is a *constant* and an *individual variable* x takes

values in the set of constants $\{1, \ldots, 5\}$. The properties of nodes and the relations between nodes are modeled as the unary predicate $\texttt{IsRed}(x)$ (5×1 vector) and the binary predicate $\texttt{HasEdge}(x, y)$ (5×5 matrix), respectively. The objective of logical reasoning is to deduce the value of the unary predicate $\texttt{AdjacentToRed}(x)$ (i.e., whether a node x has a neighbor of red color) from the *base* predicates $\texttt{IsRed}(x)$ and $\texttt{HasEdge}(x, y)$ (see Fig. 1 for an example of the deduction process).

Multi-Task Reasoning   Next, we introduce the definition of MTR. With a slight abuse of notations, let $\{p(x_1, \ldots, x_r) : r \in [1, n]\}$ be the set of input predicates sampled from any of the k different reasoning tasks, where $x_1, \ldots, x_r$ are the individual variables and n is the maximum arity. A multi-task reasoning model takes $p(x_1, \ldots, x_r)$ as its input and seeks to predict the corresponding ground-truth output predicates $q(x_1, \ldots, x_r)$. The aim is to learn multiple reasoning tasks jointly in a single model so that the reasoning skills in a task can be leveraged by other tasks to improve the general performance of all tasks at hand.

2.2 Reasoner: transforming logic rules into neural operators

The Reasoner module conducts logical deduction using a set of neural operators constructed from first-order logic rules (more specifically, a set of "learnable" Horn clauses). Its architecture is inspired by NLM (Dong et al., 2019) (details about the difference can be found in Appendix D). Three logic rules are considered as essential meta-rules: $\texttt{BooleanLogic}$, $\texttt{Expansion}$, and $\texttt{Reduction}$.

$$\texttt{BooleanLogic}: \quad \texttt{expression}(x_1, x_2, \cdots, x_r) \rightarrow \hat{p}(x_1, x_2, \cdots, x_r),$$

where $\texttt{expression}$ is composed of a combination of Boolean operations ($\texttt{AND}$, $\texttt{OR}$, and $\texttt{NOT}$) and $\hat{p}$ is the *output predicate*. For a given r-ary predicate and a given permutation $\psi \in S_n$, we define $p_\psi(x_1, \cdots, x_r) = p(x_{\psi(1)}, \cdots, x_{\psi(r)})$ where S_n is the set of all possible permutations as the arguments to an input predicate. The corresponding neural implementation of $\texttt{BooleanLogic}$ is $\sigma\left(\text{MLP}\left(p_\psi(x_1, \cdots, x_r)\right); \theta\right)$, where σ is the sigmoid activation function, MLP refers to a multi-layer perceptron, a $\text{Permute}(\cdot)$ neural operator transforms input predicates to $p_\psi(x_1, \cdots, x_r)$, and θ is the learnable parameter within the model. This is similar to the implicit Horn clause with the universal quantifier($\forall$), e.g., $p_1(x) \wedge p_2(x) \rightarrow \hat{p}(x)$ implicitly denoting $\forall x\, p_1(x) \wedge p_2(x) \rightarrow \hat{p}(x)$. The class of neural operators can be viewed as "learnable" Horn clauses.

$\texttt{Expansion}$, and $\texttt{Reduction}$ are two types of meta-rules for quantification that bridge predicates of different arities with logic quantifiers ($\forall$ and $\exists$). $\texttt{Expansion}$ introduces a new and distinct variable x_{r+1} for a set of r-ary predicates with the universal quantifier($\forall$). For this reason, $\texttt{Expansion}$ creates a new predicate q from p.

$$\texttt{Expansion}: \quad p(x_1, x_2, \cdots, x_r) \rightarrow \forall x_{r+1}, q(x_1, x_2, \cdots, x_r, x_{r+1}),$$

where $x_{r+1} \notin \{x_i\}_{i=1}^r$. The corresponding neural implementation of $\texttt{Expansion}$, denoted by $\text{Expand}(\cdot)$, expands the r-ary predicates into the $(r+1)$-ary predicates by repeating the r-ary predicates and stacking them in a new dimension. Conversely, $\texttt{Reduction}$ removes the variable x_{r+1} in a set of $(r+1)$-ary predicates via the quantifiers of $\forall$ or $\exists$.

$$\texttt{Reduction}: \quad \forall x_{r+1}\, p(x_1, x_2, \cdots, x_r, x_{r+1}) \rightarrow q(x_1, x_2, \cdots, x_r), \text{or}$$
$$\exists x_{r+1}\, p(x_1, x_2, \cdots, x_r, x_{r+1}) \rightarrow q(x_1, x_2, \cdots, x_r).$$

The corresponding neural implementation of $\texttt{Reduction}$, denoted by $\text{Reduce}(\cdot)$, reducing the $(r+1)$-ary predicates into the r-ary predicates by taking the minimum (resp. maximum) along the dimension of x_{r+1} due to the universal quantifier $\forall$ (resp. existential quantifier $\exists$).

2.3 Planner: activating and forward-chaining learnable Horn clauses

The Planner is our key module to address the capability-efficiency tradeoff in the MTR problem; it is responsible for activating the neural operators in the Reasoner and chaining them into reasoning paths. Existing learning-to-reason approaches, which are often based on inductive logic programming (ILP) (Cropper et al., 2020a; Cropper & Dumancic, 2020; Muggleton & De Raedt, 1994) and the correspondingly neural-ILP methods (Dong et al., 2019; Shi et al., 2020). Conventional ILP methods suffer from several drawbacks, such as heavy reliance on human-crafted templates and sensitivity to noise. On the other hand, neural-ILP methods (Dong et al., 2019; Shi et al., 2020), leveraging

Figure 2: Left (A): The Planner-Reasoner Architecture with an example solution. Right (B): The overall (end-to-end) training process of the model by deep reinforcement learning. "Perm" denotes `Permute` operator.

the strength of deep learning and ILP, such as the Neural Logic Machine (NLM) (Dong et al., 2019), lack explicitness in the learning process of searching for reasoning paths. Let us take the learning process of NLM for example, which follows an intuitive two-step procedure. It first fully connects all the neural blocks and then searches all possible connections (corresponding to all possible predicate candidates) exhaustively to identify the desired reasoning path (corresponding to the desired predicate).

By using our proposed Planner module, we can strike a better capability-efficiency tradeoff. Rather than conducting an exhaustive search over all possible predicate candidates as in NLM, the Planner prunes all the unnecessary operators and identifies an essential reasoning path with low complexity for a given problem. Consider the following example. As shown in Fig. 1 and Fig. 2A (the highlighted orange-colored blocks), at each reasoning step, the Planner takes the input predicates and determines which neural operators should be activated. The decision is represented as a binary vector — $[I^0 \dots I^6]$ (termed *operator footprint*) — that corresponds to the neural operators of Expand, Reduce and $\mathrm{DirectInput}$[2] at different arity groups. By chaining these sequential decisions, a sequence of operator footprints is formulated as a reasoning path, as the highlighted orange-colored path in Fig. 2A. Generally, the neural operators defined in the Reasoner can also be viewed as (learnable) Horn Clauses (Horn, 1951; Chandra & Harel, 1985), and the Planner *forward-chains* them into a reasoning path.

2.4 THE PRIMA FRAMEWORK FOR MULTI-TASK REASONING

By far, we have developed the PRISA architecture for the single-task reasoning setting. To extend PRISA to PRIMA for the multi-task reasoning setting, we add an extra nullary input predicate (O^0 in Fig. 2) to inform the planner of the current task. Based on the value of O^0, the planner will learn to activate the appropriate subset of neural operators, including a subset of shared operators and a few task-specific operators, for the current task. By doing so, PRIMA can learn to make the best use of reusable neural operators across different tasks. In Section 4, we will demonstrate such a capability of the planner on different tasks.

3 LEARNING-TO-REASON VIA REINFORCEMENT LEARNING

In our problem, the decision variables of the Planner are binary indicators of whether a neural operator module should be activated. Readers familiar with Markov decision processes (MDPs) (Puterman, 2014) might notice that the reasoning path of our model in Fig. 2A resembles a temporal rollout in MDP formulation (Sutton & Barto, 2018). Therefore, we frame learning-to-reason as a sequential decision-making problem and adopt off-the-shelf reinforcement learning (RL) algorithms.

---

[2]$\mathrm{DirectInput}$ is an identity mapping of the inputs where its following operators of $\mathrm{Permute}$, MLP and sigmoid nonlinearity can directly approximate the `BooleanLogic`.

Figure 3: The architecture of the Base Planner and its enhanced version. Left: The Base Planner is based on a one-layer fully-activated Reasoner followed by max-pooling operations to predict an indicator of whether an op should be activated. Right: The Enhanced Planner uses MCTS to further boost the performance.

3.1 AN MDP FORMULATION OF THE LEARNING-TO-REASON PROBLEM

An MDP is defined as the tuple $(\mathcal{S}, \mathcal{A}, P^a_{ss'}, R, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ are finite sets of states and actions, the transition kernel $P^a_{ss'}$ specifies the probability of transition from state $s \in \mathcal{S}$ to state $s' \in \mathcal{S}$ by taking action $a \in \mathcal{A}$, $R(s,a) : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the reward function, and $0 \leq \gamma \leq 1$ is a discount factor. A stationary policy $\pi : \mathcal{S} \times \mathcal{A} \to [0,1]$ is a probabilistic mapping from states to actions. The primary objective of an RL algorithm is to identify a near-optimal policy π^* that satisfies

$$\pi^* := \arg\max_\pi \left\{ J(\pi) := \mathbb{E}\left[\sum_{t=0}^{T_{\max}-1} \gamma^t r(s_t, a_t \sim \pi) \right] \right\},$$

where $T_{\max}$ is a positive integer denoting the horizon length — that is, the maximum length of a rollout. The resemblance between Fig. 2 and an MDP formulation is relatively intuitive as summarized in Table 1. At the t-th time step, the state s_t corresponds to the set of predicates, $s_t = [O^0_t, O^1_t, O^2_t]$, with the superscript denoting the corresponding arity. The action $a_t = [I^0_t, I^1_t, \ldots, I^{K-1}_t]$ (e.g., $a_0 = [000011]$) is a binary vector that indicates the activated neural operators (i.e., the operator footprint), where K is the number of operators per layer. The reward r_t is defined to be

$$r_t := \begin{cases} -\sum_{i=0}^{K-1} I^i_t, & \text{if } t < T_{\max} \\ \texttt{Accuracy}, & t = T_{\max} \end{cases}. \tag{1}$$

That is, the terminal reward is set to be the reasoning accuracy at the end of the reasoning path (see Appendix A.2 for its definition), and the intermediate reward at each step is chosen to be the negated number of activated operators (which penalizes the cost of performing the current reasoning step). The transition kernel $P^a_{ss'}$ corresponds to the function modeled by one Reasoner layer; each Reasoner layer will take the state (predicates) $s_{t-1} = [O^0_{t-1}, O^1_{t-1}, O^2_{t-1},]$ and the action (operator footprint) $a_t = [I^0_t, I^1_t, \ldots, I^{K-1}_t]$ as its input and then generate the next state (predicates) $s_t = [O^0_t, O^1_t, O^2_t,]$. This also implies that the Reasoner layer defines a deterministic transition kernel, i.e., given s_{t-1} and a_t the next state s_t is determined.

Table 1: The identification between the concepts of PRIMA/PRISA and that of RL at the t-th time step.

RL	State s_t	Action a_t	Reward r_t	Transition Kernel $P^a_{ss'}$	Policy	Rollout
PRIMA/PRISA	Predicates of different arities: $[O^0_t, O^1_t, O^2_t]_t$	Operator footprint: $[I^0_t \ldots I^{K-1}_t]$	Eq. (1)	One layer of **Reasoner**	**Planner**	Reasoning path

3.2 POLICY NETWORK: MODELING OF PLANNER

The Planner module is embodied in the policy network. As shown in Fig. 3A, the base planner is a separate module that has the same architecture of 1-layer (fully-activated) Reasoner followed

by a max-pooling layer. This architecture enables the reduction of input predicates to the specific indicators by reflecting whether the operations at the corresponding position of one layer of Reasoner are active or inactive. Further, we can also leverage Monte-Carlo Tree Search (MCTS) (Browne et al., 2012; Munos, 2014) to boost the performance, which leads to an Enhanced Planner (Fig. 3B). An MCTS algorithm such as the Upper Confidence Bound for Trees (UCT) method (Kocsis et al., 2006), is a model-based RL algorithm that plans the best action at each time step (Browne et al., 2012) by constructing a search tree, with states as nodes and actions as edges. The Enhanced Planner uses MCTS to exploit partial knowledge of the problem structure (i.e., the deterministic transition kernel $P_{ss'}^a$ defined by the Reasoner layer) and construct a search tree to help identify the best actions (which ops to activate). Details of the MCTS algorithms used in the Enhanced Planner can be found in Appendix A.1.

3.3 OVERALL LEARNING FRAMEWORK

As illustrated in Fig. 3, we introduce concrete data-driven decision-making methods—that is, RL approaches (Sutton & Barto, 2018)—to address the learning-to-reason problem. To illustrate this, we apply the model-free RL method REINFORCE (Williams, 1992) and the model-based method MuZero (Schrittwieser et al., 2019). Compared with model-free reinforcement learning, model-based reinforcement learning (MBRL) more effectively handles large search-space problems, such as the game of Go (Silver et al., 2017b;b;a). MuZero (Schrittwieser et al., 2019), a recently proposed MBRL approach to integrating planning and learning, has achieved great success with a variety of complex tasks. Motivated by the success of MuZero, we propose an MBRL approach for neural-symbolic reasoning. The key insight behind adopting MuZero is that in real applications, we typically have partial structural knowledge of the transition kernel $P_{ss'}^a$ and reward function $r(s, a)$. As a result of the model-based module, testing complexity can be greatly reduced by adopting MCTS, which leads to a better set of predicates. Of course, MuZero is just one option in the model-based family of approaches. We leave it as future research to propose and compare other model-based alternatives.

The pipeline of the training process is illustrated in Fig.2.B (the right subfigure). After loading the model weights, the reasoning path rollouts are executed by the agent (or model instance), according to the current policy network. The performed reasoning path rollout is then stored in the replay buffer. The Planner-Reasoner is trained via rollouts sampled from the replay buffer.

4 EXPERIMENTAL RESULTS AND ANALYSIS

In this section, we evaluate the performance of different variants of PRISA (for single-task reasoning) and PRIMA (for multi-task reasoning) on eight tasks from the family tree and graph benchmarks (Graves et al., 2016), including `1-Outdegree`, `AdjacentToRed`, `HasFather`, `HasSister`, `4-Connectivity`, `IsGrandparent`, `IsUncle`, `IsMGUncle`. These tasks are widely used benchmark domains for inductive logic programming (Krötzsch, 2020; Calautti et al., 2015). Detailed descriptions about those tasks can be found in Appendix B.1. We evaluate their testing accuracy and reasoning cost (measured in FLOPs: the number of floating-point operations executed (Clark et al., 2020)) on these tasks and compare them to several baselines. Besides, the case study is conducted on the reasoning path, which indicates the operator sharing among different tasks. All the results demonstrate the graceful capability-efficiency tradeoff of PRIMA in multi-task reasoning.

4.1 EXPERIMENTAL SETUPS

Regarding the data generated in the single-task setting, we use the same methods as in NLM (Dong et al., 2019). A task will be randomly sampled in the multi-task setting according to a pre-defined probability distribution on different tasks. Compared to the generated data with that of the single task, it is augmented by using one-hot encoding for different tasks and wrapping it into nullary (background) predicates. Also, task-specific output heads are introduced to adapt to the multi-task setting. These adaptions apply to NLM-MTR, DLM-MTR, and PRIMA. The reasoning accuracy is used as the reward for both PRISA-MuZero and PRIMA. In the inference (or testing) stage, the Reasoner is combined with the learned Base Planner to perform the tasks for PRISA-MuZero and PRIMA, instead of an enhanced planner (MCTS), to reduce the extra computation. The problem

Table 2: **Testing Accuracy and PSS** of different variants of PRISA on different tasks. PRISA-MuZero achieves the best performance on single-task reasoning, which confirms the strength of the MCTS-based Enhanced Planner and the MuZero learning strategy. "*m*": the problem size. "PSS": Percentage of Successful Seeds.

			Family Tree	HasFather	HasSister	IsGrandparent	IsUncle	IsMGUncle	Graph	AdjacentToRed	4-Connectivity	1-OutDegree
testing acc	Single Task	PRISA-REINFORCE	m=20	62.6	50.7	96.5	97.3	99.8	m=10	47.7	33.5	48.7
			m=100	87.8	69.8	2.3	97.7	98.4	m=50	71.6	92.8	97.4
			PSS	0	0	0	0	0	PSS	0	0	0
		PRISA-PPO	m=20	71.5	64.3	97.5	98.1	99.6	m=10	62.3	57.8	61.6
			m=100	93.2	78.7	98.2	97.3	99.1	m=50	85.5	95.2	96.3
			PSS	0	0	0	0	0	PSS	0	0	0
		PRISA-MuZero	m=20	**100**	**100**	**100**	**100**	**100**	m=10	**100**	**100**	**100**
			m=100	**100**	**100**	**100**	**100**	**100**	m=50	**100**	**100**	**100**
			PSS	**100**	**100**	**100**	**100**	**100**	PSS	**90**	**100**	**100**

size for training is always 10 for graph tasks and 20 for family tree tasks across all single-task and multi-task settings, regardless of the sizes of testing problems.

4.2 OVERALL PERFORMANCE

Single-task reasoning capability First, we compare the performance of three different variants of PRISA (Section 3.3) for single-task reasoning, which learns their planners based on different reinforcement learning algorithms; PRISA-REINFORCE uses REINFORCE (Williams, 1992), PRISA-PPO uses PPO (Schulman et al., 2017), and PRISA-MuZero uses MuZero (Schrittwieser et al., 2019). We report the test accuracy and the Percentage of Successful Seeds (PSS) in Table 2 to measure the model's reasoning *capabilities*, where the PSS reaches 100% of success rates (Matthieu et al., 2021). We note that PRISA-MuZero has the same 100% accuracy as NLM (Dong et al., 2019), DLM (Matthieu et al., 2021), and ∂ILP (Evans & Grefenstette, 2018) across different tasks, and outperforms MemNN (Sukhbaatar et al., 2015) (shown in the single-task part in Table 3). But it also has a higher successful percentage (PSS) in comparison with other methods. The results show that PRISA-MuZero achieves the best performance on single-task reasoning, which confirms the strength of the MCTS-based Enhanced Planner (Section 3.3) and the MuZero learning strategy. Therefore, we will use the Enhanced Planner and MuZero in PRISA and PRIMA in the rest of our empirical studies.

Multi-task reasoning capability Next, we evaluate the MTR capabilities of PRIMA. To the best of our knowledge, there is no existing approach that is designed specifically for MTR. Therefore, we adapt NLM and DLM into their multi-task versions, named NLM-MTR and DLM-MTR, respectively. NLM-MTR and DLM-MTR follow the same input and output modification as what we did to upgrade PRISA to PRIMA (Section 2.4). By this, we can examine the contribution of our proposed *Planner-Reasoner architecture* for MTR. As shown in Table 3, PRIMA (with MuZero as the Base Planner) performs well (perfectly) on different reasoning tasks. On the other hand, DLM-MTR experiences some performance degradation (on `AdjacentToRed`). This result confirms that our Planner-Reasoner architecture is more suitable for MTR. We conjecture that the benefit comes from using a Planner to explicitly select the necessary neural operators for each task, avoiding potential conflicts between different tasks during the learning process.

Experiments are also conducted to test the performance of PRIMA with different problem sizes. The problem size in training is 10 for all graph tasks and 20 for all family-tree tasks. In testing, we evaluate the methods on much larger problem sizes (50 for the graph tasks and 100 for the family tree tasks), which the methods have not seen before. Therefore, the Planner must dynamically activate a proper set of neural operators to construct a path to solve the new problem. As reported in Fig. 4 and Tables 2 and 3, PRIMA can achieve the best accuracy and lower flops when the problem sizes for training and testing are different.

Reasoning efficiency To measure the reasoning efficiency of the proposed methods at the inference stage, PRIMA is compared with NLM, MemNN, and NLM-MTR in terms of FLOPs. As shown in Fig. 4, NLM and NLM-MTR demonstrate a similar performance and suffer the highest reasoning cost when it is tested with large problem sizes, such as 50 for graph tasks and 100 for family tree tasks. For MemNN, although the FLOPs of it seem low in most cases of testing, its testing accuracy is bad and cannot achieve accurate predictions (Table 3). In contrast, PRIMA can significantly reduce the reasoning complexity by intelligently selecting ops using a planner. Overall, PRIMA strikes a satisfactory capability-efficiency tradeoff in comparison with all available multi-tasking baselines.

Table 3: **Testing Accuracy and PSS** of PRIMA and other baselines on different reasoning tasks. The results of ∂ILP, NLM, and DLM are merged in one row due to space constraints and are presented in the same order if the results are different. Note that PRIMA's test efficiency is superior to NLM-MTR's as shown in Fig. 4. "*m*": the problem size. "PSS": Percentage of Successful Seeds. Numbers in red denote $< 100\%$.

		Family Tree	HasFather	HasSister	IsGrandparent	IsUncle	IsMGUncle	Graph	AdjacentToRed	4-Connectivity	1-OutDegree
Single Task	MemNN	m=20	99.9	86.3	96.5	96.3	99.7	m=10	95.2	92.3	99.8
		m=100	59.8	59.8	97.7	96	98.4	m=50	93.1	81.3	78.6
		PSS	0	0	0	0	0	PSS	0	0	0
	∂ILP/ NLM/ DLM	m=20	100	100	100	100	100	m=10	100	100	100
		m=100	100	100	100	100	100	m=50	100	100	100
		PSS	100	100	100	100/ 90/ 100	100/ 20/ 70	PSS	100/ 90/ 90	100	100
Multi-Task	NLM-MTR	m=20	100	100	100	100	100	m=10	100	100	100
		m=100	100	100	100	100	100	m=50	100	100	100
		PSS	100	100	100	100	90	PSS	90	100	100
	DLM-MTR	m=20	100	100	100	100	100	m=10	96.7	100	100
		m=100	100	100	100	100	100	m=50	97.2	100	100
		PSS	100	100	100	100	100	PSS	0	100	100
	PRIMA	m=20	100	100	100	100	100	m=10	100	100	100
		m=100	100	100	100	100	100	m=50	100	100	100
		PSS	100	100	100	100	90	PSS	90	100	100

Operator/Path Sharing in MTR To take a closer look into how PRIMA achieves such a better capability-efficiency tradeoff (in Fig. 4), we examine the reasoning paths on three different graph tasks: `1-Outdegree`, `AdjacentToRed`, and `4-Connectivity`. Specifically, we sample instances from these three tasks and feed them into PRIMA separately to generate their corresponding reasoning paths. The results are plotted in Fig. 5A, where the gray paths denote the ones shared across tasks, and the colored ones are task-specific. It clearly shows that PRIMA learns a large set of neural operators sharable across tasks. Given each input instance from a particular task, PRIMA activates a set of shared paths along with a few task-specific paths to deduce the logical consequences.

Generalizability of the Planner To demonstrate the generalizability of the Planner module in PRIMA, we generate input instances of `AdjacentToRed` with topologies that have not been seen during training. In Fig. 5B, we show the reasoning paths activated by the Planner for these different topologies, which demonstrates that different input instances share a large portion of reasoning paths. This fact is not surprising as solving the same task of `AdjacentToRed` should rely on a common set of skills. More interestingly, we notice that even for solving this same task, the Planner will have to call upon a few *instance-dependent* sub-paths to handle the subtle inherent differences (e.g., the graph topology) that exist between different input instances. For this reason, PRIMA maintains an instance-dependent *dynamic* architecture, which is in sharp contrast to the Neural Architecture Search (NAS) approaches. Although NAS may also use RL algorithms to seek for a smaller architecture (Zoph & Le, 2017), it only searches for a *static* architecture that will be applied to all the input instances.

Figure 4: The reasoning costs (in FLOPs) of different models at the inference stage (1 M=1×10^6, 1 G=1×10^9). Compared to NLM and NLM-MTR, our PRIMA significantly reduces the reasoning complexity by intelligently selecting ops (short for neural operators) using a planner. Although the FLOPs of MemNN seem low in most cases of testing, its testing accuracy is bad and cannot achieve accurate predictions (see Table 3). "OD" denotes `1-Outdegree`, likewise, "AR":`AdjacentToRed`, "4C":`4-Connectivity`, "HF":`HasFather`, "HS":`HasSister`, "GP":`IsGrandparent`, "UN":`IsUncle`, "MG":`IsMGUncle`.

5 RELATED WORK

Multi-task Learning Multi-task Learning (Zhang & Yang, 2021; Zhou et al., 2011; Pan & Yang, 2009) has focused primarily on the supervised learning paradigm, which itself can be divided into several approaches. The first is feature-based MTL, also called multi-task feature learning, (Argyriou

A. Skill sharing among different tasks. B. Instance-dependent reasoning path within the same task.

Figure 5: The reasoning paths of PRIMA. The gray arrows denote the "shared path". The colored arrows in sub-figures (A) and (B) denote task-specific paths and instance-specific paths, respectively. In (A), besides the AdjacentToRed task we have introduced earlier, we also consider the 1-Outdegree task, which reasons about whether the out-degree of a node is exactly equal to 1, and the 4-Connectivity task, which is to decide whether there are two nodes connected within 4 hops.

et al., 2008), which explores the sharing of features across different tasks using regularization techniques (Shinohara, 2016; Liu et al., 2017). The second approach assumes that tasks are intrinsically related, such as low-rank learning (Ando & Zhang, 2005; Zhang et al., 2005), learning with task clustering (Gu et al., 2011; Zhang et al., 2016), and task-relation learning (such as via task similarity, task correlation, or task covariance) (Goncalves et al., 2016; Zhang, 2013; Ciliberto et al., 2015). MTL has also been explored under other paradigms such as unsupervised learning, for example, via multi-task clustering in (Zhang & Zhang, 2013; Zhang et al., 2015b; Gu et al., 2011; Zhang, 2015).

Neural-Symbolic Reasoning Neural-symbolic AI for reasoning and inference has a long history (Besold et al., 2017; Bader et al., 2004; Garcez et al., 2008), and neural-ILP has developed primarily in two major directions (Cropper et al., 2020b). The first direction applies neural operators such as tensor calculus to simulate logic reasoning (Yang et al., 2017; Dong et al., 2019; Shi et al., 2020) and (Manhaeve et al., 2018). This approach uses binary tensors over constant domains to represent the predicates and tensor chain products to simulate logic clauses. The second direction involves relaxed subset selection (Evans & Grefenstette, 2018; Si et al., 2019) with a predefined set of task-specific logic clauses. This approach reduces the task to a subset-selection problem by selecting a subset of clauses from the predefined set and using neural networks to search for a relaxed solution.

Our work is different from the most recent work, such as (Dong et al., 2019; Shi et al., 2020), in several ways. Compared with (Dong et al., 2019), the most notable difference is the improvement in efficiency by introducing learning-to-reason via reinforcement learning. A second major difference is that PRIMA offers more generalizability than NLM by decomposing the logic operators into more finely-grained units. We refer readers for more detailed related work to Appendix D.

6 CONCLUSION

A long-standing challenge in multi-task learning is the intrinsic conflict between capability and efficiency. In this paper, we propose a Planner-Reasoner framework for multi-task reasoning. To maintain broad capability but efficient specific performance, the Reasoner extracts shareable meta-rules via first-order logic, from which the Planner efficiently selects a subset of meta-rules to formulate the reasoning path. The model's training follows a complete data-driven end-to-end approach via deep reinforcement learning, and the performance is validated across a variety of benchmark tasks. Future work could include extending the framework to high-order logic and investigating scenarios when meta-rules have a hierarchical structure.

REPRODUCIBILITY STATEMENT

We commit to ensuring that other researchers with reasonable background knowledge in our area can reproduce our theoretical and empirical results. The algorithm details can be seen in Appendix A. Specifically, benchmark details are provided in Appendix B.1, hyper-parameter settings are provided in Appendix B.2, and computing infrastructure are detailed in Appendix B.3. The experiment details can be seen in Appendix B.

ETHICS STATEMENT

This work is about the methodology of achieving a capability-efficiency trade-off in multi-task first-order logic reasoning. The potential impact of this work is likely to further extend the framework to high-order logic and investigate scenarios when meta-rules have a hierarchical structure, which should be generally beneficial to the multi-task learning research community. We have not considered specific applications or practical scenarios as the goal of this work. Hence, it does not have any direct ethical consequences.

REFERENCES

Rie Kubota Ando and Tong Zhang. A framework for learning predictive structures from multiple tasks and unlabeled data. *JMLR*, 2005.

Jacob Andreas, Dan Klein, and Sergey Levine. Modular multitask reinforcement learning with policy sketches. In *ICML*, 2017.

Peter B Andrews. *An introduction to mathematical logic and type theory*, volume 27. Springer Science & Business Media, 2002.

Andreas Argyriou, Theodoros Evgeniou, and Massimiliano Pontil. Convex multi-task feature learning. *MLJ*, 2008.

Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

Sebastian Bader and Pascal Hitzler. Dimensions of neural-symbolic integration-a structured survey. *arXiv preprint cs/0511042*, 2005.

Sebastian Bader, Pascal Hitzler, and Steffen Hölldobler. The integration of connectionism and first-order knowledge representation and reasoning as a challenge for artificial intelligence. *arXiv preprint cs/0408069*, 2004.

Peter W Battaglia, Razvan Pascanu, Matthew Lai, Danilo Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. *arXiv preprint arXiv:1612.00222*, 2016.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Yoshua Bengio. From system 1 deep learning to system 2 deep learning. In *Thirty-third Conference on Neural Information Processing Systems*, 2019.

Tarek R Besold, Artur d'Avila Garcez, Sebastian Bader, Howard Bowman, Pedro Domingos, Pascal Hitzler, Kai-Uwe Kühnberger, Luis C Lamb, Daniel Lowd, Priscila Machado Vieira Lima, et al. Neural-symbolic learning and reasoning: A survey and interpretation. *arXiv preprint arXiv:1711.03902*, 2017.

Timo Bräm, Gino Brunner, Oliver Richter, and Roger Wattenhofer. Attentive multi-task deep reinforcement learning. In *ECML/PKDD*, 2019.

Cameron B Browne, Edward Powley, Daniel Whitehouse, Simon M Lucas, Peter I Cowling, Philipp Rohlfshagen, Stephen Tavener, Diego Perez, Spyridon Samothrakis, and Simon Colton. A survey of monte carlo tree search methods. *IEEE Transactions on Computational Intelligence and AI in games*, 4(1):1–43, 2012.

Salam El Bsat, Haitham Bou-Ammar, and Matthew E. Taylor. Scalable multitask policy gradient reinforcement learning. In *AAAI*, 2017.

Daniele Calandriello, Alessandro Lazaric, and Marcello Restelli. Sparse multi-task reinforcement learning. In *NIPS*, 2014.

Marco Calautti, Georg Gottlob, and Andreas Pieris. Chase termination for guarded existential rules. In *Proceedings of the 34th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems*, pp. 91–103, 2015.

L. Cao. Non-iid recommender systems: A review and framework of recommendation paradigm shifting. *Engineering*, 2(2):212–224, 2016.

Deepayan Chakrabarti and Christos Faloutsos. Graph mining: Laws, generators, and algorithms. *ACM computing surveys (CSUR)*, 38(1):2–es, 2006.

Ashok K Chandra and David Harel. Horn clause queries and generalizations. *The Journal of Logic Programming*, 2(1):1–15, 1985.

Jianzhong Chen, Stephen Muggleton, and José Santos. Learning probabilistic logic models from probabilistic examples. *Machine learning*, 73(1):55–85, 2008.

Xinlei Chen, Li-Jia Li, Li Fei-Fei, and Abhinav Gupta. Iterative visual reasoning beyond convolutions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7239–7248, 2018.

Carlo Ciliberto, Youssef Mroueh, Tomaso A. Poggio, and Lorenzo Rosasco. Convex learning of multiple tasks and their structure. In *ICML*, 2015.

Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. Electra: Pre-training text encoders as discriminators rather than generators. *arXiv preprint arXiv:2003.10555*, 2020.

Diane J Cook and Lawrence B Holder. *Mining graph data*. John Wiley & Sons, 2006.

Michael Crawshaw. Multi-task learning with deep neural networks: A survey. *arXiv preprint arXiv:2009.09796*, 2020.

Andrew Cropper and Sebastijan Dumancic. Inductive logic programming at 30: a new introduction. *arXiv preprint arXiv:2008.07912*, 2020.

Andrew Cropper, Sebastijan Dumancic, and Stephen H Muggleton. Turning 30: New ideas in inductive logic programming. *arXiv preprint arXiv:2002.11002*, 2020a.

Andrew Cropper, Sebastijan Dumancic, and Stephen H Muggleton. Turning 30: New ideas in inductive logic programming. *arXiv preprint arXiv:2002.11002*, 2020b.

Aniket Anand Deshmukh, Ürün Dogan, and Clayton Scott. Multi-task learning for contextual bandits. In *NIPS*, 2017.

Carlos Diuk, Andre Cohen, and Michael L Littman. An object-oriented representation for efficient reinforcement learning. In *Proceedings of the 25th international conference on Machine learning*, pp. 240–247, 2008.

Honghua Dong, Jiayuan Mao, Tian Lin, Chong Wang, Lihong Li, and Denny Zhou. Neural logic machines. *arXiv preprint arXiv:1904.11694*, 2019.

Sašo Džeroski, Luc De Raedt, and Kurt Driessens. Relational reinforcement learning. *Machine learning*, 43(1):7–52, 2001.

Lasse Espeholt, Hubert Soyer, Rémi Munos, Karen Simonyan, Volodymyr Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, Shane Legg, and Koray Kavukcuoglu. IMPALA: scalable distributed deep-RL with importance weighted actor-learner architectures. In *ICML*, 2018.

Richard Evans and Edward Grefenstette. Learning explanatory rules from noisy data. *Journal of Artificial Intelligence Research*, 61:1–64, 2018.

Melvin Fitting. *First-order logic and automated theorem proving*. Springer Science & Business Media, 2012.

Jean H Gallier. *Logic for computer science: foundations of automatic theorem proving*. Courier Dover Publications, 2015.

M. C. Ganiz, C. George, and W. M Pottenger. Higher order naive bayes: A novel non-iid approach to text classification. *IEEE Transactions on Knowledge and Data Engineering*, 23(7):1022–1034, 2010.

Artur SD'Avila Garcez, Luis C Lamb, and Dov M Gabbay. *Neural-symbolic cognitive reasoning*. Springer Science & Business Media, 2008.

André R. Goncalves, Fernando J. Von Zuben, and Arindam Banerjee. Multi-task sparse structure learning with Gaussian copula models. *JMLR*, 2016.

Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538(7626): 471–476, 2016.

Quanquan Gu, Zhenhui Li, and Jiawei Han. Learning a kernel for multi-task clustering. In *AAAI*, 2011.

Carlos Guestrin, Daphne Koller, Chris Gearhart, and Neal Kanodia. Generalizing plans to new environments in relational mdps. In *Proceedings of the 18th international joint conference on Artificial intelligence*, pp. 1003–1010, 2003.

Alfred Horn. On sentences which are true of direct unions of algebras1. *The Journal of Symbolic Logic*, 16(1):14–21, 1951.

Maximilian Igl, Andrew Gambardella, Nantas Nardelli, N. Siddharth, Wendelin Böhmer, and Shimon Whiteson. Multitask soft option learning. In *UAI*, 2020.

Herbert Jaeger. Deep neural reasoning. *Nature*, 538(7626):467–468, 2016.

Ramtin Keramati, Jay Whang, Patrick Cho, and Emma Brunskill. Strategic object oriented reinforcement learning. In *Exploration in Reinforcement Learning Workshop at the 35th International Conference on Machine Learning*, 2018.

Levente Kocsis, Csaba Szepesvári, and Jan Willemson. Improved monte-carlo search. *Univ. Tartu, Estonia, Tech. Rep*, 1, 2006.

Daphne Koller. Probabilistic relational models. In *International Conference on Inductive Logic Programming*, pp. 3–13. Springer, 1999.

Daphne Koller, Nir Friedman, Sašo Džeroski, Charles Sutton, Andrew McCallum, Avi Pfeffer, Pieter Abbeel, Ming-Fai Wong, David Heckerman, Chris Meek, et al. *Introduction to statistical relational learning*. MIT press, 2007.

Markus Krötzsch. Computing cores for existential rules with the standard chase and asp. In *Proceedings of the International Conference on Principles of Knowledge Representation and Reasoning*, volume 17, pp. 603–613, 2020.

Alessandro Lazaric and Mohammad Ghavamzadeh. Bayesian multi-task reinforcement learning. In *ICML*, 2010.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Hui Li, Xuejun Liao, and Lawrence Carin. Multi-task reinforcement learning in partially observable stochastic environments. *JMLR*, 2009.

Sijin Li, Zhi-Qiang Liu, and Antoni B. Chan. Heterogeneous multi-task learning for human pose estimation with deep convolutional neural network. *IJCV*, 2015.

Xingyu Lin, Harjatin Singh Baweja, George Kantor, and David Held. Adaptive auxiliary task weighting for reinforcement learning. In *NeurIPS*, 2019.

Pengfei Liu, Xipeng Qiu, and Xuanjing Huang. Adversarial multi-task learning for text classification. In *ACL*, 2017.

Wu Liu, Tao Mei, Yongdong Zhang, Cherry Che, and Jiebo Luo. Multi-task deep visual-semantic embedding for video thumbnail selection. In *CVPR*, 2015.

Robin Manhaeve, Sebastijan Dumancic, Angelika Kimmig, Thomas Demeester, and Luc De Raedt. Deepproblog: Neural probabilistic logic programming. In *Advances in Neural Information Processing Systems*, pp. 3749–3759, 2018.

Zimmer Matthieu, Feng Xuening, Glanois Claire, Jiang Zhaohui, Zhang Jianyi, Weng Paul, Jianye Hao, Dong Li, and Wulong Liu. Differentiable logic machines. *arXiv preprint arXiv:2102.11529*, 2021.

Nikola Mrksic, Diarmuid Ó Séaghdha, Blaise Thomson, Milica Gasic, Pei-hao Su, David Vandyke, Tsung-Hsien Wen, and Steve J. Young. Multi-domain dialog state tracking using recurrent neural networks. In *ACL*, 2015.

Stephen Muggleton and Luc De Raedt. Inductive logic programming: Theory and methods. *The Journal of Logic Programming*, 19:629–679, 1994.

Remi Munos. From bandits to monte-carlo tree search: The optimistic principle applied to optimization and planning. *Foundations and Trends in Machine Learning*, 2014.

Shayegan Omidshafiei, Jason Pazis, Christopher Amato, Jonathan P. How, and John Vian. Deep decentralized multi-task multi-agent reinforcement learning under partial observability. In *ICML*, 2017.

Rasmus Berg Palm, Ulrich Paquet, and Ole Winther. Recurrent relational networks. *arXiv preprint arXiv:1711.08028*, 2017.

Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359, 2009.

Emilio Parisotto, Jimmy Ba, and Ruslan Salakhutdinov. Actor-mimic: Deep multitask and transfer reinforcement learning. In *ICLR*, 2016.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Christopher D Rosin. Multi-armed bandits with episode context. *Annals of Mathematics and Artificial Intelligence*, 61(3):203–230, 2011.

Andrei A. Rusu, Sergio Gomez Colmenarejo, Çaglar Gülçehre, Guillaume Desjardins, James Kirkpatrick, Razvan Pascanu, Volodymyr Mnih, Koray Kavukcuoglu, and Raia Hadsell. Policy distillation. In *ICLR*, 2016.

Adam Santoro, David Raposo, David GT Barrett, Mateusz Malinowski, Razvan Pascanu, Peter Battaglia, and Timothy Lillicrap. A simple neural network module for relational reasoning. *arXiv preprint arXiv:1706.01427*, 2017.

Shibani Santurkar, Dimitris Tsipras, Andrew Ilyas, and Aleksander Madry. How does batch normalization help optimization? *arXiv preprint arXiv:1805.11604*, 2018.

Andrew M. Saxe, Adam Christopher Earle, and Benjamin Rosman. Hierarchy through composition with multitask LMDPs. In *ICML*, 2017.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *arXiv preprint arXiv:1911.08265*, 2019.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Sahil Sharma and Balaraman Ravindran. Online multi-task learning using active sampling. In *ICLR Workshop*, 2017.

Sahil Sharma, Ashutosh Kumar Jha, Parikshit Hegde, and Balaraman Ravindran. Learning to multi-task by active sampling. In *ICLR*, 2018.

Shaoyun Shi, Hanxiong Chen, Weizhi Ma, Jiaxin Mao, Min Zhang, and Yongfeng Zhang. Neural logic reasoning. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, pp. 1365–1374, 2020.

Yusuke Shinohara. Adversarial multi-task learning of deep neural networks for robust speech recognition. In *Interspeech*, 2016.

Xujie Si, Mukund Raghothaman, Kihong Heo, and Mayur Naik. Synthesizing datalog programs using numerical relaxation. *arXiv preprint arXiv:1906.00163*, 2019.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. Mastering chess and shogi by self-play with a general reinforcement learning algorithm. *arXiv preprint arXiv:1712.01815*, 2017a.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017b.

Sainbayar Sukhbaatar, Arthur Szlam, Jason Weston, and Rob Fergus. End-to-end memory networks. In *Advances in Neural Information Processing Systems*, pp. 2440–2448, 2015.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Prasad Tadepalli, Robert Givan, and Kurt Driessens. Relational reinforcement learning: An overview. In *Proceedings of the ICML-2004 workshop on relational reinforcement learning*, pp. 1–9, 2004.

Yee Whye Teh, Victor Bapst, Wojciech M. Czarnecki, John Quan, James Kirkpatrick, Raia Hadsell, Nicolas Heess, and Razvan Pascanu. Distral: Robust multitask reinforcement learning. In *NIPS*, 2017.

Rasul Tutunov, Dongho Kim, and Haitham Bou-Ammar. Distributed multitask reinforcement learning with quadratic convergence. In *NeurIPS*, 2018.

Frank Van Harmelen, Vladimir Lifschitz, and Bruce Porter. *Handbook of knowledge representation*. Elsevier, 2008.

Nelson Vithayathil Varghese and Qusay H Mahmoud. A survey of multi-task deep reinforcement learning. *Electronics*, 9(9):1363, 2020.

Tung-Long Vuong, Do Van Nguyen, Tai-Long Nguyen, Cong-Minh Bui, Hai-Dang Kieu, Viet-Cuong Ta, Quoc-Long Tran, and Thanh Ha Le. Sharing experience in multitask reinforcement learning. In *IJCAI*, 2019.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Aaron Wilson, Alan Fern, Soumya Ray, and Prasad Tadepalli. Multi-task reinforcement learning: A hierarchical Bayesian approach. In *ICML*, 2007.

Victoria Xia, Zi Wang, and Leslie Pack Kaelbling. Learning sparse relational transition models. *arXiv preprint arXiv:1810.11177*, 2018.

Fan Yang, Zhilin Yang, and William W Cohen. Differentiable learning of logical rules for knowledge base reasoning. In *Advances in Neural Information Processing Systems*, pp. 2319–2328, 2017.

Kexin Yi, Jiajun Wu, Chuang Gan, Antonio Torralba, Pushmeet Kohli, and Josh Tenenbaum. Neural-symbolic vqa: Disentangling reasoning from vision and language understanding. In *NIPS*, pp. 1031–1042, 2018.

N. Yoshida, T. Nishio, M. Morikura, K. Yamamoto, and R. Yonetani. Hybrid-fl for wireless networks: Cooperative learning mechanism using non-iid data. In *ICC 2020-2020 IEEE International Conference on Communications (ICC)*, pp. 1–7. IEEE, 2020.

Vinicius Zambaldi, David Raposo, Adam Santoro, Victor Bapst, Yujia Li, Igor Babuschkin, Karl Tuyls, David Reichert, Timothy Lillicrap, Edward Lockhart, et al. Relational deep reinforcement learning. *arXiv preprint arXiv:1806.01830*, 2018.

Jian Zhang, Zoubin Ghahramani, and Yiming Yang. Learning multiple related tasks using latent independent component analysis. In *NIPS*, 2005.

Si Zhang, Hanghang Tong, Jiejun Xu, and Ross Maciejewski. Graph convolutional networks: a comprehensive review. *Computational Social Networks*, 6(1):1–23, 2019.

Wenlu Zhang, Rongjian Li, Tao Zeng, Qian Sun, Sudhir Kumar, Jieping Ye, and Shuiwang Ji. Deep model based transfer and multi-task learning for biological image analysis. In *KDD*, 2015a.

Xianchao Zhang and Xiaotong Zhang. Smart multi-task Bregman clustering and multi-task kernel clustering. In *AAAI*, 2013.

Xianchao Zhang, Xiaotong Zhang, and Han Liu. Smart multitask Bregman clustering and multitask kernel clustering. *ACM TKDD*, 2015b.

Xianchao Zhang, Xiaotong Zhang, and Han Liu. Self-adapted multi-task clustering. In *IJCAI*, 2016.

Xiao-Lei Zhang. Convex discriminative multitask clustering. *IEEE TPAMI*, 2015.

Yu Zhang. Heterogeneous-neighborhood-based multi-task local learning algorithms. In *NIPS*, 2013.

Yu Zhang and Qiang Yang. A survey on multi-task learning. *IEEE Transactions on Knowledge and Data Engineering*, 2021.

Zhanpeng Zhang, Ping Luo, Chen Change Loy, and Xiaoou Tang. Facial landmark detection by deep multi-task learning. In *ECCV*, 2014.

Jiayu Zhou, Jianhui Chen, and Jieping Ye. Malsar: Multi-task learning via structural regularization. *Arizona State University*, 21, 2011.

Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. *AI Open*, 1:57–81, 2020.

Zhuangdi Zhu, Kaixiang Lin, and Jiayu Zhou. Transfer learning in deep reinforcement learning: A survey. *arXiv preprint arXiv:2009.07888*, 2020.

Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. *ICLR*, 2017.

SUPPLEMENTARY MATERIAL

A   ALGORITHM DETAILS

A.1   DETAILS OF MCTS: FOUR KEY STEPS

During each epoch, MCTS repeatedly performs four sequential steps: selection, expansion, simulation, and backpropagation. The selection step traverses the existing search tree until the leaf node (or termination condition) by choosing actions (edges) a_s at each node s according to a tree policy. One widely used tree policy is the UCT (Kocsis et al., 2006) policy, which conducts the node-selection via

$$a_s = \arg\max_{s' \in \mathcal{C}(s)} \left\{ V_{s'} + \beta \sqrt{\frac{2 \log N_s}{N_{s'}}} \right\}, \tag{2}$$

where $\mathcal{C}(s)$ denotes the set of all child nodes for s, the first term $V_{s'}$ is an estimate of the long-term cumulative reward that can be received when starting from the state represented by node s', and the second term represents the uncertainty (confidence-interval size) of that estimate. The confidence interval is calculated based on the upper confidence bound (UCB) (Auer et al., 2002; Auer, 2002) using N_s and $N_{s'}$, which denote the number of times that nodes s and s' have been visited (respectively). The key idea of UCT policy (2) is to select the best action according to an optimistic estimation (the upper confidence bound) of the expected return, which balances the exploitation (first term) and exploration (second term) with β controlling the trade-off. The second step (node expansion) is conducted according to a prior policy by adding a new child node if the selection process reaches a leaf node of the search tree. Next, the simulation step estimates the value function (cumulative reward) $\hat{V}_s$ by running the environment simulator with a default (simulation) policy. Finally, the *backpropagation* step updates the statistics V_s and N_s from the leaf node s_T to the root node s_0 of the selected path by recursively performing the following update (i.e., from $t = T - 1$ to $t = 0$):

$$N_{s_t} \leftarrow N_{s_t} + 1, \quad \hat{V}_{s_t} \leftarrow r(s_t, a_t) + \gamma \hat{V}_{s_{t+1}}, \quad V_{s_t} \leftarrow \left((N_{s_t} - 1) V_{s_t} + \hat{V}_{s_t} \right) / N_{s_t},$$

where $\hat{V}_{s_T}$ is the simulation return of s_T, and a_t denotes the action selected following (2) at state s_t. Generally, the expansion step and the simulation step are more time-consuming than the other two steps, as they involve a large number of interactions with the environment.

In our Enhanced Planner, we adopt a recently proposed variant of MCTS that is based on probabilistic upper confidence tree (PUCT) (Rosin, 2011). It conducts node-selection according to a so-called `PUCT` score with two components $\text{PUCT}(s, a) = Q(s, a) + U(s, a)$. $Q(s, a)$ is the mean state-action value calculated from the averaged game result that takes action a during current simulations, and $U(s, a)$ is the exploration bonus calculated as

$$U(s, a) = \pi(a|s) \frac{\sqrt{\sum_b N(s, b)}}{1 + N(s, a)} \left(c_1 + \log \left(\frac{\sum_b N(s, b) + c_2 + 1}{c_2} \right) \right),$$

where a, b are possible actions, $\pi(a|s)$ is the output of the Base Planner, $N(s, a)$ is the visit count of the (s, a) pair during current simulations, and constants c_1, c_2 are the exploration-controlling hyper-parameters.

An MCTS algorithm is a model-based RL algorithm that plans the best action at each time step (Browne et al., 2012) by constructing a search tree, with states as nodes and actions as edges. It uses the MDP model to identify the best action at each time step until the leaf node (or until other termination conditions are satisfied) by choosing actions (edges) a_s at each node s according to a tree policy. For implementations of Monte-Carlo Tree Search, we refer readers to `https://github.com/werner-duvaud/muzero-general` for details.

A.2   DETAILS OF CALCULATING REASONING ACCURACY

Since the "target" predicates are available for all objects or pairs of objects, the reasoning accuracy refers to the accuracy evaluated on all objects (for properties such as `AdjacentToRed(x)` or `1-OutDegree(x)`) or pairs of objects (for relations such as `4-Connectivity(x, y)`).

B EXPERIMENTAL DETAILS

B.1 REASONING TASKS INTRODUCTION

Graph   For graph tasks, they have the same background knowledge (or background predicate): $\texttt{HasEdge}(x, y)$, i.e., $\texttt{HasEdge}(x, y)$ is *True* if there is an undirected edge between node x and node y. However, $\texttt{AdjacentToRed}$ has an extra background predicate, $\texttt{Red}(x)$. $\texttt{Red}(x)$ is *True* if the color of node x is red. Specifically, these graph tasks seeks to predict the target concepts (or target predicates) shown as below.

- $\texttt{1-OutDegree}$: $\texttt{1-OutDegree}(x)$ is *True* if the out-degree of node x is exactly 1.

- $\texttt{AdjacentToRed}$: $\texttt{AdjacentToRed}(x)$ is *True* if the node x has an edge with a red node.

- $\texttt{4-Connectivity}$: $\texttt{4-Connectivity}(x, y)$ is *True* if there are within 4 hops between node x and node y.

Family Tree   For family tree tasks, they have the same background knowledge (or background predicates): $\texttt{IsFather}(x, y)$, $\texttt{IsMother}(x, y)$, $\texttt{IsSon}(x, y)$ and $\texttt{IsDaughter}(x, y)$. For instance, $\texttt{IsFather}(x, y)$ is *True* when y is x's father. Specifically, these family tree tasks seek to predict the target concepts (or target predicates) shown below.

- $\texttt{HasFather}$: $\texttt{HasFather}(x)$ is *True* if x has father.

- $\texttt{HasSister}$: $\texttt{HasSister}(x)$ is *True* if x has at least one sister.

- $\texttt{IsGrandparent}$: $\texttt{IsGrandparent}(x, y)$ is *True* if y is x's grandparent.

- $\texttt{IsUncle}$: $\texttt{IsUncle}(x, y)$ is *True* if y is x's uncle.

- $\texttt{IsMGUncle}$: $\texttt{IsMGUncle}(x, y)$ is *True* if y is x's maternal great uncle.

B.2 HYPER-PARAMETER SETTINGS

For simplicity, we set discount factor $\gamma = 1$ in all experiments. The $T_{\max}$ depends on the depth of the Reasoner. In single-task setting, we use the same hyper-parameter settings as in the original papers for MemNN (Sukhbaatar et al., 2015), ∂ILP (Evans & Grefenstette, 2018), NLM (Dong et al., 2019), and DLM (Matthieu et al., 2021). In multi-task setting, the probability distribution of sampling a task for NLM-MTR is $[0.09, 0.11, 0.11, 0.09, 0.09, 0.135, 0.135, 0.24]$ that is corresponding to the task list of $[\texttt{1-Outdegree}, \texttt{AdjacentToRed}, \texttt{4-Connectivity}, \texttt{HasFather}, \texttt{HasSister}, \texttt{IsGrandparent}, \texttt{IsUncle}, \texttt{IsMGUncle}]$. That distribution for DLM-MTR is $[0.1, 0.12, 0.12, 0.1, 0.1, 0.13, 0.13, 0.2]$. The details of hyper-parameters in NLM-MTR and DML-MTR can be found in Table 4. For all MLPs inside NLM-MTR, we keep the same settings as NLM. Similarly, the "Internal Logic", initial temperature and scale of the Gumbel distribution, and the dropout probability in DLM-MTR are also kept the same settings as those in DLM. Besides, the probability distribution of sampling a task for PRIMA is $[0.1, 0.12, 0.12, 0.1, 0.1, 0.13, 0.13, 0.2]$. Regarding the hyper-parameters of PRIMA, details can be found in Table 5. We also show the hyper-parameters of PRISA-REINFORCE, PRISA-PPO, PRISA-MuZero in Table 5.

We note that the problem size for training is always 10 for graph tasks and 20 for family tree tasks in single-task and multi-task settings.

B.3 COMPUTING INFRASTRUCTURE

We conducted our experiments on a CPU server where the CPU is "Intel(R) Xeon(R) Silver 4114 CPU" with 40 cores and 64 GB memory in total.

Table 4: Hyper-parameter settings for NLM-MTR and DML-MTR.

	NLM-MTR	DML-MTR
learning rate	0.005	0.005
epochs	50	200
epoch size	8000	2000
batch size (train)	4	4
breadth	3	3
depth	4	9

Table 5: Hyper-parameter settings for PRISA and PRIMA. "lr-reasoner" refers to the learning rate for the reasoner, "lr-policy" denotes the learning rate for the policy network, "lr-value" denotes the learning rate for the value network, "residual" refers to the residual connection in the reasoner, "NumWarmups" refers to the number of warm-ups before starting the training, "NumRollouts" refers to the number of roll-outs in MCTS, "RwdDecay" refers to the constant exponential decay applied on the reward, "c_1 and c_2" refers to the same constants in PUCT formula in Section A.1, "RBsize" refers to the replay buffer size that is used to count the number of stored trajectories, "BatchSize" refers to the batch size for training, "TrainingSteps" refers to the number of training steps. For PRISA-REINFORCE, PRISA-PPO, PRISA-MuZero, the "TrainingSteps" denotes the training steps for each task, while that of PRIMA represents the training steps for all 8 tasks.

	PRISA-REINFORCE	PRISA-PPO	PRISA-MuZero	PRIMA
lr-reasoner	0.005	0.005	0.005	0.004
lr-policy	0.085	0.085	0.075	0.075
lr-value	-	0.15	0.075	0.075
breadth	3	3	3	3
depth	4	4	4	4
residual	*False*	*False*	*False*	*False*
NumWarmups	-	-	200	200
NumRollouts	-	-	1200	1200
RwdDecay	5	5	5	5
c_1	-	-	30	30
c_2	-	-	19652	19652
RBsize	16	32	400	400
BatchSize	16	16	16	16
TrainingSteps	7×10^4	7×10^4	7×10^4	39×10^4

Table 6: Additional results: The performance of PRIMA w.r.t different numbers of intermediate predicates. "# pred": the number of intermediate predicates.

		Family Tree	HasFather	HasSister	IsGrandparent	IsUncle	IsMGUncle	Graph	AdjacentToRed	4-Connectivity	1-OutDegree
testing accuracy	# pred = 2	m=20	61.78	54.97	96.46	97.19	99.67	m=10	42.62	89.28	81.88
		m=100	87.5	31.2	97.7	96.5	98.4	m=50	11.1	96.6	96.5
		PSS	0	0	0	0	0	PSS	0	0	0
	# pred = 4	m=20	100	100	100	97.2	99.7	m=10	67.3	93.4	100
		m=100	100	100	100	96.6	98.4	m=50	91.7	97.8	100
		PSS	100	100	100	0	0	PSS	0	0	100
	# pred = 6	m=20	100	100	100	100	100	m=10	99.7	100	100
		m=100	100	100	100	100	100	m=50	100	100	100
		PSS	100	100	100	100	90	PSS	0	100	100
	# pred = 8	m=20	100	100	100	100	100	m=10	100	100	100
		m=100	100	100	100	100	100	m=50	100	100	100
		PSS	100	100	100	100	90	PSS	90	100	100

Figure 6: The reasoning costs (in FLOPs) of PRIMA and three variants of PRISA at the inference stage (1 M=1×10^6, 1 G=1×10^9).

C   ADDITIONAL EXPERIMENTS

C.1   REASONING COSTS OF PRISA

To demonstrate the improved reasoning efficiency in PRISA at the inference stage, three variants of PRISA (e.g., PRISA-REINFORCE, PRISA-PPO, and PRISA-MuZero) are compared with PRIMA in terms of FLOPs. As shown in Fig. 6, three variants of PRISA generally have lower reasoning complexity than PRIMA. The difference in FLOPs between PRIMA and PRISA-MuZero is primarily from the difference between multi-tasking setting and single-task setting.

C.2   PREDICATE DIMENSION ANALYSIS

Since the Reasoner only realizes a partial set of Horn clauses of FOL, the number of intermediate predicates will greatly determine the expressive power of the model. The performance of PRIMA degrades gracefully when the number of intermediate predicates decreases. This is shown in the additional experiments of examining the limiting performance of our PRIMA, where we examine the limiting performance of our PRIMA when the number of intermediate predicates at each layer decreases. The results in Table 6 show that the performance of PRIMA degrades gracefully when the number of intermediate predicates decreases; for example, it still performs reasonably well on most tasks even when the number of predicates becomes 4.

C.3   ANALYSIS OF MULTI-TASKING CAPABILITIES

Figure 7: The quantitative evaluation of ops reuse between different Tasks in PRIMA.

Why/how do different tasks share blocks (of ops) as in Fig. 7?   To quantitatively measure how different tasks reuses the "skills", we show in Fig. 7, which is a heat-map showing the probability of overlapping about Ops reuse across different tasks, where red color denotes a high-level of Ops overlapping. Ops reuse factor is defined as $\min(P_a(I^j), P_b(I^j))$ where $P_a(I^j)$ refers to the probability of ops $I^j (j \in \{0, \ldots, 9\})$ being active for task a and $P_b(I^j)$ denotes the probability of I^j being active for task b. From Fig. 7, it can be inferred that some tasks share skills more than others. For example, in most of the actions, I^8 is shared across different tasks.

D ADDITIONAL RELATED WORK

This section provides complementary contents to Sec. 5.

Multi-task RL Multi-task learning can help boost the performance of reinforcement learning, leading to multi-task reinforcement learning (Vithayathil Varghese & Mahmoud, 2020; Zhu et al., 2020). Some research (Wilson et al., 2007; Li et al., 2009; Lazaric & Ghavamzadeh, 2010; Calandriello et al., 2014; Andreas et al., 2017; Deshmukh et al., 2017; Saxe et al., 2017; Bräm et al., 2019; Vuong et al., 2019; Igl et al., 2020) has adapted the ideas behind multi-task learning to RL. For example, in (Bräm et al., 2019), a multi-task deep RL model based on attention can group tasks into sub-networks with state-level granularity. The idea of compression and distillation has been incorporated into multi-task RL as in (Parisotto et al., 2016; Rusu et al., 2016; Omidshafiei et al., 2017; Teh et al., 2017). For example, in (Parisotto et al., 2016), the proposed actor-mimic method combines deep reinforcement learning with model-compression techniques to train a policy network that can learn to act for multiple tasks. Other research in multi-task RL focuses on online and distributed settings (Bsat et al., 2017; Sharma & Ravindran, 2017; Sharma et al., 2018; Espeholt et al., 2018; Tutunov et al., 2018; Lin et al., 2019).

RL for Logic Reasoning Relational RL integrates RL with statistical relational learning and connects RL with classical AI for knowledge representation and reasoning. Most prominently, Džeroski et al. (2001) originally proposed relational RL, Tadepalli et al. (2004) surveyed relational RL, Guestrin et al. (2003) introduced relational MDPs, and Diuk et al. (2008) introduced objected-oriented MDPs (OO-MDPs). More recently, Battaglia et al. (2018) proposed to incorporate relational inductive bias, Zambaldi et al. (2018) proposed deep relational RL, Keramati et al. (2018) proposed strategic object-oriented RL, and some researchers have also adopted deep learning approaches for dealing with relations and/or reasoning, for example (Battaglia et al., 2016; Chen et al., 2018; Santoro et al., 2017; Santurkar et al., 2018; Palm et al., 2017; Xia et al., 2018; Yi et al., 2018).

Statistical Relational Reasoning Statistical relational reasoning (SRL) (Koller et al., 2007) often provides a better understanding of domains and predictive accuracy, but with more complex learning and inference processes. Unlike ILP, SRL takes a statistical and probabilistic learning perspective and extends the probabilistic formalism with relational aspects. Examples of SRL include text classification (Ganiz et al., 2010), recommendation systems (Cao, 2016), and wireless networks (Yoshida et al., 2020). SRL can be divided into two research branches: probabilistic relational models (PRMs) (Koller, 1999) and probabilistic logic models (PLMs) (Chen et al., 2008). PRMs start from probabilistic graphical models and then extend to relational aspects, while PLMs start from ILP and extend to probabilistic semantics. A related research area is graph relational reasoning, such as using graph neural networks (Zhou et al., 2020) to conduct reasoning. A discussion of this approach is beyond the scope of this paper, but we refer interested readers to (Chakrabarti & Faloutsos, 2006; Cook & Holder, 2006; Zhang et al., 2019) for a comprehensive review.

Comparisons with NLM in details The Reasoner shares the same functionality with NLM, in terms of approximating the meta-rules (`BooleanLogic`, `Expansion`, and `Reduction`). However, our Reasoner has major differences from NLM. *First*, the targets are different. Our Reasoner targets the trade-off between capability and efficiency. Compared with NLM, our Reasoner can greatly improve the efficiency by using a Planner module. *Second*, our Reasoner has more explicitness in the reasoning path. Let $[O_{i-1}^{r-1}, O_{i-1}^r, O_{i-1}^{r+1}]$ denote the output predicates (in tensor representation) from the previous layer, and $\mathrm{Concate}(\cdot)$ denotes the concatenation operation. NLM performs the intra-group computation as

$$O_i^r = \sigma\left(\mathrm{MLP}\left(\mathrm{Permute}\left(Z_i^r\right); \theta_i^r\right)\right),$$

where O_i^r is the output predicate, $Z_i^r = \mathrm{Concat}\left(\mathrm{Expand}\left(O_{i-1}^{r-1}\right), O_{i-1}^r, \mathrm{Reduce}\left(O_{i-1}^{r+1}\right)\right)$, σ is the sigmoid nonlinearity and θ_i^r denotes learnable parameters. On the contrary, in the Reasoner module

of our PRISA/PRIMA, the implementation is

$$O_i^r = \sigma \Bigg(\text{MLP}(\text{Permute}(\text{Expand}(O_{i-1}^{r-1})); \theta_i^r) + \text{MLP}(\text{Permute}(O_{i-1}^r); \theta_i^r)$$
$$+ \text{MLP}(\text{Permute}(\text{Reduce}(O_{i-1}^{r+1})); \theta_i^r) \Bigg),$$

which allows for the neural implementations of `BooleanLogic`, `Expansion`, and `Reduction` (at the same arity group) to be executed independently to some extent and reduce the unnecessary computations.