FROM t-SNE TO UMAP WITH CONTRASTIVE LEARNING

ABSTRACT

Neighbor embedding methods t-SNE and UMAP are the de facto standard for visualizing high-dimensional datasets. Motivated from entirely different viewpoints, their loss functions appear to be unrelated. In practice, they yield strongly differing embeddings and can suggest conflicting interpretations of the same data. The fundamental reasons for this and, more generally, the exact relationship between t-SNE and UMAP have remained unclear. In this work, we uncover their conceptual connection via a new insight into contrastive learning methods. Noise-contrastive estimation can be used to optimize t-SNE, while UMAP relies on negative sampling, another contrastive method. We find the precise relationship between these two contrastive methods, and provide a mathematical characterization of the distortion introduced by negative sampling. Visually, this distortion results in UMAP generating more compact embeddings with tighter clusters compared to t-SNE. We exploit this new conceptual connection to propose and implement a generalization of negative sampling, allowing us to interpolate between (and even extrapolate beyond) t-SNE and UMAP and their respective embeddings. Moving along this spectrum of embeddings leads to a trade-off between discrete/local and continuous/global structures, mitigating the risk of over-interpreting ostensible features of any single embedding. We provide a PyTorch implementation.

1 INTRODUCTION

Low-dimensional visualization of high-dimensional data is a ubiquitous step in exploratory data analysis, and the toolbox of visualization methods has been rapidly growing in the last years (McInnes et al., 2018; Amid & Warmuth, 2019; Szubert et al., 2019; Wang et al., 2021). Since all of these methods necessarily distort the true data layout (Chari et al., 2021), it is beneficial to have various tools at one's disposal. But only equipped with a theoretic understanding of the aims of and relationships between different methods, can practitioners make informed decisions about which visualization to use for which purpose and how to interpret the results.

The state of the art for non-parametric, non-linear dimensionality reduction relies on the neighbor embedding framework (Hinton & Roweis, 2002). Its two most popular examples are are t-SNE (van der Maaten & Hinton, 2008; van der Maaten, 2014) and UMAP (McInnes et al., 2018). Both can produce insightful, but qualitatively distinct embeddings. However, why their embeddings are different and what exactly is the conceptual relation between their loss functions, has remained elusive.

Here, we answer this question and thus explain the mathematical underpinnings of the relationship between t-SNE and UMAP. Our conceptual insight naturally suggests a spectrum of embedding methods complementary to that of Böhm et al. (2022), along which the focus of the visualization shifts from global to local structure (Fig. 1). On this spectrum, UMAP and t-SNE are simply two instances and inspecting various embeddings helps to guard against over-interpretation of apparent structure. As a practical corollary, our analysis identifies and remedies an instability in UMAP.

We provide the new connection between t-SNE and UMAP via a deeper understanding of contrastive learning methods. Noise-contrastive estimation (NCE) (Gutmann & Hyvärinen, 2010; 2012) can be used to optimize t-SNE (Artemenkov & Panov, 2020), while UMAP relies on another contrastive method, negative sampling (NEG) (Mikolov et al., 2013). We investigate the discrepancy between NCE and NEG, show that NEG introduces a distortion, and this distortion explains how UMAP and

Figure 1: **(a−e)** Neg-t-SNE embedding spectrum of the MNIST dataset for various values of the fixed normalization constant $\bar{Z}$, see Sec. 5. As $\bar{Z}$ increases, the scale of the embedding decreases, clusters become more compact and separated before eventually starting to merge. The Neg-t-SNE spectrum produces embeddings very similar to those of **(f)** t-SNE, **(g)** NCVis, and **(h)** UMAP, when $\bar{Z}$ equals the partition function of t-SNE, the learned normalization parameter Z of NCVis, or $|X|/m = \binom{n}{2}/m$ used by UMAP, as predicted in Sec. 4–6. **(i)** The partition function $\sum_{ij}(1+d_{ij}^2)^{-1}$ tries to match $\bar{Z}$ and grows with it. Here, we initialized all Neg-t-SNE runs using $\bar{Z} = |X|/m$; without this 'early exaggeration', low values of $\bar{Z}$ yield fragmented clusters (Fig. S7).

t-SNE embeddings differ. Finally, we discuss the relationship between neighbor embeddings and self-supervised learning (Wu et al., 2018; He et al., 2020; Chen et al., 2020; Le-Khac et al., 2020).

In summary, our contributions are

1. A new connection between the contrastive methods NCE and NEG (Sec. 4).
2. The exact relation of t-SNE and UMAP and a remedy for an instability in UMAP (Sec. 6).
3. A spectrum of 'contrastive' neighbor embeddings encompassing UMAP and t-SNE (Sec. 5).
4. A connection between neighbor embeddings and self-supervised learning (Sec. 7).
5. A unified PyTorch framework for contrastive (non-)parametric neighbor embedding methods.

2 RELATED WORK

One of the most popular methods for data visualization is t-SNE (van der Maaten & Hinton, 2008; van der Maaten, 2014). Recently developed NCVis (Artemenkov & Panov, 2020) employs noise-contrastive estimation (Gutmann & Hyvärinen, 2010; 2012) to approximate t-SNE in a sampling-based way. UMAP (McInnes et al., 2018) has matched t-SNE's popularity at least in computational biology (Becht et al., 2019), and also uses sampling-based optimization, namely negative sampling (Mikolov et al., 2013). UMAP sparked the development of further related methods, e.g., TriMAP (Amid & Warmuth, 2019) and PacMAP (Wang et al., 2021).

Given their success, t-SNE and UMAP have been scrutinized to find out which aspects are essential to their performance. Initialization was found to be strongly influencing the global structure in for both methods (Kobak & Linderman, 2021). The exact choice of the low-dimensional similarity kernel (Böhm et al., 2022) or weights of the k-nearest-neighbor graph (Damrich & Hamprecht, 2021) were shown to be largely inconsequential. Both algorithms have similar relevant hyper-parameters such as, e.g., the heavy-tailedness of the similarity kernel (Yang et al., 2009; Kobak et al., 2019).

While not obvious from the original presentations, the central difference between t-SNE and UMAP can therefore only be in their loss functions, which have been studied by Damrich & Hamprecht

(2021); Böhm et al. (2022); Wang et al. (2021), but never conceptually connected. We achieve this by deepening the link between negative sampling (NEG) and noise-contrastive estimation (NCE).

NEG was introduced as an ad hoc replacement for NCE in the context of learning word embeddings (Mikolov et al., 2013). The relationship between NEG and NCE has been discussed before (Dyer, 2014; Levy & Goldberg, 2014; Ruder, 2016; Ma & Collins, 2018; Le-Khac et al., 2020), but here we go further and provide the precise meaning of NEG: We show that, unlike NCE, NEG learns a model proportional but not equal to the true data distribution.

Both t-SNE and UMAP have parametric versions (van der Maaten, 2009; Sainburg et al., 2021) with very different logic and implementations. Here we present a unified PyTorch framework for non-parametric and parametric contrastive neighbor embeddings. As special cases, it includes UMAP and t-SNE approximations with NCE (like NCVis) and the InfoNCE loss (Jozefowicz et al., 2016; van den Oord et al., 2018), which has not yet been applied to neighbor embeddings.

Our InfoNC-t-SNE elucidates the relationship between SimCLR (Chen et al., 2020) and neighbor embeddings. The concurrent work of Hu et al. (2022) makes a qualitatively similar argument, but does not talk about negative samples. Balestriero & LeCun (2022) show how SimCLR recovers Isomap (Tenenbaum et al., 2000), while we connect SimCLR to more modern neighbor embeddings.

3 BACKGROUND

3.1 NOISE-CONTRASTIVE ESTIMATION (NCE)

The goal of parametric density estimation is to fit a parametric model q_θ to iid samples $s_1, \ldots, s_N$ from an unknown data distribution p over a space X. For maximum likelihood estimation (MLE) the parameters θ are chosen to maximize the log-likelihood of the observed samples

$$\theta^* = \arg \max_\theta \sum_{i=1}^N \log \left(q_\theta(s_i) \right). \tag{1}$$

This approach crucially requires q_θ to be a normalized model. It is otherwise trivial to increase the likelihood arbitrarily by scaling q_θ. To circumvent the expensive computation of the partition function $Z(\theta) = \sum_{x \in X} q_\theta(x)$, Gutmann & Hyvärinen (2010; 2012) introduced NCE. It turns the unsupervised problem of density estimation into a supervised problem in which the data samples need to be identified from a set containing the N data samples and m times as many noise samples $t_1, \ldots t_{mN}$ drawn from a noise distribution ξ, e.g., the uniform distribution over X. Briefly, NCE fits θ by minimizing the binary cross-entropy between the true class assignment and posterior probabilities $\mathbb{P}(\text{data} \mid x) = q_\theta(x)/\big(q_\theta(x) + m\xi(x)\big)$ and $\mathbb{P}(\text{noise} \mid x) = 1 - \mathbb{P}(\text{data} \mid x)$ (Supp. A.1):

$$\theta^* = \arg \min_\theta \left[-\sum_{i=1}^N \log \left(\frac{q_\theta(s_i)}{q_\theta(s_i) + m\xi(s_i)} \right) - \sum_{i=1}^{mN} \log \left(1 - \frac{q_\theta(t_i)}{q_\theta(t_i) + m\xi(t_i)} \right) \right]. \tag{2}$$

The key advantage of NCE is that the model does not need to be explicitly normalized by the partition function, but nevertheless learns to equal the data distribution p and hence be normalized:

Theorem 1 (Gutmann & Hyvärinen (2010; 2012)). *Suppose there exists some θ^* such that $q_{\theta^*} = p$. Then θ^* is a minimum of*

$$\mathcal{L}^{\text{NCE}}(\theta) = -\mathbb{E}_{s \sim p} \log \left(\frac{q_\theta(s)}{q_\theta(s) + m\xi(s)} \right) - m\mathbb{E}_{t \sim \xi} \log \left(1 - \frac{q_\theta(t)}{q_\theta(t) + m\xi(t)} \right) \tag{3}$$

and any other minimum $\tilde{\theta}$ also satisfies $q_{\tilde{\theta}} = p$. In addition, if $\xi(x)$ is non-zero wherever $p(x)$ is non-zero, then these are the only extrema of $\mathcal{L}^{\text{NCE}}(\theta)$.

In NCE, the model typically includes an optimizable normalization parameter Z which we emphasize by writing $q_{\theta,Z} = q_\theta/Z$. But importantly, Thm. 1 applies to any model q_θ that is able to match the data distribution p, even if it does not contain a learnable normalization parameter.

In the setting of learning language models, Jozefowicz et al. (2016) proposed a different version of NCE, called InfoNCE. Instead of classifying samples as data or noise, the aim here is to predict

the position of a data sample in an $(m + 1)$-tuple containing m noise samples and one data sample (Supp. A.2). For the uniform noise distribution ξ, this yields the expected loss function

$$\mathcal{L}^{\text{InfoNCE}}(\theta) = - \underset{\substack{x \sim p \\ x_1, \ldots, x_m \sim \xi}}{\mathbb{E}} \log \left(\frac{q_\theta(x)}{q_\theta(x) + \sum_{i=1}^m q_\theta(x_i)} \right). \tag{4}$$

Ma & Collins (2018) showed that an analogue of Thm. 1 applies to InfoNCE.

3.2 NEIGHBOR EMBEDDINGS

Neighbor embeddings (NE) (Hinton & Roweis, 2002) are a group of dimensionality reduction methods, including UMAP, NCVis, and t-SNE, that aim to find a low-dimensional embedding $e_1, \ldots, e_n \in \mathbb{R}^d$ of high-dimensional input points $x_1, \ldots, x_n \in \mathbb{R}^D$, with $D \gg d$ and usually $d = 2$ for visualization. NE methods define a notion of similarity over pairs of input points which encodes the neighborhood structure and informs the low-dimensional embedding.

The exact high-dimensional similarity distribution differs between the NE algorithms, but recent work (Böhm et al., 2022; Damrich & Hamprecht, 2021) showed that t-SNE and UMAP results stay practically the same when using the binary symmetric k-nearest-neighbor graph (skNN) instead of t-SNE's Gaussian or UMAP's Laplacian similarities. An edge ij is in skNN if x_i is among the k nearest neighbors of x_j or vice versa. The high-dimensional similarity function is then given by $p(ij) = \mathbb{1}(ij \in \text{s}k\text{NN})/|\text{s}k\text{NN}|$, where $|\text{s}k\text{NN}|$ denotes the number of edges in the skNN graph and $\mathbb{1}$ is the indicator function. NCVis uses the same similarities.

There are further differences in the choice of low-dimensional similarity between t-SNE and UMAP, but Böhm et al. (2022) showed that they are negligible. Therefore, here we use the Cauchy kernel $\phi(d_{ij}) = 1/(d_{ij}^2 + 1)$ for all NE methods to transform distances $d_{ij} = \|e_i - e_j\|$ in the embedding space into low-dimensional similarities. We abuse notation slightly by also writing $\phi(ij) = \phi(d_{ij})$.

All NE methods in this work can be cast in the framework of parametric density estimation. Here, p is the data distribution to be approximated with a model q_θ, meaning that the space X on which both p and q_θ live is the set of all pairs ij with $1 \leq i < j \leq n$. The embedding positions $e_1, \ldots, e_n$ become the learnable parameters θ of the model q_θ. For t-SNE, NCVis, and UMAP, q_θ is proportional to $\phi(\|e_i - e_j\|)$, but the proportionality and the loss functions are different.

t-SNE uses MLE and therefore requires a normalized model $q_\theta(ij) = \phi(ij)/Z(\theta)$, where $Z(\theta) = \sum_{k \neq l} \phi(kl)$ is the partition function. The loss function

$$\mathcal{L}^{t\text{-SNE}}(\theta) = -\mathbb{E}_{ij \sim p} \log \left(q_\theta(ij) \right) = -\sum_{i \neq j} \left(p(ij) \log \left(\phi(ij) \right) \right) + \log \left(\sum_{k \neq l} \phi(kl) \right) \tag{5}$$

is the expected negative log-likelihood of the embedding positions θ, making t-SNE an instance of MLE. Usually t-SNE's loss function is introduced as the Kullback-Leibler divergence between p and q_θ, which is equivalent as the entropy of p does not depend on θ.

NCVis uses NCE and optimizes the expected loss function

$$\mathcal{L}^{\text{NCVis}}(\theta, Z) = -\mathbb{E}_{ij \sim p} \log \left(\frac{q_{\theta, Z}(ij)}{q_{\theta, Z}(ij) + m\xi(ij)} \right) - m\mathbb{E}_{ij \sim \xi} \log \left(1 - \frac{q_{\theta, Z}(ij)}{q_{\theta, Z}(ij) + m\xi(ij)} \right), \tag{6}$$

where $q_{\theta, Z}(ij) = \phi(ij)/Z$ with learnable Z and ξ is approximately uniform (see Supp. D).

According to Thm. 1, NCVis has the same optimum as t-SNE and can hence be seen as a sampling-based approximation of t-SNE. Indeed, we found that Z in NCVis and the partition function $Z(\theta)$ in t-SNE converge approximately to the same value (Fig. S6).

UMAP's expected loss function is derived in (Damrich & Hamprecht, 2021):

$$\mathcal{L}^{\text{UMAP}}(\theta) = -\mathbb{E}_{ij \sim p} \log \left(q_\theta(ij) \right) - m\mathbb{E}_{ij \sim \xi} \log \left(1 - q_\theta(ij) \right), \tag{7}$$

with $q_\theta(ij) = \phi(ij)$ and ξ is approximately uniform, see Supp. D. This is the effective loss function actually implemented in the UMAP algorithm, but note that it has only about m/n of the repulsion compared to the loss stated in the original UMAP paper (McInnes et al., 2018), as shown in (Böhm et al., 2022; Damrich & Hamprecht, 2021) (Supp. C).

In practice, the expectations in UMAP's and NCVis' loss functions are evaluated via sampling, like in Eq. (2). This leads to a fast, $\mathcal{O}(n)$, stochastic gradient descent optimization scheme. Both loss functions are composed of an attractive term pulling similar data points (edges of the $skNN$ graph) closer together, and a repulsive term pushing random pairs of points further apart. Similarly, t-SNE's loss yields attraction along the graph edges while repulsion arises through the normalization term.

4 FROM NOISE-CONTRASTIVE ESTIMATION TO NEGATIVE SAMPLING

In this section we work out the precise relationship between NCE and NEG, going beyond prior work (Dyer, 2014; Goldberg & Levy, 2014; Levy & Goldberg, 2014; Ruder, 2016). NEG differs from NCE by its loss function and by the lack of the learnable normalization parameter Z. In our setting, NEG's loss function amounts to[1]

$$\mathcal{L}^{\mathrm{NEG}}(\theta) = -\mathbb{E}_{x \sim p} \log \left(\frac{q_\theta(x)}{q_\theta(x) + 1} \right) - m \mathbb{E}_{x \sim \xi} \log \left(1 - \frac{q_\theta(x)}{q_\theta(x) + 1} \right). \tag{8}$$

In order to relate it to NCE's loss function, we first generalize the latter by allowing to learn a model that is not equal but proportional to the true data distribution.

Corollary 2. *Let $\bar{Z}, m \in \mathbb{R}_+$. Assume that $\xi(x)$ is non-zero wherever $p(x)$ is non-zero and that there exist θ^* such that $q_{\theta^*} = \bar{Z}p$. Then the generalized NCE loss function*

$$\mathcal{L}_{\bar{Z}}^{\mathrm{NCE}}(\theta) = -\mathbb{E}_{x \sim p} \log \left(\frac{q_\theta(x)}{q_\theta(x) + \bar{Z}m\xi(x)} \right) - m \mathbb{E}_{x \sim \xi} \log \left(1 - \frac{q_\theta(x)}{q_\theta(x) + \bar{Z}m\xi(x)} \right) \tag{9}$$

has its only extrema where $q_\theta = \bar{Z}p$.

Proof. The result follows from Thm. 1 applied to the model distribution $\tilde{q}_\theta \coloneqq q_\theta/\bar{Z}$. $\qquad \square$

Dyer (2014) and Ruder (2016) pointed out that for a uniform noise distribution $\xi(x) = 1/|X|$ and as many noise samples as the size of X ($m = |X|$), the loss functions of NCE and NEG coincide, since $m\xi(x) = 1$. However, the main point of NCE and NEG is to use far fewer noise samples in order to attain a speed-up over MLE. Our Cor. 2 for the first time explains NEG's behavior in this more realistic setting ($m \ll |X|$). If the noise distribution is uniform, the generalized NCE loss function with $\bar{Z} = |X|/m$ equals the NEG loss function since $(|X|/m)m\xi(x) = 1$. By Cor. 2, any minimum θ^* of the NEG loss function yields $q_{\theta^*} = (|X|/m)p$, assuming that there are parameters that make this equation hold. In other words, NEG aims to find a model q_θ that is proportional to the data distribution with the proportionality factor $|X|/m$ which is typically huge. This is different from NCE, which aims to learn a model equal to the data distribution.

Choosing $m \ll |X|$ does not only offer a computational speed-up but is necessary when optimizing NEG for a neural network with SGD, like we do in Sec.7. Only one single mini-batch is passed through the neural network during each iteration and is thus available for computing the loss. Hence, all noise samples must come from the current mini-batch and their number m is upper-bounded by the mini-batch size b. Mini-batches are typically much smaller than $|X|$. Thus, this common training procedure necessitates $m \ll |X|$ highlighting the relevance of Cor. 2.

While NCE uses a model q_θ/Z with learnable Z, we can interpret NEG as using a model $q_\theta/\bar{Z}$ with fixed and very large normalization constant $\bar{Z} = |X|/m$. As a result, q_θ in NEG needs to attain much larger values to match the large $\bar{Z}$. This can be illustrated in the setting of neighbor embeddings. Applying NEG to the neighbor embedding framework yields an algorithm that we call 'Neg-t-SNE'. Recall that in this setting, $|X| = \binom{n}{2}$ is the number of pairs of points. Böhm et al. (2022) found empirically that t-SNE's partition function $Z(\theta)$ is typically between $50n$ and $100n$, while in Neg-t-SNE, $\bar{Z} = \mathcal{O}(n^2)$ is much larger for modern big datasets. To attain the larger values of $\phi(ij)$ required by NEG, points that are connected in the $skNN$ graph have to move much closer together in the embedding than in t-SNE. Indeed, using our PyTorch implementation of Neg-t-SNE on the MNIST dataset, we confirmed that Neg-t-SNE (Fig. 1d) produced more compact clusters than t-SNE (Fig. 1f). See Supp. G and Alg. S1 for implementation details.

We emphasize that the conclusions of this section only hold because NEG does not contain a learnable normalization parameter Z. If it did, then such a learnable Z would be able to absorb the term $\bar{Z}$ in Eq. (9) while leaving the parameters θ unchanged.

---

[1]We focus on the loss function, ignoring Mikolov et al. (2013)'s choices specific to word embeddings.

(a) UMAP, no annealing   (b) UMAP with annealing   (c) Neg-t-SNE, no ann.   (d) Neg-t-SNE with ann.

Figure 2: Embeddings of the MNIST dataset with UMAP and Neg-t-SNE with and without learning rate annealing. UMAP does not work well without annealing because it implicitly uses the diverging $1/d_{ij}^2$ kernel in NEG, while Neg-t-SNE uses the more numerically stable Cauchy kernel (Sec. 6).

5   NEGATIVE SAMPLING SPECTRUM

Varying the fixed normalization constant $\bar{Z}$ in Eq. (9) has important practical effects that lead to a whole spectrum of embeddings in the NE setting. The original NEG loss function Eq. (8) corresponds to Eq. (9) with $\bar{Z} = |X|/m$. We still refer to the more general case of using an arbitrary $\bar{Z}$ in Eq. (9) as 'negative sampling', and 'Neg-t-SNE' in the context of neighbor embeddings.

Figs. 1a–e show a spectrum of Neg-t-SNE visualizations of the MNIST dataset for varying $\bar{Z}$. Per Cor. 2, higher values of $\bar{Z}$ induce higher values for q_θ, meaning that points move closer together. Indeed, the scale of the embedding decreases for higher $\bar{Z}$ as evident from the scale bars in the bottom-right corner of each plot. Moreover, clusters become increasingly compact and then even start to merge. For lower values of $\bar{Z}$ the embedding scale is larger, clusters are more spread out, and eventually lose almost any separation and start to overlap for very small $\bar{Z}$.

Cor. 2 implies that the partition function $\sum_x q_\theta(x)$ should grow with $\bar{Z}$, and indeed this is what we observed (Fig. 1i). The match between between the sum of Cauchy kernels $\sum_{ij} \phi(ij)$ and $\bar{Z}$ was not perfect, but that was expected: The Cauchy kernel is bounded by 1 from above, so values $\bar{Z} > \binom{n}{2}$ are not matchable. Similarly, very small values of $\bar{Z}$ are difficult to match because of the heavy tail of the Cauchy kernel.

By adjusting the $\bar{Z}$ value, one can obtain Neg-t-SNE embeddings very similar to NCVis and t-SNE. If the NCVis loss function Eq. (6) has its minimum at some θ^* and Z^{NCVis}, then the Neg-t-SNE loss function Eq. (9) with $\bar{Z} = Z^{\text{NCVis}}$ is minimal at the same θ^*. We confirmed this experimentally: Setting $\bar{Z} = Z^{\text{NCVis}}$, yields a Neg-$t$-SNE embedding (Fig. 1c) closely resembling that of NCVis (Fig. 1g). Similarly, setting $\bar{Z}$ to the partition function $Z(\theta^{t\text{-SNE}})$, obtained by running t-SNE, yields a Neg-t-SNE embedding closely resembling that of t-SNE (compare Figs. 1b and 1f).

The Neg-t-SNE spectrum is strongly related to the attraction-repulsion spectrum from Böhm et al. (2022). They introduced a prefactor ('exaggeration') to the repulsive term in the t-SNE's loss, which exaggerates the attraction over the repulsion, and obtained embeddings similar to our spectrum when varying this parameter. We can explain this as follows. The repulsive term in the NCE loss Eq. (3) has a prefactor m and our spectrum arises from the loss Eq. (9) by varying $\bar{Z}$ in the term $\bar{Z}m$. Equivalently, our spectrum can be obtained by varying the m value (number of noise samples per one skNN edge) while holding $\bar{Z}$ fixed (Fig. S4). In other words, our spectrum arises from varying the repulsion strength in the contrastive loss setting, while Böhm et al. (2022) obtained the analogous spectrum by varying the repulsion strength in the t-SNE setting.

6   UMAP'S CONCEPTUAL RELATION TO t-SNE

Our comparison of NEG and NCE in Sec. 4 allows us for the first time to conceptually relate UMAP and t-SNE. Originally McInnes et al. (2018) motivated the UMAP algorithm by a specific choice of weights on the skNN graph and the binary cross-entropy loss. Following LargeVis (Tang et al., 2016), they implemented a sampling-based scheme to overcome the quadratic complexity of all repulsive forces in the purported binary cross-entropy loss.

Recent work (Böhm et al., 2022; Damrich & Hamprecht, 2021) pointed to the drastic effect of this optimization scheme and argued that it alters the effective loss. McInnes et al. (2018) referred to

their optimization as 'negative sampling', although UMAP's loss function Eq. (7) does not look like the NEG loss Eq. (8). Thus, it has been unclear if UMAP actually uses Mikolov et al. (2013)'s NEG.

Where NEG's loss Eq. (8) has fractions $q_\theta(ij)/(q_\theta(ij) + 1)$, UMAP's loss Eq. (7) only has $q_\theta(ij)$. Nevertheless, we can rearrange the terms to make UMAP appear as a proper instance of NEG:

$$q_\theta(ij) = \phi(ij) = 1/(1 + d_{ij}^2) = (1/d_{ij}^2)/(1/d_{ij}^2 + 1) = \tilde{q}_\theta(ij)/(\tilde{q}_\theta(ij) + 1), \qquad (10)$$

where we set $\tilde{q}_\theta(ij) \coloneqq 1/d_{ij}^2$. Put differently, UMAP does use NEG, yet not with the Cauchy kernel as parametric model, but instead with the squared inverse distance between embedding points.

For large embedding distances d_{ij} both models behave alike, but for nearby points they strongly differ: The inverse-square kernel $1/d_{ij}^2$ diverges when $d_{ij} \to 0$, unlike the Cauchy kernel $1/(1+d_{ij}^2)$. Despite this qualitative difference, we found empirically that UMAP embeddings look very similar to Neg-t-SNE embeddings at $\bar{Z} = |X|/m$, see Figs. 1d and 1h for the MNIST example.

To explain this observation, it is instructive to compare the loss terms between Neg-t-SNE and UMAP: The attractive term amounts to $-\log(1/(d_{ij}^2 + 1)) = \log(1 + d_{ij}^2)$ for UMAP and $-\log[1/(d_{ij}^2 + 1)/(1/(d_{ij}^2 + 1) + 1)] = \log(2 + d_{ij}^2)$ for Neg-t-SNE, while the repulsive term equals $\log((1 + d_{ij}^2)/d_{ij}^2)$ and $\log((2 + d_{ij}^2)/(1 + d_{ij}^2))$, respectively. While the attractive terms are very similar, the repulsive term for UMAP diverges at zero but that of Neg-t-SNE does not (Fig. S3). This divergence introduces numerical instability into the optimization process of UMAP.

We found that UMAP strongly depends on annealing its learning rate down to zero (Figs. 2a, b). Without it, clusters appear fuzzy as noise pairs can experience very strong repulsion and get catapulted out of their cluster (Fig. 2a). While Neg-t-SNE also benefits from this annealing scheme (Fig. 2d), it produces a very similar embedding even without any annealing (Fig. 2c). Thus, UMAP's effective choice of the $1/d_{ij}^2$ kernel makes it less numerically stable and more dependent on optimization tricks, compared to Neg-t-SNE.[2] See Supp. E for more details.

Our conclusion is that at its heart, UMAP is NEG applied to the t-SNE framework. UMAP's sampling-based optimization is much more than a mere optimization trick; it enables us to connect it theoretically to t-SNE. When UMAP's loss function is seen as an instance of NEG, UMAP does not use the Cauchy kernel but rather the inverse-square kernel. However, this does not make a strong difference due to the learning rate decay. As discussed in Sec. 4, the fixed normalization constant $\bar{Z}$ in Neg-t-SNE/UMAP is much larger than the learnt Z in NCVis or the partition function in t-SNE. This explains why UMAP pulls embedding points closer together than both NCVis and t-SNE and is the reason for the typically more compact clusters in UMAP plots (Böhm et al., 2022).

7 CONTRASTIVE NE AND CONTRASTIVE SELF-SUPERVISED LEARNING

Contrastive self-supervised representation learning (van den Oord et al., 2018; Tian et al., 2020; He et al., 2020; Chen et al., 2020; Caron et al., 2020) and 'contrastive neighbor embeddings' (a term we suggest for NCVis, Neg-t-SNE, UMAP, etc.) are conceptually very similar. The key difference is that the latter use a fixed kNN graph to find pairs of similar objects, while the former rely on data augmentations or context to generate pairs of similar objects on the fly. Other differences include the representation dimension (~ 128 vs. 2), the use of a neural network for parametric mapping, the flavor of contrastive loss (InfoNCE vs. NCE / NEG) or the number of noise samples m. However, these other differences are not crucial, as we establish here with our unified PyTorch framework.

As an example, we demonstrate that t-SNE can also be optimized using the InfoNCE loss, resulting in 'InfoNC-t-SNE' (Supp. G and Alg. S1). The result of InfoNC-t-SNE on MNIST (Fig. 3c) was similar to the result of NCVis (Fig. 3b). For the default number of noise samples, $m = 5$, both algorithms produced embeddings that were visibly different from t-SNE proper (Fig. 1f). Recent work in self-supervised learning (Chen et al., 2020) reports improved performance for more noise samples, in agreement with the theory of Gutmann & Hyvärinen (2010; 2012); Ma & Collins (2018). We observed that both NCVis and InfoNC-t-SNE visualizations using $m = 500$ approximated t-SNE much better (Figs. S14k and S15k). Like t-SNE, but unlike the $m = 5$ setting, $m = 500$ required early exaggeration to prevent cluster fragmentation, see Figs. S14 and S15.

---

[2]Recently, a pull request to UMAP's GitHub repository effectively changed the kernel of parametric UMAP to the Cauchy kernel, in order to overcome numerical instabilities via an ad hoc fix, see Supp. E.

(a) Neg-t-SNE   (b) NCVis   (c) InfoNC-t-SNE

(d) Param. Neg-t-SNE   (e) Param. NCVis   (f) Param. InfoNC-t-SNE

Figure 3: NE embeddings of MNIST are qualitatively similar in the non-parametric (top) and parametric settings (bottom). We used our PyTorch framework with $m = 5$ and batch size $b = 1024$.

Next, we used our PyTorch framework to obtain parametric versions of all contrastive NE algorithms discussed here (NCVis, InfoNC-t-SNE, Neg-t-SNE, UMAP). We used a fully connected neural network with three hidden layers as a parametric $\mathbb{R}^D \to \mathbb{R}^d$ mapping and optimized its parameters using Adam (Kingma & Ba, 2015) (Supp. G). We used batch size $b = 1024$ and sampled all m negative samples from within the batch; the data set was shuffled each epoch before batching. Using all four loss functions, we were able to get parametric embeddings of MNIST that were qualitatively similar to their non-parametric versions (Fig. 3). The parametric versions of NCE and InfoNCE produced much larger embeddings than their non-parametric counterparts, however the final loss values were very similar (Figs. S5a, b). For NCE, the larger scale of the parametric embedding was compensated by a smaller learned normalization parameter Z, so that both parametric and non-parametric versions were approximately normalized (Fig. S5c). Our parametric UMAP implementation is very similar to that of Sainburg et al. (2021). But our parametric, approximate t-SNE implementations strongly differ from the parametric t-SNE of van der Maaten (2009), which constructed separate kNN graphs within each batch and optimized the vanilla t-SNE loss function.

Neighbor embeddings methods achieve impressive results with only few noise samples, while existent common practice in the self-supervised learning literature (Bachman et al., 2019; Chen et al., 2020; He et al., 2020) recommends very large m. As a proof-of-concept, we demonstrate that using only $m = 16$ non-curated (Wu et al., 2017; Roth et al., 2020) noise samples can suffice for image-based self-supervised learning. We used a SimCLR setup (Chen et al., 2020) to train representations of the CIFAR-10 dataset (Krizhevsky, 2009) using a ResNet18 (He et al., 2016) backbone, a fixed batch size of $b = 1024$ and varying number of noise samples m. Other implementation details follow Chen et al. (2020)'s CIFAR-10 setup (Supp. G). The classification accuracy, measured on the ResNet output, saturates already at $m = 16$ noise samples (Tab. 1). Note that, different from the original SimCLR setup, we decoupled the batch size from the number of noise samples. Recent work found conflicting evidence when varying m for a fixed batch size (Mitrovic et al., 2020; Nozawa & Sato, 2021; Ash et al., 2022). Future research is needed to perform more systematic benchmarks into the importance of m. Here, we present these results only as a proof-of-principle that a similarly low m as in neighbor embeddings (default $m = 5$) can work in a SimCLR setting.

8 DISCUSSION AND CONCLUSION

In this work, we studied the relationship between two popular unsupervised learning methods, noise-contrastive estimation (NCE) and negative sampling (NEG). We focused on their application to neighbor embeddings (NE) because this is an active and important application area, but also because NEs allow to directly visualize the NCE/NEG outcome and to form intuitive understanding of how different algorithm choices affect the result. Our study makes three conceptual advances.

Table 1: Classification accuracies on CIFAR-10 representations obtained with InfoNCE loss and batch size $b = 1024$ saturate already at a low number of noise samples m, common for neighbor embeddings. Accuracy was computed on a test set, using the ResNet18 output $H \in \mathbb{R}^{512}$. We report mean $\pm$ std across three seeds.

	$m = 2$	$m = 16$	$m = 128$	$m = 512$	$m = 2b - 2$
kNN classifier	88.3 ± 0.4	91.8 ± 0.0	92.0 ± 0.1	92.0 ± 0.2	92.0 ± 0.0
Linear classifier	86.3 ± 0.3	91.4 ± 0.1	91.9 ± 0.1	91.9 ± 0.0	91.9 ± 0.1

First, we showed that NEG replaces NCE's learnable normalization parameter Z by a large constant $\bar{Z}$, forcing NEG to learn a scaled data distribution. While not explored here, this implies that NEG can be used to learn probabilistic models and is not only applicable for embedding learning as previously believed (Dyer, 2014; Ruder, 2016; Le-Khac et al., 2020). In the NE setting, NEG led to the method Neg-t-SNE, that differs from NCVis (Artemenkov & Panov, 2020) (which could be nicknamed 'NC-t-SNE') by a simple switch from the learnable to a fixed normalization constant. We argued that this can be a useful hyperparameter because it moves the embedding along the attraction-repulsion spectrum similar to (Böhm et al., 2022), and hence can either emphasize more discrete (Fig. S12) or more continuous data patterns (see Figs. S9 – S11 for single cell datasets). In addition, when $\bar{Z}$ equals the partition function of a t-SNE embedding, the resulting Neg-t-SNE embedding resembles that of t-SNE. Exploration of the spectrum does not require specialized knowledge. For UMAP, $\bar{Z}^{\text{UMAP}} = \binom{n}{2}/m$; for t-SNE, Böhm et al. (2022) found that the partition function $Z^{t\text{-SNE}}$ typically lies in $[50n, 100n]$. Both quantities can be computed a priori. We envisage an API that allows the user to move along the spectrum with a slider parameter s such that $s = 0, 1$ corresponds to $\bar{Z} = Z^{t\text{-SNE}}, \bar{Z}^{\text{UMAP}}$, respectively, without any need for specifying $\bar{Z}$ directly.

A caveat is that Thm. 1 and Cor. 2 both assume that the model is rich enough to perfectly fit the data distribution. This is a strong and unrealistic assumption. In the context of NEs, the data distribution is zero for most pairs of points, which is impossible to match using the Cauchy kernel. Nevertheless, the consistency of MLE and thus t-SNE also depends on this assumption. Even without it, the gradients of MLE, NCE, and NEG are similar (Supp. B). Finally, our theoretical analysis was confirmed experimentally, so that the assumption is not problematic in practice.

Second, we demonstrated that UMAP, which uses NEG, differs from Neg-t-SNE only in UMAP's implicit use of a less numerically stable similarity function. This isolates the key aspect of UMAP's success: Instead of UMAP's appraised (Oskolkov, 2022; Coenen & Pearce, 2022) high-dimensional similarities, the refined Cauchy kernel, or its stated cross-entropy loss function, it is the application of NEG that lets UMAP perform well and makes clusters in UMAP plots more compact and connections between them more continuous than in t-SNE, in agreement with Böhm et al. (2022). To the best of our knowledge, this is the first time UMAP's and t-SNE's loss functions, motivated very differently, have been conceptually connected. Our use of the standard Cauchy kernel and the binary skNN graph are only a mild limitations (Böhm et al., 2022; Damrich & Hamprecht, 2021).

Third, we argued that contrastive NEs are closely related to contrastive self-supervised learning (SSL) methods such as SimCLR (Chen et al., 2020) which can be seen as parametric InfoNC-t-SNE for learning representations in S^{128} based on the unobservable similarity graph implicitly constructed via data augmentations. We feel that this connection has been underappreciated, with the literature on NEs and on self-supervised contrastive learning staying mostly disconnected. An exception is the concurrent work of Hu et al. (2022). They propose to use t-SNE's Cauchy kernel for SSL. Instead, we bridge the gap between NE and SSL, with our InfoNC-t-SNE, as well as with parametric versions of all considered NE methods, useful for adding out-of-sample data to an existing visualization. Moreover, we demonstrated that the feasibility of few noise samples in NE translates to the SimCLR setup. We developed a concise PyTorch framework optimizing *all* of the above, which we hope will facilitate future dialogue between the two research communities.

Overall, our insights into NEs should enable practitioners to explore their datasets more reliably. Our conceptual relation between UMAP and t-SNE is therefore of practical impact – as is the fact that both are just instances on a spectrum highlighting more continuous or more discrete structures.

ETHICS STATEMENT

Our work analyses connections between popular contrastive learning methods and in particular visualization methods. Visualization methods are fundamental in exploratory data analysis, e.g., in computational biology. Given the basic nature of visualization it can of course potentially be used for malicious goals, but we expect mostly positive societal effects such as more reliable exploration of biological data.

Similarly, contrastive self-supervised learning has the potential to overcome the annotation bottleneck that machine learning faces. This might free countless hours of labelling for more productive use but could also enable institutions with sufficient resources to learn from larger and larger datasets, potentially concentrating power.

Our PyTorch implementation of contrastive neighbor embeddings is slower than existing UMAP and NCVis implementations and hence more resource intensive. We therefore recommend it primarily as a research tool into contrastive learning and contrastive neighbor embeddings, and suggest more efficient implementations for large scale applications.

REPRODUCIBILITY

All of our results are reproducible. We included proofs for the theoretical statement Cor. 2 and those in Supp. D. The datasets used in the experiments including preprocessing steps are described in Supp. F. We discuss the most important implementation details in the main text, e.g., in Sec. 7. An extensive discussion of our implementation is included in Supp. G and in Alg. S1. The code and instructions for how to reproduce the experiments are submitted as supplementary material.

REFERENCES

Ehsan Amid and Manfred K Warmuth. TriMap: Large-scale Dimensionality Reduction Using Triplets. *arXiv preprint arxiv: 1910.00204*, 2019.

Aleksandr Artemenkov and Maxim Panov. NCVis: Noise Contrastive Approach for Scalable Visualization. In *Proceedings of The Web Conference 2020*, pp. 2941–2947, 2020.

Jordan Ash, Surbhi Goel, Akshay Krishnamurthy, and Dipendra Misra. Investigating the Role of Negatives in Contrastive Representation Learning. In *Proceedings of The 25th International Conference on Artificial Intelligence and Statistics*, Proceedings of Machine Learning Research, pp. 7187–7209, 2022.

Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning Representations by Maximizing Mutual Information across Views. In *Advances in Neural Information Processing Systems*, volume 32, pp. 15535–15545, 2019.

Randall Balestriero and Yann LeCun. Contrastive and non-contrastive self-supervised learning recover global and local spectral embedding methods. *arXiv preprint arXiv:2205.11508*, 2022.

Etienne Becht, Leland McInnes, John Healy, Charles-Antoine Dutertre, Immanuel WH Kwok, Lai Guan Ng, Florent Ginhoux, and Evan W Newell. Dimensionality reduction for visualizing single-cell data using UMAP. *Nature Biotechnology*, 37(1):38–44, 2019.

Jan Niklas Böhm, Philipp Berens, and Dmitry Kobak. Attraction-Repulsion Spectrum in Neighbor Embeddings. *Journal of Machine Learning Research*, 23(95):1–32, 2022.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised Learning of Visual Features by Contrasting Cluster Assignments. In *Advances in Neural Information Processing Systems*, volume 33, pp. 9912–9924, 2020.

Tara Chari, Joeyta Banerjee, and Lior Pachter. The Specious Art of Single-Cell Genomics. *bioRxiv*, 2021.

Benjamin Charlier, Jean Feydy, Joan Alexis Glaunès, François-David Collin, and Ghislain Durif. Kernel Operations on the GPU, with Autodiff, without Memory Overflows. *Journal of Machine Learning Research*, 22(74):1–6, 2021.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A Simple Framework for Contrastive Learning of Visual Representations. In *Proceedings of the International Conference on Machine Learning*, Proceedings of Machine Learning Research, pp. 1597–1607, 2020.

Andy Coenen and Adam Pearce. A deeper dive into UMAP theory. `https://pair-code.github.io/understanding-umap/supplement.html`, 2022. Accessed: 2022-05-11.

Sebastian Damrich and Fred A Hamprecht. On UMAP's True Loss Function. In *Advances in Neural Information Processing Systems*, volume 34, pp. 5798–5809, 2021.

Chris Dyer. Notes on Noise Contrastive Estimation and Negative Sampling. *arXiv preprint arxiv: 1410.8251*, 2014.

Yoav Goldberg and Omer Levy. word2vec Explained: Deriving Mikolov et al.'s Negative-Sampling Word-Embedding Method. *arXiv preprint arxiv: 1402.3722*, 2014.

Michael U Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304, 2010.

Michael U Gutmann and Aapo Hyvärinen. Noise-Contrastive Estimation of Unnormalized Statistical Models, with Applications to Natural Image Statistics. *Journal of Machine Learning Research*, 13(2), 2012.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum Contrast for Unsupervised Visual Representation Learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Geoffrey E Hinton and Sam Roweis. Stochastic Neighbor Embedding. In *Advances in Neural Information Processing Systems*, volume 15, pp. 857–864, 2002.

Tianyang Hu, Zhili Liu, Fengwei Zhou, Wenjia Wang, and Weiran Huang. Your contrastive learning is secretly doing stochastic neighbor embedding. *arXiv preprint arXiv:2205.14814*, 2022.

Rafal Jozefowicz, Oriol Vinyals, Mike Schuster, Noam Shazeer, and Yonghui Wu. Exploring the Limits of Language Modeling. *arXiv preprint arxiv: 1602.02410*, 2016.

Sabina Kanton, Michael James Boyle, Zhisong He, Malgorzata Santel, Anne Weigert, Fátima Sanchís-Calleja, Patricia Guijarro, Leila Sidow, Jonas Simon Fleck, Dingding Han, et al. Organoid single-cell genomic atlas uncovers human-specific features of brain development. *Nature*, 574(7778):418–422, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. In *Proceedings of the International Conference on Learning Representations*, pp. 1–15, 2015.

Dmitry Kobak and Philipp Berens. The art of using t-SNE for single-cell transcriptomics. *Nature Communications*, 10(1):1–14, 2019.

Dmitry Kobak and George C Linderman. Initialization is critical for preserving global data structure in both t-SNE and UMAP. *Nature Biotechnology*, pp. 1–2, 2021.

Dmitry Kobak, George Linderman, Stefan Steinerberger, Yuval Kluger, and Philipp Berens. Heavy-Tailed Kernels Reveal a Finer Cluster Structure in t-SNE Visualisations. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 124–139. Springer, 2019.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Master's thesis, University of Toronto, 2009.

Phuc H Le-Khac, Graham Healy, and Alan F Smeaton. Contrastive Representation Learning: A Framework and Review. *IEEE Access*, 8:193907–193934, 2020.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Omer Levy and Yoav Goldberg. Neural Word Embedding as Implicit Matrix Factorization. In *Advances in Neural Information Processing Systems*, volume 27, pp. 2177–2185, 2014.

Ilya Loshchilov and Frank Hutter. SGDR: Stochastic Gradient Descent with Warm Restarts. *Proceedings of the International Conference on Learning Representations*, pp. 1–16, 2017.

Zhuang Ma and Michael Collins. Noise Contrastive Estimation and Negative Sampling for Conditional Models: Consistency and Statistical Efficiency. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3698–3707, 2018.

Leland McInnes, John Healy, and James Melville. UMAP: Uniform Manifold Approximation and Projection for Dimension Reduction. *arXiv preprint arXiv:1802.03426*, 2018.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed Representations of Words and Phrases and their Compositionality. In *Advances in Neural Information Processing Systems*, volume 26, pp. 3111–3119, 2013.

Jovana Mitrovic, Brian McWilliams, and Melanie Rey. Less can be more in contrastive learning. In *Proceedings on "I Can't Believe It's Not Better!" at NeurIPS Workshops*, pp. 70–75, 2020.

Ashwin Narayan, Bonnie Berger, and Hyunghoon Cho. Assessing single-cell transcriptomic variability through density-preserving data visualization. *Nature Biotechnology*, pp. 1–10, 2021.

Kento Nozawa and Issei Sato. Understanding Negative Samples in Instance Discriminative Self-supervised Representation Learning. In *Advances in Neural Information Processing Systems*, volume 34, pp. 5784–5797, 2021.

Nikolay Oskolkov. How Exactly UMAP Works. `https://towardsdatascience.com/how-exactly-umap-works-13e3040e1668`, 2022. Accessed: 2022-05-11.

Jonathan S Packer, Qin Zhu, Chau Huynh, Priya Sivaramakrishnan, Elicia Preston, Hannah Dueck, Derek Stefanik, Kai Tan, Cole Trapnell, Junhyong Kim, Robert H. Waterston, and John I. Murray. A lineage-resolved molecular atlas of C. elegans embryogenesis at single-cell resolution. *Science*, 365(6459):1265–1274, 2019.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *Advances in Neural Information Processing Systems 32*, pp. 8024–8035, 2019.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Pavlin G. Poličar, Martin Stražar, and Blaž Zupan. openTSNE: a modular Python library for t-SNE dimensionality reduction and embedding. *bioRxiv*, 2019.

Karsten Roth, Timo Milbich, and Bjorn Ommer. PADS: Policy-Adapted Sampling for Visual Similarity Learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6568–6577, 2020.

Sebastian Ruder. On word embeddings - Part 2: Approximating the Softmax. `http://ruder.io/word-embeddings-softmax`, 2016. Accessed: 2022-05-17.

Tim Sainburg, Leland McInnes, and Timothy Q Gentner. Parametric UMAP Embeddings for Representation and Semisupervised Learning. *Neural Computation*, 33(11):2881–2907, 2021.

Benjamin Szubert, Jennifer E Cole, Claudia Monaco, and Ignat Drozdov. Structure-preserving visualisation of high dimensional single-cell datasets. *Scientific reports*, 9(1):1–10, 2019.

Jian Tang, Jingzhou Liu, Ming Zhang, and Qiaozhu Mei. Visualizing large-scale and high-dimensional data. In *Proceedings of the 25th International Conference on World Wide Web*, pp. 287–297, 2016.

Clanuwat Tarin, B Mikel, K Asanobu, L Alex, Y Kazuaki, and H David. Deep Learning for Classical Japanese Literature. In *Proceedings of 2018 Workshop on Machine Learning for Creativity and Design (Thirty-second Conference on Neural Information Processing Systems)*, volume 3, 2018.

Joshua B Tenenbaum, Vin De Silva, and John C Langford. A Global Geometric Framework for Nonlinear Dimensionality Reduction. *Science*, 290(5500):2319–2323, 2000.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive Multiview Coding. In *Proceedings of the European Conference on Computer Vision*, pp. 776–794. Springer, 2020.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation Learning with Contrastive Predictive Coding. *arXiv e-prints*, pp. arXiv–1807, 2018.

Laurens van der Maaten. Learning a Parametric Embedding by Preserving Local Structure. In *Artificial Intelligence and Statistics*, Proceedings of Machine Learning Research, pp. 384–391, 2009.

Laurens van der Maaten. Accelerating t-SNE using Tree-Based Algorithms. *Journal of Machine Learning Research*, 15(1):3221–3245, 2014.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-SNE. *Journal of Machine Learning Research*, 9(11):2579–2605, 2008.

Daniel E. Wagner, Caleb Weinreb, Zach M. Collins, James A. Briggs, Sean G. Megason, and Allon M. Klein. Single-cell mapping of gene expression landscapes and lineage in the zebrafish embryo. *Science*, 360(6392):981–987, 2018.

Yingfan Wang, Haiyang Huang, Cynthia Rudin, and Yaron Shaposhnik. Understanding How Dimension Reduction Tools Work: An Empirical Approach to Deciphering t-SNE, UMAP, TriMAP, and PaCMAP for Data Visualization. *Journal of Machine Learning Research*, 22:1–73, 2021.

Chao-Yuan Wu, R Manmatha, Alexander J Smola, and Philipp Krahenbuhl. Sampling Matters in Deep Embedding Learning. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2840–2848, 2017.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised Feature Learning via Non-Parametric Instance Discrimination. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3733–3742, 2018.

Zhirong Yang, Irwin King, Zenglin Xu, and Erkki Oja. Heavy-Tailed Symmetric Stochastic Neighbor Embedding. In *Advances in Neural Information Processing Systems*, pp. 2169–2177, 2009.

SUPPLEMENTARY TEXT

A PROBABILISTIC FRAMEWORKS OF NCE AND INFONCE

In this section we recap the probabilistic frameworks of NCE (Gutmann & Hyvärinen, 2010; 2012) and InfoNCE (Jozefowicz et al., 2016; van den Oord et al., 2018).

A.1 NCE

In NCE the unsupervised problem of parametric density estimation is turned into a supervised problem in which the data samples need to be identified in a set S containing N data samples $s_1, \ldots, s_N$ and m times as many noise samples $t_1, \ldots, t_{mN}$ drawn from a noise distribution ξ, which can be (but does not have to be) the uniform distribution. In other words, we are interested in the posterior probability $\mathbb{P}(y|x)$ of element $x \in S$ coming from the data ($y = $ data) rather than from the noise distribution ($y = $ noise).

The probability of sampling x from noise, $\mathbb{P}(x|\text{noise})$, is just the noise distribution ξ, and similarly $\mathbb{P}(x|\text{data})$ is the data distribution p. Since the latter is unknown, it is replaced by the model q_θ. Since S contains m times as many noise samples as data samples, the prior class probabilities are $\mathbb{P}(\text{data}) = 1/(m+1)$ and $\mathbb{P}(\text{noise}) = m/(m+1)$. Thus, the unconditional probability of an element of S is $\mathbb{P}(x) = (q_\theta(x) + m\xi(x))/(m+1)$. The posterior probability for classifying some given element x of S as data rather than noise is thus

$$\mathbb{P}(\text{data}|x) = \frac{\mathbb{P}(x|\text{data})\mathbb{P}(\text{data})}{\mathbb{P}(x)} = \frac{q_\theta(x)}{q_\theta(x) + m\xi(x)}. \tag{11}$$

NCE optimizes the parameters θ by maximizing the log-likelihood of the posterior class distributions, or, equivalently, by minimizing the negative log-likelihoods. This is the same as a sum over binary cross-entropy losses (Eq. (2) in the main text):

$$\theta^* = \arg\min_\theta \left[-\sum_{i=1}^{N} \log\left(\frac{q_\theta(s_i)}{q_\theta(s_i) + m\xi(s_i)}\right) - \sum_{i=1}^{mN} \log\left(1 - \frac{q_\theta(t_i)}{q_\theta(t_i) + m\xi(t_i)}\right) \right]. \tag{12}$$

In expectation, we have the loss function (Eq. (4) in the main text)

$$\mathcal{L}^{\text{NCE}}(\theta) = -\mathbb{E}_{s\sim p} \log\left(\frac{q_\theta(s)}{q_\theta(s) + m\xi(s)}\right) - m\mathbb{E}_{t\sim\xi} \log\left(1 - \frac{q_\theta(t)}{q_\theta(t) + m\xi(t)}\right). \tag{13}$$

Since $q_\theta(x)/\big(q_\theta(x) + m\xi(x)\big) = 1/\Big[1 + \big(q_\theta(x)/\big(m\xi(x)\big)\big)^{-1}\Big]$, NCE's loss function can also be seen as binary logistic regression loss function with $\log\left(\frac{q_\theta(x)}{m\xi(x)}\right)$ as the input to the logistic function:

$$\mathcal{L}^{\text{NCE}}(\theta) = -\mathbb{E}_{s\sim p} \log\left(\sigma\left(\log\left(\frac{q_\theta(s)}{m\xi(s)}\right)\right)\right) - m\mathbb{E}_{t\sim\xi} \log\left(1 - \sigma\left(\log\left(\frac{q_\theta(t)}{m\xi(t)}\right)\right)\right), \tag{14}$$

where $\sigma(x) = 1/\big(1 + \exp(-x)\big)$ is the logistic function.

A.2 INFONCE

Again, we are casting the unsupervised problem of density estimation as a supervised classification problem. We consider a tuple of $m+1$ samples $T = (x_0, \ldots, x_m)$ one of which comes from the data and the rest from the noise distribution. Instead of classifying each sample independently as noise or data (as in Sec. A.1), here we are interested in identifying the position of the single data sample. This allows us to see the problem as a multi-class classification problem with $m+1$ classes.

Let Y be the random variable that holds the index of the data sample. A priori, we have $\mathbb{P}(Y = k) = 1/(m+1)$ for all $k = 0, \ldots, m$. Moreover, conditioned on sample k coming from the data distribution, all other samples must come from the noise distribution, i.e., we

have $\mathbb{P}(x_i|Y = k) = \xi(x_i)$ for $i \neq k$. As the data distribution is unknown, we model it with $\mathbb{P}(x_k|Y = k) = q_\theta(x_k)$ as in Sec. A.1. This yields the likelihood of tuple T given the data index $Y = k$

$$\mathbb{P}(T|Y = k) = q_\theta(x_k) \prod_{i \neq k} \xi(x_i) = \frac{q_\theta(x_k)}{\xi(x_k)} \prod_{i=0}^{m} \xi(x_i). \tag{15}$$

Marginalizing over Y, we obtain

$$\mathbb{P}(T) = \frac{1}{m+1} \prod_{i=0}^{m} \xi(x_i) \sum_{k=0}^{m} \frac{q_\theta(x_k)}{\xi(x_k)}. \tag{16}$$

Finally, we can compute the posterior via Bayes' rule as

$$\mathbb{P}(Y = k|T) = \frac{\mathbb{P}(T|Y = k)\mathbb{P}(Y = k)}{\mathbb{P}(T)} = \frac{\frac{q_\theta(x_k)}{\xi(x_k)}}{\sum_{i=0}^{m} \frac{q_\theta(x_i)}{\xi(x_i)}} = \frac{q_\theta(x_k)}{\sum_{i=0}^{m} q_\theta(x_i)}, \tag{17}$$

where the last equality only holds for the uniform noise distribution. The InfoNCE loss is the cross-entropy loss with respect to the true position of the data sample, i.e., in expectation and for uniform ξ it reads:

$$\mathcal{L}^{\text{InfoNCE}}(\theta) = - \underset{\substack{x \sim p \\ x_1, \dots, x_m \sim \xi}}{\mathbb{E}} \log \left(\frac{q_\theta(x)}{q_\theta(x) + \sum_{i=1}^{m} q_\theta(x_i)} \right). \tag{18}$$

Similar to how the NCE loss can be seen as the binary logistic regression loss function (Sec. A.1), the InfoNCE loss can be viewed as the multinomial logistic regression loss function with the terms $\log \left(\frac{q_\theta(x_i)}{\xi(x_i)} \right)$ entering the softmax function.

B GRADIENTS OF MLE, NCE, AND NEG

Here, we compute the gradients of MLE, NCE, and NEG, elaborating the discussion in (Artemenkov & Panov, 2020). Following the discussion in Secs. 3.2 and 4, we consider a normalized model $q_\theta(x) = \phi_\theta(x)/Z(\theta)$ with partition function $Z(\theta) = \sum_{x'} \phi_\theta(x')$ for MLE, a model $q_{\theta,Z}(x) = \phi_\theta(x)/Z$ with learnable normalization parameter Z for NCE, and a model $q_{\theta,\bar{Z}}(x) = \phi_\theta(x)/\bar{Z}$ with fixed normalization constant $\bar{Z} = |X|/m$ and a uniform noise distribution $\xi(x) = 1/|X|$ for NEG.

Thus, the losses are

$$\mathcal{L}^{\text{MLE}}(\theta) = -\mathbb{E}_{x \sim p} \log \left(q_\theta(x) \right) \tag{19}$$

$$\mathcal{L}^{\text{NCE}}(\theta, Z) = -\mathbb{E}_{x \sim p} \log \left(\frac{q_{\theta,Z}(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) - m\mathbb{E}_{x \sim \xi} \log \left(1 - \frac{q_{\theta,Z}(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) \tag{20}$$

$$\mathcal{L}^{\text{NEG}}(\theta) = -\mathbb{E}_{x \sim p} \log \left(\frac{\phi_\theta(x)}{\phi_\theta(x) + 1} \right) - m\mathbb{E}_{x \sim \xi} \log \left(1 - \frac{\phi_\theta(x)}{\phi_\theta(x) + 1} \right) \tag{21}$$

$$= -\mathbb{E}_{x \sim p} \log \left(\frac{q_{\theta,\bar{Z}}(x)}{q_{\theta,\bar{Z}}(x) + m\xi(x)} \right) - m\mathbb{E}_{x \sim \xi} \log \left(1 - \frac{q_{\theta,\bar{Z}}(x)}{q_{\theta,\bar{Z}}(x) + m\xi(x)} \right). \tag{22}$$

For MLE, we find

$$\frac{d\mathcal{L}^{\text{MLE}}(\theta)}{d\theta} = \frac{d}{d\theta} \left(-\mathbb{E}_{x \sim p} \log \left(q_\theta(x) \right) \right) \tag{23}$$

$$= \frac{d}{d\theta} \left(-\sum_x \left(p(x) \log \left(\phi_\theta(x) \right) \right) + \log \left(\sum_x \phi_\theta(x) \right) \right) \tag{24}$$

$$= -\sum_x \left(\frac{p(x)}{\phi_\theta(x)} \cdot \frac{d\phi_\theta(x)}{d\theta} \right) - \frac{1}{\sum_x \phi_\theta(x)} \cdot \sum_x \frac{d\phi_\theta(x)}{d\theta} \tag{25}$$

$$= -\sum_x \left(\frac{p(x)}{q_\theta(x)} - 1 \right) \cdot \frac{1}{Z(\theta)} \cdot \frac{d\phi_\theta(x)}{d\theta}. \tag{26}$$

For the NCE loss we will use the templates

$$\frac{d \log \left(\frac{f(z)}{f(z)+c} \right)}{dz} = \frac{d \log \left(\frac{1}{1+c/f(z)} \right)}{dz} \tag{27}$$

$$= -\frac{d \log(1 + c/f(z))}{dz} \tag{28}$$

$$= -\frac{1}{1+c/f(z)} \cdot \frac{-c}{f(z)^2} \cdot \frac{df(z)}{dz} \tag{29}$$

$$= \frac{c}{f(z)+c} \cdot \frac{1}{f(z)} \cdot \frac{df(z)}{dz} \tag{30}$$

$$\frac{d \log \left(\frac{c}{f(z)+c} \right)}{dz} = -\frac{d \log \left(f(z)/c + 1 \right)}{dz} \tag{31}$$

$$= -\frac{1}{f(z)/c + 1} \cdot \frac{1}{c} \cdot \frac{df(z)}{dz} \tag{32}$$

$$= -\frac{1}{f(x)+c} \cdot \frac{df(z)}{dz} \tag{33}$$

with some differentiable function $f(z)$ and c independent of z.

For the NCE loss we get

$$\frac{d\mathcal{L}^{\text{NCE}}(\theta, Z)}{d\theta} = \frac{d}{d\theta} \left(-\mathbb{E}_{x \sim p} \log \left(\frac{q_{\theta,Z}(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) - m\mathbb{E}_{x \sim \xi} \log \left(1 - \frac{q_{\theta,Z}(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) \right) \tag{34}$$

$$= \frac{d}{d\theta} \left(-\mathbb{E}_{x \sim p} \log \left(\frac{q_{\theta,Z}(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) - m\mathbb{E}_{x \sim \xi} \log \left(\frac{m\xi(x)}{q_{\theta,Z}(x) + m\xi(x)} \right) \right) \tag{35}$$

$$= -\sum_x \left[p(x) \frac{m\xi(x)}{q_{\theta,Z}(x) + m\xi(x)} \frac{1}{q_{\theta,Z}(x)} \frac{dq_{\theta,Z}(x)}{d\theta} \right. \tag{36}$$

$$\left. + m\xi(x) \frac{-1}{q_{\theta,Z}(x) + m\xi(x)} \frac{dq_{\theta,Z}(x)}{d\theta} \right] \tag{37}$$

$$= -\sum_x \left(\frac{p(x)}{q_{\theta,Z}(x)} - 1 \right) \frac{m\xi(x)}{q_{\theta,Z}(x) + m\xi(x)} \frac{1}{Z} \frac{d\phi_\theta(x)}{d\theta}. \tag{38}$$

We used our templates at the third equality sign with $f(z) = q_{\theta,Z}(x)$ and $c = m\xi(x)$. The derivation of the gradients for the NEG loss is entirely analogous to that for NCE with $q_{\theta,Z}(x)$ replaced by $q_{\theta,\bar{Z}}(x)$.

Together, the gradients of the three losses are

$$\frac{d\mathcal{L}^{\text{MLE}}(\theta)}{d\theta} = -\sum_{x \in X} \left(\frac{p(x)}{q_\theta(x)} - 1 \right) \qquad\qquad \frac{1}{Z(\theta)} \quad \frac{d\phi_\theta(x)}{d\theta} \tag{39}$$

$$\frac{d\mathcal{L}^{\text{NCE}}(\theta, Z)}{d\theta} = -\sum_{x \in X} \left(\frac{p(x)}{q_{\theta,Z}(x)} - 1 \right) \quad \frac{m\xi(x)}{q_{\theta,Z}(x) + m\xi(x)} \frac{1}{Z} \quad \frac{d\phi_\theta(x)}{d\theta} \tag{40}$$

$$\frac{d\mathcal{L}^{\text{NEG}}(\theta)}{d\theta} = -\sum_{x \in X} \left(\frac{p(x)}{q_{\theta,\bar{Z}}(x)} - 1 \right) \quad \frac{m\xi(x)}{q_{\theta,\bar{Z}}(x) + m\xi(x)} \frac{1}{\bar{Z}} \quad \frac{d\phi_\theta(x)}{d\theta} \tag{41}$$

The fractions involving $m\xi(x)$ in the gradients of $\mathcal{L}^{\text{NCE}}$ and $\mathcal{L}^{\text{NEG}}$ tend to one as $m \to \infty$ highlighting that a higher number of noise samples improves NCE's approximation of MLE (Artemenkov & Panov, 2020). All three gradients are the same up to this factor and the different choice of normalization. In all of them, the models q_θ, $q_{\theta,Z}$, or $q_{\theta,\bar{Z}}$ try to match the data distribution p according to the first factor in each gradient. This similarity of the gradients holds independent of the assumptions of Thm. 1 and Cor. 2. We optimize all losses with stochastic gradient descent and can therefore expect our analysis to hold even if the assumptions are violated.

C UMAP's loss function

In the original UMAP paper, McInnes et al. (2018) define weights $\mu(ij) \in [0, 1]$ on the skNN graph and state that these shall be reproduced by the low-dimensional similarities $\phi(ij)$ by means of a sum of binary cross-entropy loss functions, one for each edge ij

$$- \sum_{ij} \Big[\mu(ij) \log \big(\phi(ij) \big) + \big(1 - \mu(ij) \big) \log \big(1 - \phi(ij) \big) \Big]. \tag{42}$$

Indeed, this loss has its minimum at $\mu(ij) = \phi(ij)$ for all ij. However, it is of course not possible to achieve zero loss for any real-world data using the Cauchy kernel in two dimensions. Experiments show that using this loss function in practice leads to an excess of repulsion and consequently to very poor embeddings (Böhm et al., 2022). The actual UMAP implementation has much less repulsion due to the sampling of repulsive edges, see below.

As the weights $\mu(ij)$ are only supported on the sparse skNN graph, most of the $1 - \mu(ij)$ terms are equal to one. To simplify the loss function, the UMAP paper replaces all $1 - \mu(ij)$ terms by 1, leading to the loss function

$$- \sum_{ij} \Big[\mu(ij) \log \big(\phi(ij) \big) + \log \big(1 - \phi(ij) \big) \Big]. \tag{43}$$

In the implementation, UMAP samples the repulsive edges, which drastically changes the loss (Böhm et al., 2022) to the effective loss (Damrich & Hamprecht, 2021)

$$- \sum_{ij} \Big[\mu(ij) \log \big(\phi(ij) \big) + \frac{m(d_i + d_j)}{2n} \log \big(1 - \phi(ij) \big) \Big], \tag{44}$$

where $d_i = \sum_j \mu(ij)$ denotes the degree of node i and the number of negative samples m is a hyperparameter. By default, $m = 5$. Since $d_i \approx \log(k)$, the effective loss only has about $m \log(k)/n$ of the repulsion in the originally stated loss function. As a result, the $\mu(ij)$ are not reproduced in the embedding space by this loss function.

We rewrite this effective loss function further to fit into our framework. The attractive prefactors $\mu(ij)$ sum to $\sum_{ij} \mu(ij)$, while the repulsive prefactors add up to m times this factor. Dividing the entire loss function by this term does not change its properties. But then, we can write the prefactors as probability distributions $p(ij) = \mu(ij)/\sum_{ij} \mu(ij)$ and $\xi(ij) = \big(p(i) + p(j) \big)/n$ using $p(i) = \sum_j p(ij)/2$. With this, we can write the effective loss function as

$$- \sum_{ij} p(ij) \log \big(\phi(ij) \big) - m \sum_{ij} \xi(ij) \log \big(1 - \phi(ij) \big), \tag{45}$$

or in the expectation form as

$$- \mathbb{E}_{ij \sim p} \log \big(\phi(ij) \big) - m \mathbb{E}_{ij \sim \xi} \log \big(1 - \phi(ij) \big), \tag{46}$$

like we do in Eq. (7).

D Noise distributions

Here we discuss the various noise distributions used by UMAP, NCVis, and our framework. The main claim is that all these noise distributions are sufficiently close to uniform, even though their exact shape depends on the implementation details.

Since our actual implementation, as well as the reference implementations of UMAP and NCVis, considers edges ij and ji separately, we will do so from now on. Hence, there is now a total of $E := 2|s k \text{NN}|$ edges. We always assume that $p(ij) = p(ji)$ and adding up the probabilities for both directions yields one: $\sum_{i,j=1}^{n} p(ij) = 1$. For a given data distribution over pairs of points ij, we define $p(i) = \sum_{j=1}^{n} p(ij)$ so that $\sum_i p(i) = 1$. As discussed in Supp. B of (Damrich & Hamprecht, 2021), the $p(i)$ values are approximately constant when $p(ij)$ is uniform on the skNN graph or proportional to the UMAP similarities.

UMAP's noise distribution is derived in (Damrich & Hamprecht, 2021) and reads in our notation (Supp. C)

$$\xi(ij) = \frac{p(i) + p(j)}{2n} \,.$$

(47)

Note that UMAP uses a weighted version of the skNN graph. Still, ξ is close to uniform, see Supp. B of (Damrich & Hamprecht, 2021).

The noise distribution of NCVis is also close to being uniform and equals (Artemenkov & Panov, 2020):

$$\xi(ij) = \frac{p(i)}{n} \,.$$

(48)

This is a slightly different noise distribution than in UMAP and in particular it is asymmetric. However, we argue that in practice it is equivalent to the same noise distribution as in UMAP. The noise distribution is used in two ways in NCVis: for sampling noise samples and in the posterior class probabilities

$$\mathbb{P}(\text{data}|ij) = \frac{q_{\theta, Z}(ij)}{q_{\theta, Z}(ij) + m\xi(ij)} \,.$$

(49)

Both in the reference NCVis implementation and in ours, for the second role, the noise distribution is explicitly approximated by the uniform one and we use the posterior probabilities

$$\mathbb{P}(\text{data}|ij) = \frac{q_{\theta, Z}(ij)}{q_{\theta, Z}(ij) + m\frac{1}{2|skNN|}} \,.$$

(50)

Together with the symmetry of the Cauchy kernel this implies that the repulsion on the embedding vectors e_i and e_j from noise sample ij and ji is the same. As a result, the expectation

$$\mathbb{E}_{ij \sim \xi} \log \left(1 - \frac{q_{\theta, Z}(ij)}{q_{\theta, Z}(ij) + m\frac{m}{2|skNN|}} \right)$$

(51)

is the same for $\xi(ij) = p(i)/n$ and for UMAP's noise distribution

$$\xi(ij) = \frac{p(i) + p(j)}{2n} \,.$$

(52)

In our framework, the noise distribution is influenced by the batched training procedure (Alg. S1) because the negative samples can come only from the current training batch.

In every epoch, we first shuffle the set of directed edges of the skNN graph and then chunk it into batches. To emphasize, the batches consist of *directed edges* and not of the original data points. For each edge in a batch, we take its head and sample m indices from the heads and tails of all edges in the batch (excluding the already selected head) and use them as tails to form negative sample pairs.

To obtain a negative sample pair ij, the batch must contain some directed edge ik, providing the head of the negative sample, and some pair lj or jl, providing the tail. We want to derive the expected number of times that a directed edge ij is considered as a negative sample in a batch. For simplicity, let us assume that the number of batches divides the number of directed edges E. As the set of skNN edges is shuffled every epoch, the expected number of pairs ij as negative samples is the same for all batches.

Let us consider a batch B of size b. We denote by Y_{rs} the random variable that holds the number of times edge rs appears in B. We also introduce random variables $Y_{\neg rs} = \sum_{t \neq r} Y_{ts}$ and $Y_{r \neg s} = \sum_{t \neq s} Y_{rt}$. Let $p(r \neg s) = p(\neg sr) := p(r) - p(rs)$. For each occurrence of an i as head of an edge in B, we sample m tails to create negative samples uniformly from all head and tails in B with replacement, but we prevent sampling the identical head i as negative sample tail. If, however, the same node i is part of the other edges in the batch, then it may be sampled and would create a futile negative sample ii. There are m chances for creating a negative sample edge ij for every head i and any occurrence of j in the batch. The number of heads i in the batch is $Y_{ij} + Y_{i \neg j}$ and the number of occurrences of j is $Y_{ij} + Y_{ji} + Y_{\neg ij} + Y_{j \neg i}$. Since we sample the tail of a negative sample pair uniformly with replacement, any of the occurrences of j has probability $1/(2b-1)$ to be

selected. Hence, the expected number N_{ij} of times that the ordered pair ij with $i \neq j$ is considered as a negative sample in batch B is

$$N_{ij} = m(Y_{ij} + Y_{i\neg j})\frac{Y_{ij} + Y_{ji} + Y_{\neg ij} + Y_{j\neg i}}{2b-1}. \tag{53}$$

Since a head i may not choose itself to form a negative sample, the expected number of times that ii appears as negative sample in the batch is

$$N_{ii} = m\sum_{j} Y_{ij}\frac{Y_{ij} - 1 + Y_{i\neg j} + Y_{ji} + Y_{\neg ji}}{2b-1}. \tag{54}$$

Since the batches are sampled without replacement, the random variables Y_{rs} are distributed according to a multivariate hypergeometric distribution, meaning that

$$\mathbb{E}(Y_{rs}) = bp(rs) \tag{55}$$

$$\mathbb{E}(Y_{\neg rs}) = bp(\neg rs) \tag{56}$$

$$\text{Var}(Y_{rs}) = b\frac{E-b}{E-1}p(rs)\big(1 - p(rs)\big) \tag{57}$$

$$\text{Cov}(Y_{rs}, Y_{\neg uv}) = -b\frac{E-b}{E-1}p(rs)p(\neg uv). \tag{58}$$

We use these expressions and analogous ones together with the symmetries $p(rs) = p(sr)$ to compute (leaving out intermediate algebra steps) the expectation of N_{ij} over the shuffles:

$$\mathbb{E}(N_{ij}) = \frac{mb}{2b-1}\left(\frac{E-b}{E-1}p(ij) + 2\left(b - \frac{E-b}{E-1}\right)p(i)p(j)\right). \tag{59}$$

Since we sample m negative samples for each positive sample and since each batch contains b positive samples, we need to divide $\mathbb{E}(N_{ij})$ by mb to obtain $\xi(ij)$:

$$\xi(ij) = \frac{1}{2b-1}\left(\frac{E-b}{E-1}p(ij) + 2\left(b - \frac{E-b}{E-1}\right)p(i)p(j)\right). \tag{60}$$

Similarly,

$$\mathbb{E}(N_{ii}) = \frac{mb}{2b-1}\left(-\frac{b-1}{E-1}p(i) + 2\left(b - \frac{E-b}{E-1}\right)p(i)^2\right) \tag{61}$$

and hence the noise distribution value for the pair ii is

$$\xi(ii) = \frac{1}{2b-1}\left(-\frac{b-1}{E-1}p(i) + 2\left(b - \frac{E-b}{E-1}\right)p(i)^2\right). \tag{62}$$

We see that the noise distribution depends on the batch size b. This is not surprising: For example, if the batch size is equal to one, the ordered pair ij can only be sampled as a negative sample in the single batch that consists of that pair. Indeed, for $b = 1$ our formula yields

$$\xi(ij) = p(ij), \tag{63}$$

meaning that the data and the noise distributions coincide. Conversely, if $b = E$ and there is only one batch, we obtain

$$\xi(ij) = \frac{2E}{2E-1}p(i)p(j) \tag{64}$$

and the noise distribution is close to uniform. For batch sizes between 1 and E the noise distribution is in between these two extremes. For MNIST, $E \approx 1.5 \cdot 10^6$, and in our experiments we used $b = 1024$. This means that the prefactor of the share of the data distribution is about 0.0005 while that of the near-uniform distribution $p(i)p(j)$ is about 0.9995, so the resulting noise distribution is close to uniform. Note that Thm. 1 and Cor. 2 only require the noise distribution to be nonzero where the data distribution is nonzero, which is the case for any batch size.

E   OPTIMIZATION TRICKS IN UMAP'S REFERENCE IMPLEMENTATION

UMAP's repulsive term

$$-\log(1 - \phi(ij)) = \log\left(\frac{1 + d_{ij}^2}{d_{ij}^2}\right) \tag{65}$$

can lead to numerical problems if the two points of the negative sample pair are very close. In addition to the learning rate decay, discussed in Sec. 6, UMAP's implementation uses further tricks to prevent unstable or even crashing training.

In non-parametric UMAP's reference implementation, the gradient on embedding position e_i exerted by a single sampled repulsive pair ij is actually

$$2\frac{1}{d_{ij}^2 + \zeta}\frac{1}{1 + d_{ij}^2}(e_j - e_i) \tag{66}$$

with $\zeta = 0.001$ instead of $\zeta = 0$. This corresponds to the full loss function

$$-\mathbb{E}_{ij\sim p}\log(\phi(ij)) - m\left(1 + \frac{\zeta}{1 - \zeta}\right)\mathbb{E}_{ij\sim\xi}\log\left(1 + \frac{\zeta}{1 - \zeta} - \phi(ij)\right). \tag{67}$$

However, we found that ζ does not have much influence on the appearance of a UMAP embedding. Fig. S1 shows MNIST embeddings obtained using the original UMAP implementation modified to use different values of ζ. Neither a much smaller positive value such as $\zeta = 10^{-10}$ nor setting $\zeta = 0$ substantially changed the appearance of the embedding (even though some runs with $\zeta = 0$ did crash). The learning rate annealing played a much bigger role in how the embedding looked like (Fig. S1, bottom row).

The reference implementation of parametric UMAP uses automatic differentiation instead of implementing the gradients manually. To avoid terms such as $\log(0)$ in the repulsive loss, it clips the argument of the logarithm from below at the value $\varepsilon = 10^{-4}$, effectively using the loss function

$$-\mathbb{E}_{ij\sim p}\log\left(\max\left\{\varepsilon, \frac{1}{1 + d_{ij}^2}\right\}\right) - m\mathbb{E}_{ij\sim\xi}\log\left(\max\left\{\varepsilon, 1 - \frac{1}{1 + d_{ij}^2}\right\}\right). \tag{68}$$

We employ a similar clipping in our code whenever we apply the logarithm function. Again, we found that the exact value of ε is not important for our UMAP reimplementation, while using the learning rate annealing is (Fig. S2, top two rows). In the extreme case of setting $\varepsilon = 0$ our UMAP runs crashed. We believe that the reason is that we allow negative sample pairs to be of the form ii, which would not send any gradient, but would lead to a zero argument to the logarithm. The reference implementation of UMAP excludes such negative sample pairs ii.

Our Neg-t-SNE approach does not have any of these problems, as the repulsive term is

$$-\log\left(1 - \frac{\frac{1}{1 + d_{ij}^2}}{\frac{1}{1 + d_{ij}^2} + 1}\right) = \log\left(\frac{2 + d_{ij}^2}{1 + d_{ij}^2}\right) \leq \log(2) \tag{69}$$

and does not diverge for $d_{ij} \to 0$. For this reason, Neg-t-SNE is not very sensitive to the value at which we clip arguments to the logarithm and works even with $\varepsilon = 0$, both with and without learning rate annealing (Fig. S2, bottom two rows).

The attractive terms in the loss functions do not pose numerical problems in practice due to the heavy tail of the Cauchy kernel. That said, in order to keep different experiments and losses comparable, we used clipping in both the attractive and the repulsive loss terms with $\varepsilon = 10^{-10}$ for all neighbor embedding plots computed with our framework unless otherwise stated.

A recent pull request[3] to the parametric part of UMAP's reference implementation proposed another way to ameliorate the numerical instabilities. The clipping of the arguments to the logarithm was

---

[3] https://github.com/lmcinnes/umap/pull/856

(a) $\zeta = 10^{-3}$, no annealing   (b) $\zeta = 10^{-10}$, no annealing   (c) $\zeta = 0$, no annealing

(d) $\zeta = 10^{-3}$, with annealing   (e) $\zeta = 10^{-10}$, with annealing   (f) $\zeta = 0$, with annealing

Figure S1: UMAP embeddings of the MNIST dataset, ablating numerical optimization tricks of UMAP's reference implementation. The learning rate annealing is crucial (bottom row) but safe-guarding against divisions by zero in UMAP's repulsive term Eq. (66) by adding ζ to the denominator has little effect. These experiments were run using the reference implementation, modified to change the ζ value and/or to switch off the learning rate annealing.

replaced with a sigmoid of the logarithm of the Cauchy kernel, so that the attractive and repulsive terms become

$$- \log \Big(\max \big(\varepsilon, \phi(ij) \big) \Big) \rightarrow - \log \Big(\sigma \Big(\log \big(\phi(ij) \big) \Big) \Big) \tag{70}$$

$$- \log \Big(\max \big(\varepsilon, 1 - \phi(ij) \big) \Big) \rightarrow - \log \Big(1 - \sigma \Big(\log \big(\phi(ij) \big) \Big) \Big), \tag{71}$$

where $\sigma(x) = 1/\big(1 + \exp(-x)\big)$ is the sigmoid function. This change can seem drastic as, e.g., for $\phi(ij) = 1$ we have $\max\{\varepsilon, \phi(ij)\} = 1$, but $\sigma\Big(\log\big(\phi(ij)\big)\Big) = 1/2$. But unravelling the definitions shows that this turns the loss function precisely into our Neg-t-SNE loss function since

$$\sigma \Big(\log \big(\phi(ij) \big) \Big) = \frac{1}{1 + \exp\Big(- \log \big(\phi(ij) \big) \Big)} = \frac{1}{1 + \phi(ij)^{-1}} = \frac{\phi(ij)}{\phi(ij) + 1}. \tag{72}$$

So, in order to overcome the numerical problems incurred by UMAP's implicit choice of $1/d_{ij}^2$ as similarity kernel, the pull request suggested a fix that turns out to be equivalent to negative sampling using the Cauchy kernel. We encourage this change to UMAP as it makes its loss function equivalent to our Neg-t-SNE and thus also conceptually more related to t-SNE. We also suggest to implement it in the non-parametric case.

F DATASETS

We used the well-known MNIST (LeCun et al., 1998) dataset for most of our experiments. We downloaded it via the torchvision API from `http://yann.lecun.com/exdb/mnist/`. This website does not give a license. But `https://keras.io/api/datasets/mnist/` and `http://www.pymvpa.org/datadb/mnist.html` name Yann LeCun and Corinna Cortes as copyright holders and claim MNIST to be licensed under CC BY-SA 3.0, which permits use and adaptation. The MNIST dataset consists of $70\,000$ grayscale images, 28×28 pixels each, that show handwritten digits.

(a) UMAP, $\varepsilon = 10^{-4}$, no ann.   (b) UMAP, $\varepsilon = 10^{-10}$, no ann.

(c) UMAP, $\varepsilon = 10^{-4}$, with ann.   (d) UMAP, $\varepsilon = 10^{-10}$, with ann.

(e) Neg-t-SNE, $\varepsilon = 10^{-4}$, no ann.   (f) Neg-t-SNE, $\varepsilon = 10^{-10}$, no ann.   (g) Neg-t-SNE, $\varepsilon = 0$, no ann.

(h) Neg-t-SNE, $\varepsilon = 10^{-4}$, with ann. (i) Neg-t-SNE, $\varepsilon = 10^{-10}$, with ann.   (j) Neg-t-SNE, $\varepsilon = 0$, with ann.

Figure S2: UMAP and Neg-t-SNE embeddings of the MNIST dataset using different values ε at which we clip arguments to logarithm functions. These experiments were done using our implementation. Varying ε did not strongly influence the appearance of the embedding. But setting $\varepsilon = 0$ led to crashing UMAP runs. Annealing the learning rate is important for UMAP, yet not for Neg-t-SNE.

The Kuzushiji-49 dataset (Tarin et al., 2018) was downloaded from `https://github.com/rois-codh/kmnist` where it is licensed under CC-BY-4.0. It contains $270\,912$ grayscale images, 28×28 pixels each, that show 49 different cursive Japanese characters.

The SimCLR experiments were performed on the CIFAR-10 (Krizhevsky, 2009) dataset, another standard machine learning resource. We downloaded it via the `sklearn.datasets.fetch_openml` API from `https://www.openml.org/search?type=data&sort=runs&id=40927&status=active`. Unfortunately, we were not able to find a license for this dataset. CIFAR-10 consists of $60\,000$ images, 32×32 RGB pixels each, depicting objects from five animal and five vehicle classes.

The transcriptomic dataset of Kanton et al. (2019) was downloaded from `https://www.ebi.ac.uk/arrayexpress/experiments/E-MTAB-7552/`, which permits free use. We only used the $20\,272$ cells in the human brain organoid cell line '409b2'. The transcriptomic dataset (Wagner et al., 2018) was downloaded in its scanpy version from `https://kleintools.hms.harvard.edu/paper_websites/wagner_zebrafish_timecourse2018/mainpage.html`. The full dataset at `https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE112294` is free to download and reproduce. The dataset contains gene expressions for $63\,530$ cells from a developing zebrafish embryo. The downloaded UMIs of both datasets were preprocessed as in (Böhm et al., 2022; Kobak & Berens, 2019). After selecting the 1000 most variable genes, we normalized the library sizes to the median library size in the dataset, log-transformed the normalized values with $\log_2(x+1)$, and finally reduced the dimensionality to 50 via PCA.

The trascriptomic dataset of the C. elegans flatworm (Packer et al., 2019; Narayan et al., 2021) was obtained from `http://cb.csail.mit.edu/cb/densvis/datasets/` with consent of the authors who license it under CC BY-NC 2.0. It is already preprocessed to 100 principal components.

G Implementation

All contrastive embeddings were computed with our PyTorch (Paszke et al., 2019) implementation of Neg-t-SNE, NCVis, UMAP, and InfoNC-t-SNE. Exceptions are Fig. 1, and analogous Figs. S9 and S7. There for panel h we used the reference implementation of NCVis (Artemenkov & Panov, 2020) (with a fixed number of noise samples m, and not the default schedule), and for panel g we used UMAP 0.5. The t-SNE plots were created with the openTSNE (Poličar et al., 2019) (version 0.6.1) package. Similarly, we used the reference UMAP implementation in Fig. S1 and openTSNE in Figs. S14 and S15.

We extended these implementations of NCVis, UMAP, and t-SNE to make them accept custom embedding initializations and unweighted skNN graphs and to log various quantities of interest. We always used the standard Cauchy kernel for better comparability.

All PCAs were computed with sklearn (Pedregosa et al., 2011). We used PyKeOps (Charlier et al., 2021) to compute the exact skNN graph and to handle the quadratic complexity of computing the partition functions on a GPU. The same PCA initialization and skNN graph with $k = 15$ were used for all embeddings. The skNN graph for MNIST and Kuzushiji-49 was computed on a 50-dimensional PCA of the dataset.

When computing logarithms during the optimization of neighbor embeddings, we clip the arguments to the range $[10^{-10}, 1]$, save for Fig. S2, where we ablated this lower bound. The lower bound is smaller than in the reference implementation of parametric UMAP, where it is set to 10^{-4}.

Our defaults were a batch size of 1024, linear learning rate annealing from 1 (non-parametric) or 0.001 (parametric) to 0 (save for Figs. 2, S1, and S2), 750 epochs (save for Figs. S6 and S13) and $m = 5$ noise samples (save for Figs. S4, S6, S14, and S15).

We initialized all embeddings with a scaled version of PCA (save for in Figs. S14, and S15). For t-SNE embeddings we rescaled the initialization so that the first dimension has a standard deviation of 0.0001 (as is default in openTSNE), for all other embeddings to a standard deviation of 1.

We employed some version of 'early exaggeration' (van der Maaten & Hinton, 2008) for the first 250 epochs in most non-parametric plots. For t-SNE it is the default early exaggeration of openTSNE. When varying $\bar{Z}$ in non-parametric Neg-t-SNE, early exaggeration meant using $\bar{Z} = |X|/m$ for the first 250 epochs (save for Fig. S7). When varying the number of noise samples in Figs. S4, S14 and S15, we still used $m = 5$ for the first 250 epochs. In Figs. 2, 3, S1, and S2 as well as in all reference NCVis or UMAP plots, we did not use early exaggeration as neither small $\bar{Z}$ nor high m made it necessary. When we used some form of early exaggeration and learning rate annealing, the annealing to zero took place over the first 250 epochs, was then reset, and annealed again to zero for the remaining, typically 500, epochs.

Non-parametric runs were optimized with SGD without momentum and parametric runs with the Adam optimizer (Kingma & Ba, 2015). Parametric runs used the same feed-forward neural net architecture as the reference parametric UMAP implementation. That is, four layers with dimensions *input dimension* $- 100 - 100 - 100 - 2$ with ReLU activations in all but the last one. We used the vectorized, 786-dimensional version of MNIST as input to the parametric neighbor embedding methods (and not the 50-dimensional PCA; but the skNN graph was computed in the PCA space for consistency with non-parametric embeddings).

Like the reference NCVis implementation, we used the fractions $q_{\theta,Z}(x)/(q_{\theta,Z}(x) + m)$ instead of $q_{\theta,Z}(x)/\big(q_{\theta,Z}(x) + m\xi(x)\big)$. This is a mild approximation as the noise distribution is close to uniform. But it means that the model learns a scaled data distribution (cf. Cor. 2), so that we need to multiply the learned normalization parameter Z by $n(n-1)$ when comparing to t-SNE or checking normalization of the NCVis model. Similarly, we also approximate the true noise distribution by the uniform distribution for the fractions $q_\theta(x)/(q_\theta(x) + \bar{Z}m/|X|)$ — instead of $q_\theta(x)/\big(q_\theta(x) + \bar{Z}m\xi(x)\big)$ — in our Neg-t-SNE implementation.

We mentioned in Sec. 5 and showed in Fig. S4 that one can move along the attraction-repulsion spectrum also by changing the number of noise samples m, instead of the fixed normalization constant $\bar{Z}$. In UMAP's reference implementation, there is a scalar prefactor γ for the repulsive forces. Theoretically, adjusting γ should also move along the attraction-repulsion spectrum, but setting it higher than 1 led to convergence problems in (Böhm et al., 2022), Fig. A11. When varying our $\bar{Z}$, we did not have such issues.

For panels i in Figs. 1, S7 – S12 the Neg-t-SNE spectra were computed for $\bar{Z}$ equal to $Z(\theta^{t\text{-SNE}})$, Z^{NCVis}, and $\frac{n(n-1)}{m} \cdot x$, where $x \in \{5 \cdot 10^{-5}, 1 \cdot 10^{-4}, 2 \cdot 10^{-4}, 5 \cdot 10^{-4}, \ldots, 1 \cdot 10^2, 2 \cdot 10^2, 5 \cdot 10^2\}$.

For the SimCLR experiments, we trained the model for 1000 epochs, of which we used 5 epochs for warmup. The learning rate during warmup was linearly interpolated from 0 to the initial learning rate. After the warmup epochs, we annealed the learning rate with a cosine schedule (without restarts) to 0 (Loshchilov & Hutter, 2017). We optimized the model parameters with SGD and momentum 0.9. We used the same data augmentations as in (Chen et al., 2020). We used a ResNet18 (He et al., 2016) as the backbone and a projection head consisting of two linear layers $(512 - 1024 - 128)$ with a ReLU activation in-between. The loss was applied to the L_2 normalized output of the projection head, but like Chen et al. (2020) we used the output of the ResNet as the representation for the linear evaluation. As similarity function we used the exponential of the normalized scalar product (cosine similarity) and always kept the temperature at 0.5, as suggested in Chen et al. (2020). We clipped the arguments to logarithms to be non-negative. When considering the entire batch as negative samples, we omit both head and tail of the considered positive sample, while we only omit the head when sampling a smaller number of negative samples.

The ResNet was trained on the combined CIFAR-10 train and test sets. When training the classifier, we froze the ResNet and only used the train set. The reported metrics are computed on the test set. We chose sklearn's KNearestNeighbors classifier with cosine metric and $k = 15$ neighbors. The linear classifier was a simple linear layer that maps from 512 dimensions to the 10 classes and was trained via a cross-entropy loss. The linear classifier was trained for 100 epochs and an initial learning rate of 30 that was annealed with a cosine schedule to 0. We trained the linear classifier using data augmentations as in (Chen et al., 2020), that is, we randomly flipped as well as randomly resized the images.

Our code is included in the supplementary material.

Table S1: Run time overview for the most compute-heavy experiments

	Number of runs	Time per run [min] (mean±SD)
Neg-t-SNE for Figs. 1, S7, S9, S10, S11	360	39 ± 4
Neg-t-SNE for Fig. S12	24	121 ± 44
Neg-t-SNE for Fig. S13	3	3592 ± 44
NCVis (our implementation) for Fig. S6b	3	786 ± 2
SimCLR runs for Tab. 1	12	694 ± 28

Table S2: Learned normalization parameter for NCVis and partition function of t-SNE in our experiments. Mean and standard deviation is computed over three random seeds. In our setup t-SNE is deterministic.

	Z^{NCVis} [10^6]	$Z(\theta^{t\text{-SNE}})$ [10^6]
MNIST Fig. 1	34.3 ± 0.1	8.13
MNIST without EE Fig. S7	34.3 ± 0.1	6.25
MNIST imbalanced Fig. S8	6.15 ± 0.06	3.12
Human brain organoid Fig. S9	3.57 ± 0.03	1.30
Zebrafish Fig. S10	30.8 ± 0.1	7.98
C. elegans Fig. S11	36.9 ± 0.7	11.7
Kuzushiji-49 Fig. S12	395 ± 3	89.6

G.1 STABILITY

Whenever we reported a metric or show a graph, we ran the experiments for 3 different random seeds, and reported the mean $\pm$ the standard deviation. When the standard deviation was very small, we omitted it from the main text and report it in Tab. S2. Save for the usually approximate skNN graph computation, t-SNE does not depend on a random seed. As we computed the skNN exactly with PyKeOps (Charlier et al., 2021), t-SNE is deterministic in our framework.

Panels i in Figs. 1, S7 – S12 show the standard deviation as shaded area. Again, the standard deviations are very small and barely visible. The ratio of standard deviation to mean was never larger than 0.006 in panels i of Figs. 1, S7 – S12. Similarly, the standard deviation in Figs. S5 and S6, shown as shaded area, is mostly smaller than the line width.

G.2 COMPUTE

We ran our neighbor embedding experiments on a machine with 56 Intel(R) Xeon(R) Gold 6132 CPU @ 2.60GHz, 502 GB RAM and 10 NVIDIA TITAN Xp GPUs. The SimCLR experiments were conducted on a Slurm cluster node with 8 cores of an Intel(R) Xeon(R) Gold 5220 CPU @ 2.20GHz and a Nvidia V100 GPU with a RAM limit of 54.3 GB. Each experiment used one GPU at most.

Our total compute is dominated by the neighbor embedding runs for Figs. 1, S7, S9 – S12 and S6b and by the SimCLR experiments. Tab. S1 lists the number of runs and the average run time. We thus estimate the total compute time to be about 640 hours.

Our implementation uses pure PyTorch and relies on GPUs. But for the non-parametric experiments, much of the computation consists of sampling negative neighbors and computationally light updates to the embedding positions. Therefore, the CPU-based numba or C++ reference implementations of UMAP and NCVis are much faster. However, our implementation is arguably easier to inspect and adapt by the machine learning community and seamlessly integrates non-parametric and parametric settings as well as all four contrastive loss functions. It is thus more suited as a research tool rather than for large throughput application.

As the change from NCVis to Neg-t-SNE is as simple as fixing the learnable normalization parameter to a constant, we have also adapted the original NCVis code to compute Neg-t-SNE. We have

not used this for any of the experiments of the paper, but include it as part of the supplementary as this implementation would retain the speed of the original NCVis implementation.

Algorithm S1: Batched contrastive neighbor embedding algorithm

---

input : list of directed skNN graph edges $E = [i_1 j_1, \ldots, i_{|E|} j_{|E|}]$

parameters θ `// embeddings (non-param.)/ network weights (param.)`

number of epochs T

learning rate η

number of noise samples m

Cauchy kernel q `// of embeddings (non-param.)/ network output (param.)`

batch size b

loss mode $mode$

normalization constant $\bar{Z}$ `// default` $|E|/m$`, required for` $mode = $ `Neg-`t`-SNE`

output: final embeddings $e_1, \ldots, e_n$

1   **if** $mode = \textit{NCVis}$ **then**

2     $Z = 1$

3   **for** $t = 0$ **to** T **do**

     `// Learning rate annealing`

4     $\eta_t = \eta \cdot (1 - \frac{t}{T})$

5     $\alpha = 0$

6   **while** $\alpha < |E|$ **do**

7       $\mathcal{L} = 0$

8   **for** $\beta = 1, \ldots, b$ **do**

         `// Sample noise edge tails but omit head of considered edge`

9         $j_1^-, \ldots, j_m^- \sim \text{Uniform}(\{i_{\alpha+1}, j_{\alpha+1}, \ldots, \widehat{i_{\alpha+\beta}}, \ldots, j_{\alpha+b}\}$

         `// Aggregate loss based on mode`

10   **if** $mode = \textit{Neg-t-SNE}$ **then**

11         $\mathcal{L} = \mathcal{L} - \log\left(\frac{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta})}{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta}) + \bar{Z} m/|E|}\right) - \sum_{\mu=1}^{m} \log\left(\frac{q_\theta(i_{\alpha+\beta} j_\mu^-)}{q_\theta(i_{\alpha+\beta} j_\mu^-) + \bar{Z} m/|E|}\right)$

12   **else if** $mode = \textit{NCVis}$ **then**

13         $\mathcal{L} = \mathcal{L} - \log\left(\frac{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta})/Z}{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta})/Z + m}\right) - \sum_{\mu=1}^{m} \log\left(\frac{q_\theta(i_{\alpha+\beta} j_\mu^-)/Z}{q_\theta(i_{\alpha+\beta} j_\mu^-)/Z + m}\right)$

14   **else if** $mode = \textit{InfoNC-t-SNE}$ **then**

15         $\mathcal{L} = \mathcal{L} - \log\left(\frac{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta})}{q_\theta(i_{\alpha+\beta} j_{\alpha+\beta}) + \sum_{\mu=1}^{m} q_\theta(i_{\alpha+\beta} j_\mu^-)}\right)$

16   **else if** $mode = \textit{UMAP}$ **then**

17         $\mathcal{L} = \mathcal{L} - \log\left(q_\theta(i_{\alpha+\beta} j_{\alpha+\beta})\right) - \sum_{\mu=1}^{m} \log\left(q_\theta(i_{\alpha+\beta} j_\mu^-)\right)$

       `// Update parameters with SGD (non-param.)  or Adam (param.)`

18       $\theta = \theta - \eta_t \cdot \nabla_\theta \mathcal{L}$

19   **if** $mode = \textit{NCVis}$ **then**

20         $Z = Z - \eta_t \nabla_Z \mathcal{L}$

21       $\alpha = \alpha + b$

22   Shuffle E

23   **return** θ

H ADDITIONAL FIGURES

Figure S3: Attractive and repulsive loss terms of UMAP and Neg-t-SNE. The main difference is that UMAP's repulsive loss diverges at zero challenging its numerical optimization. The attractive terms are $\log(1 + d_{ij}^2)$ and $\log(2 + d_{ij}^2)$ for UMAP and Neg-t-SNE, respectively, and the repulsive ones are $\log\left((1 + d_{ij}^2)/d_{ij}^2\right)$ and $\log\left((2 + d_{ij}^2)/(1 + d_{ij}^2)\right)$, respectively.

(a) $m = 5$ (b) $m = 50$ (c) $m = 500$ (d) $m = 2b - 2 = 2046$

Figure S4: Neg-t-SNE embeddings of the MNIST dataset for varying number of noise samples m and using batch size $b = 1024$. While for NCVis and InfoNC-t-SNE more noise samples improve the approximation to t-SNE, see Figs. S14 and S15, changing m in Neg-t-SNE moves the result along the attraction-repulsion spectrum (Fig. 1) with more repulsion for larger m. However, the computational complexity of Neg-t-SNE scales with m, so that moving along the spectrum via changing $\bar{Z}$ is much more efficient. For the first 250 epochs, m was set to 5, to achieve an effect similar to early exaggeration (Supp. G).

(a) InfoNC-t-SNE loss (b) NCVis loss (c) NCVis normalization

Figure S5: **(a, b)** Loss curves for the parametric and non-parametric InfoNC-t-SNE and NCVis optimizations leading to Figs. 3b, c, e, and f. While the embedding scale differs drastically between the non-parametric and the parametric run, the loss values are close. **(c)** Normalization of the model $\sum_{ij} \phi(ij)/Z$ for the parametric and non-parametric NCVis optimizations. The difference in the embedding scale is compensated by a three orders of magnitude change in Z, so that both versions learn approximately normalized models. These experiments used our NCVis reimplementation.

(a) (b)

Figure S6: NCVis learns to have the same partition function (PF) as t-SNE on the MNIST dataset. The higher the number m of noise samples or the longer the optimization, the better the match. Both methods used early exaggeration, which for NCVis meant to start with $m = 5$ noise samples for the first 250 epochs. The learnt normalization parameter Z converged to but did not exactly equal NCVis' partition function $\sum_{ij} q_\theta(ij)$, but was of the same order of magnitude. Again, the match was better for more noise samples. Since we reinitialized the learnable Z for NCVis after the early exaggeration phase, there were brief jumps in the partition function and in Z at the beginning of the non-exaggerated phase.

Figure S7: **(a–e)** Neg-t-SNE embeddings of the MNIST dataset for various values of the fixed normalization constant $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases, clusters become more compact and separated before eventually starting to merge. The Neg-t-SNE spectrum produces embeddings very similar to those of **(f)** t-SNE, **(g)** NCVis, and **(h)** UMAP, when $\bar{Z}$ equals the partition function of t-SNE, the learned normalization parameter Z of NCVis, or $|X|/m = \binom{n}{2}/m$ used by UMAP, as predicted in Sec. 4–6. **(i)** The partition function $\sum_{ij}(1 + d_{ij}^2)^{-1}$ tries to match $\bar{Z}$ and grows with it. In contrast to Fig. 1, we did not use early exaggeration here, but initialized the Neg-t-SNE and t-SNE with PCA rescaled so that the first dimension has standard deviation 1 and 0.0001, respectively. This makes the embeddings with small $\bar{Z}$ values show cluster fragmentation, similar to the t-SNE embedding in **(f)** without early exaggeration. For very low $\bar{Z}$, the Neg-t-SNE embedding in **(a)** shows very little structure.

Figure S8: **(a–e)** Neg-t-SNE embeddings of an imbalanced version of the MNIST dataset for various values of the fixed normalization constant $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases, clusters become more compact and separated before eventually starting to merge. The Neg-t-SNE spectrum produces embeddings very similar to those of **(f)** t-SNE, **(g)** NCVis, and **(h)** UMAP, when $\bar{Z}$ equals the partition function of t-SNE, the learned normalization parameter Z of NCVis, or $|X|/m = \binom{n}{2}/m$ used by UMAP, as predicted in Sec. 4–6. **(i)** The partition function $\sum_{ij}(1 + d_{ij}^2)^{-1}$ tries to match $\bar{Z}$ and grows with it. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ and only switched to the desired $\bar{Z}$ for the last two thirds of the optimization. The dataset was created by randomly removing $10 \cdot c\%$ of the class of digit c, so that the class sizes linearly decrease from digit 0 to digit 9.

Figure S9: **(a – e)** Neg-t-SNE spectrum on the developmental single-cell RNA sequencing dataset from (Kanton et al., 2019) for various parameters $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases and the continuous structure (corresponding to the developmental stage) becomes more apparent, making higher $\bar{Z}$ more suitable for visualizing continuous datasets (Böhm et al., 2022). The spectrum produces embeddings very similar to those of **(f)** t-SNE and **(g)** NCVis when $\bar{Z}$ equals the partition function of t-SNE or the learned normalization parameter of NCVis. The UMAP embedding in **(h)** closely resembles the Neg-t-SNE embedding at $\bar{Z} = |X|/m = \binom{n}{2}/m$. **(i)** The partition function $\sum_{ij}(1 + d_{ij}^2)^{-1}$ of the Neg-t-SNE embeddings increased with $\bar{Z}$. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ and only switched to the desired $\bar{Z}$ for the last two thirds of the optimization. The dataset contains 20 272 cells and is colored by the duration of the development. There are ten times fewer cells collected after 10 days than after one month.

Figure S10: **(a – e)** Neg-t-SNE spectrum on the single-cell RNA sequencing dataset of a developing zebrafish embryo (Wagner et al., 2018) for various parameters $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases and the continuous structure (corresponding to the developmental stage) becomes more apparent, making higher $\bar{Z}$ more suitable for visualizing continuous datasets (Böhm et al., 2022). The spectrum produces embeddings very similar to those of **(f)** t-SNE and **(g)** NCVis when $\bar{Z}$ equals the partition function of t-SNE or the learned normalization parameter of NCVis. The UMAP embedding in **(h)** closely resembles the Neg-t-SNE embedding at $\bar{Z} = |X|/m = \binom{n}{2}/m$. **(i)** The partition function $\sum_{ij}(1 + d_{ij}^2)^{-1}$ of the Neg-t-SNE embeddings increased with $\bar{Z}$. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ and only switched to the desired $\bar{Z}$ for the last two thirds of the optimization. The dataset contains $63\,530$ cells and is colored by the hours post fertilization (hpf). There are ten times fewer cells collected after 8 hours than after 24.

Figure S11: **(a – e)** Neg-t-SNE spectrum of the single-cell RNA sequencing dataset of the C. elegans flatworm (Packer et al., 2019; Narayan et al., 2021) for various values of the fixed normalization constant $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases, the scale of the embedding decreases, and more continuous structure becomes apparent. The Neg-t-SNE spectrum produces embeddings very similar to those of **(f)** t-SNE, **(g)** NCVis, and **(h)** UMAP, when $\bar{Z}$ equals the partition function of t-SNE, the learned normalization parameter Z of NCVis, or $|X|/m = \binom{n}{2}/m$ used by UMAP, as predicted in Sec. 4–6. **(i)** The partition function $\sum_{ij}(1 + d_{ij}^2)^{-1}$ tries to match $\bar{Z}$ and grows with it. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ and only switched to the desired $\bar{Z}$ for the last two thirds of the optimization. The dataset contains information on $86\,024$ cells of 37 types indicated by the colors. It is imbalanced with only 25 cells of the least abundant type but $31\,375$ cells of unknown type (grey).

(f) t-SNE   (g) NCVis   (h) UMAP   (i) Partition function

Figure S12: **(a – e)** Neg-t-SNE embeddings of the Kuzushiji-49 dataset (Tarin et al., 2018) for various values of the fixed normalization constant $\bar{Z}$. As $\bar{Z}$ increases, the scale of the embedding decreases, clusters become more compact and separated before eventually starting to merge. The Neg-t-SNE spectrum produces embeddings similar to those of **(f)** t-SNE, **(g)** NCVis, and **(h)** UMAP, when $\bar{Z}$ equals the partition function of t-SNE, the learned normalization parameter Z of NCVis, or $|X|/m = \binom{n}{2}/m$ used by UMAP, as predicted in Sec. 4–6. **(i)** The partition function $\sum_{ij}(1+d_{ij}^2)^{-1}$ tries to match $\bar{Z}$ and grows with it. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ and only switched to the desired $\bar{Z}$ for the last two thirds of the optimization. The dataset contains 270 912 images of 49 different Japanese characters. The classes are imbalanced with 456 to 7 000 samples per class. We see that a higher level of repulsion than UMAP's $\bar{Z} = |X|/m$ helps to visualize the discrete structure of the dataset. The sampling based Neg-t-SNE embedding at $\bar{Z} = Z^{t\text{-SNE}}$ has less structure than the t-SNE embedding. Fig.S13 and Tab. S3 show that the Neg-t-SNE result improves for longer optimization.

(a) 500 epochs   (b) 1000 epochs   (c) 5000 epochs   (d) 10000 epochs

Figure S13: Neg-t-SNE embeddings of the Kuzushiji-49 dataset (Tarin et al., 2018) for $\bar{Z} = Z^{t\text{-SNE}}$ show more structure when optimized longer. Similar to early exaggeration in t-SNE we started all Neg-t-SNE runs using $\bar{Z} = |X|/m$ for 250 epochs and only switched to the desired $\bar{Z}$ for the remaining number of epochs indicated in the subcaptions.

Table S3: Longer run times improve the Neg-t-SNE optimization on the Kuzushiji-49 dataset (Tarin et al., 2018) for $\bar{Z} = Z^{t\text{-SNE}}$. The KL divergence is computed with respect to the normalized model $q_\theta/(\sum_{ij} q_\theta(ij))$.

Epochs	500	1000	5000	10000
Partition function [10^6]	18.96 ± 0.02	13.27 ± 0.01	6.93 ± 0.01	5.75 ± 0.01
Neg-t-SNE loss	1021 ± 2	832 ± 2	630 ± 1	599 ± 1
KL divergence	5.52 ± 0.01	5.18 ± 0.01	4.76 ± 0.01	4.65 ± 0.00

Figure S14: NCVis (our implementation) on the MNIST dataset for varying number of noise samples m and different starting conditions. Higher number of noise samples m improves the approximation quality to t-SNE (last column). The first row is initialized with isotropic Gaussian noise and the second and the third rows with PCA (both normalized to have standard deviation of one or 0.0001 in the first dimension for NCVis or t-SNE, respectively). In the third row, the first 250 epochs used $m = 5$ and the latter used the given m value for NCVis. This is similar to t-SNE's early exaggeration that we used in panel l. NCVis seems to be less dependent on early exaggeration than t-SNE, especially for low m values.

(a) $m = 5$
random init

(b) $m = 50$
random init

(c) $m = 500$
random init

(d) t-SNE
random init

(e) $m = 5$
PCA init

(f) $m = 50$
PCA init

(g) $m = 500$
PCA init

(h) t-SNE
PCA init

(i) $m = 5$
EE

(j) $m = 50$
EE

(k) $m = 500$
EE

(l) t-SNE
EE

Figure S15: InfoNC-t-SNE on the MNIST dataset for varying number of noise samples m and different starting conditions. Higher number of noise samples m improves the approximation quality to t-SNE (last column). The first row is initialized with isotropic Gaussian noise and the second and the third rows with PCA (both normalized to have standard deviation of one or 0.0001 in the first dimension for InfoNC-t-SNE or t-SNE, respectively). In the third row, the first 250 epochs used $m = 5$ and the latter used the given m value for InfoNC-t-SNE. This is similar to t-SNE's early exaggeration that we used in panel l. InfoNC-t-SNE seems to be less dependent on early exaggeration than t-SNE, especially for low m values.