SCALABLE SAMPLING FOR NONSYMMETRIC DETERMINANTAL POINT PROCESSES

ABSTRACT

A determinantal point process (DPP) on a collection of M items is a model, parameterized by a symmetric kernel matrix, that assigns a probability to every subset of those items. Recent work shows that removing the kernel symmetry constraint, yielding nonsymmetric DPPs (NDPPs), can lead to significant predictive performance gains for machine learning applications. However, existing work leaves open the question of scalable NDPP sampling. There is only one known DPP sampling algorithm, based on Cholesky decomposition, that can directly apply to NDPPs as well. Unfortunately, its runtime is cubic in M, and thus does not scale to large item collections. In this work, we first note that this algorithm can be transformed into a linear-time one for kernels with low-rank structure. Furthermore, we develop a scalable sublinear-time rejection sampling algorithm by constructing a novel proposal distribution. Additionally, we show that imposing certain structural constraints on the NDPP kernel enables us to bound the rejection rate in a way that depends only on the kernel rank. In our experiments we compare the speed of all of these samplers for a variety of real-world tasks.

1 INTRODUCTION

A determinantal point process (DPP) on M items is a model, parameterized by a symmetric kernel matrix, that assigns a probability to every subset of those items. DPPs have been applied to a wide range of machine learning tasks, including stochastic gradient descent (SGD) (Zhang et al., 2017), reinforcement learning (Osogami & Raymond, 2019; Yang et al., 2020), text summarization (Dupuy & Bach, 2018), coresets (Tremblay et al., 2019), and more. However, a symmetric kernel can only capture negative correlations between items. Recent works (Brunel, 2018; Gartrell et al., 2019) have shown that using a nonsymmetric DPP (NDPP) allows modeling of positive correlations as well, which can lead to significant predictive performance gains. Gartrell et al. (2021) provides scalable NDPP kernel learning and MAP inference algorithms, but leaves open the question of scalable sampling. The only known sampling algorithm for NDPPs is the Cholesky-based approach described in Poulson (2019), which has a runtime of $O(M^3)$ and thus does not scale to large item collections.

There is a rich body of work on efficient sampling algorithms for (symmetric) DPPs, including recent works such as Derezinski et al. (2019); Poulson (2019); Calandriello et al. (2020). Key distinctions between existing sampling algorithms include whether they are for exact or approximate sampling, whether they assume the DPP kernel has some low-rank $K \ll M$, and whether they sample from the space of all 2^M subsets or from the restricted space of size-k subsets, so-called k-DPPs. In this work we focus on exact sampling for low-rank kernels, and provide scalable algorithms for NDPPs. Our contributions are as follows, with runtime and memory details summarized in Table 1:

- Linear-time sampling (Section 3): We show how to transform the $O(M^3)$ Cholesky-decomposition-based sampler from Poulson (2019) into an $O(MK^2)$ sampler for rank-K kernels.

- Sublinear-time sampling (Section 4): Using rejection sampling, we show how to leverage existing sublinear-time samplers for symmetric DPPs to implement a sublinear-time sampler for a subclass of NDPPs that we call orthogonal NDPPs (ONDPPs).

- Learning with orthogonality constraints (Section 5): We show that the scalable NDPP kernel learning of Gartrell et al. (2021) can be slightly modified to impose an orthogonality constraint, yielding the ONDPP subclass. The constraint allows us to control the rejection sampling algorithm's

Table 1: Runtime and memory complexities for sampling algorithms developed in this work. M is the size of the entire item set (ground set), and K is the rank of the kernel (often $K \ll M$ in practice). We use k to represent the size of the sampled set (often $k \ll K$ in practice). $\omega \in [0, 1]$ is a data-dependent constant (with our specific learning scheme, $\omega \ll 1$). The sublinear-time rejection algorithm includes a one-time preprocessing step, after which each successive sample only requires "sampling time".

Sampling algorithm	Preprocessing time	Sampling time	Memory
Linear-time Cholesky-based	–	$O(MK^2)$	$O(MK)$
Sublinear-time rejection	$O(MK^2)$	$O((k^3 \log M + k^4 + K)(1 + \omega)^K)$ *	$O(MK^2)$

* This assumes some orthogonality constraint on the kernel.

rejection rate, ensuring its scalability. Experiments suggest that the predictive performance of the kernels is not degraded by this change.

For a common large-scale setting where M is 1 million, our sublinear-time sampler results in runtime that is hundreds of times faster than the linear-time sampler. In the same setting, our linear-time sampler provides runtime that is millions of times faster than the only previously known NDPP sampling algorithm, which has cubic time complexity and is thus impractical in this scenario.

2 BACKGROUND

Notation. We use $[M] := \{1, \ldots, M\}$ to denote the set of items 1 through M. We use $\boldsymbol{I}_K$ to denote the K-by-K identity matrix, and often write $\boldsymbol{I} := \boldsymbol{I}_M$ when the dimensionality should be clear from context. Given $\boldsymbol{L} \in \mathbb{R}^{M \times M}$, we use $\boldsymbol{L}_{i,j}$ to denote the entry in the i-th row and j-th column, and $\boldsymbol{L}_{A,B} \in \mathbb{R}^{|A| \times |B|}$ for the submatrix formed by taking rows A and columns B. We also slightly abuse notation to denote principal submatrices with a single subscript, $\boldsymbol{L}_A := \boldsymbol{L}_{A,A}$.

Kernels. As discussed earlier, both (symmetric) DPPs and NDPPs define a probability distribution over all 2^M subsets of a ground set $[M]$. The distribution is parameterized by a kernel matrix $\boldsymbol{L} \in \mathbb{R}^{M \times M}$ and the probability of a subset $Y \subseteq [M]$ is defined to be $\Pr(Y) \propto \det(\boldsymbol{L}_Y)$. For this to define a valid distribution, it must be the case that $\det(\boldsymbol{L}_Y) \geq 0$ for all Y. For symmetric DPPs, the non-negativity requirement is identical to a requirement that $\boldsymbol{L}$ be positive semi-definite (PSD). For nonsymmetric DPPs, there is no such simple correspondence, but prior work such as Gartrell et al. (2019; 2021) has focused on PSD matrices for simplicity.

Normalizing and marginalizing. The normalizer of a DPP or NDPP distribution can also be written as a single determinant: $\sum_{Y \subseteq [M]} \det(\boldsymbol{L}_Y) = \det(\boldsymbol{L} + \boldsymbol{I})$ (Kulesza & Taskar, 2012, Theorem 2.1). Additionally, the marginal probability of a subset can be written as a determinant: $\Pr(A \subseteq Y) = \det(\boldsymbol{K}_A)$, for $\boldsymbol{K} := \boldsymbol{I} - (\boldsymbol{L} + \boldsymbol{I})^{-1}$ (Kulesza & Taskar, 2012, Theorem 2.2)*, where $\boldsymbol{K}$ is typically called the marginal kernel.

Intuition. The diagonal element $\boldsymbol{K}_{i,i}$ is the probability that item i is included in a set sampled from the model. The 2-by-2 determinant $\det(\boldsymbol{K}_{\{i,j\}}) = \boldsymbol{K}_{i,i}\boldsymbol{K}_{j,j} - \boldsymbol{K}_{i,j}\boldsymbol{K}_{j,j}$ is the probability that both i and j are included in the sample. A symmetric DPP has a symmetric marginal kernel, meaning $\boldsymbol{K}_{i,j} = \boldsymbol{K}_{j,i}$, and hence $\boldsymbol{K}_{i,i}\boldsymbol{K}_{j,j} - \boldsymbol{K}_{i,j}\boldsymbol{K}_{j,i} \leq \boldsymbol{K}_{i,i}\boldsymbol{K}_{j,j}$. This implies that the probability of including both i and j in the sampled set cannot be greater than the product of their individual inclusion probabilities. Hence, symmetric DPPs can only encode negative correlations. In contrast, NDPPs can have $\boldsymbol{K}_{i,j}$ and $\boldsymbol{K}_{j,i}$ with differing signs, allowing them to also capture positive correlations.

2.1 RELATED WORK

Learning. Gartrell et al. (2021) proposes a low-rank kernel decomposition for NDPPs that admits linear-time learning. The decomposition takes the form $\boldsymbol{L} := \boldsymbol{V}\boldsymbol{V}^\top + \boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$ for $\boldsymbol{V}, \boldsymbol{B} \in \mathbb{R}^{M \times K}$, and $\boldsymbol{D} \in \mathbb{R}^{K \times K}$. The $\boldsymbol{V}\boldsymbol{V}^\top$ component is a rank-K symmetric matrix, which can model negative correlations between items. The $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$ component is a rank-K skew-

---

*The proofs in Kulesza & Taskar (2012) typically assume a symmetric kernel, but this particular one does not rely on the symmetry.

Algorithm 1 Cholesky-based NDPP sampling (Poulson, 2019, Algorithm 1)

1: **procedure** SAMPLECHOLESKY($\boldsymbol{K}$)   ▷ marginal kernel factorization $\boldsymbol{Z}, \boldsymbol{W}$
2:    $Y \leftarrow \emptyset$ $\boldsymbol{Q} \leftarrow \boldsymbol{W}$
3:    **for** $i = 1$ **to** M **do**
4:       $p_i \leftarrow \boldsymbol{K}_{i,i}$ $p_i \leftarrow \boldsymbol{z}_i^\top \boldsymbol{Q} \boldsymbol{z}_i$
5:       $u \leftarrow \text{uniform}(0, 1)$
6:       **if** $u \leq p_i$ **then** $Y \leftarrow Y \cup \{i\}$
7:       **else** $p_i \leftarrow p_i - 1$
8:       $\boldsymbol{K}_A \leftarrow \boldsymbol{K}_A - \frac{\boldsymbol{K}_{A,i} \boldsymbol{K}_{i,A}}{p_i}$ for $A := \{i+1, \dots, M\}$ $\boldsymbol{Q} \leftarrow \boldsymbol{Q} - \frac{\boldsymbol{Q} \boldsymbol{z}_i \boldsymbol{z}_i^\top \boldsymbol{Q}}{p_i}$
9:    **return** Y

---

symmetric matrix, which can model positive correlations between items. For compactness of notation, we will write $\boldsymbol{L} = \boldsymbol{Z} \boldsymbol{X} \boldsymbol{Z}^\top$, where $\boldsymbol{Z} = \begin{bmatrix} \boldsymbol{V} & \boldsymbol{B} \end{bmatrix} \in \mathbb{R}^{M \times 2K}$, and $\boldsymbol{X} = \begin{bmatrix} \boldsymbol{I}_K & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{D} - \boldsymbol{D}^\top \end{bmatrix} \in \mathbb{R}^{2K \times 2K}$. The marginal kernel in this case also has a rank-$2K$ decomposition, as can be shown via application of the Woodbury matrix identity:

$$\boldsymbol{K} := \boldsymbol{I} - (\boldsymbol{I} + \boldsymbol{L})^{-1} = \boldsymbol{Z} \boldsymbol{X} \left(\boldsymbol{I}_{2K} + \boldsymbol{Z}^\top \boldsymbol{Z} \boldsymbol{X} \right)^{-1} \boldsymbol{Z}^\top. \tag{1}$$

Note that the matrix to be inverted can be computed from $\boldsymbol{Z}$ and $\boldsymbol{X}$ in $O(MK^2)$ time, and the inverse itself takes $O(K^3)$ time. Thus, $\boldsymbol{K}$ can be computed from $\boldsymbol{L}$ in time $O(MK^2)$. We will develop sampling algorithms for this decomposition, as well as an orthogonality-constrained version of it. We use $\boldsymbol{W} := \boldsymbol{X} \left(\boldsymbol{I}_{2K} + \boldsymbol{Z}^\top \boldsymbol{Z} \boldsymbol{X} \right)^{-1}$ in what follows so that we can compactly write $\boldsymbol{K} = \boldsymbol{Z} \boldsymbol{W} \boldsymbol{Z}^\top$.

Sampling. While there are a number of exact sampling algorithms for DPPs with symmetric kernels, the only published algorithm that clearly can directly apply to NDPPs is from Poulson (2019) (see Theorem 2 therein). This algorithm begins with an empty set $Y = \emptyset$ and iterates through the M items, deciding for each whether or not to include it in Y based on all of the previous inclusion/exclusion decisions. Poulson (2019) shows, via the Cholesky decomposition, that the necessary conditional probabilities can be computed as follows:

$$\Pr \left(\{i\} \subseteq Y \mid \{j\} \subseteq Y \right) = \boldsymbol{K}_{i,i} - \left(\boldsymbol{K}_{i,j} \boldsymbol{K}_{j,i} \right) / \boldsymbol{K}_{j,j}, \tag{2}$$

$$\Pr \left(\{i\} \subseteq Y \mid \{j\} \not\subseteq Y \right) = \boldsymbol{K}_{i,i} - \left(\boldsymbol{K}_{i,j} \boldsymbol{K}_{j,i} \right) / \left(\boldsymbol{K}_{j,j} - 1 \right). \tag{3}$$

Algorithm 1 (left-hand side) gives pseudocode for this Cholesky-based sampling.

There has also been some recent work on *approximate* sampling for fixed-size k-NDPPs: Alimohammadi et al. (2021) provide a Markov chain Monte Carlo (MCMC) algorithm and prove that the overall runtime to approximate ε-close total variation distance is bounded by $O(M^2 k^3 \log(1/(\varepsilon \Pr(Y_0))))$, where $\Pr(Y_0)$ is probability of an initial state Y_0. Improving this runtime is an interesting avenue for future work, but for this paper we focus on exact sampling.

3 LINEAR-TIME CHOLESKY-BASED SAMPLING

In this section, we show that the $O(M^3)$ runtime of the Cholesky-based sampler from Poulson (2019) can be significantly improved when using the low-rank kernel decomposition of Gartrell et al. (2021). First, note that Line 8 of Algorithm 1, where all marginal probabilities are updated via an $(M - i)$-by-$(M - i)$ matrix subtraction, is the most costly part of the algorithm, making overall time and memory complexity $O(M^3)$ and $O(M^2)$, respectively. However, when the DPP kernel is given by a low-rank decomposition, we observe that marginal probabilities can be updated by matrix-vector multiplications of dimension $2K$, regardless of M. In more detail, suppose we have the marginal kernel $\boldsymbol{K} = \boldsymbol{Z} \boldsymbol{W} \boldsymbol{Z}^\top$ as in Eq. (1). Then, for $i \neq j$:

$$\Pr \left(\{j\} \subseteq Y \mid \{i\} \subseteq Y \right) = \boldsymbol{K}_{j,j} - \boldsymbol{K}_{j,i} \boldsymbol{K}_{i,i}^{-1} \boldsymbol{K}_{i,j} = \boldsymbol{z}_j^\top \left(\boldsymbol{W} - \frac{(\boldsymbol{W} \boldsymbol{z}_i)(\boldsymbol{z}_i^\top \boldsymbol{W})}{\boldsymbol{z}_i^\top \boldsymbol{W} \boldsymbol{z}_i} \right) \boldsymbol{z}_j, \tag{4}$$

$$\Pr \left(\{j\} \subseteq Y \mid \{i\} \not\subseteq Y \right) = \boldsymbol{z}_j^\top \left(\boldsymbol{W} - \frac{(\boldsymbol{W} \boldsymbol{z}_i)(\boldsymbol{z}_i^\top \boldsymbol{W})}{\boldsymbol{z}_i^\top \boldsymbol{W} \boldsymbol{z}_i - 1} \right) \boldsymbol{z}_j. \tag{5}$$

The conditional probabilities in Eqs. (4) and (5) are of bilinear form, and the z_j do not change during sampling. Hence, it is enough to update the $2K$-by-$2K$ inner matrix at each iteration, and obtain the marginal probability by multiplying this matrix by z_i. The details are shown on the right-hand side of Algorithm 1. The overall time and memory complexity are $O(MK^2)$ and $O(MK)$, respectively.

4 SUBLINEAR-TIME REJECTION SAMPLING

Although the Cholesky-based sampler runs in time linear in M, even this is too expensive for the large M that are often encountered in real-world datasets. To improve runtime, we consider *rejection sampling* (Von Neumann, 1963). Let p be the target distribution that we aim to sample, and let q be any distribution whose support corresponds to that of p; we call q the proposal distribution. Assume that there is a universal constant U such that $p(x) \leq Uq(x)$ for all x. In this setting, rejection sampling draws a sample x from q and accepts it with probability $p(x)/(Uq(x))$, repeating until an acceptance occurs. The distribution of the resulting samples is p. It is important to choose a good proposal distribution q so that sampling is efficient and the number of rejections is small.

Algorithm 2 Rejection NDPP sampling   (Tree-based sampling)

1: **procedure** PREPROCESS(V, B, D)

2:      $\{(\sigma_j, y_{2j-1}, y_{2j})\}_{j=1}^{K/2} \leftarrow$ YOULADECOMPOSE(B, D)[†]

3:      $\widehat{X} \leftarrow \mathrm{diag}(I_K, \sigma_1, \sigma_1, \ldots, \sigma_{K/2}, \sigma_{K/2})$

4:      $Z \leftarrow [V, y_1, \ldots, y_K]$ $\{(\lambda_i, z_i)\}_{i=1}^{2K} \leftarrow$ EIGENDECOMPOSE($Z \widehat{X}^{1/2}$)

                                               $\mathcal{T} \leftarrow$ CONSTRUCTTREE($M, [z_1, \ldots, z_{2K}]^\top$)

5:      **return** $Z, \widehat{X}$ **return** $\mathcal{T}, \{(\lambda_i, z_i)\}_{i=1}^{2K}$

6: **procedure** SAMPLEREJECT($V, B, D, Z, \hat{X}$) $\triangleright$ tree $\mathcal{T}$, eigen pair $\{(\lambda_i, z_i)\}_{i=1}^{2K}$ of $Z\widehat{X}Z$

7:      **while** true **do**

8:          $Y \leftarrow$ SAMPLEDPP($Z \widehat{X} Z^\top$) $Y \leftarrow$ SAMPLEDPP($\mathcal{T}, \{(\lambda_i, z_i)\}_{i=1}^{2K}$)

9:          $u \leftarrow \mathrm{uniform}(0, 1)$

10:         $p \leftarrow \frac{\det([VV^\top + B(D - D^\top)B^\top]_Y)}{\det([Z\widehat{X}Z^\top]_Y)}$

11:         **if** $u \leq p$ **then break**

12:      **return** Y

4.1 PROPOSAL DPP CONSTRUCTION

Our first goal is to find a proposal DPP with symmetric kernel $\widehat{L}$ that can upper bound all probabilities of samples from the NDPP with kernel L within a constant factor. To this end, we expand the determinant of a principal submatrix, $\det(L_Y)$, using the spectral decomposition of the NDPP kernel. Such a decomposition essentially amounts to combining the eigendecomposition of the symmetric part of L with the Youla decomposition (Youla, 1961) of the skew-symmetric part.

Specifically, suppose $\{(\rho_i, v_i)\}_{i=1}^K$ is the eigendecomposition of $VV^\top$ and $\{(\sigma_j, y_{2j-1}, y_{2j})\}_{j=1}^{K/2}$ is the Youla decomposition of $B(D - D^\top)B^\top$ (see Appendix D for more details). That is,

$$B(D - D^\top)B^\top = \sum_{j=1}^{K/2} \sigma_j \left(y_{2j-1} y_{2j}^\top - y_{2j} y_{2j-1}^\top \right). \qquad (6)$$

Then we can simply write $L = ZXZ^\top$, for $Z := [v_1, \ldots, v_K, y_1, \ldots, y_K] \in \mathbb{R}^{M \times 2K}$, and

$$X := \mathrm{diag}\left(\rho_1, \ldots, \rho_K, \begin{bmatrix} 0 & \sigma_1 \\ -\sigma_1 & 0 \end{bmatrix}, \ldots, \begin{bmatrix} 0 & \sigma_{K/2} \\ -\sigma_{K/2} & 0 \end{bmatrix}\right). \qquad (7)$$

Now, consider defining a related but *symmetric* PSD kernel $\widehat{L} := Z\widehat{X}Z^\top$ with $\widehat{X} := \mathrm{diag}\left(\rho_1, \ldots, \rho_K, \sigma_1, \sigma_1, \ldots, \sigma_{K/2}, \sigma_{K/2}\right)$. All determinants of the principal submatrices of $\widehat{L} = Z\widehat{X}Z^\top$ upper bound those of L, as stated below.

[†]Pseudo-code of YOULADECOMPOSE is provided in Algorithm 4. See Appendix D.

Theorem 1. *For every subset $Y \subseteq [M]$, it holds that $\det(\boldsymbol{L}_Y) \leq \det(\widehat{\boldsymbol{L}}_Y)$. Moreover, equality holds when the size of Y is equal to the rank of $\boldsymbol{L}$.*

Proof sketch: From the Cauchy-Binet formula, the determinants of $\boldsymbol{L}_Y$ and $\widehat{\boldsymbol{L}}_Y$ for all $Y \subseteq [M], |Y| \leq 2K$ can be represented as

$$\det(\boldsymbol{L}_Y) = \sum_{I \subseteq [K], |I| = |Y|} \sum_{J \subseteq [K], |J| = |Y|} \det(\boldsymbol{X}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J}), \tag{8}$$

$$\det(\widehat{\boldsymbol{L}}_Y) = \sum_{I \subseteq [2K], |I| = |Y|} \det(\widehat{\boldsymbol{X}}_I) \det(\boldsymbol{Z}_{Y,I})^2. \tag{9}$$

Many of the terms in Eq. (8) are actually zero due to the block-diagonal structure of $\boldsymbol{X}$. For example, note that if $1 \in I$ but $1 \notin J$, then there is an all-zeros row in $\boldsymbol{X}_{I,J}$, making $\det(\boldsymbol{X}_{I,J}) = 0$. We show that each $\boldsymbol{X}_{I,J}$ with nonzero determinant is a block-diagonal matrix with diagonal entries among $\rho_i, \pm\sigma_j$, or $\begin{bmatrix} 0 & \sigma_j \\ -\sigma_j & 0 \end{bmatrix}$. With this observation, we can prove that $\det(\boldsymbol{X}_{I,J})$ is upper-bounded by $\det(\widehat{\boldsymbol{X}}_I)$ or $\det(\widehat{\boldsymbol{X}}_J)$. Then, through application of the rearrangement inequality, we can upper-bound the sum of the $\det(\boldsymbol{X}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J})$ in Eq. (8) with a sum over $\det(\widehat{\boldsymbol{X}}_I) \det(\boldsymbol{Z}_{Y,I})^2$. Finally, we show that the number of non-zero terms in Eq. (8) is identical to the number of non-zero terms in Eq. (9). Combining these gives us the desired inequality $\det(\boldsymbol{L}_Y) \leq \det(\widehat{\boldsymbol{L}}_Y)$. The full proof of Theorem 1 is in Appendix E.1.

Now, recall that the normalizer of a DPP (or NDPP) with kernel $\boldsymbol{L}$ is $\det(\boldsymbol{L} + \boldsymbol{I})$. The ratio of probability of the NDPP with kernel $\boldsymbol{L}$ to that of a DPP with kernel $\widehat{\boldsymbol{L}}$ is thus:

$$\frac{\text{Pr}_{\boldsymbol{L}}(Y)}{\text{Pr}_{\widehat{\boldsymbol{L}}}(Y)} = \frac{\det(\boldsymbol{L}_Y)/\det(\boldsymbol{L} + \boldsymbol{I})}{\det(\widehat{\boldsymbol{L}}_Y)/\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})} \leq \frac{\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})}{\det(\boldsymbol{L} + \boldsymbol{I})},$$

where the inequality follows from Theorem 1. This gives us the necessary universal constant U upper-bounding the ratio of the target distribution to the proposal distribution. Hence, given a sample Y drawn from the DPP with kernel $\widehat{\boldsymbol{L}}$, we can use acceptance probability $\text{Pr}_{\boldsymbol{L}}(Y)/(U \text{Pr}_{\widehat{\boldsymbol{L}}}(Y)) = \det(\boldsymbol{L}_Y)/\det(\widehat{\boldsymbol{L}}_Y)$. Pseudo-codes for proposal construction and rejection sampling are given in Algorithm 2. Note that to derive $\widehat{\boldsymbol{L}}$ from $\boldsymbol{L}$ it suffices to run the Youla decomposition of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$, because the difference is only in the skew-symmetric part. This decomposition can run in $O(MK^2)$ time; more details are provided in Appendix D. Since $\widehat{\boldsymbol{L}}$ is a symmetric PSD matrix, we can apply existing fast DPP sampling algorithms to sample from it. In particular, in the next section we combine a fast tree-based method with rejection sampling.

4.2 SUBLINEAR-TIME TREE-BASED SAMPLING

There are several DPP sampling algorithms that run in sublinear time, such as Gillenwater et al. (2019) and Derezinski et al. (2019). Here, we consider applying the former, a tree-based approach, to sample from the proposal distribution defined by $\widehat{\boldsymbol{L}}$. We give some details of the sampling procedure, as in the course of applying it we discovered an optimization that slightly improves on the runtime of prior work. Formally, let $\{(\lambda_i, \boldsymbol{z}_i)\}_{i=1}^{2K}$ be the eigendecomposition of $\widehat{\boldsymbol{L}}$ and define $\boldsymbol{Z} := [\boldsymbol{z}_1, \ldots, \boldsymbol{z}_{2K}] \in \mathbb{R}^{M \times 2K}$. As shown in Kulesza & Taskar (2012, Lemma 2.6) the determinant of $\widehat{\boldsymbol{L}}_Y$ for every $Y \subseteq [M]$ can be written:

$$\frac{\det(\widehat{\boldsymbol{L}}_Y)}{\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})} = \sum_{I \subseteq [2K], |E| = |Y|} \det(\boldsymbol{Z}_{Y,E} \boldsymbol{Z}_{Y,E}^\top) \prod_{i \in E} \frac{\lambda_i}{\lambda_i + 1} \prod_{i \notin E} \frac{1}{\lambda_i + 1}. \tag{10}$$

A matrix of the form $\boldsymbol{Z}_{:,E} \boldsymbol{Z}_{:,E}^\top$ has exactly $|E|$ eigenvalues with value 1 and all others have value 0. This is typically called an elementary DPP. Hence, Eq. (10) can be thought of as a way of writing DPP probabilities as a mixture of elementary DPPs. Based on this mixture view, DPP sampling can be done in two steps: (1) choose an elementary DPP according to its mixture weight, and then (2) sample a subset from the selected elementary DPP. The key idea of tree-based sampling is that step (2) can be accelerated by traversing a binary tree structure, that can be done in time logarithmic in M.

Algorithm 3 Tree-based DPP sampling (Gillenwater et al., 2019)

1: **procedure** BRANCH($A, \boldsymbol{Z}$)
2:    **if** $A = \{j\}$ **then**
3:       $\mathcal{T}.A \leftarrow \{j\}, \mathcal{T}.\boldsymbol{\Sigma} \leftarrow \boldsymbol{Z}_{j,:}^{\top} \boldsymbol{Z}_{j,:}$
4:       **return** $\mathcal{T}$
5:    $A_{\ell}, A_r \leftarrow$ Split A in half
6:    $\mathcal{T}.\texttt{left} \leftarrow$ BRANCH($A_{\ell}, \boldsymbol{Z}$)
7:    $\mathcal{T}.\texttt{right} \leftarrow$ BRANCH($A_r, \boldsymbol{Z}$)
8:    $\mathcal{T}.\boldsymbol{\Sigma} \leftarrow \mathcal{T}.\texttt{left}.\boldsymbol{\Sigma} + \mathcal{T}.\texttt{right}.\boldsymbol{\Sigma}$
9:    **return** $\mathcal{T}$

10: **procedure** CONSTRUCTTREE($M, \boldsymbol{Z}$)
11:    **return** BRANCH($[M], \boldsymbol{Z}$)

12: **procedure** SAMPLEDPP($\mathcal{T}, \boldsymbol{Z}, \{\lambda_i\}_{i=1}^{K}$)
13:    $E \leftarrow \emptyset, Y \leftarrow \emptyset, \boldsymbol{Q}^Y \leftarrow \boldsymbol{0}$
14:    **for** $i = 1, \ldots, K$ **do**
15:       $E \leftarrow E \cup \{i\}$ w.p. $\lambda_i/(\lambda_i + 1)$
16:    **for** $k = 1, \ldots, |E|$ **do**
17:       $j \leftarrow$ SAMPLEITEM($\mathcal{T}, \boldsymbol{Q}^Y, E$)
18:       $Y \leftarrow Y \cup \{j\}$
19:       $\boldsymbol{Q}^Y \leftarrow \boldsymbol{I}_{|E|} - \boldsymbol{Z}_{Y,E}^{\top} \left(\boldsymbol{Z}_{Y,E} \boldsymbol{Z}_{Y,E}^{\top} \right)^{-1} \boldsymbol{Z}_{Y,E}$
20:    **return** Y

21: **procedure** SAMPLEITEM($\mathcal{T}, \boldsymbol{Q}^Y, E$)
22:    **if** $\mathcal{T}$ is a leaf **then return** $\mathcal{T}.A$
23:    $p_{\ell} \leftarrow \left\langle \mathcal{T}.\texttt{left}.\boldsymbol{\Sigma}_E, \boldsymbol{Q}^Y \right\rangle$
24:    $p_r \leftarrow \left\langle \mathcal{T}.\texttt{right}.\boldsymbol{\Sigma}_E, \boldsymbol{Q}^Y \right\rangle$
25:    $u \leftarrow$ uniform$(0, 1)$
26:    **if** $u \leq \frac{p_{\ell}}{p_{\ell} + p_r}$ **then**
27:       **return** SAMPLEITEM($\mathcal{T}.\texttt{left}, \boldsymbol{Q}^Y, E$)
28:    **else**
29:       **return** SAMPLEITEM($\mathcal{T}.\texttt{right}, \boldsymbol{Q}^Y, E$)

More specifically, given marginal kernel $\boldsymbol{K} = \boldsymbol{Z}_{:,E} \boldsymbol{Z}_{:,E}^{\top}$, where E is obtained from step (1), we start from the empty set $Y = \emptyset$ and repeatedly add an item j to Y with probability:

$$\Pr(j \in S \mid Y \subseteq S) = \boldsymbol{K}_{j,j} - \boldsymbol{K}_{j,Y}(\boldsymbol{K}_Y)^{-1}\boldsymbol{K}_{Y,j} = \boldsymbol{Z}_{j,E}\boldsymbol{Q}^Y\boldsymbol{Z}_{j,E}^{\top} = \left\langle \boldsymbol{Q}^Y, (\boldsymbol{Z}_{j,:}^{\top}\boldsymbol{Z}_{j,:})_E \right\rangle, \quad (11)$$

where S is some final selected subset, and $\boldsymbol{Q}^Y := \boldsymbol{I}_{|E|} - \boldsymbol{Z}_{Y,E}^{\top} \left(\boldsymbol{Z}_{Y,E} \boldsymbol{Z}_{Y,E}^{\top} \right)^{-1} \boldsymbol{Z}_{Y,E}$. Suppose that a node in the tree contains a subset $A = A_{\ell} \cup A_r$, such that $A_{\ell} \cap A_r = \emptyset$ and stores $\sum_{j \in A} \boldsymbol{Z}_{j,:}^{\top}\boldsymbol{Z}_{j,:}$. Then, one can sample a single item by recursively moving down to the left node with probability:

$$p_{\ell} = \frac{\left\langle \boldsymbol{Q}^Y, \sum_{j \in A_{\ell}} (\boldsymbol{Z}_{j,:}^{\top}\boldsymbol{Z}_{j,:})_E \right\rangle}{\left\langle \boldsymbol{Q}^Y, \sum_{j \in A} (\boldsymbol{Z}_{j,:}\boldsymbol{Z}_{j,:}^{\top})_E \right\rangle}, \quad (12)$$

or to the right node with probability $1 - p_{\ell}$, until reaching a leaf node. One can also build a binary tree using all eigenvectors $\boldsymbol{Z}$, and then take $|E|$-by-$|E|$ submatrices of it during the sampling stage. Full descriptions of tree construction and sampling are provided in Algorithm 3. The proposed tree-based rejection sampling for an NDPP is outlined on the right-side of Algorithm 2. The one-time preprocessing step of constructing the tree (CONSTRUCTTREE) requires $O(MK^2)$ time. The time required for sampling (after pre-processing) is given by Proposition 1; see Appendix E.2 for a proof.

Proposition 1. *The tree-based sampling procedure* SAMPLEDPP *in Algorithm 3 runs in time* $O(K + k^3 \log M + k^4)$, *where k is the size of the sampled set*[‡].

4.3 AVERAGE NUMBER OF REJECTIONS

We now return to rejection sampling and focus on the expected number of rejections. The number of rejections of Algorithm 2 is known to be a geometric random variable with mean equal to the constant U used to upper-bound the ratio of the target distribution to the proposal distribution: $\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})/\det(\boldsymbol{L} + \boldsymbol{I})$. If all columns in $\boldsymbol{V}$ and $\boldsymbol{B}$ are orthogonal, which we denote $\boldsymbol{V} \perp \boldsymbol{B}$, then the expected number of rejections depends only on the eigenvalues of the skew-symmetric part of the NDPP kernel.

Theorem 2. *Given an NDPP kernel $\boldsymbol{L} = \boldsymbol{V}\boldsymbol{V}^{\top} + \boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^{\top})\boldsymbol{B}^{\top}$ for $\boldsymbol{V}, \boldsymbol{B} \in \mathbb{R}^{M \times K}, \boldsymbol{D} \in \mathbb{R}^{K \times K}$, consider the proposal kernel $\widehat{\boldsymbol{L}}$ as proposed in Section 4.1. Let $\{\sigma_j\}_{j=1}^{K/2}$ be the positive eigenvalues obtained from the Youla decomposition of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^{\top})\boldsymbol{B}^{\top}$. If $\boldsymbol{V} \perp \boldsymbol{B}$, then $\frac{\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})}{\det(\boldsymbol{L} + \boldsymbol{I})} = \prod_{j=1}^{K/2} \left(1 + \frac{2\sigma_j}{\sigma_j^2 + 1} \right) \leq (1 + \omega)^{K/2}$, where $\omega = \frac{2}{K} \sum_{j=1}^{K/2} \frac{2\sigma_j}{\sigma_j^2 + 1} \in (0, 1]$.*

[‡]Computing p_{ℓ} via Eq. (12) improves on Gillenwater et al. (2019)'s $O(k^4 \log M)$ runtime for this step.

Proof sketch: Orthogonality between V and B allows $\det(L + I)$ to be expressed just in terms of the eigenvalues of $VV^\top$ and $B(D - D^\top)B^\top$. Since both L and $\widehat{L}$ share the symmetric part $VV^\top$, the ratio of determinants only depends on the skew-symmetric part. A more formal proof appears in Appendix E.1.

Assuming we have a kernel where $V \perp B$, we can combine Theorem 2 with the tree-based rejection sampling algorithm (right-side in Algorithm 2) to sample in time $O((K + k^3 \log M + k^4)(1+\omega)^{K/2})$. Hence, we have a sampling algorithm that is sublinear in M, and can be much faster than the Cholesky-based algorithm when $(1 + \omega)^{K/2} \ll M$. In the next section, we introduce a learning scheme with the $V \perp B$ constraint, as well as regularization to ensure that ω is small.

5 LEARNING WITH ORTHOGONALITY CONSTRAINTS

We aim to learn a NDPP that provides both good predictive performance and a low rejection rate. We parameterize our NDPP kernel matrix $L = VV^\top + B(D - D^\top)B^\top$ by

$$D = \operatorname{diag}\left(\begin{bmatrix} 0 & \sigma_1 \\ 0 & 0 \end{bmatrix}, \ldots, \begin{bmatrix} 0 & \sigma_{K/2} \\ 0 & 0 \end{bmatrix} \right) \tag{13}$$

for $\sigma_j \geq 0$, $B^\top B = I$, and, motivated by Theorem 2, require $V^\top B = 0$[§]. We call such orthogonality-constrained NDPPs "ONDPPs". Notice that if $V \not\perp B$, then L will have rank $< 2K$, meaning part of the rank-$2K$ available for modeling goes unused. Thus, this constraint can also be thought of as simply ensuring that ONDPPs use the full rank available to them.

Given example subsets $\{Y_1, \ldots, Y_n\}$ as training data, learning is done by minimizing the regularized negative log-likelihood:

$$\min_{V, B, \{\sigma_j\}_{j=1}^{K/2}} -\frac{1}{n} \sum_{i=1}^{n} \log\left(\frac{\det(L_{Y_i})}{\det(L + I)} \right) + \alpha \sum_{i=1}^{M} \frac{\|v_i\|_2^2}{\mu_i} + \beta \sum_{i=1}^{M} \frac{\|b_i\|_2^2}{\mu_i} + \gamma \sum_{j=1}^{K/2} \log\left(1 + \frac{2\sigma_j}{\sigma_j^2 + 1} \right) \tag{14}$$

where $\alpha, \beta, \gamma > 0$ are hyperparameters, μ_i is the frequency of item i in the training data, and v_i and b_i represent the rows of V and B, respectively. This objective is very similar to that of Gartrell et al. (2021), except for the orthogonality constraint and the final regularization term. Note that this regularization term corresponds exactly to the logarithm of the average rejection rate, and therefore should help to control the number of rejections.

6 EXPERIMENTS

We first show that the orthogonality constraint from Section 5 does not degrade the predictive performance of learned kernels. We then compare the speed of our proposed sampling algorithms.

6.1 PREDICTIVE PERFORMANCE RESULTS FOR NDPP LEARNING

We benchmark various DPP models, including symmetric (Gartrell et al., 2017), nonsymmetric for scalable learning (Gartrell et al., 2021), as well as our ONDPP kernels with and without rejection rate regularization. We use the scalable NDPP models (Gartrell et al., 2021) as a baseline[¶]. The kernel

---

[§]Technical details: To learn NDPP models with the constraint $V^\top B = 0$, we project V according to: $V \leftarrow V - B(B^\top B)^{-1}(B^\top V)$. For the $B^\top B = I$ constraint, we apply QR decomposition on B. Note that both operations require $O(MK^2)$ time. (Constrained learning code is provided in the supplement. We use Pytorch's `linalg.solve` to avoid the expense of explicitly computing the $(B^\top B)^{-1}$ inverse.) Hence, our learning time complexity is identical to that of Gartrell et al. (2021).

[¶]We use the code from https://github.com/cgartrel/scalable-nonsymmetric-DPPs for the NDPP baseline, which is made available under the MIT license. To simplify learning and MAP inference, Gartrell et al. (2021) set $B = V$ in their experiments. However, since we have the $V \perp B$ constraint in our ONDPP approach, we cannot set $B = V$. Hence, for a fair comparison, we do not set $B = V$ for the NDPP baseline in our experiments, and thus the results in Table 2 differ slightly from those published in Gartrell et al. (2021).

Table 2: Average MPR and AUC, with 95% confidence estimates obtained via bootstrapping, test log-likelihood, and the number of rejections for NDPP models. Bold values indicate the best MPR, outside of the confidence intervals of the two baseline methods.

Low-rank DPP Models	Metric	UK Retail M=3,941	Recipe M=7,993	Instacart M=49,677	Million Song M=371,410	Book M=1,059,437
Symmetric DPP (Gartrell et al., 2017)	MPR	76.42 ± 0.97	95.04 ± 0.69	93.06 ± 0.92	90.00 ± 1.18	72.54 ± 2.03
	AUC	0.74 ± 0.01	0.99 ± 0.01	0.86 ± 0.01	0.77 ± 0.01	0.70 ± 0.01
	Log-Likelihood	-104.89	-44.63	-73.22	-310.14	-149.76
NDPP (Gartrell et al., 2021)	MPR	77.09 ± 1.10	95.17 ± 0.67	92.40 ± 1.05	89.00 ± 1.11	72.98 ± 1.46
	AUC	0.74 ± 0.01	0.99 ± 0.00	0.87 ± 0.01	0.80 ± 0.01	0.74 ± 0.01
	Log-Likelihood	-99.09	-44.72	-74.94	-314.12	-149.93
	# of Rejections	4.136×10^{10}	78.95	6.806×10^3	3.907×10^{10}	9.245×10^6
ONDPP without regularization	MPR	$\mathbf{78.43 \pm 0.95}$	95.40 ± 0.62	92.80 ± 0.99	$\mathbf{93.02 \pm 0.83}$	75.35 ± 1.83
	AUC	0.71 ± 0.00	0.99 ± 0.01	0.83 ± 0.01	0.77 ± 0.01	0.64 ± 0.01
	Log-Likelihood	-99.45	-44.60	-72.69	-302.64	-140.53
	# of Rejections	1.818×10^9	103.81	128.96	5.563×10^7	682.22
ONDPP with regularization	MPR	77.12 ± 0.98	95.50 ± 0.59	92.99 ± 0.95	92.86 ± 0.80	$\mathbf{75.73 \pm 1.84}$
	AUC	0.72 ± 0.01	0.99 ± 0.01	0.83 ± 0.01	0.77 ± 0.01	0.64 ± 0.01
	Log-Likelihood	-103.83	-44.56	-72.72	-305.66	-140.67
	# of Rejections	26.09	21.59	79.74	45.42	61.10

components of each model are learned using five real-world recommendation datasets, which have ground set sizes that range from 3,941 to 1,059,437 items (see Appendix A for more details).

Our experimental setup and metrics mirror those of Gartrell et al. (2021). We report the mean percentile rank (MPR) metric for a next-item prediction task, the AUC metric for subset discrimination, and the log-likelihood of the test set; see Appendix B for more details on the experiments and metrics. For all metrics, higher numbers are better. For NDPP models, we additionally report the average rejection rates when they apply to rejection sampling.

In Table 2, we observe that the predictive performance of our ONDPP models generally match or sometimes exceed the baseline. This is likely because the orthogonality constraint enables more effective use of the full rank-$2K$ feature space. Moreover, imposing the regularization on rejection rate, as shown in Eq. (14), often leads to dramatically smaller rejection rates, while the impact on predictive performance is generally marginal. These results justify the ONDPP and regularization for fast sampling. Finally, we observe that the learning time of our ONDPP models is typically a bit longer than that of the NDPP models, but still quite reasonable (e.g., the time per iteration for the NDPP takes 27 seconds for the Book dataset, while our ONDPP takes 49.7 seconds).

Fig. 1 shows how the regularizer γ affects the test log-likelihood and the average number of rejections. We see that γ degrades predictive performance and reduces the rejection rate when set above a certain threshold; this behavior is seen for many datasets. However, for the Recipe dataset we observed that the test log-likelihood is not very sensitive to γ, likely because all models in our experiments achieve very high performance on this dataset. In general, we observe that γ can be set to a value that results in a small rejection rate, while having minimal impact on predictive performance.

6.2 SAMPLING TIME COMPARISON

We benchmark the Cholesky-based sampling algorithm (Algorithm 1) and tree-based rejection sampling algorithm (Algorithm 2) on ONDPPs with both synthetic and real-world data.

Synthetic datasets. We generate non-uniform random features for V, B as done by (Han & Gillenwater, 2020). In particular, we first sample $x_1, \ldots, x_{100}$ from $\mathcal{N}(0, I_{2K}/(2K))$, and integers $t_1, \ldots, t_{100}$ from Poisson distribution with mean 5, rescaling the integers such that $\sum_i t_i = M$. Next, we draw t_i random vectors from $\mathcal{N}(x_i, I_{2K})$, and assign the first K-dimensional vectors as the row vectors of V and the latter vectors as those of B. Each entry of D is sampled from $\mathcal{N}(0, 1)$. We choose $K = 100$ and vary M from 2^{12} to 2^{20}.

(a)   (b)   (a)   (b)

Figure 1: Average number of rejections and test log-likelihood with different values of the regularizer γ for ONDPPs trained on the UK Retail dataset. Shaded regions are 95% confidence intervals of 10 independent trials.

Figure 2: Wall-clock time (sec) for synthetic data for (a) NDPP sampling algorithms and (b) preprocessing steps for the rejection sampling. Shaded regions are 95% confidence intervals from 100 independent trials.

Table 3: Wall-clock time (sec) for preprocessing and sampling ONDPPs trained on real-world data, and speedup of the tree-based sampler over the Cholesky-based one. We set $K = 100$ and provide average times with 95% confidence intervals from 10 independent trials for the Cholesky-based algorithm and 100 trials for the rejection algorithm. Memory usage for the tree is also reported.

	UK Retail M=3,941	**Recipe** M=7,993	**Instacart** M=49,677	**Million Song** M=371,410	**Book** M=1,059,437
Spectral decomposition	0.209	0.226	0.505	2.639	7.482
Tree construction	0.997	1.998	12.65	119.0	340.1
Cholesky-based sampling	5.572 ± 0.056	11.36 ± 0.098	71.82 ± 1.087	545.8 ± 8.776	$1{,}631 \pm 11.84$
Tree-based rejection sampling	2.463 ± 0.417	1.331 ± 0.241	5.962 ± 1.049	14.72 ± 2.620	6.627 ± 1.294
(Speedup)	($\times 2.262$)	($\times 8.535$)	($\times 12.05$)	($\times 37.08$)	($\times 246.1$)
Tree memory usage	630.5 MB	1.279 GB	7.948 GB	59.43 GB	169.5 GB

Fig. 2(a) illustrates the runtimes of Algorithms 1 and 2. We verify that the rejection sampling time tends to increase sub-linearly with the ground set size M, while the Cholesky-based sampler runs in linear time. In Fig. 2(b), the runtimes of the preprocessing steps for Algorithm 2 (i.e., spectral decomposition and tree construction) are reported. Although the rejection sampler requires these additional processes, they are one-time steps and run much faster than a single run of the Choleksy-based method for $M = 2^{20}$.

Real-world datasets. In Table 3, we report the runtimes and speedup of NDPP sampling algorithms for real-world datasets. All NDPP kernels are obtained using learning with orthogonality constraints, with rejection rate regularization as reported in Section 6.1. We observe that the tree-based rejection sampling runs up to 246 times faster than the Cholesky-based algorithm. For larger datasets, we expect that this gap would significantly increase. As with the synthetic experiments, we see that the tree construction pre-processing time is comparable to the time required to draw a single sample via the other methods, and thus the tree-based method is often the best choice for repeated sampling[‖].

7   CONCLUSION

In this work we developed scalable sampling methods for NDPPs. One limitation of our rejection sampler is its practical restriction to the ONDPP subclass. Other opportunities for future work include the extension of our rejection sampling approach to the generation of fixed-size samples (from k-NDPPs), the development of approximate sampling techniques, and the extension of DPP samplers along the lines of Derezinski et al. (2019); Calandriello et al. (2020) to NDPPs. Scalable sampling also opens the door to using NDPPs as building blocks in probabilistic models.

[‖]We note that the tree can consume substantial memory, e.g., 169.5 GB for the Book dataset with $K = 100$. For settings where this scale of memory use is unacceptable, we suggest use of the intermediate sampling algorithm (Calandriello et al., 2020) in place of tree-based sampling. The resulting sampling may be slower, but the $O(M + K)$ memory cost is substantially lower.

REFERENCES

Yeganeh Alimohammadi, Nima Anari, Kirankumar Shiragur, and Thuy-Duong Vuong. Fractionally log-concave and sector-stable polynomials: counting planar matchings and more. In *Symposium on the Theory of Computing (STOC)*, 2021.

Victor-Emmanuel Brunel. Learning Signed Determinantal Point Processes through the Principal Minor Assignment Problem. In *Neural Information Processing Systems (NeurIPS)*, 2018.

Daniele Calandriello, Michal Derezinski, and Michal Valko. Sampling from a k-DPP without looking at all items. In *Neural Information Processing Systems (NeurIPS)*, 2020.

Daqing Chen, Sai Laing Sain, and Kun Guo. Data mining for the online retail industry: A case study of RFM model-based customer segmentation using data mining. *Journal of Database Marketing & Customer Strategy Management*, 2012.

Michal Derezinski, Daniele Calandriello, and Michal Valko. Exact sampling of determinantal point processes with sublinear time preprocessing. *Neural Information Processing Systems (NeurIPS)*, 2019.

Christophe Dupuy and Francis Bach. Learning determinantal point processes in sublinear time. In *Conference on Artificial Intelligence and Statistics (AISTATS)*, 2018.

Mike Gartrell, Ulrich Paquet, and Noam Koenigstein. Low-Rank Factorization of Determinantal Point Processes. In *Conference on Artificial Intelligence (AAAI)*, 2017.

Mike Gartrell, Victor-Emmanuel Brunel, Elvis Dohmatob, and Syrine Krichene. Learning Non-symmetric Determinantal Point Processes. In *Neural Information Processing Systems (NeurIPS)*, 2019.

Mike Gartrell, Insu Han, Elvis Dohmatob, Jennifer Gillenwater, and Victor-Emmanuel Brunel. Scalable Learning and MAP Inference for Nonsymmetric Determinantal Point Processes. In *International Conference on Learning Representations (ICLR)*, 2021.

Jennifer Gillenwater, Alex Kulesza, Zelda Mariet, and Sergei Vassilvtiskii. A Tree-Based Method for Fast Repeated Sampling of Determinantal Point Processes. In *International Conference on Machine Learning (ICML)*, 2019.

Insu Han and Jennifer Gillenwater. MAP Inference for Customized Determinantal Point Processes via Maximum Inner Product Search. In *Conference on Artificial Intelligence and Statistics (AISTATS)*, 2020.

Yifan Hu, Yehuda Koren, and Chris Volinsky. Collaborative Filtering for Implicit Feedback Datasets. In *International Conference on Data Mining (ICDM)*, 2008.

Instacart. The Instacart Online Grocery Shopping Dataset, 2017. URL https://www.instacart.com/datasets/grocery-shopping-2017. Accessed May 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

Alex Kulesza and Ben Taskar. Determinantal Point Processes for Machine Learning. *Foundations and Trends® in Machine Learning*, 2012.

Yanen Li, Jia Hu, ChengXiang Zhai, and Ye Chen. Improving One-class Collaborative Filtering by Incorporating Rich User Information. In *Conference on Information and Knowledge Management (CIKM)*, 2010.

Bodhisattwa Prasad Majumder, Shuyang Li, Jianmo Ni, and Julian J McAuley. Generating Personalized Recipes from Historical User Preferences. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2019.

Brian McFee, Thierry Bertin-Mahieux, Daniel PW Ellis, and Gert RG Lanckriet. The million song dataset challenge. In *International Conference on the World Wide Web (WWW)*, 2012.

Yuji Nakatsukasa. The low-rank eigenvalue problem. *arXiv preprint arXiv:1905.11490*, 2019.

Takayuki Osogami and Rudy Raymond. Determinantal reinforcement learning. In *Conference on Artificial Intelligence (AAAI)*, 2019.

Jack Poulson. High-performance sampling of generic Determinantal Point Processes. *arXiv preprint arXiv:1905.00165*, 2019.

Jocelyn Quaintance. *Combinatorial Identities: Table I: Intermediate Techniques for Summing Finite Series*, volume 3. 2010.

Nicolas Tremblay, Simon Barthelmé, and Pierre-Olivier Amblard. Determinantal Point Processes for Coresets. *Journal of Machine Learning Research (JMLR)*, 2019.

John Von Neumann. Various techniques used in connection with random digits. *John von Neumann, Collected Works*, 1963.

Mengting Wan and Julian McAuley. Item recommendation on monotonic behavior chains. In *Conference on Recommender Systems (RecSys)*, 2018.

Yaodong Yang, Ying Wen, Jun Wang, Liheng Chen, Kun Shao, David Mguni, and Weinan Zhang. Multi-agent determinantal q-learning. In *International Conference on Machine Learning (ICML)*, 2020.

DC Youla. A normal form for a matrix under the unitary congruence group. *Canadian Journal of Mathematics*, 1961.

Cheng Zhang, Hedvig Kjellström, and Stephan Mandt. Determinantal Point Processes for Mini-Batch Diversification. In *Conference on Uncertainty in Artificial Intelligence (UAI)*, 2017.

A FULL DETAILS ON DATASETS

We perform experiments on several real-world public datasets composed of subsets:

• **UK Retail:** This dataset (Chen et al., 2012) contains baskets representing transactions from an online retail company that sells all-occasion gifts. We omit baskets with more than 100 items, leaving us with a dataset containing 19,762 baskets drawn from a catalog of $M = 3,941$ products. Baskets containing more than 100 items are in the long tail of the basket-size distribution, so omitting these is reasonable, and allows us to use a low-rank factorization of the NDPP with $K = 100$.

• **Recipe:** This dataset (Majumder et al., 2019) contains recipes and food reviews from Food.com (formerly Genius Kitchen)[**]. Each recipe ("basket") is composed of a collection of ingredients, resulting in 178,265 recipes and a catalog of 7,993 ingredients.

• **Instacart:** This dataset (Instacart, 2017) contains baskets purchased by Instacart users[††]. We omit baskets with more than 100 items, resulting in 3.2 million baskets and a catalog of 49,677 products.

• **Million Song:** This dataset (McFee et al., 2012) contains playlists ("baskets") of songs from Echo Nest users[‡‡]. We trim playlists with more than 100 items, leaving 968,674 playlists and a catalog of 371,410 songs.

• **Book:** This dataset (Wan & McAuley, 2018) contains reviews from the Goodreads book review website, including a variety of attributes describing the items[§§]. For each user we build a subset ("basket") containing the books reviewed by that user. We trim subsets with more than 100 books, resulting in 430,563 subsets and a catalog of 1,059,437 books.

As far as we are aware, these datasets do not contain personally identifiable information or offensive content. While the UK Retail dataset is publicly available, we were unable to find a license for it. Also, we were not able to determine if user consent was explicitly obtained by the organizations that constructed these datasets.

B FULL DETAILS ON EXPERIMENTAL SETUP AND METRICS

We use 300 randomly-selected baskets as a held-out validation set, for tracking convergence during training and for tuning hyperparameters. Another 2000 random baskets are used for testing, and the rest are used for training. Convergence is reached during training when the relative change in validation log-likelihood is below a predetermined threshold. We use PyTorch with Adam (Kingma & Ba, 2015) for optimization. We initialize D from the standard Gaussian distribution $\mathcal{N}(0, 1)$, while V and B are initialized from the uniform$(0, 1)$ distribution.

Subset expansion task. We use greedy conditioning to do next-item prediction (Gartrell et al., 2021, Section 4.2). We compare methods using a standard recommender system metric: mean percentile rank (MPR) (Hu et al., 2008; Li et al., 2010). MPR of 50 is equivalent to random selection; MPR of 100 means that the model perfectly predicts the next item. See Appendix B.1 for a complete description of the MPR metric.

Subset discrimination task. We also test the ability of a model to discriminate observed subsets from randomly generated ones. For each subset in the test set, we generate a subset of the same length by drawing items uniformly at random (and we ensure that the same item is not drawn more than once for a subset). We compute the AUC for the model on these observed and random subsets, where the score for each subset is the log-likelihood that the model assigns to the subset.

[**]See https://www.kaggle.com/shuyangli94/food-com-recipes-and-user-interactions for the license for this public dataset.
[††]This public dataset is available for non-commercial use; see https://www.instacart.com/datasets/grocery-shopping-2017 for the license.
[‡‡]See http://millionsongdataset.com/faq/ for the license for this public dataset.
[§§]This public dataset is available for academic use only; see https://sites.google.com/eng.ucsd.edu/ucsdbookgraph/home for the license.

B.1 MEAN PERCENTILE RANK

We begin our definition of MPR by defining percentile rank (PR). First, given a set J, let $p_{i,J} = \Pr(J \cup \{i\} \mid J)$. The percentile rank of an item i given a set J is defined as

$$\text{PR}_{i,J} = \frac{\sum_{i' \notin J} \mathbb{1}(p_{i,J} \geq p_{i',J})}{|\mathcal{Y} \backslash J|} \times 100\%$$

where $\mathcal{Y} \backslash J$ indicates those elements in the ground set $\mathcal{Y}$ that are not found in J.

For our evaluation, given a test set Y, we select a random element $i \in Y$ and compute $\text{PR}_{i,Y\backslash\{i\}}$. We then average over the set of all test instances $\mathcal{T}$ to compute the mean percentile rank (MPR):

$$\text{MPR} = \frac{1}{|\mathcal{T}|} \sum_{Y \in \mathcal{T}} \text{PR}_{i,Y\backslash\{i\}}.$$

C HYPERPARAMETERS FOR EXPERIMENTS

Preventing numerical instabilities: The $\det(\boldsymbol{L}_{Y_i})$ in Eq. (14) will be zero whenever $|Y_i| > K$, where Y_i is an observed subset. To address this in practice we set K to the size of the largest subset observed in the data, K', as in Gartrell et al. (2017). However, this does not entirely fix the issue, as there is still a chance that the term will be zero even when $|Y_i| \leq K$. In this case though, we know that we are not at a maximum, since the value of the objective function is $-\infty$. Numerically, to prevent such singularities, in our implementation we add a small $\epsilon \boldsymbol{I}$ correction to each $\boldsymbol{L}_{Y_i}$ when optimizing Eq. (14) ($\epsilon = 10^{-5}$ in our experiments).

We perform a grid search using a held-out validation set to select the best-performing hyperparameters for each model and dataset. The hyperparameter settings used for each model and dataset are described below.

Symmetric low-rank DPP (Gartrell et al., 2017). For this model, we use K for the number of item feature dimensions for the symmetric component $\boldsymbol{V}$, and α for the regularization hyperparameter for $\boldsymbol{V}$. We use the following hyperparameter settings:

- UK Retail dataset: $K = 100, \alpha = 1$.
- Recipe dataset: $K = 100, \alpha = 0.01$
- Instacart dataset: $K = 100, \alpha = 0.001$.
- Million Song dataset: $K = 100, \alpha = 0.0001$.
- Book dataset: $K = 100, \alpha = 0.001$

Scalable NDPP (Gartrell et al., 2021). As described in Section 2.1, we use K to denote the number of item feature dimensions for the symmetric component $\boldsymbol{V}$ and the dimensionality of the nonsymmetric component $\boldsymbol{D}$. α and β are the regularization hyperparameters. We use the following hyperparameter settings:

- UK dataset: $K = 100, \alpha = 0.01$.
- Recipe dataset: $K = 100, \alpha = \beta = 0.01$.
- Instacart dataset: $K = 100, \alpha = 0.001$.
- Million Song dataset: $K = 100, \alpha = 0.01$.
- Book dataset: $K = 100, \alpha = \beta = 0.1$

ONDPP. As described in Section 5, we use K to denote the number of item feature dimensions for the symmetric component $\boldsymbol{V}$ and the dimensionality of the nonsymmetric component $\boldsymbol{C}$. α, β, and γ are the regularization hyperparameters. We use the following hyperparameter settings:

- UK dataset: $K = 100, \alpha = \beta = 0.01, \gamma = 0.5$.
- Recipe dataset: $K = 100, \alpha = \beta = 0.01, \gamma = 0.1$.
- Instacart dataset: $K = 100, \alpha = \beta = 0.001, \gamma = 0.001$.
- Million Song dataset: $K = 100, \alpha = \beta = 0.01, \gamma = 0.2$.

- Book dataset: $K = 100, \alpha = \beta = 0.01, \gamma = 0.1$.

For all of the above model configurations and datasets, we use a batch size of 800 during training.

D YOULA DECOMPOSITION: SPECTRAL DECOMPOSITION FOR SKEW-SYMMETRIC MATRIX

We provide some basic facts on the spectral decomposition of a skew-symmetric matrix, and introduce an efficient algorithm for this decomposition when it is given by a low-rank factorization. We write $\mathrm{i} := \sqrt{-1}$ and $\boldsymbol{v}^H$ as the conjugate transpose of $\boldsymbol{v} \in \mathbb{C}^M$, and denote $\mathrm{Re}(z)$ and $\mathrm{Im}(z)$ by the real and imaginary parts of a complex number z, respectively.

Given $\boldsymbol{B} \in \mathbb{R}^{M \times K}$ and $\boldsymbol{D} \in \mathbb{R}^{K \times K}$, consider a rank-$K$ skew-symmetric matrix $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$. Note that all nonzero eigenvalues of a real-valued skew-symmetric matrix are purely imaginary. Denote $\mathrm{i}\sigma_1, -\mathrm{i}\sigma_1, \ldots, \mathrm{i}\sigma_{K/2}, -\mathrm{i}\sigma_{K/2}$ by its nonzero eigenvalues where each of σ_j is real, and $\boldsymbol{a}_1 + \mathrm{i}\boldsymbol{b}_1, \boldsymbol{a}_1 - \mathrm{i}\boldsymbol{b}_1, \ldots \boldsymbol{a}_{K/2} + \mathrm{i}\boldsymbol{b}_{K/2}, \boldsymbol{a}_{K/2} - \mathrm{i}\boldsymbol{b}_{K/2}$ by the corresponding eigenvectors for $\boldsymbol{a}_j, \boldsymbol{b}_j \in \mathbb{R}^M$, which come in conjugate pairs. Then, we can write

$$\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top = \sum_{j=1}^{K/2} \mathrm{i}\sigma_j(\boldsymbol{a}_j + \mathrm{i}\boldsymbol{b}_j)(\boldsymbol{a}_j + \mathrm{i}\boldsymbol{b}_j)^H - \mathrm{i}\sigma_j(\boldsymbol{a}_j - \mathrm{i}\boldsymbol{b}_j)(\boldsymbol{a}_j - \mathrm{i}\boldsymbol{b}_j)^H \quad (15)$$

$$= \sum_{j=1}^{K/2} 2\sigma_j(\boldsymbol{a}_j\boldsymbol{b}_j^\top - \boldsymbol{b}_j\boldsymbol{a}_j^\top) \quad (16)$$

$$= \sum_{j=1}^{K/2} \begin{bmatrix} \boldsymbol{a}_j - \boldsymbol{b}_j & \boldsymbol{a}_j + \boldsymbol{b}_j \end{bmatrix} \begin{bmatrix} 0 & \sigma_j \\ -\sigma_j & 0 \end{bmatrix} \begin{bmatrix} \boldsymbol{a}_j^\top - \boldsymbol{b}_j^\top \\ \boldsymbol{a}_j^\top + \boldsymbol{b}_j^\top \end{bmatrix}. \quad (17)$$

Note that $\boldsymbol{a}_1 \pm \boldsymbol{b}_1, \ldots, \boldsymbol{a}_{K/2} \pm \boldsymbol{b}_{K/2}$ are real-valued orthonormal vectors, because $\boldsymbol{a}_1, \boldsymbol{b}_1, \ldots, \boldsymbol{a}_{K/2}, \boldsymbol{b}_{K/2}$ are orthogonal to each other and $\|\boldsymbol{a}_j \pm \boldsymbol{b}_j\|_2^2 = \|\boldsymbol{a}_j\|_2^2 + \|\boldsymbol{b}_j\|_2^2 = 1$ for all j. The pair $\{(\sigma_j, \boldsymbol{a}_j - \boldsymbol{b}_j, \boldsymbol{a}_j + \boldsymbol{b}_j)\}_{j=1}^{K/2}$ is often called the Youla decomposition (Youla, 1961) of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$. To efficiently compute the Youla decomposition of a rank-K matrix, we use the following result.

Proposition 2 (Proposition 1, Nakatsukasa (2019)). *Given $\boldsymbol{A}, \boldsymbol{B} \in \mathbb{C}^{M \times K}$, the nonzero eigenvalues of $\boldsymbol{A}\boldsymbol{B}^\top \in \mathbb{C}^{M \times M}$ and $\boldsymbol{B}^\top \boldsymbol{A} \in \mathbb{C}^{K \times K}$ are identical. In addition, if $(\lambda, \boldsymbol{v})$ is an eigenpair of $\boldsymbol{B}^\top \boldsymbol{A}$ with $\lambda \neq 0$, then $(\lambda, \boldsymbol{A}\boldsymbol{v}/\|\boldsymbol{A}\boldsymbol{v}\|_2)$ is an eigenpair of $\boldsymbol{A}\boldsymbol{B}^\top$.*

From the above proposition, one can first compute $(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top \boldsymbol{B}$ and then apply the eigendecomposition to that K-by-K matrix. Taking the imaginary part of the obtained eigenvalues gives us the σ_j's, and multiplying $\boldsymbol{B}$ by the eigenvectors gives us the eigenvectors of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$. In addition, this can be done in $O(MK^2 + K^3)$ time; when $M > K$ it runs much faster than the eigendecomposition of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$, which requires $O(M^3)$ time. The pseudo-code of the Youla decomposition is provided in Algorithm 4.

Algorithm 4 Youla decomposition of low-rank skew-symmetric matrix

1: **procedure** YOULADECOMPOSITION($\boldsymbol{B}, \boldsymbol{D}$)
2:     $\{(\eta_j, \boldsymbol{z}_j), (\overline{\eta}_j, \overline{\boldsymbol{z}}_j)\}_{j=1}^{K/2} \leftarrow$ eigendecomposition of $(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top \boldsymbol{B}$
3:     **for** $j = 1, \ldots, K/2$ **do**
4:         $\sigma_j \leftarrow \mathrm{Im}(\eta_j)$ for $j = 1, \ldots, K/2$
5:         $\boldsymbol{y}_{2j-1} \leftarrow \boldsymbol{B}\,(\mathrm{Re}(\boldsymbol{z}_j) - \mathrm{Im}(\boldsymbol{z}_j))$
6:         $\boldsymbol{y}_{2j} \leftarrow \boldsymbol{B}\,(\mathrm{Re}(\boldsymbol{z}_j) + \mathrm{Im}(\boldsymbol{z}_j))$
7:     $\boldsymbol{y}_j \leftarrow \boldsymbol{y}_j/\|\boldsymbol{y}_j\|$ for $j = 1, \ldots, K$
8:     **return** $\{(\sigma_j, \boldsymbol{y}_{2j-1}, \boldsymbol{y}_{2j})\}_{j=1}^{K/2}$

E PROOFS

E.1 PROOF OF THEOREM 1

Theorem 1. *For every subset $Y \subseteq [M]$, it holds that $\det(\boldsymbol{L}_Y) \leq \det(\widehat{\boldsymbol{L}}_Y)$. Moreover, equality holds when the size of Y is equal to the rank of $\boldsymbol{L}$.*

Proof of Theorem 1. It is enough to fix $Y \subseteq [M]$ such that $1 \leq |Y| \leq 2K$, because the rank of both $\boldsymbol{L}$ and $\widehat{\boldsymbol{L}}$ is up to $2K$. We recall the definition of $\widehat{\boldsymbol{L}}$: given $\boldsymbol{V}, \boldsymbol{B}, \boldsymbol{D}$ such that $\boldsymbol{L} = \boldsymbol{V}\boldsymbol{V}^\top + \boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$, let $\{(\rho_i, \boldsymbol{v}_i)\}_{i=1}^K$ be the eigendecomposition of $\boldsymbol{V}\boldsymbol{V}^\top$ and $\{(\sigma_j, \boldsymbol{y}_{2j-1}, \boldsymbol{y}_{2j})\}_{j=1}^{K/2}$ be the Youla decomposition of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$. Denote $\boldsymbol{Z} := [\boldsymbol{v}_1, \ldots, \boldsymbol{v}_K, \boldsymbol{y}_1, \ldots, \boldsymbol{y}_K] \in \mathbb{R}^{M \times 2K}$ and

$$
\begin{aligned}
\boldsymbol{X} &:= \operatorname{diag}\left(\rho, \ldots, \rho_K, \begin{bmatrix} 0 & \sigma_1 \\ -\sigma_1 & 0 \end{bmatrix}, \ldots, \begin{bmatrix} 0 & \sigma_{K/2} \\ -\sigma_{K/2} & 0 \end{bmatrix}\right), \\
\widehat{\boldsymbol{X}} &:= \operatorname{diag}\left(\rho_1, \ldots, \rho_K, \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_1 \end{bmatrix}, \ldots, \begin{bmatrix} \sigma_{K/2} & 0 \\ 0 & \sigma_{K/2} \end{bmatrix}\right),
\end{aligned}
$$

so that $\boldsymbol{L} = \boldsymbol{Z}\boldsymbol{X}\boldsymbol{Z}^\top$ and $\widehat{\boldsymbol{L}} = \boldsymbol{Z}\widehat{\boldsymbol{X}}\boldsymbol{Z}^\top$. Applying the Cauchy-Binet formula twice, we can write the determinant of principal submatrices of $\boldsymbol{L}$ as follows:

$$
\det(\boldsymbol{L}_Y) = \sum_{I \subseteq [2K], |I| = |Y|} \sum_{J \subseteq [2K], |J| = |Y|} \det(\boldsymbol{X}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J}). \tag{18}
$$

Similarly, for $\widehat{\boldsymbol{L}}$:

$$
\begin{aligned}
\det(\widehat{\boldsymbol{L}}_Y) &= \sum_{I \subseteq [2K], |I| = |Y|} \sum_{J \subseteq [2K], |J| = |Y|} \det(\widehat{\boldsymbol{X}}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J}) && (19) \\
&= \sum_{I \subseteq [2K], |I| = |Y|} \det(\widehat{\boldsymbol{X}}_I) \det(\boldsymbol{Z}_{Y,I})^2, && (20)
\end{aligned}
$$

where Eq. (20) follows from the fact that $\widehat{\boldsymbol{X}}$ is diagonal, which means that $\det(\widehat{\boldsymbol{X}}_{I,J}) = 0$ for $I \neq J$.

When the size of Y is equal to the rank of $\boldsymbol{L}$ (i.e., $I = J = [2K]$), the summations in Eqs. (18) and (20) simplify to single terms: $\det(\boldsymbol{L}_Y) = \det(\boldsymbol{X})\det(\boldsymbol{Z}_{Y,:})^2$ and $\det(\widehat{\boldsymbol{L}}_Y) = \det(\widehat{\boldsymbol{X}})\det(\boldsymbol{Z}_{Y,:})^2$. Now, observe that the determinants of the full $\boldsymbol{X}$ and $\widehat{\boldsymbol{X}}$ matrices are identical: $\det(\boldsymbol{X}) = \det(\widehat{\boldsymbol{X}}) = \prod_{i=1}^K \rho_i \prod_{j=1}^{K/2} \sigma_j^2$. Hence, for $|Y| = 2K$ it holds that $\det(\boldsymbol{L}_Y) = \det(\widehat{\boldsymbol{L}}_Y)$. This proves the second statement of the theorem.

To prove that $\det(\boldsymbol{L}_Y) \leq \det(\widehat{\boldsymbol{L}}_Y)$ for smaller subsets Y, we will show that the number of nonzero terms in Eq. (18) is in fact equal to the number of nonzero terms in Eq. (20), and will establish a correspondence between these terms.

First, recall that $\boldsymbol{X}$ is a block-diagonal matrix, where each block is of size either 1-by-1, containing ρ_i, or 2-by-2, containing both σ_j and $-\sigma_j$ in the form $\begin{bmatrix} 0 & \sigma_j \\ -\sigma_j & 0 \end{bmatrix}$. A submatrix $\boldsymbol{X}_{I,J}$ with rows I and columns J will only have a nonzero determinant if it contains no all-zero row or column. Hence, any $\boldsymbol{X}_{I,J}$ with nonzero determinant will have the following form (or some permutation of

this block-diagonal):

$$
\boldsymbol{X}_{I,J} = \begin{bmatrix}
\rho_{p_1} & \cdots & 0 & & & & & & & \\
\vdots & \ddots & \vdots & & & & & \Huge{0} & & \\
0 & \cdots & \rho_{p_{|P^{I,J}|}} & & & & & & & \\
& & & \pm\sigma_{q_1} & \cdots & 0 & & & & \\
& & & \vdots & \ddots & \vdots & & & & \\
& & & 0 & \cdots & \pm\sigma_{q_{|Q^{I,J}|}} & & & & \\
& & & & & & 0 & \sigma_{r_1} & & \\
& & & & & & -\sigma_{r_1} & 0 & & \\
& & & & & & & & \ddots & \\
& \Huge{0} & & & & & & & 0 & \sigma_{r_{|R^{I,J}|}} \\
& & & & & & & & -\sigma_{r_{|R^{I,J}|}} & 0
\end{bmatrix}
\tag{21}
$$

and we denote $P^{I,J} := \{p_1, \ldots, p_{|P^{I,J}|}\}$, $Q^{I,J} := \{q_1, \ldots, q_{|Q^{I,J}|}\}$, and $R^{I,J} := \{r_1, \ldots, r_{|R^{I,J}|}\}$. Indices $p \in P^{I,J}$ yield a diagonal matrix with entries ρ_p. For such p, both I and J must contain index p. Indices $r \in R^{I,J}$ yield a block-diagonal matrix of the form $\begin{bmatrix} 0 & \sigma_r \\ -\sigma_r & 0 \end{bmatrix}$. For such r, both I and J must contain a pair of indices, $(K + 2r - 1, K + 2r)$. Finally, indices $q \in Q^{I,J}$ yield a diagonal matrix with entries of $\pm\sigma_q$ (sign can be + or −). For such q, I contains $K + 2q - 1$ or $K + 2q$, and J must contain the other. Note that there is no intersection between $Q^{I,J}$ and $R^{I,J}$.

If $Q^{I,J}$ is an empty set (i.e., $I = J$) then $\det(\boldsymbol{X}_{I,J}) = \det(\widehat{\boldsymbol{X}}_{I,J})$ and

$$
\det(\boldsymbol{X}_{I,J})\det(\boldsymbol{Z}_{Y,I})\det(\boldsymbol{Z}_{Y,J}) = \det(\widehat{\boldsymbol{X}}_I)\det(\boldsymbol{Z}_{Y,I})^2.
\tag{22}
$$

Thus, the terms in Eq. (18) in this case appear in Eq. (20). Now assume that $Q^{I,J} \neq \emptyset$ and consider the following set of pairs:

$$
\mathcal{S}(I,J) := \{(I',J') \ : \ P^{I,J} = P^{I',J'}, Q^{I,J} = Q^{I',J'}, R^{I,J} = R^{I',J'}\}.
$$

In other words, for $(I',J') \in \mathcal{S}(I,J)$, the diagonal $\boldsymbol{X}_{I',J'}$ contains ρ_p, $\begin{bmatrix} 0 & \sigma_r \\ -\sigma_r & 0 \end{bmatrix}$ exactly as in $\boldsymbol{X}_{I,J}$. However, the signs of the σ_q's may differ from $\boldsymbol{X}_{I,J}$. Combining this observation with the definition of $\widehat{\boldsymbol{X}}$,

$$
|\det(\boldsymbol{X}_{I',J'})| = |\det(\boldsymbol{X}_{I,J})| = \det(\widehat{\boldsymbol{X}}_I) = \det(\widehat{\boldsymbol{X}}_{I'}) = \det(\widehat{\boldsymbol{X}}_J) = \det(\widehat{\boldsymbol{X}}_{J'}).
\tag{23}
$$

Therefore,

$$
\sum_{(I',J')\in\mathcal{S}(I,J)} \det(\boldsymbol{X}_{I',J'})\det(\boldsymbol{Z}_{Y,I'})\det(\boldsymbol{Z}_{Y,J'})
\tag{24}
$$

$$
\leq \sum_{(I',J')\in\mathcal{S}(I,J)} |\det(\boldsymbol{X}_{I',J'})|\det(\boldsymbol{Z}_{Y,I'})\det(\boldsymbol{Z}_{Y,J'})
\tag{25}
$$

$$
= \det(\widehat{\boldsymbol{X}}_I) \sum_{(I',J')\in\mathcal{S}(I,J)} \det(\boldsymbol{Z}_{Y,I'})\det(\boldsymbol{Z}_{Y,J'})
\tag{26}
$$

$$
\leq \det(\widehat{\boldsymbol{X}}_I) \sum_{(I',*)\in\mathcal{S}(I,J)} \det(\boldsymbol{Z}_{Y,I'})^2
\tag{27}
$$

$$
= \sum_{(I',*)\in\mathcal{S}(I,J)} \det(\widehat{\boldsymbol{X}}_{I'})\det(\boldsymbol{Z}_{Y,I'})^2
\tag{28}
$$

where the third line comes from Eq. (23) and the fourth line follows from the rearrangement inequality. (Note that application of this inequality does not change the number of terms in the sum.)

Finally, we show that the number of nonzero terms in Eq. (18) is equal to the number of terms in Eq. (20). We will use $k := |Y|$ to denote the size of Y. Then the number of possible choices

of $\boldsymbol{X}_{I,J}$ such that $\det(\boldsymbol{X}_{I,J}) \neq 0$ (i.e., Eq. (21)) can be counted as follows: first choose i items in $\{\rho_1, \ldots, \rho_K\}$ for $i = 0, \ldots, k$; then, choose j items in $\left\{ \begin{bmatrix} 0 & \sigma_1 \\ -\sigma_1 & 0 \end{bmatrix}, \ldots, \begin{bmatrix} 0 & \sigma_{K/2} \\ -\sigma_{K/2} & 0 \end{bmatrix} \right\}$ for $j = 0, \ldots, \lfloor \frac{k-i}{2} \rfloor$; lastly, choose $k - i - 2j$ of $\{\pm \sigma_q; q \notin R^{I,J}\}$, then choose the sign for each of these (σ_q or $-\sigma_q$). Combining all of these choices, the total number of nonzero terms is:

$$\sum_{i=0}^{k} \underbrace{\binom{K}{i}}_{\text{choice of } \rho_p} \sum_{j=0}^{\lfloor \frac{k-i}{2} \rfloor} \underbrace{\binom{K/2}{j}}_{\text{choice of } \begin{bmatrix} 0 & \sigma_r \\ -\sigma_r & 0 \end{bmatrix}} \underbrace{\binom{K/2 - j}{k - i - 2j} 2^{k-i-2j}}_{\text{choice of } \pm \sigma_q} \tag{29}$$

$$= \sum_{i=0}^{k} \binom{K}{i} \binom{K}{k - i} \tag{30}$$

$$= \binom{2K}{k} \tag{31}$$

where the second line comes from the fact that $\binom{2n}{m} = \sum_{j=0}^{\lfloor \frac{m}{2} \rfloor} \binom{n}{j} \binom{n-j}{m-2j} 2^{m-2j}$ for any integers $n, m \in \mathbb{N}$ such that $m \leq 2n$ (see (1.69) in Quaintance (2010)), and the third line follows from the fact that $\sum_{i=0}^{r} \binom{m}{i} \binom{n}{r-i} = \binom{n+m}{r}$ for $n, m, r \in \mathbb{N}$ (Vandermonde's identity).

To summarize, for every $I, J \subseteq [2K]$ where $\det(\boldsymbol{X}_{I,J})$ is nonzero, there exists a collection $\mathcal{S}(I, J)$ such that the summation $\det(\boldsymbol{X}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J})$ over $\mathcal{S}(I, J)$ is upper-bounded by a summation over $\det(\widehat{\boldsymbol{X}}_I) \det(\boldsymbol{Z}_{Y,I})^2$. Since the number of nonzero terms in both Eq. (18) and Eq. (20) is identical, this yields that

$$\det(\boldsymbol{L}_Y) = \sum_{I,J} \det(\boldsymbol{X}_{I,J}) \det(\boldsymbol{Z}_{Y,I}) \det(\boldsymbol{Z}_{Y,J}) \leq \sum_{I} \det(\widehat{\boldsymbol{X}}_{I,I}) \det(\boldsymbol{Z}_{Y,I})^2 = \det(\widehat{\boldsymbol{L}}_Y) \tag{32}$$

and we conclude the proof of Theorem 1.

E.2 PROOF OF PROPOSITION 1

Proposition 1. *The tree-based sampling procedure* SAMPLEDPP *in Algorithm 3 runs in time* $O(K + k^3 \log M + k^4)$, *where k is the size of the sampled set[¶¶].*

Proof of Proposition 1. Since computing p_ℓ takes $O(k^2)$ from Eq. (12), and since the binary tree has depth $O(\log M)$, SAMPLEITEM in Algorithm 3 runs in $O(k^2 \log M)$ time. Moreover, the query matrix $\boldsymbol{Q}^Y$ can be updated in $O(k^3)$ time as it only requires a k-by-k matrix inversion. Therefore, the overall runtime of the tree-based elementary DPP sampling algorithm (after pre-processing) is $O(k^3 \log M + k^4)^{***}$. Combining this with elementary DPP selection (Line 15 in Algorithm 3), we can sample a set in $O(K + k^3 \log M + k^4)$ time.

E.3 PROOF OF THEOREM 2

Theorem 2. *Given an NDPP kernel $\boldsymbol{L} = \boldsymbol{V}\boldsymbol{V}^\top + \boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$ for $\boldsymbol{V}, \boldsymbol{B} \in \mathbb{R}^{M \times K}, \boldsymbol{D} \in \mathbb{R}^{K \times K}$, consider the proposal kernel $\widehat{\boldsymbol{L}}$ as proposed in Section 4.1. Let $\{\sigma_j\}_{j=1}^{K/2}$ be the positive eigenvalues obtained from the Youla decomposition of $\boldsymbol{B}(\boldsymbol{D} - \boldsymbol{D}^\top)\boldsymbol{B}^\top$. If $\boldsymbol{V} \perp \boldsymbol{B}$, then $\frac{\det(\widehat{\boldsymbol{L}}+\boldsymbol{I})}{\det(\boldsymbol{L}+\boldsymbol{I})} = \prod_{j=1}^{K/2} \left(1 + \frac{2\sigma_j}{\sigma_j^2 + 1}\right) \leq (1 + \omega)^{K/2}$, where $\omega = \frac{2}{K} \sum_{j=1}^{K/2} \frac{2\sigma_j}{\sigma_j^2 + 1} \in (0, 1]$.*

[¶¶]Computing p_ℓ via Eq. (12) improves on Gillenwater et al. (2019)'s $O(k^4 \log M)$ runtime for this step.

[***]Computing p_ℓ according to Eq. (12) improves on Gillenwater et al. (2019)'s $O(k^4 \log M)$ runtime.

Proof of Theorem 2. Since the column spaces of $\boldsymbol{V}$ and $\boldsymbol{B}$ are orthogonal, the corresponding eigenvectors are also orthogonal, i.e., $\boldsymbol{Z}^\top \boldsymbol{Z} = \boldsymbol{I}_{2K}$. Then,

$$\det(\boldsymbol{L} + \boldsymbol{I}) = \det(\boldsymbol{Z}\boldsymbol{X}\boldsymbol{Z}^\top + \boldsymbol{I}) = \det(\boldsymbol{X}\boldsymbol{Z}^\top\boldsymbol{Z} + \boldsymbol{I}_{2K}) = \det(\boldsymbol{X} + \boldsymbol{I}_{2K}) \tag{33}$$

$$= \prod_{i=1}^{K}(\rho_i + 1) \prod_{j=1}^{K/2} \det\left(\begin{bmatrix} 1 & \sigma_j \\ -\sigma_j & 1 \end{bmatrix}\right) \tag{34}$$

$$= \prod_{i=1}^{K}(\rho_i + 1) \prod_{j=1}^{K/2}(\sigma_j^2 + 1) \tag{35}$$

and similarly

$$\det(\widehat{\boldsymbol{L}} + \boldsymbol{I}) = \prod_{i=1}^{K}(\rho_i + 1) \prod_{j=1}^{K/2}(\sigma_j + 1)^2. \tag{36}$$

Combining Eqs. (35) and (36), we have that

$$\frac{\det(\widehat{\boldsymbol{L}} + \boldsymbol{I})}{\det(\boldsymbol{L} + \boldsymbol{I})} = \prod_{j=1}^{K/2} \frac{(\sigma_j + 1)^2}{(\sigma_j^2 + 1)} = \prod_{j=1}^{K/2}\left(1 + \frac{2\sigma_j}{\sigma_j^2 + 1}\right) \leq \left(1 + \frac{2}{K}\sum_{j=1}^{K/2}\frac{2\sigma_j}{\sigma_j^2 + 1}\right)^{K/2} \tag{37}$$

where the inequality holds from the Jensen's inequality. This completes the proof of Theorem 2.