Logical Equivariance in Diffusion Language Models

Sunwoo Hong[*‡ 1 2] **Seo Hyun Kim**[*‡ 1 2] **Chen-Hao Chao**[2] **Younwoo Choi**[2] **Se-Young Yun**[† 1]
Rahul G. Krishnan[† 2]

Abstract

Diffusion language models replace strict left-to-right generation with iterative denoising, but removing the generation order does not necessarily remove presentation dependence. We study this issue through logical equivariance (LE): whether a model gives consistent answers across correctness-preserving symmetries of the same logical state. We introduce SUDOKU-AC-ORBIT, an exact D_4-orbit benchmark that separates favorable-view competence from full-orbit reliability, and find large orbit gaps in both large dLLMs and controlled MDLM scaling. We identify a component-level certificate gap: row-major relative-score attention, including row-major RoPE, certifies exact D_4-equivariance only under a severe offset-class collapse. Finally, we show that Logical Trajectory Supervision improves raw competence but can amplify layout dependence, while combining it with explicit D_4 exposure gives the strongest high-competence presentation-stability tradeoff among our tested interventions.

1. Introduction

A structured problem inherently possesses more than one surface form (Cohen & Welling, 2016; Bronstein et al., 2021). A Sudoku board, for instance, can be rotated or reflected without altering its underlying logical constraints. Rather than memorizing a specific layout, a model that has truly internalized this logical state should transform its predictions accordingly. Standard accuracy metrics fail to capture this distinction, often rewarding models that solve a favorable one-dimensional serialization while failing on

equivalent presentations (Segura et al., 2016; Ribeiro et al., 2020).

Diffusion language models (dLLMs) make this distinction particularly relevant (Austin et al., 2021; Ou et al., 2024; Sahoo et al., 2024; Shi et al., 2024; Nie et al., 2025; Ye et al., 2025). By replacing strict left-to-right generation with iterative masked denoising, dLLMs relax the causal order imposed by text serialization (Liu et al., 2024; Kim et al., 2025; Peng et al., 2025; Kim et al., 2026; Ni et al., 2026). This raises a natural hypothesis: freed from causal decoding constraints, dLLMs might become less tethered to the row-major presentation of structured objects. We test this hypothesis directly.

We introduce SUDOKU-AC-ORBIT, a correctness-preserving benchmark designed to measure *logical equivariance* (LE), which evaluates the consistency of a model's answers across symmetric transformations (Seely et al., 2025). By evaluating each instance across the full D_4 orbit of rotations and reflections (Lu et al., 2022; Liu et al., 2023), we separate two quantities that ordinary accuracy conflates: favorable-view competence (success in at least one presentation) and full-orbit reliability (success across all equivalent views) (Cho et al., 2025). As illustrated in Figure 1, our evaluation of large dLLMs and controlled MDLMs reveals a pervasive "orbit gap." Models reliably solve states in canonical orientations but exhibit severe presentation bias across the full symmetry orbit.

To understand why this bias persists, we identify a component-level certificate gap in the underlying architecture. Our Row-major Toeplitz–D_4 Rigidity Theorem (Theorem 4.2) proves that a full, unmasked row-major relative-score attention head is exactly D_4-equivariant under a position-only action *only* if its offset-indexed score functions undergo a severe collapse into coarse D_4-offset classes. Consequently, sequence-distance-sensitive mechanisms such as row-major RoPE (Su et al., 2023) do not enforce the grid symmetry by construction. While this does not rule out learned equivariance in a full Transformer (Vaswani et al., 2023), it explains why non-autoregressive denoising alone cannot guarantee presentation stability.

Finally, we ask whether training can compensate for this missing architectural certificate. We find that scaling im-

---

[*]Equal contribution ; [†]Corresponding authors; [‡]Work done while visiting researchers at the University of Toronto, Vector Institute. [1]Graduate School of AI, KAIST, Daejeon, South Korea [2]University of Toronto, Vector Institute, Toronto, Canada. Correspondence to: Sunwoo Hong <sunwoo@kaist.ac.kr>, Seo Hyun Kim <shkimsally@kaist.ac.kr>.

Published as a paper at the 1st FoGen workshop, ICML 2026, Seoul, South Korea, 2026. Copyright 2026 by the author(s).

Figure 1. **Presentation Bias in Diffusion Language Models.** While dLLMs offer flexible generation orders, their reasoning remains sensitive to input formatting. **(Left)** For LLaDA-8B on a 4x4 Sudoku state, rotating the board by 90° completely alters the internal unmasking order, demonstrating a lack of structural invariance. **(Right)** Confidence levels for identical logical cells shift significantly across these views, **even though the underlying logical state and target uniqueness are strictly invariant under D_4 transformations.** This illustrates how high accuracy can be a byproduct of lucky 1D layouts rather than robust logical comprehension.

proves favorable-view competence but leaves a large orbit gap. Logical Trajectory Supervision (LTS) (Shah et al., 2024) enhances raw solving capacity yet can actively amplify view dependence. Explicit D_4 exposure alone yields limited gains, but combining it with trajectory supervision provides the strongest high-competence presentation-stability tradeoff in our intervention suite.

In summary, our contributions are:

- We introduce SUDOKU-AC-ORBIT, a correctness-preserving D_4-orbit benchmark that separates favorable-view competence from full-orbit reliability.

- We prove a component-level rigidity theorem for row-major relative-score attention, showing that exact D_4-equivariance requires a severe collapse of row-major offset dependence. Row-major RoPE is therefore not a D_4-equivariance certificate by itself.

- We show that competence-oriented supervision and view exposure affect different axes of reasoning: LTS improves raw competence but can worsen presentation stability, while $LTS + D_4$ gives the strongest high-competence robustness tradeoff among the tested interventions.

2. Related Work

Diffusion Language Models. Diffusion language models (Austin et al., 2021; Ou et al., 2024; Sahoo et al., 2024; Shi et al., 2024; Nie et al., 2025; Ye et al., 2025) replace left-to-right generation with iterative denoising, often using masked or discrete diffusion objectives. Recent large dLLMs such as LLaDA and Dream show that this family can scale to strong language (Gokaslan & Cohen, 2019), math (Cobbe et al., 2021; Hendrycks et al., 2021), and code (Chen et al., 2021) performance while allowing non-left-to-right refinement (Sahoo et al., 2024; Nie et al., 2025;

Ye et al., 2025; Ben-Hamu et al., 2025). Our question is different. We do not ask whether diffusion decoding (Wu et al., 2025; Wei et al., 2025) can produce a correct answer somewhere in a large candidate pool. We ask whether the same logical state is solved consistently under all equivalent presentations.

Equivariance and Structural Generalization. Equivariance (Cohen & Welling, 2016; Lee et al., 2019) ensures a model respects task symmetries. Group-equivariant networks enforce this architecturally by tying computations across rotations and reflections. We apply this principle to evaluate language models. Without assuming equivariance by design, we check if outputs remain equivariant after canonicalization across the Sudoku D_4 orbit. Failure implies predictions depend on the presentation view, not just the logical state.

1D Positional Geometry and Layout-Sensitive Reasoning. Because Transformers process objects as 1D sequences (Vaswani et al., 2023), positional mechanisms like RoPE (Su et al., 2023) do not natively certify 2D grid symmetries (Dosovitskiy et al., 2021; Cohen & Welling, 2016). Sudoku exposes this mismatch sharply: a horizontal offset of 1 becomes 9 under a 90° rotation. Our rigidity theorem formalizes this observation, proving that exact D_4-equivariance in row-major relative-score attention requires tying score functions across the induced D_4-offset classes.

Presentation Bias and Brittle Reasoning. Language model reasoning is notoriously sensitive to input presentation. Studies like GSM-Symbolic (Mirzadeh et al., 2025) and others (Lu et al., 2022) show that models fail when variables are renamed or premises are reordered, even if the underlying logic is identical. While these works expose brittleness in natural language, our work isolates this exact presentation bias in a zero-noise environment.

Figure 2. **Visualizing stochastic orbit metrics.** For each logical state, we estimate success under every D_4 view after canonicalizing predictions back to the original board. $C_{\max}$ captures best-view capacity, while $R_{\min}$ captures worst-view reliability. SLS measures the absolute gap between them, and sECR measures the fraction of best-view capacity retained in the worst view.

3. Logical Equivariance

We use logical equivariance (LE) as a measure of presentation stability. LE is distinct from correctness: a model can be equivariant and still be consistently wrong. Instead, LE asks whether the model's behavior depends on the underlying logical state or on a particular surface layout. For Sudoku, rotations and reflections preserve the logical problem. A presentation-stable model should therefore produce correspondingly transformed answers. If the same state is solved in one view but fails in another, the success is tied to presentation geometry rather than only to the puzzle logic.

3.1. Logical Equivariance Over a Finite Group

Let G be a finite group acting bijectively on inputs $\mathcal{X}$ and outputs $\mathcal{Y}$. In our benchmark, $G = D_4$, the eight rotations and reflections of a Sudoku board (Seely et al., 2025). We include an invalid parse symbol $\perp$, set $g\perp = \perp$, and write $\mathcal{Y}_\perp = \mathcal{Y} \cup \{\perp\}$. For a probability measure Q on $\mathcal{Y}_\perp$, the pushforward under g is

$$(g_\# Q)(B) = Q(g^{-1}B). \tag{1}$$

A deterministic decoder $D : \mathcal{X} \to \mathcal{Y}_\perp$ is logically equivariant if

$$D(gx) = gD(x) \qquad \forall g \in G, \ x \in \mathcal{X}. \tag{2}$$

For a stochastic predictor $K_\theta(\cdot \mid x)$, distributional logical equivariance requires

$$K_\theta(\cdot \mid gx) = g_\# K_\theta(\cdot \mid x) \qquad \forall g \in G, \ x \in \mathcal{X}. \tag{3}$$

This is the same commutation idea used in group-equivariant architectures, but we use it as an evaluation criterion rather than as an architectural constraint (Cohen & Welling, 2016).

For a fixed base state x, define the canonicalized output law under view g as

$$K_g^c(\cdot \mid x) := g_\#^{-1} K_\theta(\cdot \mid gx). \tag{4}$$

Distributional LE on the orbit of x is equivalent to

$$K_g^c(\cdot \mid x) = K_e^c(\cdot \mid x) \qquad \forall g \in G, \tag{5}$$

where e is the identity element of G. Thus, after transforming the input and mapping the output back to the canonical coordinate system, the view label should disappear.

3.2. Correctness-Preserving Orbit Metrics

Equivariance alone does not imply correctness, so we score every prediction after mapping it back to the same canonical output space. Let $y^\star(x) \in \mathcal{Y}$ be the unique correct canonical answer for base state x. Our benchmark construction ensures gold equivariance:

$$y^\star(gx) = gy^\star(x) \qquad \forall g \in G. \tag{6}$$

For stochastic decoding with M samples per view, we estimate the canonical success probability of view g as

$$\widehat{p}_g^M(x) = \frac{1}{M} \sum_{m=1}^{M} \mathbf{1}\left[g^{-1}Y_{g,m} = y^\star(x)\right],$$
$$Y_{g,m} \sim K_\theta(\cdot \mid gx). \tag{7}$$

The per-view success estimates $\{\widehat{p}_g^M(x)\}_{g \in G}$ are the basic quantities behind all orbit metrics.

We first report the average success over the orbit:

$$\text{MeanSucc}_M = \mathbb{E}_x\left[\frac{1}{|G|} \sum_{g \in G} \widehat{p}_g^M(x)\right]. \tag{8}$$

MeanSucc measures ordinary average performance across equivalent presentations. However, two models can have the same MeanSucc while behaving very differently across the orbit. We therefore separate best-view capacity from worst-view reliability:

$$\widehat{C}_{\max}^M(x) = \max_{g \in G} \widehat{p}_g^M(x), \qquad \widehat{R}_{\min}^M(x) = \min_{g \in G} \widehat{p}_g^M(x). \tag{9}$$

Their dataset averages are

$$\widehat{C}_{\max}^M = \mathbb{E}_x\big[\widehat{C}_{\max}^M(x)\big], \qquad \widehat{R}_{\min}^M = \mathbb{E}_x\big[\widehat{R}_{\min}^M(x)\big]. \tag{10}$$

Here, $\widehat{C}_{\max}^M$ measures favorable-view capacity: can the model solve the state under at least one presentation? In contrast, $\widehat{R}_{\min}^M$ measures worst-view reliability: does that success survive the hardest equivalent presentation?

Table 1. **Summary of orbit metrics.** MeanSucc measures average performance, while $\widehat{C}_{\max}$ and $\widehat{R}_{\min}$ separate favorable-view capacity from worst-view reliability. SLS and sECR summarize logical equivariance.

Metric	Meaning	Desired
MeanSucc	Average success across views	↑
$\widehat{C}_{\max}$	Best-view capacity	↑
$\widehat{R}_{\min}$	Worst-view reliability	↑
SLS	Absolute layout-sensitivity gap	↓
sECR	Relative performance retention	↑

We summarize logical equivariance with two complementary quantities:

$$\text{SLS}_M = \widehat{C}_{\max}^M - \widehat{R}_{\min}^M,$$
$$\text{sECR}_M = \frac{\widehat{R}_{\min}^M}{\widehat{C}_{\max}^M}, \qquad (\widehat{C}_{\max}^M > 0). \tag{11}$$

SLS is the absolute layout-sensitivity gap. sECR is a normalized robustness ratio: among the model's best-view capacity, how much remains in the worst view? Robust models have low SLS and high sECR. We visualize these metrics in Figure 2.

When $M = 1$, these stochastic metrics reduce to their deterministic counterparts. MeanSucc becomes standard per-view Accuracy (ACC), while the extreme capacities reduce to the familiar ANY and ALL metrics:

$$\widehat{C}_{\max}^1(x) = \text{ANY}(x), \qquad \widehat{R}_{\min}^1(x) = \text{ALL}(x). \tag{12}$$

Thus, the deterministic ANY–ALL gap is the one-sample equivalent of SLS. To summarize deterministic robustness across the dataset (e.g., for single-shot evaluations), we report canonical logical equivariance (cLE), defined as the ratio of expected ALL to expected ANY:

$$\text{cLE} = \frac{\mathbb{E}[\text{ALL}(x)]}{\mathbb{E}[\text{ANY}(x)]}. \tag{13}$$

In the rest of the paper, we use the stochastic metrics for sampled diffusion decoding and report deterministic ANY/ALL and cLE only when evaluating a single realized decode. We summarize all proposed orbit metrics and their diagnostic roles in Table 1.

4. Method

We separate two distinct goals in reasoning evaluation: *solver competence* (if the model can solve the problem at all) and *logical equivariance* or LE (if it solves the exact same logical state consistently, regardless of how it is rotated or reflected).

This distinction is important because training recipes often improve one metric without the other. For instance, training the model exclusively on logically sound reasoning paths (Logical Trajectory Supervision, LTS) boosts raw success, but it does not inherently force the model to treat equivalent geometric views identically. We use LTS to establish a strong competence baseline, which allows us to isolate and explicitly test true presentation stability.

4.1. SUDOKU-AC-ORBIT: A Forced-Target Test

We evaluate on anchored-completion states, $x_{\text{AC}}(A, U, R)$, where A are visible clues, U are target cells, and R are unresolved blanks. We filter these states so that the target cells U have exactly one logically valid digit based on A:

$$\{s_U : s \in \mathcal{S}(A)\} = \{s_U^\star\}. \tag{14}$$

Because Sudoku's rules are symmetric under D_4 rotations and reflections, if a target is forced in the standard view, it remains forced in every transformed view. We formally prove this bijection in Appendix A.1. This ensures that a performance drop on a rotated board is not caused by a changed or ambiguous logical target. The logical target is the same; only the presentation has changed.

4.2. The Intervention Suite: Trajectory Quality Versus View Exposure

We employ a suite of post-training interventions as diagnostic probes. Our goal is to disentangle two potential drivers of stable reasoning: the *logical quality* of the training trajectory and the *geometric diversity* of the input presentation. By comparing these interventions, we can determine whether equivariance emerges naturally from high-quality reasoning or requires explicit geometric supervision.

Marginal CE baselines. These baselines serve as our control group to test whether simply seeing more views is enough to induce stability. All marginal Cross-Entropy (CE) models are trained using random masking on non-anchor cells. *Canonical SFT* (Zhao et al., 2025) trains only on the original dataset in its fixed, standard orientation. This serves as a baseline to measure the presentation bias that emerges when the model is never exposed to alternative geometric views during training. *Random-D_4 SFT* exposes the model to the full symmetry group by applying a randomly sampled dihedral transformation to each instance. Unlike the canonical version, this approach ensures the model sees all eight possible orientations throughout training, though they are shuffled randomly across different batches. *Random-D_4 grouped* further enforces geometric consistency by grouping all eight transformed views of a single puzzle into the same batch. By calculating a joint averaged loss over the entire orbit simultaneously, this variant explicitly encourages the model to learn a more unified representation of the underlying logical state. Crucially, these baselines provide no

explicit guidance on the reasoning process itself, allowing us to isolate the effect of view exposure from trajectory quality.

Logical Trajectory Supervision (LTS). LTS (Shah et al., 2024) supervises the model on partial boards that follow a valid, step-by-step solving order. This ensures the model learns the causal structure of logical deduction rather than just static pattern completion. Starting from the initial clues A_0, we use an offline Sudoku oracle to iteratively construct a reasoning trajectory. At each step t, the oracle identifies the "logical frontier" F_t (the set of cells immediately implied by A_t via one-wave deduction). The anchor set is then expanded:

$$F_t = \mathcal{O}_{1\text{wave}}(s^\star, A_t), \qquad A_{t+1} = A_t \cup F_t. \quad (15)$$

For steps where no immediate one-wave deductions are available, a higher-order solver completes the expansion to ensure a full, well-defined sequence.

The training objective at each step t is to predict the entire hidden board from the partial state x_t (where only A_t is visible):

$$\mathcal{L}_{\text{LTS}} = \frac{1}{|\mathcal{C} \setminus A_t|} \sum_{i \in \mathcal{C} \setminus A_t} \text{CE}\left(p_\theta(\cdot \mid x_t)_i, s_i^\star\right), \quad (16)$$

where $\mathcal{C}$ is the set of all 81 cells. This formulation ensures that while the oracle provides a structured sequence of logical states, the model still receives a dense supervision signal over all masked cells.

LTS+D_4. To test what actually improves LE, we compare LTS against LTS+D_4 (LTS applied across the full D_4 orbit). The goal of this comparison is to answer a specific question: when the reasoning trajectory is already logically sound, does view exposure further reduce sensitivity to layout shifts?

4.3. View Leakage: What LE Failure Leaves Behind

If a model's prediction changes when the board is rotated, its canonicalized output retains information about the hidden rotation. We call this *view leakage*.

Fix a base state x. Sample a hidden rotation V, generate an answer from Vx, and pull the answer back to canonical coordinates: $Y^c = V^{-1}Y$. Let $P_g = K_g^c(\cdot \mid x)$ be the canonicalized output law under view g, and let $\overline{P} = m^{-1} \sum_{g \in G} P_g$. The KL view leakage is:

$$L_{\text{out}}(x) = I(V; Y^c) = \frac{1}{m} \sum_{g \in G} D_{\text{KL}}(P_g \| \overline{P}). \quad (17)$$

We decompose this leakage into a view spectrum across the irreducible representations ρ of G. Write $r_g = dP_g/d\overline{P}$

and $\widehat{r}_\rho(y) = m^{-1} \sum_{g \in G} r_g(y)\rho(g)^*$. The nontrivial view spectrum is:

$$\chi_G^2(x) = \sum_{\rho \neq \mathbf{1}} d_\rho \int \|\widehat{r}_\rho(y)\|_{\text{HS}}^2 \, d\overline{P}(y). \quad (18)$$

Theorem 4.1 (Output view spectrum)**.** *For each fixed x,*

$$\chi_G^2(x) = \int \frac{1}{m} \sum_{g \in G} (r_g(y) - 1)^2 \, d\overline{P}(y). \quad (19)$$

Moreover, there are constants $0 < a_m \leq b_m < \infty$, depending only on $m = |G|$, such that:

$$a_m \chi_G^2(x) \leq L_{\text{out}}(x) \leq b_m \chi_G^2(x). \quad (20)$$

Practical Meaning. This theorem provides a mathematical diagnostic tool: any presentation bias leaves a measurable geometric signature in the nontrivial group modes of the output distribution. Appendix A.2 also proves that high ANY with low ALL forces nonzero view leakage. Since full-joint leakage is intractable to measure in large models, we use token-marginal leakage and view-classifiers as empirical proxies to detect retained presentation information.

4.4. Why Standard 1D Position Does Not Certify LE

Group-equivariant architectures enforce symmetry by construction. Our setting is different: we ask whether a standard row-major positional attention component provides a certificate for the D_4 symmetries of a two-dimensional grid. The answer is negative unless the row-major relative score collapses to very coarse offset classes.

Let $\Lambda_n := \{0, \ldots, n-1\}^2$, $p(r, c) := nr + c$, and define the row-major offset $d(u, v) := p(v) - p(u)$. Let D_4 act on Λ_n, and let Π_g denote the induced position-only permutation, meaning $(\Pi_g Z)_{gu} = Z_u$.

Theorem 4.2 (Exact rigidity of row-major relative-score attention)**.** *Consider a full, unmasked self-attention head with logits $L_{uv}(Q, K) = \ell_{d(u,v)}(Q_u, K_v)$, where ℓ_d is a finite scalar scoring function. The attention output $\text{Att}_\ell(Q, K, V)$ is exactly D_4-equivariant under the position-only action Π_g for all Q, K, V if and only if:*

$$\ell_{d(gu, gv)}(q, k) = \ell_{d(u,v)}(q, k)$$

for every $g \in D_4$, every $u, v \in \Lambda_n$, and all q, k.

Consequently, for the 9×9 Sudoku grid ($n = 9$), the score functions must collapse to three coarse classes:

$$\ell_d = \begin{cases} \ell_0, & d = 0, \\ \ell_E, & d \neq 0, \ d \equiv 0 \pmod 2, \\ \ell_O, & d \equiv 1 \pmod 2. \end{cases}$$

Table 2. **Presentation bias in large-scale diffusion models.** Evaluated on SUDOKU-AC-ORBIT (values are percentages). ANY measures favorable-view capacity, while ALL measures true orbit competence across the D_4 group. All models exhibit a significant gap between best-view and orbit-consistent performance, highlighting that scale alone does not resolve geometric sensitivity.

Model	Window	Acc. ↑	ANY ↑	ALL ↑	cLE ↑
LLaDA-8B	AC16	49.7	97.7	1.8	1.8
LLaDA-8B	AC24	20.3	75.2	0.1	0.1
LLaDA-8B	AC32	3.9	24.9	0.0	0.0
Dream-7B	AC24	89.3	100.0	53.8	53.8
Dream-7B	AC32	68.0	98.9	17.4	17.6

Corollary 4.3 (Bilinear relative attention and row-major RoPE). *If the relative score has the bilinear-affine form $\ell_d(q, k) = q^\top M_d k + b_d$, exact D_4-equivariance requires $M_{d(gu,gv)} = M_{d(u,v)}$. Standard row-major RoPE uses $M_d = R_d$. Therefore, a nondegenerate row-major RoPE head that distinguishes offsets in the same D_4-offset class (e.g., $R_1 \neq R_9$) does not by itself certify exact D_4-equivariance on a 9×9 grid.*

Practical meaning. The theorem isolates a component-level certificate gap. It demonstrates that a standard row-major relative-score attention head does not enforce the D_4 symmetry of a grid by construction unless its offset dependence collapses to the theorem's coarse classes. Because the architecture provides no geometric guarantee, any presentation stability must be entirely learned from data. Thus, non-autoregressive denoising alone should not be expected to automatically remove layout bias. This motivates our empirical question: whether scale, trajectory supervision, or explicit orbit exposure can recover this missing stability in practice.

5. Experiments

Our experiments are designed to rigorously test one core claim: *solver competence* (raw solving ability) and *logical equivalance* (presentation stability) are distinct axes of reasoning. We therefore report raw capacity and orbit consistency separately, structuring our analysis around three primary questions:

1. Do large off-the-shelf dLLMs naturally acquire presentation-stable reasoning?

2. Does scaling the model parameters inherently close the presentation gap?

3. How do trajectory-based supervision (LTS) and explicit geometric exposure (D_4) independently and jointly affect presentation stability?

Figure 3. **Scaling Fails to Close the Orbit Gap (AC24).** Increasing the model scale improves favorable-view capacity (ANY), but the full-orbit competence (ALL) remains strictly bottlenecked. This empirical gap demonstrates that the presentation bias persists regardless of model scale.

We place pass-style candidate diagnostics, smoothing details for leakage estimates, and hyperparameters in the appendix to focus the main text on presentation stability.

5.1. Protocol

Data. We use the KAGGLE-3M Sudoku dataset (Radcliffe, 2018). We allocate 500 unique puzzles for the test set, which are augmented across all 8 dihedral views to create a total of 4,000 test instances for our main benchmark. Additionally, we set aside 2,000 puzzles for validation and 80,000 puzzles specifically for the post-training interventions. The remainder of the dataset, approximately 2.9 million puzzles, is used for pretraining. This setup ensures that the model's logical equivalance is evaluated across a robust and diverse set of logical states while maintaining a strict separation between training and evaluation instances.

Benchmark. The primary diagnostic benchmark is SUDOKU-AC-ORBIT. To construct these anchored completion (AC) states, we pair each base puzzle with a deterministic solver trace $s_1, s_2, \ldots, s_m$. For a chosen trace index t and window length k, we define the visible anchors as $A_t = \text{givens} \cup \{s_1, \ldots, s_{t-1}\}$ and the target cells as $U_t = \{s_t, \ldots, s_{t+k-1}\}$. The model is tasked to complete the logically forced targets in U_t, while all remaining cells are treated as unknown. We denote this setting as ACk (e.g., AC16, AC24).

Crucially, we use the AC settings to evaluate the baseline reasoning stability of pretrained and non-post-trained models. For the main results concerning post-training interventions, however, we evaluate models on the full completion task, where the model must fill all original blanks in the puzzle.

Table 3. **Controlled MDLM scaling on SUDOKU-AC-ORBIT.** Scaling improves raw solver competence (MeanSucc^{16} and $\widehat{R}^{16}_{\min}$), but full-orbit one-shot competence (ALL^1) remains bottlenecked at 2–3%. Token view leakage decreases slightly with scale but persists, confirming that scaling alone does not eliminate structural presentation bias.

| Params | Window | One sample / view | | | $K = 16$ samples / view | | | | Leakage |
		ANY^1 ↑	ALL^1 ↑	cLE^1 ↑	MeanSucc^{16} ↑	$\widehat{R}^{16}_{\min}$ ↑	sECR^{16} ↑	SLS^{16} ↓	$\widehat{L}_{\text{tok}}$ ↓
5M	AC16	66.49	0.12	0.18	16.87	6.18	20.53	23.91	0.096
5M	AC24	57.24	0.05	0.09	12.76	3.69	14.89	21.07	0.097
10M	AC16	84.03	1.27	1.51	30.13	16.20	35.52	29.41	0.083
10M	AC24	80.02	0.84	1.05	26.31	12.88	31.08	28.56	0.085
50M	AC16	88.79	2.86	3.22	36.27	21.61	41.24	30.79	0.076
50M	AC24	86.07	2.14	2.48	32.85	18.71	38.53	29.86	0.077
100M	AC16	87.32	2.55	2.92	34.61	20.32	40.61	29.72	0.076
100M	AC24	84.68	1.90	2.25	31.07	17.24	37.15	29.16	0.077

All evaluations are conducted across all eight D_4 views, with predictions canonicalized before scoring to ensure a rigorous measure of logical equivariance.

Models. We evaluate two large dLLMs, LLaDA-8B (Nie et al., 2025) and Dream-7B (Ye et al., 2025), to test whether large-scale masked diffusion naturally acquires presentation-stable reasoning. We also train controlled MDLMs from scratch on KAGGLE-3M with four scales (5M, 10M, 50M, and 100M parameters) to isolate scaling effects from post-training interventions. For MDLM pretraining, we use DiT backbones with SUBS parameterization and sequence length 81. The maximum training steps are scale-dependent: 500K(5M, 10M, 50M), and 700k (100M). For all models, we selected the best checkpoint based on validation performance. The global batch size is 512 for 5M/10M/50M and 256 for 100M. For sampling-based evaluation, we fix the random seed to 0.

Metrics. To clearly decouple raw solver competence from presentation stability, we categorize our metrics into three analytical axes.

1. Competence (Raw Capacity): For deterministic decoding, we report Acc (average per-view accuracy) and ANY (solved in at least one view). For stochastic decoding ($K = 16$ samples per view), we report mean success (MeanSucc$_{16}$) and best-view capacity ($\widehat{C}^{16}_{\max}$).

2. Logical Equivariance (Presentation Stability): To evaluate how consistently the model solves puzzles across views, we report deterministic orbit competence (ALL) and canonical logical equivariance (cLE). For stochastic decoding, we measure worst-view reliability ($\widehat{R}^{16}_{\min}$), stochastic orbit

consistency (sECR$_{16}$), and the success spread (SLS$_{16}$):

$$\text{sECR}_{16} = \frac{\mathbb{E}[\widehat{R}^{16}_{\min}(x)]}{\mathbb{E}[\widehat{C}^{16}_{\max}(x)]},$$

$$\text{SLS}_{16} = \mathbb{E}\left[\widehat{C}^{16}_{\max}(x) - \widehat{R}^{16}_{\min}(x)\right]. \quad (21)$$

To detect retained bias in the output distribution, we report token-marginal view leakage ($\widehat{L}_{\text{tok}}(x)$), which measures the KL divergence between view-specific and orbit-average token distributions:

$$\widehat{L}_{\text{tok}}(x) = \frac{1}{|U|} \sum_{i \in U} \frac{1}{|G|} \sum_{g \in G} D_{\text{KL}}\left(\widehat{p}_{g,i} \| \widehat{\overline{p}}_i\right). \quad (22)$$

3. Robustness (Diagnostic Gaps): To separate true structural bias from statistical extrema noise inherent in finite sampling, we evaluate against a canonical pseudo-orbit (Section 5.5) and define:

$$\text{RobustGap} = \widehat{R}^{16,\text{real}}_{\min} - \widehat{R}^{16,\text{pseudo}}_{\min},$$

$$\text{SLSGap} = \text{SLS}^{\text{real}}_{16} - \text{SLS}^{\text{pseudo}}_{16}. \quad (23)$$

A negative RobustGap and a positive SLSGap collectively confirm that the observed fragility is driven by genuine structural blind spots rather than sampling noise.

5.2. Large dLLMs Show Capacity Without Presentation Stability

We first test the optimistic hypothesis that large diffusion models naturally become presentation-stable due to their flexible generation order. If true, favorable-view capacity (ANY) and orbit competence (ALL) would be nearly identical, because the underlying logical constraints are strictly invariant across all eight D_4 transformations.

Table 2 shows the opposite. LLaDA-8B (Nie et al., 2025) successfully solves many states when presented in a lucky

Table 4. **Evaluating post-training interventions for logical equivariance.** Combining trajectory supervision with explicit view exposure (LTS+D_4) provides the optimal robustness-aware tradeoff. Relative to LTS alone, this combined recipe significantly improves MeanSucc, worst-view reliability, and sECR, while drastically reducing the statistical robustness gaps.

Recipe	Competence			Logical Equivariance			Robustness	
	MeanSucc$^{16}\uparrow$	$\widehat{C}_{max}^{16}\uparrow$	$\widehat{R}_{min}^{16}\uparrow$	sECR$^{16}\uparrow$	SLS$^{16}\downarrow$	$\widehat{L}_{tok}\downarrow$	RobustGap$\uparrow$	SLSGap$\downarrow$
Pretrained	31.53	47.29	17.41	36.82	**29.88**	0.0775	**-0.51**	**1.24**
Canonical 80k	41.58	57.79	25.94	44.88	31.85	0.0712	-1.69	2.79
Canonical 10k	43.12	59.76	27.43	45.89	32.34	0.0714	-1.56	3.64
D_4	42.16	58.46	26.64	45.56	31.82	0.0709	-1.20	2.88
D_4 grouped	41.15	57.35	25.60	44.64	31.75	0.0709	-1.27	2.16
LTS	45.74	**65.81**	26.16	39.75	39.65	0.0783	-6.04	11.11
LTS+D_4	**47.00**	63.89	**30.50**	**47.74**	33.39	**0.0684**	-2.34	4.05

geometric layout (ANY), but fails catastrophically across the full orbit (ALL). While Dream-7B (Ye et al., 2025) demonstrates stronger raw accuracy, it still exhibits a massive 81.5% presentation gap (ANY minus ALL) on the harder AC32 window. This confirms that even highly capable dLLMs often rely on incidental 1D text layouts rather than true structural comprehension. Large-scale diffusion decoding, despite its flexibility, does not automatically certify logical equivariance.

5.3. Controlled MDLM Scaling

To eliminate language priors, formatting biases, and uncontrolled training noise present in off-the-shelf large models, we train symbolic MDLMs (Sahoo et al., 2024) from scratch, holding the data, corruption process, and evaluation strictly constant.

If scale alone resolved presentation sensitivity, both ANY and ALL would improve together. However, as Table 3 and Figure 3 clearly demonstrate, increasing parameters heavily inflates favorable-view capacity (ANY) but leaves a massive real-orbit gap. This indicates that while larger models become highly proficient at solving specific 1D layouts, scale alone does not foster true structural comprehension or eliminate geometric bias.

5.4. Post-Training Decouples Competence from Logical Equivariance

All models in Table 4 are fine-tuned from a pretrained 50M MDLM for 9,000 steps. To control for data scale, Canonical 10k and 80k SFT serve as base controls, while Random-D_4 SFT applies all eight symmetries to the 10k base puzzles. Crucially, our trajectory methods operate on a stricter budget. LTS filters the 10k puzzles to 4.6k strictly logically solvable instances, expanding them into 41k intermediate reasoning states. LTS+D_4 then augments these 41k states across the full D_4 orbit. Metrics are categorized into *Competence*, *Logical Equivariance*, and *Robustness* to decouple these

performance axes.

Table 4 demonstrates that competence and equivariance improve independently. Standard scaling (Canonical 80k) increases raw success but leaves large robustness gaps, while naive view exposure (D_4) yields only moderate equivariance gains. This decoupling is most evident in the LTS results. Focusing exclusively on reasoning paths yields the highest peak competence ($\widehat{C}_{max}^{16}$), yet it actively degrades presentation stability. Worst-view performance ($\widehat{R}_{min}^{16}$) remains weak, and performance volatility (SLS_{16}) alongside view leakage ($\widehat{L}_{tok}$) noticeably worsens.

$LTS + D_4$ reduces this imbalance. It does not maximize every metric: peak capacity is lower than LTS alone, and residual orbit gaps remain. However, it gives the best high-competence robustness tradeoff in our suite, improving MeanSucc, $\hat{R}_{min}^{16}$, sECR, and token view leakage relative to LTS. This suggests that trajectory supervision and view exposure address different failure modes: LTS improves logical competence, while D_4 exposure helps make that competence less presentation-dependent.

5.5. Real Orbit Versus Pseudo-Orbit

Because taking the minimum or maximum over eight views with finite samples ($K = 16$) naturally introduces statistical extrema bias, we use a canonical pseudo-orbit to verify that our observed presentation sensitivity is not a statistical artifact. As described in Section 5.1, we define *RobustGap* and *SLSGap* to rigorously isolate true structural bias from sampling noise.

For a model to be considered truly equivariant, its performance should be indistinguishable from the pseudo-orbit baseline, resulting in gaps near zero. A distinctly *negative RobustGap* indicates that the model's failure on rotated views is genuinely worse than what random chance predicts, while a *positive SLSGap* confirms that the performance volatility is driven by layout sensitivity rather than finite-sample variance.

As shown in Table 4, despite its high raw competence, LTS yields a massive RobustGap (-6.04%) and SLSGap (11.11%). $LTS + D_4$ substantially reduces these gaps relative to LTS (e.g., SLSGap drops to 4.05%), indicating that explicit orbit exposure mitigates layout-dependent volatility. The remaining gap shows that the intervention improves, but does not fully certify, presentation stability.

5.6. Experimental Takeaways

Our results separate the factors driving reasoning performance:

- Scaling up parameters dramatically improves favorable-view capacity, but leaves the model fundamentally sensitive to presentation shifts.

- Logical Trajectory Supervision (LTS) delivers the strongest raw competence gain by ensuring the model learns only from mathematically sound steps.

- However, LTS alone does not prevent the model from overfitting to the canonical layout. Combining it with view exposure (LTS+D_4) yields the best overall performance.

The strongest recipe is not simply more augmentation, nor is it stronger local supervision alone. It is their combination: LTS supplies a sound reasoning path, and D_4 exposure ensures it is geometrically stable.

6. Limitations & Discussion

SUDOKU-AC-ORBIT isolates logical equivariance within a strictly symmetric, zero-noise domain. While this exactness cleanly exposes presentation bias without linguistic confounders, extending LE evaluation to domains with softer equivalences will require task-specific semantic canonicalization. Theoretically, our rigidity theorem is intentionally component-level. It establishes that standard row-major attention lacks a geometric certificate by construction, leaving the characterization of full multi-layer Transformer dynamics as an important theoretical next step. Finally, while $LTS + D_4$ provides the strongest high-competence robustness tradeoff without architectural modifications, fully eliminating layout sensitivity may ultimately require natively spatial architectures, explicit equivariance losses, or D_4-aware positional mechanisms.

7. Conclusion

We introduced SUDOKU-AC-ORBIT to explicitly separate solver competence from logical equivariance. Across large dLLMs and controlled MDLM scaling, models often solve a logical state in a favorable presentation but fail to do so consistently across its full D_4 orbit. Our theory grounds this empirical gap in a component-level certificate gap: standard sequence-distance-sensitive mechanisms, such as row-major RoPE, do not enforce grid symmetries by construction unless their offset dependence collapses. This explains why arbitrary-order denoising and higher raw success do not, by themselves, guarantee presentation-stable structured reasoning.

Our post-training interventions demonstrate that competence and equivariance can move in different directions. While Logical Trajectory Supervision (LTS) improves raw solving capacity, it can simultaneously increase layout dependence. Combining it with explicit D_4 exposure yields the strongest high-competence robustness tradeoff among our tested recipes. More broadly, our results argue that structured reasoning systems should be evaluated not only by whether they solve a favorable presentation, but by whether their solutions remain stable over the invariant quotient structure of the task.

Acknowledgements

RGK gratefully acknowledges support from the Canada Research Chairs Program (CRC-2022-00049) and the Canada CIFAR AI Chairs Program. This research was funded in part by a NFRF Special Call Award (NFRFR-2022-00526) and NSERC Discovery Grant (RGPIN-2022-04546).

This work was supported in part by the Institute of Information & Communications Technology Planning & Evaluation (IITP) grant funded by the Korea government (MSIT) under the AI Excellence Global Innovative Leader Education Program (No. RS-2022-00143911), the AI Research Hub Project (No. RS-2024-00457882), and the Development of Goal-Oriented Reinforcement Learning Techniques for Contact-Rich Robotic Manipulation of Everyday Objects (No. RS-2022-II220311).

References

Austin, J., Johnson, D. D., Ho, J., Tarlow, D., and Van Den Berg, R. Structured denoising diffusion models in discrete state-spaces. *Advances in neural information processing systems*, 34:17981–17993, 2021.

Ben-Hamu, H., Gat, I., Severo, D., Nolte, N., and Karrer, B. Accelerated sampling from masked diffusion models via entropy bounded unmasking. *arXiv preprint arXiv:2505.24857*, 2025.

Bronstein, M. M., Bruna, J., Cohen, T., and Veličković, P. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges, 2021. URL https://arxiv.org/abs/2104.13478.

Chen, M., Tworek, J., Jun, H., Yuan, Q., Pinto, H. P. D. O., Kaplan, J., Edwards, H., Burda, Y., Joseph, N., Brockman, G., et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Cho, S., Ruberto, S., and Terragni, V. Metamorphic testing of large language models for natural language processing. In *2025 IEEE International Conference on Software Maintenance and Evolution (ICSME)*, pp. 174–186. IEEE, 2025. doi: 10.1109/icsme64153.2025.00025. URL http://dx.doi.org/10.1109/ICSME64153.2025.00025.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Cohen, T. S. and Welling, M. Group equivariant convolutional networks, 2016. URL https://arxiv.org/abs/1602.07576.

Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N. An image is worth 16x16 words: Transformers for image recognition at scale, 2021. URL https://arxiv.org/abs/2010.11929.

Gokaslan, A. and Cohen, V. OpenWebText corpus. http://Skylion007.github.io/OpenWebTextCorpus, 2019. Accessed: 2025-05-16.

Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., and Steinhardt, J. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Kim, J., Shah, K., Kontonis, V., Kakade, S., and Chen, S. Train for the worst, plan for the best: Understanding token ordering in masked diffusions. *arXiv preprint arXiv:2502.06768*, 2025.

Kim, S. H., Hong, S., Jung, H., Park, Y., and Yun, S.-Y. Klass: Kl-guided fast inference in masked diffusion models, 2026. URL https://arxiv.org/abs/2511.05664.

Lee, J., Lee, Y., Kim, J., Kosiorek, A. R., Choi, S., and Teh, Y. W. Set transformer: A framework for attention-based permutation-invariant neural networks, 2019. URL https://arxiv.org/abs/1810.00825.

Liu, N. F., Lin, K., Hewitt, J., Paranjape, A., Bevilacqua, M., Petroni, F., and Liang, P. Lost in the middle: How language models use long contexts, 2023. URL https://arxiv.org/abs/2307.03172.

Liu, S., Nam, J., Campbell, A., Stärk, H., Xu, Y., Jaakkola, T., and Gómez-Bombarelli, R. Think while you generate: Discrete diffusion with planned denoising. *arXiv preprint arXiv:2410.06264*, 2024.

Lu, Y., Bartolo, M., Moore, A., Riedel, S., and Stenetorp, P. Fantastically ordered prompts and where to find them: Overcoming few-shot prompt order sensitivity, 2022. URL https://arxiv.org/abs/2104.08786.

Mirzadeh, I., Alizadeh, K., Shahrokhi, H., Tuzel, O., Bengio, S., and Farajtabar, M. Gsm-symbolic: Understanding the limitations of mathematical reasoning in large language models, 2025. URL https://arxiv.org/abs/2410.05229.

Ni, Z., Wang, S., Yue, Y., Yu, T., Zhao, W., Hua, Y., Chen, T., Song, J., Yu, C., Zheng, B., and Huang, G. The flexibility trap: Why arbitrary order limits reasoning potential in diffusion language models, 2026. URL https://arxiv.org/abs/2601.15165.

Nie, S., Zhu, F., You, Z., Zhang, X., Ou, J., Hu, J., Zhou, J., Lin, Y., Wen, J.-R., and Li, C. Large language diffusion models, 2025. URL https://arxiv.org/abs/2502.09992.

Ou, J., Nie, S., Xue, K., Zhu, F., Sun, J., Li, Z., and Li, C. Your absorbing discrete diffusion secretly models the conditional distributions of clean data. *arXiv preprint arXiv:2406.03736*, 2024.

Peng, F. Z., Bezemek, Z., Patel, S., Rector-Brooks, J., Yao, S., Tong, A., and Chatterjee, P. Path planning for masked diffusion model sampling. *arXiv preprint arXiv:2502.03540*, 2025.

Radcliffe, N. J. 3 Million Sudoku Puzzles with Ratings. https://www.kaggle.com/datasets/radcliffe/3-million-sudoku-puzzles-with-ratings, 2018.

Ribeiro, M. T., Wu, T., Guestrin, C., and Singh, S. Beyond accuracy: Behavioral testing of NLP models with CheckList. In Jurafsky, D., Chai, J., Schluter, N., and Tetreault,

J. (eds.), *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4902–4912, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.442. URL https://aclanthology.org/2020.acl-main.442/.

Sahoo, S., Arriola, M., Schiff, Y., Gokaslan, A., Marroquin, E., Chiu, J., Rush, A., and Kuleshov, V. Simple and effective masked diffusion language models. *Advances in Neural Information Processing Systems*, 37:130136–130184, 2024.

Seely, J., Imajuku, Y., Zhao, T., Cetin, E., and Jones, L. Sudoku-bench: Evaluating creative reasoning with sudoku variants, 2025. URL https://arxiv.org/abs/2505.16135.

Segura, S., Fraser, G., Sanchez, A. B., and Ruiz-Cortés, A. A survey on metamorphic testing. *IEEE Transactions on Software Engineering*, 42(9):805–824, 2016. doi: 10.1109/TSE.2016.2532875.

Shah, K., Dikkala, N., Wang, X., and Panigrahy, R. Causal language modeling can elicit search and reasoning capabilities on logic puzzles, 2024. URL https://arxiv.org/abs/2409.10502.

Shi, J., Han, K., Wang, Z., Doucet, A., and Titsias, M. Simplified and generalized masked diffusion for discrete data. *Advances in neural information processing systems*, 37:103131–103167, 2024.

Su, J., Lu, Y., Pan, S., Murtadha, A., Wen, B., and Liu, Y. Roformer: Enhanced transformer with rotary position embedding, 2023. URL https://arxiv.org/abs/2104.09864.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., and Polosukhin, I. Attention is all you need, 2023. URL https://arxiv.org/abs/1706.03762.

Wei, Q., Zhang, Y., Liu, Z., Liu, D., and Zhang, L. Accelerating diffusion large language models with slowfast: The three golden principles. *arXiv preprint arXiv:2506.10848*, 2025.

Wu, C., Zhang, H., Xue, S., Liu, Z., Diao, S., Zhu, L., Luo, P., Han, S., and Xie, E. Fast-dllm: Training-free acceleration of diffusion llm by enabling kv cache and parallel decoding. *arXiv preprint arXiv:2505.22618*, 2025.

Ye, J., Xie, Z., Zheng, L., Gao, J., Wu, Z., Jiang, X., Li, Z., and Kong, L. Dream 7b: Diffusion large language models, 2025. URL https://arxiv.org/abs/2508.15487.

Zhao, S., Gupta, D., Zheng, Q., and Grover, A. d1: Scaling reasoning in diffusion large language models via reinforcement learning, 2025. URL https://arxiv.org/abs/2504.12216.

A. Appendix

A. Additional Proofs and Protocol Details

All logarithms are natural. The group size is denoted by $m = |G|$. In the experiments, $G = D_4$ and $m = 8$. The output space includes the invalid parse symbol $\perp$, with $g\perp = \perp$. All probability statements below are for a fixed base logical state x unless stated otherwise.

A.1. Forced-target validity of SUDOKU-AC-ORBIT

This appendix proves the claim used in Section 4.1: if the target cells are forced in the canonical board, then the corresponding target cells are forced in every rotated or reflected view. This matters because then an accuracy drop under a transformed view cannot be explained by a harder or more ambiguous puzzle.

Let $\Lambda = \{1, \ldots, 9\}^2$ be the set of Sudoku cells. A completed Sudoku solution is a function $s : \Lambda \to \{1, \ldots, 9\}$ satisfying the row, column, and 3×3 box constraints. For a set of anchors A, let $\mathcal{S}(A)$ be the set of valid completed Sudoku grids that agree with the anchored digits. For $U \subseteq \Lambda$, write s_U for the restriction of s to U.

Proposition A.1 (Forced targets are preserved under D_4). *Let $g \in D_4$. Then*

$$\mathcal{S}(gA) = g\mathcal{S}(A) := \{gs : s \in \mathcal{S}(A)\}. \tag{24}$$

Consequently, if

$$\{s_U : s \in \mathcal{S}(A)\} = \{s_U^\star\}, \tag{25}$$

then

$$\{t_{gU} : t \in \mathcal{S}(gA)\} = \{(gs^\star)_{gU}\}. \tag{26}$$

Proof. Every element of D_4 is a rotation or reflection of the 9×9 square. It maps rows to rows or columns, columns to columns or rows, and 3×3 boxes to 3×3 boxes. Thus s satisfies the Sudoku constraints if and only if gs satisfies the Sudoku constraints. Also, s agrees with anchors A if and only if gs agrees with transformed anchors gA. Hence $\mathcal{S}(gA) = g\mathcal{S}(A)$.

If $t \in \mathcal{S}(gA)$, then by the first part there exists $s \in \mathcal{S}(A)$ with $t = gs$. Therefore $t_{gU} = (gs)_{gU} = g(s_U)$. Since $s_U = s_U^\star$ for all $s \in \mathcal{S}(A)$, the transformed restriction is always $(gs^\star)_{gU}$. This proves target uniqueness in every view. $\square$

A.2. View leakage and the output view spectrum

This appendix proves the two facts used in Section 4.3. First, zero view leakage is exactly distributional logical equivalence on the orbit of x. Second, the χ^2-version of view leakage decomposes exactly into the nontrivial Fourier modes of the group. The KL leakage L_{out} is not itself an exact Fourier norm; it is equivalent to that Fourier norm up to constants depending only on $|G|$.

Sample $V \sim \text{Unif}(G)$, generate $Y \sim K_\theta(\cdot \mid Vx)$, and canonicalize $Y^c = V^{-1}Y$. Let

$$P_g := g_\#^{-1} K_\theta(\cdot \mid gx), \qquad \overline{P} := \frac{1}{m} \sum_{g \in G} P_g. \tag{27}$$

Then the conditional law of Y^c given $V = g$ is P_g, and the marginal law of Y^c is $\overline{P}$.

Proposition A.2 (Zero leakage is distributional LE).

$$L_{\text{out}}(x) := I(V; Y^c) = \frac{1}{m} \sum_{g \in G} D_{\text{KL}}(P_g \| \overline{P}). \tag{28}$$

Moreover,

$$L_{\text{out}}(x) = 0 \iff P_g = P_h \quad \forall g, h \in G. \tag{29}$$

Proof. The joint law of (V, Y^c) is

$$\Pr(V = g, Y^c \in B) = \frac{1}{m} P_g(B). \tag{30}$$

The marginal law of Y^c is $\overline{P}$. Therefore

$$I(V; Y^c) = D_{\mathrm{KL}}\big(\Pr_{V,Y^c} \,\|\, \Pr_V \otimes \Pr_{Y^c}\big) = \frac{1}{m}\sum_{g\in G} D_{\mathrm{KL}}(P_g\|\overline{P}). \tag{31}$$

Mutual information is zero if and only if V and Y^c are independent. Since all views have positive probability, independence is equivalent to $P_g = \overline{P}$ for every g, which is equivalent to $P_g = P_h$ for all $g, h \in G$. $\qquad\square$

We now decompose the view dependence by irreducible representations. Let $\widehat{G}$ be a set of unitary irreducible representations of G. For $\rho \in \widehat{G}$, let d_ρ be its dimension. The trivial representation is denoted by $\mathbf{1}$.

Because $\overline{P}$ is an average containing each P_g, we have $P_g \ll \overline{P}$. Define

$$r_g(y) := \frac{dP_g}{d\overline{P}}(y). \tag{32}$$

Then $0 \le r_g(y) \le m$ for $\overline{P}$-almost every y, and

$$\frac{1}{m}\sum_{g\in G} r_g(y) = 1. \tag{33}$$

For each y, view $g \mapsto r_g(y)$ as a function on the group, and define its Fourier coefficient by

$$\widehat{r}_\rho(y) := \frac{1}{m}\sum_{g\in G} r_g(y)\rho(g)^*. \tag{34}$$

Theorem A.3 (Output view spectrum). *Define*

$$\chi_G^2(x) := \int \frac{1}{m}\sum_{g\in G}\big(r_g(y) - 1\big)^2 \, d\overline{P}(y). \tag{35}$$

Then

$$\chi_G^2(x) = \sum_{\rho\neq\mathbf{1}} d_\rho \int \|\widehat{r}_\rho(y)\|_{\mathrm{HS}}^2 \, d\overline{P}(y). \tag{36}$$

Furthermore, there exist constants $0 < a_m \le b_m < \infty$, depending only on $m = |G|$, such that

$$a_m\chi_G^2(x) \le L_{\mathrm{out}}(x) \le b_m\chi_G^2(x). \tag{37}$$

Proof. For each fixed y, apply the normalized Plancherel identity on the finite group:

$$\frac{1}{m}\sum_{g\in G}|f(g)|^2 = \sum_{\rho\in\widehat{G}} d_\rho\|\widehat{f}(\rho)\|_{\mathrm{HS}}^2, \qquad \widehat{f}(\rho) = \frac{1}{m}\sum_{g\in G} f(g)\rho(g)^*. \tag{38}$$

Use $f(g) = r_g(y)$. The trivial coefficient is

$$\widehat{r}_{\mathbf{1}}(y) = \frac{1}{m}\sum_{g\in G} r_g(y) = 1. \tag{39}$$

Thus Plancherel gives

$$\frac{1}{m}\sum_{g\in G}\big(r_g(y) - 1\big)^2 = \sum_{\rho\neq\mathbf{1}} d_\rho\|\widehat{r}_\rho(y)\|_{\mathrm{HS}}^2. \tag{40}$$

Integrating over $\overline{P}$ proves Eq. (36).

For the KL comparison, let

$$\varphi(t) := t\log t - t + 1, \qquad \varphi(0) := 1. \tag{41}$$

Since $\int r_g \, d\overline{P} = 1$,

$$D_{\mathrm{KL}}(P_g \| \overline{P}) = \int r_g \log r_g \, d\overline{P} = \int \varphi(r_g) \, d\overline{P}. \tag{42}$$

The ratio $\varphi(t)/(t-1)^2$, with value $1/2$ at $t = 1$ by continuous extension, is positive and finite on the compact interval $[0, m]$. Hence there are constants a_m, b_m such that

$$a_m(t-1)^2 \leq \varphi(t) \leq b_m(t-1)^2 \qquad \forall t \in [0, m]. \tag{43}$$

Apply this pointwise to $t = r_g(y)$, average over g, and integrate over $\overline{P}$. $\qquad \square$

The following proposition connects the spectrum to the correctness metrics. It is useful because it turns an observed Any–All gap into a lower bound on nontrivial view information.

Proposition A.4 (Orbit failure forces view leakage). *For deterministic decoding,*

$$L_{\mathrm{out}}(x) \geq h_2(1/m)\big(\mathrm{Any}(x) - \mathrm{All}(x)\big), \tag{44}$$

where $h_2(p) = -p \log p - (1-p) \log(1-p)$. For stochastic decoding, if $p_g(x) = P_g(\{y^\star(x)\})$, then

$$L_{\mathrm{out}}(x) \geq \frac{(C_{\max}(x) - R_{\min}(x))^2}{m}. \tag{45}$$

Proof. For deterministic decoding, $Y^c = \widehat{y}_V(x)$ is a deterministic function of V, so $L_{\mathrm{out}}(x) = H(Y^c)$. If $\mathrm{Any}(x) - \mathrm{All}(x) = 0$, the stated inequality is immediate. If the gap is one, then one canonicalized prediction equals the unique target and at least one does not. Hence Y^c is a nonconstant function of a uniform m-point variable. The minimum entropy of such a nonconstant image occurs when one fiber has size 1 and another has size $m - 1$, giving $H(Y^c) \geq h_2(1/m)$.

For stochastic decoding, let $C = \mathbf{1}[Y^c = y^\star(x)]$. Data processing gives $I(V; Y^c) \geq I(V; C)$. With $\overline{p} = m^{-1} \sum_g p_g$,

$$I(V; C) = \frac{1}{m} \sum_{g \in G} \mathrm{kl}(p_g \| \overline{p}). \tag{46}$$

Pinsker's inequality for Bernoulli laws gives $\mathrm{kl}(p_g \| \overline{p}) \geq 2(p_g - \overline{p})^2$. Let $\delta = C_{\max} - R_{\min}$. Choose views g_+, g_- attaining the maximum and minimum. Then

$$|p_{g_+} - \overline{p}| + |p_{g_-} - \overline{p}| \geq \delta, \tag{47}$$

and therefore

$$(p_{g_+} - \overline{p})^2 + (p_{g_-} - \overline{p})^2 \geq \delta^2/2. \tag{48}$$

Thus

$$L_{\mathrm{out}}(x) \geq I(V; C) \geq \frac{2}{m} \sum_g (p_g - \overline{p})^2 \geq \frac{\delta^2}{m}. \tag{49}$$

$\qquad \square$

A.3. Row-major Toeplitz–D_4 rigidity

This appendix proves the positional obstruction stated in Section 4.4. The statement is only about scalar pair kernels that depend on row-major offset. It is not an impossibility theorem for a full Transformer.

Let

$$\Lambda_n := \{0, \ldots, n-1\}^2, \qquad p(r, c) := nr + c. \tag{50}$$

A scalar row-major relative-position kernel has the form

$$B_{uv} = a_{p(v)-p(u)}. \tag{51}$$

Let $\mathcal{T}_n$ be the vector space of all such kernels. Let

$$\mathcal{C}_n := \{B : B_{gu,gv} = B_{uv} \; \forall g \in D_4, \; u, v \in \Lambda_n\} \tag{52}$$

be the space of D_4-invariant scalar pair kernels.

Theorem A.5 (Row-major Toeplitz–D_4 rigidity). *For $n \geq 2$,*

$$\dim(\mathcal{T}_n \cap \mathcal{C}_n) = \begin{cases} 2, & n \text{ even}, \\ 3, & n \text{ odd}. \end{cases} \tag{53}$$

More explicitly, if n is even, then every $B \in \mathcal{T}_n \cap \mathcal{C}_n$ has the form

$$B_{uv} = \alpha \mathbf{1}[p(v) - p(u) = 0] + \beta \mathbf{1}[p(v) - p(u) \neq 0]. \tag{54}$$

If n is odd, then every $B \in \mathcal{T}_n \cap \mathcal{C}_n$ has the form

$$B_{uv} = \alpha \mathbf{1}[d = 0] + \beta \mathbf{1}[d \neq 0 \text{ and } d \text{ even}] + \gamma \mathbf{1}[d \text{ odd}], \qquad d = p(v) - p(u). \tag{55}$$

In particular, for the 9×9 Sudoku grid, the certified row-major scalar relative-position algebra has only the three classes 0, nonzero-even, and odd.

Proof. For a pair of cells $u = (r, c)$ and $v = (r', c')$, define the displacement

$$(x, y) := (r' - r, c' - c), \qquad x, y \in \{-(n-1), \ldots, n-1\}. \tag{56}$$

The row-major offset is

$$\delta(x, y) := p(v) - p(u) = nx + y. \tag{57}$$

The group D_4 acts on displacements by sign changes and coordinate swaps:

$$(x, y) \mapsto (\pm x, \pm y), \qquad (x, y) \mapsto (\pm y, \pm x), \tag{58}$$

with the signs constrained by the chosen rotation or reflection.

The only subtle point is that the same offset may have several feasible displacement representations. For example, $nx + y = nx' + y'$ can hold with $(x, y) \neq (x', y')$. Define an equivalence relation $\sim$ on offsets by the following generators: two offsets are equivalent if they are the same integer, or if they arise from feasible displacements related by a D_4 transformation. Then $B \in \mathcal{T}_n \cap \mathcal{C}_n$ exactly means $a_d = a_{d'}$ whenever $d \sim d'$. Thus the dimension of $\mathcal{T}_n \cap \mathcal{C}_n$ is the number of equivalence classes of offsets.

First, offset 0 is a singleton class. If $nx + y = 0$ with $|x|, |y| \leq n - 1$, then $x \neq 0$ would imply $|nx| \geq n > |y|$, impossible. Hence $x = y = 0$.

Second, every nonzero offset is equivalent to one of $1, \ldots, n - 1$. By a $180°$ rotation, $d \sim -d$, so take $d > 0$. Write $d = nq + r$ with $0 \leq r \leq n - 1$. If $q = 0$, then $d = r \in \{1, \ldots, n - 1\}$. If $q \geq 1$ and $r = 0$, then

$$d = \delta(q, 0) \sim \delta(0, q) = q < d. \tag{59}$$

If $q \geq 1$ and $r > 0$, then

$$d = \delta(q, r) \sim \delta(q, -r) = nq - r < d. \tag{60}$$

Repeating this strict descent reaches a positive offset in $\{1, \ldots, n - 1\}$.

Third, for every $1 \leq k \leq n - 3$,

$$k \sim k + 2. \tag{61}$$

Indeed,

$$k = \delta(1, k - n) \tag{62}$$
$$\sim \delta(n - k, -1) \tag{63}$$
$$= n(n - k) - 1 \tag{64}$$
$$= \delta(n - k - 1, n - 1) \tag{65}$$
$$\sim \delta(-(n - k - 1), n - 1) \tag{66}$$
$$= \delta(-(n - k - 2), -1) \tag{67}$$
$$\sim \delta(1, k + 2 - n) \tag{68}$$
$$= k + 2. \tag{69}$$

All displacements used above lie in $[-(n-1), n-1]^2$ when $1 \le k \le n-3$.

Now suppose n is odd. Since

$$\delta(x, y) = nx + y \equiv x + y \pmod{2}, \tag{70}$$

and D_4 only changes signs and swaps coordinates, offset parity is invariant. By Eq. (61), all positive small odd offsets are equivalent and all positive small even offsets are equivalent. The descent argument then shows that all nonzero odd offsets form one class and all nonzero even offsets form one class. Together with the singleton class $\{0\}$, this gives three classes.

Finally suppose n is even. For $n = 2$, direct inspection gives $1 = \delta(0, 1) \sim \delta(1, 0) = 2$, so all nonzero offsets are equivalent. For $n \ge 4$,

$$1 = \delta(1, 1-n) \sim \delta(1, n-1) = 2n-1 = \delta(2, -1) \sim \delta(1, -2) = n-2. \tag{71}$$

The offset $n - 2$ is even. By Eq. (61), it is equivalent to 2. Hence $1 \sim 2$, so the odd and even nonzero classes merge. The descent argument then shows that all nonzero offsets form one class. Together with $\{0\}$, this gives two classes. $\qquad\square$

Consequence for 1D RoPE. Let M_d be the matrix used by a 1D relative positional component at row-major offset d. For fixed query/key contents a, b, the scalar positional term has form

$$B_{uv}^{a,b} = a^* M_{p(v)-p(u)} b. \tag{72}$$

If this scalar term is D_4-invariant for every a, b, then Theorem A.5 forces $M_d = M_{d'}$ whenever d and d' lie in the same offset class. On a 9×9 grid, this means all nonzero odd offsets must share the same matrix, including 1, 9, and -9. Standard nondegenerate 1D RoPE separates these offsets. Therefore row-major 1D RoPE does not provide a component-level scalar D_4 positional certificate.

This conclusion is deliberately limited. It does not say that a full Transformer with 1D RoPE cannot learn an equivariant function. It says that the standard scalar row-major positional component does not enforce the certificate by itself.

A.4. Row-major relative-score attention rigidity

This appendix proves the positional certificate result stated in Section 4.4. The result is deliberately component-level: it concerns a full, unmasked attention head whose logits are indexed by row-major relative offset. It is not an impossibility theorem for full multi-layer Transformers.

Let

$$\Lambda_n := \{0, \ldots, n-1\}^2, \qquad p(r, c) := nr + c,$$

and define the row-major offset

$$d(u, v) := p(v) - p(u).$$

Let D_4 act on Λ_n, and let Π_g denote the induced position-only permutation, with the convention

$$(\Pi_g Z)_{gu} = Z_u.$$

The action permutes positions only and does not transform hidden channels.

We first record the offset-class fact used in the main theorem.

Lemma A.6 (Row-major Toeplitz–D_4 offset classes). *Let $\sim$ be the equivalence relation on row-major offsets generated by*

$$d(u, v) \sim d(gu, gv) \qquad \text{for all } g \in D_4, \ u, v \in \Lambda_n.$$

Then, for $n \ge 2$, the offset 0 is a singleton class. For nonzero offsets:

$$\begin{cases} \text{all nonzero offsets form one class,} & n \text{ even,} \\ \text{all nonzero-even offsets form one class and all odd offsets form one class,} & n \text{ odd.} \end{cases}$$

In particular, for $n = 9$, any row-major offset-indexed object that is constant on D_4-related cell pairs must have the form

$$a_d = \begin{cases} a_0, & d = 0, \\ a_E, & d \ne 0, \ d \equiv 0 \pmod{2}, \\ a_O, & d \equiv 1 \pmod{2}. \end{cases}$$

Proof. For a pair of cells $u = (r, c)$ and $v = (r', c')$, write the displacement as

$$(x, y) := (r' - r, c' - c), \qquad x, y \in \{-(n-1), \ldots, n-1\}.$$

The row-major offset is

$$\delta(x, y) := p(v) - p(u) = nx + y.$$

The group D_4 acts on displacements by coordinate swaps and sign changes:

$$(x, y) \mapsto (\pm x, \pm y), \qquad (x, y) \mapsto (\pm y, \pm x),$$

with the signs determined by the chosen rotation or reflection.

The only subtlety is that the same offset may have more than one feasible displacement representation. For example, $nx + y = nx' + y'$ may hold with $(x, y) \neq (x', y')$. We therefore work directly with the equivalence relation on offsets generated by equality of offsets and by D_4-related feasible displacements.

First, offset 0 is a singleton. If $nx + y = 0$ with $|x|, |y| \leq n - 1$, then $x \neq 0$ would imply

$$|nx| \geq n > |y|,$$

which is impossible. Hence $x = y = 0$.

Second, every nonzero offset is equivalent to one of $\{1, \ldots, n-1\}$. By a $180°$ rotation, $d \sim -d$, so it suffices to consider $d > 0$. Write

$$d = nq + r, \qquad 0 \leq r \leq n - 1.$$

If $q = 0$, then $d = r \in \{1, \ldots, n-1\}$. If $q \geq 1$ and $r = 0$, then

$$d = \delta(q, 0) \sim \delta(0, q) = q < d.$$

If $q \geq 1$ and $r > 0$, then

$$d = \delta(q, r) \sim \delta(q, -r) = nq - r < d.$$

Repeating this strict descent reaches a positive offset in $\{1, \ldots, n-1\}$.

Third, for every $1 \leq k \leq n - 3$,

$$k \sim k + 2.$$

Indeed,

$$
\begin{align}
k &= \delta(1, k - n) \tag{73} \\
&\sim \delta(n - k, -1) \tag{74} \\
&= n(n - k) - 1 \tag{75} \\
&= \delta(n - k - 1, n - 1) \tag{76} \\
&\sim \delta(-(n - k - 1), n - 1) \tag{77} \\
&= \delta(-(n - k - 2), -1) \tag{78} \\
&\sim \delta(1, k + 2 - n) \tag{79} \\
&= k + 2. \tag{80}
\end{align}
$$

All displacements used above lie in $[-(n-1), n-1]^2$ when $1 \leq k \leq n - 3$.

Now suppose n is odd. Since

$$\delta(x, y) = nx + y \equiv x + y \pmod 2,$$

and D_4 only swaps coordinates and changes signs, offset parity is invariant. By Eq. (A.4), all positive small odd offsets are equivalent and all positive small even offsets are equivalent. The descent argument then shows that all nonzero odd offsets form one class and all nonzero even offsets form one class. Together with the singleton class $\{0\}$, this gives the stated three classes.

Finally suppose n is even. For $n = 2$, the positive offsets are $1, 2, 3$. We have

$$1 = \delta(0, 1) \sim \delta(1, 0) = 2,$$

and

$$3 = \delta(1, 1) \sim \delta(1, -1) = 1,$$

so all nonzero offsets are equivalent. For $n \geq 4$,

$$1 = \delta(1, 1 - n) \sim \delta(1, n - 1) = 2n - 1 = \delta(2, -1) \sim \delta(1, -2) = n - 2.$$

The offset $n - 2$ is even. By Eq. (A.4), it is equivalent to 2. Hence $1 \sim 2$, so the odd and even nonzero classes merge. The descent argument then shows that all nonzero offsets form one class. Together with $\{0\}$, this gives the stated two classes. $\square$

We now prove the attention-head rigidity theorem from the main text.

Proof of Theorem 4.2. Let

$$\Delta_n := \{d(u, v) : u, v \in \Lambda_n\}.$$

For each $d \in \Delta_n$, let

$$\ell_d : \mathbb{R}^{r_q} \times \mathbb{R}^{r_k} \to \mathbb{R}$$

be a finite scalar scoring function. The attention logits are

$$L_{uv}(Q, K) = \ell_{d(u,v)}(Q_u, K_v),$$

and the row-stochastic attention matrix is

$$A_\ell(Q, K) = \mathrm{softmax}_v(L(Q, K)).$$

Thus

$$\mathrm{Att}_\ell(Q, K, V) = A_\ell(Q, K)V.$$

Assume first that the attention head is exactly D_4-equivariant under the position-only action. Then, for every $g \in D_4$ and every value array V,

$$A_\ell(\Pi_g Q, \Pi_g K)\Pi_g V = \Pi_g A_\ell(Q, K)V.$$

Since this identity holds for all V, we may write $W = \Pi_g V$ and obtain

$$A_\ell(\Pi_g Q, \Pi_g K)W = \Pi_g A_\ell(Q, K)\Pi_g^{-1} W \qquad \forall W.$$

Therefore,

$$A_\ell(\Pi_g Q, \Pi_g K) = \Pi_g A_\ell(Q, K)\Pi_g^{-1}.$$

Equivalently, for every $u, v \in \Lambda_n$,

$$A_\ell(\Pi_g Q, \Pi_g K)_{gu,gv} = A_\ell(Q, K)_{u,v}.$$

For finite logits, equality of two row-wise softmax distributions is equivalent to equality of the corresponding logits up to an additive constant depending only on the row. Hence, for each fixed g, u, Q, K, there exists a scalar $c_{g,u}(Q, K)$ such that

$$L_{gu,gv}(\Pi_g Q, \Pi_g K) = L_{u,v}(Q, K) + c_{g,u}(Q, K) \qquad \forall v \in \Lambda_n.$$

Using the row-major relative-score form and the position-only action,

$$(\Pi_g Q)_{gu} = Q_u, \qquad (\Pi_g K)_{gv} = K_v,$$

so Eq. (A.4) becomes

$$\ell_{d(gu,gv)}(Q_u, K_v) = \ell_{d(u,v)}(Q_u, K_v) + c_{g,u}(Q, K) \qquad \forall v.$$

Because the attention head is full and unmasked, the self-edge $v = u$ is available. Setting $v = u$, we have

$$d(u, u) = d(gu, gu) = 0.$$

Therefore Eq. (A.4) gives

$$\ell_0(Q_u, K_u) = \ell_0(Q_u, K_u) + c_{g,u}(Q, K),$$

and hence

$$c_{g,u}(Q, K) = 0.$$

Substituting this back into Eq. (A.4),

$$\ell_{d(gu,gv)}(Q_u, K_v) = \ell_{d(u,v)}(Q_u, K_v) \qquad \forall g, u, v, Q, K.$$

Since the theorem assumes equivariance for all Q, K, the vectors Q_u and K_v can be varied arbitrarily. Thus

$$\ell_{d(gu,gv)}(q, k) = \ell_{d(u,v)}(q, k)$$

for every $g \in D_4$, every $u, v \in \Lambda_n$, and all $q \in \mathbb{R}^{r_q}$, $k \in \mathbb{R}^{r_k}$.

Conversely, suppose the score functions are tied on all D_4-related row-major offsets:

$$\ell_{d(gu,gv)}(q, k) = \ell_{d(u,v)}(q, k) \qquad \forall g, u, v, q, k.$$

Then

$$
\begin{align}
L_{gu,gv}(\Pi_g Q, \Pi_g K) &= \ell_{d(gu,gv)}((\Pi_g Q)_{gu}, (\Pi_g K)_{gv}) \tag{81} \\
&= \ell_{d(gu,gv)}(Q_u, K_v) \tag{82} \\
&= \ell_{d(u,v)}(Q_u, K_v) \tag{83} \\
&= L_{u,v}(Q, K). \tag{84}
\end{align}
$$

Hence

$$L(\Pi_g Q, \Pi_g K) = \Pi_g L(Q, K) \Pi_g^{-1}.$$

Row-wise softmax commutes with simultaneous row and column permutation, so

$$A_\ell(\Pi_g Q, \Pi_g K) = \Pi_g A_\ell(Q, K) \Pi_g^{-1}.$$

Multiplying by $\Pi_g V$, we get

$$
\begin{align}
\mathrm{Att}_\ell(\Pi_g Q, \Pi_g K, \Pi_g V) &= A_\ell(\Pi_g Q, \Pi_g K) \Pi_g V \tag{85} \\
&= \Pi_g A_\ell(Q, K) V \tag{86} \\
&= \Pi_g \, \mathrm{Att}_\ell(Q, K, V). \tag{87}
\end{align}
$$

This proves the equivalence.

For $n = 9$, Lemma A.6 gives exactly three row-major offset classes:

$$d = 0, \qquad d \neq 0, \ d \equiv 0 \pmod 2, \qquad d \equiv 1 \pmod 2.$$

Therefore the score functions must collapse as

$$
\ell_d = \begin{cases}
\ell_0, & d = 0, \\
\ell_E, & d \neq 0, \ d \equiv 0 \pmod 2, \\
\ell_O, & d \equiv 1 \pmod 2.
\end{cases}
$$

In particular, the offsets 1, 9, and -9 are all odd offsets on a 9×9 grid, so an exactly D_4-equivariant row-major relative-score attention head must tie their score functions. $\qquad\square$

Proof of Corollary 4.3. Assume the relative score has the bilinear-affine form

$$\ell_d(q, k) = q^\top M_d k + b_d.$$

By Theorem 4.2, exact D_4-equivariance implies

$$q^\top M_{d(gu,gv)} k + b_{d(gu,gv)} = q^\top M_{d(u,v)} k + b_{d(u,v)}$$

for every $g \in D_4$, every $u, v \in \Lambda_n$, and all q, k.

Setting $q = 0$ gives

$$b_{d(gu,gv)} = b_{d(u,v)}.$$

After subtracting the equal biases, we obtain

$$q^\top \left(M_{d(gu,gv)} - M_{d(u,v)} \right) k = 0 \qquad \forall q, k.$$

Choosing q and k to range over standard basis vectors gives

$$M_{d(gu,gv)} = M_{d(u,v)}.$$

For $n = 9$, Lemma A.6 then implies

$$(M_d, b_d) = \begin{cases} (M_0, b_0), & d = 0, \\ (M_E, b_E), & d \neq 0, \ d \equiv 0 \pmod 2, \\ (M_O, b_O), & d \equiv 1 \pmod 2. \end{cases}$$

For row-major RoPE, let R_t denote the block-diagonal rotary matrix at sequence position t, with the usual property

$$R_a^\top R_b = R_{b-a}.$$

Applying RoPE to query and key vectors at row-major positions $p(u)$ and $p(v)$ gives, up to the conventional sign convention,

$$(R_{p(u)} q_u)^\top (R_{p(v)} k_v) = q_u^\top R_{p(u)}^\top R_{p(v)} k_v \tag{88}$$
$$= q_u^\top R_{p(v)-p(u)} k_v. \tag{89}$$

Thus row-major RoPE is a bilinear relative-score instance with

$$M_d = R_d$$

up to sign convention and the usual attention scaling constant, which can be absorbed into M_d. Therefore, if the RoPE relative matrices distinguish two offsets in the same D_4-offset class, such as 1 and 9 on a 9×9 grid, the RoPE score does not satisfy the tying condition required by Theorem 4.2. Hence such a nondegenerate row-major RoPE head does not by itself certify exact D_4-equivariance. $\qquad \square$

Scope of the result. Theorem 4.2 is a component-level certificate theorem. It assumes a single full, unmasked attention head, a row-major relative-score form, and a position-only D_4 action on hidden states. It does not imply that a full multi-layer Transformer with MLPs, residual streams, normalization, multi-head interactions, or learned internal representations cannot learn a D_4-equivariant function from data. It says that standard row-major relative-score attention does not enforce the D_4 certificate by itself unless its offset dependence collapses to the offset classes above. If hidden channels transform under a nontrivial D_4 representation, or if a mask removes the self-edge $v = u$, the necessary tying condition changes.

A.5. Representation-wise denoising accounting

This appendix gives a denoising-accounting identity. The result is a posterior L^2 identity, not a KL identity. It tracks the nontrivial representation modes of the hidden view label through the reverse denoising chain.

Let $V \sim \mathrm{Unif}(G)$. For any random variable S, define the posterior likelihood ratio of the view label by

$$\alpha_S(g) := \frac{\Pr(V = g \mid S)}{\Pr(V = g)} = m\Pr(V = g \mid S). \tag{90}$$

Then $m^{-1}\sum_g \alpha_S(g) = 1$. For $\rho \in \widehat{G}$, define

$$\widehat{\alpha}_{S,\rho} := \frac{1}{m}\sum_{g \in G} \alpha_S(g)\rho(g)^*. \tag{91}$$

For nontrivial $\rho \neq \mathbf{1}$, define the ρ-view energy in S by

$$\mathcal{E}_\rho(S) := d_\rho \mathbb{E}_S\left[\|\widehat{\alpha}_{S,\rho}\|_{\mathrm{HS}}^2\right]. \tag{92}$$

For two random variables S, T, define the conditional innovation

$$\mathcal{J}_\rho(T; V \mid S) := d_\rho \mathbb{E}_{S,T}\left[\|\widehat{\alpha}_{S,T,\rho} - \widehat{\alpha}_{S,\rho}\|_{\mathrm{HS}}^2\right]. \tag{93}$$

Lemma A.7 (Posterior Pythagorean identity)**.** *For any S, T and any nontrivial ρ,*

$$\mathcal{E}_\rho(S,T) = \mathcal{E}_\rho(S) + \mathcal{J}_\rho(T; V \mid S). \tag{94}$$

The same identity holds with S and T interchanged.

Proof. Bayes posterior averaging gives

$$\alpha_S(g) = \mathbb{E}[\alpha_{S,T}(g) \mid S]. \tag{95}$$

Fourier transform in the group variable is linear, so

$$\widehat{\alpha}_{S,\rho} = \mathbb{E}[\widehat{\alpha}_{S,T,\rho} \mid S]. \tag{96}$$

The Hilbert-space conditional variance identity gives

$$\mathbb{E}\|A\|_{\mathrm{HS}}^2 = \mathbb{E}\|\mathbb{E}[A \mid S]\|_{\mathrm{HS}}^2 + \mathbb{E}\|A - \mathbb{E}[A \mid S]\|_{\mathrm{HS}}^2, \tag{97}$$

with $A = \widehat{\alpha}_{S,T,\rho}$. Multiplying by d_ρ proves the result. $\square$

Now run the reverse denoising chain under input Vx and pull each state back to canonical coordinates:

$$Z_H^c, Z_{H-1}^c, \ldots, Z_0^c, Y^c. \tag{98}$$

For each step define

$$A_h^\rho := \mathcal{J}_\rho(Z_{h-1}^c; V \mid Z_h^c), \qquad B_h^\rho := \mathcal{J}_\rho(Z_h^c; V \mid Z_{h-1}^c), \tag{99}$$

and for the readout define

$$A_R^\rho := \mathcal{J}_\rho(Y^c; V \mid Z_0^c), \qquad B_R^\rho := \mathcal{J}_\rho(Z_0^c; V \mid Y^c). \tag{100}$$

Theorem A.8 (Representation-wise denoising accounting)**.** *For every nontrivial representation $\rho \neq \mathbf{1}$,*

$$\mathcal{E}_\rho(Y^c) = \mathcal{E}_\rho(Z_H^c) + \sum_{h=1}^{H}(A_h^\rho - B_h^\rho) + A_R^\rho - B_R^\rho. \tag{101}$$

Consequently,

$$\mathcal{E}_\rho(Y^c) \leq \mathcal{E}_\rho(Z_H^c) + \sum_{h=1}^{H} A_h^\rho + A_R^\rho. \tag{102}$$

Proof. Apply Lemma A.7 to $(S,T) = (Z_h^c, Z_{h-1}^c)$ and to $(S,T) = (Z_{h-1}^c, Z_h^c)$. The two expressions for $\mathcal{E}_\rho(Z_h^c, Z_{h-1}^c)$ give

$$\mathcal{E}_\rho(Z_{h-1}^c) - \mathcal{E}_\rho(Z_h^c) = A_h^\rho - B_h^\rho. \tag{103}$$

Summing over $h = 1, \ldots, H$ gives

$$\mathcal{E}_\rho(Z_0^c) = \mathcal{E}_\rho(Z_H^c) + \sum_{h=1}^H (A_h^\rho - B_h^\rho). \tag{104}$$

Apply the same argument to (Z_0^c, Y^c) to obtain

$$\mathcal{E}_\rho(Y^c) - \mathcal{E}_\rho(Z_0^c) = A_R^\rho - B_R^\rho. \tag{105}$$

Combining the two displays proves Eq. (101). Since all B_h^ρ and B_R^ρ are nonnegative by definition, dropping them proves Eq. (102). $\qquad\square$

Corollary A.9 (A nonzero output mode requires a nonzero source). *Assume the initial canonical noise state carries no ρ-view mode, $\mathcal{E}_\rho(Z_H^c) = 0$, and the readout injects no new ρ-view mode, $A_R^\rho = 0$. If $\mathcal{E}_\rho(Y^c) > 0$, then at least one reverse denoising step has $A_h^\rho > 0$. In particular,*

$$\max_{1 \le h \le H} A_h^\rho \ge \frac{\mathcal{E}_\rho(Y^c)}{H}. \tag{106}$$

Proof. Under the assumptions, Eq. (102) becomes

$$\mathcal{E}_\rho(Y^c) \le \sum_{h=1}^H A_h^\rho. \tag{107}$$

If the left side is positive, the sum is positive, so at least one term is positive. The displayed lower bound follows by averaging. $\qquad\square$

If the canonicalized reverse transition at step h is independent of V given Z_h^c, then $Z_{h-1}^c \perp V \mid Z_h^c$, which implies $A_h^\rho = 0$ for every nontrivial ρ. Thus $A_h^\rho > 0$ is a one-way witness: the transition cannot be view-independent on the posterior support. The converse need not hold, because a transition may depend on the view in a way that is outside the posterior support or invisible to the particular representation mode.

A.6. Finite-K extrema and the pseudo-orbit control

This appendix explains why the stochastic metrics are averaged over base states and why pseudo-orbits are reported. With K samples per view, empirical maxima and minima are biased: maxima tend to be too high and minima tend to be too low. This can create a gap even when all views have the same true success probability.

For fixed x, let $\widehat{p}_{g,K}(x)$ be the empirical mean of K Bernoulli success samples with mean $p_g(x)$. Hoeffding's inequality and a union bound give

$$\Pr\left[\max_{g \in G} |\widehat{p}_{g,K}(x) - p_g(x)| > \epsilon\right] \le 2|G| e^{-2K\epsilon^2}. \tag{108}$$

On the complementary event,

$$|\widehat{C}_{\max,K}(x) - C_{\max}(x)| \le \epsilon, \qquad |\widehat{R}_{\min,K}(x) - R_{\min}(x)| \le \epsilon. \tag{109}$$

This controls concentration, but it does not remove extrema bias.

The canonical pseudo-orbit estimates that bias directly. For each base state x, draw $|G|K$ samples from the canonical layout only. Randomly split them into $|G|$ groups of size K and compute the same max/min metrics as if those groups were views. Because all pseudo-views come from the same layout, any pseudo gap is due to finite-sample extrema. A larger real-orbit gap indicates presentation sensitivity beyond sampling noise.

All confidence intervals are computed by paired bootstrap over base logical states. The eight transformed views of a single base state are not treated as eight independent test examples.

B. Experimental details

This appendix gives the details needed to reproduce the experiments in Section 5. The main paper states the logic of each experiment. Here we state how the data, parser, sampling controls, and uncertainty estimates are implemented.

B.1. Anchored-completion generation

We generate anchored-completion states only after the base Sudoku puzzle split. For each base puzzle, we choose anchors A, target cells U, and unresolved cells R. We keep the state only if the values of U are forced by A:

$$\{s_U : s \in \mathcal{S}(A)\} = \{s_U^\star\}. \tag{110}$$

The verification uses a Sudoku solver that enumerates completions until either two different target assignments are found or the target assignment is certified unique. The full grid need not be unique. Only the target assignment must be unique.

After a state is retained, we apply all eight elements of D_4. Because rotations and reflections preserve Sudoku row, column, and box constraints, every transformed state has the corresponding transformed target. During scoring, every prediction is mapped back to canonical coordinates before comparison.

B.2. Parsing and scoring

The model is asked to output the values of the target cells. A prediction is valid only if it can be parsed into exactly one digit for each requested target cell. If the output is malformed, incomplete, contains an invalid digit, or assigns two different values to the same target cell, it is mapped to the invalid symbol $\perp$ and scored as incorrect.

We report invalid-parse rate separately from wrong-but-valid rate. This separation matters because a parser failure and a logically wrong assignment are different errors. For all orbit metrics, $\perp$ is fixed by the group action: $g\perp = \perp$.

B.3. Stochastic sampling

For stochastic evaluation, we draw $K = 16$ samples per view unless otherwise stated. For each base state x and view g, the empirical success probability is

$$\widehat{p}_{g,K}(x) = \frac{1}{K} \sum_{k=1}^{K} \mathbf{1}[g^{-1}Y_{g,k} = y^\star(x)]. \tag{111}$$

We then compute

$$\widehat{C}_{\max}^K(x) = \max_{g\in G} \widehat{p}_{g,K}(x), \qquad \widehat{R}_{\min}^K(x) = \min_{g\in G} \widehat{p}_{g,K}(x). \tag{112}$$

The extrema are computed within each base state and then averaged over base states. We do not pool transformed views as independent examples.

B.4. Canonical pseudo-orbit control

The pseudo-orbit control estimates the best-view/worst-view gap caused only by finite sampling. For each base state, we draw $|G|K$ samples from the canonical layout, randomly split them into $|G|$ groups of size K, and compute the same extrema used for the real orbit:

$$\widehat{C}_{\max}^{K,\text{pseudo}}(x), \qquad \widehat{R}_{\min}^{K,\text{pseudo}}(x). \tag{113}$$

The pseudo-orbit has no true geometric view shift. Therefore, if the real orbit has a much lower $\widehat{R}_{\min}^K$ or a much larger view gap than the pseudo-orbit, the difference is evidence of presentation sensitivity rather than extrema bias.

B.5. Token view-leakage diagnostic

For each target cell i and view g, we estimate a token distribution $\widehat{p}_{g,i}$ from the K canonicalized samples. We add a small symmetric smoothing constant ϵ to every digit count before normalization. The reported token view-leakage proxy is

$$\widehat{L}_{\text{tok}}(x) = \frac{1}{|U|} \sum_{i\in U} \frac{1}{|G|} \sum_{g\in G} D_{\text{KL}}(\widehat{p}_{g,i}\|\widehat{\overline{p}}_i), \qquad \widehat{\overline{p}}_i = \frac{1}{|G|} \sum_{g\in G} \widehat{p}_{g,i}. \tag{114}$$

This diagnostic uses token marginals only. It can show that views disagree at the cell level, but it cannot certify that the full joint output distributions agree. The main correctness claims therefore use ALL, $\widehat{R}_{\min}^{K}$, and the real-vs-pseudo gap.

We also report per-view success plots. These plots show whether failures concentrate on rotations, reflections, or a particular canonical layout. They are useful for diagnosing the geometry of the failure, but the orbit metrics remain the primary summary.