Second Guess: Detecting Uncertainty Through Abstention and Answer Stability in Small Language Models

Abstract

Large language models often generate confident but incorrect answers rather than abstaining when uncertain. This problem is particularly acute for small language models (SLMs), where computational constraints and autonomous operation amplify the need for reliable uncertainty detection. We propose **Second Guess**, a lightweight, parameter-free prompting technique for abstention in multiple-choice question answering (MCQA) that is well-suited for SLMs. Our key empirical insight is that models which truly know an answer will select it consistently, while uncertain models exhibit unstable behavior when an "I don't know" option is added. Evaluated on four open models (2B-8B parameters) and four benchmarks, Second Guess achieves the highest composite risk improvement of 10.81%. Notably, it maintains an 8% composite risk improvement on fine-tuned models where entropy-based methods degrade, and improves most for lower-performing models. All code and results required to reproduce this work is available in https://anonymous.4open.science/r/second-guess-B6C1/

1 Introduction

While large language models (LLMs) often generate confident, but incorrect, answers rather than acknowledging uncertainty and abstain, the challenge is even more acute for small language models (SLMs), denoted here as transformer-based generative models with fewer than 10B parameters. SLMs are important in many contexts, including deployment on edge and mobile devices (Lu et al., 2024), where computational constraints can amplify the importance of reliable uncertainty detection, and autonomous operation precedes the availability of human oversight (Tomani et al., 2024).

Recent work addresses abstention through diverse methodological approaches, each with distinct constraints. *Training-based* methods (Zhu

Figure 1: Overview of the Second Guess technique. The model is prompted twice: once with the original options and once with an "I don't know" option added. If the model's answer changes between the two prompts, it is classified as an abstention; otherwise, the original answer is retained.

et al., 2025; Kanber, 2025) leverage "I don't know" labels or dedicated tokens during fine-tuning, though they require direct access to model weights. *Prompt-based* methods (Zong et al., 2026; Kadavath et al., 2022; Ren et al., 2026) attempt to elicit uncertainty through explicit queries, but their effectiveness depends on the assumption that models accurately self-report their confidence. *Sampling-based* methods (Cole et al., 2023; Wang et al., 2022) achieve robustness through consensus across multiple model outputs, at the cost of substantial computational overhead.

In this paper, we propose **Second Guess**, a novel parameter-free prompting technique that operates under the key insight that models exhibiting stable knowledge will provide consistent answers *regardless* of available options (Figure 1). The method prompts each model twice per question: once with

the standard choice set and again with an "I don't know" option added. We treat answer discrepancies between these two prompts as an abstention signal, while unchanged responses are retained as confident predictions. This approach demands only two forward passes per question, making it applicable even to black-box SLMs without access to (internal) model parameters or uncertainty scores.

We evaluate Second Guess on four SLMs (2B–8B parameters) and four MCQ benchmarks, and contribute: (i) a parameter-free abstention technique with only 2 queries and no access to internal state of the model; (ii) comprehensive evaluation showing Second Guess achieves highest composite risk improvements while maintaining robustness to fine-tuning; and (iii) empirical insights demonstrating that improvements stem from detecting unstable answer switching and showing the method is best suited for challenging tasks and lower-performing models.

2 Related Work

Abstention, the ability to decline answering a question when uncertain, is critical for deployed language models, as incorrect predictions often cause greater harm than no prediction at all in safety critical domains like healthcare. Existing approaches include training-based methods that require weight access and retraining (Zhu et al., 2025; Kanber, 2025) and prompt-based methods that rely on self-reported uncertainty (Zong et al., 2026; Kadavath et al., 2022). Consistency-based approaches measure behavioral stability across perturbations (Cole et al., 2023), but existing work uses unstructured stochastic sampling requiring many forward passes. While these approaches are well established, achieving reliable abstention in LLMs remains a challenge (Kirichenko et al., 2026; Wen et al., 2025).

Small language models (SLMs), typically fewer than 10 billion parameters, increasingly deployed on edge and mobile devices where latency and privacy constraints preclude API calls (Lu et al., 2024; Wang et al., 2025). Calibration generally improves with model scale (Kalai and Vempala, 2024; El-hady et al., 2025): smaller models exhibit greater overconfidence and susceptibility to perturbations, thereby more in need of reliability harness around them (Aravindan and Kejriwal, 2026). Crucially, SLMs are often deployed autonomously in embedded systems where incorrect answers carry di-

rect consequences, yet sampling-based consistency methods (Cole et al., 2023) are computationally prohibitive.

3 Methodology

3.1 Second Guess

Consider a question Q and its four corresponding answer choices $\mathcal{C} = \{c_1, c_2, c_3, c_4\}$ presented in a zero-shot prompt[1]. In the first stage, the model's response R_1 is extracted from the original prompt. In the second stage, an abstention option "I don't know" is inserted at a random position to $\mathcal{C}$ as the fifth option, and the model's response R_2 to the augmented prompt is extracted. If the model's answer remains consistent between stages ($R_1 = R_2$), the original answer choice is retained. Conversely, if the response changes ($R_1 \neq R_2$), regardless of what it changes to, the model's output is classified as an abstention response "I don't know".

Formally, the final model answer R is derived as follows:

$$R = \begin{cases} R_1 & \text{if } R_1 = R_2 \\ \text{"I don't know"} & \text{if } R_1 \neq R_2 \end{cases} \quad (1)$$

3.2 Experimental Setup

3.2.1 Models and Datasets

We evaluate four instruction-tuned language models: Mistral-7B-Instruct-v0.3 (Jiang et al., 2023), Llama-3.1-8B-Instruct (Grattafiori et al., 2024), IBM Granite-3.3-2B-Instruct[2], and Qwen3-4B-Instruct-2507 (Yang et al., 2025). More information about the models used is provided in Appendix A (Table 2). We evaluate model behavior across four multiple-choice question-answering datasets: CommonsenseQA (Talmor et al., 2019), QASC (Khot et al., 2020), MMLU-Pro (Wang et al., 2024), and SuperGPQA (Du et al., 2025). For each model and dataset, we sample 100 random questions and normalize them to contain exactly four options per question. A detailed summary of the datasets is provided in Appendix A (Table 3).

3.2.2 Baselines

Because our approach is lightweight and requires only model outputs, we select baselines that are

---

[1]We reproduce a standard multiple-choice prompt template in Figure 3 in Appendix A, demonstrating the structured format used in our experiments.

[2]https://huggingface.co/ibm-granite/granite-3.3-2b-instruct

similarly lightweight and practical. Therefore complex and sampling based approaches like proposed by (Cole et al., 2023) are not evaluated against. The baselines evaluated are:

1. **Original Prompt only**: The standard multiple-choice options $\mathcal{C} = \{c_1, c_2, c_3, c_4\}$ without augmentation. The options are shuffled randomly to avoid bias due to ordering.

2. **Augmented Prompt only**: A single-stage variant where the abstention option "I don't know" is added at a random position to the original options from the outset, forming $\mathcal{C}' = \{c_1, c_2, c_3, c_4, \text{"I don't know"}\}$. This baseline directly exposes the model to the possibility of abstaining in a single pass.

3. **Self-Evaluation** (Kadavath et al., 2022): A two-step prompting strategy adapted for abstention. In the first stage, the model generates an answer; in the second stage, it is presented with this answer and asked to verify its correctness, abstaining when it doesn't accept the proposed answer.

4. **Entropy-based Uncertainty Estimation and Thresholding** (Malinin and Gales, 2020): A post-hoc baseline where responses with output token entropy exceeding the mean plus one standard deviation of the entropy distribution across the entire dataset are automatically converted to abstentions; otherwise, the model's response is preserved. See Figure 4 in Appendix C for more details.

3.2.3 Fine-tuning with Low-Rank Adaptation

To understand whether the advantage of the two-stage prompting technique persists when models are highly capable in MCQA task, we fine-tune two models (Qwen and Llama) using low-rank adaptation (LoRA) (Hu et al., 2022). Details regarding the hyperparameters used for model training are provided in Appendix B.

3.2.4 Evaluation Metrics

We employ three metrics to evaluate model performance. We define the following notation: N = total number of questions, N_c = count of correct answers, N_i = count of incorrect answers, N_a = count of abstentions and N_{ca} = count of abstentions that were correct answers in the original prompt. The three evaluation metrics are defined as follows:

1. **Precision** The proportion of non-abstained questions answered correctly. It is computed as: $\frac{N_c}{N_c + N_i} \times 100$

2. **Error Rate** The proportion of incorrect answers relative to the total number of questions, computed as: $\frac{N_i}{N} \times 100$

3. **Composite Risk** The proportion of problematic outcomes, combining both incorrect answers and cases where the model abstains when it provided a correct response in the original prompt (Shen and Kejriwal, 2025), computed as: $\frac{N_i + N_{ca}}{N} \times 100$

4 Results

Finding 1: Second Guess provides a significant improvement in Composite Risk across models and datasets. Table 1 presents the average performance of different methods across all base models and datasets. The Augmented prompt only baseline demonstrates minimal improvement, with changes of 2.25% in Composite Risk over the Original prompt. Entropy Thresholding shows moderate improvement (3-6% drop), especially when using the Augmented prompt. Self-Evaluation proves to be the best baseline with 7.69% drop in Composite Risk. Whereas, Second Guess improves performance across all metrics, achieving particularly strong gains in Composite Risk with a 10.81% drop, while using only 2 model queries, just as much as Self-Evaluation. Table 11 in Appendix E presents a detailed breakdown across all model-dataset combinations.

Finding 2: Second Guess also works on fine-tuned models while other baselines degrade Even for models that are already effective at the task, Second Guess delivers an 8% improvement in Composite Risk, with Self-Evaluation also keeping up, whereas other methods achieve improvements of roughly 0-2.5%. Notably, Entropy Thresholding loses out on finetuned models since with finetuning, the confidence of the models on that dataset increases and token entropy is no longer very informative on the models' uncertainty. Second Guess continues to offer almost double the reduction in Error Rate compared to Self-Evaluation while almost matching the improvement in Precision. In Appendix D, Table 4 shows comparative results for fine-tuned models averaged across all datasets against baselines, while Table 5 compares the results against the corresponding base models.

Finding 3: There is an inverse relationship between improvement in Composite Risk and the model's base performance Figure 2 reveals a clear inverse relationship between a model's base

Table 1: Average performance of each method across all base models and datasets. Each cell shows the mean and standard deviation of metric value followed by the averaged percentage change versus the *Original* baseline.

Method	Precision ↑	Error Rate ↓	Composite Risk ↓
Original	59.75 ± 16.72	40.25 ± 16.72	40.25 ± 16.72
Augmented	61.04 ± 16.77 (+1.29)	38.00 ± 15.99 (-2.25)	38.00 ± 15.99 (-2.25)
Self-Evaluation	62.10 ± 17.31 (+2.35)	32.56 ± 15.18 (-7.69)	32.56 ± 15.18 (-7.69)
Entropy Thresholding (Original)	63.30 ± 18.03 (+3.55)	32.00 ± 16.18 (-8.25)	36.56 ± 15.34 (-3.69)
Entropy Thresholding (Augmented)	63.49 ± 18.54 (+3.74)	29.88 ± 14.78 (-10.38)	34.69 ± 14.26 (-5.56)
Second Guess (Ours*)	**68.40 ± 14.93 (+8.65)**	**20.12 ± 5.32 (-20.12)**	**29.44 ± 8.66 (-10.81)**

Figure 2: Composite Risk Reduction vs. Base Accuracy. The scatter plot shows the relationship between a model's base accuracy and the improvement achieved by Second Guess across all model-dataset combinations. The negative linear trend (fitted line: $y = -0.47x + 38.97$) demonstrates that models with lower base accuracy benefit more from our approach.

accuracy and the improvement in Composite Risk delivered by Second Guess. Specifically, models with lower base accuracy exhibit substantially higher Composite Risk reductions, while those with higher base accuracy see more modest improvements. The fitted line ($y = -0.47x + 38.97$) demonstrates that for every 1% increase in base accuracy, the expected composite risk reduction decreases by approximately 0.47 percentage points. As also seen in Table 11 in Appendix E, the models with the lowest base accuracy—such as Llama on SuperGPQA (base accuracy ≈ 32%)—benefit the most, achieving composite risk reductions exceeding 25%. Conversely, models already performing well, such as Qwen on CommonsenseQA (base accuracy ≈ 85%), see no improvement. This observation suggests that Second Guess is more valuable for use in challenging domains, where model accuracy is lower and error reduction is most critical.

Finding 4: Composite Risk gains primarily stem from option switching rather than "I don't

know" selection Table 12 in Appendix F shows the distribution of models' choices in the Augmented prompt versus the Original prompt. The models rarely selects the "I don't know" option and instead tends to switch between wrong answers. For example, the Qwen model on MMLU Pro, switches only 2 of its incorrect answers in the Original Prompt to "I don't know" in the Augmented Prompt, while switching 21 of those to some other choices in the latter prompt, showing that most of the error rate reduction came from capturing this option switching behaviour rather than explicit abstention by the model. This pattern generalizes across all models and datasets, with multiple settings where models chose "I don't know" zero times.

5 Discussion

The experiments show that Second Guess can be effective in improving useful abstention and is also practical due to minimal computation requirements. Our evaluation spans a broad set of question types involving both reasoning and knowledge retrieval (Table 3), suggesting general applicability. Second Guess is also a parameter-free method, requiring no tuning or hyperparameter optimization across different models or domains, making it accessible.

Interestingly, Finding 3 suggests that finetuned versions of models should benefit less from Second Guess compared to their base counterparts. For the Qwen model, finetuning does result in a reduction in the Composite Risk improvement observed (-9.75% base vs -5.25% finetuned). But for the Llama model, there is actually a modest increase in the Composite Risk improvement after finetuning (-9.50% base vs -10.75% finetuned) (see Table 5 in Appendix D). Hence, behavioral uncertainty exploited by Second Guess is likely unaffected by finetuning, and may be inherent to the model itself, possibly connected to knowledge gained during pre-training (Zhou et al., 2023).

6 Limitations

This study has several important limitations that should be considered when interpreting the results. First, the study focusses on smaller language models with fewer than 10 billion parameters. The analysis in Finding 3 reveals an inverse relationship between model capability and improvement magnitude: as base model performance increases, the gains from Second Guess diminish. This pattern raises an important question about scalability to frontier-scale models, which already achieve high performance on many benchmarks. For frontier models, Second Guess may primarily benefit only in specialized domains requiring niche knowledge not already in the training data or tasks that remain challenging despite their scale. However, this limitation should not diminish the significance of improving the reliability of smaller models. Smaller language models remain critical in many real-world applications (Belcak et al., 2025), particularly in scenarios with stringent latency, computational, or privacy constraints. In such settings, Second Guess demonstrates substantial value by consistently improving performance and reliability without incurring massive additional inference costs.

Furthermore, this study evaluates models without Chain-of-Thought (CoT) reasoning (Wei et al., 2022), which has become standard practice for extracting maximum performance from modern language models. Although our evaluation shows performance variation across models (e.g., Base Qwen achieving 86% on CommonsenseQA while Llama scores only 32% on SuperGPQA, as detailed in Table 6 in Appendix E), indicating that Second Guess benefits models across performance levels, the absence of CoT likely underestimates the baseline capabilities of evaluated models. Future work should investigate how Second Guess interacts with advanced prompting strategies to establish its utility when models operate at closer to their maximum potential.

References

Ashwath Vaithinathan Aravindan and Mayank Kejriwal. 2026. Fragile thoughts: How large language models handle chain-of-thought perturbations. *arXiv preprint arXiv:2603.03332*.

Peter Belcak, Greg Heinrich, Shizhe Diao, Yonggan Fu, Xin Dong, Saurav Muralidharan, Yingyan Celine Lin, and Pavlo Molchanov. 2025. Small language models are the future of agentic ai. *arXiv preprint arXiv:2506.02153*.

Jeremy Cole, Michael Zhang, Dan Gillick, Julian Eisenschlos, Bhuwan Dhingra, and Jacob Eisenstein. 2023. Selectively answering ambiguous questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 530–543.

Xinrun Du, Yifan Yao, Kaijing Ma, Bingli Wang, Tianyu Zheng, King Zhu, Minghao Liu, Yiming Liang, Xiaolong Jin, Zhenlin Wei, and 1 others. 2025. Supergpqa: Scaling llm evaluation across 285 graduate disciplines. *arXiv preprint arXiv:2502.14739*.

Ahmed Elhady, Eneko Agirre, and Mikel Artetxe. 2025. Wicked: A simple method to make multiple choice benchmarks more challenging. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1183–1192.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.

Albert Qiaochu Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *ArXiv*, abs/2310.06825.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, and 1 others. 2022. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*.

Adam Tauman Kalai and Santosh S Vempala. 2024. Calibrated language models must hallucinate. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing*, pages 160–171.

Baris Kanber. 2025. All we also need is abstain: Eliminating hallucinations via a single token. *Preprints*.

Tushar Khot, Peter Clark, Michal Guerquin, Peter Jansen, and Ashish Sabharwal. 2020. Qasc: A dataset for question answering via sentence composition. *arXiv:1910.11473v2*.

Polina Kirichenko, Mark Ibrahim, Kamalika Chaudhuri, and Samuel J Bell. 2026. Abstentionbench: Reasoning llms fail on unanswerable questions. *Advances in Neural Information Processing Systems*, 38.

Zhenyan Lu, Xiang Li, Dongqi Cai, Rongjie Yi, Fangming Liu, Xiwen Zhang, Nicholas D Lane, and Mengwei Xu. 2024. Small language models: Survey, measurements, and insights. *arXiv preprint arXiv:2409.15790*.

Andrey Malinin and Mark Gales. 2020. Uncertainty estimation in autoregressive structured prediction. *arXiv preprint arXiv:2002.07650*.

Jingyi Ren, Ante Wang, Yunghwei Lai, Xiaolong Wang, Linlu Gong, Weitao Li, Weizhi Ma, and Yang Liu. 2026. Beyond" i don't know": Evaluating llm self-awareness in discriminating data and model uncertainty. *arXiv preprint arXiv:2604.17293*.

Ke Shen and Mayank Kejriwal. 2025. Defining and evaluating decision and composite risk in language models applied to natural language inference. *Engineering Applications of Artificial Intelligence*, 161:112253.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. 2019. CommonsenseQA: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4149–4158, Minneapolis, Minnesota. Association for Computational Linguistics.

Christian Tomani, Kamalika Chaudhuri, Ivan Evtimov, Daniel Cremers, and Mark Ibrahim. 2024. Uncertainty-based abstention in llms improves safety and reduces hallucinations. *arXiv preprint arXiv:2404.10960*.

Fali Wang, Zhiwei Zhang, Xianren Zhang, Zongyu Wu, Tzuhao Mo, Qiuhao Lu, Wanjing Wang, Rui Li, Junjie Xu, Xianfeng Tang, and 1 others. 2025. A comprehensive survey of small language models in the era of large language models: Techniques, enhancements, applications, collaboration with llms, and trustworthiness. *ACM Transactions on Intelligent Systems and Technology*, 16(6):1–87.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, and 1 others. 2024. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *Advances in Neural Information Processing Systems*, 37:95266–95290.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Bingbing Wen, Jihan Yao, Shangbin Feng, Chenjun Xu, Yulia Tsvetkov, Bill Howe, and Lucy Lu Wang. 2025. Know your limits: A survey of abstention in large language models. *Transactions of the Association for Computational Linguistics*, 13:529–556.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, and 1 others. 2023. Lima: Less is more for alignment. *Advances in Neural Information Processing Systems*, 36:55006–55021.

Runchuan Zhu, Zhipeng Ma, Jiang Wu, Junyuan Gao, Jiaqi Wang, Dahua Lin, and Conghui He. 2025. Utilize the flow before stepping into the same river twice: Certainty represented knowledge flow for refusal-aware instruction tuning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 26157–26165.

Haotian Zong, Binze Li, Yufei Long, Sinyin Chang, Jialong Wu, and Gillian K Hadfield. 2026. I-calm: Incentivizing confidence-aware abstention for llm hallucination mitigation. *arXiv preprint arXiv:2604.03904*.

Appendix Contents

A Prompt, Models and Datasets

Figure 3 shows the prompt template used for the multiple-choice question answering used in experiments. Tables 2 and 3 provide more information about the models and datasets used respectively.

B LoRA Hyperparameter Details

Training Hyperparameters Hyperparameters for all LoRA model trainings are set as follows:

- Learning rate: 2×10^{-4}

- Maximum prompt length: 1024

- Batch size: 64

- LoRA rank: 32

Implementation We use the Tinker library for implementing LoRA fine-tuning.

Dataset-specific Sample Counts The number of samples used for fine-tuning varies by dataset:

- CommonsenseQA: 9000 samples

- MMLU-Pro: 10000 samples

- QASC: 8000 samples

- SuperGPQA: 10000 samples

C Entropy Thresholding Baseline

The threshold value of mean + standard deviation was selected from a pool of statistical candidates for the thresholds (mean, mean + std/2, mean + std, mean + 2*std). Figure 4 shows how separation of responses for abstention works on the overall entropy distribution.

You are given a question and some options. Output the correct option letter only and nothing else.
<question>
For the two linear equations 2 * x + 3 * y = 10 and 4 * x + 4 * y = 12 with variables x and y. Use cramer's rule to solve these two variables.
</question>
<options>
(A) [4, 1]
(B) [-2, 6]
(C) [3, 2]
(D) [-1, 4]
(E) I don't know
</options>
The correct option is: (

Figure 3: Prompt template used in the MCQA tasks.

Table 2: List of models evaluated in this study. Release dates are approximate and sourced from Hugging Face and arXiv.

Model	Parameter Count	Release Date	License
mistralai/Mistral-7B-Instruct-v0.3	7B	May 22, 2024	Apache 2.0
meta-llama/Llama-3.1-8B-Instruct	8B	July 23, 2024	Llama 3.1 Community License Agreement
ibm-granite/granite-3.3-2b-instruct	2B	April 16, 2025	Apache 2.0
Qwen/Qwen3-4B-Instruct-2507	4B	August 5, 2025	Apache 2.0

Table 3: Summary of datasets used in this study. Release dates are approximate and sourced from Hugging Face and arXiv.

Dataset	Description	Release Date	License
CommonsenseQA	Benchmark for evaluating common-sense reasoning capabilities through multiple-choice questions.	November 2, 2018	MIT
QASC	Question-answering dataset requiring compositional reasoning and multi-step inference across multiple facts.	October 21, 2019	Creative Commons Attribution 4.0
MMLU-Pro	Enhanced MMLU benchmark covering STEM, social sciences, and humanities with challenging multiple-choice questions.	May 8, 2024	MIT
SuperGPQA	Graduate-level question-answering benchmark covering advanced concepts in physics, chemistry, and biology.	February 20, 2025	Open Data Commons License Attribution

Figure 4: Entropy distribution for the Llama model on CommonsenseQA dataset comparing original and augmented prompts. The histogram shows the distribution of entropy values across correct predictions (green) and incorrect predictions (red). The dashed line indicates the threshold (mean + standard deviation) used to determine whether predictions should be abstained from. This visualization demonstrates how entropy-based thresholding leverages the overlap between the two distributions to selectively abstain from low-confidence predictions.

D Results of Finetuned models

Tables 4 compares the performance of Second Guess against the baselines for the finetuned Qwen and Llama models in isolation. Table 5 shows how Second Guess helps the finetuned Qwen and Llama models in comparison to their base counterparts.

E Results for Baseline Methods

Tables 6, 7, 8, 9, 10, and 11 contain per-(dataset, model) results for Original, Augmented, Self-Evaluation, Entropy Thresholding (Original), Entropy Thresholding (Augmented), and Second Guess (Ours*) respectively

Table 4: Average performance for fine-tuned models, each evaluated only on its fine-tuning dataset. Cells show the mean and standard deviation of metric value followed by the averaged percentage change vs the Original baseline.

Method	Precision ↑	Error Rate ↓	Composite Risk ↓
Original	68.12 ± 18.29	31.88 ± 18.29	31.88 ± 18.29
Augmented	70.19 ± 17.71 (+2.06)	29.38 ± 17.05 (-2.50)	29.38 ± 17.05 (-2.50)
Self-Evaluation	**75.59 ± 18.23 (+7.46)**	24.00 ± 18.13 (-7.88)	24.00 ± 18.13 (-7.88)
Entropy Thresholding (Original)	73.40 ± 21.31 (+5.27)	24.50 ± 22.23 (-7.38)	31.25 ± 17.61 (-0.63)
Entropy Thresholding (Augmented)	74.20 ± 19.96 (+6.08)	22.38 ± 18.75 (-9.50)	30.50 ± 14.31 (-1.38)
Second Guess (Ours*)	75.28 ± 16.05 (+7.16)	**17.38 ± 6.99 (-14.50)**	**23.88 ± 11.43 (-8.00)**

Table 5: Second Guess average performance comparing base and fine-tuned variants of Qwen and Llama, restricted to the datasets where both variants are available. Each cell shows the mean and standard deviation of metric value followed by the averaged percentage change vs the Original baseline.

Variant	Precision ↑	Error Rate ↓	Composite Risk ↓
Qwen (Base)	73.94 ± 14.45 (+8.94)	17.75 ± 5.56 (-17.25)	25.25 ± 9.54 (-9.75)
Qwen (FT)	74.97 ± 17.02 (+5.72)	17.50 ± 6.81 (-13.25)	25.50 ± 11.62 (-5.25)
Llama (Base)	68.22 ± 18.87 (+6.97)	21.75 ± 7.27 (-17.00)	29.25 ± 9.11 (-9.50)
Llama (FT)	75.59 ± 17.64 (+8.59)	17.25 ± 8.22 (-15.75)	22.25 ± 12.76 (-10.75)

Table 6: Original baseline per-(dataset, model) results across all models (base and fine-tuned). Raw metric values.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	72.00	28.00	28.00
CommonsenseQA	Llama	80.00	20.00	20.00
CommonsenseQA	Llama-FT	86.00	14.00	14.00
CommonsenseQA	Mistral	76.00	24.00	24.00
CommonsenseQA	Qwen	86.00	14.00	14.00
CommonsenseQA	Qwen-FT	86.00	14.00	14.00
MMLU Pro	Granite	47.00	53.00	53.00
MMLU Pro	Llama	59.00	41.00	41.00
MMLU Pro	Llama-FT	65.00	35.00	35.00
MMLU Pro	Mistral	49.00	51.00	51.00
MMLU Pro	Qwen	61.00	39.00	39.00
MMLU Pro	Qwen-FT	69.00	31.00	31.00
QASC	Granite	67.00	33.00	33.00
QASC	Llama	74.00	26.00	26.00
QASC	Llama-FT	77.00	23.00	23.00
QASC	Mistral	62.00	38.00	38.00
QASC	Qwen	72.00	28.00	28.00
QASC	Qwen-FT	80.00	20.00	20.00
SuperGPQA	Granite	41.00	59.00	59.00
SuperGPQA	Llama	32.00	68.00	68.00
SuperGPQA	Llama-FT	40.00	60.00	60.00
SuperGPQA	Mistral	37.00	63.00	63.00
SuperGPQA	Qwen	41.00	59.00	59.00
SuperGPQA	Qwen-FT	42.00	58.00	58.00
Avg	*All*	62.54 ± 17.34	37.46 ± 17.34	37.46 ± 17.34

Table 7: Augmented per-(dataset, model) results across all models (base and fine-tuned). Each cell shows the metric value with percentage change vs Original.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	74.75 (+2.75)	25.00 (-3.00)	25.00 (-3.00)
CommonsenseQA	Llama	78.00 (-2.00)	22.00 (+2.00)	22.00 (+2.00)
CommonsenseQA	Llama-FT	87.00 (+1.00)	13.00 (-1.00)	13.00 (-1.00)
CommonsenseQA	Mistral	75.76 (-0.24)	24.00 (+0.00)	24.00 (+0.00)
CommonsenseQA	Qwen	85.00 (-1.00)	15.00 (+1.00)	15.00 (+1.00)
CommonsenseQA	Qwen-FT	85.71 (-0.29)	14.00 (+0.00)	14.00 (+0.00)
MMLU Pro	Granite	52.13 (+5.13)	45.00 (-8.00)	45.00 (-8.00)
MMLU Pro	Llama	61.62 (+2.62)	38.00 (-3.00)	38.00 (-3.00)
MMLU Pro	Llama-FT	69.00 (+4.00)	31.00 (-4.00)	31.00 (-4.00)
MMLU Pro	Mistral	51.06 (+2.06)	46.00 (-5.00)	46.00 (-5.00)
MMLU Pro	Qwen	66.33 (+5.33)	33.00 (-6.00)	33.00 (-6.00)
MMLU Pro	Qwen-FT	69.00 (+0.00)	31.00 (+0.00)	31.00 (+0.00)
QASC	Granite	69.07 (+2.07)	30.00 (-3.00)	30.00 (-3.00)
QASC	Llama	73.00 (-1.00)	27.00 (+1.00)	27.00 (+1.00)
QASC	Llama-FT	84.00 (+7.00)	16.00 (-7.00)	16.00 (-7.00)
QASC	Mistral	68.69 (+6.69)	31.00 (-7.00)	31.00 (-7.00)
QASC	Qwen	71.72 (-0.28)	28.00 (+0.00)	28.00 (+0.00)
QASC	Qwen-FT	78.79 (-1.21)	21.00 (+1.00)	21.00 (+1.00)
SuperGPQA	Granite	35.79 (-5.21)	61.00 (+2.00)	61.00 (+2.00)
SuperGPQA	Llama	36.00 (+4.00)	64.00 (-4.00)	64.00 (-4.00)
SuperGPQA	Llama-FT	48.00 (+8.00)	52.00 (-8.00)	52.00 (-8.00)
SuperGPQA	Mistral	31.25 (-5.75)	66.00 (+3.00)	66.00 (+3.00)
SuperGPQA	Qwen	46.46 (+5.46)	53.00 (-6.00)	53.00 (-6.00)
SuperGPQA	Qwen-FT	40.00 (-2.00)	57.00 (-1.00)	57.00 (-1.00)
Avg	*All*	64.09 ± 17.27 (+1.55)	35.12 ± 16.51 (-2.33)	35.12 ± 16.51 (-2.33)

Table 8: Self-Evaluation per-(dataset, model) results across all models (base and fine-tuned). Each cell shows the metric value with percentage change vs Original.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	72.92 (+0.92)	26.00 (-2.00)	26.00 (-2.00)
CommonsenseQA	Llama	86.57 (+6.57)	9.00 (-11.00)	9.00 (-11.00)
CommonsenseQA	Llama-FT	86.87 (+0.87)	13.00 (-1.00)	13.00 (-1.00)
CommonsenseQA	Mistral	78.00 (+2.00)	22.00 (-2.00)	22.00 (-2.00)
CommonsenseQA	Qwen	86.87 (+0.87)	13.00 (-1.00)	13.00 (-1.00)
CommonsenseQA	Qwen-FT	87.37 (+1.37)	12.00 (-2.00)	12.00 (-2.00)
MMLU Pro	Granite	49.28 (+2.28)	35.00 (-18.00)	35.00 (-18.00)
MMLU Pro	Llama	70.97 (+11.97)	18.00 (-23.00)	18.00 (-23.00)
MMLU Pro	Llama-FT	65.00 (+0.00)	35.00 (+0.00)	35.00 (+0.00)
MMLU Pro	Mistral	48.00 (-1.00)	52.00 (+1.00)	52.00 (+1.00)
MMLU Pro	Qwen	64.89 (+3.89)	33.00 (-6.00)	33.00 (-6.00)
MMLU Pro	Qwen-FT	70.10 (+1.10)	29.00 (-2.00)	29.00 (-2.00)
QASC	Granite	67.39 (+0.39)	30.00 (-3.00)	30.00 (-3.00)
QASC	Llama	74.67 (+0.67)	19.00 (-7.00)	19.00 (-7.00)
QASC	Llama-FT	77.00 (+0.00)	23.00 (+0.00)	23.00 (+0.00)
QASC	Mistral	64.00 (+2.00)	36.00 (-2.00)	36.00 (-2.00)
QASC	Qwen	73.47 (+1.47)	26.00 (-2.00)	26.00 (-2.00)
QASC	Qwen-FT	78.95 (-1.05)	20.00 (+0.00)	20.00 (+0.00)
SuperGPQA	Granite	39.73 (-1.27)	44.00 (-15.00)	44.00 (-15.00)
SuperGPQA	Llama	35.82 (+3.82)	43.00 (-25.00)	43.00 (-25.00)
SuperGPQA	Llama-FT	39.39 (-0.61)	60.00 (+0.00)	60.00 (+0.00)
SuperGPQA	Mistral	37.37 (+0.37)	62.00 (-1.00)	62.00 (-1.00)
SuperGPQA	Qwen	43.62 (+2.62)	53.00 (-6.00)	53.00 (-6.00)
SuperGPQA	Qwen-FT	100.00 (+58.00)	0.00 (-58.00)	0.00 (-58.00)
Avg	*All*	66.59 ± 18.41 (+4.05)	29.71 ± 16.35 (-7.75)	29.71 ± 16.35 (-7.75)

Table 9: Entropy Thresholding (Original) per-(dataset, model) results across all models (base and fine-tuned). Each cell shows the metric value with percentage change vs Original.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	71.72 (-0.28)	28.00 (+0.00)	29.00 (+1.00)
CommonsenseQA	Llama	90.00 (+10.00)	8.00 (-12.00)	16.00 (-4.00)
CommonsenseQA	Llama-FT	89.02 (+3.02)	9.00 (-5.00)	22.00 (+8.00)
CommonsenseQA	Mistral	84.71 (+8.71)	13.00 (-11.00)	17.00 (-7.00)
CommonsenseQA	Qwen	88.54 (+2.54)	11.00 (-3.00)	12.00 (-2.00)
CommonsenseQA	Qwen-FT	94.74 (+8.74)	4.00 (-10.00)	18.00 (+4.00)
MMLU Pro	Granite	47.87 (+0.87)	49.00 (-4.00)	51.00 (-2.00)
MMLU Pro	Llama	61.25 (+2.25)	31.00 (-10.00)	41.00 (+0.00)
MMLU Pro	Llama-FT	69.77 (+4.77)	26.00 (-9.00)	31.00 (-4.00)
MMLU Pro	Mistral	52.44 (+3.44)	39.00 (-12.00)	45.00 (-6.00)
MMLU Pro	Qwen	65.06 (+4.06)	29.00 (-10.00)	36.00 (-3.00)
MMLU Pro	Qwen-FT	79.49 (+10.49)	16.00 (-15.00)	23.00 (-8.00)
QASC	Granite	68.75 (+1.75)	30.00 (-3.00)	31.00 (-2.00)
QASC	Llama	78.75 (+4.75)	17.00 (-9.00)	28.00 (+2.00)
QASC	Llama-FT	84.52 (+7.52)	13.00 (-10.00)	19.00 (-4.00)
QASC	Mistral	65.52 (+3.52)	30.00 (-8.00)	35.00 (-3.00)
QASC	Qwen	76.40 (+4.40)	21.00 (-7.00)	25.00 (-3.00)
QASC	Qwen-FT	87.65 (+7.65)	10.00 (-10.00)	19.00 (-1.00)
SuperGPQA	Granite	43.96 (+2.96)	51.00 (-8.00)	52.00 (-7.00)
SuperGPQA	Llama	31.96 (-0.04)	66.00 (-2.00)	67.00 (-1.00)
SuperGPQA	Llama-FT	40.00 (+0.00)	60.00 (+0.00)	60.00 (+0.00)
SuperGPQA	Mistral	41.56 (+4.56)	45.00 (-18.00)	50.00 (-13.00)
SuperGPQA	Qwen	44.30 (+3.30)	44.00 (-15.00)	50.00 (-9.00)
SuperGPQA	Qwen-FT	42.00 (+0.00)	58.00 (+0.00)	58.00 (+0.00)
Avg	*All*	66.67 ± 19.34 (+4.12)	29.50 ± 18.28 (-7.96)	34.79 ± 15.95 (-2.67)

Table 10: Entropy Thresholding (Augmented) per-(dataset, model) results across all models (base and fine-tuned). Each cell shows the metric value with percentage change vs Original.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	74.49 (+2.49)	24.00 (-4.00)	25.00 (-3.00)
CommonsenseQA	Llama	85.19 (+5.19)	12.00 (-8.00)	21.00 (+1.00)
CommonsenseQA	Llama-FT	88.89 (+2.89)	9.00 (-5.00)	24.00 (+10.00)
CommonsenseQA	Mistral	79.76 (+3.76)	17.00 (-7.00)	25.00 (+1.00)
CommonsenseQA	Qwen	87.37 (+1.37)	12.00 (-2.00)	14.00 (+0.00)
CommonsenseQA	Qwen-FT	90.00 (+4.00)	8.00 (-6.00)	20.00 (+6.00)
MMLU Pro	Granite	48.35 (+1.35)	42.00 (-11.00)	47.00 (-6.00)
MMLU Pro	Llama	69.23 (+10.23)	23.00 (-18.00)	30.00 (-11.00)
MMLU Pro	Llama-FT	72.41 (+7.41)	24.00 (-11.00)	30.00 (-5.00)
MMLU Pro	Mistral	50.00 (+1.00)	34.00 (-17.00)	42.00 (-9.00)
MMLU Pro	Qwen	72.09 (+11.09)	22.00 (-17.00)	25.00 (-14.00)
MMLU Pro	Qwen-FT	78.21 (+9.21)	17.00 (-14.00)	25.00 (-6.00)
QASC	Granite	69.07 (+2.07)	28.00 (-5.00)	28.00 (-5.00)
QASC	Llama	80.49 (+6.49)	16.00 (-10.00)	23.00 (-3.00)
QASC	Llama-FT	89.16 (+12.16)	9.00 (-14.00)	19.00 (-4.00)
QASC	Mistral	71.43 (+9.43)	24.00 (-14.00)	32.00 (-6.00)
QASC	Qwen	75.56 (+3.56)	22.00 (-6.00)	25.00 (-3.00)
QASC	Qwen-FT	87.01 (+7.01)	10.00 (-10.00)	21.00 (+1.00)
SuperGPQA	Granite	36.26 (-4.74)	53.00 (-6.00)	54.00 (-5.00)
SuperGPQA	Llama	36.56 (+4.56)	59.00 (-9.00)	61.00 (-7.00)
SuperGPQA	Llama-FT	50.55 (+10.55)	45.00 (-15.00)	47.00 (-13.00)
SuperGPQA	Mistral	32.47 (-4.53)	49.00 (-14.00)	54.00 (-9.00)
SuperGPQA	Qwen	47.50 (+6.50)	41.00 (-18.00)	49.00 (-10.00)
SuperGPQA	Qwen-FT	37.37 (-4.63)	57.00 (-1.00)	58.00 (+0.00)
Avg	*All*	67.06 ± 19.29 (+4.52)	27.38 ± 16.20 (-10.08)	33.29 ± 14.11 (-4.17)

Table 11: Second Guess (Ours*) per-(dataset, model) results across all models (base and fine-tuned). Each cell shows the metric value wih Wpercentage change vs Original.

Dataset	Model	Precision ↑	Error Rate ↓	Composite Risk ↓
CommonsenseQA	Granite	81.82 (+9.82)	14.00 (-14.00)	23.00 (-5.00)
CommonsenseQA	Llama	83.15 (+3.15)	15.00 (-5.00)	21.00 (+1.00)
CommonsenseQA	Llama-FT	89.36 (+3.36)	10.00 (-4.00)	12.00 (-2.00)
CommonsenseQA	Mistral	83.33 (+7.33)	14.00 (-10.00)	20.00 (-4.00)
CommonsenseQA	Qwen	88.30 (+2.30)	11.00 (-3.00)	14.00 (+0.00)
CommonsenseQA	Qwen-FT	88.17 (+2.17)	11.00 (-3.00)	15.00 (+1.00)
MMLU Pro	Granite	63.79 (+16.79)	21.00 (-32.00)	31.00 (-22.00)
MMLU Pro	Llama	72.06 (+13.06)	19.00 (-22.00)	29.00 (-12.00)
MMLU Pro	Llama-FT	78.38 (+13.38)	16.00 (-19.00)	23.00 (-12.00)
MMLU Pro	Mistral	58.46 (+9.46)	27.00 (-24.00)	38.00 (-13.00)
MMLU Pro	Qwen	77.14 (+16.14)	16.00 (-23.00)	23.00 (-16.00)
MMLU Pro	Qwen-FT	80.00 (+11.00)	15.00 (-16.00)	24.00 (-7.00)
QASC	Granite	73.17 (+6.17)	22.00 (-11.00)	29.00 (-4.00)
QASC	Llama	76.92 (+2.92)	21.00 (-5.00)	25.00 (-1.00)
QASC	Llama-FT	84.62 (+7.62)	14.00 (-9.00)	14.00 (-9.00)
QASC	Mistral	72.37 (+10.37)	21.00 (-17.00)	28.00 (-10.00)
QASC	Qwen	76.47 (+4.47)	20.00 (-8.00)	27.00 (-1.00)
QASC	Qwen-FT	81.72 (+1.72)	17.00 (-3.00)	21.00 (+1.00)
SuperGPQA	Granite	46.51 (+5.51)	23.00 (-36.00)	44.00 (-15.00)
SuperGPQA	Llama	40.74 (+8.74)	32.00 (-36.00)	42.00 (-26.00)
SuperGPQA	Llama-FT	50.00 (+10.00)	29.00 (-31.00)	40.00 (-20.00)
SuperGPQA	Mistral	46.34 (+9.34)	22.00 (-41.00)	40.00 (-23.00)
SuperGPQA	Qwen	53.85 (+12.85)	24.00 (-35.00)	37.00 (-22.00)
SuperGPQA	Qwen-FT	50.00 (+8.00)	27.00 (-31.00)	42.00 (-16.00)
Avg	*All*	70.69 ± 15.32 (+8.15)	19.21 ± 5.92 (-18.25)	27.58 ± 9.79 (-9.88)

F Second Guess: Change Breakdown for Remaining (Dataset, Model) Pairs

Table 12 shows how the responses given my models vary between the Original and Augmented prompt in the Second Guess technique, for all models and datasets evaluated.

Table 12: Breakdown of paired-question outcomes under Second Guess across all remaining (dataset, model) pairs. Columns split by correctness on the Original prompt; within each group, the model's Augmented-prompt answer is one of: IDK, a different non-IDK option, or unchanged from the Original answer ("Preserved"). The two non-Preserved columns are forced to IDK by Second Guess. Counts are out of the paired-question set.

| Dataset | Model | Originally Correct | | | | Originally Incorrect | | | |
		$\rightarrow$ IDK	$\rightarrow$ Other	Preserved	Total	$\rightarrow$ IDK	$\rightarrow$ Other	Preserved	Total
CommonsenseQA	Granite	0	9	63	72	1	13	14	28
CommonsenseQA	Llama	0	6	74	80	0	5	15	20
CommonsenseQA	Llama-FT	0	2	84	86	0	4	10	14
CommonsenseQA	Mistral	0	6	70	76	1	9	14	24
CommonsenseQA	Qwen	0	3	83	86	0	3	11	14
CommonsenseQA	Qwen-FT	2	2	82	86	0	3	11	14
MMLU Pro	Granite	2	8	37	47	4	28	21	53
MMLU Pro	Llama	0	10	49	59	1	21	19	41
MMLU Pro	Llama-FT	0	7	58	65	0	19	16	35
MMLU Pro	Mistral	1	10	38	49	5	19	27	51
MMLU Pro	Qwen	0	7	54	61	2	21	16	39
MMLU Pro	Qwen-FT	0	9	60	69	0	16	15	31
QASC	Granite	1	6	60	67	2	9	22	33
QASC	Llama	0	4	70	74	0	5	21	26
QASC	Llama-FT	0	0	77	77	0	9	14	23
QASC	Mistral	1	6	55	62	0	17	21	38
QASC	Qwen	1	6	65	72	0	8	20	28
QASC	Qwen-FT	1	3	76	80	0	3	17	20
SuperGPQA	Granite	2	19	20	41	3	33	23	59
SuperGPQA	Llama	0	10	22	32	0	36	32	68
SuperGPQA	Llama-FT	0	11	29	40	0	31	29	60
SuperGPQA	Mistral	3	15	19	37	1	40	22	63
SuperGPQA	Qwen	0	13	28	41	1	34	24	59
SuperGPQA	Qwen-FT	2	13	27	42	3	28	27	58