Learning Binary Multi-Scale Games on Networks

Abstract

Network games are a natural modeling framework for strategic interactions of agents whose actions have local impact on others. Recently, a multi-scale network game model has been proposed to capture local effects at multiple network scales, such as among both individuals and groups. We propose a framework to learn the utility functions of binary multi-scale games from agents' behavioral data. Departing from much prior work in this area, we model agent behavior as following logit-response dynamics, rather than acting according to a Nash equilibrium. This defines a generative time-series model of joint behavior of both agents and groups, which enables us to naturally cast the learning problem as maximum likelihood estimation (MLE). We show that in the important special case of multi-scale linear-quadratic games, this MLE problem is convex. Extensive experiments using both synthetic and real data demonstrate that our proposed modeling and learning approach is effective in both game parameter estimation as well as prediction of future behavior, even when we learn the game from only a single behavior time series. Furthermore, we show how to use our framework to develop a statistical test for the existence of multi-scale structure in the game, and use it to demonstrate that real time-series data indeed exhibits such structure.

2 INTRODUCTION

A broad class of scenarios involving strategic interaction among a large collection of agents can be modeled by network (graphical) games, including investment in a public good [Bramoullé and Kranton, 2007, Grossklags et al., 2008], information diffusion [Galeotti et al., 2010], peer effects in social networks [Ballester et al., 2006], and adoption of innovation [Jackson, 2010]. A prominent feature of network games is local effects, where an agent's utility depends only on the actions of its network neighbors [Kearns et al., 2001]. Many real networks, however, additionally exhibit group or community structure [Girvan and Newman, 2002], and Jin et al. [2021] recently proposed a multi-scale network game model that embeds such structure into the network game representation. However, a multi-scale game representation is often not given a priori, and instead what is available is time-series data of actual behavior, such as trade interactions among nations, or homicides arising from organized crime activities. Our goal is to develop a scalable framework for learning parametric models of multi-scale network games from such time-series data.

The general problem of learning utility functions in games from observed behavior has been extensively studied [Chajewska et al., 2001, Vorobeychik et al., 2007, Waugh et al., 2011, Honorio and Ortiz, 2015, Garg and Jaakkola, 2016, Leng et al., 2020]. A common assumption in this line of work is that agents are *fully rational* in that they act according to a Nash equilibrium. However, much experimental evidence suggests that this assumption is commonly violated [Andreoni and Miller, 1993, Camerer, 2003]. In addition, time-series behavior data often exhibits intertemporal dependence, such as the self-exciting nature of crime data [Mohler et al., 2011], a feature that is lost if behavior is modeled by a Nash equilibrium of a single-shot game.

We propose to use *logit-response dynamics (LRD)*—a classic framework to capture bounded rational behavior in games [Blume, 1993, Alós-Ferrer and Netzer, 2010]—as a solution concept in learning utility functions from time-series data representing behavior in repeated strategic interactions. In LRD, each action by a player is played with a probability proportional to its utility, with actions of the other players fixed to what was played in the previous time step. LRD has two advantages over Nash equilibrium. First, it explicitly captures intertemporal dependence in behavior, since agents are responding to previously observed choices by others; in contrast, Nash equilibrium behavior in a one-

Submitted to the 38th Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only**.

shot game exhibits no temporal dependence. Second, LRD solution concept is more psychologically plausible than Nash equilibrium behavior [Haile et al., 2008, Fudenberg et al., 1998, Stahl II and Wilson, 1994]. While Duong et al. [2010] also explicitly modeled intertemporal dependence in behavior, their approach was limited to consensus games, and required knowledge of utilities associated with player actions. Finally, ours is the first approach to consider multi-scale structure of strategic interactions on networks.

Armed with the game-theoretic generative model of time-series behavior data, we formulate the game learning problem as maximum likelihood estimation (MLE). In general, this problem can be (approximately) solved using gradient ascent; however, neither optimality nor consistency of estimation is guaranteed in our setting, where data is not generated i.i.d. To address this, we instantiate our framework in the context of parametric multi-scale linear-quadratic utility models. We prove that in this special case, the MLE problem is convex and can thus be solved efficiently. Our final technical contribution is a likelihood ratio test that enables us to statistically determine whether behavioral data generated by a multi-scale game model actually reflects multi-scale structure, where the null hypothesis is that only single-scale interactions significantly impact behavior.

We use extensive experiments on both synthetic and real datasets to demonstrate that the proposed approach effectively learns game parameters from time-series data. Furthermore, we show that our approach outperforms state-of-the-art baselines in predicting future agent behavior. Finally, we show that the game models we learn on real data offer interesting insights about behavior in the associated settings. For example, in the case of gang violence data, we show that the model we learn exhibits temporal self-excitation of homicides at multiple scales (that is, stemming from both individual gang member interaction, as well as interactions among gangs), generalizing insights from prior literature [Mohler et al., 2011].

Related Work Preference (or utility) elicitation, or inferring preferences of agents through active interaction, is a classic problem in decision theory [Fischhoff and Manski, 2000, Blum et al., 2004]. The passive counterpart of preference elicitation is preference or utility learning from observed time-series data of behavior [Chajewska et al., 2001, Nielsen and Jensen, 2004]. Of direct relevance to our work is the literature on learning utility functions of players in game-theoretic models of their behavior. In this there are two major strands: learning utilities from observations of behavior time-series [Honorio and Ortiz, 2015, Garg and Jaakkola, 2016, Leng et al., 2020, Ling et al., 2018, Waugh et al., 2011], and learning utilities from observed payoffs [Duong et al., 2009, Vorobeychik et al., 2007]. The principal difference between our framework and the former set of approaches stems from our use of LRD model of behavior, which considerably simplifies the learning problem

and naturally allows us to capture temporal interdependence. Our approach draws some inspiration from the framework for learning from collective behavior by Kearns and Wortman [2008]. However, the key general result in Kearns and Wortman [2008] requires learning with reset (i.e., a large collection of independently generated sequences of behavior), whereas we learn from only a single observed behavior sequence. Duong et al. [2010], like us, explicitly modeled intertemporal dependence in behavior. However, their approach was limited to consensus games, and required knowledge of player utilities.

3 MODEL

3.1 BINARY MULTI-SCALE GAME ON NETWORKS

A binary multi-scale game is defined on a network, which we represent by the adjacency matrix A. The network can be directed or undirected, weighted or unweighted. We only assume that there are no self-loops in the network. For expository purposes, A is unweighted and undirected in the present paper. The agents in the game are situated on the vertices of A, denoted by $\mathcal{V} = \{v_1, \ldots, v_n\}$, and are partitioned into K groups, i.e., $\mathcal{V} = \cup_{i=1}^{K} \mathcal{G}_i$, and $\mathcal{G}_i \cap \mathcal{G}_j = \emptyset$ for any $i \neq j$. We use the set $\mathcal{J} = \{\mathcal{G}_i \mid i = 1, \ldots, K\}$ to represent the K groups. Intuitively, we can use each group $\mathcal{G}_i$ to represent a neighborhood when the underlying network is an urban network, or an interest group if the underlying network is a social network. The group membership of agent i is encoded by a mapping $\alpha(i)$ from the agent's index to its group index, i.e., $\alpha(i) = j$ for $i \in \mathcal{G}_j$. Throughout, we assume that the network structure A, the mapping $\alpha(i)$, and the group structure $\mathcal{J}$ are known.

We use $x_i \in \mathcal{S}_i$ to represent agent i's action, where $\mathcal{S}_i = \{0, 1\}$. We use public goods investment as a running example, where $x_i = 1$ (resp. $x_i = 0$) means that agent i invests (resp. does not invest) in the public goods. Consequently, we will refer the choice $x_i = 1$ as an agent's decision to invest, while $x_i = 0$ means that i decides not to invest. The marginal cost of making an investment is captured by a constant $c_i \in \mathbb{R}_+$, e.g., monetary cost, time, and/or effort exerted. The action profile of all agents is represented by $x \in \{0, 1\}^n$, where the i-th entry is x_i. We use the set $\mathcal{N}(i)$ to represent agent i's neighbors. The action profile restricted to agent i's neighbors is $x_{\mathcal{N}(i)}$.

To capture multi-scale (group) structure of the game, we define a vector $y \in \mathbb{R}^K$, which represents some aggregate statistic at the group level. Typically, y_i will be the total investment by group i, i.e., $y_i = \sum_{j \in \mathcal{G}_i} x_j$. We emphasize, however, that the definition of y is quite general, e.g., y_i can also be the median investment from group i, or any other reasonable group-level statistic. The key idea behind the multi-scale representation is that while agents have concrete

knowledge about the behavior of those they regularly interact with (network neighbors), they only have higher-level knowledge about other groups, as captured by the associated statistics for those groups. A concrete example is vaccination: an agent usually has more specific knowledge about the vaccination status of her close friends, which is encoded by $\boldsymbol{x}_{\mathcal{N}(i)}$, but only aggregate vaccination information at the level of counties or states, which is captured by $\boldsymbol{y}$. The utility function of agent i is defined as follows:

$$u_i(x_i, \boldsymbol{x}_{-i}) = g_i\left(x_i, \boldsymbol{x}_{\mathcal{N}(i)}\right) + h_i(x_i, \boldsymbol{y}) - c_i x_i, \quad (1)$$

where $\boldsymbol{y}$ is implicitly a function of the full action profile $\boldsymbol{x}$. The function g_i models local effects between an agent and its direct neighbors, capturing the externality that agent i experiences from its neighbors' (and its own) investment. The function h_i generalizes local effects from the individual level to the group level, encoding the multi-scale structure in the game. The term $c_i x_i$ captures the cost of investment. Putting everything together, we define a *binary multi-scale game on networks* as a tuple $\texttt{b-MSGN}(\boldsymbol{A}, \mathcal{J}, \{\mathcal{S}_i\}, \{u_i\}_{i=1}^n)$, where $\boldsymbol{A}$ is the underlying network, $\mathcal{J}$ is the group structure, $\mathcal{S}_i$ are pure strategy sets of players, and u_i are player utilities defined in Equation (1).

3.2 LOGIT-RESPONSE DYNAMICS

When modeling agents' strategic behavior, a common assumption is that agents are *rational*, i.e., they always choose the action with the highest utility. This is formally modeled by the best-response rule: $x_i \in \arg\max_{x_i'} u_i(x_i', \boldsymbol{x}_{-i})$, where $\boldsymbol{x}_{-i}$ represents all agents' actions other than agent i. In the conventional Nash equilibrium solution concept that has been common in prior literature on learning games from data [Honorio and Ortiz, 2015, Leng et al., 2020], all players are assumed to simultaneously choose a best response to each other. In reality, however, an agent may not make completely rational decisions, due to 1) limited resources or computational power needed to precisely solve the argmax problem and 2) inability to perfectly assess small differences in its utility. Furthermore, a Nash equilibrium of a static game cannot capture intertemporal dependencies that may be present in time-series behavior data, and multiplicity of equilibria creates a further practical challenge in learning general-sum games from data. A common alternative to the Nash equilibrium solution concept is a *quantal response equilibrium (QRE)* [McKelvey and Palfrey, 1995], which was recently used in a framework for learning *two-player zero-sum* games from data [Ling et al., 2018]. However, multiplicity of equilibria (both Nash and QRE) in general-sum games has limited further progress.

Our key conceptual contribution is to combine bounded rationality in action choices with bounded rationality in dynamic agent behavior. While such combination seems entirely natural, we are the first to explore it in the context of learning games from time-series data. Our experiments below vindicate this approach, which resolves both the issue of multiplicity of equilibria and dynamic interdependencies in behavior. Specifically, we adopt a classic model of bounded-rational dynamic behavior: *logit-response dynamics (LRD)* [Blume, 1993, Alós-Ferrer and Netzer, 2010]. LRD presumes a repeated one-shot game in which agents select actions with probabilities proportional to their utilities (as in QRE) in every step, taking choices made by others as given from the previous step (*unlike* QRE). In our context, the probability of agent i choosing to invest ($x_i = 1$) in the next time step is

$$p(x_i^{t+1} = 1 \mid \boldsymbol{x}^t, \boldsymbol{y}^t) = \frac{e^{\gamma \cdot u_i(1, \boldsymbol{x}_{-i}^t, \boldsymbol{y}^t)}}{e^{\gamma \cdot u_i(1, \boldsymbol{x}_{-i}^t, \boldsymbol{y}^t)} + e^{\gamma \cdot u_i(0, \boldsymbol{x}_{-i}^t, \boldsymbol{y}^t)}}$$
$$= \frac{1}{1 + e^{\gamma \left(u_i(0, \boldsymbol{x}_{-i}^t, \boldsymbol{y}^t) - u_i(1, \boldsymbol{x}_{-i}^t, \boldsymbol{y}^t) \right)}}. \quad (2)$$

The scalar γ quantifies the noise level in the agent's decision-making. As γ goes to infinity, the logit-response converges to the best-response rule. For any $0 < \gamma < \infty$, the agent chooses non-best response with positive probability, and the actions yielding larger utility are chosen with higher probability. Throughout the paper, we assume that γ is known (in practice, we set it to 1, as it simply scales the utility functions). We define the probability $p(x_i^{t+1} = 1 \mid \boldsymbol{x}^t, \boldsymbol{y}^t)$ as the *investment probability* at time step $t + 1$. When the context is clear we use $p(x_i^{t+1})$ to represent the investment probability, omitting the dependence on $\boldsymbol{x}^t$ and $\boldsymbol{y}^t$.

In LRD, we assume that at each time step each agent updates its action independently according to the logit response function (2). Consequently, given $\boldsymbol{x}^t$ and $\boldsymbol{y}^t$ the agents' investment probabilities at time step $t + 1$ are conditionally independent, i.e., $p(x_i^{t+1})$ and $p(x_j^{t+1})$ are independent for $i \neq j$. The assumption of conditional independence conceptually utilizes the classic idea of Maximum Pseudo-Likelihood [Besag, 1974], which simplifies the derivation of the data likelihood by avoiding the computation of the normalization constant. Additionally, this property implies convergence of agents' behavior to a stationary distribution. Specifically, let $\mathcal{M}$ be the discrete Markov chain induced from the logit-response dynamics, with state space $\mathcal{S} = \{0, 1\}^n$. The transition probability $p(\boldsymbol{x}^{t+1} | \boldsymbol{x}^t)$ equals to $\prod_{i=1}^n p(x_i^{t+1} = 1 \mid \boldsymbol{x}^t, \boldsymbol{y}^t)$, which by definition is always positive, including the transition probability from a state to itself. Consequently, the state transition graph of $\mathcal{M}$ is strongly connected and aperiodic.[1] This in turn implies that the stationary distribution π of the Markov chain exists and is unique [Chung and Graham, 1997, Wildstrom, 2005].

---

[1]The state transition graph of a discrete Markov chain is aperiodic if the transition probability from a state to itself is positive.

4 THE LEARNING FRAMEWORK

Since in practice we typically only have a single trail of past behavior to learn from, we consider the problem of learning a game model parameters from a single behavior sequence collected over l time steps, i.e., $\mathcal{D}_l = \{(\boldsymbol{x}^1, \boldsymbol{y}^1), \ldots, (\boldsymbol{x}^l, \boldsymbol{y}^l)\}$, where $\boldsymbol{x}^k$ is the action profile of all agents at time step k and $\boldsymbol{y}^k$ is the group-level statistics that capture aggregate behavior by each group in the multi-scale game. We assume that the utility functions of players u_i have parametric representations, with associated parameter vectors denoted by $\boldsymbol{\theta}_i \in \mathcal{F}_i := [-1, 1]^m$, where m is the dimension of $\boldsymbol{\theta}_i$; these are concatenations of the parameters of g_i and h_i (and the cost c_i), the two main constituent functions in player utilities. We use $\Theta = \{\boldsymbol{\theta}_1, \ldots, \boldsymbol{\theta}_n\}$ to represent all learnable parameters of the game, where $\Theta \in \Pi = \bigtimes_{i=1}^{n} \mathcal{F}_i$. The utility function in (1) is a high-level description; we will instantiate g_i and h_i to specific parametric functions below. We present a general likelihood-based approach for learning multi-scale games from such data, and subsequently study an important special case which admits efficient learning.

4.1 THE GENERAL CASE

The binary multi-scale game together with the logit-response dynamics define a generative time-series model of joint behavior of both agents and groups. We assume that $\boldsymbol{y}^t$ is a deterministic function of the individual-level action profile $\boldsymbol{x}^t$, which simplifies the derivation of the data likelihood, as the joint probability of $\boldsymbol{x}^{t+1}$ and $\boldsymbol{y}^{t+1}$ reduces to the marginal probability of $\boldsymbol{x}^{t+1}$. The generative model is a discrete Markov chain over action profiles. Omitting the dependence of the investment probability on $\boldsymbol{x}^t$ and $\boldsymbol{y}^t$, the data likelihood $\mathcal{L}(\mathcal{D}_l; \Theta)$ is formulated as follows:

$$\mathcal{L}(\mathcal{D}_l; \Theta) = p(\boldsymbol{x}^1) \prod_{t=1}^{l-1} p(\boldsymbol{x}^{t+1} | \boldsymbol{x}^t, \boldsymbol{y}^t) =$$

$$\prod_{t=1}^{l-1} \prod_{i=1}^{n} \left[p(x_i^{t+1} = 1) \right]^{x_i^{t+1}} \left[1 - p(x_i^{t+1} = 1) \right]^{1-x_i^{t+1}},$$

$$\tag{3}$$

where the last equality utilizes the independence of investment probabilities and the fact that $p(\boldsymbol{x}^1) = 1$. We learn the parameters Θ by resorting to the maximum likelihood estimation (MLE). In general, we can leverage gradient-based methods and automatic differentiation tools to maximize the likelihood, as long as the utility functions are differentiable.

With a slight abuse of notation, we use $\mathtt{b-MSGN}(\Theta)$ to represent the generative model (consisting of the game together with the logit-response dynamics solution concept), with the utility functions parameterized by Θ. We now instantiate the utility function to a specific parametric form. In particular, we consider the games with *linear-quadratic utility functions*, augmented with the h_i to account for the multi-scale

structures. The resulting MLE problem is convex, and can thus be (near-)optimally solved using interior point methods. We also develop a statistical test for the existence of multi-scale structure in this game based on the classic likelihood ratio test.

4.2 LEARNING MULTI-SCALE LINEAR-QUADRATIC GAMES

Linear-quadratic games have been used in much prior literature on network game modeling both in economics and machine learning [Ballester et al., 2006, Bramoullé and Kranton, 2007, Galeotti et al., 2020, Leng et al., 2020], with Leng et al. [2020] specifically considering the problem of learning network structure in such models from Nash equilibrium behavior by the agents. The standard utility function in linear-quadratic network games is defined as

$$u_i(x_i, \boldsymbol{x}_{-i}) = b_i x_i + \beta_i x_i \sum_{j \in \mathcal{V}} A_{i,j} x_j - c_i x_i^2, \tag{4}$$

where $b_i \geq 0$ is the marginal benefit of investing, $c_i \geq 0$ is the cost to invest, and $\beta_i \in \mathbb{R}$ captures peer effects from the neighbors' investment. When $\beta_i > 0$ (resp. $\beta_i < 0$) higher investment from the neighbors encourages agent i to make more (resp., less) investment.

To model the multi-scale structure in the game, we consider the following group-level aggregate function h_i:

$$h_i(x_i, \boldsymbol{y}) = \eta_i x_i \left(y_{\alpha(i)} - \frac{\sum_{g \in \mathcal{J} \setminus \{\mathcal{G}_{\alpha(i)}\}} y_g}{|\mathcal{J}| - 1} \right), \tag{5}$$

where $y_{\alpha(i)}$ is some group-level statistics from agent i's group and the second term in the parentheses is the average of the statistics from other groups. The difference models the relative magnitude of the statistics between agent i's group and other groups. When $\eta_i > 0$ (resp., $\eta_i < 0$), higher relative investment by agent i's group compared to other groups encourages (resp., discourages) i's own investment.

We augment the linear-quadratic payoff with the function h_i, leading to the *multi-scale linear-quadratic utility*:

$$u_i(x_i, \boldsymbol{x}_{-i}) = (b_i - c_i) x_i + \beta_i x_i \sum_{j \in \mathcal{V}} A_{i,j} x_j + h_i(x_i, \boldsymbol{y}). \tag{6}$$

The set $\boldsymbol{\theta}_i = \{b_i, \beta_i, \eta_i, c_i\}$ consists of the parameters we aim to learn from data. Note that as the action space in our setting is binary, the term $b_i x_i - c_i (x_i)^2$ becomes $(b_i - c_i) x_i$. As a result, accurately estimating the two parameters may not be feasible, as they can be shifted the same amount without changing the difference.[2] Therefore, we treat $b_i - c_i$ as a single *marginal benefit* that we estimate from data.

---

[2]This problem is not specific to our model: in prior literature, the cost constant c_i is usually set to $\frac{1}{2}$ in order to avoid the invariance of $b_i - c_i$ to the shifting.

As we now show, the key property of this multi-scale linear quadratic game model is that the resulting MLE problem is convex.

Proposition 4.1. *Consider a* b-MSGN$(\boldsymbol{A}, \mathcal{J}, \{u_i\}_{i=1}^n)$*. If* $\{u_i\}_{i=1}^n$ *are instantiated as the multi-scale linear-quadratic utilities, the resulting MLE optimization problem is convex.*

Proof. Recall that $\Theta \in \Pi = \bigtimes_{i=1}^n \mathcal{F}_i$, that is, a Cartesian product of a set of convex sets. Thus, the feasible region Π of the MLE is convex. In what follows, we show that the log-likelihoof function $\log \mathcal{L}(\mathcal{D}_l; \Theta)$ is concave w.r.t. Θ.

Note that $\log \mathcal{L}(\mathcal{D}_l; \Theta) = \sum_{t=1}^{l-1} \log p(\boldsymbol{x}^{t+1}|\boldsymbol{x}^t)$; it is sufficient to show that $\log p(\boldsymbol{x}^{t+1}|\boldsymbol{x}^t)$ is concave w.r.t. Θ for any $1 \leq t \leq l-1$. We expand $\log p(\boldsymbol{x}^{t+1}|\boldsymbol{x}^t)$ as follows:

$$\log p(\boldsymbol{x}^{t+1}|\boldsymbol{x}^t) =$$
$$\sum_{i=1}^n \Big[x_i^{t+1} \log p(x_i^{t+1} = 1)$$
$$+ (1 - x_i^{t+1}) \log \big[1 - p(x_i^{t+1} = 1)\big] \Big],$$

The logarithm of the investment probability is as follows:

$$\log p(x_i^{t+1} = 1) = \log \left[\frac{1}{1 + e^{-\gamma \cdot u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)}} \right].$$

It is direct that $u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)$ is a linear function of $\boldsymbol{\theta}_i$. In addition, $\log p(x_i^{t+1} = 1)$ is concave w.r.t. $u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)$, as the second derivative is negative over the domain, i.e.,

$$\frac{\partial^2 \log p(x_i^{t+1} = 1)}{\partial^2 u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)} = -\frac{e^{\gamma \cdot u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)} \cdot \gamma^2}{(1 + e^{\gamma \cdot u_i(1|\boldsymbol{x}^t, \boldsymbol{y}^t, \boldsymbol{\theta}_i)})^2} < 0.$$

The composition of a linear function with a concave function leads to a concave function (chapter 3.2.2 at [Boyd and Vandenberghe, 2004]); thus, $\log p(x_i^{t+1} = 1)$ is concave w.r.t. $\boldsymbol{\theta}_i$. We can similarly show that $\log[1 - p(x_i^{t+1} = 1)]$ is convex w.r.t. $\boldsymbol{\theta}_i$, which implies that $(1 - x_i^{t+1}) \log p(x_i^{t+1} = 1)$ is concave w.r.t. $\boldsymbol{\theta}_i$. A linear combination of concave functions is still concave, so $\log p(\boldsymbol{x}^{t+1}|\boldsymbol{x}^t)$ is concave w.r.t. Θ. $\square$

A Statistical Test for Multi-Scale Structure We now further leverage the proposed framework to develop a statistical test to check whether the game exhibits the multi-scale structure. This test is based on the classic *likelihood ratio test* [Wasserman, 2013]. Specifically, let $\hat{\Theta} = \{\hat{\boldsymbol{b}}, \hat{\boldsymbol{c}}, \hat{\boldsymbol{\beta}}, \hat{\boldsymbol{\eta}}\}$ be the MLE estimator. The feasible region of $\hat{\Theta}$ is $\mathcal{F} = \{\hat{\Theta} \mid \hat{\boldsymbol{b}} \geq 0, \hat{\boldsymbol{c}} \geq 0, \hat{\boldsymbol{\beta}} \in [-\mathbf{1}, \mathbf{1}], \hat{\boldsymbol{\eta}} \in [-\mathbf{1}, \mathbf{1}]\}$. The null hypothesis set is $\mathcal{F}_0 = \{\hat{\Theta} \in \mathcal{F} \mid \hat{\boldsymbol{\eta}} = \mathbf{0}\}$, encoding the hypothesis that group-level statistics have no impact on agents' utilities. The test statistic is as follows:

$$\lambda = 2 \log \left(\frac{\max_{\Theta \in \mathcal{F}} \mathcal{L}(\mathcal{D}_l; \Theta)}{\max_{\Theta \in \mathcal{F}_0} \mathcal{L}(\mathcal{D}_l; \Theta)} \right). \quad (7)$$

Intuitively, λ is large if there is some estimator $\hat{\Theta}$ in the feasible region $\mathcal{F}$ for which the data $\mathcal{D}_l$ is much more likely

than for any estimator in the null hypothesis set $\mathcal{F}_0$. The p-value is equal to $p(\chi_n^2 > \lambda)$, where χ_n^2 follows a chi-square distribution with n degrees of freedom. In the Experiments section, we present experiments on synthetic data to show that the test is indeed effective at identifying multi-scale structure in games. We then use it on real data to demonstrate that such data also exhibits statistically significant multi-scale behavior dependence.

5 EXPERIMENTS

We focus our experimental study on learning a multi-scale linear-quadratic game b-MSGN(Θ^*). In all cases, we learn the game from a single sequence $\mathcal{D}_l$, and experiment on both synthetic and real-world data. We use synthetic data to demonstrate the effectiveness of our approach at *recovering the ground-truth parameters* of the linear-quadratic games, and additionally show that the statistical test successfully identifies multi-scale game structure.

In addition, we evaluate the efficacy of the proposed approach to predict future time-series behavior. For both synthetic and real data, we first compare predictive efficacy of the proposed game learning approach with three conventional generative baseline approaches commonly applied in similar settings with the primary purpose of time-series prediction: a discrete Markov chain, a homogeneous Poisson process, and the Hawkes process [Mohler et al., 2011]. Specifically, our experiments use a discrete-time Hawkes process with exponential decay function; the intensity function at time step t is: $\lambda(t) = \lambda_0 + \alpha \sum_{t_i < t} z_{t_i} e^{-\beta(t-t_i)}$; λ_0 and α are estimated through MLE; β is selected by cross-validation; z_{t_i} is the sum of $\boldsymbol{x}^{t_i}$, i.e., $\sum_{j=1}^n x_j^{t_i}$. We show that the proposed approach outperforms these baselines in terms of prediction efficacy.

Additionally, we compare our approach with a method for learning *Linear Influence Games* (LIGs) [Honorio and Ortiz, 2015], a state-of-the-art game-theoretic baseline for learning utility functions from time-series behavior in network games. LIG is a generative model that assumes that behavior in each step in a time-series is generated according to a mixture of two distributions: a uniform distribution over the set of all pure-strategy Nash equilibria, and a uniform distribution over the set of all non-equilibrium strategy profiles.[3] The learnable parameters of an LIG include the parameters of the players' utility functions as well as a parameter deciding which distribution an action profile comes from. The parameters are learned by maximizing the proportion of equilibria observed in the training data.

---

[3]Note that the LIG approach assumes that the set of all pure-strategy Nash equilibria can be efficiently sampled. Another advantage of the proposed approach over LIG is that we do not need this assumption.

5.1 SYNTHETIC DATA

We generate a synthetic sequence $\mathcal{D}_l$ by simulating b-MSGN(Θ^*) for $l-1$ iterations, with starting action profile initialized as zeros. In each time step, every agent makes a decision according to the Bernoulli distribution with success rate equal to the investment probability (i.e., Equation (2)). The ground-truth parameters $\Theta^* = \{\boldsymbol{b}^*, \boldsymbol{c}^*, \boldsymbol{\beta}^*, \boldsymbol{\eta}^*\}$ are specified as follows: $b_i^* \sim \mathcal{N}(0.3, 0.01^2)$, $c_i^* \sim \mathcal{N}(1.3, 0.1^2)$, $\beta_i^* \sim \mathcal{N}(-1, 0.01^2)$ and $\eta_i^* \sim \mathcal{N}(0.1, 0.01^2)$. The parameter γ is set to 5. We consider three classes of synthetic networks: Barabási-Albert (BA) [Barabási and Albert, 1999], Watts-Strogatz (WS) [Watts and Strogatz, 1998], and Block Two-level Erdős-Rényi (BTER) [Seshadhri et al., 2012] networks. For each class, we randomly generate 20 networks with 100 nodes each. For each randomly generated network, we run the community detection algorithm proposed by Clauset et al. [2004] and use the resulting communities as groups.

Figure 1 shows the effectiveness of learning the game parameters from synthetic data. As the length l increases, the Root Mean Squared Error (RMSE) between the estimated parameters and the true parameters consistently decreases, converging to near-zero; this indicates that the MLE estimator approximates the ground-truth Θ^* reasonably well.

Figure 1: The RMSE between the estimated parameters and the true parameters across various lengths l. **Left**: BA (avg. degree=5.82, avg. clustering coeff.=0.1067); **Middle**: WS (avg. degree=9.1064, avg. clustering coeff.=0.3542); **Right**: BTER (avg. degree=9.3200, avg. clustering coeff.=0.1299).

Next, we show that the statistical test successfully determines the existence of the multi-scale structure in the game. We simulate two sets of data, one is called "with groups" and the other "without group". The "with groups" data is simulated as usual, such that the agents' utilities are influenced by the multi-scale structure. The "without group" data is simulated with η_i^* set to zero, which implies that the multi-scale structure does not have a direct impact on the agents' utilities. The p-values for the two sets of data are showed in Figure 2. The red horizontal lines represent where $p(\chi_n^2 > \lambda) = 0.05$: we reject the null hypothesis when the p-value is below the red line. The blue lines represent the p-values for the "with groups" data. We can see that as l (the number of observations) increases the p-values consistently decrease. In particular, for BA (resp. WS) networks when $l > 1500$ (resp. $l > 750$) we correctly reject the null hypothesis. One exception is the BTER network, where the

null hypothesis is not rejected with 2000 steps; the average p-value is $0.18(\pm 0.074)$. This may due to greater structural complexity of BTER networks compared to BA and WS. The dashed orange lines represent the p-values for the "without group" data. Note that the orange lines are consistently above 0.05 by a large margin, which means that we never incorrectly reject the null hypothesis (i.e., never falsely claim the existence of multi-scale structure).

Figure 2: Experimental results for the statistical test. The blue solid lines (resp. orange dashed lines) represent the p-values evaluated on the data with (resp. without) the multi-scale structure. **Left**: BA; **Middle**: WS; **Right**: BTER.

5.2 REAL-WORLD DATA

Gang-Related Homicides. We learn the game on a gang-related homicides data from Los Angeles [Valasik et al., 2017]. The data includes 1425 incidents from 1978 to 2012. Each incident consists of several attributes, including date, address, coordinates (X and Y correspond to latitude and longitude, respectively), and demographic information of the victim and the suspect. Each incident includes a label indicating whether the homicide is gang-related, and if so, includes an attribute of the suspect's gang affiliation. All sensitive attributes in the experimental results are anonymized with numerical values. The data is preprocessed as follows. First, we keep only the incidents that are gang-related, and discard the incidents with missing attributes. Second, to correct errors in incident coordinates, we compute the geometric center of the incidents' coordinates, and then fit a standard Gaussian distribution on their distances to the center, and finally discard any incidents that are three standard deviation away from the center. After preprocessing, the data contains 606 incidents committed by suspects from 54 gangs. A gang's location is approximated by the geometric center of its associated incidents. We treat the 54 gangs as the agents in the game; they are partitioned into three groups according to their neighborhood information. The network $\boldsymbol{A}$ is weighted, undirected, and complete, with the gangs as nodes. The weight on an edge is the inverse of the driving time between the two endpoints (gangs) obtained by querying the Google Maps API. A visualization of the processed data is provided in the Supplement.

Next, we construct a sequence $\mathcal{D}_l$ of action profiles from the processed data by discretizing time and grouping incidents that occur in each time interval, where T is the hyperparameter corresponding to the length of the interval in days (i.e., how finely the data is discretized). We experiment with

different values of T, e.g., $T = 30, 60, 90$. We set $x_j^t = 1$ if there is at least one incident associated with the j-th gang at time step t, and set $x_j^t = 0$ otherwise. The aggregate statistic $y_i^t = \sum_{j \in \mathcal{G}_i} x_j^t$, measuring the overall level of violence in group $\mathcal{G}_i$.

We first apply the statistical test on data aggregated with different values of T. The p-values are less than 0.05 across the values of T, except for $T = 30$ and 120. The overall observation is that the data consistently exhibits statistically significant multi-scale behavior dependence, an effect that is relatively robust to time discretization; the only instances where its influence is not statistically significant is for $T = 30$ and 120.

Figure 3: Comparison of our approach with the game-theoretic baseline LIG and three conventional generative approaches in terms of predictive log-likelihood on test data.

Figure 4: A visualization of the predicted total crimes on test data with $T = 30$ (i.e., each time step represents 30 days). We omit Poisson and LIG as their predictions are far from the ground-truth. The shaded area represents two standard deviations of the prediction from b-MSGN.

To compare the proposed approach, in which we learn the linear-quadratic game on this data, with several baselines in terms of predictive log-likelihood on test data, we split $\mathcal{D}_l$ into training data and test data with ratio $9 : 1$. The results are showed in Figure 3. We observe that our approach is considerably better than LIG, particularly for smaller values of T. In addition, our approach is competitive in predictive efficacy with all but the Markov chain baseline (which is considerably worse), including the Hawkes process, which is the state-of-the-art approach for modeling crime data of this kind [Mohler et al., 2011].

A visualization of the predicted total crimes on test data is showed in Figure 4; the shaded area represents two standard deviations of the prediction from b-MSGN. The prediction from Poisson and LIG is omitted as they are far from the ground-truth; both are almost horizontal lines without capturing any trends exhibited in real data. We can observe that

b-MSGN is capturing the overall trend with high confidence, i.e., the ground-truth lies within two standard deviations of the prediction.

Figure 5: The estimates of $b_i - c_i$, β_i and η_i. **Top**: the homicides data aggregated with $T = 60$. **Bottom**: the bilateral trading data.

The key advantage of the proposed approach comes from its interpretability as capturing strategic interactions, and in linear-quadratic games in particular, the parameters we learn have a natural interpretation, which we now consider. Specifically, to analyze the game parameters we have learned, we set $T = 60$ as an illustration (the results are quite robust to this), so that the resulting sequence $\mathcal{D}_l$ has $l = 213$ time steps. As we do not have access to the ground-truth utility functions, the analysis serves to provide insights about the gangs' behavior. The learned parameters are showed in the top row of Figure 5. First, the estimated $b_i - c_i$ are showed on the left of the figure; the median is -0.77. Note that the estimates are negative, that is, perceived costs of homicides by gang members exceed benefits. Overall, gang-related homicides are relatively rare; indeed there are on average 4.7% gangs that committed homicides at each time step; when increasing T to 365, there are on average 19.7% gangs that committed homicides at each time step and the median of $b_i - c_i$ becomes -0.56.

The estimates of β_i are shown in the middle of the figure. Most of the estimates take two extreme values, $+1$ or -1. The mean is 0.18, which indicates that gang members on average tend to commit more homicides as the number of homicides from other members of their gang increases. This may be explained by the self-excitation phenomenon observed by Mohler et al. [2011] that an incident involving rival gangs can lead to retaliatory acts of homicide. Finally, estimated η_i are shown on the right of the figure. Most estimates are positive (except a few outliers), which suggests an intuitive observation that a greater overall level of violence in a gang's neighborhood tends to lead to greater incidence of violence by the gang.

To see how the discretization affects the estimates, we plot the estimated parameters across the values of T as in Figure 6. The estimates of $b_i - c_i$ increase slightly increasing as T gets larger, due simply to a greater number of homicides being aggregated in each step. However, the difference is not significant. Similarly, the estimates of β_i and η_i are not severely affected by the values of T.

Figure 6: From left to right, the estimations of $b_i - c_i$, β_i and η_i across different values of T; the feasible region of each estimated parameter is restricted to $[-1, 1]$.

Bilateral Trading Data. The second dataset we consider is the bilateral trading data from the United Nations Comtrade Database (https://comtrade.un.org/). The data consists of statistics for international bilateral trading (e.g., imports and exports), including over 170 reporting economies and records from 1962 to 2018. We focus on annual exports data in terms of their value in US-dollars and extract a subset consisting of 127 reporting economies with complete statistics since 1962; the reporting economies are partitioned into six groups according to the continents they are located on: Asia, Africa, Europe, South America, Australia and North America. We treat the reporting economies as agents in the game. The graph underlying the game is directed and weighted, where an edge from i to j means that i has exported goods/service to j, and the weight on the edge is the normalized total value of exports since 1962. As the graph is directed, we define the neighborhood of economy i as its exporting destinations. The sequence $\mathcal{D}_l$ of action profiles consists of 57 time steps, each corresponding to a year. For every economy, we track a moving average of the value of exports over k time steps. Let e_i^t be the value of exports of economy i at time step t. For $t > k$, if the value is greater than the moving average, i.e., $e_i^t > (e_i^{t-1} + \cdots + e_i^{t-k})/k$, we set $x_i^t = 1$; otherwise $x_i^t = 0$. For $t = 1, \ldots, k$ the actions x_i^t are always set to zero. Intuitively, $x_i^t = 1$ encodes that economy i has a higher value of exports compared with the average value of last three years, which signals economic growth [Michaely, 1977]. The group-level statistic is again $y_i^t = \sum_{j \in \mathcal{G}_i} x_j^t$. We experiment with five values of k, ranging from 1 to 5.

We first run the statistical test on $\mathcal{D}_l$. The resulting p-values are nearly zero across all the values of k, providing evidence for the importance of multi-scale structure.

Next, we compare the game with the baselines on test data (the last 5% of the entire sequence) in terms of predicted log-likelihoods. The results for $k = 5$ are as follows: 1) Markov Chain: -36.8413, 2) Poisson: -36.9614, 3) Hawkes: -29.9843, 4) LIG: -31.4041, and 5) b-MSGN: -24.7406; the results for other values of k are similar. Note that in this case the proposed b-MSGN approach outperforms all baselines, including the Hawkes process.

Finally, the estimated parameters are shown in Figure 5 (second row). The estimated $b_i - c_i$ are mostly negative,

indicating that for most economies it is difficult to maintain a steady growth in exports; some exceptions include Hong Kong, Japan, Ireland, Central African Republic, and Taiwan, which are the top five economies ranked by the estimated $b_i - c_i$ in descending order. Most estimated values of β_i are positive, suggesting that an economy will have a growth in exports when its exporting destinations also have increasing exports. Similarly, we rank the economies in terms of the estimated β_i in descending order, with Australia, New Zealand, Aruba, Venezuela, and Dominica the top five. For each of these, we identify the top three major export goods in terms of the share in the total value of exports since 1962. The major exporting goods of the five economies are raw materials, e.g., iron ore, meat, crude/refined petroleum, and fruits/nuts. The interpretation is that when the exports of other economies grow, the demand for raw materials also increases. Finally, most estimated values of η_i are positive, which suggests that the relative growth of a group's exports (compared with other groups) is a good predictor of the participating economies' growth.

To study the sensitivity of the estimated parameters to k, we plot the estimated parameters across the values of k in Figure 7. There is a decreasing trend in the estimate of $b_i - c_i$ for smaller values of k, suggesting that the interpretation of the estimate has to consider the specific value of k. The estimates of β_i and η_i are not sensitive to k.

Figure 7: From left to right, the estimations of $b_i - c_i$, β_i and η_i across different values of k; the feasible region of each estimated parameter is restricted to $[-1, 1]$.

6 CONCLUSION

We propose a game-theoretic generative model of time-series behavior data by combining single-shot multi-scale network games with logit-response dynamics. We do not assume that the agents are fully rational, but rather that they make decisions according to logit-response dynamics. We then present a general learning framework based on maximum likelihood estimation (MLE) for inferring parameters of such games. In the special case of multi-scale linear-quadratic games we prove that the MLE is a convex optimization problem and thus admits efficient solution algorithms. We further develop a statistical test to determine whether the game exhibits multi-scale structure. We use extensive experiments on both synthetic and real datasets to show the efficacy of the proposed approach.

REFERENCES

Carlos Alós-Ferrer and Nick Netzer. The logit-response dynamics. *Games and Economic Behavior*, 68(2):413–427, 2010.

James Andreoni and John H Miller. Rational cooperation in the finitely repeated prisoner's dilemma: Experimental evidence. *Economic Journal*, 103(418):570–85, 1993.

Coralio Ballester, Antoni Calvó-Armengol, and Yves Zenou. Who's who in networks. wanted: The key player. *Econometrica*, 74(5):1403–1417, 2006.

Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. *Science*, 286(5439):509–512, 1999.

Julian Besag. Spatial interaction and the statistical analysis of lattice systems. *Journal of the Royal Statistical Society: Series B (Methodological)*, 36(2):192–225, 1974.

Avrim Blum, Jeffrey Jackson, Tuomas Sandholm, and Martin Zinkevich. Preference elicitation and query learning. *Journal of Machine Learning Research (JMLR)*, 5(Jun):649–667, 2004.

Lawrence E Blume. The statistical mechanics of strategic interaction. *Games and economic behavior*, 5(3):387–424, 1993.

Stephen Boyd and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Yann Bramoullé and Rachel Kranton. Public goods in networks. *Journal of Economic Theory*, 135(1):478–494, 2007.

Colin Camerer. *Behavioral Game Theory: Experiments in Strategic Interaction*. Princeton University Press, 2003.

Urszula Chajewska, Daphne Koller, and Dirk Ormoneit. Learning an agent's utility function by observing behavior. In *Proceedings of the 18th International Conference on Machine Learning*, pages 35–42, 2001.

Fan RK Chung and Fan Chung Graham. *Spectral graph theory*. American Mathematical Society, 1997.

Aaron Clauset, Mark EJ Newman, and Cristopher Moore. Finding community structure in very large networks. *Physical review E*, 70(6):066111, 2004.

Quang Duong, Yevgeniy Vorobeychik, Satinder Singh, and Michael Wellman. Learning graphical game models. In *Proceedings of the 21st International Joint Conference on Artificial Intelligence (IJCAI)*, 2009.

Quang Duong, Michael P Wellman, Satinder Singh, and Yevgeniy Vorobeychik. History-dependent graphical multiagent models. In *Proceedings of the 9th International Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, pages 1215–1222, 2010.

Baruch Fischhoff and Charles F Manski. *Elicitation of preferences*, volume 19. Springer Science & Business Media, 2000.

Drew Fudenberg, Fudenberg Drew, David K Levine, and David K Levine. *The theory of learning in games*, volume 2. MIT press, 1998.

Andrea Galeotti, Sanjeev Goyal, Matthew O Jackson, Fernando Vega-Redondo, and Leeat Yariv. Network games. *The Review of Economic Studies*, 77(1):218–244, 2010.

Andrea Galeotti, Benjamin Golub, and Sanjeev Goyal. Targeting interventions in networks. *Econometrica*, 88(6):2445–2471, 2020.

Vikas Garg and Tommi Jaakkola. Learning tree structured potential games. In *Proceedings of the 29th International Conference on Neural Information Processing Systems (NeurIPS)*, volume 29, pages 1552–1560, 2016.

Michelle Girvan and Mark EJ Newman. Community structure in social and biological networks. *Proceedings of the national academy of sciences*, 99(12):7821–7826, 2002.

Jens Grosslags, Nicolas Christin, and John Chuang. Security and insurance management in networks with heterogeneous agents. In *Proceedings of the 9th ACM Conference on Electronic Commerce (EC)*, pages 160–169, 2008.

Philip A Haile, Ali Hortaçsu, and Grigory Kosenok. On the empirical content of quantal response equilibrium. *American Economic Review*, 98(1):180–200, 2008.

Jean Honorio and Luis Ortiz. Learning the structure and parameters of large-population graphical games from behavioral data. *Journal of Machine Learning Research (JMLR)*, 16:1157–1210, 2015.

Matthew O Jackson. *Social and economic networks*. Princeton university press, 2010.

Kun Jin, Yevgeniy Vorobeychik, and Mingyan Liu. Multiscale games: Representing and solving games on networks with group structure. In *Proceedings of the AAAI Conference on Artificial Intelligence*, 2021.

Michael Kearns, Michael L Littman, and Satinder Singh. Graphical models for game theory. In *Proceedings of the 17th conference on Uncertainty in artificial intelligence (UAI)*, pages 253–260, 2001.

Michael J Kearns and Jennifer Wortman. Learning from collective behavior. In *Proceedings of the 21st Conference on Learning Theory (COLT)*, pages 99–110, 2008.

Yan Leng, Xiaowen Dong, Junfeng Wu, and Alex Pentland. Learning quadratic games on networks. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, pages 5820–5830. PMLR, 2020.

Chun Kai Ling, Fei Fang, and J. Zico Kolter. What game are we playing? end-to-end learning in normal and extensive form games. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI)*, 2018.

Richard D McKelvey and Thomas R Palfrey. Quantal response equilibria for normal form games. *Games and Economic Behavior*, 10(1):6–38, 1995.

Michael Michaely. Exports and growth: an empirical investigation. *Journal of development economics*, 4(1):49–53, 1977.

G. O. Mohler, M. B. Short, P. J. Brantingham, F. P. Schoenberg, and G. E. Tita. Self-exciting point process modeling of crime. *Journal of the American Statistical Association*, 106(493):100–108, 2011.

Thomas D Nielsen and Finn V Jensen. Learning a decision maker's utility function from (possibly) inconsistent behavior. *Artificial Intelligence*, 160(1-2):53–78, 2004.

Comandur Seshadhri, Tamara G Kolda, and Ali Pinar. Community structure and scale-free collections of erdős-rényi graphs. *Physical Review E*, 85(5):056109, 2012.

Dale O Stahl II and Paul W Wilson. Experimental evidence on players' models of other players. *Journal of economic behavior & organization*, 25(3):309–327, 1994.

Matthew Valasik, Michael S. Barton, Shannon E. Reid, and George E. Tita. Barriocide: Investigating the temporal and spatial influence of neighborhood structural characteristics on gang and non-gang homicides in east los angeles. *Homicide Studies*, 21, 2017.

Yevgeniy Vorobeychik, Michael P Wellman, and Satinder Singh. Learning payoff functions in infinite games. *Machine Learning*, 67(1-2):145–168, 2007.

Larry Wasserman. *All of statistics: a concise course in statistical inference*. Springer Science & Business Media, 2013.

Duncan J Watts and Steven H Strogatz. Collective dynamics of small-world networks. *Nature*, 393(6684):440, 1998.

Kevin Waugh, Brian D Ziebart, and J Andrew Bagnell. Computational rationalization: The inverse equilibrium problem. In *Proceedings of the 28th International Conference on Machine Learning (ICML)*, 2011.

Jacob Wildstrom. The convergence of markov chain on directed graph. `http://www.math.ucsd.edu/~fan/teach/262/notes/paul/10_24_notes.pdf`, 2005.

7 A VISUALIZATION OF THE GANG-RELATED HOMICIDES DATASET

The spread of the data is displayed in Figure 8 left, where each dot represents an incident and the color indicates the suspect's gang affiliation. The horizontal axes and the vertical axes represent latitude and longitude, respectively. A gang's location is approximated by the geometric center of its associated incidents. The spread of the gangs are showed in Figure 8 middle. We treat the 54 gangs as the agents of the game; they are partitioned into three groups according to their neighborhoods information. The groups are shown in Figure 8 right, where gangs in the same group have the same color. The network A is weighted, undirected and complete, with the gangs as nodes. The weight on an edge is the inverse of the driving time between the two endpoints (gangs), obtained by querying the Google Map API.

Figure 8: A visualization of the gang-related homicides dataset. The horizontal axes and the vertical axes represent latitude and longitude, respectively. **Left**: each dot represents an incident and the color indicates the suspect's gang affiliation. **Middle**: each dot represents a gang, where the location is the geometric center of its associated incidents. **Right**: the partition of the gangs into three groups, with each group representing a neighborhood.