If You've Trained One You've Trained Them All: Inter-Architecture Similarity Increases With Robustness

Abstract

Previous work has shown that commonly-used metrics for comparing representations between neural networks overestimate similarity due to correlations between data points. We show that intra-example feature correlations also causes significant overestimation of network similarity and propose an image inversion technique to analyze only the features used by a network. With this technique, we find that similarity across architectures is significantly lower than commonly understood, but we surprisingly find that similarity between models with different architectures increases as the adversarial robustness of the models increase. Our findings indicate that robust networks tend towards a universal set of representations, regardless of architecture, and that the robust training criterion is a strong prior constraint on the functions that can be learned by diverse modern architectures. We also find that the representations learned by a robust network of any architecture have an asymmetric overlap with non-robust networks of many architectures, indicating that the representations used by robust neural networks are highly entangled with the representations used by non-robust networks.

1 INTRODUCTION

There is evidence that neural networks—across architectures and weight initializations—rely on similar features for classification. Previous literature has proposed the *universality hypothesis*, which posits that neural networks learn essentially the same representations when trained on the same data, regardless of exact architecture or training algorithm [Olah et al., 2020]. However, we know that different architectures and random initializations often make different predictions [Lakshminarayanan et al., 2017]. This paper re-

Figure 1: Representation-layer similarity of neural networks increases with robustness. Our proposed metric, based on image inversions, is averaged across every pair of architectures. The representations used by robust neural networks are extremely similar across architectures and random initializations, and show high similarity with non-robust networks.

examines the similarity question from a novel viewpoint by considering the effect of an adversarial robustness constraint during training.

Robust training is a well-established procedure to decrease the sensitivity of a network's outputs to small changes in inputs Madry et al. [2018]. It is well-known that increasing the robustness of neural networks against adversarial examples comes with a cost to accuracy [Tsipras et al., 2019]. However, little attention has been paid to the effect that robust training has on agreement between models. We empirically show through multiple methods of similarity analysis that the representations, and consequently the functions, learned by networks of different architectures become significantly more similar as robustness increases. This finding indicates

that robustness serves as a strong prior on the functions that can be learned, and in fact may be a strong enough constraint to matter more than the specific network architecture. While surprising, this hypothesis is consistent with recent theoretical results showing that modern networks are actually under-parameterized to represent smooth functions in high dimensions [Bubeck and Sellke, 2021].

Many methods have been proposed to measure similarity between neural networks, including centered kernel alignment (CKA) [Kornblith et al., 2019], Canonical Correlation Analysis (CCA) [Hardoon et al., 2004], singular vector canonical correlation analysis (SVCCA) [Raghu et al., 2017], subspace match [Wang et al., 2018] and more. In this paper, we show that existing methods for evaluating representation similarity tend to over-estimate similarity due to feature correlations. We develop a novel method for measuring network representation similarity that deconfounds the effect of correlated features by constructing model-specific datasets where each data point has been transformed to contain only the features used by the model. Using this metric, we present a comprehensive study examining the similarity between neural networks as a function of the robustness level used in adversarial training.

Figure 1 summarizes our results using the novel similarity metric we propose. The similarity between networks with different architectures is extremely high amongst robust networks, and robust networks indeed show high similarity with non-robust networks, indicating that there is significant entanglement between robust and non-robust representations. Overall, we find two novel and surprising results:

1. Similarity between networks trained with empirical risk minimization is limited, and this similarity is overestimated by existing correlation-based similarity metrics due to feature correlations present in the dataset itself. We present experimental evidence that non-robust neural networks rely on features that are highly correlated in the data yet measure distinct patterns.

2. Adversarial robustness is a strong constraint on the function that is learned by a network, regardless of architecture or random initialization. We find that similarity between robust networks is extremely high, and that robust networks also show asymmetric similarity with non-robust neural networks.

2   RELATED WORK

Cui et al. [2022] investigate the confounding effect of input data on representational similarity across deep neural networks. They highlight that *inter*-example input similarity can cause representation similarity to be spuriously high even between networks with Gaussian noise added to their parameters. They propose to regress out the input similarity structure from the representation similarity structure and

find that doing so corrects for the failure of CKA to distinguish between random neural networks, among other benefits. Ding et al. [2021] further investigates issues surrounding similarity indices, finding that CKA and CCA both fail to satisfy at least one of their proposed criteria expected of similarity metrics. We identify an additional limitation to these similarity metrics by showing that correlated features in the input data can likewise cause the similarity between neural networks to be overestimated.

Bai et al. [2021] propose a method to study the representations learned by neural networks by removing all non-linear components of a network and integrating all linear components into linear subnetworks W. By analyzing the weight vectors of W, the authors find that adversarially-trained networks cluster along class hierarchies while standard networks do not. Likewise, Salman et al. [2020] find that the representations learned by robust neural networks provide a better starting point for transfer learning than the representations learned by non-robust networks. These findings may indicate that adversarially-trained networks are extracting more semantic and generalizeable representations than standard networks.

Springer et al. [2021b] investigate the ability of adversarially trained neural networks to generate targeted adversarial examples. They find that classifiers that have been adversarially trained, even those only robust to small-magnitude perturbations, are much more effective than standard classifiers at generating targeted adversarial examples. Based on their findings, they argue that the representations used by slightly robust neural networks are shared widely across non-robust networks. We present further evidence for this hypothesis by evaluating the representational similarity of robust and non-robust neural networks.

3   METHODS

We consider a labelled classification dataset $\mathcal{D} = X, y$ of data points and ground truth labels. Given two neural networks f_1 and f_2, comprised of layers

$$f_1 = f_1^{(L_1)} \circ f_1^{(L_1-1)} \circ \ldots f_1^{(1)}$$
$$f_2 = f_2^{(L_2)} \circ f_2^{(L_2-1)} \circ \ldots f_2^{(1)}$$

we are interested in the activations at the *representation* layers (i.e. the second-to-last, or penultimate, layer) of f_1 and f_2, denoted A and B

$$g_1 = f_1^{(L_1-1)} \circ \ldots \circ f_1^1 \qquad A = g_1(X)$$
$$g_2 = f_1^{(L_1-1)} \circ \ldots \circ f_1^1 \qquad B = g_2(X)$$

3.1 CENTERED KERNEL ALIGNMENT

We use centered kernel alignment to compare representations between neural networks. Given two mean-centered matrices of activations $A \in \mathbb{R}^{n \times p_1}$ and $B \in \mathbb{R}^{n \times p_2}$ of p_1 and p_2 neurons on a set of n examples, CKA computes a value in the range $[0, 1]$ with values closer to 1 indicating higher similarity. Kornblith et al. [2019] show that CKA has a number of desirable properties, including the ability to calculate similarity between layers with a differing number of neurons, invariance to isotropic scaling, and the ability to identify correspondences between the layers of identical architectures trained from different initializations—something many widely used metrics lack.

Since Kornblith et al. [2019] show that linear and radial basis function kernels compute similar similarity indices, we use a linear kernel for simplicity. The linear CKA between A and B is given by:

$$
\begin{aligned}
\mathrm{CKA}(A, B) &= \frac{\|B^T A\|_F^2}{\|A^T A\|_F \|B^T B\|_F} \\
&= \frac{\|cov(A^T, B^T)\|_F^2}{\|cov(A^T, A^T)\|_F \|cov(B^T, B^T)\|_F}
\end{aligned}
\quad (1)
$$

Previous studies have evaluated CKA between each pair of layers in the networks to be compared. In this study, we restrict our attention to the penultimate layer of each network, since this layer effectively captures the summary statistics used by each network for classification.

In this work, we empirically demonstrate a shortcoming of CKA, as traditionally applied. Suppose that two features are perfectly correlated in a dataset: $X_{\cdot,i} = c\ X_{\cdot,j}$ for some $|c| > 0$ and $i \neq j$. Also suppose that each network computes its representations $A_{\cdot,l}$ and $B_{\cdot,m}$ using only one of these correlated features each, i for f_1 and j for f_2 respectively. Then, CKA evaluated on test data will show that representations l and m are perfectly correlated, although it does not indicate similar feature usage between the networks. In large, high-dimensional datasets with many correlated features, such as natural images, this shortcoming can lead to a dramatic overestimation of network similarity.

3.2 REPRESENTATION-LAYER INVERSION.

We use an inversion technique from the adversarial robustness literature to eliminate the effect of correlated features in test data. Ilyas et al. [2019] propose a technique known as *representation inversion* to investigate the features used by robust and non-robust classifiers. Representation inversion constructs a model-specific *inverted dataset* $\mathcal{I}_f(\mathcal{D})$ for a given classifier f where all features *not* used by f are randomized.

Given a labeled dataset $\mathcal{D}$, we choose a pair of inputs that have *different* labels. The first of each pair will be the *seed* image s and the second the *target* image t. Using the seed image as a starting point, we perform gradient descent to find an image that induces the same activations at the representation layer as the target image, under a specific neural network f. We construct this image through gradient descent in input space (with the constraint that the resulting image has pixel values in the range $[0, 1]$) by optimizing the following objective:

$$
\tilde{s} = \min_s \|g(s) - g(t)\|_2 \quad (2)
$$

We perform this process on a subset of $10,000$ images drawn from the ImageNet validation set [Deng et al., 2009], producing a unique inverted dataset $\mathcal{I}_f(\mathcal{D})$ for each model. There is no constraint to limit the difference between the seed image s and the inverse image $\tilde{s}$, but extensive experiments show that gradient descent consistently finds inverse images close to the seeds with representations very closely matching the target images, regardless of the source/target pair chosen. The difference between s and $\tilde{s}$ tends to increase as the robustness of the network f increases.

By sampling pairs of seed and target images that have distinct labels we eliminate features correlated with the target class that are not used by the model for classification of the target class. For example, if we have a seed and target pair of "microwave" and "cat" respectively, and a given neural network is using the feature of "cat ear" to classify cat images but *not* "cat fur", by starting from an image of a microwave we can produce an image with the model's representation of "cat ear" that does not contain the correlated feature of "cat fur". If done successfully, the similarity between a neural network utilizing "cat fur" and a neural network utilizing "cat ear" will not be inflated by the co-occurrence of these features.

3.3 REPRESENTATION STITCHING

Csiszárik et al. [2021] approaches neural network similarity from the *functional* perspective, asking the question "*can network f_1 achieve its task using the representations of network f_2?*". Their simple and elegant method stitches together the activations A from a *body* network f_1 with the last layer of a *head* network $f_2^{(L_2)}$ by fitting an affine transformation $B \approx AW + b$. This procedure creates a *stitched* network:

$$
f_{2 \circ 1} = f_2^{(L_2)} \circ (g_1 W + b)
$$

Stitching is performed via linear regression using only the activations on training data, and we perform no task-specific fine tuning on the stitching parameters W, b. If there exists an identifiable linear transformation between the networks at the penultimate layer, then the stitched network will achieve high performance. Importantly, since the last layer of each

ε	0.0	0.01	0.03	0.05	0.1	0.25	0.5	1.0	3.0	5.0
ResNet18	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ResNet50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
WRN50-2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
WRN50-4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
ResNeXt50	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗
VGG16-bn	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗
DenseNet	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗
ShuffleNet	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗
MobileNet	✓	✗	✗	✗	✗	✗	✗	✗	✓	✗

Table 1: Pretrained ImageNet models used in experiments with available ℓ_2 robustnesses, provided by Salman et al. [2020] (github.com/microsoft/robust-models-transfer). WRN50-N is a WideResNet50-N [Zagoruyko and Komodakis, 2016].

network is dense layer followed by a softmax, when the representation stitching procedure causes the stitched model to agree with the head model, it shows that the representations computed by the body network are compatible and useful with respect to the head model.

3.4 ADVERSARIAL TRAINING

Adversarial training has been shown to be effective for constructing neural networks that are robust to adversarial examples [Madry et al., 2018]. In addition, adversarial training yields neural networks with a number of desirable qualities, including interpretable gradients [Tsipras et al., 2019], high-quality representations that are useful for transfer learning [Salman et al., 2020], and the ability to generate transferable adversarial examples [Springer et al., 2021c]. Despite the extensive research into this training paradigm, to our knowledge no comprehensive study has explored the relationship between network similarity and robustness.

During adversarial training, the empirical risk minimization regime is augmented so it produces a model that is robust to adversarial perturbations within a bounded region $S(x)$ around each input point x. We use the common choice of an $\varepsilon \in \mathbb{R}$ sized ℓ_2-ball and refer to ε as the *robustness level* of the model. This set of perturbations, S, is incorporated into the risk, reformulating it as the following min-max optimization:

$$\min_{\theta} \ \mathbb{E}_{(x,y) \sim \mathcal{D}} \left[\max_{\delta \in S(x)} \mathcal{L}(x + \delta, y; \theta) \right] \quad (3)$$

Due to computational requirements, we use the pretrained ℓ_2-robust ImageNet models released by Salman et al. [2020]. The specific architectures and robustnesses (ε) studied are outlined in Table 1.

4 EXPERIMENTS

We extensively evaluate our proposed method for estimating representation similarity, and show that it leads to consistent conclusions with other accepted methods for network similarity evaluation. Section 4.1 discusses the overestimation of neural network similarity and proposes a novel method for similarity estimation based on image inversions. Sections 4.2 to 4.4 discuss our findings on the convergence of representation similarity across robust neural networks, demonstrating that disparate methods for similarity estimation lead to the consistent conclusion that similarity increases significantly between architectures and random initialization as a function of robustness.

4.1 OVERESTIMATION OF NEURAL NETWORK SIMILARITY

Many previous studies have examined the similarity between neural networks with different architectures or weight initializations [Kornblith et al., 2019, Nguyen et al., 2021, Hermann and Lampinen, 2020]. Here, we argue that similarity between networks may be substantially overestimated by these studies. While these studies suggest that neural network activations are often highly correlated across different networks, none of them have taken into account the substantial confounder that neuron responses may appear to be correlated despite responding to distinct patterns, due to frequent co-occurrence of the patterns in the dataset.

We first present experimental results demonstrating that this confounder is present for standard, *non-robust* neural networks, shown in Figure 2. The left heatmap presents the CKA similarity at the representation layer between all non-robust architectures on a subset of the ImageNet validation set. As is commonly reported, the similarity between all architectures is relatively high with an average of 0.67 between the penultimate layers of distinct architectures. In the right heatmap, at each row-column entry, we present the CKA similarity between the row and column architecture using the inverted dataset $\mathcal{I}_f(\mathcal{D})$ generated by the *row*'s architecture. We perform these image inversions using $2,000$ iterations of stochastic gradient descent with a step size of $1/8$. In contrast to the high similarities found in the left

Figure 2: Representation layer similarity of *non-robust* neural networks on the test set $\mathcal{D}$ and the inverted datasets $\mathcal{I}_f(\mathcal{D})$. High similarity is observed under the natural image dataset and low similarity when on datasets generated by non-robust models. These results indicate that similarity is systematically overestimated when based on responses to natural images but can be more reliably estimated using responses to inverse images.

Figure 3: Representation layer similarity of robust neural networks ($\varepsilon = 3$) on the inverted datasets $\mathcal{I}_f(\mathcal{D})$. Similarity is much higher than observed in Figure 2.

heatmap, all similarities are significantly lower with an average between distinct architectures of 0.09.

The trends shown in Figure 2 clearly show that current similarity metrics are overestimating network similarity to a significant degree due to correlations between distinct features in the data. When images containing only the relevant features for one of the models are used in the similarity calculation, we see that models are far more dissimilar than

standard metrics indicate. We therefore propose evaluating CKA on inverted image datasets in order to best measure the manner in which each network computes sufficient and necessary features for classification.

4.2 ADVERSARIAL TRAINING INCREASES REPRESENTATION SIMILARITY

We apply our new method for network similarity estimation to investigate how robustness affects the similarity of neural networks. In Figure 3 we calculate similarity between networks in a similar fashion to the rightmost plot in Figure 2; however, this time all architectures being compared were adversarially trained with an ℓ_2 robustness of $\varepsilon = 3$. In this plot we find that robust networks are significantly more similar to each other on the inverted datasets $\mathcal{I}_f(\mathcal{D})$ than non robust networks are (average similarity of 0.80, compared to 0.09 for standard models as seen in Figure 2); this may indicate that robust neural networks tend towards a similar set of representations, regardless of architecture.

In Figure 5 we plot the similarity between neural networks across architecture and robustness on the inverted datasets $\mathcal{I}_f(\mathcal{D})$, restricted to a comparison of three architectures for readability. In each heatmap we present the similarity between the outer-row and outer-column architecture, varied across ε for each. Each inner-row and inner-column tick corresponds to the robustness of their respective outer-row and outer-column architecture, with the row architecture being the source of the inverted dataset $\mathcal{I}_f(\mathcal{D})$. In these plots we see a strong and consistent trend: when similar-

ity is calculated between architectures using an inverted dataset produced by a non-robust or slightly-robust model (low value column ticks), low similarity is observed across all column-architecture robustnesses. However, when an inverted dataset produced by a *robust* architecture is used, we see notably *higher* similarity across all column-architecture robustnesses. Average comparisons between all architectures are shown in Figure 1, showing that this trend holds for all architectures evaluated.

Our results show a strong asymmetric relationship between robust and non-robust models. Inversions produced for a robust model shows high similarity with all other models, but inversions produced for a non-robust model show low similarity with all other models. This finding support the idea that features used by non-robust neural networks are highly entangled with the features used by robust neural networks [Springer et al., 2021a]. As is seen in Figure 5, the features present in the inverted datasets $\mathcal{I}_f(\mathcal{D})$ generated by robust models are causing the representations used by non-robust classifiers to activate, yet the opposite does not hold.

Figure 5: Representation-layer similarity of neural networks on the natural images and the inverted datasets $\mathcal{I}_f(\mathcal{D})$, pairwise across different robustness levels.

4.3 ADVERSARIAL TRAINING INCREASES GRADIENT SIMILARITY

We further show the increase in similarity among robust neural networks with an intriguing result that as the pairwise-robustness of models increase, the cosine-similarity of their saliency-maps [Simonyan et al., 2014] with respect to the ground truth labels increases as well. For each pair of models at identical robustness, we compute the cosine similarity between their saliency maps, and present the results in in Figure 4. In a similar fashion to the results in Section 4.1 and Section 4.2, we find that the similarity between standard models is quite low, however, as the pairwise robustness between models increases, so does the gradient similarity.

Figure 4: Cosine similarity of model gradients in input space across robustness levels. Error bars indicate 1 std. deviation.

4.4 ADVERSARIAL TRAINING INCREASES FUNCTIONAL SIMILARITY

It has been argued that assessments of network similarity must examine *functional similarity*, since evaluation on known ground-truth labels gives a concrete, performance-based test [Ding et al., 2021]. Here, we apply the representation stitching methodology (Section 3.3) to "stitch" together networks of two different architectures using a single affine transformation. Within each robustness level, we evaluate every pair of models, using the first model as a *body* and the second model as a *head*. Figure 6 shows that stitching representations across architectures is effective; regardless of robustness level, when the head and body networks agreee on a label, the stitched model also predicts the same label (93.9% for correct labels and 83.2% for incorrect labels). Interestingly, when the head and body networks predict different labels, we find that agreement between the stitched model and the head model increases significantly as a function of robustness (Figure 7). In other words, it appears that there is a stronger linear correspondence between representations of the body and head network, from a functional perspective, at higher robustness levels.

5 DISCUSSION

We find that while existing correlation-based similarity metrics overestimate the similarity between non-robust neural networks due to co-occurrence of features in the evaluation dataset, robust neural networks exhibit substantial similarity. We find that as the adversarial robustness of a neural network increases, its similarity to other networks increases,

Figure 6: Average agreement between stitched models and their corresponding head models on data instances where the body and head networks agree. Robustness has no effect on agreement. Confidence bands indicate 1 std. error.

Figure 7: Average agreement between stitched models and their corresponding head models on data instances where the body and head networks disagree. Agreement increases as robustness increases. Confidence band indicate 1 std. error.

even across differences in architecture and random initialization. This trend of similarity is also present in the gradients, where we find that the Jacobians with respect to inputs are more similar for robust networks than for their non-robust counterparts. These results suggest a modified universality hypothesis, which suggests that neural networks, regardless of exact training condition (i.e., architecture, random initialization, learning parameters) will learn similar representations under mild constraints, such as adversarial robustness. We find empirically that robust neural networks satisfy this hypothesis. Furthermore, we find that the representations of non-robust neural networks overlap substantially with the representations of robust neural networks despite less overlap with the representations of other non-robust neural networks. This suggests that non-robust representations can be thought of as "components" of robust representations, much as a feature that represents the ear of a cat can be thought of as a component of the feature that represents an entire cat.

Our results provide an important step towards understanding the representations learned by neural networks. Our framework justifies the previously observed exceptional transferability of adversarial examples constructed using robust neural networks by demonstrating that non-robust and robust representations exhibit substantial overlap [Springer et al., 2021b]. In addition, we suspect that the fact that a single robust neural network has some degree of similarity to all non-robust neural networks can explain why robust neural networks are often better at learning representations that transfer to new tasks [Salman et al., 2020].

Neural network architectures and optimization procedures have often been viewed from a Bayesian perspective as a

strong prior on the functions that these networks can learn [Wilson and Izmailov, 2020, Kleinberg et al., 2018]. Our results indicate that robust training, likewise, is a very strong prior which can constrain both the representations extracted from a dataset and the functions learned, independent of architecture. Viewing adversarial robustness as an inductive bias may lead to understanding the limitations of our current models for adversarial robustness, and may help us develop better notions of robustness and improve the accuracy of robust models.

6 CONCLUSION

Increased similarity between robust neural networks could mean that empirical analysis of a single robust neural network will reveal insight into the representations learned by *every* other robust neural network, which may lead us to understand the nature of adversarial robustness itself. If neural networks learn a solution that is largely dependent on the data itself rather than the learning algorithm, random initialization, or architecture, then we may be able to derive insight into the innate structure of data by using the representations learned by neural networks.

While we find that non-robust neural networks do not strongly support the universality hypothesis, there is a convergence between both the representations used and the functions encoded by robust neural networks of different architectures. If true, even in the limited case of robust models, the universality hypothesis has substantial implications for the field of machine learning, and more broadly artificial intelligence and neuroscience. First, identifying and understanding the representations used by any individual neural

network may allow us to understand the representations learned by *every* neural network that has been trained on the same dataset. This can have applications in mitigating transferable adversarial examples [Moosavi-Dezfooli et al., 2017] as well as building representations that are more useful for transfer learning [Salman et al., 2020]. Second, if architecture matters less given a robustness constraint, robust representations may give us insight into patterns learned by biological brains [Conwell et al., 2021a,b, Zhuang et al., 2021, Yamins et al., 2014, Güçlü and van Gerven, 2015, Eickenberg et al., 2017].

References

Yang Bai, Xin Yan, Yong Jiang, Shutao Xia, and Yisen Wang. Clustering effect of (linearized) adversarial robust models. *ArXiv*, abs/2111.12922, 2021.

Sébastien Bubeck and Mark Sellke. A universal law of robustness via isoperimetry. *CoRR*, abs/2105.12806, 2021. URL https://arxiv.org/abs/2105.12806.

Colin Conwell, David Mayo, Michael A. Buice, Boris Katz, George A. Alvarez, and Andrei Barbu. Neural regression, representational similarity, model zoology & neural taskonomy at scale in rodent visual cortex. *bioRxiv*, 2021a. doi: 10.1101/2021.06.18.448431. URL https://www.biorxiv.org/content/early/2021/06/18/2021.06.18.448431.

Colin Conwell, Jacob S. Prince, George A. Alvarez, and Talia Konkle. What can 5.17 billion regression fits tell us about artificial models of the human visual system? In *SVRHM 2021 Workshop @ NeurIPS*, 2021b. URL https://openreview.net/forum?id=i_xiyGq6FNT.

Adrián Csiszárik, Péter Korösi-Szabó, Ákos K. Matszangosz, Gergely Papp, and Dániel Varga. Similarity and matching of neural network representations. *ArXiv*, abs/2110.14633, 2021.

Tianyu Cui, Yogesh Kumar, Pekka Marttinen, and Samuel Kaski. Deconfounded representation similarity for comparison of neural networks. *ArXiv*, abs/2202.00095, 2022.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, K. Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009.

Frances Ding, Jean-Stanislas Denain, and Jacob Steinhardt. Grounding representation similarity with statistical testing. *ArXiv*, abs/2108.01661, 2021.

Michael Eickenberg, Alexandre Gramfort, Gaël Varoquaux, and Bertrand Thirion. Seeing it all: Convolutional network layers map the function of the human visual system. *NeuroImage*, 152:184–194, 2017.

Umut Güçlü and Marcel AJ van Gerven. Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. *Journal of Neuroscience*, 35(27):10005–10014, 2015.

David Roi Hardoon, Sándor Szedmák, and John Shawe-Taylor. Canonical correlation analysis: An overview with application to learning methods. *Neural Computation*, 16:2639–2664, 2004.

Katherine L. Hermann and Andrew Kyle Lampinen. What shapes feature representations? exploring datasets, architectures, and training. *ArXiv*, abs/2006.12433, 2020.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features, 2019.

Robert Kleinberg, Yuanzhi Li, and Yang Yuan. An alternative view: When does SGD escape local minima? In Jennifer G. Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 2703–2712. PMLR, 2018. URL http://proceedings.mlr.press/v80/kleinberg18a.html.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey E. Hinton. Similarity of neural network representations revisited. *ArXiv*, abs/1905.00414, 2019.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 6402–6413, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/9ef2ed4b7fd2c810847ffa5fa85bce38-Abstract.html.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *ArXiv*, abs/1706.06083, 2018.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 86–94, 2017.

Thao Nguyen, Maithra Raghu, and Simon Kornblith. Do wide and deep networks learn the same things? uncovering how neural network representations vary with width and depth. *ArXiv*, abs/2010.15327, 2021.

Chris Olah, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter. Zoom in: An introduction to circuits. *Distill*, 5(3):e00024–001, 2020.

Maithra Raghu, Justin Gilmer, Jason Yosinski, and Jascha Sohl-Dickstein. Svcca: Singular vector canonical correlation analysis for deep learning dynamics and interpretability. In *NIPS*, 2017.

Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? *ArXiv*, abs/2007.08489, 2020.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *CoRR*, abs/1312.6034, 2014.

Jacob M. Springer, Melanie Mitchell, and Garrett T. Kenyon. Adversarial perturbations are not so weird: Entanglement of robust and non-robust features in neural network classifiers, 2021a.

Jacob M. Springer, Melanie Mitchell, and Garrett T. Kenyon. A little robustness goes a long way: Leveraging universal features for targeted transfer attacks, 2021b.

Jacob M. Springer, Melanie Mitchell, and Garrett T. Kenyon. Uncovering universal features: How adversarial training improves adversarial transferability. In *ICML 2021 Workshop on Adversarial Machine Learning*, 2021c. URL https://openreview.net/forum?id=tzModtpOW7l.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy, 2019.

Liwei Wang, Lunjia Hu, Jia-Yuan Gu, Yue Kris Wu, Zhiqiang Hu, Kun He, and John E. Hopcroft. Towards understanding learning representations: To what extent do different neural networks learn the same representation. In *NeurIPS*, 2018.

Andrew Gordon Wilson and Pavel Izmailov. Bayesian deep learning and a probabilistic perspective of generalization. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/322f62469c5e3c7dc3e58f5a4d1ea399-Abstract.html.

Daniel LK Yamins, Ha Hong, Charles F Cadieu, Ethan A Solomon, Darren Seibert, and James J DiCarlo. Performance-optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the national academy of sciences*, 111(23):8619–8624, 2014.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *ArXiv*, abs/1605.07146, 2016.

Chengxu Zhuang, Siming Yan, Aran Nayebi, Martin Schrimpf, Michael C. Frank, James J. DiCarlo, and Daniel L. K. Yamins. Unsupervised neural network models of the ventral visual stream. *Proceedings of the National Academy of Sciences*, 118 (3), 2021. ISSN 0027-8424. doi: 10.1073/pnas.2014196118. URL https://www.pnas.org/content/118/3/e2014196118.