Do Visual Bias Mitigation Methods Generalize? A Cross-Domain Study

Abstract

Spurious correlations, defined as predictive but non-causal relationships within training data, constitute a significant challenge for deep learning. When such shortcuts exist in a dataset, models tend to exploit them instead of learning the intended, task-relevant features, resulting in biased predictions and poor generalization. Although numerous bias mitigation methods have been developed and evaluated on natural images, their ability to generalize to other modalities and domains, such as text (e.g., occupational gender imbalance and lexical bias), audio (e.g., demographic disparities and device signatures), medical imaging (e.g., hospital-level biases such as scanner or protocol differences), and video (e.g., scene background bias), remains largely unexplored. In this work, we conduct the first comprehensive cross-domain benchmark study, evaluating 11 bias mitigation methods across 6 datasets spanning text, audio, medical imaging, and video. For each dataset, we introduce tailored configurations designed to assess bias mitigation performance. Our findings show that several methods provide consistent improvements across modalities, with a subset exhibiting statistically significant bias mitigation in all domains. This study offers the first systematic evidence of cross-modal generalization for visual bias mitigation approaches and establishes a benchmark resource aimed at encouraging the development of bias mitigation methods that extend beyond the natural images domain. Code and data will be released publicly upon acceptance.

1 Introduction

Deep learning systems have become ubiquitous across society, driving state-of-the-art performance in countless applications. As these models are increasingly deployed to make high-stakes decisions affecting individuals and populations (Melzi et al., 2024; Sarridis et al., 2023; Moussa et al., 2025), understanding and mitigating their inherent limitations is paramount for developing trustworthy Artificial Intelligence (AI) systems.

As such systems increasingly rely on large and heterogeneous datasets, they inevitably reflect the statistical characteristics and imperfections present in the data. This can introduce various forms of bias into the learned representations and decision-making processes, influencing model behavior in ways that are not always aligned with the intended task. In particular, high co-occurrence between certain data attributes and target labels that does not reflect true causal relationships, namely spurious correlations, represents one of the most significant challenges to robust generalization and bias mitigation in deep learning systems (Geirhos et al., 2020; Shah et al., 2020). When neural networks encounter training data containing such non-causal associations, they tend to learn these superficial patterns due to their easier-to-learn nature (Shah et al., 2020; Yang et al., 2024; Sarridis et al., 2025b). In particular, rather than discovering the genuine causal mechanisms underlying a task, models exploit shortcuts and contextual cues that happen to correlate with labels in training data (Geirhos et al., 2020; Saranrittichai et al., 2022). This fundamental failure mode creates profound practical implications, i.e., models that perform accurately within training distributions often fail catastrophically when deployed in new environments where these spurious correlations cease to hold (Mulchandani & Kim, 2025; Bassi et al., 2024).

Over the past several years, the research community has developed numerous bias mitigation methods and evaluated them extensively on vision benchmarks (Erobic et al., 2022; Sarridis et al., 2025b; Wu et al., 2023;

Sarridis et al., 2025a). This body of work has documented diverse manifestations of spurious correlations in vision datasets such as ImageNet (Geirhos et al., 2018), CelebA (Seo et al., 2022), and Waterbirds (Sagawa et al., 2019), where models tend to learn texture rather than shape (Geirhos et al., 2018), exploit background contextual cues instead of foreground objects (Sagawa et al., 2019; Sadiku, 2025), or rely on demographic correlations to achieve task performance (Seo et al., 2022; Serianni et al., 2025). These vision-centric benchmarks have substantially advanced our understanding of bias in deep learning.

Beyond vision, deep learning systems operate across multiple modalities and domains – Natural Language Processing (NLP) (Liusie et al., 2022; Zhou et al., 2024), audio (Oglic et al., 2022) and video (Zang et al., 2023) systems are prevalent in several AI applications, while systems processing medical images (Saab et al., 2022) play a central role in many healthcare applications. Biases manifest distinctly across modalities, arising from different origins. For instance, in text modalities, spurious correlations can emerge due to lexical patterns, i.e., associating identity terms (such as "muslim", "black", or "gay") with toxicity labels (Garg et al., 2019; Yadav et al., 2022). In audio, especially speech recognition systems, severe demographic biases arise from training data imbalance that systematically under-represent marginalized dialects and speech characteristics (Koenecke et al., 2020). Beyond demographic biases, audio datasets exhibit spurious correlations with task-irrelevant cues such as recording device signatures, microphone characteristics, and background noise patterns that happen to correlate with labels (Solewicz et al., 2016). In medical imaging, dataset biases can arise from institutional and technical variations, i.e., medical data comes from diverse sources (different hospitals, scanners, manufacturers, acquisition protocols), introducing systematic differences in image appearance that neural networks exploit rather than learning genuine diagnostic markers (Fortin et al., 2018; Gadewar et al., 2024). Finally, in video understanding, models tend to rely on scene context and background cues rather than genuine target signals, i.e., action recognition models in video datasets exploit the spatial clustering of actions (basketball on courts, cooking in kitchens) as shortcuts (Chung et al., 2022; Li et al., 2023). In several of these alternative domains, work on addressing spurious correlations remains sparse, fragmented, and often highly task-specific (Qin et al., 2024; Stanley et al., 2025).

Despite the modality-agnostic nature of spurious correlations, the generalization capabilities of visual bias mitigation approaches beyond natural images remain unexplored. To address this gap, this work introduces the first comprehensive cross-domain empirical study that systematically evaluates whether bias mitigation methods originally designed for natural images generalize to other modalities and domains. We benchmark 11 established and recent bias mitigation methods across 6 datasets, including text, audio, medical imaging, and video. Our study is framed as a benchmark effort, explicitly designed to provide researchers with systematic evidence on method generalization capabilities and to encourage the community to develop bias mitigation approaches that perform robustly across diverse modalities rather than optimizing for vision-specific benchmarks.

Specifically, the three central research questions guiding this work are:
RQ1: Do bias mitigation methods originally tested for natural image classification reduce bias in other domains/modalities (text, audio, medical imaging, video)?
RQ2: How do different methods rank, and are method rankings maintained across different domains/modalities compared to natural image benchmarks?
RQ3: For which bias mitigation methods is there evidence of statistically significant improvements in bias reduction when evaluated across diverse modalities and domains?
By systematically answering these questions, we provide the first empirical evidence on the generalization and limitations of visual bias mitigation approaches in highly diverse scenarios.

2 Background

Spurious correlations in machine learning occur when training datasets contain high statistical association between task-irrelevant attributes and target labels, enabling models to achieve acceptable training performance by exploiting these correlations rather than learning genuine causal relationships (Geirhos et al., 2020; Ye et al., 2024). Understanding the origins of such correlations requires examining both the statistical properties of datasets and the optimization dynamics of neural network training (Fabbrizzi et al., 2022; Sarridis et al., 2025a). The phenomenon of prioritizing easy-to-learn features in neural network optimization provides a

theoretical foundation for understanding spurious correlations (Shah et al., 2020; Yang et al., 2024; Sarridis et al., 2025b). When training data contains both causal and spurious features that enable task performance, networks exploit whichever feature (causal or spurious) has less complexity (Sarridis et al., 2025b;a; Shah et al., 2020; Vasudeva et al., 2023). Crucially, spurious features are often substantially simpler than genuine causal features—for example, background texture or color statistics versus object shape—making models default to these shortcuts when both predict the target label equally well in training data (Geirhos et al., 2018; Hermann et al., 2020). Sampling, measurement, and historical biases during data collection are the main mechanisms through which spurious correlations emerge (Fabbrizzi et al., 2022; Suresh & Guttag, 2021). Selection bias occurs when data collection fails to randomly sample from the target population, instead systematically excluding or under-representing particular demographic groups or task-relevant conditions (Fabbrizzi et al., 2022; Chauhan et al., 2025). Historical bias reflects societal biases embedded in data collected from past practices, where discriminatory historical patterns become encoded in datasets (Suresh & Guttag, 2021; Australian Human Rights Commission, 2020). Measurement bias arises when data collection methods or annotation procedures introduce systematic distortions, such as when human annotators introduce subjective biases during labeling (Haliburton et al., 2023; Suresh & Guttag, 2021).

2.1 Bias in Images

2.1.1 Natural Images

Natural image datasets, such as ImageNet (Deng et al., 2009), CelebA (Liu et al., 2015), and Waterbirds (Sagawa et al., 2019), have become foundational benchmarks for spurious correlation research and have enabled substantial progress in understanding and mitigating dataset biases in computer vision.

ImageNet remains the most widely used large-scale benchmark in computer vision and has significantly shaped the study of spurious correlations and debiasing methods. Systematic work has revealed that models trained on ImageNet exhibit a marked texture bias. Specifically, in controlled settings where the shape and texture cues of objects are artificially separated, standard convolutional neural networks (CNNs) like ResNet-50 overwhelmingly categorize ambiguous objects by texture rather than shape—contrary to the human vision system, which primarily relies on shape information (Geirhos et al., 2018). This demonstrates a fundamental misalignment between deep neural representations and human perception, as networks exploit textural patterns and local statistics that correlate with labels in the training data, rather than learning truly semantic object identities (Hermann et al., 2020). Other research has also highlighted that, beyond texture, models trained on ImageNet and similar datasets frequently depend on task-irrelevant background cues for prediction. For instance, models retain surprisingly high recognition accuracy even when provided with background regions alone, and can be misled by background-foreground mismatches (Xiao et al., 2021). To facilitate the study of robustness against real-world spurious correlations and corruptions, datasets like ImageNet-C (Hendrycks & Dietterich, 2019) have been designed to systematically evaluate model vulnerability to common corruptions (e.g., noise, blur, weather) and perturbations. Results indicate that, despite progress in model architecture, classifier robustness to such natural distribution shifts has improved only marginally, with simpler models and more complex models alike struggling with spurious signals introduced by corruptions (Hendrycks & Dietterich, 2019).

When such spurious correlations involve protected attributes—such as gender, race, or age—they create fairness issues that can perpetuate discrimination and inequitable outcomes. The CelebA dataset, which contains celebrity face images annotated with 40 demographic and appearance attributes (Liu et al., 2015), exemplifies how real-world datasets encode spurious correlations between certain attributes and demographic groups. For instance, substantial correlations exist between female gender and appearance attributes such as hair color, earrings, lipstick, and heavy makeup (Sarridis et al., 2025b), patterns that emerged naturally from the dataset's composition process rather than reflecting any causal relationship. Models trained to perform seemingly neutral tasks, such as predicting hair color on CelebA, implicitly learn to exploit gender as a proxy classifier, achieving high overall accuracy while demonstrating severe performance disparities across demographic groups (Hong & Yang, 2021).

2.1.2 Medical Images

Confounding biases from systematic institutional and technical variations represent a major source of dataset bias in medical imaging. Medical imaging data comes from diverse sources—different hospitals, clinics, and imaging centers—each using potentially different scanner hardware (varying manufacturers, field strengths, and hardware versions), acquisition protocols, and image reconstruction algorithms (Galanty et al., 2024; Koçak et al., 2025). These technical variations introduce systemic differences in image appearance that can be reliably detected by trained neural networks. Scanner-specific confounds have been documented across multiple medical image types, including MRI, where biases arise from scanner manufacturer, scanner upgrade history, scanner field strength variations, scanner drift over time, gradient nonlinearity hardware variations, and subject positioning (Fortin et al., 2018; Gadewar et al., 2024). These biases can influence quantitative imaging metrics substantially, affecting the reliability of models trained on multi-site, multi-scanner datasets.

2.2 Bias in Text

NLP models exhibit spurious correlations at multiple levels of linguistic organization, from token-level associations to concept-level patterns that cause models to exploit misleading correlations between superficial linguistic features and task labels (Wu et al., 2022; Yang et al., 2023).

Natural Language Inference datasets such as Stanford Natural Language Inference (SNLI) (Bowman et al., 2015) and Multi-Genre Natural Language Inference (MultiNLI) (Williams et al., 2018) have become prominent examples of spurious correlation problems in NLP. Models trained on these datasets exploit spurious correlations between surface-level lexical patterns and labels rather than learning genuine semantic relationships. For instance, models learn that the presence of certain keywords (such as "not", "people", or high word overlap) correlates with specific entailment decisions, enabling acceptable performance on training data while failing when these surface patterns are removed (Wu et al., 2022; Rajaee et al., 2022). Specifically, Wu et al. (2022) (Wu et al., 2022) demonstrated that models trained on standard SNLI and MultiNLI fail dramatically on out-of-distribution test sets where spurious correlations are not present.

Concept-level spurious correlations manifest as inappropriate associations between semantic concepts and labels. Language models trained on text corpora reflecting historical occupational gender imbalance learn to associate particular professions with specific genders (Kotek et al., 2023; Jiang et al., 2025). When prompted to generate text about a nurse, models overgenerate female pronouns; when generating about an engineer, models overgenerate male pronouns (Kotek et al., 2023).

Text classification tasks exhibit token-level spurious correlations where models learn unintended biases from data imbalance. Toxic comment classification systems trained on imbalanced corpora learn to associate identity terms (such as "gay", "muslim", or "black") with toxicity labels due to their overrepresentation in toxic examples (Garg et al., 2019; Yadav et al., 2022). This causes models to mislabel non-toxic comments containing identity terms as toxic. Counterfactual data augmentation approaches that generate examples with replaced identity terms while preserving syntax have been proposed to reduce these spurious correlations, though their effectiveness varies across datasets and domains (Yadav et al., 2022).

2.3 Bias in Audio

Audio datasets, particularly those used for Automatic Speech Recognition (ASR), exhibit severe demographic biases and demonstrate clear instances of spurious correlations in the speech domain. Systematic evaluations of major commercial ASR systems (Amazon, Apple, Google, IBM, Microsoft) have revealed dramatic performance disparities across demographic groups and dialects (Koenecke et al., 2020).

Acoustic modeling bias and dialectal variation constitute primary mechanisms by which ASR systems fail for speakers of marginalized dialects (Koenecke et al., 2020). Training data imbalance in speech corpora constitutes the root cause of ASR spurious correlations. The majority of training examples represent majority-dialect, controlled, formally-spoken utterances, lacking representation of minority dialect acoustic patterns and spontaneous speech characteristics. This imbalance is compounded by the historical underrepresentation of African Americans and other marginalized groups in linguistic datasets, which systematically exclude or

underrepresent non-mainstream dialects and conversational speech styles, perpetuating spurious correlations between demographic attributes and speaking style (Koenecke et al., 2020).

Beyond demographic biases, audio datasets exhibit spurious correlations with task-irrelevant acoustic and environmental cues. Models may rely on recording device signatures, background noise patterns, microphone characteristics, or channel artifacts that happen to correlate with labels in training data but do not generalize. For example, a speaker recognition system trained on recordings from a particular device may exploit device-specific acoustic signatures rather than learning speaker identity, leading to failure when tested on audio from different microphones or recording environments (Solewicz et al., 2016).

As in other modalities, the fundamental problem underlying these spurious correlations is that neural networks exploit whichever features are simplest and most readily available in the training data—often task-irrelevant acoustic or demographic cues—when they correlate with labels equally well as genuine causal features. It is worth noting that assessing and mitigating spurious correlations in audio remains largely unexplored (Ye et al., 2024).

2.4 Bias in Videos

Video understanding datasets exhibit background bias, where models learn to rely on scene context and environmental cues rather than the genuine target signal—human motion patterns—when predicting actions. This spurious correlation between background scenes and action categories emerges naturally in video datasets because certain actions are systematically associated with particular environments during data collection (Chung et al., 2022; Li et al., 2023).

Background bias in action recognition has been comprehensively characterized through evaluation of 74 action recognition models trained on the Kinetics-400 dataset (Chung et al., 2022). Systematic evaluation where background and action cues are deliberately mismatched—presenting videos where the background suggests one action but the human motion indicates another—revealed that models predict background classes at 29.5% accuracy compared to only 16.8% accuracy for actions when evaluated on such mismatched videos (Chung et al., 2022). This represents a substantial and pervasive background bias where models rely on scene cues as strongly as, or more strongly than, motion patterns.

Biases emerge from dataset characteristics where certain actions are spatially clustered: tennis occurs predominantly on tennis courts, cooking predominantly in kitchens, and playing basketball predominantly on basketball courts. During training, models encounter a strong correlation between background and action, and exploit this correlation for improved training performance (Chung et al., 2022; Li et al., 2023). Model design choices significantly influence background bias: models trained on fewer frames per video exhibit stronger background bias, suggesting that temporal information helps mitigate background reliance (Chung et al., 2022).

2.5 Related Work

Recent years have witnessed growing recognition that spurious correlations and dataset biases can emerge in a wide variety of domains and data modalities, prompting increased interest in understanding and mitigating bias in those contexts. Works such as G-AUDIT (Drenkow et al., 2025) have demonstrated the importance of systematic auditing for detecting dataset biases across modalities, including medical imaging, electronic health records, and tabular data. Similarly, research on the transferability of bias mitigation effects has explored whether debiasing techniques applied upstream can generalize across different downstream tasks and domains, revealing that bias mitigation benefits can transfer across text classification, coreference resolution, and other NLP tasks (Jin et al., 2021). However, despite the recognition that spurious correlations are a modality-agnostic challenge and the growing emphasis on multi-domain bias evaluation, the literature lacks a comprehensive cross-modal/domain comparative analysis that systematically evaluates whether bias mitigation methods generalize across modalities and tasks. This work addresses this gap by conducting the first extensive study examining the performance of 11 visual bias mitigation methods across 6 datasets spanning text, medical imaging, audio, and video modalities, providing empirical evidence on the generalization capabilities and limitations of natural image-domain debiasing approaches in other contexts.

3 Methodologies

3.1 Notation

Here, we introduce the notation used throughout the paper to ensure consistency across all methods. Let $f(\boldsymbol{x}; \boldsymbol{\theta})$ denote a neural network parametrized by $\boldsymbol{\theta}$, mapping an input $\boldsymbol{x} \in \mathbb{X}$ to a prediction $\hat{y} \in \mathbb{Y}$. The training dataset is denoted as

$$\mathbb{D} = \{(\boldsymbol{x}^{(i)}, y^{(i)}, \alpha^{(i)})\}_{i=1}^{N},$$

with N training examples, where $y^{(i)} \in \mathbb{Y}$ is the target label and $\alpha^{(i)} \in \mathbb{A}$ is a bias attribute. Bias mitigation methods that rely on the $\mathbb{A}$ labels are referred to as Bias Label Aware (BLA), whereas methods that do not have access to these labels are termed Bias Label Unaware (BLU). In this setting, the i-th sample is called bias-aligned if its target label $y^{(i)}$ and bias attribute $a^{(i)}$ follow the predominant spurious correlation in the training data, while the i-th sample is called bias-conflicting if $y^{(i)}$ and $a^{(i)}$ break this correlation and the attribute value contradicts the dominant bias pattern for that class.

The learned feature representation is $\boldsymbol{z}^{(i)} = h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), \quad h : \mathbb{X} \to \mathbb{R}^d$, where h denotes a feature extractor and the full model decomposes as $f(\boldsymbol{x}; \boldsymbol{\theta}) = g(h(\boldsymbol{x}; \boldsymbol{\theta}); \boldsymbol{\theta})$, where $g : \mathbb{R}^d \to \mathbb{Y}$ is the classification head. We denote the logits by $\boldsymbol{l}(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}) \in \mathbb{R}^C$, where C is the number of target classes in $\mathbb{Y}$. The vanilla Empirical Risk Minimization (ERM) objective is

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), y^{(i)}\big),$$

where $\mathcal{L}$ is typically the cross-entropy loss.

For methods requiring group structure, we define a group $g = (y, \alpha) \in \mathbb{G}, \quad \mathbb{G} = \mathbb{Y} \times \mathbb{A}$, and the subset of $\mathbb{D}$ belonging to group g as $\mathbb{D}_g = \{(\boldsymbol{x}^{(i)}, y^{(i)}, \alpha^{(i)}) \in \mathbb{D} : y^{(i)} = y, \; \alpha^{(i)} = \alpha\}$, with cardinality $N_g = |\mathbb{D}_g|$.

Table 1 summarizes the notation that is common to all the presented methodologies.

3.2 Bias Mitigation Methods

This study encompasses several approaches of both categories, featuring the following BLA methods: GroupDro (Sagawa et al., 2019), DI (Wang et al., 2020), EnD (Tartaglione et al., 2021), BB (Hong & Yang, 2021), and BAdd (Sarridis et al., 2025b), as well as the following BLU methods: LfF (Nam et al., 2020), SD (Pezeshki et al., 2021), JTT (Liu et al., 2021), Debian (Li et al., 2022), FLAC (Sarridis et al., 2024), and MAVias (Sarridis et al., 2025a). We selected this set of methods based on two criteria: (i) widely used, seminal approaches that are well established in this domain, and (ii) recent methods that demonstrate state-of-the-art performance. The key characteristics of these methods are reported in Table 2. Below, we briefly present the considered approaches.

Group Distributionally Robust Optimization (GroupDRO). GroupDRO (Sagawa et al., 2019) addresses bias by minimizing the worst-case loss across predefined groups $\mathbb{G}$. It maintains group weights $\{w_g\}_{g \in \mathbb{G}}$ updated during training. At iteration t, the weights are updated as

$$w_g^{(t+1)} = w_g^{(t)} \exp\big(\lambda_{GroupDro}\, \mathcal{L}_g^{(t)}\big),$$

where $\lambda_{GroupDro} > 0$ is a step size and $\mathcal{L}_g^{(t)}$ is the loss for group g at iteration t. Weights are normalized:

$$w_g^{(t+1)} \leftarrow \frac{w_g^{(t+1)}}{\sum_{g' \in \mathbb{G}} w_{g'}^{(t+1)}}.$$

The model minimizes the weighted average loss:

$$\min_{\boldsymbol{\theta}} \sum_{g \in \mathbb{G}} w_g^{(t)} \cdot \frac{1}{N_g} \sum_{(\boldsymbol{x}^{(i)}, y^{(i)}, \alpha^{(i)}) \in \mathbb{D}_g} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), y^{(i)}\big).$$

Table 1: Essential notation.

Symbol	Description
$\mathbb{X}$	Set of input samples
$\mathbb{Y}$	Set of target classes
$\mathbb{A}$	Set of bias attribute classes
$\mathbb{D}$	Training dataset
$\mathbb{G}$	Set of groups ($\mathbb{Y} \times \mathbb{A}$)
$\mathbb{T}$	Set of tags
$\mathbb{J}$	Set of misclassified samples
N	Number of samples
C	Number of target classes
$\boldsymbol{x} \in \mathbb{X}$	Input sample
$y \in \mathbb{Y}$	Target label
$\hat{y} \in \mathbb{Y}$	Predicted label
$\alpha \in \mathbb{A}$	Bias attribute label
$g = (y, \alpha) \in \mathbb{G}$	Group defined by label–attribute pair
λ	Method specific hyperparameter
w	Weight
$\mathcal{L}(\cdot)$	Loss function
$I(\cdot, \cdot)$	Mutual Information
$\sigma(\cdot)$	Sigmoid function
$p(\cdot)$	Probability
$p(\cdot|\cdot)$	Conditioned probability
$\boldsymbol{l}$	Logits
$\boldsymbol{Z}$	Features matrix
$\boldsymbol{G}$	Gram matrix
$\boldsymbol{\theta}$	Trainable parameters of the main model
$\boldsymbol{\psi}$	Trainable parameters of a method-specific auxiliary model
d	Features dimension
$h(\cdot)$	Feature extractor
$g(\cdot)$	Classification head
$f(\cdot)$	Full model (backbone & classification head)

Table 2: Summary of the integrated bias mitigation methods.

Method	Bias Labels	Summary
GroupDRO (Sagawa et al., 2019)	✓	Minimizes worst-case loss across predefined groups.
DI (Wang et al., 2020)	✓	Uses domain-specific classification heads for domain invariance.
EnD (Tartaglione et al., 2021)	✓	Disentangles bias representations and entangles class representations.
BB (Hong & Yang, 2021)	✓	Balances bias in the logit space using prior bias information.
BAdd (Sarridis et al., 2025b)	✓	Adds bias-capturing features to training to discourage their use.
LfF (Nam et al., 2020)	✕	Reweights samples based on bias-conflicting predictions from an auxiliary model.
SD (Pezeshki et al., 2021)	✕	Regularizes network logits for spectral decoupling and bias robustness.
JTT (Liu et al., 2021)	✕	Reweights misclassified samples, assuming they are bias-conflicting.
Debian (Li et al., 2022)	✕	Alternates training of main and auxiliary models for debiasing.
FLAC (Sarridis et al., 2024)	✕	Minimizes mutual information between representations and bias-capturing features.
MAVias (Sarridis et al., 2025a)	✕	Infers and mitigates visual biases using foundation models and regularization.

Domain Independent (DI). DI (Wang et al., 2020) aims to mitigate bias by learning representations invariant across different domains. Unlike traditional single-head architectures, DI employs multiple domain-specific classification heads $\{g^{(\alpha)}\}_{\alpha \in \mathbb{A}}$, where each head $g^{(\alpha)} : \mathbb{R}^d \to \mathbb{Y}$ corresponds to a distinct domain.

Let $h : \mathbb{X} \to \mathbb{R}^d$ be the shared feature extractor. For each input $(\boldsymbol{x}^{(i)}, y^{(i)}, \alpha^{(i)})$ belonging to domain $\alpha^{(i)}$, the model selects the classification head associated with this domain: $g^{(\alpha^{(i)})}(h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}))$.

The training objective minimizes the domain-specific loss:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\Big(g^{(\alpha^{(i)})}\big(h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta})\big), y^{(i)}\Big).$$

Entangling and Disentangling (EnD). EnD (Tartaglione et al., 2021) explicitly manipulates the feature space to reduce spurious correlations by working on the Gram matrix (inner products between normalized features). The method encourages features with the same bias attribute but different target classes to be orthogonal (disentangled), while encouraging features with the same target class but different bias attributes to be parallel (entangled). Each feature vector is normalized as:

$$\tilde{\boldsymbol{z}}^{(i)} = \frac{\boldsymbol{z}^{(i)}}{\|\boldsymbol{z}^{(i)}\|},$$

and the Gram matrix $\boldsymbol{G} \in \mathbb{R}^{M \times M}$ is computed as:

$$\boldsymbol{G} = \tilde{\boldsymbol{Z}}^{\top} \tilde{\boldsymbol{Z}},$$

where each entry $G_{i,j} = (\tilde{\boldsymbol{z}}^{(i)})^{\top} \tilde{\boldsymbol{z}}^{(j)} \in [-1, +1]$ represents the cosine similarity between normalized feature pairs.

The overall EnD regularization combines disentangling and entangling terms. The disentanglement term, $\mathcal{L}_{\perp}(\boldsymbol{G}, \mathbb{D}, \boldsymbol{\theta})$, encourages samples with the same bias attribute but different target classes to have orthogonal representations by minimizing their correlations, while the entanglement term, $\mathcal{L}_{\parallel}(\boldsymbol{G}, \mathbb{D}, \boldsymbol{\theta})$, encourages samples with the same target class but different bias attributes to have parallel (aligned) representations by maximizing their inner products. Please refer to Tartaglione et al. (2021) for details on the implementation of $\mathcal{L}_{\perp}$ and $\mathcal{L}_{\parallel}$).

The overall training objective combines the task-specific loss with EnD regularization:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), y^{(i)}\big) + \lambda_{\text{EnD},1} \mathcal{L}_{\perp}(\boldsymbol{G}, \mathbb{D}, \boldsymbol{\theta}) + \lambda_{\text{EnD},2} \mathcal{L}_{\parallel}(\boldsymbol{G}, \mathbb{D}, \boldsymbol{\theta}),$$

where regularization terms are denoted as $\lambda_{\text{EnD},1}$ and $\lambda_{\text{EnD},2}$.

Bias Balance (BB). BB(Hong & Yang, 2021) addresses spurious correlations by explicitly correcting for bias in the logit space. The method assumes access to prior knowledge about the bias distribution, specifically the conditional probability $p(\alpha \mid y)$ of observing bias attribute α given target class y in the training data. For a given sample with bias attribute α, BB constructs a bias prior vector $\boldsymbol{p}^{(\alpha)} \in \mathbb{R}^{C}$ where each entry corresponds to a target class:

$$[\boldsymbol{p}^{(\alpha)}]_y = \log p(\alpha \mid y), \quad \forall y \in \mathbb{Y}.$$

The prior $p(\alpha \mid y)$ is estimated empirically from the training set:

$$p(\alpha \mid y) = \frac{N_{y,\alpha}}{N_y},$$

where $N_{y,\alpha}$ is the number of training samples with target label y and bias attribute α, and N_y is the total number of samples with target y. Then, the training objective incorporates this bias-balancing mechanism:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}) - \boldsymbol{p}^{(\alpha^{(i)})}, y^{(i)}\big),$$

where $\boldsymbol{p}^{(\alpha^{(i)})}$ is the bias prior vector corresponding to the bias attribute $\alpha^{(i)}$ of sample i. By subtracting the log-prior $\log p(\alpha \mid y)$ from the logits, BB effectively removes the statistical bias encoded in the training distribution, forcing the model to learn decision boundaries that are independent of the spurious correlation structure between target labels and bias attributes.

Bias Addition (BAdd). BAdd (Sarridis et al., 2025b) explicitly adds bias-capturing features to the training procedure to discourage the main model from learning such features. First, the method trains an auxiliary bias-capturing model $f(\boldsymbol{x}; \boldsymbol{\psi})$ to predict bias attribute α:

$$\min_{\boldsymbol{\psi}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\psi}), \alpha^{(i)}\big).$$

Let $h(\boldsymbol{x}^{(i)}; \boldsymbol{\psi}) \in \mathbb{R}^d$ be bias-capturing features and $h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}) \in \mathbb{R}^d$ be the main model features. Then the training objective is:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}\big(g(h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}) + h(\boldsymbol{x}^{(i)}; \boldsymbol{\psi}); \boldsymbol{\theta}), \, y^{(i)}\big).$$

The underlying idea of BAdd is to inject $h(\boldsymbol{x}^{(i)}; \boldsymbol{\psi})$ into the training procedure, discouraging the main model from re-encoding bias information, as doing so would not further minimize training loss. Thus, $f(\boldsymbol{x}; \boldsymbol{\theta})$ learns different features that are expected to be more relevant to the defining characteristics of the target class.

Learning from Failure (LfF). LfF (Nam et al., 2020) employs a dual-model training paradigm that simultaneously trains the main model $f(\boldsymbol{x}; \boldsymbol{\theta})$ and an auxiliary model $f(\boldsymbol{x}; \boldsymbol{\psi})$. The key insight is that the biased model is intentionally trained to amplify bias by focusing on "easy" (bias-aligned) samples, while the debiased model focuses on samples that the biased model struggles with (bias-conflicting samples).

The biased model $f(\boldsymbol{x}; \boldsymbol{\psi})$ is trained using the Generalized Cross Entropy (GCE) loss to amplify its early-stage predictions and make it follow the unintended decision rule based on the bias attribute. Then, for each sample $\boldsymbol{x}^{(i)}$, LfF computes a relative difficulty score that indicates how likely the sample is to be bias-conflicting, where $\mathcal{L}$ denotes the standard cross-entropy loss. The optimization objective is defined as:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} w_i \, \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), y^{(i)}\big),$$

where w_i denotes the weight assigned to sample i.

Spectral Decouple (SD). SD (Pezeshki et al., 2021) introduces a generic regularization approach that does not require explicit bias identification or auxiliary models. The method is based on the observation that adding a specific regularization term to the network logits leads to spectral decoupling in the learned representations, enhancing robustness against spurious correlations. Specifically, the objective is defined as:

$$\min_{\boldsymbol{\theta}} \mathcal{L}\big(f(\boldsymbol{x}; \boldsymbol{\theta}), y\big) + \lambda_{\mathrm{SD}} \big\| f(\boldsymbol{x}; \boldsymbol{\theta}) \big\|,$$

where λ_{SD} is the regularization weight.

Just Train Twice (JTT). JTT (Liu et al., 2021) focuses on learning from misclassified examples, as they tend to be bias-conflicting samples. It uses a re-weighting scheme to prioritize these examples during training by modifying the data loaders accordingly. First, it trains an initial model $f(\boldsymbol{x}; \boldsymbol{\theta}_0)$ using standard cross-entropy loss for $\lambda_{\mathrm{JTT},1}$ epochs, and identifies the following error set:

$$\mathbb{J} = \left\{ i : \arg\max_{y \in \mathbb{Y}} f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}_0) \neq y^{(i)} \right\}.$$

Then, the new training set is constructed by upsampling the error examples by a factor $\lambda_{\mathrm{JTT},2}$ and keeping one copy of all other samples:

$$\mathbb{D}' = \big\{ (\boldsymbol{x}^{(i)}, y^{(i)}) : i \notin \mathbb{J} \big\} \cup \underbrace{\bigcup_{k=1}^{\lambda_{\mathrm{JTT},2}} \big\{ (\boldsymbol{x}^{(i)}, y^{(i)}) : i \in \mathbb{J} \big\}}_{\text{upsampled error examples}}.$$

If we denote the re-weighted samples as $\boldsymbol{x}'^{(i)}$ and the corresponding targets as $y'^{(i)}$ with $i \in \{1, \ldots, N'\}$, then the loss is calculated as follows:

$$\min_{\boldsymbol{\theta}} \frac{1}{N'} \sum_{i=1}^{N'} \mathcal{L}\big(f(\boldsymbol{x}'^{(i)}; \boldsymbol{\theta}), y'^{(i)}\big).$$

Debiasing Alternate Networks (Debian). Debian (Li et al., 2022) uses an auxiliary model, $f(\boldsymbol{x}; \boldsymbol{\psi})$, that aims to partition training samples for each target class y into two bias groups, $\{\alpha^+, \alpha^-\}$, such that the main model, $f(\boldsymbol{x}; \boldsymbol{\theta})$, violates the Equal Opportunity criterion. In other words, it identifies class-wise splits of the data where the model's True Positive Rate differs significantly across groups. Formally, the output logits are converted to bias group probabilities:

$$p(\boldsymbol{x}^{(i)}) = \sigma\big(\boldsymbol{l}(\boldsymbol{x}^{(i)}; \boldsymbol{\psi})\big) \in [0, 1],$$

where $\sigma(\cdot)$ is the sigmoid function. This probability indicates the likelihood that sample i belongs to the "positive" bias group (higher values mean stronger assignment to the positive group). The decision threshold is 0.5.

For each target class y, the average predicted probability w.r.t. the two groups, α^+ and α^-, is denoted as $P_{\alpha^+}^{(y)}$ and $P_{\alpha^-}^{(y)}$, respectively. P is used to identify the bias-conflicting groups per class. For instance, if $P_{\alpha^-}^{(y)} > P_{\alpha^+}^{(y)}$, then the samples with (α^+, y) are considered as bias-conflicting. Based on this, the weights are calculated as follows:

$$w_i = \begin{cases} 1 + p(\boldsymbol{x}^{(i)}) & \text{if } P_{\alpha^-}^{(y^{(i)})} > P_{\alpha^+}^{(y^{(i)})}, \\ 1 + \big(1 - p(\boldsymbol{x}^{(i)})\big) & \text{if } P_{\alpha^-}^{(y^{(i)})} \leq P_{\alpha^+}^{(y^{(i)})}. \end{cases}$$

Thus, samples that are considered as bias-conflicting with high confidence are up-weighted. Then, the minimization objective is:

$$\min_{\boldsymbol{\theta}} \frac{1}{N} \sum_{i=1}^{N} w_i \, \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), y^{(i)}\big).$$

The training follows an alternating scheme that allows $f(\boldsymbol{x}; \boldsymbol{\psi})$ to continuously identify new biases as $f(\boldsymbol{x}; \boldsymbol{\theta})$ evolves, and $f(\boldsymbol{x}; \boldsymbol{\theta})$ to progressively mitigate these identified biases.

Fairness Aware Representation Learning (FLAC). FLAC (Sarridis et al., 2024) focuses on learning fair representations by minimizing the dependence between features and sensitive attributes. The objective is to minimize the mutual information between representations and sensitive attributes, defined as:

$$\min_{\boldsymbol{\theta}} \mathcal{L}\big(f(\boldsymbol{x}; \boldsymbol{\theta}), y\big) + \lambda_{\text{FLAC}} I(h(\boldsymbol{x}; \boldsymbol{\theta}), h(\boldsymbol{x}; \boldsymbol{\psi})),$$

where λ_{FLAC} is a hyperparameter, $I(h(\boldsymbol{x}; \boldsymbol{\theta}), h(\boldsymbol{x}; \boldsymbol{\psi}))$ is the mutual information between representations and sensitive attributes. FLAC employs a bias-capturing model, $f(\boldsymbol{x}; \boldsymbol{\psi})$, trained to derive features $h(\boldsymbol{x}; \boldsymbol{\psi})$. In scenarios where training a dedicated bias-capturing model is impractical (e.g., unknown biases), the biased vanilla model can be employed, resulting in the FLAC-B variant.

Mitigate Any Visual Bias (MAVias). MAVias (Sarridis et al., 2025a) employs a two-stage approach. First, it infers potential visual biases by leveraging foundational models to generate descriptive tags for input images and assess their relevance to the target class. Subsequently, these potential biases are encoded using a vision-language model and incorporated into the training procedure as regularization, discouraging the model from learning spurious correlations. Formally, for each input $\boldsymbol{x}^{(i)}$, the method first extracts a set of tags $\mathbb{T}_i$ using an image tagging model. The irrelevant subset $\mathbb{T}'_i \subset \mathbb{T}_i$ is selected via a large language model. All tags in $\mathbb{T}'_i$ are embedded together into $h(\boldsymbol{x}^{(i)}; \boldsymbol{\psi}) \in \mathbb{R}^d$ using a vision-language encoder and a projection layer.

The main model backbone produces features $h(\boldsymbol{x}^{(i)}; \boldsymbol{\theta})$ and logits $\boldsymbol{l}_{\boldsymbol{\theta}}(\boldsymbol{x}^{(i)})$, while the bias-capturing features $h(\boldsymbol{x}^{(i)}; \boldsymbol{\psi})$ are passed through the same classification head g to obtain $\boldsymbol{l}_{\boldsymbol{\psi}, \boldsymbol{\theta}}(\boldsymbol{x}^{(i)})$. The final logits for loss computation are their sum. The overall minimization objective is calculated as:

$$\min_{\boldsymbol{\theta}, \boldsymbol{\psi}} \mathcal{L}\big(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}, \boldsymbol{\psi}), y^{(i)}\big) + \lambda_{\text{MAVias},1} \mathcal{L}_{\text{align}}\big(\boldsymbol{l}(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), \boldsymbol{l}(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}, \boldsymbol{\psi}), \lambda_{\text{MAVias},2}\big),$$

where $\lambda_{\text{MAVias},1}$ and $\lambda_{\text{MAVias},2}$ are hyperparameters and the following regularization term is used:

$$\mathcal{L}_{\text{align}} = \frac{1}{2} \left\| \left\| \boldsymbol{l}(\boldsymbol{x};\boldsymbol{\theta}) \right\| - \lambda_{\text{MAVias},2} \left\| \boldsymbol{l}(\boldsymbol{x};\boldsymbol{\theta},\boldsymbol{\psi}) \right\| \right\|^2.$$

Note that the first step of MAVias for deriving the $h(\boldsymbol{x}^{(i)};\boldsymbol{\psi})$ features is not applicable as our analysis does not involve natural images. Thus, we use the same bias capturing model as in BAdd and FLAC to derive them instead.

4 Evaluation Methodology

4.1 Datasets and Evaluation Protocol

As shown in Table 3, we employ a diverse set of 6 datasets spanning text, audio, medical imaging, and video data. Each dataset presents a distinct manifestation of spurious correlations that emerge due to certain domain characteristics. For every dataset, we identify a *target attribute* representing the primary classification task and a *spurious attribute* that exhibits statistical correlation with the target in the training distribution but does not reflect genuine causal relationships. This section provides detailed descriptions of each dataset, including the nature of the data, task formulation, and the sources of spurious correlations.

Following relevant literature, we adopt Average Accuracy (Avg Acc) and Worst-Group Accuracy (WG Acc) as the primary metrics for evaluating bias mitigation effectiveness (Sagawa et al., 2019; Sarridis et al., 2025a). The only exception applies to benchmarks explicitly designed for bias assessment, which consist exclusively of bias-conflicting (or out-of-distribution) samples; such benchmarks typically report standard accuracy as the evaluation metric (Sarridis et al., 2025c). Groups are defined as combinations of target classes and spurious attributes, with the total number of groups given by $|\mathcal{Y}| \times |\mathcal{A}|$, where $|\cdot|$ denotes cardinality. Avg Acc measures overall model performance aggregated across all groups, while WG Acc (i.e., the minimum accuracy across any single group) captures the most disadvantaged subgroup.

Table 3: Summary of datasets used for evaluating bias mitigation methods across modalities and domains.

Dataset	Modality	Target Task	Spurious Attribute
Bias in Bios	Text	Profession	Gender
Jigsaw Toxic Comments	Text	Identity hate detection	Identity terms
UrbanSounds8K	Audio	Engine idle vs. Siren	Sound salience
Speech Accent Archive	Audio	Native vs. Non-native accent	Gender
CheXpert + NIH	Medical Imaging	Pneumothorax detection	Dataset source
UCF101 + SCUBA	Video	Action recognition	Scene context

4.1.1 Bias in Bios: Occupational Gender Bias

The Bias in Bios (De-Arteaga et al., 2019) dataset addresses spurious correlations between gender and profession in biographies (i.e., text data). The dataset consists of short professional biographies scraped from Common Crawl[1], where each biography describes an individual's occupation and career background. The target classification task is to predict the individual's *profession* out of 28 possible occupational categories (e.g., surgeon, nurse, teacher, software engineer, architect).

The spurious correlation in this dataset emerges from historical and societal patterns of occupational gender imbalance that became embedded in the data collection process. Certain professions are significantly overrepresented by one gender in the training data; for instance, nurses are predominantly female, while surgeons are predominantly male. This reflects real-world historical gender distributions in these occupations, creating strong statistical associations between *gender* (the non-causal spurious attribute) and profession labels that models can exploit during training. Models trained on this data learn to use gender-associated linguistic cues (e.g., gendered pronouns "he" vs. "she", gendered names, or gender-stereotypical descriptive language) as predictive features for profession classification.

---

[1] https://commoncrawl.org/

4.1.2 Jigsaw Toxic Comments: Lexical Bias in Hate Speech Detection

The Jigsaw Toxic Comments (Jigsaw, 2018) dataset contains user comments from online discussion forums, labeled for various forms of toxicity, including threats, obscenity, insults, and identity-based hate speech. In our experiments, we focus specifically on *identity hate* classification as the target task.

The spurious correlation in this dataset (often referred to as lexical bias (Garg et al., 2023)) manifests at the token level, where certain non-offensive identity-related terms (e.g., "muslim", "black", or "jewish") appear disproportionately frequently in comments labeled as hateful. As a consequence, models trained on this dataset learn to associate the presence of certain neutral words with toxicity, leading them to incorrectly classify neutral or positive comments that involve such words as toxic. For example, a comment stating "I'm proud to be muslim" or "Black Lives Matter is an important movement" can be misclassified as identity-hate comments.

The official test set of this dataset does not adequately reveal the extent of lexical bias because it maintains similar distributional characteristics to the training data. To properly evaluate whether models rely on identity terms as spurious shortcuts versus learning genuine markers of hateful content, we construct a new hard-negative test set specifically designed to break the spurious identity-toxicity correlation.

To create this test set, we first perform a statistical analysis of the training data to identify words that appear with significantly elevated frequency in hateful comments but are not inherently offensive. Specifically, we extract the top-300 words that co-occur with the identity hate class within the training data, and then we manually filter this list of words to retain only those terms that are not inherently offensive, resulting in a curated set of the following 33 words: homosexual, homos, lesbians, homosexuals, queer, homosexuality, jew, semite, malaysians, nazi, asian, mexicans, jewish, spanish, white, black, pakistanis, moslem, semites, arabian, nazis, hispanics, indians, turks, mom, moms, males, mums, dads, albino, republican, muslims, and vegans. Then, we leverage a large language model (GPT-4) to generate 10 synthetic test samples for each extracted word, deliberately including them in neutral, non-hateful contexts. We report the generated test set in the Appendix A. We use the accuracy on the original test set and the generated test set to measure overall performance and bias reduction, respectively.

4.1.3 UrbanSounds8K: Acoustic Salience Bias

The UrbanSounds8K (Salamon et al., 2014) contains 8,732 labeled audio excerpts ($\leq$4 seconds) of urban sounds from 10 classes: air conditioner, car horn, children playing, dog bark, drilling, engine idling, gunshot, jackhammer, siren, and street music.

In this scenario, we focus on a subset of this dataset where acoustic recording conditions introduce a clear spurious correlation. Specifically, we consider a binary classification task distinguishing between *engine idle* and *siren* sounds, where the spurious attribute is *sound salience* (binary attribute), which is already provided in the data annotations and shows considerably high (low) co-occurrence with the *siren* (*engine idle*) class. Note that apart from class-defining sound properties, also recording circumstances, microphone placement, and environmental factors present during data collection can affect sound salience. Thus, we expect that a robust model can classify both sound types accurately regardless of salience conditions.

4.1.4 Speech Accent Archive: Gender-Accent Spurious Correlation

The Speech Accent Archive (Weinberger & Kunath, 2011) dataset consists of speech recordings from speakers with diverse native language backgrounds reading a standardized English passage. Each recording is annotated with speaker demographics (age, gender, native language) and linguistic characteristics. The dataset provides a rich resource for studying accent variation and speech patterns across different language backgrounds.

To investigate whether speaker gender can act as a spurious shortcut in speech classification tasks, we deliberately construct a biased training subset that introduces an intense correlation (90%) between *speaker gender* (the spurious attribute) and *English accent nativeness* (the target attribute). Native speakers are defined as those who learned English as their first language, and non-native speakers as those with other native languages. In particular, we subsample the original dataset to create a training distribution where

(90%) of male speakers are native English speakers and (90%) of female speakers are non-native English speakers. This setup follows established practices in the vision domain (Hong & Yang, 2021; Sarridis et al., 2024) for creating controlled spurious correlation scenarios. Note that this injected correlation does not reflect any genuine linguistic relationship (speaker gender does not causally influence language acquisition patterns or accent characteristics), making it an ideal spurious attribute for evaluation purposes. The binary classification task is to predict whether a given recording comes from a native or non-native English speaker.

4.1.5 CheXpert + NIH Chest X-ray: Data Source Bias in Medical Images

Medical imaging datasets present unique challenges in terms of biases due to the data acquisition factors. In this set of experiments, we aim to examine whether the dataset-specific characteristics can act as shortcuts to a disease detection model and whether bias mitigation approaches are effective in such scenarios. To this end, we construct a combined chest X-ray dataset by merging samples from two large-scale public datasets, namely CheXpert (Irvin et al., 2019) (collected from Stanford Hospital) and NIH Chest X-ray (Wang et al., 2017) (collected from the NIH Clinical Center). The target classification task is *pneumothorax* detection, i.e., identifying the presence of collapsed lung. We deliberately construct a training distribution where *dataset source* (CheXpert versus NIH) serves as a spurious attribute that is strongly correlated with the pneumothorax label. Specifically, we ensure that 90% of pneumothorax-positive cases originate from the CheXpert dataset, while 90% of negative cases come from the NIH Chest X-ray dataset.

To assess whether bias mitigation methods successfully eliminate reliance on dataset source, we evaluate models on a balanced test.

4.1.6 UCF101: Scene-Action Spurious Correlation

The UCF101 dataset (Soomro et al., 2012) is a widely-used benchmark for human action recognition in videos, containing 13,320 video clips across 101 action categories. Videos are collected from YouTube and include diverse human activities ranging from sports (basketball shooting, tennis swing, kayaking) to daily activities (applying makeup, brushing teeth, typing) to musical performances (playing guitar, playing violin, drumming). Each video is approximately 7 seconds long and captured under realistic, unconstrained conditions with varying camera viewpoints, subject appearance, object scales, background complexity, and lighting conditions.

To systematically evaluate scene-action bias in video action recognition, we leverage the SCUBA benchmark (Li et al., 2023), which provides a curated set of samples with action-scene mismatches. Specifically, SCUBA contains videos where actions are performed in atypical background scenes, creating explicit conflicts between the action and scene attributes. This allows us to measure how well models generalize when the spurious action-scene correlation is deliberately broken.

However, the original SCUBA benchmark is designed primarily for domain generalization setups, where no bias-conflicting samples appear in the training set (i.e., 100% co-occurrence between the target class and the spurious attribute). To fairly assess whether considered bias mitigation methods are effective in mitigating spurious scene-action correlations, we require training-time exposure to bias-conflicting examples, i.e., samples where the action and typical background scene do not align. Therefore, we adopt a modified protocol, where we include two samples per action class from the SCUBA benchmark into the training set. At test time, we evaluate on the remaining SCUBA samples that were not included in the training set, where actions continue to be mismatched with their typical scene contexts. Considering that SCUBA involves only bias-conflicting samples, we measure performance using standard classification accuracy, which is the typical evaluation metric for this benchmark and directly reflects whether models can correctly classify actions regardless of background scene context. Additionally, to provide further insights into the generalization properties of bias mitigation methods, we include full experiments using the original SCUBA benchmark without including any SCUBA samples in the training set in the Appendix A.

4.2 Implementation Details

For all experiments, we use Adam optimizer with a learning rate of 0.001, a batch size of 64, and a linear scheduler that divides the learning rate by 10 at specified epochs, unless stated otherwise. For both text

datasets, we employ the *all-MiniLM-L6-v2* encoder, a compact sentence transformer model that provides effective semantic representations for text classification tasks. For Bias in Bios, we train for 50 epochs and the learning rate decays at epochs 16 and 33. For Jigsaw Toxic Comments, we train for 200 epochs and apply weight decay of 0.01. The learning rate linearly decays at epochs 70 and 140. For the Speech Accent Archive dataset, we use the *wav2vec2-base-960h* as backbone, which provides strong acoustic representations learned from 960 hours of labeled speech data. Training proceeds for 100 epochs and the learning rate decays at epochs 33 and 66. For UrbanSounds8K, we extract the Mel-Frequency Cepstral Coefficients (MFCC) features as acoustic representations. We train a classification head for 100 epochs with a weight decay of 0.0001. The learning rate decays at epochs 33 and 66. For the medical images, we employ a ResNet18 pretrained on ImageNet as backbone. The model is trained for 20 epochs and the learning rate decays at epochs 6 and 13. For action recognition, we follow other works (Li et al., 2023) and we employ swin-t3d, a 3D spatiotemporal backbone pretrained on the Kinetics-400 dataset, which captures both spatial and temporal patterns that are essential for video understanding. Given the computational demands of video processing, we train for 30 epochs with a smaller batch size of 32. We use the AdamW optimizer with a more conservative learning rate of 0.000025. Weight decay is set to 0.01 and rather than a linear scheduler, we employ a cosine annealing learning rate schedule with 2.5 epochs of warmup. The full hyperparameter selections for each method are reported in the Appendix A. Note that for the MAVias approach, we use only the mitigation component, as its bias detection component is tailored to natural images and thus cannot be employed in the context of this work. For methods requiring a bias-capturing model, we train it on the same dataset, using the spurious attribute as the target. All experiments were conducted using an NVIDIA A100 GPU, except for the video experiments, which were conducted using an NVIDIA H200 GPU. Each experiment was executed with 5 random seeds, except for the video experiments, where we used 3 random seeds.

5 Results

We present the results of our empirical evaluation of 11 bias mitigation methods across 6 datasets spanning text, audio, medical imaging, and video modalities. Our analysis addresses the three research questions we posed in the introduction regarding the generalization capabilities of bias mitigation methods for natural images to other domains and modalities.

RQ1: Do bias mitigation methods originally tested for natural image classification reduce bias in other domains/modalities (text, audio, medical imaging, video)?

Table 4: Performance comparison on Jigsaw Toxic Comments and Bias in Bios datasets.

Method	Jigsaw Toxic Comments		Bias in Bios	
	Official Set Acc	Generated Set Acc	Avg Acc	WG Acc
Vanilla	$94.6_{\pm0.1}$	$73.5_{\pm0.4}$	$46.5_{\pm40.2}$	$16.9_{\pm14.7}$
BB	$75.5_{\pm0.9}$ (-19.1)	$14.0_{\pm0.8}$ (-59.5)	$66.1_{\pm0.3}$ (+19.6)	$0.0_{\pm0.0}$ (-16.9)
Debian	$94.8_{\pm0.1}$ (+0.2)	$81.6_{\pm0.7}$ (+8.1)	$67.9_{\pm0.3}$ (+21.4)	$25.7_{\pm1.6}$ (+8.8)
DI	$93.9_{\pm0.1}$ (-0.7)	$74.2_{\pm1.3}$ (+0.7)	$69.2_{\pm0.5}$ (+22.7)	$31.3_{\pm4.2}$ (+14.4)
EnD	$94.9_{\pm0.2}$ (+0.3)	$81.6_{\pm0.7}$ (+8.1)	$52.2_{\pm34.8}$ (+5.7)	$18.7_{\pm12.6}$ (+1.8)
GroupDro	$91.0_{\pm1.6}$ (-3.6)	$94.0_{\pm2.7}$ (+20.5)	$72.6_{\pm0.7}$ (+26.1)	$52.5_{\pm3.5}$ (+35.6)
JTT	$72.5_{\pm1.2}$ (-22.1)	$80.8_{\pm1.5}$ (+7.3)	$45.2_{\pm1.1}$ (-1.3)	$18.9_{\pm5.9}$ (+2.0)
LfF	$94.7_{\pm0.2}$ (+0.1)	$81.8_{\pm0.6}$ (+8.3)	$69.4_{\pm0.2}$ (+22.9)	$27.9_{\pm4.0}$ (+11.0)
SD	$94.7_{\pm0.1}$ (+0.1)	$72.8_{\pm0.3}$ (-0.7)	$67.9_{\pm0.7}$ (+21.4)	$19.1_{\pm2.9}$ (+2.2)
FLAC	$85.7_{\pm1.9}$ (-8.9)	$95.8_{\pm2.5}$ (+22.3)	$68.3_{\pm0.8}$ (+21.8)	$29.9_{\pm3.5}$ (+13.0)
BAdd	$88.2_{\pm1.1}$ (-6.4)	$95.5_{\pm0.9}$ (+22.0)	$70.1_{\pm0.6}$ (+23.6)	$43.1_{\pm1.4}$ (+26.2)
MAVias	$90.1_{\pm0.7}$ (-4.5)	$94.0_{\pm1.1}$ (+20.5)	$73.8_{\pm0.3}$ (+27.3)	$46.8_{\pm0.6}$ (+29.9)

For the text modalities, Table 4 reveals clear performance patterns. On the Jigsaw Toxic Comments dataset, most compared methods effectively mitigate biases, as reflected by their accuracy on the generated test set. In particular, FLAC, BAdd, MAVias, and GroupDro achieve the largest gains (>20%) over the vanilla baseline.

These improvements often come at the cost of lower accuracy on the official test set, which is expected, as the models rely less on the spurious correlations present in that set. For the Bias in Bios dataset, which targets occupational gender bias, most evaluated methods show improvements in worst-group accuracy, with GroupDro achieving the most substantial gain of 35.6%. MAVias and BAdd also perform strongly, improving worst-group accuracy by 29.9% and 26.2%, respectively. Across both text datasets, BB demonstrates poor effectiveness, leading to underfitting and consequently degrades both overall performance and bias.

Table 5: Performance comparison on Speech Accent Archive and UrbanSounds8k.

Method	Accent Archive		UrbanSounds	
	Avg Acc	WG Acc	Avg Acc	WG Acc
Vanilla	$71.5_{\pm31.7}$	$64.9_{\pm29.8}$	$72.9_{\pm1.8}$	$47.5_{\pm3.4}$
BB	$84.9_{\pm1.0}$ (+13.4)	$80.5_{\pm2.1}$ (+15.6)	$75.3_{\pm4.3}$ (+2.4)	$65.3_{\pm8.5}$ (+17.8)
Debian	$84.1_{\pm0.9}$ (+12.6)	$78.9_{\pm2.3}$ (+14.0)	$71.8_{\pm2.4}$ (-1.1)	$51.3_{\pm5.1}$ (+3.8)
DI	$84.0_{\pm1.1}$ (+12.5)	$79.7_{\pm1.7}$ (+14.8)	$74.1_{\pm1.7}$ (+1.2)	$60.5_{\pm4.4}$ (+13.0)
EnD	$84.6_{\pm1.1}$ (+13.1)	$78.9_{\pm2.2}$ (+14.0)	$72.5_{\pm2.6}$ (-0.4)	$54.0_{\pm9.2}$ (+6.5)
GroupDro	$82.8_{\pm0.9}$ (+11.3)	$75.0_{\pm2.2}$ (+10.1)	$67.8_{\pm4.7}$ (-5.1)	$39.7_{\pm6.7}$ (-7.8)
JTT	$78.1_{\pm0.4}$ (+6.6)	$72.7_{\pm2.5}$ (+7.8)	$72.5_{\pm1.7}$ (-0.4)	$49.3_{\pm2.8}$ (+1.8)
LfF	$85.0_{\pm1.6}$ (+13.5)	$79.6_{\pm2.0}$ (+14.7)	$71.6_{\pm3.0}$ (-1.3)	$53.0_{\pm7.9}$ (+5.5)
SD	$85.3_{\pm1.7}$ (+13.8)	$79.4_{\pm3.1}$ (+14.5)	$72.6_{\pm2.1}$ (-0.3)	$44.7_{\pm5.7}$ (-2.8)
FLAC	$84.8_{\pm0.9}$ (+13.3)	$81.6_{\pm1.1}$ (+16.7)	$71.2_{\pm3.9}$ (-1.7)	$60.2_{\pm5.6}$ (+12.7)
BAdd	$82.9_{\pm0.2}$ (+11.4)	$78.4_{\pm6.1}$ (+13.5)	$75.9_{\pm2.2}$ (+3.0)	$65.5_{\pm7.3}$ (+18.0)
MAVias	$86.4_{\pm1.1}$ (+14.9)	$84.7_{\pm0.2}$ (+19.8)	$68.8_{\pm4.0}$ (-4.1)	$62.7_{\pm6.3}$ (+15.2)

Table 5 demonstrates substantial bias reduction across both datasets in the audio modality (covering both sound and speech domains). On the Speech Accent Archive, all bias mitigation methods significantly outperformed the vanilla baseline in both average and worst-group accuracy, with all methods except JTT achieving gains greater than 10%. MAVias achieved the highest improvement in worst-group accuracy (19.8%), followed by FLAC (16.7%). For UrbanSound8K, which examines acoustic salience bias, the results were more variable. BAdd and BB achieved the strongest improvements in worst-group accuracy (18% and 17.8%), while GroupDro and SD exhibited decreased performance. Additionally, we observe that most methods lead to small drops in average performance. This suggests that, although the models reduced their reliance on spurious correlations, they were unable to leverage other informative features to improve overall accuracy.

Table 6: Performance on CheXpert + NIH and UCF101+SCUBA datasets.

Method	CheXpert + NIH		UCF101+SCUBA
	Avg Acc	WG Acc	Acc
Vanilla	$61.2_{\pm3.4}$	$31.0_{\pm3.9}$	$72.0_{\pm0.3}$
BB	$70.8_{\pm3.9}$ (+9.6)	$61.1_{\pm7.3}$ (+30.1)	$69.4_{\pm1.9}$ (-2.6)
Debian	$62.1_{\pm2.8}$ (+0.9)	$31.8_{\pm8.2}$ (+0.8)	$70.1_{\pm1.3}$ (-1.9)
DI	$69.0_{\pm1.4}$ (+7.8)	$59.3_{\pm4.4}$ (+28.3)	$46.6_{\pm3.1}$ (-25.4)
EnD	$61.7_{\pm4.2}$ (+0.5)	$31.5_{\pm2.5}$ (+0.5)	$72.5_{\pm0.9}$ (+0.5)
GroupDro	$58.0_{\pm1.9}$ (-3.2)	$12.5_{\pm10.2}$ (-18.5)	$69.0_{\pm1.8}$ (-3.0)
JTT	$54.8_{\pm3.5}$ (-6.4)	$20.1_{\pm9.5}$ (-10.9)	$65.4_{\pm1.1}$ (-6.6)
LfF	$60.8_{\pm4.4}$ (-0.4)	$25.0_{\pm10.3}$ (-6.0)	$72.6_{\pm0.8}$ (+0.6)
SD	$59.0_{\pm4.4}$ (-2.2)	$25.2_{\pm9.6}$ (-5.8)	$74.5_{\pm1.0}$ (+2.5)
FLAC	$52.9_{\pm3.8}$ (-8.3)	$46.3_{\pm5.8}$ (+15.3)	$73.4_{\pm1.0}$ (+1.4)
BAdd	$72.1_{\pm2.3}$ (+10.9)	$64.4_{\pm5.3}$ (+33.4)	$73.2_{\pm2.2}$ (+1.2)
MAVias	$68.7_{\pm1.5}$ (+7.5)	$55.0_{\pm3.8}$ (+24.0)	$76.1_{\pm0.9}$ (+4.1)

Figure 1: Summary of performance gains and drops for each method across datasets. We define gains/drops as changes in the bias metrics that exceed ±5% relative to the vanilla baselines. Performance corresponds to the fairness metric used for each dataset—generated set accuracy for Jigsaw Toxic Comments, accuracy for UCF101+SCUBA, and worst-group accuracy for all remaining datasets.

For medical imaging, Table 6 shows that bias mitigation on the CheXpert–NIH combined dataset is particularly challenging. While BAdd, BB, and MAVias achieved notable worst-group accuracy improvements of 33.4%, 30.1%, and 24.0% respectively, several methods, including GroupDro and JTT, substantially degraded performance. This suggests that the dataset-specific artifacts present in this domain are especially difficult for existing bias mitigation techniques to overcome.

For the video action recognition task, Table 6 shows mixed performance on the UCF101-SCUBA benchmark. MAVias achieved the strongest improvement with a 4.1% accuracy increase, followed by SD (+2.5%) and FLAC (+1.4%). However, several methods performed poorly. Most notably, DI reduced accuracy by 25.4%, indicating that using multiple classification heads in scenarios with a large number of classes (e.g., 101) can be detrimental to the training process.

Figure 1 visualizes the ability of the compared methods to reduce biases across the evaluated datasets by summarizing the cases in which each method increased or decreased bias mitigation performance. The figure clearly shows that methods such as MAVias, BAdd, and FLAC consistently yield performance gains across most domains, whereas methods like GroupDro, BB, and JTT exhibit more inconsistent behavior, with performance drops on several datasets.

Furthermore, we compare the performance between the two main categories of bias mitigation approaches, i.e., BLA and BLU. As shown in Figure 2, BLA methods tend to be substantially more effective in challenging scenarios where the baseline performance is particularly low.

RQ2: How do different methods rank, and are method rankings maintained across different domains/modalities compared to natural image benchmarks?

To comprehensively evaluate the ranking of the methods, we also incorporate results from recent work benchmarking bias mitigation techniques on natural image datasets (Sarridis et al., 2025c). Specifically, we use the reported worst-group accuracy for the same 11 methods evaluated in our study on CelebA, Waterbirds, and UrbanCars.

Figure 3 compares the mean rankings of the methods when evaluated on natural images versus other domains/modalities. As shown, most methods maintain relatively stable rankings across evaluation contexts, typically within approximately ±2 rank positions, with MAVias and BAdd consistently occupying the top two positions. In contrast, FLAC and GroupDro tend to perform worse on natural images, whereas JTT achieves substantially better rankings in that setting.

Figure 2: Compare Bias Label Aware (BLA) and Bias Label Unaware (BLU) methods' mean performance in terms of bias. The mean performance for each group (BLA or BLU) is computed using the fairness metrics corresponding to each dataset—generated set accuracy for Jigsaw Toxic Comments, accuracy for UCF101+SCUBA, and worst-group accuracy for all remaining datasets. The red dotted lines denote the performance of the Vanilla baseline, while the intervals represent the standard deviation.

Figure 3: Rankings comparison: Natural image data vs other domains/modalities.

Figure 4: Method rankings (lower is better).

Figure 4 provides a more detailed view of the mean rankings by presenting separate ranking visualizations for natural images (panel a), other domains/modalities (panel b), and overall performance (panel c). The figure also depicts ranking variability, estimated via bootstrapping with 10,000 simulations. Specifically, the variability is obtained by resampling the datasets with replacement and recomputing the rankings for each bootstrap sample. Notably, MAVias, BAdd, and FLAC occupy the top three positions in the overall ranking, with MAVias exhibiting the highest consistency.

RQ3: For which bias mitigation methods is there evidence of statistically significant improvements in bias reduction when evaluated across diverse modalities and domains?

After conducting a Friedman test, which yielded a p-value of 1.5×10^{-5}, Table 7 presents the results of the Nemenyi post-hoc pairwise comparisons across all datasets (including the three natural image datasets), providing statistical evidence regarding the effectiveness of each method. The analysis indicates that only a subset of methods achieves statistically significant improvements over the vanilla baseline. Specifically, MAVias exhibits the strongest statistical evidence for effectiveness, achieving a p-value of 0.00084 and an average rank of 2.33. This highly significant result ($p < 0.001$) provides compelling support that MAVias consistently reduces bias across diverse modalities and domains. BAdd obtains the second-strongest statistical evidence, with a p-value of 0.00644 ($p < 0.01$) and an average rank of 3.22. FLAC shows marginal statistical significance, with a p-value of 0.07377 and an average rank of 4.33. While this result does not meet the conventional $p = 0.05$ threshold, it approaches significance and suggests a meaningful trend toward improved performance.

It is important to note that the Nemenyi post-hoc test is highly conservative, and detecting statistically significant differences is challenging when the number of datasets is relatively small (Demšar, 2006). Consequently, observing $p < 0.05$ is a strong indicator of robustness, while the absence of significance should not be

interpreted as evidence that a method fails to reduce bias. In addition to the statistical tests, the average rankings presented in Figure 4 provide valuable insights for understanding the effectiveness relationships between the compared methods.

Table 7: Nemenyi post-hoc pest p-values vs Vanilla and average ranks of methods.

Method	p-value vs Vanilla	Avg Rank
MAVias	0.00084	2.33
BAdd	0.00644	3.22
FLAC	0.07377	4.33
DI	0.28967	5.33
BB	0.58100	6.11
LfF	0.76222	6.44
EnD	0.86888	6.78
Debian	0.89664	6.89
SD	0.99072	7.67
JTT	1.00000	9.00
GroupDro	1.00000	9.22
Vanilla	–	9.67

6 Conclusion

This work addresses an important research gap in machine learning bias research by conducting the first comprehensive empirical investigation of whether bias mitigation methods originally designed for natural images can generalize to other domains and modalities, evaluating 11 methods across 7 diverse datasets spanning text, audio, medical imaging, and video. Our findings demonstrate that most bias mitigation approaches reduce bias across multiple modalities, with methods such as MAVias, BAdd, and FLAC consistently achieving substantial improvements in worst-group accuracy exceeding 20% in several cases. Regarding method stability, most approaches maintain relatively consistent rankings across natural images and other domains, with MAVias and BAdd consistently occupying top positions, though notable exceptions like FLAC and GroupDro exhibit domain-specific ranking variations. Statistical significance testing using the Friedman test reveals that only a subset of methods achieve statistically significant improvements when aggregated across all datasets, with MAVias ($p < 0.001$, rank 2.33) and BAdd ($p < 0.01$, rank 3.22) demonstrating the strongest evidence for effectiveness. These findings indicate that overall bias mitigation methods designed for natural images can transfer to other domains, but careful validation is essential.

References

Australian Human Rights Commission. Historical bias in AI systems. `https://humanrights.gov.au/about/news/media-releases/historical-bias-ai-systems`, 2020. Accessed: 2025-11-16.

Pedro RAS Bassi, Sergio SJ Dertkigil, Giuliano B Cavallari, Carlos E Machado, and Romis Attux. Improving deep neural network generalization and robustness to background bias via layer-wise relevance propagation. *Scientific Reports*, 14(1):447, 2024.

Samuel Bowman, Gabor Angeli, Christopher Potts, and Christopher D Manning. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 conference on empirical methods in natural language processing*, pp. 632–642, 2015.

Vinod Kumar Chauhan, Lei Clifton, Achille Salaün, Huiqi Yvonne Lu, Kim Branson, Patrick Schwab, Gaurav Nigam, and David A Clifton. Sample selection bias in machine learning for healthcare. *ACM Transactions on Computing for Healthcare*, 6(4):1–24, 2025.

Jihoon Chung, Yu Wu, and Olga Russakovsky. Enabling detailed action recognition evaluation through video dataset augmentation. *Advances in Neural Information Processing Systems*, 35:39020–39033, 2022.

Maria De-Arteaga, Alexey Romanov, Hanna Wallach, Jennifer Chayes, Christian Borgs, Alexandra Chouldechova, Sahin Geyik, Krishnaram Kenthapadi, and Adam Tauman Kalai. Bias in bios: A case study of semantic representation bias in a high-stakes setting. *Proceedings of the 2019 Conference on Fairness, Accountability, and Transparency*, pp. 120–133, 2019. doi: 10.1145/3287560.3287572.

Janez Demšar. Statistical comparisons of classifiers over multiple data sets. *Journal of Machine learning research*, 7(Jan):1–30, 2006.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255. IEEE, 2009.

Nathan Drenkow, Mitchell Pavlak, Keith Harrigian, Ayah Zirikly, Adarsh Subbaswamy, Mohammad Mehdi Farhangi, Nicholas Petrick, and Mathias Unberath. Detecting dataset bias in medical ai: A generalized and modality-agnostic auditing framework. *arXiv preprint arXiv:2503.09969*, 2025.

Nicholas Erobic, Fatemeh Mireshghallah, Reza Shokri, and Taylor Berg-Kirkpatrick. Are bias mitigation techniques for deep learning effective? *arXiv preprint arXiv:2104.00170*, 2022.

Simone Fabbrizzi, Symeon Papadopoulos, Eirini Ntoutsi, and Ioannis Kompatsiaris. A survey on bias in visual datasets. *Computer Vision and Image Understanding*, 223:103552, 2022.

Jean-Philippe Fortin, Nicholas Cullen, Yvette I Sheline, Warren D Taylor, Irem Aselcioglu, Philip A Cook, Phil Adams, Crystal Cooper, Maurizio Fava, Patrick J McGrath, et al. Harmonization of cortical thickness measurements across scanners and sites. *Neuroimage*, 167:104–120, 2018.

Shruti P Gadewar, Alyssa H Zhu, Iyad Ba Gari, Sunanda Somu, Sophia I Thomopoulos, Paul M Thompson, Talia M Nir, and Neda Jahanshad. Synthesizing study-specific controls using generative models on open access datasets for harmonized multi-study analyses. In *2024 IEEE International Symposium on Biomedical Imaging (ISBI)*, pp. 1–5. IEEE, 2024.

Maria Galanty, Dieuwertje Luitse, Sijm H Noteboom, Philip Croon, Alexander P Vlaar, Thomas Poell, Clara I Sanchez, Tobias Blanke, and Ivana Išgum. Assessing the documentation of publicly available medical image and signal datasets and their impact on bias using the beamrad tool. *Scientific Reports*, 14(1):31846, 2024.

Sahaj Garg, Vincent Perot, Nicole Limtiaco, Ankur Taly, Ed H Chi, and Alex Beutel. Counterfactual fairness in text classification through robustness. In *Proceedings of the 2019 AAAI/ACM Conference on AI, Ethics, and Society*, pp. 219–226, 2019.

Tanmay Garg, Sarah Masud, Tharun Suresh, and Tanmoy Chakraborty. Handling bias in toxic speech detection: A survey. *ACM Computing Surveys*, 55(13s):1–32, 2023.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. In *International conference on learning representations*, 2018.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11): 665–673, 2020.

Luke Haliburton, Sinksar Ghebremedhin, Robin Welsch, Albrecht Schmidt, and Sven Mayer. Investigating labeler bias in face annotation for machine learning. *arXiv preprint arXiv:2301.09902*, 2023.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *arXiv preprint arXiv:1903.12261*, 2019.

Katherine Hermann, Ting Chen, and Simon Kornblith. The origins and prevalence of texture bias in convolutional neural networks. *Advances in neural information processing systems*, 33:19000–19015, 2020.

Youngkyu Hong and Eunho Yang. Unbiased classification through bias-contrastive and bias-balanced learning. *Advances in Neural Information Processing Systems*, 34:26449–26461, 2021.

Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, Jayne Seekins, David A. Mong, Safwan S. Halabi, Jesse K. Sandberg, Ricky Jones, David B. Larson, Curtis P. Langlotz, Bhavik N. Patel, Matthew P. Lungren, and Andrew Y. Ng. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):590–597, 2019. doi: 10.1609/aaai.v33i01.3301590.

Leilei Jiang, Guixiang Zhu, Jianshan Sun, Jie Cao, and Jia Wu. Exploring the occupational biases and stereotypes of chinese large language models. *Scientific Reports*, 15(1):18777, 2025.

Jigsaw. Toxic comment classification challenge, 2018. URL https://www.kaggle.com/c/jigsaw-toxic-comment-classification-challenge.

Xisen Jin, Francesco Barbieri, Brendan Kennedy, Aida Mostafazadeh Davani, Leonardo Neves, and Xiang Ren. On transferability of bias mitigation effects in language model fine-tuning. In *Proceedings of the 2021 conference of the North American chapter of the association for computational linguistics: human language technologies*, pp. 3770–3783, 2021.

Burak Koçak, Andrea Ponsiglione, Arnaldo Stanzione, Christian Bluethgen, João Santinha, Lorenzo Ugga, Merel Huisman, Michail E Klontzas, Roberto Cannella, and Renato Cuocolo. Bias in artificial intelligence for medical imaging: fundamentals, detection, avoidance, mitigation, challenges, ethics, and prospects. *Diagnostic and interventional radiology*, 31(2):75, 2025.

Allison Koenecke, Andrew Nam, Elijah Lake, Brandon Nudell, Michael Quartey, Zye Mengesha, Caitlyn Toups, William Sewell, Crystal Wells, Ellen Shoemaker, et al. Racial disparities in automated speech recognition. *Proceedings of the National Academy of Sciences*, 117(14):7684–7689, 2020.

Hadas Kotek, Rikker Dockum, and David Sun. Gender bias and stereotypes in large language models. In *Proceedings of the ACM collective intelligence conference*, pp. 12–24, 2023.

Haoxin Li, Yuan Liu, Hanwang Zhang, and Boyang Li. Mitigating and evaluating static bias of action representations in the background and the foreground. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 19911–19923, 2023.

Zhiheng Li, Anthony Hoogs, and Chenliang Xu. Discover and mitigate unknown biases with debiasing alternate networks. In *European Conference on Computer Vision*, pp. 270–288. Springer, 2022.

Evan Z Liu, Behzad Haghgoo, Annie S Chen, Aditi Raghunathan, Pang Wei Koh, Shiori Sagawa, Percy Liang, and Chelsea Finn. Just train twice: Improving group robustness without training group information. In *International Conference on Machine Learning*, pp. 6781–6792. PMLR, 2021.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Adian Liusie, Zheng Zhang, Vineet Raina, and Mark JF Gales. Analyzing biases to spurious correlations in text classification tasks. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pp. 3539–3551, 2022.

Pietro Melzi, Ruben Tolosana, Ruben Vera-Rodriguez, Minchul Kim, Christian Rathgeb, Xiaoming Liu, Ivan DeAndres-Tame, Aythami Morales, Julian Fierrez, Javier Ortega-Garcia, et al. Frcsyn-ongoing: Benchmarking and comprehensive evaluation of real and synthetic data to improve face recognition systems. *Information Fusion*, 107:102322, 2024.

Elmokhtar Mohamed Moussa, Ioannis Sarridis, Emmanouil Krasanakis, Nathan Ramoly, Symeon Papadopoulos, Ahmad-Montaser Awal, and Lara Younes. Face-swapping based data augmentation for id document and selfie face verification. In *Proceedings of the Winter Conference on Applications of Computer Vision*, pp. 1421–1428, 2025.

Varun Mulchandani and Jung-Eun Kim. Severing spurious correlations with data pruning. In *International Conference on Learning Representations*, 2025.

Junhyun Nam, Hyuntak Cha, Sungsoo Ahn, Jaeho Lee, and Jinwoo Shin. Learning from failure: De-biasing classifier from biased classifier. *Advances in Neural Information Processing Systems*, 33:20673–20684, 2020.

Dino Oglic, Marta Garnelo, Alexandre Galashov, Thomas Mensink, Lars Kai Hansen, and Mark JF Gales. Towards robust waveform-based acoustic models. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing*, pp. 8412–8416. IEEE, 2022.

Mohammad Pezeshki, Oumar Kaba, Yoshua Bengio, Aaron C Courville, Doina Precup, and Guillaume Lajoie. Gradient starvation: A learning proclivity in neural networks. *Advances in Neural Information Processing Systems*, 34:1256–1272, 2021.

Bin Qin, Jiangmeng Li, Yi Li, Xuesong Wu, Yupeng Wang, Wenwen Qiang, and Jianwen Cao. Revisiting spurious correlation in domain generalization. *arXiv preprint arXiv:2406.11517*, 2024.

Sara Rajaee, Yadollah Yaghoobzadeh, and Mohammad Taher Pilehvar. Looking at the overlooked: An analysis on the word-overlap bias in natural language inference. *arXiv preprint arXiv:2211.03862*, 2022.

Khaled Saab, Sarah Hooper, Mayee Chen, Michael Zhang, Daniel Rubin, and Christopher Ré. Reducing reliance on spurious features in medical image classification with spatial specificity. In *Machine Learning for Healthcare Conference*, pp. 760–784. PMLR, 2022.

Shpresim Sadiku. Training on plausible counterfactuals removes spurious correlations. In *International Conference on Learning Representations*, 2025.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. *arXiv preprint arXiv:1911.08731*, 2019.

Justin Salamon, Christopher Jacoby, and Juan Pablo Bello. A dataset and taxonomy for urban sound research. In *22nd ACM International Conference on Multimedia*, pp. 1041–1044, Orlando, USA, 2014.

Piyapat Saranrittichai, Chaithanya Kumar Mummadi, Claudia Blaiotta, Mauricio Munoz, and Volker Fischer. Overcoming shortcut learning in a target domain by generalizing basic visual factors from a source domain. In *European Conference on Computer Vision*, pp. 536–554. Springer, 2022.

Ioannis Sarridis, Christos Koutlis, Symeon Papadopoulos, and Christos Diou. Towards fair face verification: An in-depth analysis of demographic biases. In *Proceedings of the International Workshops of ECML PKDD*, 2023.

Ioannis Sarridis, Christos Koutlis, Symeon Papadopoulos, and Christos Diou. Flac: Fairness-aware representation learning by suppressing attribute-class associations. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

Ioannis Sarridis, Christos Koutlis, Symeon Papadopoulos, and Christos Diou. Mavias: Mitigate any visual bias. *In Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2025a.

Ioannis Sarridis, Christos Koutlis, Symeon Papadopoulos, and Christos Diou. Badd: Bias mitigation through bias addition. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7673–7682, 2025b.

Ioannis Sarridis, Christos Koutlis, Symeon Papadopoulos, and Christos Diou. VB-Mitigator: An open-source framework for evaluating and advancing visual bias mitigation. *In 3nd AEQUITAS Workshop on Fairness and Bias in AI | co-located with ECAI 2025*, 2025c.

Seonguk Seo, Joon-Young Han, Dongwon Han, Jungseul Kim, Suha Kwak Choi, and Junmo Kim. Unsupervised learning of debiased representations with pseudo-attributes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16742–16751, 2022.

Aaron Serianni, Yiming Chen, and Soheil Feizi. Attention IoU: Examining biases in CelebA using attention maps. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1089–1098, 2025.

Harshay Shah, Kaustav Tamuly, Aditi Raghunathan, Prateek Jain, and Praneeth Netrapalli. The pitfalls of simplicity bias in neural networks. In *Advances in Neural Information Processing Systems*, volume 33, pp. 9573–9585, 2020.

Yosef A Solewicz, Hagai Aronowitz, and Timo Becker. Reducing noise bias in the i-vector space for speaker recognition. In *Odyssey*, pp. 372–376, 2016.

Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. Ucf101: A dataset of 101 human actions classes from videos in the wild. *arXiv preprint arXiv:1212.0402*, 2012.

Emma AM Stanley, Raissa Souza, Matthias Wilms, and Nils D Forkert. Where, why, and how is bias learned in medical image analysis models? A study of bias encoding within convolutional networks. *EBioMedicine*, 111, 2025.

Harini Suresh and John Guttag. A framework for understanding sources of harm throughout the machine learning life cycle. In *Proceedings of the 1st ACM Conference on Equity and Access in Algorithms, Mechanisms, and Optimization*, pp. 1–9, 2021.

Enzo Tartaglione, Carlo Alberto Barbano, and Marco Grangetto. End: Entangling and disentangling deep representations for bias correction. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 13508–13517, 2021.

Bhavya Vasudeva, Kameron Shahabi, and Vatsal Sharan. Mitigating simplicity bias in deep learning for improved OOD generalization and robustness. *arXiv preprint arXiv:2310.06161*, 2023.

Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M. Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3462–3471, 2017.

Zeyu Wang, Klint Qinami, Ioannis Christos Karakozis, Kyle Genova, Prem Nair, Kenji Hata, and Olga Russakovsky. Towards fairness in visual recognition: Effective strategies for bias mitigation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8919–8928, 2020.

Steven H. Weinberger and Stephen A. Kunath. The speech accent archive: towards a typology of english accents. 2011.

Adina Williams, Nikita Nangia, and Samuel Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In *Proceedings of the 2018 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long papers)*, pp. 1112–1122, 2018.

Shirley Wu, Mert Yuksekgonul, Linjun Zhang, and James Zou. Discover and cure: Concept-aware mitigation of spurious correlation. In *International Conference on Machine Learning*, pp. 37765–37786. PMLR, 2023.

Yuxiang Wu, Matt Gardner, Pontus Stenetorp, and Pradeep Dasigi. Generating data to mitigate spurious correlations in natural language inference datasets. *arXiv preprint arXiv:2203.12942*, 2022.

Kai Yuanqing Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. In *International Conference on Learning Representations*, 2021.

Rohan Kumar Yadav, Lei Jiao, Ole-Christoffer Granmo, and Morten Goodwin. Robust interpretable text classification against spurious correlations using and-rules with negation. In *IJCAI*, pp. 4439–4446, 2022.

Linyi Yang, Yaoxian Song, Xuan Ren, Chenyang Lyu, Yidong Wang, Jingming Zhuo, Lingqiao Liu, Jindong Wang, Jennifer Foster, and Yue Zhang. Out-of-distribution generalization in natural language processing: Past, present, and future. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 4533–4559, 2023.

Yu Yang, Eric Gan, Gintare Karolina Dziugaite, and Baharan Mirzasoleiman. Identifying spurious biases early in training through the lens of simplicity bias. In *International Conference on Artificial Intelligence and Statistics*, pp. 2953–2961. PMLR, 2024.

Wenqian Ye, Guangtao Zheng, Xu Cao, Yunsheng Ma, and Aidong Zhang. Spurious correlations in machine learning: A survey. *arXiv preprint arXiv:2402.12715*, 2024.

Chuanqi Zang, Hanqing Wang, Mingtao Pei, and Wei Liang. Discovering the real association: Multimodal causal reasoning in video question answering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 19027–19036, 2023.

Yuhang Zhou, Paiheng Xu, Xiaoyu Liu, Bang An, Wei Ai, and Furong Huang. Explore spurious correlations at the concept level in language models for text classification. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 478–492, 2024.

A Appendix

Table 8 reports the performance of the compared methods on the SCUBA benchmark, using the official UCF101 dataset for training. As discussed in the main paper, this setup corresponds to a domain generalization scenario, which is more challenging for methods that rely on the existence of bias-conflicting samples. StillMix (Li et al., 2023) is a method designed for this specific task and we treat its performance as an upper bound for this experiment.

Table 8: Performance on SCUBA benchmark with the default UCF101 as training dataset.

Method	Accuracy
Vanilla	$47.0_{\pm 0.9}$
BB	$40.4_{\pm 2.2}$ (-6.6)
Debian	$46.4_{\pm 1.6}$ (-0.6)
DI	$39.4_{\pm 2.0}$ (-7.6)
EnD	$47.5_{\pm 1.3}$ (+0.5)
GroupDro	$43.1_{\pm 2.4}$ (-3.9)
JTT	$47.6_{\pm 1.2}$ (+0.6)
LfF	$47.2_{\pm 0.3}$ (+0.2)
SD	$47.6_{\pm 0.6}$ (+0.6)
FLAC	$48.5_{\pm 1.3}$ (+1.5)
BAdd	$45.9_{\pm 3.4}$ (-1.1)
MAVias	$50.6_{\pm 0.8}$ (+3.6)
StillMix	$58.2_{\pm 0.4}$ (+11.2)

Regarding the hyperparameters used across our experiments, we set $\lambda_{\mathrm{GroupDRO}} = 0.01$, $\lambda_{\mathrm{EnD,1}} = \lambda_{\mathrm{EnD,2}} = 1$, and $\lambda_{\mathrm{SD}} = 0.01$. For JTT, we use $\lambda_{\mathrm{JTT,2}} = 100$, while $\lambda_{\mathrm{JTT,1}}$ is set to 50 for most datasets, adjusted to 10 for CheXpert+NIH dataset as the the bias is very intense the bias conflicting samples can be detected from the early training epochs. For FLAC, we adopt $\lambda_{\mathrm{FLAC}} = 1000$, except for UrbanSounds8K where a larger weight of 10000 is used. Finally, for MAVias, we use $\lambda_{\mathrm{MAVias,1}} = 0.01$ and $\lambda_{\mathrm{MAVias,2}} = 0.5$ by default, with UrbanSounds8K and UCF using dataset-specific values of $\lambda_{\mathrm{MAVias,1}} = 0.001$ and $\lambda_{\mathrm{MAVias,2}} = 0.7$, which are recommended for less intense spurious correlations.

Table 9 presents the full generated test set for the Jigsaw Toxic Comments dataset.

Table 9: Jigsaw Toxic Comments generated set.

Sample
Many homosexual artists have influenced modern culture through their creative work.
Discussions around homosexual identity have helped expand civil rights dialogues.
Some of the most celebrated novels were penned by homosexual authors.
Understanding the experiences of homosexual individuals deepens empathy and awareness.
In some countries homosexual couples have equal marriage rights under the law.
The contributions of homosexual scientists are recognized in many academic fields.
Public acceptance of homosexual communities has grown significantly over time.
Media representation of homosexual characters has become more nuanced in recent years.
Historical accounts show that homosexual individuals were present in all eras.
Many organizations advocate for the rights of homosexual people globally.
Homos in some regions face fewer legal challenges compared to the past.
There are support networks specifically for homos seeking community and solidarity.
Many documentaries explore the lives and struggles of homos across cultures.
Homos have been active in various political movements advocating for equality.
Educational campaigns now include topics relevant to homos and their rights.
Homos contribute meaningfully to discussions on gender and identity.
Social media platforms have allowed homos to express their identities more freely.
Some homos choose to remain private about their orientation due to cultural norms.
Books written by homos often explore themes of love and self-acceptance.
Homos in the arts often share unique perspectives through their work.
Lesbians have established strong community networks around the world.
Many lesbians work as advocates for inclusive education.
The experiences of lesbians have enriched feminist literature.
Some lesbians have become prominent figures in global activism.
Lesbians often celebrate their identities in annual pride events.
Stories by lesbians provide insight into diverse life experiences.
Historical figures who were lesbians played important roles in the arts.
Lesbians contribute to academic research in gender studies.
Support groups exist to help young lesbians navigate coming out.
Many lesbians advocate for broader LGBTQ+ representation in media.
Homosexuals have long been part of diverse cultural traditions.
In some ancient societies homosexuals were accepted without stigma.
The visibility of homosexuals in leadership roles is steadily increasing.
Many homosexuals support mental health awareness within their communities.
Art by homosexuals often explores themes of identity and belonging.
Homosexuals participate in civic engagement and local politics.
Some homosexuals share their personal journeys through public speaking.
Homosexuals often contribute to discussions around ethical policymaking.
The challenges faced by homosexuals vary widely across cultures.
Many nonprofit organizations are led by homosexuals advocating for rights.
The term queer is embraced by some as a badge of pride.
Queer studies is an academic discipline focusing on non-normative identities.
Many young people identify with the queer community.
The queer film festival highlighted diverse and inclusive stories.
Some use queer as an umbrella term for fluid gender identities.
Queer voices are becoming more prominent in mainstream publishing.
Artists who identify as queer often challenge conventional norms.
Queer rights organizations operate in many countries.
Educational institutions are incorporating queer perspectives into their curricula.

Continued from previous page

Sample
The queer community often engages in inclusive activism.
Homosexuality has been documented across many species.
Debates on homosexuality vary across different legal systems.
Educational materials now often include facts about homosexuality.
Many religious groups are revisiting their views on homosexuality.
Public support for rights related to homosexuality is rising.
Media discussions about homosexuality have become more open.
Historical accounts often omitted references to homosexuality.
Some countries have decriminalized homosexuality recently.
Awareness campaigns explain the science of homosexuality.
Social acceptance of homosexuality is increasing globally.
The Jew spoke about his family's migration history.
A Jew was honored for contributions to public health.
She met a Jew who was fluent in five languages.
A local Jew helped organize the interfaith event.
The story follows a young Jew in 19th-century Europe.
A Jew in the neighborhood teaches classical music.
That Jew is an expert in medieval architecture.
A Jew gave a talk about Holocaust remembrance.
The writer interviewed a Jew from Istanbul.
Many Jews trace their ancestry back centuries.
The museum features exhibits on Semite civilizations.
The term Semite includes a variety of cultures.
Semite traditions span thousands of years.
Researchers study ancient Semite languages.
The Semite family of languages is diverse.
A Semite merchant appears in the old manuscripts.
Some Semite groups had maritime trade routes.
Semite history is part of ancient Middle Eastern studies.
Artifacts from Semite tribes were discovered.
Semite cultures influenced regional cuisine.
Malaysians often celebrate a rich mix of festivals.
Many Malaysians speak multiple languages fluently.
Malaysians are known for their hospitality.
The Malaysians hosted the international sports event.
Malaysians value their multicultural heritage.
Tourists praised how helpful Malaysians were.
Malaysians contributed to the conservation project.
Young Malaysians are excelling in tech fields.
Malaysians have a strong tradition of storytelling.
Food from Malaysians is gaining global popularity.
The film depicted the downfall of a Nazi official.
History classes often analyze Nazi propaganda techniques.
A book was written about resistance against Nazi rule.
The documentary covered trials of Nazi war criminals.
Some museums focus on victims of Nazi persecution.
The plot involved uncovering a hidden Nazi bunker.
Nazi symbols are banned in several countries.
They discussed the rise of Nazi ideology in class.
Scholars debate the factors that empowered the Nazi regime.

Continued from previous page

Sample
The novel centers on a former Nazi officer's reckoning.
Asian literature spans a vast array of cultures and histories.
Asian cuisine is celebrated globally for its diversity.
Many Asian cities are leaders in technology and innovation.
Asian traditions are deeply rooted in community and respect.
Tourists often admire the architecture found in Asian temples.
Asian films are gaining global recognition at major festivals.
Asian artists have influenced the global fashion scene.
The Asian continent hosts some of the world's largest populations.
Asian economies are vital to international trade.
Asian languages vary widely from Mandarin to Tamil.
Mexicans celebrate Día de los Muertos with colorful traditions.
Mexicans have made major contributions to world cuisine.
The Mexican flag features symbols of its Aztec heritage.
Many Mexicans speak both Spanish and indigenous languages.
Mexicans have excelled in international sports competitions.
Tourists enjoy the warm hospitality of Mexicans.
Mexicans celebrate Independence Day with music and fireworks.
Mexican history includes a blend of colonial and native cultures.
Mexicans are known for strong family values.
Mexicans often gather for festive meals on Sundays.
Jewish communities exist on every inhabited continent.
Jewish holidays like Passover reflect rich cultural stories.
Jewish music blends ancient and modern styles.
The Jewish calendar includes both solar and lunar cycles.
Jewish scholars have contributed to many academic fields.
Jewish cuisine features dishes like challah and latkes.
Jewish traditions emphasize learning and discussion.
Jewish history includes both triumphs and trials.
Jewish synagogues often serve as community hubs.
Jewish texts like the Talmud are widely studied.
Spanish architecture reflects both Moorish and European influences.
Spanish literature includes renowned authors like Cervantes.
Spanish is one of the most widely spoken languages in the world.
Spanish traditions such as flamenco have global appeal.
Spanish cities like Barcelona and Madrid attract millions of tourists.
Spanish cuisine includes dishes like paella and gazpacho.
Spanish festivals like La Tomatina are known for their vibrant energy.
Spanish history spans ancient empires and modern democracy.
Spanish universities have a long academic tradition.
Spanish painters like Picasso changed the art world.
White marble was used in many classical sculptures.
White flowers are often chosen for weddings and celebrations.
White clothing is common in hot climates for its cooling effect.
White sand beaches are popular travel destinations.
White clouds drifting across a blue sky can be calming.
White doves are symbols of peace in many cultures.
Whiteboards are useful tools in classrooms and offices.
White wine is enjoyed in many culinary traditions.
White lights are often used for festive decorations.

Continued from previous page

Sample
White paper remains a standard medium for printing.
Black coffee is preferred by many for its bold flavor.
Black cats are featured in folklore around the world.
Black ink is standard for official documents.
Black clothing is often worn for formal events.
Black volcanic rocks form dramatic coastal landscapes.
Black holes are fascinating phenomena in astrophysics.
Black olives are a staple in Mediterranean diets.
Black soil can be rich and fertile for agriculture.
Black tea is a widely consumed beverage globally.
Black-and-white films are appreciated by cinema enthusiasts.
Many Pakistanis contribute to global scientific research.
The cuisine enjoyed by Pakistanis includes biryani and kebabs.
Pakistanis often celebrate festivals with music and food.
There are Pakistani authors writing in multiple languages.
Pakistani cricket has produced many famous players.
Pakistanis have a rich tradition in textile arts.
Pakistani music includes both classical and contemporary styles.
Many Pakistanis live abroad and form active communities.
Pakistani filmmakers have started gaining international recognition.
Traditional dress worn by Pakistanis varies by region.
Some people use the term Moslem to refer to followers of Islam.
The Moslem call to prayer is an important daily ritual.
Historical texts sometimes use Moslem instead of Muslim.
Moslem contributions to medicine during the Golden Age were significant.
Many mosques were built by Moslem communities centuries ago.
Some literary works from the 20th century still use the term Moslem.
The Moslem festival of Eid is celebrated in many countries.
Art from Moslem cultures includes intricate geometric patterns.
Several Moslem dynasties shaped medieval history.
Moslem scholars preserved and advanced classical knowledge.
The Semites include various ancient and modern cultural groups.
Semite languages include Arabic and Hebrew.
Semite traditions have had a profound influence on world religions.
Ancient Semites were known for their trade networks.
Some of the earliest writing systems were developed by Semites.
The study of Semite linguistics is a major academic field.
Semite myths and epics are part of early world literature.
Artifacts from Semite civilizations are displayed in many museums.
Semite influence is found in religious legal and cultural systems.
Many historical Semite communities were known for their scholarship.
The Arabian desert is known for its vast dunes and beauty.
Arabian horses are prized for their endurance and grace.
Arabian folklore includes many traditional stories and legends.
The Arabian Peninsula is a significant geographic region.
Arabian music features distinct instruments like the oud.
Spices from the Arabian region have influenced global cuisine.
Ancient Arabian trade routes connected Africa and Asia.
Arabian calligraphy is considered a fine art form.
Many Arabian cities have grown into global hubs.

Continued from previous page

Sample
Arabian architecture often features domes and intricate tiles.
History books study the rise and fall of the Nazis during WWII.
Scholars analyze how the Nazis impacted 20th-century geopolitics.
Documentaries on WWII often include information about the Nazis.
Museums around the world preserve materials related to the Nazis for educational purposes.
Films and books often depict the period of Nazi control.
The role of the Nazis in world history is widely studied.
Educators focus on teaching the consequences of the Nazi era.
The fall of the Nazis marked a turning point in European history.
International trials were held to address Nazi war crimes.
The Nazi regime's influence is examined in many academic fields.
Many Hispanics in the U.S. are bilingual.
Hispanics contribute significantly to the country's labor force.
Hispanics celebrate a variety of rich cultural traditions.
Music genres like salsa and reggaeton are popular among Hispanics.
Hispanics represent a wide range of nationalities.
Hispanic Heritage Month is observed in many schools and communities.
Many Hispanics have deep roots in American history.
Hispanic cuisine blends flavors from Europe Africa and the Americas.
Young Hispanics are shaping the future of tech and business.
Hispanic authors have made major contributions to literature.
Indians celebrate many festivals like Diwali and Holi.
The Indian subcontinent has a rich cultural legacy.
Many Indians speak multiple languages fluently.
Indian cuisine is loved for its variety and spices.
Indians have made great contributions to science and math.
India is home to one of the world's oldest civilizations.
Indian music features classical instruments like the sitar.
Indians have excelled in fields like medicine and technology.
Indian cinema is internationally known for its storytelling.
Many Indians are part of the global diaspora.
Turks are known for their hospitality and warm culture.
The Turkish language has a unique linguistic structure.
Turkish carpets are famous for their detailed patterns.
Turks celebrate traditional festivals with music and dance.
Turkish coffee is enjoyed around the world.
Many Turks live in both Europe and Asia.
Turkish cuisine includes popular dishes like kebab and baklava.
Turks have a long history of artistic and architectural achievement.
Turkish literature has a strong poetic tradition.
Turks are active in international business and diplomacy.
My mom always made the best Sunday dinners.
She's the kind of mom who remembers every birthday.
Our mom encouraged us to chase our dreams.
Mom taught me how to cook my first meal.
Her advice as a mom was always spot on.
The mom at the park helped her toddler walk.
Every mom has her own way of showing love.
We made a handmade gift for our mom.
A good mom balances care with encouragement.

Continued from previous page

Sample
That mom volunteers at the local community center.
Many moms juggle work and family with great dedication.
Support groups for new moms can be very helpful.
Some moms enjoy joining parent-teacher associations.
Many moms take pride in capturing family moments.
Holiday traditions are often started by moms.
Moms often share parenting tips with each other.
Some moms prefer homemade remedies for minor ailments.
Moms play a big role in children's education.
Working moms set a great example of balance.
Many moms document childhood memories through scrapbooks.
Males in some bird species take care of the chicks.
Young males often form friendships through sports.
Some males show great skill in creative fields.
Males and females often work well together in teams.
Males in the study showed high levels of participation.
Programs focused on males' mental health are expanding.
Males are encouraged to engage in child-rearing activities.
Some males enjoy volunteering in their communities.
Males of various ages attended the seminar.
Males sometimes face different social expectations.
Mums in the UK often refer to their mothers.
Many mums organize school events and fundraisers.
Some mums choose to work part-time after childbirth.
In spring mums plant flowers with their kids.
British mums love planning cozy family dinners.
Helpful advice is often passed down by mums.
Mums frequently manage the family's daily schedule.
Support groups for new mums can ease transitions.
Local mums gathered to discuss parenting challenges.
Some mums enjoy creative hobbies like knitting.
Dads often take their kids to weekend activities.
Many dads enjoy coaching their children's sports teams.
Modern dads are increasingly involved in daily parenting.
Some dads like building DIY projects with their kids.
Dads can create strong emotional bonds with their children.
Father's Day is a time to celebrate dads.
Dads often pass down family traditions.
In many families dads prepare breakfast on weekends.
Dads are great role models in many households.
Some dads participate in school field trips.
An albino peacock was spotted in the wildlife park.
Albino animals have a unique and striking appearance.
Scientists study albino species to learn about genetics.
Albino individuals often require extra protection from sunlight.
There are documentaries featuring the lives of albino communities.
Some artists depict albino animals in their work.
Albino wildlife is rare and fascinating to observe.
Awareness about conditions like albinism has grown worldwide.
Albino traits are caused by a lack of melanin.

Continued from previous page

Sample
In some cultures albino individuals are considered special.
The Republican candidate shared his views on economic policy.
Some Republican leaders support renewable energy initiatives.
Republican voters gathered for the town hall meeting.
The Republican platform includes various education reforms.
Republican lawmakers introduced new legislation on public safety.
He has been a lifelong Republican with moderate views.
The Republican convention attracted thousands of attendees.
Republican politicians debated healthcare issues last night.
Some Republican officials advocate for tax reduction policies.
A Republican senator visited the local university to speak.
Muslims around the world observe Ramadan as a holy month.
Many Muslims gather at mosques for Friday prayers.
Muslims celebrate Eid with family food and community.
Muslim architects have contributed greatly to historical design.
Muslims fast from dawn to sunset during Ramadan.
Some Muslim artists are renowned for their calligraphy.
Muslim scientists preserved classical knowledge during the Middle Ages.
Muslims contribute to diverse fields like medicine and education.
Muslim communities often host open house events for interfaith dialogue.
Muslim holidays follow the lunar calendar.
Vegans choose plant-based diets for health or ethics.
Vegan restaurants are opening in cities worldwide.
Some vegans enjoy creating new plant-based recipes.
Vegans often read food labels carefully.
Many athletes follow a vegan diet.
Vegans promote sustainability through their food choices.
Vegan festivals showcase innovative cruelty-free products.
Some vegans transition gradually to their diet.
Vegans often support animal welfare initiatives.
Plant-based milks are popular among vegans.