A MAX-AFFINE SPLINE PERSPECTIVE OF RECURRENT NEURAL NETWORKS

ABSTRACT

We develop a framework for understanding and improving recurrent neural networks (RNNs) using *max-affine spline operators* (MASO). We prove that RNNs using piecewise affine and convex nonlinearities can be written as a simple piecewise affine spline operator. The resulting representation provides several new perspectives for analyzing RNNs, three of which we study in this paper. First, we show that an RNN internally partitions the input space during training and that it builds up the partition through time. Second, we show that the affine parameter of an RNN corresponds to an input-specific template, from which we can interpret an RNN as performing a simple template matching (matched filtering) given the input. Third, by closely examining the MASO RNN formula, we prove that injecting Gaussian noise in the initial hidden state in RNNs corresponds to an explicit ℓ_2 regularization on the affine parameters, which links to exploding gradient issues and improves generalization. Extensive experiments on several datasets of various modalities demonstrate and validate each of the above analyses. In particular, using initial hidden states elevates simple RNNs to state-of-the-art performance on these datasets.

1 INTRODUCTION

Recurrent neural networks (RNNs) are a powerful class of models for processing sequential inputs and have been the basic building block for more advanced models that have found success in challenging problems, including classification (e.g., sentiment analysis (Socher et al., 2013; Li et al., 2016; Teng et al., 2016)), sequence generation (e.g., machine translation (Bahdanau et al., 2014)), speech recognition, and image captioning. Despite the successes, our understanding of how RNNs work still remains limited. An attractive theoretical result is the universal approximation property that states that an RNN can approximate an arbitrary function (Schäfer & Zimmermann, 2006; Siegelmann & Sontag, 1995; Hammer, 2000). These classical theoretical results have been obtained primarily from a dynamical system (Siegelmann & Sontag, 1995; Schäfer & Zimmermann, 2006) and measure theory (Hammer, 2000) perspective. These theories provide approximation error bounds but unfortunately limited guidance on applying RNNs and understanding their performance and behaviors in practice.

In this paper, we provide a new angle for understanding RNNs using *max-affine spline operators* (MASOs) (Magnani & Boyd, 2009; Hannah & Dunson, 2013) from approximation theory. MASOs are a piecewise affine approximation to arbitrary functions that provide a useful framework to study neural networks. For example, Balestriero & Baraniuk (2018); Balestriero & Baraniuk (2018a) have provided detailed analysis in the context of feedforward networks that highlights the practical value that spline operators bring to interpreting deep networks. Here, we go one step further and demonstrate the new insights and interpretations from the MASO perspective for RNNs. We will see that the input space partitioning and matched filtering views extend to RNNs and yield interesting insights into the inner workings of RNNs. Moreover, the MASO formulation of RNNs allows us to theoretically justify the use of noise in initial hidden state and improve RNN performance.

For concreteness, We focus our analysis on a specific class of simple RNNs (Elman, 1990) with piecewise affine and convex nonlinearities such as the ReLU (Glorot et al., 2011). RNNs with such nonlinearities have recently gained considerable attention due to their ability to combat the exploding gradient problem; with proper initialization (Le et al., 2015; Talathi & Vartak, 2016) and

Figure 1: Visualization of an RNN. A cell (purple) and a layer (red) are highlighted.

clever parametrization of the recurrent weight (Arjovsky et al., 2016; Wisdom et al., 2016; Jing et al., 2017; Hyland & Rätsch, 2017; Mhammedi et al., 2017; Helfrich et al., 2018), these RNNs achieve performance on par with more complex ones such as LSTMs. Below is a summary of our key contributions:

Contribution 1. We prove that an RNN with piecewise affine and convex nonlinearities can be rewritten as a composition of MASOs, making it a piecewise affine spline operator that has an elegant analytical form (Section 2).

Contribution 2. We leverage the partitioning of piecewise affine spline operators to analyze the input space partitioning that RNN implicitly performs. We show that RNN calculates a new, high dimensional representation of an input sequence that captures informative underlying characteristics of the input. We also provide a new perspective for RNN dynamics by visualizing the evolution of RNN VQ partitioning through time. (Section 3).

Contribution 3. We show the piecewise affine mapping in an RNN associated with a given input sequence is an input-dependent template, from which we can interpret the RNN as performing greedy template matching at every RNN cell. (Section 4).

Contribution 4. We rigorously prove that adding noise to the initial hidden state of an RNN corresponds to an explicit regularizer that links to exploding gradient and empirically show that such regularization improves RNN performance on four datasets of different modalities (Section 5).

1.1 BACKGROUND: RECURRENT NEURAL NETWORKS (RNNs)

A simple RNN unit (Elman, 1990) per layer ℓ and time step t, referred to as a "cell", performs the following recursive computation:

$$\boldsymbol{h}^{(\ell,t)} = \sigma\left(\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t)} + \boldsymbol{W}_r^{(\ell)}\boldsymbol{h}^{(\ell,t-1)} + \boldsymbol{b}^{(\ell)}\right), \tag{1}$$

where $\boldsymbol{h}^{(\ell,t)}$ is the hidden state at layer ℓ and time step t, $\boldsymbol{h}^{(0,t)} := \boldsymbol{x}^{(t)}$ which is the input sequence, σ is an activation function and $\boldsymbol{W}^{(\ell)}, \boldsymbol{W}_r^{(\ell)}$ and $\boldsymbol{b}^{(\ell)}$ are time-invariant parameters at layer ℓ. Unrolling the RNN through time gives an intuitive view of the RNN dynamics, which we visualize in Figure 1. The output of the overall RNN is usually an affine transformation of hidden state of the last layer L at each time step t:

$$\boldsymbol{z}^{(t)} = \boldsymbol{W}\boldsymbol{h}^{(L,t)} + \boldsymbol{b}. \tag{2}$$

In the special case when the RNN has one output at the end of processing the entire input sequence, the RNN output is an affine transformation of the hidden state at the last time step, i.e., $\boldsymbol{z}^{(T)} = \boldsymbol{W}\boldsymbol{h}^{(L,T)} + \boldsymbol{b}$.

1.2 BACKGROUND: MAX-AFFINE SPLINE OPERATORS (MASOs)

A max-affine spline operator (MASO) is piecewise affine and convex with respect to each output dimension $k = 1, \ldots, K$. It is defined as a parametric function $S : \mathbb{R}^D \to \mathbb{R}^K$ with parameters $\boldsymbol{A} \in \mathbb{R}^{K \times R \times D}$ and $\boldsymbol{B} \in \mathbb{R}^{K \times R}$. A MASO leverages K independent max-affine splines (Magnani & Boyd, 2009), each with R partition regions. Its output for each output dimension k is produced via

$$[\boldsymbol{y}]_k = [S(\boldsymbol{x})]_k = \max_{r=1,\ldots,R} \left\{ \langle [\boldsymbol{A}]_{k,r,\cdot}, \boldsymbol{x} \rangle + [\boldsymbol{B}]_{k,r} \right\}, \tag{3}$$

where $\boldsymbol{x} \in \mathbb{R}^D$ and $\boldsymbol{y} \in \mathbb{R}^K$ are dummy variables that respectively denote the input and output of the MASO S and $\langle \cdot, \cdot \rangle$ denotes inner product. The three subscripts of the "slope" parameter $[\boldsymbol{A}]_{k,r,d}$ correspond to output k, partition region r, and input signal index d. The two subscripts of the "bias" parameter $[\boldsymbol{B}]_{k,r}$ correspond to output k and partition region r.

We highlight two important and interrelated MASO properties relevant to the discussions throughout the paper. First, a MASO performs implicit input space partitioning, which is made explicit by rewriting Eq. 3 as

$$[\boldsymbol{y}]_k = \sum_{r=1}^{R} [Q]_{k,r} \left(\langle [\boldsymbol{A}]_{k,r,\cdot}, \, \boldsymbol{x} \rangle + [\boldsymbol{B}]_{k,r} \right), \tag{4}$$

where $Q \in \mathbb{R}^{K \times R}$ is a partition selection matrix[1] calculated as

$$[Q]_{k,r} = \mathbb{1}(r = [\boldsymbol{r}^*]_k), \quad \text{where} \;\; [\boldsymbol{r}^*]_k = \arg\max_{r=1,\cdots,R} \langle [\boldsymbol{A}]_{k,r,\cdot}, \, \boldsymbol{x} \rangle + [\boldsymbol{B}]_{k,r}. \tag{5}$$

Namely, Q contains K stacked one-hot row vectors, each of which selects the $[\boldsymbol{r}^*]_k^{\text{th}}$ partition of the input space that maximizes Eq. 4 for each output dimension k. As a consequence, knowing Q is equivalent to knowing the partition of an input $\boldsymbol{x}$ that the MASO implicitly computes. We will use this property in Section 3 to provide new insights into RNN dynamics.

Second, given the partition $\boldsymbol{r}^*$ that an input belongs to, as determined by Eq. 5, the output of MASO of each dimension k (Eq. 3) reduces to a simple affine transformation of the input:

$$[\boldsymbol{y}]_k = [A]_{k,\cdot} \boldsymbol{x} + [B]_k, \quad \text{where} \;\; [A]_{k,\cdot} = [\boldsymbol{A}]_{k,[\boldsymbol{r}^*]_k,\cdot} \;\; \text{and} \;\; [B]_{k,\cdot} = [\boldsymbol{B}]_{k,[\boldsymbol{r}^*]_k}.$$

Here, the selected affine parameters $A \in \mathbb{R}^{K \times D}$ and $B \in \mathbb{R}^K$ are specific to the input's partition region $[\boldsymbol{r}^*]_k$, which are simply the $[\boldsymbol{r}^*]_k^{\text{th}}$ slice and $[\boldsymbol{r}^*]_k^{\text{th}}$ column of $\boldsymbol{A}$ and $\boldsymbol{B}$, respectively, for each output dimension k. We emphasize that A and B are input-dependent: different input $\boldsymbol{x}$ gives rise to different A and B. [2] We will use this property in Section 4 to link RNNs to matched filterbanks.

2 RNNs as Piecewise Affine Spline Operators

We now leverage the MASO framework to rewrite, interpret and analyze RNNs. We focus on RNNs with piecewise affine and convex nonlinearities in order to derive rigorous analytical results. Our goal of this section is to show that an RNN has a simple, elegant analytical form when rewritten using MASOs. Analyses of RNNs with other nonlinearities are left for future work.

We first derive the MASO formula for an RNN cell (Eq. 1), then extend to one layer of time-unrolled RNN and finally to a multi-layer, time-unrolled RNN. Let $\boldsymbol{z}^{(\ell,t)} = \left[\boldsymbol{h}^{(\ell-1,t)^\top}, \boldsymbol{h}^{(\ell,t-1)^\top} \right]^\top$ be the input to an RNN cell which is the concatenation of the current input $\boldsymbol{h}^{(\ell-1,t)}$ and the previous hidden state $\boldsymbol{h}^{(\ell,t-1)}$. Then we have the following result, which is a straightforward extension of Prop. 4 in Balestriero & Baraniuk (2018).

Proposition 1. *An RNN cell of the form in Eq. 1 is a MASO defined as follows:*

$$\boldsymbol{h}^{(\ell,t)} = A^{(\ell,t)} \boldsymbol{z}^{(\ell,t)} + B^{(\ell,t)}, \tag{6}$$

where $A^{(\ell,t)} = A_\sigma^{(\ell,t)} [\boldsymbol{W}^{(\ell)}, \boldsymbol{W}_r^{(\ell)}]$ and $B^{(t)} = A_\sigma^{(\ell,t)} \boldsymbol{b}^{(\ell)}$ are the affine parameters and $A_\sigma^{(\ell,t)}$ is the affine parameter corresponding to the nonlinearity $\sigma(\cdot)$[3] that depend on the cell input $\boldsymbol{z}^{(\ell,t)}$.

We then proceed to derive the explicit affine formula of a time-unrolled RNN at layer ℓ. Let $\boldsymbol{h}^{(\ell-1)} = \left[\boldsymbol{h}^{(\ell-1,1)^\top}, \cdots, \boldsymbol{h}^{(\ell-1,T)^\top} \right]^\top$ be the entire input sequence to the RNN at layer ℓ and $\boldsymbol{h}^{(\ell)} = \left[\boldsymbol{h}^{(\ell,1)^\top}, \cdots, \boldsymbol{h}^{(\ell,T)^\top} \right]^\top$ be all the hidden states that are the outputs of the RNN at layer ℓ. With some algebra and simplification, we arrive at the following result.

---

[1] Prior work denotes the partition selection matrix as T. But in the context of RNNs, T usually denotes the length of the input sequence. Thus we denote this matrix as Q in this work to avoid notation conflicts.

[2] The standard notation for the affine parameters A and B in previous literature are $A[\boldsymbol{x}]$ and $B[\boldsymbol{x}]$, respectively, which highlight their input dependency. In this paper, we drop the input dependency when writing these affine parameters to simplify notation, and we use brackets to strictly denote indexing or concatenation.

[3] Recall that, in this work, $\sigma(\cdot)$ is assumed to be piecewise affine and convex.

Theorem 1. *The ℓ^{th} layer of an RNN is a piecewise affine spline operator defined as follows:*

$$
\begin{pmatrix} \boldsymbol{h}^{(\ell,T)} \\ \vdots \\ \boldsymbol{h}^{(\ell,1)} \end{pmatrix} = \underbrace{\begin{pmatrix} \mathcal{A}_{T:T}^{(\ell)} \cdots \mathcal{A}_{1:T}^{(\ell)} \\ \vdots \ddots \vdots \\ \boldsymbol{0} \cdots \mathcal{A}_{1:1}^{(\ell)} \end{pmatrix}}_{upper\ triangular} \underbrace{\begin{pmatrix} A_{\sigma}^{(\ell,T)} \boldsymbol{W}^{(\ell)} \cdots \boldsymbol{0} \\ \vdots \ddots \vdots \\ \boldsymbol{0} \cdots A_{\sigma}^{(\ell,1)} \boldsymbol{W}^{(\ell)} \end{pmatrix}}_{diagonal} \begin{pmatrix} \boldsymbol{h}^{(\ell-1,T)} \\ \vdots \\ \boldsymbol{h}^{(\ell-1,1)} \end{pmatrix} + \begin{pmatrix} \sum_{t=T}^{1} \mathcal{A}_{t:T}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:T}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \\ \vdots \\ \mathcal{A}_{1:1}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:1}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \end{pmatrix}
$$

$$
= A_{\text{RNN}}^{(\ell)} \boldsymbol{h}^{(\ell-1)} + B_{\text{RNN}}^{(\ell)} \,, \tag{7}
$$

where $\mathcal{A}_{t:T'}^{(\ell)} = \left(\prod_{s=T'}^{t+1} A_{\sigma}^{(\ell,s)} \boldsymbol{W}_r^{(\ell)} \right)$ for $t < T'$ and identity otherwise, [4] *$\boldsymbol{h}^{(\ell,0)}$ is the initial hidden state of the RNN at layer ℓ and $A_{\text{RNN}}^{(\ell)}$ and $B_{\text{RNN}}^{(\ell)}$ are affine parameters that depend on the layer input $\boldsymbol{h}^{(\ell-1)}$ and the initial hidden state $\boldsymbol{h}^{(\ell,0)}$.*

We present the proof for Thm. 1 in Appendix G. The key point here is that, by leveraging MASOs, we can represent the time-unrolled RNN as a simple affine transformation of the entire input sequence (Eq. 7). Note that this affine transformation changes depending on the partition region in which the input belongs to (recall Eqs. 4 and 5). Note also that the initial hidden state affects the layer output by influencing the affine parameters and contributing a bias term $A_{0:t}^{(\ell)} \boldsymbol{h}^{(\ell,0)}$ to the bias parameter $B_{\text{RNN}}^{(\ell)}$. We study the impact of the initial hidden state in more detail in Section 5.

We are now ready to generalize the above result to multi-layer RNNs. Let $\boldsymbol{x} = \left[\boldsymbol{x}^{(1)^\top}, \cdots, \boldsymbol{x}^{(T)^\top} \right]^\top$ be the input sequence to a multi-layer RNN and and $\boldsymbol{z} = \left[\boldsymbol{z}^{(1)^\top}, \cdots, \boldsymbol{z}^{(T)^\top} \right]^\top$ the output sequence. We state the following result for the overall mapping of a multi-layer RNN.

Theorem 2. *The output of an L-layer RNN is a piecewise affine spline operator defined as*

$$
\boldsymbol{z} = \mathcal{W} \left(\boldsymbol{h}^{(L)} \right) + \boldsymbol{b} = \mathcal{W} \left(A_{\text{RNN}} \boldsymbol{x} + B_{\text{RNN}} \right) + \boldsymbol{b} \,, \tag{8}
$$

where $A_{\text{RNN}} = \prod_{\ell=L}^{1} A_{\text{RNN}}^{(\ell)}$ and $B_{\text{RNN}} = \sum_{\ell=1}^{L} \left(\prod_{\ell'=\ell}^{L-1} A_{\text{RNN}}^{(\ell')} \right) B_{\text{RNN}}^{(\ell)}$ are the affine parameters of the L-layer RNN. $\mathcal{W}$ and $\boldsymbol{b}$ are parameters of the fully connected output layer where $\mathcal{W} = [\boldsymbol{W}, \boldsymbol{W}, \ldots, \boldsymbol{W}]$ when the RNN outputs at every time step and $\mathcal{W} = [\boldsymbol{W}, 0, \ldots, 0]$ when the RNN only outputs at the last time step.

Thm. 2 shows that, using MASOs, we have a simple, elegant analytical formula of a multi-layer RNN, and that the output is computed via locally very simple functions. This theorem is proved by recursively applying the proof for Thm. 1.

The above affine formula opens doors for many analyses of RNNs by examining the affine parameters because now the affine parameters are simply a matrix and a vector, and we can use many established matrix theories to shed light on RNNs through its affine formula. In the remaining sections, we provide three analyses that leverage RNNs' affine formula. First, we show that RNNs partition the input space and that they develop the partitions through time. Second, we analyze the forms of the slope affine parameter and link RNNs to matched filterbanks. Third, we study the impact of initial hidden state and justify the use of noise in initial hidden state. From now on, for simplicity, we will assume zero initial hidden state unless otherwise stated.

3 INTERNAL INPUT SPACE PARTITIONING IN RNNS

In this section, we show that RNNs implicitly partition the input sequences and do so through time, which provides a new perspective of the dynamics of RNNs. To see this, first recall that, for an RNN cell, the piecewise affine and convex nonlinearity partitions each dimension of the cell input $\boldsymbol{z}^{(\ell,t)}$ into R regions (for ReLU, $R = 2$). Knowing the state of the nonlinearity (which region r is activated) is thus equivalent to knowing the partition of a cell input. Then, for a multi-layer RNN composed of many RNN cells (recall Figure 1), the partition of an input sequence is retrieved by

---

[4] In our context, $\prod_{i=m}^{n} a_i := a_m \cdot a_{m-1} \cdots a_{n+1} \cdot a_n$ for $m > n$ as opposed to the empty product.

Figure 2: t-SNE visualization of the evolution of partitioning of input sequences that an RNN computes on the MNIST test set. Each color represents one class. We can see that RNN gradually develops and refines the partitioning through time.

accessing the collection of states of all nonlinearities. Since an RNN processes an input sequence one step at a time, the input space partition is gradually built up and refined through time.

As a consequence, the forward pass of an RNN becomes simply developing partitions of input sequences, which is easier to interpret than the seemingly convoluted RNN dynamics when not viewed from a MASO perspective. Visualizing the evolution of partitioning can be potentially beneficial for diagnosing RNNs and understanding their behaviors. As an example, we demonstrate the evolution of input space partitioning of a one-layer ReLU RNN trained on MNIST dataset, each image flattened into a 1-dimensional sequence. Details of model and experiments are in Appendix C. Since ReLU induces only 2 partition regions, we thus retrieve the partitioning of input images that the RNN computes by simply binarizing and concatenating all hidden states. Figure 2 visualizes how the partitioning of images in the MNIST test set develops through time using t-SNE . The figure clearly shows the evolution of the RNN input space partitioning, from hardly any separation to forming more clustered partitions through time. We can also know that the model is well behaved since the final partition shows that the images are well clustered based on their labels. Additional visualizations are available in Section D.

4   RNN AS A MATCHED FILTERBANK

In this section, we show that RNNs can be regarded as matched filterbanks and that the classification decision is informed via inner product between the "template" and the input sequence. To see this, we apply similar argument to that in Section 3. First, note that the slope parameter $A^{(\ell,t)}$ for each RNN cell is a "locally optimal template" because it maximizes each output dimension over R regions that the nonlinearity induces (recall Eqs. 3 and 6). Then, for a multi-layer RNN composed of many RNN cells, the overall "template" A_{RNN} corresponds to the composition of optimal templates obtained at each RNN cell and can be computed simply via $d\boldsymbol{z}/d\boldsymbol{x}$ (recall Eq. 8). Thus, we can view the RNN as a *matched filterbank* that computes the output by finding the maximum inner product between the overall template A_{RNN} and the input (Trees, 1992; 2013). The overall template is also known in the machine learning community as salience map; see Li et al. (2016) for an example of using saliency maps to visualize RNNs. Our new insight here is that a good template produces a larger inner product with the input *regardless of the visual quality of the template*, thus complementing prior work. A template matching view of RNNs thus provides a principled and motivated way to visualize and diagnose RNNs by examining the inner products between inputs and templates.

As an example, we train a one-layer ReLU RNN on the polarized Stanford Sentiment Treebank (SST-2) (Socher et al., 2013), which is a binary classification problem, and show in Figure 3 the templates corresponding to the correct and incorrect classes of an input where the correct class is negative sentiment. We see that the input has a much larger inner product with the template corresponding to the correct class (left plot) than that corresponding to the incorrect class (right plot), which informs us that the model correctly classifies this input. Additional experimental results are in Appendix E.

Figure 3: Templates corresponding to the correct and incorrect class of a negative sentiment input from the SST-2 dataset. Each column is the gradient corresponding to an input word. Quantitatively, we can see that the inner product between input and the correct class template (left) produces a bigger value than that between input and the incorrect class template (right), which demonstrate the matched filtering that an RNN performs.

5 IMPROVING RNNS VIA NOISY INITIAL HIDDEN STATE

In this section, we provide theoretical insights on the use of noise in an RNN's initial hidden state. Little is understood about setting the value for the initial hidden state except for Zimmermann et al. (2012)'s dynamical system argument. Therefore the initial hidden state is typically set to zero without much justification. Leveraging the MASO formula of RNNs, we prove that noisy initial hidden state is equivalent to explicit regularizing the affine parameter associated with the initial hidden state.

5.1 NOISY INITIAL HIDDEN STATE AS AN EXPLICIT REGULARIZER

Let $\widetilde{\mathcal{L}}$ be the loss with noise injected to the initial hidden state, N be the total number of data points, C be the total number of classes and define $\mathcal{A}_h := \mathcal{A}_{1:T} = \prod_{s=T}^{1} A_\sigma^{(\ell,s)} \boldsymbol{W}_r^{(\ell)}$ (Recall Eq. 7). We first state the theoretical result and then link it to the exploding gradient problem.

Theorem 3. *Let $\epsilon \sim \mathcal{N}(0, \sigma_\epsilon^2 \boldsymbol{I})$ be a Gaussian noise where σ_ϵ^2 is small. We have that*

$$\mathbb{E}_\epsilon \left[\widetilde{\mathcal{L}} \right] = \mathcal{L} + \mathcal{R}. \tag{9}$$

For cross entropy loss with softmax output, $\mathcal{R} = \frac{\sigma_\epsilon^2}{2N} \sum_{n=1}^{N} \left\| \mathrm{diag}\left(\left[\frac{d\widehat{y}_{ni}}{\partial z_{nj}} \right]_{i=j} \right) \mathcal{A}_h \right\|^2$ where $\widehat{y}_{ni}$ is the i^{th} dimension of the softmax output of the n^{th} data point and $i, j \in \{1, \cdots, C\}$ are the class indices . For mean squared error loss, $\mathcal{R} = \frac{\sigma_\epsilon^2}{2N} \sum_{n=1}^{N} \|\mathcal{A}_h\|^2$.

We prove this result for the cross entropy case in Appendix G.2. We can see that the noise standard deviation σ_ϵ controls the importance of the regularization term and recovers the standard case for $\sigma_\epsilon = 0$. Additionally, the regularizer does not depend on the accuracy of the classifier, which is a regularization scheme on the model itself (Wager et al., 2013).

Interpretation and Connections to Prior Work. Closely inspecting the form of $\mathcal{A}_h$, we see that this term is the gradient of the RNN output with respect to the initial hidden state. In fact, the gradient of the RNN output with respect to hidden state at any time step takes the following form:

$$\frac{\partial \mathcal{L}}{\partial \boldsymbol{h}^{(t)}} = \frac{\partial \mathcal{L}}{\partial \boldsymbol{z}} \frac{\partial \boldsymbol{z}}{\partial \boldsymbol{h}^{(T)}} \left(\prod_{s=t}^{T} \frac{\partial \boldsymbol{h}^{(T)}}{\partial \boldsymbol{h}^{(s)}} \right) = \frac{\partial \mathcal{L}}{\partial \boldsymbol{z}} \boldsymbol{W} \left(\prod_{s=t}^{T} \boldsymbol{D}_\sigma^{(s)} \boldsymbol{W}_r \right), \tag{10}$$

which is the basis of studying gradient exploding problems in RNNs, since it is clear that constraining this term will help limit the gradient in the backward pass. By introducing noise to the initial hidden state, we regularize the term with the most number of matrix multiplications in the gradient calculation of the recurrent weight. While whether regularizing this term amounts to regularizing every other term in the recurrent weight gradient calculation remains to be investigated, we provide empirical evidence that the regularization introduced by noisy initial hidden state already reduces the magnitude of the recurrent weight gradient and improves model performance. A detailed review of exploding gradient problem is provided in Appendix H.

Figure 4: Visualization of the regularization effect on the adding task ($T = 100$). **Top**: norm of $\mathbf{A}_h$ at every 100 iterations; **Middle**: norm of gradient of recurrent weight at every 100 iterations; **Bottom**: validation loss at every epoch. Each epoch contains 1000 iterations.

5.2 EXPERIMENTS

We provide extensive empirical evidence to advocate for the use of noisy initial hidden state and demonstrate that a properly chosen noise standard deviation σ_ϵ improves performance for all the datasets that we experiment on. Unless otherwise mentioned, we use identity-initialized ReLU RNNs of 128-dimensional hidden state (denoted as RNN) in all our experiments. We summarize in this section the gist of our experimental results; Details on models, datasets, experiment setup and additional results are available in Appendix C and F.

Visualizing the Regularization Effect of the Noisy Initial Hidden State. We first visualize the regularization effect when injecting noise into the initial hidden state on a simulation task of adding 2 sequences of length 100. This is a ternary classificaion problem with input $\boldsymbol{X} \in \mathbb{R}^{2 \times T}$ and target $y \in \{0, 1, 2\}$, $y = \sum_i \mathbb{1}_{\boldsymbol{X}_{2i}=1} \cdot \boldsymbol{X}_{1i}$. The first row of $\boldsymbol{X}$ contains randomly chosen 0's and 1's, and the second row of $\boldsymbol{X}$ contains 1's at 2 randomly chosen indices and 0's everywhere else. Note that prior work treats this task as a regression task (Arjovsky et al., 2016). Results for treating this task as a regression problem is provided in Appendix F.1, which are similar to those presented here.

In Fig. 4, we visualize the norm of $\mathcal{A}_h$, the norm of recurrent weight gradient $\|\frac{d\mathcal{L}}{d\boldsymbol{W}_r}\|$ and validation loss against training epochs for various noise standard deviations. The top two plots clearly demonstrate the regularization effect of noisy initial hidden state in regularize both $\mathcal{A}_h$ and norm of the recurrent weight gradient, since larger σ_ϵ reduces the magnitudes of both $\boldsymbol{A}_h$ and $\|\frac{d\mathcal{L}}{d\boldsymbol{W}_r}\|$. Notably, this regularization effect happens even when the regularizer does not directly regularize these two terms, which validates our intuition. The plot in the last row shows that setting a big σ_ϵ can negatively impact learning. This can be explained by having too much regularization effect with a σ_ϵ that is too large. This brings the question of choosing σ_ϵ in practice, which we investigate below.

Choosing the Noise Parameter. We examine the performance of different noise standard deviations using RMSprop and SGD with varying learning rates to provide practical guidance on choosing the noise parameter σ_ϵ. We perform experiments on MNIST dataset, each image flattened to a length 784 sequence (recall Section 3). Experimental results are included in Appendix F.2. Here, we report two interesting findings . First, for both optimizers, using noisy initial hidden state permits the use of higher learning rates that typically lead to exploding gradient when training RNNs without noisy initial hidden state. Second, RMSprop is more tolerable to the choice of σ_ϵ than SGD and achieves favorable accuracies even when σ_ϵ is very large (e.g., $\sigma_\epsilon = 5$). This might be due to the gradient smoothing that RMSprop performs during optimization. We therefore recommend the use of RMSprop with noisy initial hidden state to improve model performance.

We then use RMSprop to train ReLU RNNs of one or two layers and with or without noisy initial hidden state on MNIST, permuted MNIST[5] and SST-2 datasets. Table 1 shows the classification accuracies of these models as well as a few state-of-the-art results. These results further suggest

---
[5]We apply a fixed permutation to all MNIST images in this case.

Table 1: Classification accuracies on (permuted) MNIST and SST-2 test set for various models. We see that using noisy initial hidden state elevates simple RNNs to strong competitors of complex, state-of-the-art models.

Model	Dataset		
	MNIST	permuted MNIST	SST-2
RNN, 1 layer	0.970	0.891	0.871
RNN, 1 layer, noise	0.981	0.922	0.873
	($\sigma_\epsilon = 0.1$)	($\sigma_\epsilon = 0.01$)	($\sigma_\epsilon = 0.1$)
RNN, 2 layer	0.969	0.873	0.884
RNN, 2 layer, noise	**0.987**	0.927	0.888
	($\sigma_\epsilon = 0.5$)	($\sigma_\epsilon = 0.005$)	($\sigma_\epsilon = 0.005$)
GRU	0.986	0.888	0.881
LSTM	0.978	0.913	0.849
uRNN (Arjovsky et al., 2016)	0.951	0.914	-
scoRNN (Helfrich et al., 2018)	0.985	**0.966**	-
C-LSTM (Zhou et al., 2015)	-	-	0.878
Tree-LSTM (Tai et al., 2015)	-	-	0.88
Bi-LSTM+SWN-Lex (Teng et al., 2016)	-	-	**0.892**

the use of noisy initial hidden state in improving performance of ReLU RNN, elevating such simple model to a strong competitor of a number of more complex, state-of-the-art models.

Noisy Initial Hidden State in Complex Models. We perform exploratory experiments on the use of initial hidden state in more complex models. We first evaluate a one-layer gated recurrent unit (GRU) on MNIST and permuted MNIST datasets, with and without noisy initial hidden state. Although not as impressive as those for ReLU RNNs, results for GRUs show that we still obtain modestly improved accuracy with noisy initial hidden state, from 0.986 to 0.987 for MNIST and 0.888 to 0.904 for permuted MNIST.

We then evaluate a more complex, convolutional-recurrent model composed of 4 convolution layers followed by 2 GRU layers (Cakir et al., 2017) on the Bird Audio Detection Challenge dataset[6] which involves a binary classification problem to detect whether or not an audio recording contain bird songs; see Appendix C for details. We use the area under the curve (AUC) as the evaluation metric since the dataset is highly imbalanced. Results show a 3 points of percentage improvement in AUC when using noisy initial hidden state, from 90.5% to 93.4%. These encouraging preliminary results imply that, while more theoretical and empirical investigations are needed, noisy initial hidden state potentially improves more complex RNN models where the nonlinearities are no longer piecewise affine and convex. Further experimentation and theoretical development to understand and characterize using noise in initial hidden state in these elaborate models are left for future work.

6   CONCLUSIONS AND FUTURE WORK

We provide a novel perspective of RNNs using max-affine spline operators (MASOs). We prove that RNNs with piecewise affine and convex nonlinearities becomes piecewise affine spline operators that have a simple, elegant analytical form. Leveraging this formulation, we provide new insights and visualizations of RNNs from input space partitioning and matched filtering perspectives. Furthermore, we show that injecting noise in the initial hidden state of an RNN corresponds to an explicit regularization and improves generalization. Extensive empirical studies demonstrate the utility of the new insights and the effectiveness of noisy initial hidden state.

The MASO framework offers abundant promising research directions for understanding RNNs, two of which we briefly discuss here. First, generalizing MASOs to probabilistic cases (Balestriero & Baraniuk, 2018b), we can extend our study to RNNs with other nonlinearities such as GRUs and LSTMs. Second, we can apply random matrix theory from a recent result (Martin & Mahoney, 2018) to study the affine parameter A_{RNN}, e.g., the change of distribution of its singular values during training, to understand the training dynamics of RNNs.

---

[6]A list of benchmarks can be found in `https://goo.gl/TyaFrd`.

REFERENCES

M. Arjovsky, A. Shah, and Y. Bengio. Unitary evolution recurrent neural networks. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 48, pp. 1120–1128, Jun. 2016.

D. Bahdanau, K. Cho, and Y. Bengio. Neural Machine Translation by Jointly Learning to Align and Translate. *ArXiv e-prints*, 1409.0473, September 2014.

R. Balestriero and R. G. Baraniuk. Mad max: Affine spline insights into deep learning. *ArXiv e-prints*, 1805.06576, May 2018a.

R. Balestriero and R. G. Baraniuk. From Hard to Soft: Understanding Deep Network Nonlinearities via Vector Quantization and Statistical Inference. *ArXiv e-prints*, 1810.09274, Oct 2018b.

R. Balestriero and R. G. Baraniuk. A spline theory of deep networks. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 80, pp. 374–383, Jul 2018.

E. Cakir, S. Adavanne, G. Parascandolo, K. Drossos, and T. Virtanen. Convolutional recurrent neural networks for bird audio detection. In *Eur. Signal Process. Conf. (EUSIPCO)*, pp. 1744–1748, Aug 2017.

T. Cooijmans, N. Ballas, C. Laurent, C. Gulcehre, and A. C. Courville. Recurrent batch normalization. In *Proc. Int. Conf. Learn. Representations (ICLR)*, Apr. 2017.

A. Dieng, R. Ranganath, J. Altosaar, and D. Blei. Noisin: Unbiased regularization for recurrent neural networks. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 80, pp. 1252–1261, Jul. 2018.

J. L. Elman. Finding structure in time. *Cogn. Sci.*, 14:179–211, 1990.

X Glorot, Bordes A., and Y. Bengio. Deep sparse rectifier neural networks. In *Proc. Int. Conf. Artificial Intell. and Statist. (AISTATS)*, volume 15, pp. 315–323, Apr. 2011.

B. Hammer. On the approximation capability of recurrent neural networks. *Neurocomputing*, 31(1): 107–123, Mar. 2000.

L. A. Hannah and D. B. Dunson. Multivariate convex regression with adaptive partitioning. *J. Mach. Learn. Res.*, 14:3261–3294, 2013.

K. Helfrich, D. Willmott, and Q. Ye. Orthogonal recurrent neural networks with scaled Cayley transform. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 80, pp. 1969–1978, Jul. 2018.

M. Henaff, A. Szlam, and Y. LeCun. Recurrent orthogonal networks and long-memory tasks. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 48, pp. 2034–2042, Jun. 2016.

S. L. Hyland and G. Rätsch. Learning unitary operators with help from u (n). In *Proc. AAAI conf. Artificial Intell.*, pp. 2050–2058, Feb. 2017.

L. Jing, Y. Shen, T. Dubcek, J. Peurifoy, S. Skirlo, Y. LeCun, M. Tegmark, and M. Soljačić. Tunable efficient unitary neural networks (EUNN) and their application to RNNs. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 70, pp. 1733–1741, Aug. 2017.

C. Jose, M. Cisse, and F. Fleuret. Kronecker recurrent units. In *Proc. Int. Conf. Learn Representations (ICLR)*, Apr. 2018.

D Krueger, T. Maharaj, J. Kramar, M. Pezeshki, N. Ballas, N. R. Ke, A. Goyal, Y. Bengio, H. Larochelle, A. C. Courville, and C. Pal. Zoneout: Regularizing rnns by randomly preserving hidden activations. In *Proc. Int. Conf. Learn Representations (ICLR)*, Apr. 2017.

Q. V. Le, N. Jaitly, and G. E. Hinton. A Simple Way to Initialize Recurrent Networks of Rectified Linear Units. *ArXiv e-prints*, 1504.00941, Apr. 2015.

J. Li, X. Chen, E. Hovy, and D. Jurafsky. Visualizing and understanding neural models in NLP. In *Proc. Conf. North Amer. Chapter Assoc. Comput. Linguistics: Human Language Technol. (NAACL HLT)*, pp. 681–691, Jun. 2016.

L. Maaten and G. Hinton. Visualizing data using t-SNE. *J. Mach. Learn. Res.*, 9(Nov):2579–2605, 2008.

A. Magnani and S. P. Boyd. Convex piecewise-linear fitting. *Optimization Eng.*, 10(1):1–17, Mar. 2009.

C. H. Martin and M. W. Mahoney. Implicit Self-Regularization in Deep Neural Networks: Evidence from Random Matrix Theory and Implications for Learning. *ArXiv e-prints*, 1810.01075, Oct 2018.

Z. Mhammedi, A. Hellicar, A. Rahman, and J. Bailey. Efficient orthogonal parametrisation of recurrent neural networks using householder reflections. In *Proc. Int. Conf. Mach. Learn. (ICML)*, volume 70, pp. 2401–2409, Aug. 2017.

R. Pascanu, T. Mikolov, and Y. Bengio. On the difficulty of training recurrent neural networks. In *Proc. Int. Conf. Mach. Learn. (ICML)*, pp. 1310–1318, Jun. 2013.

J. Pennington, R. Socher, and C. D. Manning. Glove: Global vectors for word representation. In *Proc. Conf. Empirical Methods Natural Language Process. (EMNLP)*, pp. 1532–1543, Oct. 2014.

V. Pham, T. Bluche, C. Kermorvant, and J. Louradour. Dropout improves recurrent neural networks for handwriting recognition. In *Proc. Int. Conf. Frontiers Handwriting Recognition (ICFHR)*, pp. 285–290, Sept. 2014.

A. M. Schäfer and H. G. Zimmermann. Recurrent neural networks are universal approximators. In *Proc. Int. Conf. Artificial Neural Netw. (ICANN)*, pp. 632–640, Sept. 2006.

H. T. Siegelmann and E. D. Sontag. On the computational power of neural nets. *J. Comput. Syst. Sci.*, 50(1):132–150, Feb. 1995.

R. Socher, A. Perelygin, J. Wu, J. Chuang, C. D. Manning, A. Ng, and C. Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proc. Conf. Empirical Methods Natural Language Process. (EMNLP)*, pp. 1631–1642, Oct. 2013.

D. Stowell and M. D. Plumbley. An open dataset for research on audio field recording archives: Freefield1010. In *Proc. Audio Eng. Soc. 53rd Conf. Semantic Audio (AES53)*, pp. 1–7, 2014.

Kai Sheng Tai, Richard Socher, and Christopher D. Manning. Improved semantic representations from tree-structured long short-term memory networks. In *Proc. Annu. Meeting Assoc. Comput. Linguistics (ACL)*, pp. 1556–1566, Jul. 2015.

S. S. Talathi and A. Vartak. Improving performance of recurrent network network with relu nonlinearity. In *Proc. Int. Conf. Learn Representations (ICLR)*, Apr. 2016.

Z. Teng, D. T. Vo, and Y. Zhang. Context-sensitive lexicon features for neural sentiment analysis. In *Proc. Conf. Empirical Methods Natural Language Process. (EMNLP)*, pp. 1629–1638, Nov. 2016.

H. L. V. Trees. *Detection, Estimation, and Modulation Theory: Radar-Sonar Signal Processing and Gaussian Signals in Noise*. Krieger Publishing Co., Inc., 1992.

H. L. V. Trees. *Detection, estimation, and modulation theory, part I*. John Wiley & Sons, Inc.,, 2013.

S. Wager, S. Wang, and P. Liang. Dropout training as adaptive regularization. In *Proc. Advances Neural Inform. Process. Syst. (NIPS)*, volume 1, pp. 351–359, Dec. 2013.

S. Wisdom, T. Powers, J. R. Hershey, J. Le Roux, and L. Atlas. Full-capacity unitary recurrent neural networks. In *Proc. Advances Neural Inform. Process. Syst. (NIPS)*, Dec. 2016.

W. Zaremba, I. Sutskever, and O. Vinyals. Recurrent Neural Network Regularization. *ArXiv e-prints*, 1409.2329, September 2014.

C. Zhou, C. Sun, Z. Liu, and F. C. M. Lau. A C-LSTM Neural Network for Text Classification. *ArXiv e-prints*, 1511.08630, November 2015.

H. Zimmermann, C. Tietz, and R. Grothmann. Forecasting with recurrent neural networks: 12 tricks. *Neural Netw.: Tricks of the Trade*, pp. 687–707, 2012.

A Notation

L, ℓ	Total number of layers: $L \geq 0$; Index of the layer in an RNN: $\ell \in \{0, \cdots, L\}$
T, t	Total number of time steps: $T \geq 0$; Index of time steps of an RNN: $t \in \{0, \cdots, T\}$
C, c	Total number of output classes: $C > 0$; Index of the output class: $c \in \{1, \cdots, C\}$
N, n	total number of examples: $N \geq 1$;
Index of example in a dataset: $n \in \{1, \cdots, N\}$
$R^{(\ell)}$	Index of the partition region induced by the piecewise nonlinearity at layer l
$D^{(\ell)}$	Dimension of input to the RNN at layer ℓ
K, k	Total number of output dimensions of a MASO, $K \geq 0$; Index of MASO output dimension, $k \in \{1, \cdots, K\}$
Q	The partition region selection matrix
$\boldsymbol{x}^{(t)}$	t^{th} time step of a discrete time-serie, $\boldsymbol{x}^{(t)} \in \mathbb{R}^{D^{(0)}}$
$\boldsymbol{x}$	Concatenation of the whole length T time-serie: $\boldsymbol{x} = \left[\boldsymbol{x}^{(1)\top}, \cdots, \boldsymbol{x}^{(T)\top} \right]^{\top}, \boldsymbol{x} \in \mathbb{R}^{D^{(0)}T}$
$\boldsymbol{X}$	A dataset of N time-series: $\boldsymbol{X} = \{\boldsymbol{x}_n\}_1^N$
$\widehat{y}(\boldsymbol{x})$	Output/prediction associated with input $\boldsymbol{x}$
y_n	True label (target variable) associated with the nth time-serie example $\boldsymbol{x}_n$.
For classification $y_n \in \{1, \ldots, C\}$, $C > 1$; For regression $y_n \in \mathbb{R}^C, C \geq 1$
$\boldsymbol{h}^{(\ell,t)}$	Output of an RNN cell at layer ℓ and time step t;
Alternatively, input to an RNN cell at layer $\ell + 1$ and time step $t - 1$
$\boldsymbol{h}^{(\ell)}$	Concatenation of hidden state $\boldsymbol{h}^{(\ell,t)}$ of all time steps at layer ℓ: $\boldsymbol{h}^{(\ell)} = \left[\boldsymbol{h}^{(\ell,1)\top}, \cdots, \boldsymbol{x}^{(\ell,T)\top} \right]^{\top}, \boldsymbol{h}^{(\ell)} \in \mathbb{R}^{D^{(\ell)}T}$
$\boldsymbol{z}^{(\ell,t)}$	Concatenated input to an RNN cell at layer ℓ and time step t: $\boldsymbol{z}^{(\ell,t)} = \left[\boldsymbol{h}^{(\ell-1,t)\top}, \boldsymbol{h}^{(\ell,t-1)\top} \right]^{\top}, \boldsymbol{z}^{(\ell,t)} \in \mathbb{R}^{2D^{(\ell)}}$
$\boldsymbol{W}_r^{(\ell)}$	ℓth layer RNN weight associated with the input $\boldsymbol{h}^{(\ell,t-1)}$ from the previous time step: $\boldsymbol{W}_r^{(\ell)} \in \mathbb{R}^{D^{(\ell)} \times D^{(\ell)}}$
$\boldsymbol{W}^{(\ell)}$	ℓth layer RNN weight associated with the input $\boldsymbol{h}^{(\ell-1,t)}$ from the previous layer: $\boldsymbol{W}^{(\ell)} \in \mathbb{R}^{D^{(\ell)} \times D^{(\ell-1)}}$
$\boldsymbol{W}$	Weight of the last fully connected layer: $\boldsymbol{W} \in \mathbb{R}^{C \times D^{(L)}}$
$\boldsymbol{b}^{(\ell)}$	ℓth layer RNN bias: $\boldsymbol{b}^{(\ell)} \in \mathbb{R}^{D^{(\ell)}}$
$\boldsymbol{b}$	Bias of the last fully connected layer: $\boldsymbol{b} \in \mathbb{R}^C$
$\sigma(\cdot)$	Pointwise nonlinearity in an RNN (assumed to be piecewise affine and convex in this paper)
$\sigma_{\boldsymbol{\epsilon}}$	Standard deviation of noise injected into the initial hidden state $\boldsymbol{h}^{(\ell,0)} \, \forall \ell$
$A_\sigma^{(\ell,t)}$	MASO formula of the RNN activation $\sigma(\cdot)$ at layer ℓ and time step t: $A_\sigma \in \mathbb{R}^{D^\ell \times D^{(\ell)}}$
$A^{(\ell,t)}, B^{(\ell,t)}$	MASO parameters of an RNN at layer ℓ and time step t:
$A^{(\ell,t)} \in \mathbb{R}^{D^{(\ell)} \times R^{(\ell)} \times D^{(\ell-1)}}, B^{(\ell,t)} \in \mathbb{R}^{D^{(\ell)} \times R^{(\ell)}}$

B Datasets and Preprocessing Steps

Below we describe the datasets and explain the preprocessing steps for each dataset.

MNIST. The dataset[7] consists of 60k images in the training set and 10k images in the test set. We randomly select 10k images from the training set as validation set. We flatten each image to a 1-

---
[7] http://yann.lecun.com/exdb/mnist/

dimensional vector of size 784. Each image is also centered and normalized with mean of 0.1307 and standard deviation of 0.3081 (PyTorch default values). For

permuted MNIST. We apply a fixed permutation to all images in the MNIST dataset to obtain the permuted MNIST dataset.

SST-2. The dataset[8] consists of 6920, 872, 1821 sentences in the training, validation and test set, respectively. Total number of vocabulary is 17539, and average sentence length is 19.67. Each sentence is minimally processed into sequences of words and use a fixed-dimensional and trainable vector to represent each word. We initialize these vectors either randomly or using GloVe (Pennington et al., 2014). Due to the small size of the dataset, the phrases in each sentence that have semantic labels are also used as part of the training set in addition to the whole sentence during training. Dropout of 0.5 is applied to all experiments. Phrases are not used during validation and testing, i.e., we always use entire sentences during validation and testing.

Bird Audio Dataset. The dataset[9] consists of $7,000$ field recording signals of 10 sec. sampled at 44 kHz from the Freesound Stowell & Plumbley (2014) audio archive representing slightly less than 20 hours of audio signals. The audio waveforms are extracted from diverse scenes such as city, nature, train, voice, water, etc., some of which include bird songs. The labels regarding the bird detection task can be found in the file `freefield1010`. Performance is measured by Area Under Curve (AUC) due to the unbalanced distribution of the classes (3 for 1). We preprocess every audio clip by first using short-time Fourier transform (STFT) with 40ms and 50% overlapping Hamming window to obtain audio spectrum and then by extracting 40 log mel-band energy features. After preprocessing, each input is of dimension $D = 96$ and $T = 999$.

C EXPERIMENTAL SETUP

Experiment setup for various datasets is summarized in Table 2. Some of the experiments do not appear in the main text but in the appendix; we include setup for those experiments as well. A setting common to all experiments is that we use learning rate scheduler so that when validation loss plateaus for 5 consecutive epochs, we reduce the current learning rate by a factor of 0.7.

Setup of the experiments on influence of various noise standard deviation under different settings. We use σ_ϵ chosen in $\{0.001, 0.01, 0.1, 1, 5\}$ and learning rates in $\{1 \times 10^{-5}, 1 \times 10^{-4}, 1.5 \times 10^{-4}, 2 \times 10^{-4}\}$ for RMSprop and $\{1 \times 10^{-7}, 1 \times 10^{-6}, 1.25 \times 10^{-6}, 1.5 \times 10^{-6}\}$ plain SGD.

Setup of input space partitioning. For the results in the main text, we use tSNE visualization (Maaten & Hinton, 2008) with 2 dimensions and the default settings from the python `sklearn` package. Visualization is performed on the whole 10k test set images. For finding the nearest neighbors of examples in the SST-2 dataset, since the examples are of varying lengths, we constrain the distance comparison to within +/-10 words of the target sentence. When the sentence lengths are not the same, we simply pad the shorter ones to the longest one, then process it with RNN and finally calculate the distance as the L-2 distance of the VQ (i.e., concatenation of all hidden states) that RNN computes. We justify the comparison between examples of different lengths using padding by noting that batching examples, a common practice in modern NLP tasks, pad the examples to the longest example in the batch.

Setup of exploratory experiments. We experimented with one-layer GRU with 128 hidden unites for MNIST and permuted MNIST datasets. We use RMSprop optimizer with an initial learning rate of 0.001. We experimented with various noise standard deviations in the initial hidden state including $\{0.01, 0.05, 0.1, 0.5, 1, 5\}$. The optimal noise standard deviations that produce the results in the main text are $\sigma_\epsilon = \{0.01, 0.05, 0.01\}$, for MNIST, permuted MNIST and bird detection datasets, respectively.

D ADDITIONAL INPUT SPACE PARTITION VISUALIZATIONS

We provide ample additional visualizations to demonstrate the internal input space partitioning that an RNN performs. Here, the results are focused more on the properties of the final input space

---

[8] https://nlp.stanford.edu/sentiment/index.html
[9] http://machine-listening.eecs.qmul.ac.uk/bird-audio-detection-challenge/

Table 2: Various experiment setup. Curly brackets indicate more than one value is attempted for this experiment.

Settings	Dataset				
	Add task	MNIST	Permuted MNIST	SST-2	Bird detection
Type of RNN	ReLU RNN	ReLU RNN	ReLU RNN	ReLU RNN	GRU
#Layers	{1, 2}	{1, 2}	{1, 2}	{1, 2}	2
Input size	2	1	1	128	96
Hidden size	128	128	128	300	256
Output size	3	3	10	2	2
Initial Learning Rate	1e-4	1e-4	1e-4	1e-4	1e-4
Optimizer	RMSprop	{RMSprop, SGD}	RMSprop	Adam	Adam
Batch size	50	64	64	64	64
Epochs	100	200	200	100	50

partitioning, i.e., partition of the entire input sequence, instead of part of the input sequence. Several additional sets of experimental results are shown; the first three on MNIST and the last one on SST-2.

First, we visualize the nearest and farthest neighbors of several MNIST digits in Figure 5. The left column is the original image; The next five columns are the five nearest neighbors to the original image; The last five columns are five farthest neighbors. This figure shows that the images are well clustered.

Figure 5: Internal input space partitioning visualization for pixel-by-pixel (i.e., flattened to a 1-dimensional, length 784 vector) MNIST dataset using a trained ReLU RNN (one layer, 128-dimensional hidden state). Here, we visualize the nearest 5 and farthest 5 images of one selected image from each class. Leftmost column is the original image; the middle 5 images are the 5 nearest neighbors; the rightmost 5 images are the farthest neighbors.

Second, we visualize the nearest neighbors of a few wrongly classified images in Figure 6. This figure further shows the impressive input clustering that a simple RNN is able to achieve, in that even wrongly classified images have neighbors that are clearly of the same class as the wrongly classified ones.

Third, we show the two dimensional projection using tSNE of the raw pixel and VQ representations of each data points in the MNIST dataset and visualize them in Figure 7. We clearly see a more distinct clustering using VQ representation of the data than using the raw pixel representation. This comparison demonstrate the ability of the RNN to extract useful information from the raw representation of the data in the form of VQ.

Fourth, we perform a KNN classification with $k \in \{1, 2, 5, 10\}$ using 1) the RNN reparametrized data representation and 2) raw pixel data representation the MNIST test set to illustrate that the data reparametrized by the RNN has better clustering property than the original data representations. We use 80% of the test set to train the classifier and the rest for testing. The results are reported in Table 3. We see that the classification accuracies when using RNN reparametrized representations are significantly higher than those when using raw pixel representations. This result again shows the

Figure 6: Nearest neighbors of some wrongly classified MNIST images. We can see the superior input partitioning of the RNN since even images that are wrongly classified have neighbors that are the same class as those that are wrongly classified.

Figure 7: tSNE visualization of MNIST test set images using raw pixel representation (**left**) and RNN VQ representation (**right**). We see more distinct clusters in the tSNE plot using RNN VQ representation of images than the raw pixel representation, implying the useful information that RNN extracts in the form of VQ.

superior quality of the input space partitioning that RNN produces, and may suggest a new way to improve classification accuracy by just using the reparametrized data with a KNN classifier.

Table 3: K-nearest neighbor classification accuracies using data reparametrized by RNN compared to those using raw pixel data. We can see that classification accuracies using RNN reparametrized data are much higher than those using raw pixel data for all k's.

k	MNIST, raw pixels	MNIST, VQ
1	0.950	**0.977**
2	0.936	**0.974**
5	0.951	**0.977**
10	0.939	**0.975**

Finally, we visualize the 5 nearest and 5 farthest neighbors of a selected sentence from the SST-2 dataset to demonstrate that the partitioning effect on dataset of another modality. The results are shown in Figure 8. We can see that all sentences that are nearest neighbors are of similar sentiment to the target sentence, whereas all sentences that are farthest neighbors are of the opposite sentiment.

E ADDITIONAL TEMPLATE VISUALIZATIONS

We provide here more templates on images and texts in Figures 9 and 10. Notice here that although visually the templates may look similar or meaningless, they nevertheless have meaningful inner

Original text
It is a film that will have people walking out halfway through , will encourage others to stand up and applaud , and will , undoubtedly , leave both camps engaged in a ferocious debate for years to come . (**+**)

Nearest 2 neighbors	Farthest 2 neighbors
Well-written , nicely acted and beautifully shot and scored , the film works on several levels , openly questioning social mores while ensnaring the audience with its emotional pull . (**+**, 22.00)	Marries the amateurishness of The Blair Witch Project with the illogic of Series 7 : The Contenders to create a completely crass and forgettable movie . (**-**, 37.60)
A stunning piece of visual poetry that will , hopefully , be remembered as one of the most important stories to be told in Australia 's film history . (**+**, 22.23)	K-19 may not hold a lot of water as a submarine epic , but it holds even less when it turns into an elegiacally soggy Saving Private Ryanovich . (**-**, 37.42)
Cute , funny , heartwarming digitally animated feature film with plenty of slapstick humor for the kids , lots of in-jokes for the adults and heart enough for everyone . (**+**, 22.61)	This is a great subject for a movie , but Hollywood has squandered the opportunity , using it as a prop for warmed-over melodrama and the kind of choreographed mayhem that director John Woo has built his career on . (**-**, 37.24)
Though it is by no means his best work , Laissez-Passer is a distinguished and distinctive effort by a bona-fide master , a fascinating film replete with rewards to be had by all willing to make the effort to reap them . (**+**, 22.78)	Flotsam in the sea of moviemaking , not big enough for us to worry about it causing significant harm and not smelly enough to bother despising . (**-**, 37.15)
An absorbing trip into the minds and motivations of people under stress as well as a keen , unsentimental look at variations on the theme of motherhood . (**+**, 22.89)	If you 're not a prepubescent girl , you 'll be laughing at Britney Spears ' movie-starring debut whenever it does n't have you impatiently squinting at your watch . (**-**, 36.98)

Figure 8: Nearest and furthest neighbors of a postive movie review. The sentiment (+ or -) and the euclidean distance between the input and the neighbor vector quantizations are shown in parenthesis after each neighbor.

Figure 9: Templates of three selected MNIST images. The leftmost column are the original input image. The next ten images of each row are the ten templates of a particular input image corresponding to each class. For each template image, we show the class and the inner product of this template with the input. Text under the template of the true class of each input image is bolded.

product with the input. The class index of the template that produces the largest inner product with the input is typically the correct class, as can be seen in the two figures.

Figure 10: Additional template visualizations of an example from the SST-2 dataset. Each word in the sentence is marked as a tick label in the x axis. The values of inner products are marked below each template. The template that has the bigger inner product is the true class of the sentence. We see that the template corresponding to the correct class produces a significantly bigger inner product with the input than other templates.

F   ADDITIONAL EXPERIMENTAL RESULTS FOR NOISY INITIAL HIDDEN STATE

Here, we include additional experimental results for Section 5.

F.1   REGULARIZATION EFFECT FOR REGRESSION PROBLEM

We present the regularization effect on adding task formulated as a regression problem, following setup in Arjovsky et al. (2016). Result is shown in Figure 11. We see regularization effect similar to that presented in Figure 4, which demonstrates that the regularization effect does indeed happens for both classification and regression problems, as Thm. 3 suggests.

F.2   CHOOSING NOISE PARAMETER

Table 4 shows the classification accuracies under various settings. The discussion of the results is in Section 5.

G   PROOFS

We present detailed proofs for several results in the main text.

Figure 11: Various plots during training of add problem (T=100, regression). **Top**: norm of $\mathbf{A}_h$ at every 100 iterations; **Middle**: norm of gradient of recurrent weight at every 100 iterations; **Bottom**: validation loss at every epoch. Each epoch contains 1000 iterations.

Table 4: Classification accuracy for MNIST dataset under 2 different optimizers, various learning rates and different standard deviation σ_ϵ in the initial hidden state noise. Results suggest a RMSprop tolerates various choices of σ_ϵ while SGD works for smaller σ_ϵ.

	RMSprop				**SGD**			
σ_ϵ	1e-5	1e-4	1.5e-4	2e-4	1e-7	1e-6	1.25e-6	1.5e-6
0	0.960	0.973	0.114	0.114	**0.837**	0.879	0.870	0.098
0.001	**0.963**	0.974	0.978	0.970	0.835	0.895	0.913	0.875
0.01	0.962	0.980	0.978	0.976	0.834	**0.898**	**0.922**	**0.918**
0.1	0.955	0.976	**0.981**	0.976	0.803	0.833	0.913	0.908
1	0.956	0.977	0.980	0.976	0.520	0.640	0.901	0.098
5	0.952	**0.981**	0.973	**0.981**	0.471	0.098	0.098	0.098

G.1 PROOF OF THM. 1

To simplify notation, similar to the main text, in the proof here we drop the affine parameters' dependencies on the input, but keep in mind the input-dependency of these parameters.

We first derive the expression for a hidden state $\boldsymbol{h}^{(\ell,t)}$ at a given time step t and layer ℓ. Using Prop. 1, we start with unrolling the RNN cell of layer ℓ at time step t for two time steps to $t-2$ by recursively applying Eq. 1 as follows:

$$\boldsymbol{h}^{(\ell,t)} = \sigma\left(\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t)} + \boldsymbol{b}^{(\ell)} + \boldsymbol{W}_r^{(\ell)}\boldsymbol{h}^{(\ell,t-1)}\right) \tag{11}$$

$$= A_\sigma^{(\ell,t)}\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t)} + A_\sigma^{(t)}\boldsymbol{b}^{(\ell)} + A_\sigma^{(t)}\boldsymbol{W}_r^{(\ell)}\boldsymbol{h}^{(\ell,t-1)} \tag{12}$$

$$\begin{aligned}= A_\sigma^{(\ell,t)}\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t)} + A_\sigma^{(t)}\boldsymbol{b}^{(\ell)} \\ + A_\sigma^{(\ell,t)}\boldsymbol{W}_r^{(\ell)}\left(A_\sigma^{(\ell,t-1)}\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t-1)} + A_\sigma^{(\ell,t-1)}\boldsymbol{b}^{(\ell)} + A_\sigma^{(\ell,t-1)}\boldsymbol{W}_r^{(\ell)}\boldsymbol{h}^{(\ell,t-2)}\right)\end{aligned} \tag{13}$$

$$\begin{aligned}= \left(A_\sigma^{(\ell,t)}\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t)} + A_\sigma^{(\ell,t)}\boldsymbol{W}_r^{(\ell)}A_\sigma^{(\ell,t-1)}\boldsymbol{W}^{(\ell)}\boldsymbol{h}^{(\ell-1,t-1)}\right) \\ + \left(A_\sigma^{(\ell,t)} + A_\sigma^{(\ell,t)}\boldsymbol{W}_r^{(\ell)}A_\sigma^{(\ell,t-1)}\right)\boldsymbol{b}^{(\ell)} + A_\sigma^{(\ell,t)}\boldsymbol{W}_r^{(\ell)}A_\sigma^{(\ell,t-1)}\boldsymbol{W}_r^{(\ell)}\boldsymbol{h}^{(\ell,t-2)}.\end{aligned} \tag{14}$$

From Eq. 11 to Eq. 12, we use the result of Prop. 1. From Eq. 12 to Eq. 13, we expand the term that involves the hidden state $\boldsymbol{h}^{(\ell,t-1)}$ at the previous time step recursively using Eq. 12. From Eq. 13 to Eq. 14, we group terms and write them compactly.

Now define $\mathcal{A}_{s:t}^{(\ell,s)} := \prod_{k=t}^{s+1} A_{\sigma}^{(\ell,k)} \boldsymbol{W}_r^{(\ell)}$ for $s < t$ and $\mathcal{A}_{t:t}^{(\ell,t)} := \boldsymbol{I}$ where $\boldsymbol{I}$ is the identity matrix. Using this definition, we rewrite Eq. 14 and proceed with the unrolling to the initial time step as follows:

$$\boldsymbol{h}^{(\ell,t)} = \begin{pmatrix} \mathcal{A}_{t:t}^{(\ell)} & \mathcal{A}_{t-1:t}^{(\ell)} \end{pmatrix} \begin{pmatrix} A_{\sigma}^{(\ell,t)} \boldsymbol{W}^{(\ell)} \\ A_{\sigma}^{(\ell,t-1)} \boldsymbol{W}^{(\ell)} \end{pmatrix} \begin{pmatrix} \boldsymbol{h}^{(\ell-1,t)} \\ \boldsymbol{h}^{(\ell-1,t-1)} \end{pmatrix} + \sum_{s=t}^{t-1} \mathcal{A}_{s:t}^{(\ell)} B^{(\ell,s)} \tag{15}$$

$$\cdots$$

$$= \begin{pmatrix} \mathcal{A}_{t:t}^{(\ell)} & \cdots & \mathcal{A}_{1:t}^{(\ell)} \end{pmatrix} \begin{pmatrix} A_{\sigma}^{(\ell,t)} \boldsymbol{W}^{(\ell)} \\ \vdots \\ A_{\sigma}^{(\ell,1)} \boldsymbol{W}^{(\ell)} \end{pmatrix} \begin{pmatrix} \boldsymbol{h}^{(\ell-1,t)} \\ \vdots \\ \boldsymbol{h}^{(\ell-1,1)} \end{pmatrix} + \sum_{s=t}^{t-1} \mathcal{A}_{s:t}^{(\ell)} B^{(\ell,s)} + \mathcal{A}_{0:t}^{(\ell)} \boldsymbol{h}^{(\ell,0)} , \tag{16}$$

where $B^{(\ell,s)} = A_{\sigma}^{(\ell,s)} \boldsymbol{b}^{(\ell)}$ as defined in Prop. 1.

Repeat the above derivation for $t \in \{1, \cdots, T\}$ and stack $\boldsymbol{h}^{(\ell,t)}$ in decreasing time steps from top to bottom, we have:

$$\begin{pmatrix} \boldsymbol{h}^{(\ell,T)} \\ \vdots \\ \boldsymbol{h}^{(\ell,1)} \end{pmatrix} = \begin{pmatrix} \mathcal{A}_{T:T}^{(\ell)} \cdots \mathcal{A}_{1:T}^{(\ell)} \\ \vdots \ddots \vdots \\ \boldsymbol{0} \cdots \mathcal{A}_{1:1}^{(\ell)} \end{pmatrix} \begin{pmatrix} A_{\sigma}^{(\ell,T)} \boldsymbol{W}^{(\ell)} \cdots & \boldsymbol{0} \\ \vdots \ddots \vdots \\ \boldsymbol{0} \cdots A_{\sigma}^{(\ell,1)} \boldsymbol{W}^{(\ell)} \end{pmatrix} \begin{pmatrix} \boldsymbol{h}^{(\ell-1,T)} \\ \vdots \\ \boldsymbol{h}^{(\ell-1,1)} \end{pmatrix} + \begin{pmatrix} \sum_{t=T}^{1} \mathcal{A}_{t:T}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:T}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \\ \vdots \\ \mathcal{A}_{1:1}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:1}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \end{pmatrix}$$

$$= A_{\mathrm{RNN}}^{(\ell)} \boldsymbol{h}^{(\ell-1)} + B_{\mathrm{RNN}}^{(\ell)} , \tag{17}$$

where

$$A_{\mathrm{RNN}}^{(\ell)} = \begin{pmatrix} \mathcal{A}_{T:T}^{(\ell)} & \cdots & \mathcal{A}_{1:T}^{(\ell)} \\ \vdots & \ddots & \vdots \\ \boldsymbol{0} & \cdots & \mathcal{A}_{1:1}^{(\ell)} \end{pmatrix} , \; B_{\mathrm{RNN}}^{(\ell)} = \begin{pmatrix} \sum_{t=T}^{1} \mathcal{A}_{t:T}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:T}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \\ \vdots \\ \mathcal{A}_{1:1}^{(\ell)} B^{(\ell,t)} + \mathcal{A}_{0:1}^{(\ell)} \boldsymbol{h}^{(\ell,0)} \end{pmatrix} , \; \boldsymbol{h}^{(\ell-1)} = \begin{pmatrix} \boldsymbol{h}^{(\ell-1,T)} \\ \vdots \\ \boldsymbol{h}^{(\ell-1,1)} \end{pmatrix} ,$$

which concludes the proof.

Thm. 2 follows from the recursive application of the above arguments for each layer $\ell \in \{1, \cdots, L\}$.

G.2 PROOF OF THM. 3

We prove for the case of multi-class classification problem with softmax output. The proof for the case of regression problems easily follows.

Let $\boldsymbol{a}_i$ be the i^{th} row of the input-dependent affine parameter $\mathcal{A}_h$ where $\mathcal{A}_h := \mathcal{A}_{1:T} = \prod_{s=T}^{1} A_{\sigma}^{(\ell,s)} \boldsymbol{W}_r^{(\ell)}$ (recall Section 5.1), $\boldsymbol{x}_n = [\boldsymbol{x}_n^{(1)\top}, \cdots, \boldsymbol{x}_n^{(T)\top}]^\top$ be the concatenation of the n^{th} input sequence of length T and c be the index of the correct class. We assume the noise amplitude is small so that the input-dependent affine parameter $\mathcal{A}_h$, which also depends on $\boldsymbol{h}^{(0)}$, does not change when noise is injected into $\boldsymbol{h}^{(0)}$. Also, let $\boldsymbol{z}_n = f_{\mathrm{RNN}}(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})$ be the overall RNN computation that represents Eq. 8.

We first rewrite the cross entropy loss with noise injected hidden state $\widetilde{\mathcal{L}}_{\mathrm{CE}} = \mathcal{L}_{\mathrm{CE}} \left(\mathrm{softmax} \left(f_{\mathrm{RNN}} \left(\boldsymbol{x}_n, \boldsymbol{h}^{(0)} + \boldsymbol{\epsilon} \right) \right) \right)$ as follows:

$$
\begin{aligned}
\widetilde{\mathcal{L}}_{\mathrm{CE}} &= \frac{1}{N} \sum_{n=1}^{N} -\log \left(\mathrm{softmax} \left(f_{\mathrm{RNN}} \left(\boldsymbol{x}_n^{(1:T)}, \boldsymbol{h}^{(0)} + \boldsymbol{\epsilon} \right) \right) \right) \\
&= \frac{1}{N} \sum_{n=1}^{N} -\log \left(\frac{\exp(z_{nc} + \boldsymbol{a}_c \boldsymbol{\epsilon})}{\sum_{j=1}^{C} \exp(z_{nj} + \boldsymbol{a}_j \boldsymbol{\epsilon})} \right) \\
&= \frac{1}{N} \sum_{n=1}^{N} \left\{ -z_{nc} - \boldsymbol{a}_c \boldsymbol{\epsilon} + \log \left(\sum_{j=1}^{C} \exp(z_{nj} + \boldsymbol{a}_j \boldsymbol{\epsilon}) \right) \right\}.
\end{aligned}
\tag{18}
$$

Taking expectation of the $\widetilde{\mathcal{L}}$ with respect to the error distribution, we have

$$
\mathbb{E}[\widetilde{\mathcal{L}}_{\mathrm{CE}}] = \mathcal{L}_{\mathrm{CE}} + \mathcal{R},
\tag{19}
$$

where

$$
\mathcal{R} = \frac{1}{N} \sum_{n=1}^{N} \left\{ \mathbb{E} \left[\log \left(\sum_{j=1}^{C} \exp(z_{nj} + \boldsymbol{a}_j \boldsymbol{\epsilon}) \right) \right] - \log \left(\sum_{j=1}^{C} \exp(z_{nj}) \right) \right\}.
\tag{20}
$$

We note that similar forms of Eq. 20 have been previously derived by Wager et al. (2013).

We now simplify Eq. 20 using second order Taylor expansion on $\boldsymbol{h}^{(0)}$ of the summation inside the log function. Define function $u(\boldsymbol{x}_n^{(1:T)}, \boldsymbol{h}^{(0)}) := \log(\sum_j \exp(z_{nj})) = \log(\sum_j \exp(f(\boldsymbol{x}_n^{(1:T)}, \boldsymbol{h}^{(0)})))$. Then, we can approximate Eq. 20 as follows:

$$
\begin{aligned}
\mathcal{R} &\approx \frac{1}{N} \sum_{n=1}^{N} \left\{ \mathbb{E} \left[u(\boldsymbol{x}_n, \boldsymbol{h}^{(0)}) + \frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})}{d\boldsymbol{h}^{(0)}} \boldsymbol{\epsilon} + \frac{1}{2} \boldsymbol{\epsilon}^\top \frac{\partial u(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \boldsymbol{\epsilon} \right] - u(\boldsymbol{x}_n, \boldsymbol{h}^{(0)}) \right\} \\
&= \frac{1}{N} \sum_{n=1}^{N} \frac{1}{2} \mathbb{E} \left[\mathrm{Tr} \left(\boldsymbol{\epsilon}^\top \frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \boldsymbol{\epsilon} \right) \right] \\
&= \frac{1}{N} \sum_{n=1}^{N} \frac{1}{2} \mathrm{Tr} \left(\frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \mathbb{E} \left[\boldsymbol{\epsilon} \boldsymbol{\epsilon}^\top \right] \right) \\
&= \frac{1}{N} \sum_{n=1}^{N} \frac{\sigma_{\boldsymbol{\epsilon}}^2}{2} \mathrm{Tr} \left(\frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \right),
\end{aligned}
\tag{21}
$$

where $\frac{\partial u(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}}$ is the Hessian matrix:

$$
\begin{aligned}
\left[\frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \right]_{il} &= \frac{\partial u(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{\partial \boldsymbol{h}_i^{(0)} \partial \boldsymbol{h}_l^{(0)}} \\
&= \frac{\partial}{\partial \boldsymbol{h}_l^{(0)}} \underbrace{\frac{\exp(z_{ni})}{\sum_{j=1}^{C} \exp(z_{nj})}}_{\widehat{y}_{ni}} \boldsymbol{a}_i \\
&= \frac{\partial \widehat{y}_{ni}}{\partial z_{nl}} \frac{\partial z_{nl}}{\boldsymbol{h}_l^{(0)}} \boldsymbol{a}_i \\
&= \widehat{y}_{ni} (\mathbb{1}_{i=l} - \widehat{y}_{nl}) \langle \boldsymbol{a}_i, \boldsymbol{a}_l \rangle.
\end{aligned}
$$

Then, we can write the trace term in Eq. 21 as follows:

$$
\mathrm{Tr} \left(\frac{du(\boldsymbol{x}_n, \boldsymbol{h}^{(0)})^2}{d^2 \boldsymbol{h}^{(0)}} \right) = \left\| \mathrm{diag} \left(\left[\frac{\partial y_{ni}}{\partial z_{nl}} \right]_{i=l} \right) \mathcal{A}_h \right\|^2.
$$

As a result, using the above approximations, we can rewrite the loss with noisy initial state in Eq. 18 as:

$$\widetilde{\mathcal{L}}_{\text{CE}} = \mathcal{L}_{\text{CE}} + \frac{\sigma_\epsilon^2}{2N} \sum_{n=1}^{N} \left\| \text{diag}\left(\left[\frac{\partial y_{ni}}{\partial z_{nl}} \right]_{i=l} \right) \mathcal{A}_h \right\|^2. \tag{22}$$

We see that this regularizer term does not dependent on the correct class index c of each data points.

H PRIOR WORK ON THE EXPLODING GRADIENT IN RNNS

The problem of exploding gradients has been widely studied from different perspectives. First approaches have attempted to directly control the amplitude of the gradient through gradient clipping (Pascanu et al., 2013). A more model driven approach has leveraged the analytical formula of the gradient when using specific nonlinearities and topologies in order to develop parametrization of the recurrent weights. This has led to various unitary reparametrizations of the recurrent weight (Arjovsky et al., 2016; Wisdom et al., 2016; Helfrich et al., 2018; Henaff et al., 2016; Jing et al., 2017; Mhammedi et al., 2017; Hyland & Rätsch, 2017; Jose et al., 2018). A soft version of such parametrization lies in regularization of the DNNs. This includes dropout applied to either the output layer (Pham et al., 2014) or hidden state (Zaremba et al., 2014), noisin (Dieng et al., 2018), zoneout (Krueger et al., 2017) and recurrent batch normalization (Cooijmans et al., 2017). Lastly, identity initialization of ReLU RNNs has been studied in Le et al. (2015) and Talathi & Vartak (2016). Our results complements prior works in that simply injecting noise to the initial hidden state and without changing the RNN structure also relieves the exploding gradient problem by regularization the potentially largest term in the recurrent weight gradient.