CAPTURING HUMAN CATEGORY REPRESENTATIONS BY SAMPLING IN DEEP FEATURE SPACES

ABSTRACT

Understanding how people represent categories is a core problem in cognitive science, with the flexibility of human learning remaining a gold standard to which modern artificial intelligence and machine learning aspires. Decades of psychological research have yielded a variety of formal theories of categories, yet validating these theories with naturalistic stimuli remains a challenge. The problem is that human category representations cannot be directly observed and running informative experiments with naturalistic stimuli such as images requires having a reasonable representation of these images. Deep neural networks have recently been successful in a range of computer vision tasks, and provide a way to represent the features of images. In this paper, we outline a method for estimating the structure of human categories that draws on ideas from both cognitive science and machine learning, blending human-based algorithms with state-of-the-art deep representation learners. We provide qualitative and quantitative results as a proof of concept for the feasibility of the method. Samples drawn from human distributions rival the quality of current state-of-the-art generative models and outperform alternative methods for estimating the structure of human categories.

1 INTRODUCTION

Categorization (or classification) is a central problem in cognitive science (Cohen & Lefebvre, 2005), artificial intelligence, and machine learning (Duda et al., 1973). In its most general description, it concerns why and how we divide the world into discrete units (and various levels of abstraction), and what we do with this information. The most challenging problem in the study of human categorization is that there is no way to directly examine the content of mental category representations. While laboratory methods have been developed for estimating this content from human behavior, they rely on small artificial stimulus sets with hand-specified or low-dimensional feature descriptions. However, the study of categorization as an intelligent process is principally motivated by the robust performance we observe in humans in complex ecological settings.

One of the challenges of applying psychological methods to naturalistic stimuli such as images is finding a way to represent these stimuli. Recent work in machine learning has shown that deep learning models, such as convolutional neural networks, perform well on a range of computer vision tasks (LeCun et al., 2015). The features discovered by these models provide a way to represent complex images. This approach suggests it may be possible to express human category structure using these features, an idea supported by recent work in cognitive science (Lake et al., 2015; Peterson et al., 2016).

Ideally, we would want to combine state-of-the-art deep learning models with experimental methods for estimating the structure of human categories with as few assumptions as possible. Furthermore, we would like a method that inherently avoids the problem of dataset bias. In what follows, we propose a method that uses a human in the loop and allows for the direct estimation of arbitrary distributions over complex feature spaces, adapting a framework that can exploit advances in deep architectures and computing power to increasingly capture and sharpen the precise structure of human category representations. We see such information as crucial in eventually providing an ecological theory of intelligent categorization behavior, as well as providing a ground-truth benchmark for which to guide and inspire future work in machine learning.

2 BACKGROUND

2.1 ESTIMATING THE STRUCTURE OF HUMAN CATEGORIES

Methods for estimating human internal category templates have existed for some time. In psychophysics, the most popular and well-understood method is known as *classification images* (Ahumada, 1996). In this experimental procedure, the human is shown stimuli from two classes A and B, both augmented by white noise, and asked to indicate the correct label. On most trials, the participant will select the exemplar generated from the category in question. However, if the added white noise significantly perturbs features of the image important to make that discrimination, they may fail. Exploiting this, we can estimate the decision boundary from a number of these trials using the the simple formula:

$$(\mu_{AA} + \mu_{BA}) - (\mu_{AB} + \mu_{BB}), \tag{1}$$

where μ_{XY} is the average of the stimuli across trials where the correct class is X but the observer chooses Y.

Vondrick et al. (2015) used a variation on classification images using invertible deep feature spaces. In order to avoid dataset bias introduced through perturbing real class exemplars, white noise in the feature space was used to generate stimuli. In this special case, category templates reduce to $\mu_A - \mu_B$. In their experiment, participants on each trial were asked to select which of two images (inverted from feature noise) most resembled a particular category. Since the feature vectors were random, thousands of images could be pre-inverted offline using methods that require access to large data sets. This early inversion method was applied to mean feature vectors for thousands of positive choices in the experiments and yielded qualitatively decipherable category template images, as well as better machine classification decision boundaries that were regularized by human bias. Under the assumption that human category distributions are Gaussian with equal variance, this method yields the vector that aligns with the line between means, although a massive amount of pairs of random vectors (trials) are required.

Greene et al. (2014) conducted similar experiments in which a low-dimensional multi-scale gabor PCA basis was used to represent black and white images of scenes. People indicated which of two images was more similar to a seen image or a mental image of a scene. These judgments were used in an online genetic algorithm to lead participants to converge to their mental image. This method allowed for fast, direct estimation of mental templates, although it lacks even the few theoretical guarantees of Vondrick et al. (2015), and yields only a single meaningful image.

Finally, an alternative to classification images called Markov Chain Monte Carlo with People (MCMCP; Sanborn and Griffiths, 2007) provides a way for humans to behave as valid acceptance functions in the Metropolis-Hastings algorithm, exploiting the fact that a well-known model of human choice behavior corresponds exactly to a valid acceptance function called the Barker function (see equation in Figure 1). On the first trial, an arbitrary stimulus is drawn from this parameter space and compared to another proposed stimulus likely to be nearby in the parameter space, and the participant makes a forced choice of the better exemplar of the category. If the initial stimulus is chosen, it will remain as the current state of the Markov chain and a new proposal will be compared to it on the next trial. If the newly proposed stimulus is chosen, it will be taken as the next state of the chain and compared to another proposed animal on the next trial. MCMCP has been successfully employed to capture a number of different categories (Sanborn & Griffiths, 2007; Martin et al., 2012), but while these spaces are higher-dimensional than previous laboratory experiments, they are still relatively small and artificial compared to real images. Unlike classification images, this method makes no assumptions about the structure of the category distributions, and so can estimate means, variances, and higher order moments, and so we take it as a starting point for this paper, explained in the next section.

2.2 DEEP NEURAL NETWORKS FOR IMAGES

Generally, deep networks are neural networks with a large number of hidden layers between their input and output. In the field of computer vision, the most common deep network is the convolutional neural network (CNN; LeCun et al., 1989). CNNs get their name from the use of convolutional layers, which learn a set of image filters that produce feature maps of spatially-organized

Figure 1: Deep MCMCP. A current state z and proposal z^* are fed to a pretrained deep image generator network (left). The corresponding images x and x^* are presented to human raters in the MCMC loop who chose between the two in accordance with the Barker acceptance function (right).

inputs like images. Deep image classifiers like AlexNet (Krizhevsky et al., 2012) are excellent for learning category representations, but are difficult to interpret, especially in how they relate to human categorization behavior. Generative Adversarial Networks (GANs; Goodfellow et al., 2014) and Variational Autoencoders (VAEs; Kingma & Welling, 2014) provide a generative approach to understanding image categories. In particular, these generative models provide an opportunity to examine how inference over a set of images and categories is performed. Generative models frame their approach theoretically on the following Bayesian decomposition of image-label joint density $p(z, x) = p(z)p(x|z)$, where z and x are random variables that represent a natural image distribution and its feature representation. $p(z)$ therefore represents the distribution of natural images, and $p(x|z)$ is the distribution of features vectors given an image. In other words, $p(z)$ and $p(x|z)$ together produce a high dimensional constraint on image generation. This allows for easy visualization of the latent space learned, a property we will exploit presently.

3 MARKOV CHAIN MONTE CARLO IN DEEP FEATURE SPACES

A schematic of our method is shown in Figure 1. We employ an MCMCP algorithm to map categories in deep feature spaces and invert these representations in real time using a deep generator. Any generative model or inversion network can be used here. Human choice behavior mimics the Barker acceptance function, and the proposal distribution can be varied to obtain the best exploration strategies. The resulting distributions both derive human category boundaries and can be sampled from to create new images, yielding new human-like generative image models.

More specifically, popular deep generative networks such as GANs and VAEs learn a probability distribution $p(z)$ over some latent variable z, from which the objective of the network ensures of the mapping (generator or decoder) M that $p(f(z; M)) = p(x)$, where $p(x)$ is the distribution over pixels in the dataset, f is the family of deterministic functions s.t. $f : M \times z \rightarrow x$. If we assume that human psychological space y results from some invertible transformation T of x, then correspondingly $p(g(y; T^{-1}) = p(x)$ where g is the family of functions s.t. $g : T^{-1} \times y \rightarrow x$. Since people in our experiments see only actual images x, interpreted as y, the judgments they make are related to the deep latent space through the following equation:

$$p(f(z; M)) = p(x) = p(g(y; T^{-1})). \tag{2}$$

This assumes that humans approximate $p(x)$ analogously to an unsupervised learner, however, even if T is a more specific feature representation supervised by classification pressure in the environment, we can assume information is only lost and not added, so that our deep generative models, if successful in their goal, will ultimately encode this information as a subset. Further, the equation above entails that $p(y)$ need not be identical to $p(z)$, and M need not equal T^{-1}. However, for the practical sake of convergence using human subjects, we would prefer that psychological space y be similar to the deep latent space z (we hope they contain the same relevant featural content for most images). While this assumption is hard to verify beyond face validity at this time, recent work suggests that some deep features spaces can be linearly transformed to approximate human psycho-

Figure 2: Left: Fisher Linear Discriminant projections of all four chains for each of the four face categories. Right: Individual chain means and overall category means.

logical space (Peterson et al., 2016), and so we assume the deep latent space is relevant enough to human feature representations to act as surrogate.

There are several theoretical advantages to our method over previous efforts. First, MCMCP can capture arbitrary distributions, so it is not as sensitive the structure of the underlying low-dimensional feature space, and should provide better category boundaries than classification images when required. This is important when using various deep features spaces that were learned with different constraints. MCMC inherently spends less time in low probability regions, so it should in theory also waste less trials. Since the images are generated online and as a function of the participant, there is no data set or sampling bias, and auto-correlation can be addressed by removing temporally adjacent samples from the chain.

4   HUMAN EXPERIMENTS

For our experiments, we explored two image generator networks trained on various datasets. Since even relatively low-dimensional deep image embeddings are large compared to controlled laboratory stimulus parameter spaces, we use a hybrid proposal distribution in which a Gaussian with a low variance is used with probability P and a Gaussian with a high variance is used with probability $1 - P$. This allows participants to both refine and escape nearby modes, but is simple enough to avoid excessive experimental piloting that more advanced proposal methods often require.

Participants in all experiments completed exactly 64 trials (image comparisons), collectively taking about 5 minutes, containing segments of several chains for multiple categories. The order of the categories and chains within those categories were always interleaved. All experiments were conducted on Amazon Mechanical Turk.

5   A FIRST PROOF OF CONCEPT: FACE CATEGORIES

5.1   METHODS

We first test our method using DCGAN (Radford et al., 2015) trained on the Asian Faces Dataset. We chose this dataset because it requires a deep architecture to produce reasonable samples (unlike MNIST for example), yet it is constrained enough to test-drive our method using a relatively simple latent space. Four chains for each of four categories (male, female, happy, and sad) were used. Proposals were generated from an isometric Gaussian with an SD of 0.25 50% of the time, and 2 otherwise. In addition, we conducted a baseline in which two new initial state proposals were drawn on every trial, and were independent of previous trials (classification images). The final dataset contained 50 subjects and over 3, 200 trials (samples) in total for all chains. The baseline classification images (CI) dataset contained the same number of trials and subjects.

Figure 3: Human two-alternative forced-choice tasks reveal a strong preference for MCMCP means as representations of a category, even with only half the trials.

5.2 RESULTS

MCMCP chains are visualized using Fisher Linear Discriminant Analysis in Figure 2, along with the resulting averages for each chain and each category. Chain means within a category show interesting variation, yet converge to very similar regions in the latent space. Interestingly, it appears that female faces are viewed as more happy (although significantly less than the happy category means), whereas male faces are more neutral. This effect that could be due to dataset used for training, especially if the women pictured smile more in photos. What's more important however is the apparent improvement over the baseline CI means shown in the right-most column of Figure 2. MCMCP means appear to have converged quickly, whereas CI means only show a moderate resemblance to their corresponding category. All four CI means appear closer to a mean face, which is what one would expect from averages of noise. We validate this improvement with a human experiment in which 30 participants made forced choices between CI and MCMCP means. The results are reported in Figure 3. MCMCP means are consistently highly preferred as representations of each category as compared to CI. This remained true even when an additional 50 participants (total of 100) were run on the CI task, obtaining twice as many image comparison trials as MCMCP.

6 LARGER NETWORKS & LARGER SPACES

The results in the previous section show that reasonable category templates can be obtained using our method, yet the complexity of the stimulus space used does not rival that of large object classification networks. In this section, we tackle a more challenging (and interesting) form of the problem. To do this, we employ a bidirectional generative adversarial network (BiGAN; Donahue et al., 2016) trained on the entire 1.2 million-image ilsvrc12 dataset (64×64 center-cropped). We also simultaneously learn a corresponding inference network, which regularizes the rest of the network and produces unconditional samples competitive with the state-of-the-art. This also allows for the later possibility of comparing human distributions with other networks as well as assessing machine classification performance with new images based on the granular human biases captured.

6.1 METHODS

Our generator network was trained given uniform rather than Gaussian noise, which allows us to guarantee participants cannot get lost in extremely improbable regions. Additionally, we avoid proposing states outside of this hypercube by forcing z to wrap around (proposals that travel outside of z are injected back in from the opposite direction by the amount originally exceeded). In particular we run our MCMC chains through an unbounded state space by redefining each bounded dimension z_k as

$$z_k' = \begin{cases} -sgn(z_k) \times [1 - (z_k - \lfloor z_k \rfloor)], & \text{if } |z| > 1 \\ z_k, & \text{otherwise.} \end{cases} \tag{3}$$

Proposals were generated from an isometric Gaussian with an SD of 0.1 60% of the time, and 0.7 otherwise.

Figure 4: Most interpretable mixture component means (modes) taken from the top 40

We use this network to obtain large chains for two groups of five categories. Group1 included *bottle*, *car*, *fire hydrant*, and *person*, *television*, following Vondrick et al. (2015). Group2 included *bird*, *body of water*, *fish*, *flower*, and *landscape*. Each chain was approximately $1,040$ states long, and four of these chains were used for each category (approximately $4,160$). In total, across both groups of categories, we obtained exactly $41,600$ samples from 650 participants.

To demonstrate the efficiency and flexibility of our method compared to alternatives, we obtained an equivalent number of trials for all categories using the variant of classification images introduced in Vondrick et al. (2015), with the exception that we used our BiGAN generator instead of offline inversion previously used. This also serves as an important baseline (since it estimates the simplest possible template) against which to quantitatively evaluate our method.

Figure 5: Fisher Linear Discriminant projections of **A**. Classification images comparisons for each category of group 1, **B.** samples for MCMCP chains for category group 1, **C.** Classification images comparisons for each category of group 2, and **D.** samples for MCMCP chains for category group 2. For A and C, large dots represent category means. For B and D, large dots represent chain means.

6.2 RESULTS

The acceptance rate was approximately 50% for both category groups, which is near the common goal for MCMCP experiments. The samples for all ten categories are shown in Figure 5B and D using Fisher Linear Discriminant Analysis. Similar to the face chains, the four chains for each category converge to similar regions in space, largely away from other categories. In contrast, classification images shows little separation with so few trials (5C and D). Previous work suggests that at least an order of magnitude higher number of comparisons may be needed for satisfactory estimation of category means. Our method estimates well-separated category means in a manageable number of trials, allowing for the method to scale greatly. This makes sense given that it proposes comparisons between arbitrary images, potentially wasting many trials, and clearly suffers from a great deal of noise.

Beyond yielding our decision rule, our method additionally produces a density estimate of the entire category distribution. In classification images, mean template images can be viewed, while we are able to visualize several modes in the category distribution. Figure 4 visualizes these modes using the means of each component in a mixture of Gaussians density estimate. This produces

Table 1: Classification performance compared to chance for both category sets (chance is 0.20).

	bird	body of water	fish	flower	landscape	all
MCMCP Mean	0.33	0.28	0.01	0.57	0.67	0.37
MCMCP Density	0.23	0.31	0.18	0.44	0.73	**0.38**
CI Mean	0.23	0.30	0.2	0.24	0.52	0.30

	bottle	car	fire hydrant	person	television	all
MCMCP Mean	0.15	0.32	0.11	0.77	0.73	**0.42**
MCMCP Density	0.25	0.56	0.26	0.19	0.50	0.35
CI Mean	0.28	0.62	0.15	0.12	0.13	0.26

CI = classification images

realistic-looking multi-modal mental category templates, which to our knowledge has never been accomplished with respect to natural image categories.

6.3 Using Estimated Human Categories for Classification

We also provide a quantitative assessment of the samples we obtained and compare them to classification images (CI) using an external classification task. To do this, we scraped approximately 500 images from flickr for each of our ten categories, which was used for a classification task. To classify the images with using our samples, we used (1) the nearest-mean decision rule, and (2) a decision rule based on the highest log-probability given by our ten density estimates. For, classification images, only a nearest-mean decision rule can be tested.

In all cases, decision rules based on our MCMCP-obtained samples overall outperform a nearest-mean decision rule using classification images (see Figure 1). In category group 1, the MCMCP density performed best and was more even across classes. In category group 2, nearest-mean using our MCMCP samples did much better than a density estimate or CI-based nearest-mean.

7 Discussion & Conclusion

Our results demonstrate the potential of our method, which leverages both psychological methods and deep surrogate representations to make the problem of capturing human category representations tractable. The flexibility of our method in fitting arbitrary generative models allows us to visualize multi-modal category templates for the first time, and improve on human-based classification performance benchmarks. It is difficult to guarantee that our chains explored enough of the relevant space to actually capture the concepts in their entirety, but the diversity in the modes visualized and the improvement in class separation achieved are positive indications that we are on the right track. Further, the framework we present can be straightforwardly improved as generative image models advance, and a number of known methods for improving the speed, reach, and accuracy of MCMC algorithms can be applied to MCMCP make better use of costly human trials.

There are several obvious limitations of our method. First, the structure of the underlying feature spaces used may either lack the expressiveness (some features may be missing) or the constraints (too many irrelevant features or possible images wastes too many trials) needed to map all characteristics of human mental categories in a practical number of trials. Even well-behaved spaces are very large and require many trials to reach convergence. Addressing this will require continuing exploration of a variety of generative image models. We see our work are as part of an iterative refinement process that can yield more granular human observations and inform new deep network objectives and architectures, both of which may yet converge on a proper, yet tractable model of real-world human categorization.

REFERENCES

Ahumada. Perceptual classification images from vernier acuity masked by noise. *Perception*, 25 (1_suppl):2–2, 1996.

Henri Cohen and Claire Lefebvre. *Handbook of categorization in cognitive science*. Elsevier, 2005.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. *arXiv preprint arXiv:1605.09782*, 2016.

Richard O Duda, Peter E Hart, David G Stork, et al. *Pattern classification*, volume 2. Wiley New York, 1973.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adverserial networks. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Michelle R Greene, Abraham P Botros, Diane M Beck, and Li Fei-Fei. Visual noise from natural scene statistics reveals human scene category representations. *arXiv preprint arXiv:1411.5331*, 2014.

Diederik P. Kingma and Max Welling. Auto-encoding variational Bayes. In *Proceedings of the 2nd International Conference on Learning Representation. ICLR 2014.*, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Brenden M Lake, Wojciech Zaremba, Rob Fergus, and Todd M Gureckis. Deep neural networks predict category typicality ratings for images. In *CogSci*, 2015.

Yann LeCun, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel. Backpropagation applied to handwritten zip code recognition. *Neural computation*, 1(4):541–551, 1989.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Jay B Martin, Thomas L Griffiths, and Adam N Sanborn. Testing the efficiency of markov chain monte carlo with people using facial affect categories. *Cognitive science*, 36(1):150–162, 2012.

Joshua Peterson, Joshua Abbott, and Tom Griffiths. Adapting deep network features to capture psychological representations. In *Proceedings of the 38th Annual Conference of the Cognitive Science Society*, Austin, TX, 2016.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

Adam Sanborn and Thomas L Griffiths. Markov Chain Monte Carlo with people. In *NIPS*, pp. 1265–1272, 2007.

Carl Vondrick, Hamed Pirsiavash, Aude Oliva, and Antonio Torralba. Learning visual biases from human imagination. In *Advances in neural information processing systems*, pp. 289–297, 2015.