Differentiable Architecture Search for Reinforcement Learning

Anonymous[1]

[1]Anonymous Institution

Abstract In this paper, we investigate the fundamental question: *To what extent are gradient-based neural architecture search (NAS) techniques applicable to RL?* Using the original DARTS as a convenient baseline, we discover that the discrete architectures found can achieve up to 250% performance over manual architecture designs on both discrete and continuous action space environments across off-policy and on-policy RL algorithms, at only 3x more computation time. Furthermore, through numerous ablation studies, we systematically verify that not only does DARTS correctly upweight operations during its supernet phrase, but also gradually improves resulting discrete cells up to 30x more efficiently than random search, suggesting DARTS is surprisingly an effective tool for improving architectures in RL.

1 Introduction and Motivation

Over the past few years, Differentiable Architecture Search (DARTS) (Liu et al., 2019) has dramatically risen in popularity as a method for neural architecture search (NAS), with multiple modifications and improvements (Chu et al., 2020c; Li et al., 2021; Chu et al., 2020a; Liang et al., 2019; Wang et al., 2021a; Chu et al., 2020b; Hundt et al., 2019; Wang et al., 2021b; Chen and Hsieh, 2020; Zela et al., 2020) constantly proposed at a rapid speed. From a broader perspective, one may wonder how far we may push the limits of differentiable search, as differentiability is the cornerstone of all deep learning

Figure 1: DARTS is potentially a natural fit for RL, as a DARTS supernet can simply inserted into the network components of a standard RL training pipeline, which may potentially be highly distributed.

research. One such very large application space is in reinforcement learning (RL), with DARTS being a natural fit due to its simplicity and modularity in integrating with large distributed RL training pipelines. Shockingly however, among the vast amounts of literature on DARTS, there are virtually no works addressing its viability in RL.

This can be attributed to the fact that RL fundamentally does not follow the same optimization paradigm as SL. The end goal of RL is not to simply minimize the loss or accuracy over a fixed dataset, but rather to improve a policy's reward over an entire environment whose training data is generated by the policy itself. This scenario raises the possibility of a negative feedback loop in which a poorly trained policy may achieve trivial reward even if it successfully optimizes its loss to zero, and thus the loss is not an indicator of a policy's true performance. As DARTS is purely reliant on optimizing the architecture topology by using only the loss as the search signal, therein lies the simple question: *Would DARTS even work in RL?*

It is highly valuable to answer this question, as recently, works in larger-scale RL suggest that policy architecture designs greatly affect various metrics such as generalization, transferrability, and efficiency. One surprising phenomenon found on Procgen (Cobbe et al., 2020), a procedural

generation benchmark for RL, was that "IMPALA-CNN", a residual convolutional architecture from (Espeholt et al., 2018), could substantially outperform "NatureCNN", the standard 3-layer architecture used for Atari (Mnih et al., 2013), in both generalization and sample complexity under limited and infinite data regimes respectively (Cobbe et al., 2019). Furthermore, in robotics subfields such as grasping (Kalashnikov et al., 2018; Rao et al., 2020), cameras collect very detailed real-world images (ex: 472 x 472, 4x larger than ImageNet (Russakovsky et al., 2015)) for observations which require deep image encoders consisting of more than 15 convolutions, raising concerns on efficiency and speed in policy training and inference. As such RL policy networks gradually become larger and more sophisticated, so does the need for understanding and automating such designs, as part of the broader Automated Reinforcement Learning (AutoRL) (Parker-Holder et al., 2022) field.

In this paper, we show that DARTS can in fact find better architectures efficiently in RL, one of the first instances in which the loss does not directly affect the final objective. This work may be of interest to both the gradient-based NAS community as means to expand to the RL domain, and the AutoRL community as a practical toolset and method for co-training policies and neural architectures for better performing agents. Our contributions are:

- We conceptually identify the key differences between SL and RL in terms of their usage of the loss function, which raise important hypothetical questions and issues about whether DARTS is applicable to RL. In particular, these deal with the quality of the training signal to the architecture variables during supernet training, and downstream effects on discrete cells during evaluation.

- Empirically, we find that DARTS is in fact compatible with several on-policy and off-policy algorithms including PPO (Schulman et al., 2017), Rainbow-DQN (Hessel et al., 2018), and SAC (Haarnoja et al., 2018). The discrete architectures found can reach up to 150 % improvement over manual architecture designs on discrete action (e.g. Procgen) and continuous control (e.g. DM-Control) environments, at only 3x more computation time.

- Through comprehensive ablation studies, we show the supernet successfully trains, and reasonably upweights optimal operations. We further verify both qualitatively and quantitatively that discretized cells gradually evolve to better architectures. However, we also demonstrate how this can fail, especially if the corresponding supernet fails to train, with further extensive ablations in the Appendix.

Related Works. Most previous NAS for RL works only involve small policies trained via black-box/evolutionary optimization methods, which include (Song et al., 2021; Gaier and Ha, 2019; Stanley and Miikkulainen, 2002; Stanley et al., 2009), utilizing CPU workers for forward pass evaluations rather than exact gradient computation on GPUs. Such methods are usually unable to train policies involving more than 10K+ parameters due to the sample complexity of zeroth order methods in high dimensional parameter space (Agarwal et al., 2010). The only previous known application of gradient-based routing is (Akinola et al., 2021), which searches for the optimal way of combining observation and action tensors together in off-policy QT-OPT (Kalashnikov et al., 2018), but does not search for image encoders nor uses the supernet for inference, as it trains using off-policy robotic data collected independently. This leaves the applicability of DARTS to inference-dependent RL as an open question addressed in our work.

2 Problem Overview and Method

DARTS Preliminaries. Since we only use the original DARTS (Liu et al., 2019) to reduce confounding factors, we thus give a very brief overview of DARTS to save space and only discuss notation. More comprehensive details can be found in Appendix H.5 and the original paper. Denote the total set of possible operations in our searchable network as $\mathcal{O} = \mathcal{O}_{base} \cup \{Zero, Skip\}$ which must contain Zero and Skip Connection ops, while $\mathcal{O}_{base}$ is user-defined. Denote α to be the pre-softmax trainable

---

Algorithm 1: RL-DARTS Procedure.

---
1. **Supernet training**: Compute α^* from $\arg\max_{\theta,\alpha} J(\pi_{\theta,\alpha})$ via $\arg\min_{\theta,\alpha} \mathcal{L}^{RL}(\theta,\alpha)$.
2. **Discretization**: Discretize α^* to construct evaluation policy $\pi_{\phi,\delta(\alpha^*)}$.
3. **Evaluation**: Report $\max_\phi J(\pi_{\phi,\delta(\alpha^*)})$ via $\arg\min_\phi \mathcal{L}_{\delta(\alpha^*)}(\phi)$.

---

architecture variables in the supernet. A predefined loss function $\mathcal{L}(\theta)$ over neural network weights θ will thus be redefined as $\mathcal{L}(\theta,\alpha)$ when under DARTS's *search mode*, where the original model f_θ will be replaced with a dense supernet $f_{\theta,\alpha}$. During evaluation time, a trained α^* is then *discretized* into a sparser final cell $\delta(\alpha^*)$, from which we retrain the new loss $\mathcal{L}_{\delta(\alpha^*)}(\phi)$, now dependent on only fresh sparse weights ϕ to obtain the final reported metric.

RL Preliminaries. For RL notation, given an MDP $\mathcal{M}$, denote s_t, a_t, r_t as state, action, reward respectively at time t. π is the policy and $\mathcal{D}$ is the replay buffer containing collected trajectories $\tau = (s_0, a_0, r_0, s_1, \ldots)$. The goal is to maximize $J(\pi) = \mathbb{E}_{\tau \sim \pi}\left[\sum_{t \geq 0} r_t\right]$, the expected cumulative reward using policy π. In most RL algorithms, there is the notion of a neural network torso or *encoder* f_θ mapping the state s to a final feature vector when forming π. In the DARTS case, we use a supernet encoder $f_{\theta,\alpha}$ leading to a supernet policy denoted as $\pi_{\theta,\alpha}$ and also a corresponding discretized-cell policy $\pi_{\phi,\delta(\alpha^*)}$ for evaluation.

2.1 Methodology

SL features the notion of training and validation sets, with corresponding losses $\mathcal{L}_{train}^{SL}, \mathcal{L}_{val}^{SL}$, where the learning procedure consists of a bilevel optimization problem and the goal is to find $\alpha^* = \arg\min_\alpha \mathcal{L}_{val}^{SL}(\theta^*, \alpha)$ where $\theta^* = \arg\min_\theta \mathcal{L}_{train}^{SL}(\theta, \alpha)$. In this paper, we do not need to use the original bilevel optimization framework, as we are optimizing sample complexity and raw training performance, which are standard metrics in RL. Furthermore, bilevel optimization is notoriously difficult and unstable, sometimes requiring special techniques (Liu et al., 2018; Dong and Yang, 2019; Hundt et al., 2019; Li et al., 2020; Chu et al., 2020b,a,c; Liang et al., 2019; Wang et al., 2021b) specific to SL optimization, which can confound the results and message of our paper.

We thus joint optimize both θ and α, and the full procedure is concisely summarized in Algorithm 1 as "RL-DARTS". However, this is easier said than done, as we explain the core issues of applying DARTS to RL below.

SL vs RL DARTS. Fundamentally, SL relies on a fixed dataset $\mathcal{D}^{SL} = \{(x_i, y_i) \mid i \geq 1\}$, in which the loss is defined as $\mathcal{L}^{SL}(\theta) = \mathbb{E}_{(x,y) \sim \mathcal{D}}\left[\ell(f_\theta(x), y)\right]$ where $\ell(\cdot)$ is defined as mean squared error, cross-entropy loss, or negative log-likelihood depending on application. These losses are strongly correlated or even equivalent to the final objective (e.g. accuracy or density estimation), and this reason can be considered a significantly contributing factor to the success of DARTS in SL. Unfortunately in RL, there are no such guarantees that minimizing the loss $\mathcal{L}^{RL}(\cdot)$ necessarily improves the true objective $J(\cdot)$, for two primary reasons:

1. The RL agent's dataset (a.k.a. replay buffer) $\mathcal{D}^{RL} = \{\tau_i \mid i \geq 1\}$ is significantly non-stationary and self-dependent, as it constantly changes based on the current performance of data collection actors, which themselves are functions of θ. Thus, a negative feedback loop may arise, where θ produces an actor which collects poor training data, leading to convergence towards an even poorer θ'. While the loss $\mathcal{L}^{RL}(\cdot)$ converges to 0 over low quality data, the reward $J(\cdot)$ still does not increase. This issue is commonplace in RL, such as in any environments which require exploration. Hypothetically in the DARTS case, α can potentially produce the same negative feedback loop by converging to subpar operations and impairing supernet training, also leading to a poor discrete cell $\delta(\alpha)$.

2. The losses are considerably more complex and utilize multiple auxiliary losses which are used to assist training but never used during evaluation. For PPO, the loss is defined as $\mathcal{L}_{PPO}^{RL}(\theta) = \mathbb{E}_{\tau \sim \mathcal{D}_{RL}}[L_{CLIP}(\theta) - L_{VF}(\theta) + \mathcal{H}(\theta)]$. However, the value function (corresponding to L_{VF}) nor the policy entropy (corresponding to $\mathcal{H}$) are never used to evaluate final reward. This is similarly the case for off-policy algorithms such as SAC which strongly emphasizes maximizing the entropy $\mathcal{H}$ and Rainbow-DQN which also uses value functions to assist training. The question is thus raised in the DARTS case as to whether such auxiliary losses are actually useful signals, or inhibit proper training of α, whose main goal is only maximize $J(\cdot)$ using discrete cell $\delta(\alpha)$.

The core theme of our experiments will be understanding whether these are obstacles to DARTS's application to RL.

3 Experiments

Experiment Setup: To verify that every component of RL-DARTS works as intended, we seek to answer all questions below, by first presenting end-to-end results, and then further key ablation studies:

1. **End-to-End Performance**: Overall, how do the final discrete cells perform at evaluation, and what gains can we obtain from architecture search? Furthermore, how does RL-DARTS compare against random search?

2. **Supernet Training**: During supernet training, how does the α change? Does α converge towards a sparse solution and select good operations over supernet training?

3. **Discrete Cells**: Even if the supernet trains, do the corresponding discrete cells also improve in evaluation performance throughout α's training? What kinds of failure modes occur?

Following common NAS practices (Zoph et al., 2018; Pham et al., 2018; Zoph and Le, 2016), we construct our supernet (with I intermediate cells) by stacking both normal (N times) and reduction cells (R times) together into *blocks*, which are themselves also stacked together D times (see Figure 2). Reduction cells apply a stride of 2 on the input. Each block possesses its own convolutional channel depth, used throughout all cells in the block. During search, we train a smaller supernet (i.e. depth 16) to reduce computation time, but evaluate final discretized cells on larger models (i.e. depth 64), with $D = 3$ layers for cheap large-scale runs and $D = 5$ layers for fine-grained A/B testing.

Figure 2: Illustration of our network via stacking normal and reduction cells. Solid lines correspond to selected ops after discretization from all possible ops weighted using α. If $R > 0$, we add an iniital Conv3x3 for preprocessing.

For the operation search space, we consider the following base ops $\mathcal{O}_{base}$ and corresponding algorithms:

- **Classic on PPO**: $\mathcal{O}_{base,N}$ = {Conv3x3+ReLU, Conv5x5+ReLU, Dilated3x3+ReLU, Dilated5x5+ReLU} for normal ops and $\mathcal{O}_{base,R}$ = {Conv3x3, MaxPool3x3, AveragePool3x3} for reduction ops, which is standard in supervised learning (Liu et al., 2019; Zoph et al., 2018; Pham et al., 2018).

- **Micro on Rainbow and SAC**: We also propose $\mathcal{O}_{base,N}$ = {Conv3x3, ReLU, Tanh}, a more fine-grained and novel search space which has not been used previously in SL. The inclusion of Tanh

is motivated by its use previously for continuous control architectures (Salimans et al., 2017; Song et al., 2020).

For benchmarks, we primarily use Procgen (Cobbe et al., 2019, 2020) for discrete action spaces, with PPO (Schulman et al., 2017) and Rainbow DQN (Hessel et al., 2018) as training algorithms, with Procgen's difficulty set to "easy" similar to other works (Raileanu et al., 2020; Raileanu and Fergus, 2021; Parker-Holder et al., 2021a). Procgen comprehensively evaluates all aspects of RL-DARTS, as it possesses a diverse selection of 16 games, each with infinite levels to simulate large data regimes where episodes may drastically change, relevant for generalization. It further uses the IMPALA-CNN architecture (Espeholt et al., 2018) as a strong hand-designed baseline, and can be seen as a specific instance of the stacked cell design in Figure 2, where its "Reduction Cell" consists of a Conv3x3 and MaxPool3x3 (Stride 2) with $R = 1$ and its "Normal Cell" consists of a residual layer with Conv3x3's and ReLU's, with $N = 2$. For fair comparisons to IMPALA-CNN, we use $(N, R, I) = (1, 1, 4)$ on the classic search space, while $(N, R, I) = (2, 0, 4)$ on the Micro search space, where reduction ops default to IMPALA-CNN's in order to avoid hidden confounding effects when visualizing Micro cells.

In addition, we also assess DARTS's viability in continuous control which is common in robotics tasks. We use the common DM-Control benchmark (Tassa et al., 2018) along with the popular SAC algorithm. We use $N = 3, I = 4, K = 1$ with "Micro" search space to remain fair to the 4-layer convolutional encoder baseline observing images of size 64×64 (full details in Appendix H).

Unless specified, we by default use consistent hyperparameters (found in Appendix H) for all comparisons found inside a figure, although learning rate and minibatch size may be altered when training models of different sizes due to GPU memory limits. Thus, even though RL is commonly sensitive to hyperparameters (Zhang et al., 2021), we surprisingly find that **once a pre-existing RL baseline has already been setup, incorporating DARTS requires no extra cost in tuning, as evidence of its ease-of-use**.

3.1 End-to-End Results on Multi-task, Discrete and Continuous Control Tasks

Figure 3: **Left 2x2 Plot**: Evaluation of the discrete cell joint-trained over all environments using depths 64×5 to emphasize comparison differences. **Right (Top)**: Discrete cell found. **Right (Bottom)**: Average normalized rewards over all 16 games during supernet + baseline training.

Multi-game Search. We first begin with the most surprising and largest end-to-end result in terms of scale of data and compute shown in Figure 3: **By training a supernet across infinite levels**

across *all 16 Procgen games* to find a single transferrable cell, we are able to achieve up to **250% performance over the IMPALA-CNN baseline** over select environments. This is achieved using Rainbow with our proposed "Micro" search space, where a learner performs gradient updates over actor replay data (with normalized rewards) from all games.

Figure 4: **Left 2x2 Plot**: Examples of discrete cell evaluations using the "Classic" search space with PPO, with depths 64×3. **Right**: Normal (Top) and Reduction (Bottom) cells found for "Plunder" which achieves faster training than IMPALA-CNN. Note the interesting use of 5x5 convolutional kernel sizes later in the cell.

	IMPALA-CNN	RL-DARTS (Discrete Cell)	Random Search
Avg. Normalized Reward	0.708	0.709	0.489

Table 1: Average normalized rewards across all 16 environments w/ PPO, using the normalization method from (Cobbe et al., 2020). Full details and results (including Rainbow) are presented in Appendix E.

Single-game Search. We further compare DARTS's end-to-end performance against random search, but more appropriately applied to single game scenarios. On the PPO side, we use the "Classic" search space (total size 4×10^{11}, see Appendix I.1). For a fair comparison, we ensure total wall-clock time (with same hardware) stays equal, as common in (Liu et al., 2019). Since in Appendix A, Table 4, a PPO supernet takes 2.5x longer to reach 25M steps, this is rounded to a random search budget of 3 cells to be trained with depths 16×3 for 25M steps. The best of the 3 cells is used

Figure 5: Histogram of 100 random cells' rewards on Dodgeball with Rainbow + "Micro" search space (depths 64×3), with 95% substantially worse and 55% unable to even train. More results in Appendix F.

for full evaluation. In Table 1, on average, random search underperforms significantly, while in Figure 4 we further find that RL-DARTS is capable of finding game-specific architectures from

scratch which outperform IMPALA-CNN on select environments such as Plunder and Heist, while maintaining competitive performance on others.

100 Random Cell Comparison. To further present a more comprehensive comparison against random search, we compare against 100 unique random cells in Figure 5 and find that in certain cases such as in the game "Dodgeball" using Rainbow, DARTS remains the top-ranking cell, showing DARTS possesses a strong search capability, achieving $100/3 \approx 30x$ efficiency over random search.

DM-Control with Soft Actor-Critic. DARTS also consistently finds better and stable architectures over multiple lightweight environments involving continuous control (see Figure 6) trained up to 1M steps.

Figure 6: RL-DARTS on DM-Control with SAC also finds better architectures over the corresponding baseline.

3.2 Role of Supernet Training

In Figure 7, we verify that **training the supernet end-to-end works effectively, even with minimal hyperparameter tuning**. Furthermore, the training only requires at 3x more compute time, with extensive efficiency metrics calculated in Appendix A. However, as mentioned in Subsec. 2.1, it is unclear whether the right signals are provided to operation routing variables α via the RL training loss, and whether α produces the correct behavior, which we investigate.

Figure 7: **Left**: Softmax op weights over all edges in the cell when training the supernet with PPO + "Classic" search space on Dodgeball. Zero op weight is not shown to improve clarity. **Right**: Sanity check to verify that the supernet eventually achieves a regular training curve, using vanilla IMPALA-CNN as a rough gauge. Both use depths 16×3. Note that while we show the curve up to 50M steps, we by default discretize α at 25M steps, as op choices have already converged towards a sparser solution. Analogous figure for Rainbow in Appendix B.

Conveniently in Figure 7, we find that α strongly downweights all base ops (in particular, 5x5 ops) except for the standard Conv3x3+ReLU. This provides an opportunity to understand whether α **downweights suboptimal ops throughout training**. We confirm this result in Table 2 by evaluating standard IMPALA-CNN cells using either purely 3x3 or 5x5 convolutions for the whole network, and demonstrating that the 3x3 setting outperforms the 5x5 setting (especially in limited data, e.g. 200-level training/test regime), suggesting the signaling ability of α on op choice.

Answering the converse question is just as important: *Can any supernet train?* The supernet possesses an incredibly dense set of weights, and thus one might wonder whether trainability occurs with any search space or settings. We answer in the negative, where a **poorly designed supernet can fail**. To show this clearly, we remove all ReLU nonlinearities from the "Classic"

Scenario	Conv 3x3	Conv 5x5
Train (Inf. levels)	**15.1 ± 2.5**	13.2 ± 2.3
Train (200 levels)	**12.1 ± 1.7**	9.8 ± 2.1
Test (from Train)	**10.2 ± 2.3**	5.9 ± 1.7

Table 2: PPO IMPALA-CNN evaluations (mean return at 50M steps) on Dodgeball. Learning curves can be found in Appendix D.1, Figure 14.

search space ops used for PPO, as well as simply freeze α to be uniform for Rainbow, and find both cases produce poor training in Table 3. **Thus, the supernet in RL provides important search signals in terms of reward and α during training, especially on the quality of a search space.**

	Rainbow (25M Steps)		PPO (50M Steps)	
Scenario	Trainable α	Uniform α	With ReLU	No ReLU
Training (Inf. levels) Reward	**3.1 ± 0.5**	0.9 ± 0.2	**7 ± 0.9**	1.9 ± 0.3

Table 3: Supernet training rewards on Dodgeball. Learning curves can be found in Appendix C.

3.3 Discrete Cell Improvement

We further must analyze whether discrete cells also improve, as they are used for final evaluation and deployment. Strong supernet performance (via continuous relaxation) does not necessarily imply strong evaluation cell performance (via discretization), due to the existence of *integrality gaps* (Wang et al., 2021b,a). Nevertheless, we demonstrate that even using the default δ discretization from (Liu et al., 2019) leads to both quantitative and quantitative improvements.

Quantitative improvement. As α changes during supernet training, so do the outputs of the discretization procedure on α. We collect all distinct discrete cells $\{\delta(\alpha_1), \delta(\alpha_2), \ldots\}$ into a sequence, and evaluate each cell's performance $\max_\phi J(\pi_{\phi, \delta(a_i)}) \ \forall i$ via training from scratch for 25M steps (Figure 8). The performance generally improves over time, indicating that supernet optimization selects better cells. However, we find that such behavior can be environment-dependent, as some environments possess less monotonic evaluation curves (see Fig. 17 in Appendix D).

Figure 8: Evaluation of 9 distinct discrete cells in order from the trajectory of α on the Starpilot environment when using Rainbow.

Qualitative improvement. We visualize discrete cells $\delta(\alpha_{start}), \delta(\alpha_{end})$ from the start and end of supernet training with Rainbow on the Starpilot environment in Fig. 9. The earlier cell consists of only linear operators is clearly a poor design in comparison to the later cell. We find similar cell evolution results for PPO in Figures 15, 16 in Appendix D.2, displaying more sophisticated yet still interpretable changes in cell topology.

Figure 9: Evolution of discovered cells over a DARTS optimization process. **Left**: $\delta(\alpha_{start})$ discovered in the early stage which is dominated by skip connections and only linear ops. **Right**: $\delta(\alpha_{end})$ discovered in the end which possesses several reasonable local structures similar to Conv + ReLU residual connections.

We further answer one of the most common questions in DARTS research: *What is the direct relationship between a supernet and its discrete cell?* In Figure 10, we provide two supernet runs along with their corresponding discrete cells, side by side in order to answer this question. While "Supernet 1" is a standard successful training run, "Supernet 2" is a failed run which can commonly occur due to the inherent sensitivity and variance in RL training. As it turns out, this directly leads to differences between their corresponding discrete cells both quantitatively and qualitatively as well, in which "Discretized Cell 1"'s design appears to make sense and train properly, while "Discretized Cell 2" is clearly a suboptimal design, and fails to train at all. Thus, a major reason for why a **discretized cell may underperform is if its corresponding supernet fails to learn**.

We investigate further in Appendix D.3, Figure 18, and find that supernet and discrete cell rewards are indeed correlated, after adjusting for environment-dependent factors, suggesting that search quality can be improved via both better supernet training (Raileanu et al., 2020; Zhang et al., 2021), as well as better discretization procedures (Liang et al., 2019; Wang et al., 2021b).

(a) Different supernet runs, with corresponding discretized cell (depths 64×5) training curves.

(b) Discretized Cell 1

(c) Discretized Cell 2

Figure 10: (a) Two different supernets trained on the Dodgeball environment using Rainbow, with corresponding discretized cells evaluated using 3 random seeds. (b) Discretized cell from Supernet 1. Note the similarity to regular Conv3x3 + ReLU designs. (c) Discretized cell from Supernet 2, which uses too many Tanh nonlinearities, known to cause vanishing gradient effects.

4 Conclusions, Limitations, and Broader Impact Statement

Conclusion. Even though RL uses complex loss functions defined over nonstationary data, we empirically showed that nonetheless, DARTS is capable of improving policy architectures in a minimally invasive and efficient way (only 3x more compute time) across several different algorithms (PPO, Rainbow, SAC) and environments (Procgen, DM-Control). Our paper is the first to have comprehensively provided evidence for the applicability of softmax/gradient-based architecture search outside of standard classification and SL.

Limitations. To avoid confounding factors and for simplicity, our paper uses the default DARTS method. However, we outline multiple possible improvements in Appendix G, as RL is a completely new frontier for which to understand softmax routing and continuous relaxation techniques.

Broader Impact. In this paper, we have provided concrete evidence that architecture search can be conducted practically and efficiently in RL, via DARTS. We believe that this could start important initiatives into finding better and more efficient (Cai et al., 2019) architectures for large-scale robotics (James et al., 2019; Akinola et al., 2021), transferable architectures in offline RL (Levine et al., 2020), as well as RNNs for memory (Pritzel et al., 2017; Fortunato et al., 2019; Kapturowski et al., 2019) and adaptation (Duan et al., 2016; Wang et al., 2017).

References

Agarwal, A., Dekel, O., and Xiao, L. (2010). Optimal algorithms for online convex optimization with multi-point bandit feedback. In Kalai, A. T. and Mohri, M., editors, *COLT 2010 - The 23rd Conference on Learning Theory, Haifa, Israel, June 27-29, 2010*, pages 28–40. Omnipress.

Akinola, I., Angelova, A., Lu, Y., Chebotar, Y., Kalashnikov, D., Varley, J., Ibarz, J., and Ryoo, M. S. (2021). Visionary: Vision architecture discovery for robot learning. In *ICRA*.

Bellemare, M. G., Dabney, W., and Munos, R. (2017). A distributional perspective on reinforcement learning. In Precup, D. and Teh, Y. W., editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 449–458. PMLR.

Cai, H., Zhu, L., and Han, S. (2019). Proxylessnas: Direct neural architecture search on target task and hardware. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net.

Chen, X. and Hsieh, C. (2020). Stabilizing differentiable architecture search via perturbation-based regularization. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 1554–1565. PMLR.

Chu, X., Wang, X., Zhang, B., Lu, S., Wei, X., and Yan, J. (2020a). DARTS-: robustly stepping out of performance collapse without indicators. *CoRR*, abs/2009.01027.

Chu, X., Zhang, B., and Li, X. (2020b). Noisy differentiable architecture search. *CoRR*, abs/2005.03566.

Chu, X., Zhou, T., Zhang, B., and Li, J. (2020c). Fair DARTS: eliminating unfair advantages in differentiable architecture search. In Vedaldi, A., Bischof, H., Brox, T., and Frahm, J., editors, *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XV*, volume 12360 of *Lecture Notes in Computer Science*, pages 465–480. Springer.

Cobbe, K., Hesse, C., Hilton, J., and Schulman, J. (2020). Leveraging procedural generation to benchmark reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 2048–2056. PMLR.

Cobbe, K., Klimov, O., Hesse, C., Kim, T., and Schulman, J. (2019). Quantifying generalization in reinforcement learning. In Chaudhuri, K. and Salakhutdinov, R., editors, *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pages 1282–1289. PMLR.

Dong, X. and Yang, Y. (2019). Searching for a robust neural architecture in four GPU hours. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pages 1761–1770. Computer Vision Foundation / IEEE.

Dong, X. and Yang, Y. (2020). Nas-bench-201: Extending the scope of reproducible neural architecture search. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Duan, Y., Schulman, J., Chen, X., Bartlett, P. L., Sutskever, I., and Abbeel, P. (2016). Rl$ˆ2$: Fast reinforcement learning via slow reinforcement learning. *CoRR*, abs/1611.02779.

Espeholt, L., Soyer, H., Munos, R., Simonyan, K., Mnih, V., Ward, T., Doron, Y., Firoiu, V., Harley, T., Dunning, I., Legg, S., and Kavukcuoglu, K. (2018). IMPALA: scalable distributed deep-rl with importance weighted actor-learner architectures. In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1406–1415. PMLR.

Fortunato, M., Tan, M., Faulkner, R., Hansen, S., Badia, A. P., Buttimore, G., Deck, C., Leibo, J. Z., and Blundell, C. (2019). Generalization of reinforcement learners with working and episodic memory. In Wallach, H. M., Larochelle, H., Beygelzimer, A., d'Alché-Buc, F., Fox, E. B., and Garnett, R., editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 12448–12457.

Gaier, A. and Ha, D. (2019). Weight agnostic neural networks. In Wallach, H. M., Larochelle, H., Beygelzimer, A., d'Alché-Buc, F., Fox, E. B., and Garnett, R., editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 5365–5379.

Guadarrama, S., Korattikara, A., Ramirez, O., Castro, P., Holly, E., Fishman, S., Wang, K., Gonina, E., Wu, N., Kokiopoulou, E., Sbaiz, L., Smith, J., Bartók, G., Berent, J., Harris, C., Vanhoucke, V., and Brevdo, E. (2018). TF-Agents: A library for reinforcement learning in tensorflow. https://github.com/tensorflow/agents. [Online; accessed 25-June-2019].

Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. (2018). Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 1856–1865. PMLR.

Hessel, M., Modayil, J., van Hasselt, H., Schaul, T., Ostrovski, G., Dabney, W., Horgan, D., Piot, B., Azar, M. G., and Silver, D. (2018). Rainbow: Combining improvements in deep reinforcement learning. In McIlraith, S. A. and Weinberger, K. Q., editors, *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pages 3215–3222. AAAI Press.

Hoffman, M., Shahriari, B., Aslanides, J., Barth-Maron, G., Behbahani, F., Norman, T., Abdolmaleki, A., Cassirer, A., Yang, F., Baumli, K., Henderson, S., Novikov, A., Colmenarejo, S. G., Cabi, S., Gulcehre, C., Paine, T. L., Cowie, A., Wang, Z., Piot, B., and de Freitas, N. (2020). Acme: A research framework for distributed reinforcement learning. *arXiv preprint arXiv:2006.00979*.

Hundt, A., Jain, V., and Hager, G. D. (2019). sharpdarts: Faster and more accurate differentiable architecture search. *CoRR*, abs/1903.09900.

James, S., Wohlhart, P., Kalakrishnan, M., Kalashnikov, D., Irpan, A., Ibarz, J., Levine, S., Hadsell, R., and Bousmalis, K. (2019). Sim-to-real via sim-to-sim: Data-efficient robotic grasping via randomized-to-canonical adaptation networks. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pages 12627–12637. Computer Vision Foundation / IEEE.

Kalashnikov, D., Irpan, A., Pastor, P., Ibarz, J., Herzog, A., Jang, E., Quillen, D., Holly, E., Kalakrishnan, M., Vanhoucke, V., and Levine, S. (2018). Scalable deep reinforcement learning for vision-based robotic manipulation. In *2nd Annual Conference on Robot Learning, CoRL 2018, Zürich, Switzerland, 29-31 October 2018, Proceedings*, volume 87 of *Proceedings of Machine Learning Research*, pages 651–673. PMLR.

Kapturowski, S., Ostrovski, G., Quan, J., Munos, R., and Dabney, W. (2019). Recurrent experience replay in distributed reinforcement learning. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net.

Kostrikov, I., Yarats, D., and Fergus, R. (2020). Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *CoRR*, abs/2004.13649.

Levine, S., Kumar, A., Tucker, G., and Fu, J. (2020). Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *CoRR*, abs/2005.01643.

Li, G., Qian, G., Delgadillo, I. C., Müller, M., Thabet, A. K., and Ghanem, B. (2020). SGAS: sequential greedy architecture search. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pages 1617–1627. IEEE.

Li, L., Khodak, M., Balcan, N., and Talwalkar, A. (2021). Geometry-aware gradient algorithms for neural architecture search. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Liang, H., Zhang, S., Sun, J., He, X., Huang, W., Zhuang, K., and Li, Z. (2019). DARTS+: improved differentiable architecture search with early stopping. *CoRR*, abs/1909.06035.

Liu, C., Zoph, B., Neumann, M., Shlens, J., Hua, W., Li, L., Fei-Fei, L., Yuille, A. L., Huang, J., and Murphy, K. (2018). Progressive neural architecture search. In Ferrari, V., Hebert, M., Sminchisescu, C., and Weiss, Y., editors, *Computer Vision - ECCV 2018 - 15th European Conference, Munich, Germany, September 8-14, 2018, Proceedings, Part I*, volume 11205 of *Lecture Notes in Computer Science*, pages 19–35. Springer.

Liu, H., Simonyan, K., and Yang, Y. (2019). DARTS: differentiable architecture search. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*.

Luo, R., Tian, F., Qin, T., Chen, E., and Liu, T. (2018). Neural architecture optimization. In Bengio, S., Wallach, H. M., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R., editors, *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pages 7827–7838.

Mellor, J., Turner, J., Storkey, A. J., and Crowley, E. J. (2020). Neural architecture search without training. *CoRR*, abs/2006.04647.

Mnih, V., Kavukcuoglu, K., Silver, D., Graves, A., Antonoglou, I., Wierstra, D., and Riedmiller, M. A. (2013). Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602.

Parker-Holder, J., Nguyen, V., Desai, S., and Roberts, S. J. (2021a). Tuning mixed input hyperparameters on the fly for efficient population based autorl. *CoRR*, abs/2106.15883.

Parker-Holder, J., Nguyen, V., Desai, S., and Roberts, S. J. (2021b). Tuning mixed input hyperparameters on the fly for efficient population based autorl. *CoRR*, abs/2106.15883.

Parker-Holder, J., Nguyen, V., and Roberts, S. J. (2020). Provably efficient online hyperparameter optimization with population-based bandits. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H., editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Parker-Holder, J., Rajan, R., Song, X., Biedenkapp, A., Miao, Y., Eimer, T., Zhang, B., Nguyen, V., Calandra, R., Faust, A., Hutter, F., and Lindauer, M. (2022). Automated reinforcement learning (autorl): A survey and open problems. *CoRR*, abs/2201.03916.

Pham, H., Guan, M. Y., Zoph, B., Le, Q. V., and Dean, J. (2018). Efficient neural architecture search via parameter sharing. In Dy, J. G. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pages 4092–4101. PMLR.

Pritzel, A., Uria, B., Srinivasan, S., Badia, A. P., Vinyals, O., Hassabis, D., Wierstra, D., and Blundell, C. (2017). Neural episodic control. In Precup, D. and Teh, Y. W., editors, *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pages 2827–2836. PMLR.

Raileanu, R. and Fergus, R. (2021). Decoupling value and policy for generalization in reinforcement learning. *CoRR*, abs/2102.10330.

Raileanu, R., Goldstein, M., Yarats, D., Kostrikov, I., and Fergus, R. (2020). Automatic data augmentation for generalization in deep reinforcement learning. *CoRR*, abs/2006.12862.

Rao, K., Harris, C., Irpan, A., Levine, S., Ibarz, J., and Khansari, M. (2020). Rl-cyclegan: Reinforcement learning aware simulation-to-real. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pages 11154–11163. IEEE.

Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M. S., Berg, A. C., and Li, F. (2015). Imagenet large scale visual recognition challenge. *Int. J. Comput. Vis.*, 115(3):211–252.

Salimans, T., Ho, J., Chen, X., and Sutskever, I. (2017). Evolution strategies as a scalable alternative to reinforcement learning. *CoRR*, abs/1703.03864.

Schaul, T., Quan, J., Antonoglou, I., and Silver, D. (2016). Prioritized experience replay. In Bengio, Y. and LeCun, Y., editors, *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*.

Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. (2017). Proximal policy optimization algorithms. *CoRR*, abs/1707.06347.

Song, X., Choromanski, K., Parker-Holder, J., Tang, Y., Peng, D., Jain, D., Gao, W., Pacchiano, A., Sarlós, T., and Yang, Y. (2021). ES-ENAS: combining evolution strategies with neural architecture search at no extra cost for reinforcement learning. *CoRR*, abs/2101.07415.

Song, X., Jiang, Y., Tu, S., Du, Y., and Neyshabur, B. (2020). Observational overfitting in reinforcement learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Stanley, K. O., D'Ambrosio, D. B., and Gauci, J. (2009). A hypercube-based encoding for evolving large-scale neural networks. *Artif. Life*, 15(2):185–212.

Stanley, K. O. and Miikkulainen, R. (2002). Efficient reinforcement learning through evolving neural network topologies. In Langdon, W. B., Cantú-Paz, E., Mathias, K. E., Roy, R., Davis, D., Poli, R., Balakrishnan, K., Honavar, V. G., Rudolph, G., Wegener, J., Bull, L., Potter, M. A., Schultz, A. C., Miller, J. F., Burke, E. K., and Jonoska, N., editors, *GECCO 2002: Proceedings of the Genetic and Evolutionary Computation Conference, New York, USA, 9-13 July 2002*, pages 569–577. Morgan Kaufmann.

Tassa, Y., Doron, Y., Muldal, A., Erez, T., Li, Y., de Las Casas, D., Budden, D., Abdolmaleki, A., Merel, J., Lefrancq, A., Lillicrap, T. P., and Riedmiller, M. A. (2018). Deepmind control suite. *CoRR*, abs/1801.00690.

Wang, H., Yang, R., Huang, D., and Wang, Y. (2021a). idarts: Improving DARTS by node normalization and decorrelation discretization. *CoRR*, abs/2108.11014.

Wang, J., Kurth-Nelson, Z., Soyer, H., Leibo, J. Z., Tirumala, D., Munos, R., Blundell, C., Kumaran, D., and Botvinick, M. M. (2017). Learning to reinforcement learn. In Gunzelmann, G., Howes, A., Tenbrink, T., and Davelaar, E. J., editors, *Proceedings of the 39th Annual Meeting of the Cognitive Science Society, CogSci 2017, London, UK, 16-29 July 2017*. cognitivesciencesociety.org.

Wang, R., Cheng, M., Chen, X., Tang, X., and Hsieh, C.-J. (2021b). Rethinking architecture selection in differentiable nas. In *International Conference on Learning Representations, ICLR 2021*. OpenReview.net.

White, C., Zela, A., Ru, B., Liu, Y., and Hutter, F. (2021). How powerful are performance predictors in neural architecture search? *CoRR*, abs/2104.01177.

Zela, A., Elsken, T., Saikia, T., Marrakchi, Y., Brox, T., and Hutter, F. (2020). Understanding and robustifying differentiable architecture search. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Zhang, B., Rajan, R., Pineda, L., Lambert, N. O., Biedenkapp, A., Chua, K., Hutter, F., and Calandra, R. (2021). On the importance of hyperparameter optimization for model-based reinforcement learning. *CoRR*, abs/2102.13651.

Zoph, B. and Le, Q. V. (2016). Neural architecture search with reinforcement learning. *CoRR*, abs/1611.01578.

Zoph, B., Vasudevan, V., Shlens, J., and Le, Q. V. (2018). Learning transferable architectures for scalable image recognition. In *2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018*, pages 8697–8710. IEEE Computer Society.