Semi-Supervised Video Salient Object Detection Based on Uncertainty-Guided Pseudo Labels

Abstract

Semi-Supervised Video Salient Object Detection (SS-VSOD) is challenging because of the lack of temporal information caused by sparse annotations in video sequences. Most works address this problem by generating pseudo labels for unlabeled data. However, error-prone pseudo labels negatively affect the VOSD model. Therefore, a deeper insight into pseudo labels should be developed. In this work, we aim to explore 1) how to utilize the incorrect predictions in pseudo labels to guide the network to generate more robust pseudo labels and 2) how to further screen out the noise that still exists in the improved pseudo labels. To this end, we propose an Uncertainty-Guided Pseudo Label Generator (UGPLG), which makes full use of inter-frame information to ensure the temporal consistency of the pseudo-labels and improves the robustness of the pseudo labels by strengthening the learning of difficult scenarios. Furthermore, we also introduce adversarial learning to address the noise problems in pseudo labels, guaranteeing the positive guidance of pseudo labels during model training. Experimental results demonstrate that our methods outperform existing semi-supervised method and partial fully-supervised methods across five public benchmarks of DAVIS, FBMS, MCL, ViSal, and SegTrack-V2.

1 Introduction

Video Salient Object Detection (VSOD) aims to locate and segment the objects people are most interested in in the video consequence. With the increasing demand for video data processing, research on VSOD has received increased attention. As a fundamental technique in computer vision, many video-related applications adopt it as preprocessing to allocate more attention to salient regions, such as video tracking [44] , video object segmentation [31], video compression [20], video captioning [33].

Compared with still-image-based SOD tasks, VSOD is more challenging because the prediction of salient objects in video is heavily dependent on temporal dynamics. In recent years, deep-learning-based VSOD has achieved significant progress with the development of CNN. However, it is usually expensive and difficult to label temporally consistent pixel-level annotations for videos. To reduce the heavy efforts of labeling segmentation ground truth, numerous pseudo-label based semi-supervised video methods [47, 6, 14] are proposed. These works try to use limited, sparsely annotated ground-truth labels to generate labels for unlabeled data through self-training or label propagation, to make up for the lack of temporal information between sparsely annotated frames. Because video data has much redundant information (*et al.*, 24 fps in the DAVIS [35] dataset), we believe using a small amount of ground truth and large amounts of pseudo labels to supervise the model's training tends to be more efficient for VSOD.

Yan *et al.* [47] try to address semi-supervised VSOD by proposing a teacher network trained with the sparsely sampled annotations (sample every n frames, n > 1) to generate pseudo labels for the

| RGB$_t$ | GT$_t$ | RGB$_{t+n}$ | PL$_{t+n}$ | RGB$_k$ | GT$_k$ | RGB$_{k+n}$ | PL$_{k+n}$ |

Figure 1: PL$_{t+n}$ and PL$_{k+n}$ are the pseudo labels generated by the pseudo label generation network in RCR [47] for RGB$_{t+n}$ and RGB$_{k+n}$, respectively. The areas corresponding to the red box is error-prone. These four scenarios correspond to deformed objects, details of complex objects, interference of similar objects, and blurred boundaries caused by fast motion.

unlabeled data, which are involved in the subsequent training of the video saliency model with manually annotated labels. Despite their great performance, further refinements for pseudo labels should be concerned. We observe that pseudo labels tend to have obvious errors regarding difficult scenarios, such as deformed objects, interference from similar objects, and complex contours(shown in Fig. 1). Error-prone pseudo labels are usually detrimental to final detection. Inspired by these observations, we think two key issues need to be considered: 1) How do we use the incorrect information in pseudo labels to guide the pseudo labels generation network to generate more reliable predictions in difficult scenarios. 2) How do we suppress the noise that still exists in pseudo labels for further improving the video saliency model.

In this paper, we strive to overcome difficulties toward accurate semi-supervised VSOD. The primary challenge toward this goal is to generate high-quality pseudo labels and avoid the interference of the noise that still exists in the pseudo labels. The key aspect in the success of our method is to utilize the erroneous prediction in pseudo labels to strengthen the robustness of the pseudo label generator and formulate noise suppression as an adversarial learning problem. Concretely, our contributions are threefold:

- We propose a pseudo label generator that is equipped with an Uncertainty-Aware Dual Decoder Module(UADDM). It makes full use of the inter-frame information to locate the salient objects in unlabeled frames, ensuring the temporal consistency of pseudo labels. Uncertain regions can be used by UADDM to guide the network to generate more robust pseudo labels.
- We introduce adversarial learning to learn the distribution of the sparsely labeled training set, and the regions that do not conform to the ground truth distribution in pseudo labels can be filtered out by the generative adversarial network.
- We conduct extensive experiments on 5 widely-used datasets and demonstrate that our method outperforms existing semi-supervised VSOD method and partial fully-supervised methods.

2 Related Work

2.1 Salient Object Detection

During the past decades, large amounts of conventional methods have been developed for SOD. Early works [23, 5, 48] mainly rely on intrinsic cues (*e.g.*, color and texture) to extract saliency features. However, because low-level features cannot capture rich contextual semantic information, the application scenarios of these traditional methods are very limited. Later on, with the development of deep learning techniques, deep-learning-based methods (*et al.*, [17, 9, 45, 36, 12]) are dominant in this field, which can be divided into integration-based models and edge-based models. Integration-based models aim to aggregate multi-scale features to leverage context information of different levels. Hou *et al.* [17] introduce short connections by linking the deep layers towards shallower ones to integrate features of different layers. Deng *et al.* [9]combine features from both deep and shallow layers to iteratively refine the saliency maps step-by-step. Wu *et al.* [45] aggregate partial high-level features to generate a coarse attention map to guide the network to output more accurate maps. Edge-based models attempt to generate prediction maps with clear boundaries by making better use of edge information. Qin *et al.* [36] Propose a hybrid loss that fuses BCE, SSIM, and

IoU to supervise the training process on pixel-level, patch-level, and map-level. Feng *et al.* [12] introduces a boundary-enhanced loss as an assistant to learning exquisite object contours which saves the post-processing operations to refine the boundaries. Wei *et al.* [43] design pixel position aware loss to assign higher weights to edge positions which can help the network focus more on boundary regions.

2.2 Video Salient Object Detection

Existing VSOD methods can be divided into two categories: conventional models and deep learning models. Traditional methods rely on people's prior knowledge to extract hand-crafted features, such as color-contrast [29], background prior [46] and morphology cues [37]. Because low-level features have limited representational ability, these conventional methods are usually only suitable for specific scenarios. With the development of CNN, deep-learning-based VOSD models have recently achieved great success. Fan *et al.* [11] present a baseline model with a saliency-shift-aware convLSTM module to progressively integrate temporal information. Li *et al.* [27] propose a dual-stream network to enhance appearance features with motion features or motion saliency. Gu *et al.* [15] design a 3D pyramid constrained self-attention module to capture local motion cues of salient objects. Liu *et al.* [49] proposes a dynamic context-sensitive filtering module to dynamically generate context-sensitive convolution kernels and introduce a bidirectional fusion strategy to fuse spatial and temporal features. However, the remarkable performance achieved by these methods relies on densely annotated video datasets which cost considerable expense and time. Researchers explore addressing VSOD by using weak supervision or semi-supervision to relieve the burden of handcrafted labeling. Zhao *et al.* [50] designs multiple losses from the perspectives of boundary, structure, and front-background similarity to learn SOD by using fixation guided scribble annotations. Yan *et al.* [47] proposes to utilize a self-training method to generate pseudo labels to ease the effort of acquiring high-quality manually annotated data.

3 Our methods

3.1 Overview

To avoid low-quality pseudo labels that negatively affect VSOD, our method aims to progressively enhance the quality of pseudo labels and strictly filter out the noise in pseudo labels: (shown in Fig. 2)) We propose an Uncertainty-Guided Pseudo Label Generator (UGPLG) which uses inter-frame information to generate consecutive pseudo labels and enhances the learning of difficult scenarios to further improve the robustness of pseudo labels. 2) We introduce adversarial learning for noise suppression (NS-GAN) to screen out the regions in pseudo labels that do not conform to the distribution of ground truth, making pseudo labels more reliable.

The proposed UGPLG (shown in **Stage 1** of Fig. 2) follows the encoder-decoder architecture. The sharing encoder is based on ResNet50 [16] with ASPP [7]. It consists of a Cross-Frame Global Matching Module (CFGMM) and an Uncertainty-Aware Dual Decoder Module (UADDM). CFGMM aims to refer to the saliency cues in the same video to guarantee the temporal consistency of pseudo labels. And UADDM aims to enhance the learning of uncertain regions in pseudo labels to improve the robustness of pseudo labels. Equipped with the two modules, UGPLG can generate high-quality pseudo labels for complex scenerios.

The proposed NS-GAN (shown in **Stage 2** of Fig. 2) uses a video saliency model as the generator. In the process of adversarial learning, the discriminator can accurately distinguish between the ground truths and the predictions of the generator. Thus by using the discriminator to filter the noise for the pseudo labels, the training process of the generator is free from the negative effects of noise.

3.2 Uncertainty-Guided Pseudo Label Generator

Cross-Frame Global Matching. Generating pseudo labels for unlabeled video data is very dependent on temporal information because it contains motion cues and location information of the salient objects. The generated pseudo labels are temporally inconsistent if temporal information is not fully utilized. A straightforward utilization of temporal information [13] is computing the optical flow to warp labels to the unlabeled frames. However, optical flow generated from [19] [39] usually cannot accurately predict the geometric relationship between two frames within a long time interval.

Figure 2: The overall process of our method.

Therefore, to model the long-term temporal relationship, we select inter-frame global matching which
can ignore time intervals to build a bridge for the saliency information propagation between labeled
frames and unlabeled frames.

The whole propagation process is divided into two steps. In the first step, shown as **Stage 1** in Fig. 2,
given two video frames I_t and frame I_{t+n} in the same video, $F_t \in \mathbb{R}^{C \times (HW)}$ and $F_{t+n} \in \mathbb{R}^{C \times (HW)}$
represent the corresponding features from the sharing encoder. We aim to compute the similarity
matrix S between F_t and F_{t+n} by leveraging the non-local [2] mechanism:

$$S = (flat(F_t * L_t))^{\mathsf{T}} W flat(F_{t+n}) \in \mathbb{R}^{(HW) \times (HW)}, \tag{1}$$

where $W \in \mathbb{R}^{C \times C}$ means a weight matrix and $flat$ means the operation of flatten. Then we
normalize S in a column-wise way with a softmax function:

$$S^c = softmax(S) \in \mathbb{R}^{(HW) \times (HW)}. \tag{2}$$

Each column of the matrix S represents the relevance between a position on the unlabeled frame and
each position on the salient regions of the labeled frame. In the second step, we aim to find out the
features in F_{t+n} that are most correlated to salient objects in F_t. The transposed F_t is multiplied by
the similarity matrix S, and we can get the warped feature $\widetilde{F}_{t+n}$ propagated from F_t,

$$\widetilde{F}_{t+n} = F_t^{\mathsf{T}} S^c \in \mathbb{R}^{C \times (HW)}. \tag{3}$$

Each element of $\widetilde{F}_{t+n}$ represents the sum of the similarity of all positions on F_t and current position
on F_{t+n}. By concatenating $\widetilde{F}_{t+n}$ and F_{t+n}, we can achieve F_{fuse} which not only retains the spatial
information of current frame but also integrates the prior information about salient objects of other
frames in the same video. In this way, our UGPLG can generate temporally consistent pseudo labels.

$$F_{fuse} = [F_{t+n}, \widetilde{F}_{t+n}] \in \mathbb{R}^{2C \times (HW)}, \tag{4}$$

where $[\,\cdot\,,\,\cdot\,]$ means concatenation operation.

Uncertainty-aware Dual Decoder. Since conventional pseudo label generators are difficult to
make accurate predictions in difficult scenarios, to achieve robust pseudo labels, we design an
Uncertainty-Aware Dual Decoder Module (UADDM) to detect and utilize the uncertain regions in
pseudo labels to improve the performance of UGPLG. During training, when we feed the temporally

enhanced feature F_{fuse} to the UADDM, the auxiliary decoder makes a coarse prediction for I_{t+n} and it is supervised by L_{t+n}:

$$l_{aux} = l_{bce}(Aux(F_{fuse}), L_{t+n}) \in \mathbb{R}^{H \times W}, \tag{5}$$

where $Aux(\cdot)$ means the auxiliary decoder and L_{t+n} means the label of I_{t+n}. When a certain position of l_{aux} is greater than a fixed value, we consider the auxiliary decoder's prediction for that position to be uncertain. To improve the pseudo label generator's prediction of the uncertain regions, we obtain a set of weights to guide the main decoder to strengthen the learning of the uncertain regions.

$$weight = 1 + \alpha * \mathbb{I}(l_{aux} > T_{loss}) \in \mathbb{R}^{H \times W}, \tag{6}$$

$$l_{main} = weight * (l_{bce}(Main(I_{t+n}), L_{t+n}) + l_{iou}(Main(I_{t+n}), L_{t+n})), \tag{7}$$

where $\mathbb{I}(\cdot)$ is the indicator function, T_{loss} is a fixed threshold which is empirically set as 0.3, and $Main(\cdot)$ means main decoder. Thus, the pseudo labels generated by UGPLG can be more robust. It is noted that the auxiliary decoder is used only in the training stage. Apart from the standard BCELoss, we also introduce IoU loss to enable the model to focus on global structure. l_{bce} and l_{iou} are defined as:

$$l_{bce} = -\sum_{x=1}^{HW}\sum_{y=1}^{HW}(L(x,y)log(P(x,y)) + (1 - L(x,y))log(1 - P(x,y))), \tag{8}$$

$$l_{iou} = 1 - \frac{\sum_{x=1}^{HW}\sum_{y=1}^{HW}L(x,y)P(x,y)}{\sum_{x=1}^{HW}\sum_{y=1}^{HW}L(x,y) + P(x,y) - L(x,y)P(x,y)}, \tag{9}$$

where (x, y) means the location of the pixel, H, W means the height and width, $P(\cdot)$ means the prediction of the model, and $L(\cdot)$ means ground truth.

3.3 Adversarial Learning for noise suppression

Generative Adversarial Network. To further improve the reliability of pseudo labels, we propose a GAN-based noise suppression mechanism to filter out the regions that do not conform to the distribution of ground truth. The generator is trained to confuse the discriminator so that the distribution of the generator can be closer to the ground truth distribution. Correspondingly, in the process of adversarial learning, the ability of the discriminator also becomes stronger. In that case, the discriminator can accurately identify the noise that still exists in the pseudo labels. By suppressing the noise, we can ensure that pseudo labels are always providing positive guidance to the generator. The detailed structure of the generator is shown in Fig. 3, which is a classic two-stream network. The upper symmetrical branch is the RGB branch which learns information such as color and outline, and the lower branch is the optical flow branch which learns information such as position and semantics. The two symmetrical branches perform information fusion through a well-designed cross-modality information integration module CRM [22]. Since the information of the two branches is complementary, the fused features of the

Figure 3: The overall architecture of our video saliency model.

aggregation branch retain both local detailed information and global structural information. The generator takes both labeled and unlabeled data as input and outputs the predictions of the three branches. The encoder of each symmetrical branch is based on ResNet50 [16] with ASPP [7]. The decoder of the symmetrical branch consists of three convolutional layers, and the decoder of the aggregation branch has one more than that of the symmetrical branch. Similar to [18], our discriminator network is based on FCN [30]. It takes the prediction maps of the saliency model or ground truth labels as input and then outputs a probability map of size $H \times W \times 1$.

Training with labeled data. The generator and the discriminator are alternately trained on labeled data. For the training of the discriminator. We minimize the loss using:

$$l_D = l_{bce}(D(G_{fuse}(I_l, O_l)), M0) + l_{bce}(D(Y_l), M1), \tag{10}$$

where $G_{fuse}(\cdot)$ is the output of the aggregation branch in the saliency model, $M0$ is an all-zero matrix and $M1$ is an all-one matrix. I_l, O_l, and Y_l are the image, optical flow, and ground truth of the labeled frame, respectively. When the input is from ground truth, the discriminator output an all-one map, and when the input comes from the prediction map of the generator, the discriminator output an all-zero map.

To enable the generator to generate prediction maps with the similar distribution as ground truth, $G_{rgb}(\cdot)$, $G_{opt}(\cdot)$, $G_{fuse}(\cdot)$ are all supervised by standard BCEloss, and $G_{fuse}(\cdot)$ is additionally supervised by the adversarial loss l_{adv}. The total loss of the generator supervised by labeled data l_{GL} is defined as:

$$l_{GL} = l_{bce}(G_{rgb}(I_l), Y_l) + \delta(l_{bce}(G_{opt}(O_l), Y_l)) + l_{bce}(G_{fuse}(I_l, O_l), Y_l), \tag{11}$$

Where δ is a hyperparameter with its value of 0.2, and $G_{rgb}(\cdot)$, $G_{opt}(\cdot)$ mean the prediction map of RGB branch, Optical Flow branch, respectively. l_{adv} is defined as:

$$l_{adv} = -\sum log(D(G_{fuse}(I_l, O_l))). \tag{12}$$

With l_{adv}, the generator is trained to confuse the discriminator by maximizing the probability of the confidence map. Then the distribution of the prediction output by the generator gets closer to the distribution of ground truth.

Training with unlabeled data. Before using pseudo labels for supervised training, to avoid noise providing wrong guidance to the saliency model, we need to filter out the noise in pseudo labels at first. We feed the pseudo labels to the discriminator and obtain the corresponding confidence maps. Then the confidence map $D(PL_u)$ is directly used as the weight of l_{GU} which is the total loss of the generator supervised by unlabeled data:

$$l_{GU} = D(PL_u) * (l_{bce}(G_{rgb}(I_u), PL_u) + \delta(l_{bce}(G_{opt}(O_u), PL_u)) + l_{bce}(G_{fuse}(I_u, O_u), PL_u)), \tag{13}$$

Where the δ is the same as in Eq. 11. I_u, O_u, and PL_u are the image, optical flow, and pseudo label of the unlabeled frame, respectively. Because the weights of the noisy regions are very small, the noisy regions have little effect on the loss l_{GU}, thus avoiding the model learning from the noise in the pseudo-labels, ensuring the stability of saliency model training and helping the model to converge better. At last, the total loss of the generator is composed of the three types of loss:

$$l_G = l_{GL} + l_{adv} + l_{GU}. \tag{14}$$

4 Experiments

4.1 Datasets

To evaluate the performance of our method, we conduct experiments on five widely-used VSOD datasets for fair comparisons. **DAVIS** [35] is the most popular VSOD dataset, with 50 high-quality fully annotated video sequences. The whole dataset is split into 30 sequences (2079 frames) for training and 20 sequences (1376 frames) for testing. **FBMS** [32] includes 59 natural video sequences which contains 13860 frames while only 780 of them are sparsely annotated. The whole dataset is split into 29 sequences (353 frames) for training and 30 sequences (720 frames) for testing. **ViSal** [41] is the first specially collected dataset for VSOD. It contains 17 video sequences with 193 sparsely annotated frames. **MCL** [24] includes 9 video sequences about objects with fast movement. There are total 463 sparsely annotated frames. **SegTrack-V2** [25] is the earliest VOS dataset which contains 13 videos, with a total of 1025 annotated frames. For fair comparisons, we split the above datasets in the same splitting way in [11][12][13], and evaluate our proposed method on the test datasets of all the five datasets.

4.2 Experimental Setup

Evaluation Metrics. We use three universally-agreed criterions to evaluate our results, $i.e.$, mean absolute error (MAE) [34], max F-measure (F_β^{max}) [1] and structure-measure (S_α) [10]. MAE measures absolute pixel errors between saliency predictions and ground truth. F_β^{max} is combined with precision and recall. S_α evaluates the object-aware and region-aware structural similarity.

Implementation Details.   Our network is implemented on the Pytorch framework with $4 \times$ GTX 1080Ti GPU. We choose the train set of DAVIS and FBMS as our training set to train both Uncertainty-Guided Pseudo Label Generator (UGPLG) and Noise-Suppressed Generative Adversarial Network (NS-GAN). **For the training of UGPLG**, the initial learning rate is set as 0.005 and decays 0.1 times every 25 epochs with a batch size of 8. **For the training of NS-GAN**, the initial learning rate is set as 0.015 and decays 0.1 times every 20 epochs with a batch size of 12. Images are uniformly resized to 448×448. We adopt an SGD optimizer in which the momentum and weight decay are set to 0.9, 5e-4. **In the pre-train phase for NS-GAN**, we pretrain the RGB branch on DUTS [40] which is a commonly used static-image SOD dataset. The initial learning rate is set as 0.01 and decays 0.1 times every 30 epochs with a batch size of 40.

Table 1: Quantitative comparisons of S_α, F_β^{max} and MAE on five widely-used VSOD datasets. The best three results are shown in **boldface**, red, and blue fonts respectively. * means conventional methods. - means no available results. † means semi-supervised methods.

Methods	DAVIS [35]			FBMS [32]			ViSal [41]			MCL [24]			SegTrack-V2 [25]		
	$S_\alpha\uparrow$	$F_\beta^{max}\uparrow$	MAE↓	$S_\alpha\uparrow$	$F_\beta^{max}\uparrow$	MAE↓	$S_\alpha\uparrow$	$F_\beta^{max}\uparrow$	MAE↓	$S_\alpha\uparrow$	$F_\beta^{max}\uparrow$	MAE↓	$S_\alpha\uparrow$	$F_\beta^{max}\uparrow$	MAE↓
SGSP* [28]	0.692	0.655	0.138	0.661	0.630	0.172	0.706	0.677	0.165	0.670	0.605	0.102	0.681	0.673	0.124
SCOM* [8]	0.832	0.783	0.048	0.794	0.797	0.079	0.762	0.831	0.122	0.569	0.422	0.204	0.815	0.764	0.030
SCNN [38]	0.783	0.714	0.064	0.794	0.762	0.095	0.847	0.831	0.071	0.730	0.628	0.054	-	-	-
DLVS [42]	0.794	0.708	0.061	0.794	0.759	0.091	0.881	0.852	0.048	0.682	0.551	0.060	-	-	-
FGRN [26]	0.838	0.783	0.043	0.809	0.767	0.088	0.848	0.848	0.045	0.709	0.625	0.044	-	-	-
SSAV [11]	0.893	0.861	0.028	0.879	0.865	0.040	0.943	0.939	0.020	0.819	0.773	0.026	0.851	0.801	0.023
PCSA [15]	0.902	0.880	0.022	0.868	0.837	0.040	0.946	0.940	0.017	-	-	-	0.865	0.810	0.025
FDS [21]	0.922	0.912	0.020	0.888	0.875	0.041	0.903	0.869	0.029	0.866	0.823	0.024	0.849	0.773	0.028
DCF [49]	0.914	0.900	0.016	0.873	0.840	0.039	0.952	0.953	0.010	0.767	0.713	0.028	0.883	0.839	0.015
RCR† [47]	0.886	0.848	0.027	0.872	0.859	0.053	0.922	0.906	0.026	0.820	0.742	0.028	0.842	0.781	0.035
Ours†	0.914	0.900	0.019	0.899	0.892	0.027	0.930	0.926	0.019	0.860	0.822	0.018	0.844	0.778	0.027

4.3 Comparison with State-of-the-Art

As shown in Table. 1, we compare our methods with two conventional video salient object methods (remarked with *): SGSP [28]*, SCOM [8]*, and eight deep-learning based methods: SCNN [38], DLVS [42], FGRN [26], SSAV [11], PCSA [15], FDS [21], DCF [49], RCR [47]. To guarantee fair comparisons, we utilize the widely-used evaluation code provided by [11]. **First**, compared to the existing Semi-Supervised VSOD method RCR, our method significantly outperforms them on all datasets. Specifically, our method improves the MAE by 29.6%, 49.1%, 26.9%, 35.7% on DAVIS, FBMS, ViSal, and SegTrack-V2, respectively, using only 40% of their labeled data (568 versus 1406, shown in Table. 2). **Second**, compared to the fully supervised methods, our method achieves state-of-the-art on FBMS dataset, and achieves 98.7%, 97.2%, 99.9% and 92.7% of the SOTA accuracy on F_β^{max} on DAVIS, ViSal, MCL and SegTrack-V2, respectively. Despite our great performance, the number of ground truths we use is only 5% of current state-of-the-art fully-supervised methods. **Finally**, Fig. 4 shows visual comparisons to demonstrate the effectiveness of our proposed method to deal with complex scenarios, such as interference of complex background objects (1^{st} and 2^{nd} rows), similar foreground and background (3^{rd} and 4^{th} rows) and multiple objects (5^{rd} and 6^{th} rows). In these complex cases, it can be observed that our saliency model generalizes better than most VSOD models, which proves that our method can help the network to generate more robust predictions in a variety of complex scenarios.

Table 2: Quantitative comparisons with the number of training data used by state-of-the-art method DCF. The colummn Total calculates the sum of training video frames. † means semi-supervised methods.

Model	Video	Total
DCF	DAVSOD + DAVIS + VOS	11.5K
RCR†	**20%**(DAVIS + FBMS + VOS)	1406
Ours†	**10%**(DAVIVS) + FBMS	568

4.4 Ablation Studies

The Effectiveness of UGPLG.   Uncertainty-Guided Pseudo Label Generator (UGPLG) consists of Cross-Frame Global Matching Module(CFGMM) and Uncertainty-Aware Dual Decoder Module (UADDM), aiming to generate high-quality pseudo labels to guide the training of the saliency model.

| RGB | GT | Ours | RCR | FDS | DCF | SSAV | FGRN | SCNN | DLVS | SCOM | SGSP |

Figure 4: Qualitative comparisons of state-of-the-art methods. The ground truth (GT) is shown in the foremost column. The prediction map generated by our model in some difficult scenarios can approach or even exceed fully supervised methods.

We perform abundant experiments to validate the effectiveness of each component of UGPLG. As shown in Table. 4, case (1) refers to our baseline model which only retrains the encoder and the main decoder in UGPLG, and the generator in NS-GAN.

First, compared to the baseline, case (3) equips with CFGMM additionally. The great performance improvement achieved in case (3) powerfully demonstrates the effectiveness of CFGMM. To further prove the effectivity of CFGMM on introducing temporal information, we propose case (2) by removing the reference to the adjacent ground truth in CFGMM. Compared to case (3), case (2) encounters obvious performance degradation which demonstrates that our CFGMM can effectively utilize inter-frame information to generate high-quality pseudo labels. **Second**, to prove the effect of UADDM on strengthening the learning of difficult scenarios, we add UADDM (denoted as case (4)) based on case (3). Compared to case (3), the performance improves by 14% and 15% on DAVIS and MCL respectively in terms of MAE. **Moreover**, we directly test the performance of pseudo labels on the DAVIS dataset, shown in Table. 3. Specifically, we train case (1) to case (4) with 10% of the ground truth in DAVIS and then generate pseudo-labels for the remaining 90% of the dataset. The experimental results show that the modules in UGPLG can gradually improve the performance of pseudo labels, finally reaching an impressive performance of 0.007 on MAE. **At last**, we provide the corresponding visualization results in Fig. 5. It can be found that the pseudo labels are getting more consistent temporally. The boundaries of the pseudo labels are getting clearer and the content of salient objects is getting more complete.

Table 3: Quantitative comparisons on the quality of the pseudo labels generated for the training set of DAVIS.

| | UGPLG | | | DAVIS$_{train}$ | | |
Case	CFGMM-O	CFGMM	UADDM	$S_\alpha \uparrow$	$F_\beta^{max} \uparrow$	MAE$\downarrow$
(1)	-	-	-	0.937	0.927	0.016
(2)	✓	-	-	0.943	0.931	0.015
(3)	-	✓	-	0.952	0.942	0.012
(4)	-	✓	✓	0.958	0.951	0.007

Table 4: Quantitative comparisons of the performance of our method on the DAVIS and MCL datasets.

| | UGPLG | | | NS-GAN | | DAVIS | | | MCL | | |
Case	CFGMM-O	CFGMM	UADDM	GAN	NS	MAE$\downarrow$	$S_\alpha \uparrow$	$F_\beta^{max} \uparrow$	MAE$\downarrow$	$S_\alpha \uparrow$	$F_\beta^{max} \uparrow$
(1)	-	-	-	-	-	0.031	0.900	0.887	0.027	0.839	0.803
(2)	✓	-	-	-	-	0.030	0.902	0.887	0.027	0.842	0.807
(3)	-	✓	-	-	-	0.028	0.907	0.892	0.026	0.848	0.803
(4)	-	✓	✓	-	-	0.024	0.909	0.888	0.022	0.854	0.805
(5)	-	✓	✓	✓	-	**0.019**	0.910	0.894	0.019	**0.860**	0.815
(6)	-	✓	✓	✓	✓	**0.019**	**0.914**	**0.900**	**0.018**	**0.860**	**0.822**

The Effectiveness of NS-GAN. To highlight the importance of the noise suppression mechanism, we conduct a comparative experiment between an ordinary GAN [3] (denoted as case (5)) and NS-GAN (denoted as case (6)), shown in Table. 4. It can be observed that under the condition that case (5) has achieved a great performance, our NS-GAN still creates a further performance improvement which demonstrates the effectiveness of further suppressing the noise of high-quality pseudo labels. Case (6a) and case (6b) in Fig. 5 show the confidence maps generated by the discriminator at different training stages for case (4). As the training process goes on, the discriminator can accurately identify noise areas, ensuring that pseudo labels always provide positive guidance to the saliency model.

| RGB$_t$ | GT$_t$ | RGB$_{t+n}$ | case (2) | case (3) | case (4) | case (6a) | case (6b) |

Figure 5: Case (2) to case (4) represent the pseudo labels generated by case (2) to case (4). Case (6a) and case (6b) are the confidence maps generated for case (4) by the discriminator of NS-GAN in the early and middle stages of training process, respectively.

Table 5: Quantitative comparisons on different ratios of GT to PL. The best three results are shown in **boldface**, red, and blue fonts, respectively. The configuration S contains 5% GT of DAVIS and 50% GT of FBMS. The configuration M contains 10% GT of DAVIS and 100% GT of FBMS. The configuration L contains 30% GT of DAVIS and 100% GT of FBMS. We generate pseudo labels for all unused data in DAVIS and FBMS. All proportional experiments are divided according to the proportion of the pseudo labels for training. All experiments involving pseudo labels are equipped with noise suppression strategy. GT means ground truth and PL means pseudo labels.

Dataset	Metrics	\multicolumn{4}{c}{S}				\multicolumn{4}{c}{M}				\multicolumn{4}{c}{L}			
		0%	20%	50%	100%	0%	20%	50%	100%	0%	20%	50%	100%
DAVIS	$S_\alpha \uparrow$	0.873	0.899	0.911	0.911	0.880	0.902	0.914	0.910	0.894	0.903	0.915	**0.918**
	$F_\beta^{max} \uparrow$	0.847	0.880	0.895	0.901	0.851	0.882	0.900	0.895	0.867	0.878	0.901	**0.905**
	MAE$\downarrow$	0.040	0.022	0.019	**0.018**	0.034	0.023	0.019	0.020	0.032	0.023	**0.018**	**0.018**
FBMS	$S_\alpha \uparrow$	0.870	0.885	0.893	**0.897**	0.887	0.889	0.889	0.892	0.885	0.891	0.896	0.891
	$F_\beta^{max} \uparrow$	0.860	0.880	0.890	0.893	0.873	0.879	0.892	0.894	0.877	0.881	**0.901**	0.893
	MAE$\downarrow$	0.054	0.034	0.030	0.028	0.043	0.032	**0.027**	0.031	0.041	0.032	0.031	0.032

Different Ratios of Ground Truth to Pseudo Labels. We set up multiple comparative experiments to verify the effectiveness of our method on different ratios of ground truths (GT) to pseudo labels (PL). Table. 5 shows that in all three configurations, our method using 50% pseudo labels already achieves the results that are comparable to the fully-supervised VSOD methods, which fully demonstrates the superiority of our method. Finally, since the training time with 90% pseudo-labels is more than double that with 50% pseudo labels and considering the trade-off between performance and training time, we chose the configuration M using 50% pseudo labels as our final configuration.

5 Conclusion

In this paper, we strive to face the challenge of error-prone pseudo labels are usually detrimental to final detection. We propose an Uncertainty-Guided Pseudo Label Generator (UGPLG), which makes full use of temporal information to generate temporally consistent pseudo labels, and enhances the learning of uncertain regions to improve the robustness of pseudo labels. To screen out the noise that still exists in the pseudo labels, we further propose an adversarial learning strategy for noise suppression to ensure that the pseudo labels can always guide the network positively. Experimental results demonstrate that our method outperforms the existing semi-supervised VSOD method and partial fully-supervised VSOD model while using only 5% labeled data used by the SOTA fully-supervised methods.

References

[1] Radhakrishna Achanta, Sheila Hemami, Francisco Estrada, and Sabine Susstrunk. Frequency-tuned salient region detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1597–1604.

330   IEEE, 2009.

[2] Xiaolong Wang, Ross Girshick, Abhinav Gupta, and Kaiming He. Non-local neural networks. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7794–7803, 2018.

[3] Pauline Luc, Camille Couprie, Soumith Chintala, and Jakob Verbeek. Semantic segmentation using adversarial networks. In *NIPS Workshop on Adversarial Training (NIPS)*, 2016.

[4] Wei-Chih Hung, Yi-Hsuan Tsai, Yan-Ting Liou, Yen-Yu Lin, and Ming-Hsuan Yang. Adversarial learning for semi-supervised semantic segmentation. In *British Machine Vision Conference (BMVC)*, 2018.

[5] Ali Borji and Laurent Itti. Exploiting local and global patch rarities for saliency detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 478–485. IEEE, 2012.

[6] Liang-Chieh Chen, Raphael Gontijo Lopes, Bowen Cheng, Maxwell D Collins, Ekin D Cubuk, Barret Zoph, Hartwig Adam, and Jonathon Shlens. Naive-student: Leveraging semi-supervised learning in video sequences for urban scene segmentation. In *European Conference on Computer Vision (ECCV)*, pages 695–714. Springer, 2020.

[7] Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. In *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 40(4):834–848, 2017.

[8] Yuhuan Chen, Wenbin Zou, Yi Tang, Xia Li, Chen Xu, and Nikos Komodakis. Scom: Spatiotemporal constrained optimization for salient object detection. In *IEEE Transactions on Image Processing (TIP)*, 27(7):3345–3357, 2018.

[9] Zijun Deng, Xiaowei Hu, Lei Zhu, Xuemiao Xu, Jing Qin, Guoqiang Han, and Pheng-Ann Heng. R3net: Recurrent residual refinement network for saliency detection. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 684–690. AAAI Press Menlo Park, CA, USA, 2018.

[10] Deng-Ping Fan, Ming-Ming Cheng, Yun Liu, Tao Li, and Ali Borji. Structure-measure: A new way to evaluate foreground maps. In *International Conference on Computer Vision (ICCV)*, pages 4548–4557, 2017.

[11] Deng-Ping Fan, Wenguan Wang, Ming-Ming Cheng, and Jianbing Shen. Shifting more attention to video salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8554–8564, 2019.

[12] Mengyang Feng, Huchuan Lu, and Errui Ding. Attentive feedback network for boundary-aware salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1623–1632, 2019.

[13] Raghudeep Gadde, Varun Jampani, and Peter V Gehler. Semantic video cnns through representation warping. In *International Conference on Computer Vision (ICCV)*, pages 4453–4462, 2017.

[14] Aditya Ganeshan, Alexis Vallet, Yasunori Kudo, Shin-ichi Maeda, Tommi Kerola, Rares Ambrus, Dennis Park, and Adrien Gaidon. Warp-refine propagation: Semi-supervised auto-labeling via cycle-consistency. In *International Conference on Computer Vision (ICCV)*, pages 15499–15509, 2021.

[15] Yuchao Gu, Lijuan Wang, Ziqin Wang, Yun Liu, Ming-Ming Cheng, and Shao-Ping Lu. Pyramid constrained self-attention network for fast video salient object detection. In *AAAI conference on artificial intelligence (AAAI)*, volume 34, pages 10869–10876, 2020.

[16] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

[17] Qibin Hou, Ming-Ming Cheng, Xiaowei Hu, Ali Borji, Zhuowen Tu, and Philip HS Torr. Deeply supervised salient object detection with short connections. In *Conference on Computer Cision and Pattern Recognition (CVPR)*, pages 3203–3212, 2017.

[18] Wei-Chih Hung, Yi-Hsuan Tsai, Yan-Ting Liou, Yen-Yu Lin, and Ming-Hsuan Yang. Adversarial learning for semi-supervised semantic segmentation. In *British Machine Vision Conference (BMVC)*, 2018.

[19] Eddy Ilg, Nikolaus Mayer, Tonmoy Saikia, Margret Keuper, Alexey Dosovitskiy, and Thomas Brox. Flownet 2.0: Evolution of optical flow estimation with deep networks. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2462–2470, 2017.

[20] Laurent Itti. Automatic foveation for video compression using a neurobiological model of visual attention. In *IEEE Transactions on Image Processing (TIP)*, 13(10):1304–1318, 2004.

[21] Ge-Peng Ji, Keren Fu, Zhe Wu, Deng-Ping Fan, Jianbing Shen, and Ling Shao. Full-duplex strategy for video object segmentation. In *International Conference on Computer Vision (ICCV)*, pages 4922–4933, 2021.

[22] Wei Ji, Jingjing Li, Shuang Yu, Miao Zhang, Yongri Piao, Shunyu Yao, Qi Bi, Kai Ma, Yefeng Zheng, Huchuan Lu, et al. Calibrated rgb-d salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9471–9481, 2021.

[23] Huaizu Jiang, Jingdong Wang, Zejian Yuan, Yang Wu, Nanning Zheng, and Shipeng Li. Salient object detection: A discriminative regional feature integration approach. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2083–2090, 2013.

[24] Hansang Kim, Youngbae Kim, Jae-Young Sim, and Chang-Su Kim. Spatiotemporal saliency detection for video sequences based on random walk with restart. In *IEEE Transactions on Image Processing (TIP)*, 24(8):2552–2564, 2015.

[25] Fuxin Li, Taeyoung Kim, Ahmad Humayun, David Tsai, and James M Rehg. Video segmentation by tracking many figure-ground segments. In *International Vonference on Vomputer Vision (ICCV)*, pages 2192–2199, 2013.

[26] Guanbin Li, Yuan Xie, Tianhao Wei, Keze Wang, and Liang Lin. Flow guided recurrent neural encoder for video salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3243–3252, 2018.

[27] Haofeng Li, Guanqi Chen, Guanbin Li, and Yizhou Yu. Motion guided attention for video salient object detection. In *International Conference on Computer Vision (ICCV)*, pages 7274–7283, 2019.

[28] Zhi Liu, Junhao Li, Linwei Ye, Guangling Sun, and Liquan Shen. Saliency detection for unconstrained videos using superpixel-level graph and spatiotemporal propagation. In *IEEE Transactions on Circuits and Systems for Video Technology (TCSVT)*, 27(12):2527–2542, 2016.

[29] Zhi Liu, Xiang Zhang, Shuhua Luo, and Olivier Le Meur. Superpixel-based spatiotemporal saliency detection. In *IEEE Transactions on Circuits and Systems for Video Technology (TCSVT)*, 24(9):1522–1540, 2014.

[30] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3431–3440, 2015.

[31] Dwarikanath Mahapatra, Syed Omer Gilani, and Mukesh Kumar Saini. Coherency based spatio-temporal saliency detection for video object segmentation. In *IEEE Journal of Selected Topics in Signal Processing (JSTSP)*, 8(3):454–462, 2014.

[32] Peter Ochs, Jitendra Malik, and Thomas Brox. Segmentation of moving objects by long term video analysis. In *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 36(6):1187–1200, 2013.

[33] Yingwei Pan, Ting Yao, Houqiang Li, and Tao Mei. Video captioning with transferred semantic attributes. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6504–6512, 2017.

[34] Federico Perazzi, Philipp Krähenbühl, Yael Pritch, and Alexander Hornung. Saliency filters: Contrast based filtering for salient region detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 733–740. IEEE, 2012.

[35] Federico Perazzi, Jordi Pont-Tuset, Brian McWilliams, Luc Van Gool, Markus Gross, and Alexander Sorkine-Hornung. A benchmark dataset and evaluation methodology for video object segmentation. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 724–732, 2016.

[36] Xuebin Qin, Zichen Zhang, Chenyang Huang, Chao Gao, Masood Dehghan, and Martin Jagersand. Basnet: Boundary-aware salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7479–7489, 2019.

[37] Esa Rahtu, Juho Kannala, Mikko Salo, and Janne Heikkilä. Segmenting salient objects from images and videos. In *European conference on computer vision (ECCV)*, pages 366–379. Springer, 2010.

[38] Yi Tang, Wenbin Zou, Zhi Jin, Yuhuan Chen, Yang Hua, and Xia Li. Weakly supervised salient object detection with spatiotemporal cascade neural networks. In *IEEE Transactions on Circuits and Systems for Video Technology (TCSVT)*, 29(7):1973–1984, 2018.

[39] Zachary Teed and Jia Deng. Raft: Recurrent all-pairs field transforms for optical flow. In *European Conference on Computer Vision (ECCV)*, pages 402–419. Springer, 2020.

[40] Lijun Wang, Huchuan Lu, Yifan Wang, Mengyang Feng, Dong Wang, Baocai Yin, and Xiang Ruan. Learning to detect salient objects with image-level supervision. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 136–145, 2017.

[41] Wenguan Wang, Jianbing Shen, and Ling Shao. Consistent video saliency using local gradient flow optimization and global refinement. In *IEEE Transactions on Image Processing (TIP)*, 24(11):4185–4196, 2015.

[42] Wenguan Wang, Jianbing Shen, and Ling Shao. Video salient object detection via fully convolutional networks. In *IEEE Transactions on Image Processing (TIP)*, 27(1):38–49, 2017.

[43] Jun Wei, Shuhui Wang, and Qingming Huang. F^{3}net: fusion, feedback and focus for salient object detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pages 12321–12328, 2020.

[44] Hefeng Wu, Guanbin Li, and Xiaonan Luo. Weighted attentional blocks for probabilistic object tracking. In *The Visual Computer*, 30(2):229–243, 2014.

[45] Zhe Wu, Li Su, and Qingming Huang. Cascaded partial decoder for fast and accurate salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3907–3916, 2019.

[46] Tao Xi, Wei Zhao, Han Wang, and Weisi Lin. Salient object detection with spatiotemporal background priors for video. In *IEEE Transactions on Image Processing (TIP)*, 26(7):3425–3436, 2016.

[47] Pengxiang Yan, Guanbin Li, Yuan Xie, Zhen Li, Chuan Wang, Tianshui Chen, and Liang Lin. Semi-supervised video salient object detection using pseudo-labels. In *International Conference on Computer Vision (ICCV)*, pages 7284–7293, 2019.

[48] Qiong Yan, Li Xu, Jianping Shi, and Jiaya Jia. Hierarchical saliency detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1155–1162, 2013.

[49] Miao Zhang, Jie Liu, Yifei Wang, Yongri Piao, Shunyu Yao, Wei Ji, Jingjing Li, Huchuan Lu, and Zhongxuan Luo. Dynamic context-sensitive filtering network for video salient object detection. In *International Conference on Computer Vision (ICCV)*, pages 1553–1563, 2021.

[50] Wangbo Zhao, Jing Zhang, Long Li, Nick Barnes, Nian Liu, and Junwei Han. Weakly supervised video salient object detection. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 16826–16835, 2021.