ODC: Orthogonal Drift Correction for Improved Text-to-Image Semantic Alignment at Inference

Abstract

Text-to-image models have achieved remarkable success in generating high-quality images from textual descriptions. However, they often struggle with "semantic drift," where the generated output fails to precisely align with complex or nuanced text prompts. While recent approaches have attempted to address semantic errors regarding attribute binding or object presence, there remains a gap for a more holistic method that addresses these issues by directly refining the text embeddings of the initial user prompt. In this work, we introduce Orthogonal Drift Correction (ODC), an inference-time guidance method designed to mitigate semantic drift without requiring model retraining or additional user inputs. ODC guides image generation through a two-stage process. In the first stage, it identifies the semantic drift by evaluating the initially generated image against the user prompt in a shared vision-language embedding space. It then isolates the component of this drift vector that is orthogonal to the prompt's direction and translates it back into text via a vocabulary-based surrogate mechanism. In the second stage, it produces refined text conditioning for a second generation pass by feeding both the initial text embedding and the re-embedded drift representation into an adaptive rank-reduced concept removal module. Our experiments demonstrate the effectiveness of ODC in enhancing prompt-image alignment, yielding images that more accurately reflect detailed compositional instructions. As a plug-and-play module, ODC offers a practical and efficient method for improving the reliability of state-of-the-art text-to-image models.

1 Introduction

Modern text-to-image (T2I) models have opened new creative possibilities, allowing people to generate compelling images that would have been impossible to generate just a few years ago. Models such as Stable Diffusion (Rombach et al., 2022a), Imagen (Saharia et al., 2022), and DALL-E 2 (Ramesh et al., 2022) have demonstrated an unprecedented ability to synthesize visually compelling and artistic images from natural language descriptions, unlocking wide-ranging applications across numerous domains.

However, despite these profound capabilities, current state-of-the-art T2I models frequently fall short in generating images that precisely align with the full semantic meaning and composition of their input text prompts. This lack of precise semantic alignment, a phenomenon we term "semantic drift", pertains to the frequent failure of these models to precisely adhere to user prompts. For instance, they often misinterpret complex compositional instructions, leading to incorrect attribute binding (e.g., wrong material on objects), catastrophic neglect (Chefer et al., 2023) (omitting subjects from the prompt), or a failure to adhere to specified spatial relationships. This alignment gap forces users into frustrating trial-and-error prompt engineering, a practice that underscores the limitations of such models in accurately interpreting semantic intent.

This difficulty largely stems from how T2I models process textual information. State-of-the-art T2I diffusion models employ a U-Net architecture with cross-attention layers (Rombach et al., 2022a), which are crucial for fusing visual and textual features. While these layers encode rich semantic relations, the interaction can sometimes skew feature representations, causing semantic misalignment between the input and output. A variety of approaches have been proposed to address this problem. Fine-tuning methods like DreamBooth (Ruiz et al., 2023) and CoMat (Jiang et al., 2024), personalize models for specific subjects but can be

computationally demanding. Architectural expansions like ControlNet (Zhang et al., 2023) and T2I-Adapter (Mou et al., 2024) provide explicit spatial control through auxiliary inputs but require additional inputs and specialized training. Alternatively, a growing class of methods focuses on training-free, inference-time manipulation of attention maps or latent representations. Techniques such as Attend-and-Excite (Chefer et al., 2023), CONFORM (Meral et al., 2024), and ToMe (Hu et al., 2024) directly intervene in the generation process to ensure robust semantic binding and alignment. While effective for specific tasks such as subject presence and attribute binding, they do not address the misalignment caused by imperfect initial text embeddings. This body of work reveals a clear gap for a method that can efficiently improve text-image alignment by directly correcting the text embedding to resolve complex compositional failures.

In this paper, we address this gap by introducing Orthogonal Drift Correction (ODC), a unique inference-time technique that directly corrects the text conditioning vector to prevent semantic drift. Our approach is based on the key insight that semantic drift originates from the components of the computed text embedding that are orthogonal to the prompt's true semantic direction. ODC guides the image generation process through a two-stage mechanism. First, it generates an initial candidate image. Then, it leverages the shared embedding space of a pre-trained vision-language model, to identify the semantic error vector between the generated image and the prompt. Crucially, instead of using the entire error, it isolates its orthogonal component via vector rejection. This component, which intuitively represents the "off-topic" deviation, is then removed from the initial text embedding. The resulting purified embedding guides a second generation pass, producing a final image with substantially higher prompt-image alignment. Our contributions can be summarized as follows:

- We identify *orthogonal semantic drift* in text embeddings as a key source of prompt-image misalignment in text-to-image models, and propose a model-agnostic, training-free, inference-time method that corrects the text conditioning embeddings without modifying the diffusion process or requiring fine-tuning.

- We propose an adaptive rank-reduced concept removal strategy that refines the text conditioning by processing the initial text embedding alongside a re-embedded drift representation, obtained via a vocabulary-based surrogate mechanism.

- We introduce CoalBench-300 (**CO**mpositional **AL**ignment Benchmark), 300 synthetically generated prompts curated to rigorously probe semantic drift and prompt-image alignment. To support our method, we curate a large-scale vocabulary of over 300,000 words and phrases, compiled from multiple sources and refined through several preprocessing steps, to effectively capture and mitigate semantic drift.

2 Background & Related Work

We provide the necessary context for understanding our proposed method below.

Prompt-Image Alignment. Prompt-image alignment refers to the faithfulness of a generated image to the full semantic meaning and compositional structure of its input text prompt. While the goal of Text-to-Image (T2I) models is to translate natural language into visually aligned results, achieving precise alignment in terms of the spatial composition, complex layouts, poses, shapes, and forms described in a prompt remains a significant challenge (Huang et al., 2023; Saharia et al., 2022). This often necessitates numerous trial-and-error cycles from users to achieve their desired output. Our method contributes to improving prompt-image alignment without requiring these cycles.

Text-to-Image Models. The dominant architecture in modern T2I generation is the Latent Diffusion Model (LDM) (Rombach et al., 2022b). Unlike earlier diffusion models that operated in the high-dimensional pixel space (Ho et al., 2020), LDMs perform the computationally intensive denoising process in the compressed latent space of a pre-trained variational autoencoder (VAE). This significantly reduces computational overhead while maintaining high-fidelity output.

The core of an LDM's denoising process is a U-Net architecture (Ronneberger et al., 2015), which comprises a series of downsampling and upsampling blocks with residual connections. Interspersed within this network are self-attention layers, which capture global spatial dependencies, and crucially, cross-attention layers. These cross-attention layers are the primary mechanism through which textual guidance is integrated into

the image generation process. They allow the model to attend to different parts of the text prompt at each denoising step, conditioning the visual features being generated. More advanced models like Stable Diffusion XL (SDXL) (Podell et al., 2023) enhance this architecture with a larger U-Net and a dual text encoder setup to achieve superior performance.

Text Embeddings and Conditioning. The journey from a text prompt to a guiding signal begins with tokenization, where the input string is converted into a sequence of discrete tokens. These tokens are then mapped to high-dimensional embedding vectors. This sequence of vectors is processed by a powerful text encoder, such as the CLIP text encoder (Radford et al., 2021) or a larger language model like T5 (Raffel et al., 2020), to produce the final conditioning embedding.

This text embedding conditions the denoising U-Net at multiple resolutions via the cross-attention mechanism. At each cross-attention layer, the intermediate visual features (the query) attend to the text embedding (the key and value). This process generates spatial attention maps that define a rich semantic relationship between image regions and prompt tokens, critically influencing the final image's composition. Our method, intervenes at the very beginning of this pipeline. It is plugged into the process by modifying the conditioning embedding *before* it is passed to the U-Net, thereby correcting the guidance signal at its source.

Previous Attempts to Improve Alignment. The challenge of prompt-image misalignment has inspired a wide variety of solutions. Prior work can be broadly categorized into three categories: prompt engineering, training-based methods, and inference-time guidance.

Prompt Engineering: At the most fundamental level, users engage in manual prompt engineering, iteratively refining text to achieve desired results. More structured approaches include prompt weighting, which allows users to amplify or attenuate the semantic influence of specific words, and the use of negative prompts. Negative prompts modify the unconditional embedding used in classifier-free guidance to explicitly steer the model away from unwanted concepts (Ho & Salimans, 2022). The efficacy of these prompts depends heavily on the capacity of the text encoder to capture complex relationships. Saharia et al. (2022) demonstrated that scaling the frozen text encoder (e.g., T5-XXL) yields significantly larger improvements in alignment than scaling the diffusion model itself. Beyond manual refinement and architectural scaling, researchers have also explored optimizing the input space directly to represent specific concepts. Textual Inversion (Gal et al., 2022) optimizes new pseudo-words within the embedding space of a frozen model to capture unique subjects or styles, acting as a bridge between the user's intent and the model's vocabulary.

Training-Based Methods: A powerful but resource-intensive approach involves fine-tuning the model. DreamBooth (Ruiz et al., 2023) fine-tunes the entire diffusion model to bind a unique identifier with a specific subject, allowing for the generation of that subject in novel contexts with high fidelity. To mitigate the high computational cost of full fine-tuning, Low-Rank Adaptation (LoRA) (Hu et al., 2022) freezes pre-trained weights and injects trainable rank-decomposition matrices, enabling efficient adaptation to new tasks or styles with minimal parameter updates. While these methods focus on personalization, other works target general alignment failures such as concept ignorance. CoMat (Jiang et al., 2024) introduces an end-to-end fine-tuning strategy that leverages an image-to-text captioning model to minimize the discrepancy between the prompt and the generated image's caption, aligning the model to revisit ignored concepts and correct attribute mismapping.

Inference-Time Guidance: This category includes methods that, like ours, operate at inference time without modifying model weights. The foundational technique in this category is Classifier-Free Guidance (CFG) (Ho & Salimans, 2022), which mixes conditional and unconditional score estimates to trade off sample diversity for higher text alignment. Building on this, Chung et al. (2024) identified that standard CFG suffers from "off-manifold" issues that harm editability and alignment, proposing CFG++ to correct the sampling trajectory to remain on the data manifold. Beyond sampling adjustments, several methods intervene specifically in the cross-attention layers or latent optimization during inference to correct semantic failures. Hertz et al. (2022) introduced Prompt-to-Prompt, which injects cross-attention maps from a source generation into a new generation to maintain structural layout while editing semantic content. To address "catastrophic neglect", Attend-and-Excite (Chefer et al., 2023) optimizes the latent at each timestep to ensure all subject tokens maximize their attention activations. Similarly, CONFORM (Meral et al., 2024) applies a contrastive objective during inference to segregate objects in attention maps while keeping attributes close to their

subjects. Taking a different approach to binding, Hu et al. (2024) proposed Token Merging (ToMe), which merges relevant tokens into a composite token and iteratively updates this embedding during the early denoising steps using semantic binding and entropy losses. Finally, rather than optimizing the denoising path, InitNO (Guo et al., 2024) focuses on the initialization phase. It partitions the initial latent space into valid and invalid regions based on attention conflict scores and optimizes the initial noise vector to ensure it is predisposed toward semantically faithful generation before denoising begins.

Crucially, our work differs from existing inference-time approaches in its point of intervention. Whereas prior methods act by altering the internal dynamics of the U-Net denoising process, our approach is simpler and more direct: we refine the conditioning embeddings before diffusion begins. In contrast to training-based approaches, our method is entirely training-free, requiring no fine-tuning or additional optimization. Similarly, unlike attention-manipulation techniques, our intervention operates directly on the text embeddings, making it straightforward to implement and agnostic to the choice of U-Net architecture. By correcting semantic drift at its source, ODC provides a generalizable and principled way to correct semantic drift at its source, improving the alignment and reliability of pre-trained text-to-image models.

3 Orthogonal Drift Correction

Our proposed method, Orthogonal Drift Correction (ODC), is an inference-time guidance technique designed to enhance the semantic alignment of text-to-image models. The central hypothesis is that suboptimal prompt alignment, or *semantic drift*, stems from the components of the initial text embedding that are orthogonal to the prompt's primary semantic direction. ODC operates in a two-stage process. An initial image is generated and then evaluated against the prompt in a shared vision-language embedding space. The identified semantic error is then used to refine the initial text embedding for a second, more accurate generation pass.

3.1 Notations

Let p_{txt} denote the input text prompt. The text-to-image model consists of two text encoders, a token-level encoder $\mathcal{E}_{\text{tok}}$ and a pooled encoder $\mathcal{E}_{\text{pool}}$, together with an image generator $\mathcal{G}$ (typically a U-Net implementing a reverse diffusion process). The standard generation process first encodes the text prompt as

$$\mathbf{E}_p = \mathcal{E}_{\text{tok}}(p_{\text{txt}}), \qquad \mathbf{e}_p = \mathcal{E}_{\text{pool}}(p_{\text{txt}}), \tag{1}$$

where $\mathbf{E}_p \in \mathbb{R}^{L \times H}$ is the sequence of per-token embeddings and $\mathbf{e}_p \in \mathbb{R}^H$ is a pooled sentence-level vector. The image generator then produces an initial image I conditioned on both representations:

$$I = \mathcal{G}(\mathbf{E}_p, \mathbf{e}_p). \tag{2}$$

To evaluate and correct for semantic drift, we employ a pre-trained vision–language model (VLM), denoted $\mathcal{E}_{\text{VLM}}$, which embeds both text and images into a shared multimodal space.

3.2 The Orthogonal Drift Correction (ODC) Algorithm

The ODC algorithm consists of two main stages, comprising six sequential steps in total. These steps are described in detail below and summarized in Algorithm 1. An overview of the process is illustrated in Figure 1.

Step 1: Initial Image Generation. First, an initial image I is generated using the standard process. The text prompt p_{txt} is encoded by two complementary text encoders: one produces a sequence of per-token embeddings $\mathbf{E}_p$, while the other yields a pooled sentence-level representation $\mathbf{e}_p$. Both conditioning signals are then provided to the image generator $\mathcal{G}$ to synthesize the initial image.

$$\mathbf{E}_p = \mathcal{E}_{\text{tok}}(p_{\text{txt}}), \qquad \mathbf{e}_p = \mathcal{E}_{\text{pool}}(p_{\text{txt}}), \qquad I = \mathcal{G}(\mathbf{E}_p, \mathbf{e}_p). \tag{3}$$

Step 2: Semantic Drift Vector Calculation. Next, we quantify the semantic discrepancy between the generated image I and the original prompt p_{txt}. We use $\mathcal{E}_{\text{VLM}}$ to project both onto a shared embedding space. The *semantic drift vector*, $\mathbf{v}_{\text{drift}}$, captures the discrepancy between these two embeddings. This vector

Figure 1: The workflow of Orthogonal Drift Correction (ODC). In the first stage, vocabulary items that best capture the orthogonal drift vector are retrieved. In the second stage, these vocabulary items are used in a concept removal operation, producing embeddings that better align with the user's text prompt and serve as input for the final image generation.

essentially encodes the semantic error, i.e., the direction and magnitude of the deviation of the image's content from the prompt's intent as perceived by the VLM.

$$\mathbf{v}_{\text{text}} = \mathcal{E}_{\text{VLM}}(p_{\text{txt}}), \qquad \mathbf{v}_{\text{img}} = \mathcal{E}_{\text{VLM}}(I), \qquad \mathbf{v}_{\text{drift}} = \mathbf{v}_{\text{img}} - \mathbf{v}_{\text{text}}. \tag{4}$$

Step 3: Orthogonal Drift Component Isolation and Vocabulary Retrieval. For $\mathbf{v}_{\text{drift}}$, we hypothesize that the most detrimental error components are those that introduce concepts extraneous to the prompt, which correspond to the direction orthogonal to the prompt's own embedding, $\mathbf{v}_{\text{text}}$. To isolate those components, we estimate the vector rejection of $\mathbf{v}_{\text{drift}}$ from $\mathbf{v}_{\text{text}}$. This is achieved by subtracting the projection of $\mathbf{v}_{\text{drift}}$ onto $\mathbf{v}_{\text{text}}$ from $\mathbf{v}_{\text{drift}}$ itself. The projection, $\mathbf{v}_{\text{proj}}$, is calculated as

$$\mathbf{v}_{\text{proj}} = \left(\frac{\mathbf{v}_{\text{drift}} \cdot \mathbf{v}_{\text{text}}}{\|\mathbf{v}_{\text{text}}\|^2} \right) \mathbf{v}_{\text{text}}. \tag{5}$$

The *orthogonal drift vector*, $\mathbf{v}_{\text{orth}}$, is then the rejection:

$$\mathbf{v}_{\text{orth}} = \mathbf{v}_{\text{drift}} - \mathbf{v}_{\text{proj}}. \tag{6}$$

To obtain a discrete, textual surrogate for $\mathbf{v}_{\text{orth}}$, we retrieve candidate terms from a custom vocabulary. To this end, we construct a large-scale vocabulary retrieval dataset designed to cover both visually grounded concepts and general linguistic phrases. The dataset construction process involves several stages of aggregation and filtering. We provide details of the dataset and its construction in Section 4.1. Each vocabulary item w is associated with an embedding $\mathbf{e}_w$, and cosine similarities are computed as:

$$s(w) = \frac{\mathbf{v}_{\text{orth}} \cdot \mathbf{e}_w}{\|\mathbf{v}_{\text{orth}}\| \, \|\mathbf{e}_w\|}. \tag{7}$$

The top-k terms with the highest similarity scores are selected, forming a discrete approximation of $\mathbf{v}_{\text{orth}}$. We denote this retrieved set of tokens as $\mathcal{S}_{\text{orth}}$.

Step 4: Approximating Orthogonal Drift in Text Encoder Space. The retrieved items $\mathcal{S}_{\text{orth}}$ are then re-embedded via the text encoders of the text-to-image model, yielding a per-token embedding matrix $\mathbf{E}_i$ and a pooled embedding vector $\mathbf{e}_i$ for each item $w_i \in \mathcal{S}_{\text{orth}}$. Since $\mathcal{S}_{\text{orth}}$ typically contains more than one item, we combine them using a softmax-weighted pooling to obtain equivalent representative embeddings:

$$\mathbf{E}_{\text{orth}} = \sum_i \beta_i \, \mathbf{E}_i, \qquad \mathbf{e}_{\text{orth}} = \sum_i \beta_i \, \mathbf{e}_i, \tag{8}$$

where the weights β_i are defined by the normalized cosine similarity scores:

$$\beta_i = \frac{\exp(s(w_i))}{\sum_j \exp(s(w_j))}. \tag{9}$$

This results in a pair $(\mathbf{E}_{\text{orth}}, \mathbf{e}_{\text{orth}})$ that represents the surrogate set in the embedding space of the text encoders of our T2I model. These representative embeddings, in addition to the original embeddings, are supplied to the concept removal module.

Step 5: Adaptive Rank-Reduced Concept Removal. To remove undesired semantic concepts from the text embeddings, we employ an adaptive rank-reduction approach that automatically identifies and retains the meaningful semantic components while filtering out noise. We denote this operator by $\mathcal{R}$, and the procedure of its computation is summarized in Algorithm 2.

Given embedding tensors $\mathbf{E}_1, \mathbf{E}_2 \in \mathbb{R}^{B \times L \times H}$ (batch size B, sequence length L, hidden dimension H), we first determine the semantic rank of $\mathbf{E}_2$ through QR decomposition. For each batch element:

$$\mathbf{E}_2^T = \mathbf{QR}, \tag{10}$$

where $\mathbf{Q}$ contains orthonormal basis vectors. We identify semantically meaningful components by selecting basis vectors whose relative magnitude exceeds $\zeta = 1\%$ of the primary component:

$$k = \max \left\{ i : \frac{|r_{ii}|}{|r_{11}|} > \zeta \right\}, \tag{11}$$

where r_{ii} are the diagonal elements of $\mathbf{R}$. We selected this threshold empirically to separate information from noise. Our analysis shows that while the majority of energy is concentrated in the first component, semantic distinctions are spread across several smaller components (ranks 3–15).

We then reconstruct a denoised version using only the top-k basis vectors:

$$\mathbf{E}_2^{\text{reduced}} = (\mathbf{E}_2 \mathbf{Q}_{:,:k}) \mathbf{Q}_{:,:k}^T. \tag{12}$$

The concept removal operates on flattened representations to capture global semantic relationships. Let $\tilde{\mathbf{E}}_1 = \text{flatten}(\mathbf{E}_1)$ and $\tilde{\mathbf{E}}_2 = \text{flatten}(\mathbf{E}_2^{\text{reduced}})$. We compute:

$$\tilde{\mathbf{E}}_{\text{out}} = \tilde{\mathbf{E}}_1 - \alpha \, \text{Rej}_{\tilde{\mathbf{E}}_1}(\tilde{\mathbf{E}}_2) = \tilde{\mathbf{E}}_1 \cdot \left(1 + \alpha \cdot \frac{\langle \tilde{\mathbf{E}}_1, \tilde{\mathbf{E}}_2 \rangle}{\|\tilde{\mathbf{E}}_1\|_2^2} \right) - \alpha \cdot \tilde{\mathbf{E}}_2, \tag{13}$$

where α controls the removal strength. The output is reshaped to the original dimensions. This adaptive approach automatically adjusts to concept complexity, i.e., simple concepts require fewer ranks while complex concepts utilize more, achieving robust removal without over-filtering.

Step 6: Final Image Generation. Finally, a new image I^* is generated using the refined conditioning embeddings $(\mathbf{E}_{\text{refined}}, \mathbf{e}_{\text{refined}})$ produced by the concept removal module. The image generator $\mathcal{G}$ then synthesizes:

$$I^* = \mathcal{G}(\mathbf{E}_{\text{refined}}, \mathbf{e}_{\text{refined}}). \tag{14}$$

By incorporating the correction derived from the surrogate embeddings, the refined conditioning better suppresses drift components while preserving the original semantic intent of the prompt.

4 Vocabulary Retrieval Dataset and COALBench-300

4.1 Construction of the Vocabulary Retrieval Dataset

To represent the isolated orthogonal drift vector $\mathbf{v}_{\text{orth}}$ using discrete textual surrogates, we constructed a vocabulary retrieval dataset of over 300,000 words and phrases designed to cover a diverse set of visually grounded and general linguistic concepts. The data was compiled from the following sources:

- **Open Images** (Krasin et al., 2017): Object class labels provided in the official release.

Algorithm 1 Orthogonal Drift Correction (ODC)

1: **Input:** Prompt p_{txt}, vocabulary $\mathcal{V}$
2: **Output:** Final image I^*
3: $(\mathbf{E}_p, \mathbf{e}_p) \leftarrow (\mathcal{E}_{\text{tok}}(p_{\text{txt}}), \mathcal{E}_{\text{pool}}(p_{\text{txt}}))$
4: $I \leftarrow \mathcal{G}(\mathbf{E}_p, \mathbf{e}_p)$
5: $\mathbf{v}_{\text{txt}} \leftarrow \mathcal{E}_{\text{VLM}}(p_{\text{txt}})$
6: $\mathbf{v}_{\text{img}} \leftarrow \mathcal{E}_{\text{VLM}}(I)$
7: $\mathbf{v}_{\text{drift}} \leftarrow \mathbf{v}_{\text{img}} - \mathbf{v}_{\text{txt}}$
8: $\mathbf{v}_{\text{proj}} \leftarrow \frac{\mathbf{v}_{\text{drift}} \cdot \mathbf{v}_{\text{txt}}}{\|\mathbf{v}_{\text{txt}}\|^2} \mathbf{v}_{\text{txt}}$
9: $\mathbf{v}_{\text{orth}} \leftarrow \mathbf{v}_{\text{drift}} - \mathbf{v}_{\text{proj}}$
10: **for** each $w \in \mathcal{V}$ **do**
11: $\quad \mathbf{e}_w \leftarrow \text{embedding}(w)$
12: $\quad s(w) \leftarrow \frac{\mathbf{v}_{\text{orth}} \cdot \mathbf{e}_w}{\|\mathbf{v}_{\text{orth}}\| \|\mathbf{e}_w\|}$
13: **end for**
14: $\mathcal{S}_{\text{orth}} \leftarrow$ Top-k items by $s(w)$
15: Re-embed $\mathcal{S}_{\text{orth}}$: $\{(\mathbf{E}_i, \mathbf{e}_i)\}_{w_i \in \mathcal{S}_{\text{orth}}}$
16: Compute weights $\alpha_i \leftarrow \frac{\exp(s(w_i))}{\sum_j \exp(s(w_j))}$
17: $\mathbf{E}_{\text{orth}} \leftarrow \sum_i \alpha_i \mathbf{E}_i, \quad \mathbf{e}_{\text{orth}} \leftarrow \sum_i \alpha_i \mathbf{e}_i$
18: $(\mathbf{E}_{\text{refined}}, \mathbf{e}_{\text{refined}}) \leftarrow \mathcal{R}((\mathbf{E}_p, \mathbf{e}_p), (\mathbf{E}_{\text{orth}}, \mathbf{e}_{\text{orth}}))$
19: $I^* \leftarrow \mathcal{G}(\mathbf{E}_{\text{refined}}, \mathbf{e}_{\text{refined}})$
20: **return** I^*

Algorithm 2 Adaptive Rank-Reduced Concept Removal $(\mathcal{R})$

Require: $\mathbf{E}_1, \mathbf{E}_2 \in \mathbb{R}^{B \times L \times H}$, $\alpha \in [0, 1]$, $\zeta = 0.01$; bounds $k_{\min} = 3$, $k_{\max} = 15$
Ensure: $\mathbf{E}_{\text{out}} \in \mathbb{R}^{B \times L \times H}$
1: **for** $b = 1$ to B **do**
2: $\quad (\mathbf{Q}^{(b)}, \mathbf{R}^{(b)}) \leftarrow \text{QR\_decomposition}(\mathbf{E}_2^{(b)\top})$
3: $\quad \mathbf{r} \leftarrow \text{diag}(|\mathbf{R}^{(b)}|)$
4: $\quad k \leftarrow \max\{i : r_i/r_1 > \zeta\}$
5: $\quad k \leftarrow \text{clip}(k, k_{\min}, k_{\max})$
6: $\quad$ Let $\mathbf{Q}_k^{(b)}$ be the first k columns of $\mathbf{Q}^{(b)}$
7: $\quad \mathbf{E}_{2,\text{reduced}}^{(b)} \leftarrow (\mathbf{E}_2^{(b)} \mathbf{Q}_k^{(b)}) \mathbf{Q}_k^{(b)\top}$
8: $\quad \tilde{\mathbf{E}}_1 \leftarrow \text{flatten}(\mathbf{E}_1^{(b)})$
9: $\quad \tilde{\mathbf{E}}_2 \leftarrow \text{flatten}(\mathbf{E}_{2,\text{reduced}}^{(b)})$
10: $\quad \text{norm}_1 \leftarrow \|\tilde{\mathbf{E}}_1\|_2$
11: $\quad s \leftarrow 1 + \alpha \cdot \langle \tilde{\mathbf{E}}_1/\text{norm}_1, \tilde{\mathbf{E}}_2/\text{norm}_1 \rangle$
12: $\quad \tilde{\mathbf{E}}_{\text{out}} \leftarrow s \cdot \tilde{\mathbf{E}}_1 - \alpha \cdot \tilde{\mathbf{E}}_2$
13: $\quad \mathbf{E}_{\text{out}}^{(b)} \leftarrow \text{reshape}(\tilde{\mathbf{E}}_{\text{out}}, [L, H])$
14: **end for**
15: **return** $\mathbf{E}_{\text{out}}$

- **Visual Genome** (Krishna et al., 2017): Object annotations, which supply a wide range of free-form object names contributed by annotators.

- **Wikipedia** (Wikimedia Foundation, 2022): To augment the visual vocabulary with more general linguistic coverage, we parsed 1,000 articles extracted from English Wikipedia dataset (March 1, 2022 dump) using SpaCy's dependency parser (Honnibal et al., 2020). From each article, we extracted noun chunks, retaining those appearing at least three times across the corpus. This yielded a complementary set of multi-word expressions such as "machine learning" or "climate change."

In addition, we used a curated English word list (i.e., the `web2` dictionary via the `english-words` python package) to ensure broad lexical coverage (Wiens, 2025).

Following data collection from these sources, we apply a comprehensive preprocessing phase to clean and refine the dataset. This procedure consists of three primary stages: normalization, heuristic filtering, and spelling correction.

Normalization. All candidate strings were lowercased, Unicode-normalized, stripped of non-alphanumeric symbols, and reduced to tokens separated by single spaces. This step removed morphological noise such as capitalization, punctuation, and diacritics.

Heuristic filtering. To eliminate uninformative entries, we applied a series of heuristic rules. First, we enforced length constraints, retaining only terms that contain 1 to 3 tokens and span between 3 and 30 characters. Next, we discarded strings dominated by digits or punctuation, as well as isolated stopword phrases (e.g., "and", "the"). Finally, to ensure that short but meaningful concepts were not mistakenly removed by these length constraints, we implemented a whitelist to preserve essential terms such as "tv" and "pc".

Spelling correction. Because crowdsourced annotations introduce spelling inconsistencies, we employed the SymSpell algorithm (Garbe, 2025) with a maximum edit distance of 2 to canonicalize misspellings. This reduced duplication from typographic errors.

This multi-stage process produced a broad and diverse vocabulary containing both concrete, visually grounded object names and higher-level conceptual phrases. In total, the final vocabulary contains approximately 323,000 items, which serves as the vocabulary retrieval dataset for our experiments.

4.2 Construction of COALBench-300

In order to evaluate the semantic alignment between text-to-image models and user intent, we created COALBench-300 (**CO**mpositional **AL**ignment Benchmark), a curated collection of 300 imaginative prompts specifically designed to test challenging semantic alignment scenarios not emphasized in existing benchmarks. The goal was to establish a standardized set of inputs characterized by richness and diversity such that alignment failures would be clearly observable. To this end, we queried three distinct large language models: OpenAI o3 (`o3-2025-04-16`), Anthropic Claude Opus-4 (`claude-opus-4-20250514`), and Google Gemini 2.5 Pro (`gemini-2.5-pro`), with instructions to propose creative and highly visual text-to-image prompts. Each model produced a large pool of candidate prompts emphasizing diverse styles, scenarios, and semantic complexity.

From the generated pool, we manually reviewed and curated a final set of 300 prompts. This final collection of curated prompts provides a compact but challenging benchmark that allows us to systematically probe how well text-to-image models respect compositional semantics. Unlike generic caption corpora, these prompts emphasize stress-testing of alignment through imaginative and specific requests. The resulting dataset is presented in Table A1 of Appendix A.

5 Experiments

5.1 Experimental Setup

Models. To demonstrate the model-agnostic nature of ODC, we test it across Stable Diffusion XL (SDXL) (Podell et al., 2023) and FLUX.1 [schnell] (Black Forest Labs, 2024). We use BLIP2-ITM-ViT-G model (Li et al., 2023) for vocabulary retrieval in the first stage of ODC.

Inference Parameters. We used the default inference parameters recommended by the model authors for all experiments. This includes an image resolution of 1024×1024 pixels, with SDXL running the Euler Discrete sampler (30 steps, CFG=7.5), and FLUX.1 [schnell] running the Flow Matching Euler Discrete sampler (4 steps). To ensure statistical robustness, we generated three images per prompt using fixed seeds across all methods and report the mean values for all metrics. Our method introduces a few inference-time hyperparameters. To determine their optimal values, we conducted a hyperparameter search on a 100-prompt subset of COALBench-300. The final selected configurations, along with ablation plots detailing performance across different parameter values, are provided in Appendix B.

Benchmarks and Datasets. We evaluate our method using three distinct sets of prompts. First, we employ COALBench-300, introduced in Section 4.2. Second, we utilize PartiPrompts (Yu et al., 2022) to probe imaginative and open-ended generation. For our experiments, we filter this dataset to retain only prompts containing ten words or more, ensuring that all evaluated prompts provide sufficient semantic grounding. Lastly, we employ T2I-CompBench (Complex) (Huang et al., 2025), a challenging benchmark subset that evaluates the generation of complex scenes involving multiple objects, attributes, and relationships. Experiments with these datasets present a thorough evaluation of the methods.

Baselines. We compare ODC against several baselines to better understand its performance. We use the unmodified output from the base T2I models as our Vanilla reference. We also perform a CFG-Sweep, reporting results across different scales to compare against simply strengthening prompt guidance. Additionally, we evaluate a Negative Prompt baseline, where we create a tailored negative prompt for each generation by joining retrieved vocabulary items, using it in place of generic negative prompts (e.g., 'bad anatomy, extra fingers, blurry'). Finally, we compare against two specific inference-time guidance approaches, Attend-and-Excite (Chefer et al., 2023), which refines the latent code during generation by optimizing cross-attention units to "excite" neglected subject tokens (adapted for SDXL; see Appendix C), and ToMe (Hu et al., 2024), which merges object and attribute embeddings into composite tokens to unify their cross-attention maps via iterative optimization and entropy regularization.

Table 1: Main quantitative results on CoalBench-300 and PartiPrompts benchmarks. We report alignment metrics across SDXL and FLUX.1 [schnell]. Best results are in **bold**. Blue and Orange rows highlight our methods. ODC-BoT selects the best image from the two available choices—see text for details.

| Method | CoalBench-300 | | | | PartiPrompts | | | |
| | SDXL | | FLUX.1 [schnell] | | SDXL | | FLUX.1 [schnell] | |
	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑
Vanilla	30.3279	0.6078	29.4499	0.6076	30.8338	0.6030	31.2665	0.6051
CFG-Sweep (CFG=5.0)	30.0022	0.6070	-	-	30.4468	0.6021	-	-
CFG-Sweep (CFG=12.0)	30.4509	0.6083	-	-	31.1269	0.6040	-	-
Negative Prompt	30.3282	0.6078	29.4616	0.6074	30.8336	0.6030	31.1844	0.6051
ODC (Ours)	31.7976	0.6121	29.9181	0.6084	32.5043	0.6074	31.5468	0.6051
ODC-BoT (Ours)	**32.2907**	**0.6127**	**30.4549**	**0.6097**	**32.9911**	**0.6082**	**32.1538**	**0.6067**

Table 2: Comparison with state-of-the-art. We report CLIP and BLIP scores for CoalBench-300 and PartiPrompts benchmarks. For T2I-CompBench, we report the metrics on the complex subset, including the final 3-in-1 average score. Best results are in **bold**. All methods use SDXL as the baseline.

| Method | CoalBench-300 | | PartiPrompts | | T2I-CompBench (Complex) | | | |
	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	BLIP-VQA ↑	UniDet ↑	CLIP ↑	3-in-1 ↑
SDXL (Podell et al., 2023)	30.305	0.608	30.834	0.603	0.442	**0.025**	0.293	0.3294
A&E (Chefer et al., 2023)	29.542	0.608	30.15	0.604	0.436	0.023	0.290	0.3259
ToMe (Hu et al., 2024)	30.397	0.608	30.681	0.603	0.468	0.022	0.292	0.3417
ODC (Ours)	**31.741**	**0.612**	**32.503**	**0.607**	**0.494**	0.020	**0.300**	**0.3572**

Evaluation Metrics. We use established metrics for text-image alignment and computational efficiency. To measure semantic alignment between a prompt and its generated image, we rely on both CLIPScore (ViT-L/14) (Hessel et al., 2021), a widely used metric for general semantic similarity, and BLIPScore (BLIP2-ITM-ViT-G) (Li et al., 2023), which leverages the more advanced BLIP-2 vision-language model for finer-grained evaluations. Additionally, for the T2I-CompBench (Complex) benchmark, we report the "3-in-1" score alongside the individual component scores (BLIP-VQA, UniDet, and CLIPScore) to assess performance across attribute binding, spatial arrangement, and semantic alignment. Given that our method operates during inference, we measure its computational overhead in terms of both latency, defined as the average wall-clock time required to generate a single image, and GPU memory usage during generation.

5.2 Quantitative Results

To establish the efficacy of our method, we present a thorough quantitative evaluation. As shown in Tables 1 and 2, ODC consistently and significantly outperforms all baselines across all faithfulness metrics on both Stable Diffusion XL and FLUX.1 [schnell] (statistical significance validated in Appendix D).

Across all evaluations and for both model backbones (Stable Diffusion XL and FLUX.1 [schnell]), ODC consistently improves semantic alignment scores compared to existing baselines. Since ODC naturally produces both the original baseline image and the corrected variant, we can adopt a simple best-of-two (ODC-BoT) strategy by returning

Table 3: Efficiency analysis on SDXL.

Method	Latency (s/img)	Memory (GB)
Vanilla	3.637	23.015
ODC	7.560	23.015

whichever image achieves the higher score. This strategy yields improved results with negligible computational overhead. Furthermore, ODC preserves visual fidelity. We verify this using Kernel Inception Distance (KID) (Bińkowski et al., 2018). Near-zero scores (ranging from −0.00152 to 0.00093) for both SDXL and FLUX.1 [schnell] across CoalBench-300 and PartiPrompts confirm that the corrected distributions remain statistically indistinguishable from the baselines. This demonstrates that ODC surgically removes drift without shifting the generation out of the data manifold. See Appendix E for details.

As shown in Table 3, ODC introduces some latency overhead while leaving memory consumption unchanged. Compared to the vanilla baseline, latency increases from 3.637 s/img to 7.56 s/img, reflecting the additional

correction pass. Importantly, GPU memory usage remains constant at 23.015 GB, making the approach just as accessible in practice as the baseline methods. Overall, these results demonstrate that the gains in semantic alignment come with predictable and manageable efficiency costs.

Ultimately, we validated our quantitative results via a human evaluation consisting of 600 blind pairwise comparisons. These were collected from 12 domain experts evaluating 50 randomly sampled prompts from CoalBench-300. As shown in Table 4, ODC is preferred in 61.8% of decisive votes (95% CI: [57.0%, 66.3%]) versus the baseline's 38.2%. This represents a statistically significant improvement, as the CI strictly excludes 50%. Furthermore, a 30.7% tie rate indicates that ODC preserves fidelity in already well-aligned images rather than applying unnecessary alterations.

5.3 Qualitative Results

Visual inspection of the generated images provides the most intuitive evidence of ODC's effectiveness. In Figure 2, we present a side-by-side comparison of images generated by vanilla SDXL and FLUX, alongside our ODC-corrected method for a variety of challenging prompts. We observe that ODC improves compositional accuracy and attribute binding, and leads to reduced semantic drift. The baseline often struggles with correct modifier-object relationships

Table 4: Human evaluation results. Win rates are computed over decisive votes (ties excluded).

Metric	Value	95% CI
ODC Win Rate	61.8%	[57.0%, 66.3%]
Baseline Win Rate	38.2%	[33.7%, 43.0%]
Tie Rate	30.7%	—

and maintaining fine-grained attributes, while ODC generates images that align more accurately with the user description. Furthermore, for prompts that are vulnerable to spurious additions (e.g., "Victorian astronaut playing violin inside ornate greenhouse orbiting Saturn's rings"), the baseline model introduces unintended elements, such as additional violinists, that reduce alignment with the user prompt. In contrast, ODC constrains generations to the requested content and avoids unwanted additions, yielding outputs that more faithfully reflect the intended semantics. These qualitative examples demonstrate that by refining the initial text embedding, ODC provides a more reliable conditioning for the image generation process. Additional qualitative results are provided in Appendix F. The list of vocabulary items ($\mathcal{S}_{\text{orth}}$) retrieved by ODC for images in Figure 2 are included in a detailed table in Appendix G.

5.4 Ablation Studies

The Importance of Orthogonal Correction. Our central claim is that isolating and removing the *orthogonal* component of the semantic drift is key. To validate this, we compare ODC against two alternative correction strategies (Table 5). First, we test a "Simple Concept Removal" baseline, which directly subtracts the embeddings of the retrieved drift keywords from the prompt embeddings. While this improves upon the vanilla baseline, it substantially underperforms compared to the other approaches. Second, we test "Full Vector Correction," which removes

Table 5: Quantitative ablation results for SDXL on CoalBench-300.

Method	CLIP ↑
Vanilla	30.305
Simple Concept Removal	30.970
Full Vector Correction	31.489
Orthogonal Drift Correction	**31.741**

the entire semantic drift vector ($\mathbf{v}_{\text{drift}}$). Despite outperforming simple concept removal, it still underperforms our proposed ODC (Figure 3), as removing the full vector inadvertently strips away useful on-axis semantic information. In contrast, ODC surgically removes only the irrelevant, orthogonal semantic contents, achieving the highest alignment.

Dependence on Vision-Language Model ($\mathcal{E}_{\text{VLM}}$). To evaluate ODC's dependency on the VLM, we conducted an ablation study on CoalBench-300 using three models of varying capacity: `CLIP ViT-L/14`, `SigLIP2 SO400M`, and `EVA-Giant Plus`. To ensure a rigorous comparison across different embedding spaces, we calibrated ODC's removal strength (α) on a held-out set of 50 prompts and evaluated performance on the remainder. As shown in Table 6, ODC generalizes across VLMs, with all models improving baseline alignment. `CLIP ViT-L/14` and `EVA-Giant Plus` outperform `SigLIP2`, with CLIP slightly outperforming the larger EVA on SDXL. We attribute this to architectural parity, as SDXL and FLUX.1 natively condition on the `CLIP ViT-L/14` text encoder, making its calculated drift vectors inherently better aligned with the

Figure 2: Qualitative comparison of images generated with and without Orthogonal Drift Correction (ODC). For each prompt, we show the output from the baseline model (left) and our ODC-corrected version (right).

generator's manifold. Nonetheless, EVA's strong performance, with its marginal lead on FLUX.1, confirms that high-capacity VLMs can effectively approximate this drift, ensuring ODC remains robust regardless of the chosen VLM.

6 Limitations

Despite its strong performance, ODC has some inherent limitations. First, its effectiveness is bound by the perceptual capabilities of the vision-language model (VLM) used in the first stage. If the VLM cannot

Figure 3: Qualitative ablation comparing baseline (SDXL), Full Vector Correction, and ODC on three prompts. Results show ODC corrects semantic discrepancies in the left and middle columns.

Table 6: Ablation Study on Vision-Language Model Dependency ($\mathcal{E}_{\text{VLM}}$).

Method	CLIP ViT-L/14				SigLIP2 SO400M				EVA-Giant Plus			
	SDXL		FLUX.1 [schnell]		SDXL		FLUX.1 [schnell]		SDXL		FLUX.1 [schnell]	
	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑	CLIP ↑	BLIP ↑
Vanilla	30.258	0.607	29.329	0.607	30.258	0.607	29.329	0.607	30.258	0.607	29.329	0.607
ODC	31.662	0.611	29.616	0.608	31.173	0.610	29.504	0.608	31.642	0.611	29.629	0.608
ODC-BoT	32.106	0.612	30.105	0.609	31.559	0.611	30.141	0.609	32.126	0.612	30.354	0.610

see a specific semantic error, ODC may not correct it. For instance, because VLMs struggle with precise counting, ODC might fail to correct numerical discrepancies, such as generating exactly "A desert landscape with three suns setting on the horizon" (Figure 4(a)). Similarly, VLMs can miss nuanced artistic styles; if a baseline misses the intended style of a prompt like "An Art Deco robot butler serving cocktails at a party," the VLM may not recognize this drift, causing ODC to push the image towards realism rather than the desired style (Figure 4(b)). Furthermore, VLMs can misinterpret polysemous words, misguiding ODC. For example, with the prompt "Lightning striking sand creating glass," the VLM might anchor onto the household object rather than the material, causing ODC to insert a literal drinking glass instead of a glassy formation (Figure 4(c)). As VLM embeddings continue to improve in compositional and structural reasoning, we expect ODC's robustness in these cases to advance as well.

Second, the two-stage correction process inherently increases the inference latency compared to a standard single pass, as shown in Table 3. While the overhead from the embedding calculations themselves is negligible, the need for an initial generation pass represents a direct trade-off between computational cost and semantic drift correction. Nevertheless, considering that T2I generation is generally an offline task, this limitation is of minor nature. Moreover, our method can potentially reduce the time associated with manual trial and error process involved in prompt engineering considerably by providing better alignment of outputs to the prompts.

(a) (b) (c)

Figure 4: Representative failure cases: ODC (bottom) and Baseline (top).

7 Conclusion

In this paper, we addressed the critical problem of semantic drift in text-to-image models. We introduced Orthogonal Drift Correction (ODC), a training-free, inference-time method that guides the image generation through a two-stage process. It estimates the components of text embeddings causing the drift and mitigates them. Our extensive experiments demonstrate that ODC significantly enhances prompt-image alignment across multiple models and benchmarks. Without requiring any retraining or architectural changes, ODC provides a practical and generalizable solution for improving the alignment and reliability of existing pre-trained text-to-image models, making them more powerful creative tools.

Reproducibility Statement

To ensure reproducibility, we provide detailed algorithmic descriptions of our method in Section 3, along with hyperparameter configurations and experimental settings in Section 5. Our proposed prompt dataset, CoalBench-300, is provided in full in Appendix A, and all other datasets used in our experiments are publicly available. All experiments are conducted using publicly available models and libraries. We intend to release our code publicly in the future.

Broader Impact Statement

Improving prompt-image alignment improves reliability and reduces user frustration. Like any alignment technique, ODC makes models more faithful to their inputs, which could include harmful or inappropriate prompts if applied to base models with weak safety filters. Importantly, ODC does not expand the generative capabilities of the base model, but merely reduces semantic drift. To prevent misuse, ODC should be deployed in conjunction with standard content moderation and safety filtering mechanisms.

References

Mikołaj Bińkowski, Danica J Sutherland, Michael Arbel, and Arthur Gretton. Demystifying mmd gans. *arXiv preprint arXiv:1801.01401*, 2018.

Black Forest Labs. Announcing Black Forest Labs. Web Page, August 2024. URL `https://bfl.ai/blog/24-08-01-bfl`.

Hila Chefer, Yuval Alaluf, Yael Vinker, Lior Wolf, and Daniel Cohen-Or. Attend-and-excite: Attention-based semantic guidance for text-to-image diffusion models. *ACM transactions on Graphics (TOG)*, 42(4):1–10, 2023.

Hyungjin Chung, Jeongsol Kim, Geon Yeong Park, Hyelin Nam, and Jong Chul Ye. Cfg++: Manifold-constrained classifier free guidance for diffusion models. *arXiv preprint arXiv:2406.08070*, 2024.

Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit H Bermano, Gal Chechik, and Daniel Cohen-Or. An image is worth one word: Personalizing text-to-image generation using textual inversion. *arXiv preprint arXiv:2208.01618*, 2022.

Wolf Garbe. SymSpell: 1 million times faster spelling correction and fuzzy search through symmetric delete spelling correction algorithm. `https://github.com/wolfgarbe/SymSpell`, 2025. Version 6.7.3.

Xiefan Guo, Jinlin Liu, Miaomiao Cui, Jiankai Li, Hongyu Yang, and Di Huang. Initno: Boosting text-to-image diffusion models via initial noise optimization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9380–9389, 2024.

Amir Hertz, Ron Mokady, Jay Tenenbaum, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. Prompt-to-prompt image editing with cross attention control. *arXiv preprint arXiv:2208.01626*, 2022.

Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. Clipscore: A reference-free evaluation metric for image captioning. *arXiv preprint arXiv:2104.08718*, 2021.

Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. *arXiv preprint arXiv:2207.12598*, 2022.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33:6840–6851, 2020.

Matthew Honnibal, Ines Montani, Sofie Van Landeghem, and Adriane Boyd. spaCy: Industrial-strength natural language processing in python, 2020. URL `https://doi.org/10.5281/zenodo.1212303`.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3, 2022.

Taihang Hu, Linxuan Li, Joost van de Weijer, Hongcheng Gao, Fahad Shahbaz Khan, Jian Yang, Ming-Ming Cheng, Kai Wang, and Yaxing Wang. Token merging for training-free semantic binding in text-to-image synthesis. *Advances in Neural Information Processing Systems*, 37:137646–137672, 2024.

Kaiyi Huang, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench: A comprehensive benchmark for open-world compositional text-to-image generation. *Advances in Neural Information Processing Systems*, 36:78723–78747, 2023.

Kaiyi Huang, Chengqi Duan, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench++: An enhanced and comprehensive benchmark for compositional text-to-image generation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2025.

Dongzhi Jiang, Guanglu Song, Xiaoshi Wu, Renrui Zhang, Dazhong Shen, Zhuofan Zong, Yu Liu, and Hongsheng Li. Comat: Aligning text-to-image diffusion model with image-to-text concept matching. *Advances in Neural Information Processing Systems*, 37:76177–76209, 2024.

Ivan Krasin, Tom Duerig, Neil Alldrin, Vittorio Ferrari, Sami Abu-El-Haija, Alina Kuznetsova, Hassan Rom, Jasper Uijlings, Stefan Popov, Shahab Kamali, Matteo Malloci, Jordi Pont-Tuset, Andreas Veit, Serge Belongie, Victor Gomes, Abhinav Gupta, Chen Sun, Gal Chechik, David Cai, Zheyun Feng, Dhyanesh Narayanan, and Kevin Murphy. Openimages: A public dataset for large-scale multi-label and multi-class image classification. *Dataset available from https://storage.googleapis.com/openimages/web/index.html*, 2017.

Ranjay Krishna, Yuke Zhu, Oliver Groth, Justin Johnson, Kenji Hata, Joshua Kravitz, Stephanie Chen, Yannis Kalantidis, Li-Jia Li, David A Shamma, et al. Visual genome: Connecting language and vision using crowdsourced dense image annotations. *International journal of computer vision*, 123(1):32–73, 2017.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pp. 19730–19742. PMLR, 2023.

Tuna Han Salih Meral, Enis Simsar, Federico Tombari, and Pinar Yanardag. Conform: Contrast is all you need for high-fidelity text-to-image diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9005–9014, 2024.

Chong Mou, Xintao Wang, Liangbin Xie, Yanze Wu, Jian Zhang, Zhongang Qi, and Ying Shan. T2i-adapter: Learning adapters to dig out more controllable ability for text-to-image diffusion models. In *Proceedings of the AAAI conference on artificial intelligence*, volume 38, pp. 4296–4304, 2024.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmLR, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 1(2):3, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10684–10695, 2022a.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10684–10695, 2022b.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 22500–22510, 2023.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in neural information processing systems*, 35:36479–36494, 2022.

Matt Wiens. english-words: Generate sets of english words by combining different word lists, 2025. URL `https://pypi.org/project/english-words/`. Version 2.0.2.

Wikimedia Foundation. Wikimedia Downloads, 2022. URL `https://dumps.wikimedia.org`. Dump date: 2022-03-01.

Jiahui Yu, Yuanzhong Xu, Jing Yu Koh, Thang Luong, Gunjan Baid, Zirui Wang, Vijay Vasudevan, Alexander Ku, Yinfei Yang, Burcu Karagol Ayan, et al. Scaling autoregressive models for content-rich text-to-image generation. *arXiv preprint arXiv:2206.10789*, 2(3):5, 2022.

Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 3836–3847, 2023.

A COALBench-300

Table A1 presents the CoalBench-300 dataset used in our experiments, consisting of 300 prompts generated as described in Section 4.2.

Table A1: Full list of prompts in CoalBench-300.

#	Prompt	#	Prompt
1	Neon cityscape reflected in rain puddles at midnight	2	Ancient library filled with floating glowing books
3	Steampunk octopus playing violin underwater	4	Cherry blossoms falling on samurai armor
5	Cyberpunk cat cafe with holographic menu displays	6	Dragon made entirely of autumn leaves
7	Astronaut planting flowers on Mars surface	8	Victorian greenhouse overflowing with bioluminescent plants
9	Robot chef preparing sushi in minimalist kitchen	10	Northern lights dancing above crystal ice castle
11	Abandoned amusement park reclaimed by nature	12	Phoenix rising from coffee cup steam
13	Underwater city inside giant glass bubble	14	Mechanical butterfly landing on child's outstretched hand
15	Storm clouds shaped like galloping horses	16	Art deco train station at golden hour
17	Jellyfish constellation floating through space	18	Medieval knight riding mechanical dragon
19	Sunflowers growing from piano keys	20	Time traveler's workshop filled with clocks
21	Magical forest where trees have doorways	22	Origami birds transforming into real ones
23	Vintage typewriter typing rainbow colored words	24	Giant teacup island in cloudy sky
25	Bioluminescent mushroom cave with crystal formations	26	Retro diner floating in outer space

Continued on next page

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
27	Library ladder reaching into starry sky	28	Glass sculpture garden during thunderstorm
29	Mechanical whale swimming through clouds	30	Paint brushes growing like flowers in pot
31	Lighthouse made of stacked books	32	Geometric mountains with gradient sunset colors
33	Tiny fairy village inside terrarium	34	Steam locomotive made of flowers
35	Crystal skull containing miniature galaxy	36	Hot air balloons shaped like planets
37	Underwater ballet performed by seahorses	38	Gothic cathedral made of ice
39	Neon sign reflected in cyberpunk alley	40	Tree house connected by rope bridges
41	Desert oasis with mirror-like water	42	Mechanical heart with gears and flowers
43	Floating islands connected by waterfalls	44	Vintage camera capturing memories as butterflies
45	Snow globe containing miniature city	46	Giant mushroom houses in enchanted forest
47	Clock tower melting like Salvador Dali painting	48	Paper airplane leaving trail of stars
49	Underwater ruins with glowing hieroglyphs	50	Mechanical bee pollinating metal flowers
51	Aurora borealis inside crystal cave	52	Sailing ship made of autumn leaves
53	Robot gardener tending glass flowers	54	Mountain peak piercing through clouds
55	Neon Tokyo street in heavy rain	56	Butterfly wings made of stained glass
57	Ancient tree with doors to other worlds	58	Mechanical dragon breathing rainbow fire
59	Floating market on lily pad boats	60	Crystal palace reflecting sunset colors
61	Origami crane transforming into phoenix	62	Underwater volcano with lava lamp effect
63	Clockwork owl perched on moon	64	Garden maze viewed from above
65	Holographic whale swimming through city	66	Ice sculpture melting into butterflies
67	Vintage bicycle with flower basket	68	Portal opening in library wall
69	Mechanical spider weaving light web	70	Treehouse city in giant redwood forest
71	Glass elevator ascending through clouds	72	Firefly jar illuminating dark forest
73	Geometric deer made of neon lines	74	Floating tea party in sky

Continued on next page

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
75	Crystal bridge over mirror lake	76	Mechanical hummingbird feeding on gear flowers
77	Northern lights reflected in frozen lake	78	Paper boat sailing on book pages
79	Bonsai tree with tiny glowing lanterns	80	Underwater castle made of coral
81	Steampunk hot air balloon city	82	Galaxy swirling in coffee cup
83	Ice phoenix rising from frozen waterfall	84	Mechanical butterfly collection in display case
85	Floating geometric islands at sunset	86	Glass greenhouse in snowy landscape
87	Lightning striking sand creating glass	88	Origami dragon breathing paper fire
89	Crystal cave with rainbow reflections	90	Vintage train crossing bridge at dawn
91	Mechanical whale breaching ocean surface	92	Fairy ring mushrooms glowing at twilight
93	Neon arcade in rain-soaked alley	94	Tree growing through abandoned car
95	Holographic fish swimming through air	96	Ice palace under aurora borealis
97	Steampunk telescope viewing distant galaxies	98	Garden path made of piano keys
99	Crystal butterfly landing on metal flower	100	Lighthouse beam cutting through fog
101	A bioluminescent jellyfish floating through a neon-lit cyberpunk city	102	A lone knight overlooking a valley of giant, glowing mushrooms
103	A crystal skull filled with a swirling, miniature galaxy	104	A serene, minimalist Japanese garden in the pouring rain
105	An ancient Roman library on a terraformed, dusty Mars	106	A tiny fairy house built inside a broken teapot
107	A grand piano with keys melting like liquid Dali-style	108	A cozy, cluttered bookstore on a foggy autumn evening
109	A Viking longship sailing on a sea of clouds	110	A stained glass window depicting a cosmic horror entity
111	A sleek, organic starship gliding silently past a vibrant nebula	112	A grizzly bear made of constellations in the night sky
113	A forgotten, overgrown greenhouse filled with strange, glowing plants	114	A city skyline at sunset, rendered in 8-bit pixel art
115	A steampunk inventor's workshop, cluttered with brass and clockwork	116	A macro photograph of a single dewdrop on a spiderweb
117	A majestic castle made of obsidian and jagged lightning	118	The concept of "silence" visualized as a physical object
119	An Art Deco robot butler serving cocktails at a party	120	A floating market on a serene, otherworldly alien canal
121	A portrait of a queen, made entirely from pressed flowers	122	A paper-craft, origami world with a flowing paper river

Continued on next page

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
123	A cat made of glass, filled with swirling, colored smoke	124	A haunted forest where the trees have screaming human faces
125	Impossible Escher-like architecture carved from a single, giant tree	126	A gourmet hamburger made entirely of sparkling, edible gemstones
127	A desert landscape with three suns setting on the horizon	128	An ancient, moss-covered golem sleeping in a sunlit forest
129	A city street scene painted in the style of Van Gogh	130	A lone, red telephone box in the middle of nowhere
131	A mechanical heart with glowing tubes and intricate gears	132	A tranquil koi pond that reflects a starry night sky
133	An astronaut discovering an ancient alien ruin on the moon	134	A single, perfect rose encased in a block of ice
135	An island that is the back of a giant, swimming turtle	136	A shadowy figure standing at the end of a long pier
137	A black and white photograph of a 1940s detective's office	138	A city built inside a colossal, hollowed-out crystal cavern
139	A samurai warrior with glowing, cybernetic neon tattoos	140	A massive, ancient library where the books float between shelves
141	A cup of coffee with a swirling galaxy in it	142	A child releasing a kite that is actually a dragon
143	A detailed anatomical drawing of a mythical griffin	144	A vaporwave sculpture garden with pink and blue neon lights
145	A doorway to another dimension opening in a brick wall	146	A city street dissolving into musical notes in the air
147	A lone lighthouse battered by a furious, cosmic storm	148	A portrait of "joy" as an explosion of vibrant colors
149	A medieval feast with ghosts sitting amongst the living guests	150	An underwater city inhabited by elegant, humanoid sea creatures
151	A tree whose leaves are made of delicate, colored glass	152	A futuristic high-speed train blurring through a bamboo forest
153	A sad clown looking at his reflection in a puddle	154	A cinematic shot of a dinosaur roaring in a modern city
155	A map of a fantasy world burned onto old leather	156	An ornate, Venetian mask with intricate filigree and feathers
157	A car rusting in a field of blooming sunflowers	158	A mountain range shaped like a sleeping stone dragon
159	A wizard's spellbook lying open, glowing with powerful magic	160	A skeleton in a spacesuit, sitting on a desolate asteroid
161	A beautiful landscape painting done on a crumbling concrete wall	162	A ceramic mosaic depicting the birth of a star
163	A clock tower where the numbers are flying away	164	An elven city built seamlessly into giant, living trees

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
165	A low-poly render of a wolf howling at the moon	166	A secret garden hidden behind a waterfall
167	A single, burning feather falling from a dark sky	168	A long exposure photograph of highway lights at night
169	A palace made entirely of ice, glistening in the sun	170	A chessboard with living pieces preparing for battle
171	A surreal landscape where the ground is a reflective mirror	172	A powerful phoenix rising from ashes, cinematic fantasy art
173	A ukiyo-e woodblock print of a busy Tokyo intersection	174	An old, forgotten god statue entangled in jungle vines
175	A gentle robot tending to a garden of metal flowers	176	An underwater submarine discovering the lost city of Atlantis
177	The solar system re-imagined as a delicate, hanging mobile	178	A tiny mouse wearing intricate, hand-crafted medieval armor
179	A world where the oceans are in the sky	180	A close-up of a dragon's eye, reflecting a battle
181	A hyper-realistic painting of a spilled glass of milk	182	A towering, complex sandcastle about to be hit by a wave
183	A lush, tropical beach inside a giant, open clam shell	184	A synthwave-style sunset over a retro-futuristic highway
185	A collection of magical potions, glowing on a dusty shelf	186	A double exposure portrait of a woman and a forest
187	A pirate ship sailing through a massive electrical storm	188	A whimsical town where all the buildings are books
189	A soldier's helmet from the future, cracked and abandoned	190	A tree of life connecting the earth and the cosmos
191	A blueprint-style technical drawing of a fantasy airship	192	A labyrinth made of tall, perfectly trimmed hedges
193	An abstract sculpture representing the sound of laughter	194	A street market on a space station, full of aliens
195	A beautiful, haunting portrait of a porcelain doll	196	The world balanced on the tip of a giant's finger
197	A polar bear sleeping under the vibrant aurora borealis	198	A vintage 1950s car flying through the clouds
199	A stone staircase spiraling down into the deep, dark ocean	200	A single, glowing key lying on an empty city street
201	Neon samurai meditating under cherry blossoms, cyberpunk city distant horizon	202	Golden dragon soaring above tempestuous sea during crimson twilight storm
203	Victorian astronaut playing violin inside ornate greenhouse orbiting Saturn's rings	204	Gigantic marble statues emerging from desert dunes beneath aurora sky

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
205	Steam-powered whale floating over steampunk city releasing glowing lanterns peacefully	206	Surreal library labyrinth with endless staircases and levitating luminous books
207	Winter fox spirits dancing around ancient shrine under full moon	208	Retro-futuristic diner on Mars serving milkshakes to robot cowboys today
209	Bioluminescent jungle river reflecting twin moons, explorers paddling crystal canoes	210	Minimalist ink painting depicting thunderstorm over solitary mountain tea house
211	Ancient turtle island carrying cherry forest drifting across tranquil ocean	212	Post-apocalyptic fashion runway among ruins, models wearing repurposed metallic couture
213	Glass butterflies emerging from cracked sculpture in abandoned classical gallery	214	Cosmic carnival Ferris wheel spinning galaxies instead of passenger gondolas
215	Medieval alchemist laboratory illuminated by swirling emerald and violet potions	216	Peaceful Zen garden floating among clouds, koi fish swimming air
217	Art deco submarine cruising crystal Arctic waters beneath shimmering aurora	218	Gothic cathedral built from bones, candles flickering with blue flames
219	Whimsical cat orchestra performing symphony inside giant teacup on meadow	220	Autumn maple leaves transforming into origami cranes mid gentle breeze
221	Futuristic Venice with glass canals and levitating gondolas at sunset	222	Alien botanist tending glowing succulents within transparent asteroid greenhouse sphere
223	Samurai mech duel atop skyscraper during torrential rain and lightning	224	Childhood memories visualized as floating polaroid cubes above grassy field
225	Mushroom village illuminated by fireflies, tiny gnomes celebrating midsummer feast	226	Surreal chessboard landscape where pieces are skyscrapers casting elongated shadows
227	Golden hour lighthouse standing on clouds guiding paper boats home	228	Cybernetic phoenix reborn from neon flames above dystopian alleyway rooftops
229	Mythical underwater library with coral shelves and manta ray librarians	230	Celtic wolf warrior howling beside rune-carved stone under starry sky
231	Industrial robots painting classical renaissance portrait inside abandoned factory hall	232	Pastel vaporwave beach scene with dolphins and pixelated palm trees
233	Ice cream planet orbiting candy stars within childlike cosmic dreamscape	234	Ethereal ballerina composed of smoke gracefully twirling through candlelit ballroom

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
235	Ancient astronauts carved into mountain, projections igniting during equinox ceremony	236	Monochrome noir city where rain turns neon once striking pavement
237	Giant panda knight wearing bamboo armor charging across sunflower plains	238	Sailing ship overhead sky ocean, clouds shaped like wandering whales
239	Magnificent art nouveau dragonfly airship docking at crystal palace port	240	Crimson haired witch brewing constellation soup in antique cast-iron cauldron
241	Time travelers picnic within looping paradox meadow filled with suns	242	Dreamy pastel clouds dripping like paint over sleepy coastal village
243	Crystal caverns resonating music, stalactites functioning as grand pipe organ	244	Pharaoh cyborg sitting upon holographic throne inside starship pyramid command
245	Origami dragons battling above waterfall, paper scraps becoming swirling mist	246	Intergalactic farmers harvesting stardust using laser scythes and hover wagons
247	Snowy owl postman delivering letters between lonely mountain observatories nightly	248	Renaissance painting fused with glitch art, saints pixelated yet divine
249	Lonely astronaut gardening roses inside cracked helmet on barren exoplanet	250	Midsummer carnival mirrored on lake surface, reflections showing alternate dimension
251	Celestial koi swimming through starry void forming luminous cosmic patterns	252	Gigabyte forest where data streams cascade like waterfalls between trees
253	Clockwork hummingbirds pollinating gears within enormous steampunk garden mechanism today	254	Futuristic samurai riding holographic horse across neon rice paddies night
255	Survivalists camping on colossal lily pads floating down moonlit river	256	Hyperrealistic microphotography style city built upon a dandelion seed closeup
257	Norwegian fjord village illuminated solely by bioluminescent algae and stars	258	Astral projection commuters riding light beams between futuristic office towers
259	Fairytale bakery selling clouds, customers bottling rainbows for frosting today	260	Desert caravan of holographic camels crossing dunes under binary suns
261	Spaceship graveyard turned skatepark, teenagers grinding along rusted hulls today	262	Fantasy opera house shaped like seashell, audience wearing pearl masks
263	Interactive graffiti walls repaint themselves according to passerby's emotional aura	264	Robot monk studying lotus algorithm amidst tranquil chrome bamboo grove

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
265	Abandoned amusement park reclaimed by jungle, rollercoaster entwined with vines	266	Crystalline wolf pack running across frozen lake under kaleidoscope aurora
267	Pocket watch melting into river, time flowing downstream with salmon	268	Digital renaissance fair where knights duel using augmented reality dragons
269	Samurai standing in field of wind turbines during golden sunrise	270	Galactic mail carrier surfing solar winds to deliver interstellar postcards
271	Carousel horses awakening midnight, galloping across city streets leaving sparks	272	Northern lights shaped like dragons over mirrorlike fjord with rowboat
273	Cyberpunk mermaid lounging on neon coral reef playing electric harp	274	Snow globe metropolis shaking, skyscraper flakes swirling around central park
275	Mystical doorway inside tree trunk leading to floating candlelit staircase	276	Marble chess pieces crying tears, puddles reflecting parallel universe conflicts
277	Steampunk octopus captain steering dirigible through thunderous cloud ocean today	278	Silk road marketplace set on asteroid, merchants trading gravity spices
279	Lone monk meditating atop newspaper stack skyscraper in bustling metropolis	280	Candy-coated castle melting under sunrise, rivers of caramel surrounding battlements
281	Moonlit bamboo forest where shadows of past lives perform theatre	282	Quantum computer envisioned as cathedral, qubits glowing like stained glass
283	Vibrant coral reef mirrored above water, sky filled with fish	284	Ghostly steam train crossing galaxy, passengers silhouettes made from stardust
285	Medieval tavern hosting extraterrestrial travelers swapping holographic treasure maps tonight	286	Arcade cabinet forest, joysticks sprouting like mushrooms among pixel leaves
287	Viking ship sailing across clouds towards colossal floating mead hall	288	Haunted typewriter printing poems by itself inside candlelit attic loft
289	Interdimensional bus stop where travelers trade memories for tickets home	290	Mid-century modern house perched atop giant redwood, overlooking fog valley
291	Lavender fields beneath glass dome, drones pollinating under artificial sunlight	292	Ancient rune compass projecting holographic maps above weathered pirate desk
293	Swan boat gliding through clouds, passengers sipping tea with angels	294	Neo-Tokyo skyline reflected in raindrop on cybernetic geisha's finger nail
295	Prismatic desert canyon walls refracting sunlight into rainbow patterned sand	296	Clocktower orchard where apples tick loudly with winding golden gears

Table A1 – *Continued from previous page*

#	Prompt	#	Prompt
297	Giraffe skyscrapers eating cloud leaves in whimsical metropolitan savanna today	298	Secluded monastery balanced atop waterfall edge within verdant hidden valley
299	Elegant cyborg ballerinas rehearsing in abandoned warehouse filled with mirrors	300	Thunderstorm brewing inside snow globe resting on antique wooden desk

Figure A1: Hyperparameter ablation study on a 100-prompt validation subset of CoalBench-300. Top row: SDXL. Bottom row: FLUX.1. The dashed line represents the unmodified baseline. Red markers indicate the hyperparameters chosen for our pipeline.

B Hyperparameter Ablation

To justify the empirical selections in our pipeline, we conduct an ablation study on the ODC hyperparameters using a 100-prompt validation subset of CoalBench-300. The results are visualized in Figures A1 and A2.

Number of Keywords (k). We evaluate the number of top retrieved vocabulary terms used to construct the orthogonal drift vector $\mathbf{v}_{\mathrm{orth}}$. As shown in Figure A1(a, d), performance saturates rapidly from top-1 to top-3. For FLUX.1, $k = 3$ yields the clear peak performance. For SDXL, $k = 3$ and $k = 5$ perform nearly identically. However, we select $k = 5$ for SDXL as it provides a better balance of semantic coverage. We therefore adopt $k = 5$ for SDXL and $k = 3$ for FLUX.1 as our final parameters.

Concept Removal Weight (α). This parameter scales the magnitude of the correction. Figure A1(b, e) demonstrates that optimal removal strength is model-dependent. SDXL requires a stronger correction ($\alpha = 1.0$), whereas FLUX.1 is highly sensitive, as an α of 0.8 causes catastrophic over-correction and collapse (CLIP 24.957). We select $\alpha = 0.3$ for FLUX.1, which provides a safe margin from the over-correction cliff while achieving strong alignment.

Keywords Weights Temperature (τ). The temperature controls the sharpness of the softmax applied to the similarity scores. We select $\tau = 0.50$ for SDXL and $\tau = 0.05$ for FLUX.1. As shown in Figure A1(c, f), ODC is robust to this parameter across an order of magnitude ($\tau \in [0.05, 1.0]$), confirming that the method does not rely on sharp, one-hot weighting.

Adaptive Rank-Reduction Bounds and Energy Threshold ($k_{\min}$, $k_{\max}$, ζ). The adaptive rank-reduction in $\mathcal{R}$ (Algorithm 2) relies on bounds $k_{\min} = 3$ and $k_{\max} = 15$ to balance concept completeness against noise inclusion. To justify these bounds and our energy threshold $\zeta = 0.01$, we analyze the drift embeddings $\mathbf{E}_{\mathrm{orth}}$ across our validation set. As shown in Figure A2(a), we computed the QR decomposition and recorded the rank k where the relative diagonal magnitude $|r_{ii}|/|r_{11}|$ dropped below ζ, prior to applying

any clamping. Evaluated across multiple thresholds ($\zeta \in \{0.1\%, 0.5\%, 1.0\%, 2.0\%\}$), the rank consistently falls within the $[3, 15]$ range. Ranks below 3 are too sparse to represent a complete concept, while ranks above 15 encode irrelevant noise.

Furthermore, Figure A2(b) demonstrates that the threshold $\zeta = 1.0\%$ provides the optimal empirical performance, yielding the highest CLIP Score (31.613). Tighter thresholds (e.g., 0.1%) or looser thresholds (e.g., 2.0%) incorporate either too much noise or too little semantic information, respectively. Therefore, $\zeta = 1.0\%$ combined with the safety rails $[3, 15]$ ensures our concept removal operator targets only the unwanted semantic drift.

Figure A2: (a) Distribution of the rank k where the relative diagonal magnitude $|r_{ii}|/|r_{11}|$ drops below ζ, derived from SDXL drift embeddings across different thresholds. The dashed lines indicate the chosen bounds $[3, 15]$. (b) Mean CLIP Score achieved by ODC as a function of ζ, with the red marker indicating the chosen threshold ($\zeta = 1.0\%$).

C   Adaptation of Attend-and-Excite for SDXL

To employ Attend-and-Excite (A&E) as a baseline for the Stable Diffusion XL (SDXL) architecture, we adapted the official implementation to account for the model's increased latent resolution and dual text-encoder structure. While the core Generative Semantic Nursing (GSN) logic remains consistent with Chefer et al. (2023), our implementation introduces the following specific changes:

1. **Attention Map Extraction:** The original method operates on 16×16 attention maps. In SDXL, we found this resolution (corresponding to a 64-pixel stride) too coarse. We instead extract maps from the 32×32 cross-attention layers of the U-Net. We aggregate attention probabilities across heads and derive token indices using the tokenizer associated with the second text encoder (OpenCLIP ViT-bigG/14).

2. **Padding and Smoothing:** To prevent the optimization from exploiting edge artifacts, we apply *reflection padding* to the attention maps prior to Gaussian smoothing (kernel size 3×3, $\sigma = 0.5$). This ensures that subjects generated near the image boundaries are not penalized by zero-padding in the loss calculation. Additionally, we scale the raw attention scores by a factor of 100 before the Softmax operation to sharpen the attention distribution.

3. **Optimization Schedule:** We perform the latent optimization during the first 25 steps of a 30-step generation schedule. We utilize an iterative refinement strategy at timesteps $t \in \{0, 10, 20\}$ with acceptance thresholds $\tau \in \{0.1, 0.5, 0.8\}$. The latent code z_t is updated with a gradient step size α_t that follows a linear decay schedule:

$$\alpha_t = S \cdot \left(1 - 0.5 \cdot \frac{t}{T_{total}}\right), \tag{15}$$

where the initial scale factor S is set to 20.0. Gradients are normalized if their norm exceeds 1×10^{-5} to maintain stability within the SDXL latent space.

4. **Subject Selection:** We automate the selection of subject tokens using a Part-of-Speech (POS) tagger to identify nouns and proper nouns within the input prompts.

D Statistical Significance Analysis

To assess the robustness of our reported improvements, we compute 95% confidence intervals (CIs) and perform paired t-tests across all CoalBench-300 prompts and 3 seeds (N=900). The complete results are detailed in Table A2.

Table A2: Statistical significance analysis across CoalBench-300 prompts and 3 seeds (N=900). We report Mean ± Std and 95% CIs for the baseline, ODC, and ODC-BoT, along with the paired t-test results for the ODC improvement.

Model	Metric	Baseline (Mean ± Std)	ODC (Mean ± Std)	ODC-BoT (Mean ± Std)	Δ (95% CI)	p-value
SDXL	CLIP ↑	30.306 ± 3.517	31.741 ± 3.399	32.205 ± 3.202	1.436 [1.251, 1.621]	$< 10^{-46}$
	BLIP ↑	0.6080 ± 0.0082	0.6123 ± 0.0075	0.6129 ± 0.0070	0.0042 [0.0038, 0.0046]	$< 10^{-68}$
FLUX.1	CLIP ↑	29.275 ± 3.732	29.722 ± 3.610	30.232 ± 3.564	0.447 [0.306, 0.587]	$< 10^{-9}$
	BLIP ↑	0.6076 ± 0.0078	0.6083 ± 0.0077	0.6097 ± 0.0073	0.0007 [0.0004, 0.0010]	$< 10^{-4}$

Our analysis confirms reliable improvements in alignment scores, with robust gains observed for both CLIP Score (SDXL: $p < 10^{-46}$, FLUX.1: $p < 10^{-9}$) and BLIP Score (SDXL: $p < 10^{-68}$, FLUX.1: $p < 10^{-4}$). Crucially, across all configurations, the 95% confidence intervals for the performance delta Δ (ODC $-$ Baseline) lie strictly above zero, demonstrating that ODC consistently improves alignment without compromising baseline fidelity. This statistical robustness is further corroborated by our human evaluation (Table 4), where domain experts consistently favored ODC-corrected images.

E Quantitative Assessment of Visual Fidelity

To verify that ODC preserves visual fidelity, we conduct a quantitative evaluation using the Kernel Inception Distance (KID) (Bińkowski et al., 2018) across both the CoalBench-300 and PartiPrompts datasets. KID measures the distributional similarity between the images generated by ODC and the unmodified baseline. As an unbiased estimator of the squared Maximum Mean Discrepancy (MMD), KID can yield slightly negative values due to sampling variance; in practice, a score near zero indicates that the two distributions are statistically indistinguishable. As summarized in Table A3, the near-zero or marginally negative scores observed for both SDXL and FLUX.1 confirm that ODC does not degrade visual fidelity.

Table A3: Image Fidelity Assessment (ODC vs. Baseline) via KID Score (Mean ± Std) ↓. Near-zero or negative scores indicate no measurable degradation in image fidelity.

Model	CoalBench-300	PartiPrompts
SDXL	0.00093 ± 0.00023	0.00034 ± 0.00015
FLUX.1 [schnell]	-0.00152 ± 0.00008	-0.00095 ± 0.00011

These results validate the core design of ODC. The method functions as a surgical modification to the conditioning space, successfully removing semantic drift components while ensuring the generated images remain firmly within the manifold of natural image distributions.

F Additional Qualitative Results

In this section, we provide further qualitative results to complement the main paper. These examples demonstrate our method's ability to improve prompt-image alignment and preserve visual fidelity across a diverse set of prompts.

Figure A3: Additional qualitative results comparing baseline generations with Orthogonal Drift Correction (ODC). For each prompt, we show the output from the baseline SDXL model (left) and our ODC-corrected version (right).

Figure A4: Additional qualitative results comparing baseline generations with Orthogonal Drift Correction (ODC). For each prompt, we show the output from the baseline FLUX.1 model (left) and our ODC-corrected version (right).

G   Retrieved Drift Vocabulary $\mathcal{S}_{\text{orth}}$

To provide examples of the retrieved vocabulary used by ODC, we list the top-5 terms ($\mathcal{S}_{\text{orth}}$) for the exact prompts featured in our qualitative results (Figure 2) in Table A4. These terms serve as the discrete textual surrogate for the isolated orthogonal drift vector ($\mathbf{v}_{\text{orth}}$). ODC utilizes the embeddings of these top-5 terms in aggregate to define the removal direction. Consequently, while individual words may appear abstract in isolation, their combined embedding closely approximates the true semantic drift direction, allowing ODC to target the spurious concepts accurately.

Table A4: Retrieved Drift Vocabulary ($\mathcal{S}_{\mathrm{orth}}$) for Representative Prompts

Index	Prompt Text	Model	Retrieved Drift Words ($\mathcal{S}_{\mathrm{orth}}$)	Interpretation
151	A tree whose leaves are made of delicate, colored glass	SDXL	`stained glass art`, `glass art`, `light panels`, `light panel`, `glasswork`	Unintended glass/art style elements.
149	A medieval feast with ghosts sitting amongst the living guests	SDXL	`the abbess`, `illustre`, `preillustration`, `overillustration`, `tabernacler`	Misplaced religious/illustrative terms.
30	Paint brushes growing like flowers in pot	SDXL	`utensils or brushes`, `craft materials`, `brush land`, `petrographer`, `makeup kit`	Spurious, unrelated tools/materials.
4	Cherry blossoms falling on samurai armor	SDXL	`wallpaper`, `rider and horse`, `person horse`, `illustre`, `art wall decor`	Misplaced compositional elements.
46	Giant mushroom houses in enchanted forest	SDXL	`mushroom by`, `forest floor`, `agaricic`, `agaricales`, `toader`	Unexpected botanical elements.
63	Clockwork owl perched on moon	SDXL	`tartary`, `overillustration`, `odontolith`, `nightfowl`, `antecavern`	Unrelated archaic/anatomical terms.
280	Candy-coated castle melting under sunrise...	SDXL	`enchanted landscape`, `castle on`, `fantasy scene`, `rapunzel`, `castle`	Generic fantasy tropes overriding details.
203	Victorian astronaut playing violin inside ornate greenhouse...	SDXL	`the duo`, `musicians`, `a duet`, `twopenny`, `the two brothers`	Erroneous secondary subject.
300	Thunderstorm brewing inside snow globe...	SDXL	`in the winter`, `house in the`, `with snow`, `semiglobe`, `snow globe`	Literal winter concepts overriding interior.
10	Northern lights dancing above crystal ice castle	FLUX.1	`iglulirmiut`, `alpenglow`, `the arctic ocean`, `arcticwards`, `icelidae`	Unexpected arctic/celestial concepts.
24	Giant teacup island in cloudy sky	FLUX.1	`islandlike`, `that island`, `land formation`, `an island`, `a small island`	Detail misinterpreted as geography.
185	A collection of magical potions, glowing on a dusty shelf	FLUX.1	`liquor bottles`, `small bottles`, `alcohol bottles`, `bottles of liquor`, `bottle liquor`	Mundane domain overriding fantasy context.
85	Floating geometric islands at sunset	FLUX.1	`these islands`, `some islands`, `many islands`, `air lane sunrise`, `small islands`	Repetitive island concepts.
31	Lighthouse made of stacked books	FLUX.1	`lighthouse picture`, `lighthouse`, `light house`, `lighthouse base`, `the lighthouse`	Redundant literal subject terms.
158	A mountain range shaped like a sleeping stone dragon	FLUX.1	`the western alps`, `the alps`, `the eastern alps`, `the italian alps`, `the fra mauro formation`	Geographic literalism over metaphor.
291	Lavender fields beneath glass dome...	FLUX.1	`beekeeping`, `lavender plants`, `apiary`, `pollenlike`, `the pollen`	Real-world agriculture over sci-fi.
150	An underwater city inhabited by elegant, humanoid sea creatures	FLUX.1	`the new atlantis`, `undersea`, `the ocean floor`, `underseas`, `the sea bottom`	Environmental setting overriding architectural subject.
268	Digital renaissance fair where knights duel using AR dragons	FLUX.1	`dragonlike`, `a dragon`, `their armor`, `dragon statue`, `their armour`	Literal dragons/armor over AR concept.