Learning Rules with Stratified Negation in Differentiable ILP

Abstract

Differentiable methods to learn rules (logic programs) have the potential to integrate the interpretability, transferability and low data requirements of inductive logic programming with the noise tolerance of non-symbolic learning. While negation is an essential component of reasoning, incorporating it into a logic programming framework poses several problems (hence its central place in the logic programming and nonmonotonic reasoning communities). Current implementations of differentiable rule learners either exclude negation entirely or else treat it only in passing. In this work, we introduce stratified negation into a differentiable inductive logic programming framework, and we demonstrate that the resulting system can learn recursive programs in which negation plays a central role. We include examples from multiple domains, e.g., arithmetic, graph, sets and lists.

1 Introduction

Learning logic programs using gradient descent-based methods has the potential to integrate the interpretability, transferability, and low data requirements of inductive logic programming (ILP) with the noise tolerance of non-symbolic learning. In recent years, several differentiable rule learning systems have been introduced (discussed below). Nevertheless, while negation is a critical component of reasoning (expressing some concepts, e.g., *prime* and *unconnected*, require it) and it plays a central role in formal logic, knowledge representation, automated theorem proving, and other fields, several existing implementations either explicitly exclude negation, do not mention it, or else treat it only in passing.

Incorporating negation into differential ILP poses some challenges. The use of unrestricted negation may result in inconsistent reasoning. Care must be taken to ensure that negation is added using some reasoned methodology (such as stratification) and that the resulting system allows interesting programs to be learned via gradient descent.

In this work, using the differentiable inductive logic programming system ∂ILP [5] as the underlying framework, we add stratified, safe negation (i.e., as used in Datalog[3]), and we demonstrate that our system can learn recursive programs that fundamentally rely on negation.

Our **main contributions** are the following:

1. We modify ∂ILP to incorporate stratified negation [1]. This requires extending both the syntax and the semantics for clauses and modifying the forward chaining deduction process to ensure that consequences are correctly computed *wrt* stratified negation.

2. We present ILP problems of varying complexity requiring negations from several domains (arithmetic, graphs, sets and lists). We use these to demonstrate that our system is expressive and that our modifications work well with gradient descent-based learning of programs.

Submitted to 35th Conference on Neural Information Processing Systems (aiplans 2021). Do not distribute.

3. In order to reduce ambiguity in final programs without sacrificing the space of learnable programs, we introduce 'entropy of rule weights' as a regularizer.[1]

Related Works: The ∂ILP [5] system which we extend uses forward-chaining inference and allows predicate invention and recursion in learned rules. To reduce complexity, ∂ILP restricts the the search space of rules using rule templates. *Differentiable Neural Logic-ILP* [10] also uses forward-chaining but does not require restrictive rule templates, and allows Boolean functions in rule bodies. The examples presented, however, do not involve negation, and it is unclear (to us) how the system, particularly since it utilizes forward-chaining with a maximum number of steps, performs on learning relations depending on negation. *Neural Logic Inductive Learning* [14] also allows unrestricted rule bodies, but the examples presented again do not contain negation. In *Neural logic machines* [4], rules are encoded as weights of a network, and so extracting symbolic rules would be nontrivial.

Neural Theorem Provers (NTPs) [11, 12] use differentiable backward-chaining to reason over distributed representations of constants and predicates as well as generalized rule structures. Negation (which requires special care in classical backward chaining) is not addressed. Campero et al. [2] describe a forward-chaining framework similar to NTPs (again using vector representations of predicates and constants). The authors compare it to ∂ILP and indicate that generates correct results more frequently. Negation is not addressed, however. Regarding systems based on semantics for logic programs with negation, Nickles [9] presents *differentiable Satisfiability and Answer Set Programming*. This system learns sets of models rather than rules, however, and so it has a different focus.

2   Methods

Inductive logic programming (*ILP*) [7, 8] is a machine learning framework in which the learned hypothesis is a logic program. A background knowledge base B and sets of positive and negative examples (P, N) are used as inputs, and the objective is to generate a program Π such that $\Pi \cup B \models a$ for all $a \in P$ and $\Pi \cup B \not\models a$ for all $a \in N$. Here, $\Pi \models a$ means that a is a consequence of Π.

The *ILP* framework is agnostic to the specific logic programming syntax and semantics used. In ∂ILP, the hypotheses are *definite logic programs*, i.e., collections of rules (clauses) r of the form $a \; :- \; b_1, b_2, \ldots, b_n$, where a and each b_i are *atomic formulas* (*atoms*) and $head(r) = a$ and $body(r) = \{b_1, \ldots, b_n\}$. An atom, e.g., $p(d, X)$, is a predicate (p) followed by constant (d) and variable (X) *terms*.[2] In ∂ILP, B, P, and N are sets of *ground* atoms (i.e, no variables appear), while no constants appear in rules. This is essentially positive *Datalog* [3].

If Π is definite, the ground atoms a such that $\Pi \cup B \models a$ can be computed via the *immediate consequence operator* T_Π which maps interpretations to interpretations. An interpretation $\mathcal{I}$ is a set of ground atoms; atom a is *true* in $\mathcal{I}$ iff $a \in \mathcal{I}$, and it *false* is otherwise. Below, $G(\Pi)$ is the set of ground rules made from all of the the rules of Π.

$$T_\Pi(\mathcal{I}) = \{head(r) | \text{ rule } r \in G(\Pi) \text{ and each member of } body(r) \text{ is true according to } \mathcal{I}\}$$

Intuitively, we start with $\mathcal{I} = \varnothing$ and apply T_Π to incrementally perform forward-chaining inference. If Π is definite, a monotonically nondecreasing sequence of interpretations is created which eventually reaches a fixpoint. The fixpoint is precisely the set of all ground atomic consequences of Π.

∂ILP: One approach in ILP is a top-down generate-and-test approach where all possible programs (from a given template) are generated and evaluated on the training data. This problem can be posed as an instance of SAT by assigning Boolean flags to the candidate clauses and stipulating that the resulting programs must be consistent with the training data. ∂ILP([5]) is a differentiable relaxation of 'ILP as SAT' approach. Programs are generated with trainable continuous weights on collections of clauses. Logical deduction occurs via forward chaining performed to a preset limit. Deduction also utilizes differentiable operators: $\wedge$ is replaced by multiplication, and $\vee$ is replaced by maximum. The (real valued) evaluation of each ground atom is obtained by forward chaining of programs computing it. The loss value is given by the cross entropy between values computed for ground instances of target predicate and the positive/negative examples. Gradient descent is used to train

---

[1] ∂ILP defines 'entropy of rule weights' as a measure of the number of programs with non-zero weights learned. We use this as a regularizer in the loss term as explained in the implementation.

[2] As in ∂ILP, we disallow function expressions as terms.

weights, and the program with the highest weight is taken as output. So, solving the ILP becomes an optimization problem of the form: $min_W L(Q, C, W)$ where Q is the ILP problem, C is the set of clauses generated using a program template, W is the set of weights and L is the loss function measuring the accuracy of the program (or prediction from program).

Stratified Negation: $\partial\texttt{ILP}$ restricts hypotheses to be sets of definite clauses, and while the semantics is straightforward, the restriction is significant. The more expressive *normal logic programs* allow negated atoms $\neg b$ in rule bodies. One difficulty with them is that the forward chaining process used for definite programs cannot be directly applied. E.g., if $\neg b$ is false when b is true and vice versa, forward chaining would alternate between $\{\}$ and $\{a, b\}$ when given the rules $\{a \; :- \; \neg b, b \; :- \; \neg a\}$. Similar behavior occurs in $\partial\texttt{ILP}$ if we take the $value(\neg b) = 1 - value(b)$ (see Appendix A).

One widely known semantics for normal logic programs is based on *stratified negation* [1]. It is only defined for *stratified* programs, i.e., programs Π which can be partitioned into subsets Π_1, ..., Π_k such that for any Π_i and any rule $r \in \Pi_i$, if $b \in body(r)$, the rules defining b are contained in $\bigcup_{j \leq i} \Pi_j$, and if $\neg b \in body(r)$, the rules defining b are contained in $\bigcup_{j < i} \Pi_j$. The idea is to use T_Π to compute the fixpoint for Π_1 and use the result to provide truth values for the negative literals in Π_2. The consequences of Π_2 can then be computed. A new sequence of interpretations is defined which terminates in what is sometimes called the *perfect model* of Π. Semantics for stratified normal logic program is discussed further in Appendix B

Implementation of safe stratified negation in $\partial\texttt{ILP}$: The following are the major modifications that we made to $\partial\texttt{ILP}$ to implement safe, stratified negation. Our clause generation respects stratification. The strata themselves are specified as part of the $\partial\texttt{ILP}$ program template, along with names and arities of predicates to be learned. $\partial\texttt{ILP}$ requires clauses to be *safe*, i.e., every variable in the head of a rule appears in the body of the rule (i.e., `p(X) :- q(Y)` is not safe). We generalize safety to normal clauses by requiring that all variables of a rule appear in positive (non-negated) atoms in the body. Our clause generation process allows negation and respects stratification and safety. An example is included in Appendix D. The negation of an atom P is evaluated as $value(\neg P) = 1 - value(P)$, and forward chaining is done on a stratum-by-stratum basis. This is implemented using binary masks with value of 1 when predicate belong in current stratum, 0 otherwise. The total number of forward chaining steps were equally divided for the number of strata.

To prevent high entropy of the rule weights, we introduced average entropy of the rule weights as a regularization term in loss as $L = 0.5 * H(P) + 0.5 * H(N) + \gamma * avgH(R)$ where L is the loss, H is the cross entropy, P and N are positive and negative examples respectively, γ is the learning rate and R is the rule weights. We used a small γ, so the regularization does not prevent trajectory from leaving local minima. We varied the number of steps of forward chaining (5 to 15 steps per strata), learning rate (from 0.0001 and 0.05) and regularization coefficient (from 10e-4 to 10e-2). To prevent class imbalance on positive and negative examples, we used equal weighted cross-entropy from prediction for positive and negative training data. We noted that when a run converges with low loss, but with high entropy, more than 1 program with non-zero weight, the correct program (with respect to the training data) may not be weighted the highest. In these cases, we observed that the 3 highest weighted programs included correct program.

3 Experiments and Results

We tested our framework [3] on problems requiring negation with varying levels of complexity across different domains (non-monotonic logic, arithmetic, graph, sets and lists). Table 1 summarizes our result.[4] Here we outline the problems considered. For details of the ILP problem, see Appendix E.

We first considered negation in programs with a single clause using a classical example from non-monotonic logic ("all birds fly except penguins"). This problem can be expressed as a disjunction of all birds with flight, but has a simpler program with negation. We then considered $A \wedge \neg B$, which is the simplest program requiring negation. In the domain of sets, the problem of learning $\notin$ given elements of a set is similar, but more complex as it has two types of constants - sets and

---

[3]Implimentation of our framework is available at https://anonymous.4open.science/r/dilp-negation-code-for-review-04E2

[4]We give only one of the learned programs, and we removed guards needed for safety e.g., learned program would be 'prime(X):-¬ factor(X), x=x. For brevity, we use | to indicate the disjunction of clauses.

Table 1: Programs learned and convergence in ∂ILP with stratified negation.

Name	Program Found	Convergence
Bird fly	`fly(X):- birds(X), ¬ penguin(X).`	100 %
A not B	`target(X) :- A(X), ¬ B(X).`	100 %
Prime	`prime(X) :- ¬ factor(X, Y).`	100 %
	`factor(X,Y) :- div(X,Y), ¬ eq(X,Y).`	
Relative Prime	`rprime(X) :- ¬ comFactor(X, Y).`	50 %
	`comFactor(X,Y) :- div(X,Z), div(Y,Z).`	
Not Element	`notEle(X,Y) :- ¬ element(X,Y).`	100 %
Not Subset	`notSubset(X,Y) :- ele(X,Z), notEle(Y,Z).`	10 %
	`notEle(X,Y):- ¬ ele(X,Y).`	
Not in List	`ListNotEle(X,Y) :- ¬ListEle(X,Y).`	100 %
	`ListEle(X,Y):-head(X,Y)	tail(X,Z), head(Z,Y).`	
Unconnected	`unconn(X,Y):- ¬ path(X, Y).`	93 %
	`path(X,Y):- edge(X,Y)| edge(X,Z),path(Z,Y).`	
Monopoly	`m(X,Y):- gpath(X,Y),¬ rpath(X, Y).`	85 %
	`rpath(X,Y):- redge(X,Y)| redge(X,Z),rpath(Z,Y).`	
	`gpath(X,Y):- gedge(X,Y)| gedge(X,Z),gpath(Z,Y).`	

elements (that are undifferentiated). We then examined problems requiring invented predicates and negation (such as prime and relative-prime, given divisibility as background), and $\not\subset$ (given sets and elements as background).[5] We also examined graph problems requiring negation and recursive invented predicates. These include unconnected vertices (given the edges of a directed graph as background) and *monopoly* i.e., the existence of a green-path but not a red-path in an edge coloured graph (given the edge-colours of a directed, edge coloured graph as background). We also considered 'not an element of' a list, which requires recursion as a list is coded using $head$ and $tail$ predicates.

Our system was able to learn correct programs from very small training sets (loss across experiments are given in Appendix C). The domain of sets includes two types of objects (sets and elements), this generated a lot of type-incorrect ground atoms causing majority of learned program to only check for type instead of the correct programs.

For selected examples (less than, predecessor, family relationships), we ensured that our system reproduces results from ∂ILP [5]. Furthermore, we verified that the problems from Table 1 cannot be solved by ∂ILP without negation, and that unsafe or unstratified negation does not converge (Appendix C), and we examined the noise tolerance in the "birds fly" problem, where the system was able to identify the correct program even with high (up to 70%) noise (Appendix C). We expect these result to generalize to other problems.

The learned program is taken as the clauses with the highest weights after training. However, there are several conditions when the distribution of weights are distributed across multiple clauses even when the loss converged. To prevent these conditions, we used the average entropy of weights across clauses as a regularizer. This significantly reduced average rule entropy, specifically from 0.12 to 10e-4 for prime problem, Appendix C.

4 Discussion and Conclusion

We modified the ∂ILP framework to incorporate safe, stratified negation. Our system was able to learn programs that require invented predicates, recursion and negation across several domains (arithmetic, graphs, sets and lists). We also identified entropy of rule weights as a useful regularizer. Our method is motivated by well-studied theoretical considerations. So, it can be generalized to other differentiable implementations of ILP. As such, any application of differentiabale inductive logic programming, such as Reinforcement Learning [13, 6] can benefit from our work.

---

[5]Here, $\subset$ is expressed with an implication. So it is directly expressed as the negation of $\not\subset$.

References

[1] K. R. Apt, H. A. Blair, and A. Walker. Chapter 2 - towards a theory of declarative knowledge. In J. Minker, editor, *Foundations of Deductive Databases and Logic Programming*, pages 89–148. Morgan Kaufmann, 1988.

[2] A. Campero, A. Pareja, T. Klinger, J. Tenenbaum, and S. Riedel. Logical rule induction and theory learning using neural theorem proving. *CoRR*, abs/1809.02193, 2018.

[3] S. Ceri, G. Gottlob, and L. Tanca. What you always wanted to know about datalog (and never dared to ask). *IEEE Transactions on Knowledge and Data Engineering*, 1(1):146–166, 1989.

[4] H. Dong, J. Mao, T. Lin, C. Wang, L. Li, and D. Zhou. Neural logic machines. In *International Conference on Learning Representations*, 2019.

[5] R. Evans and E. Grefenstette. Learning Explanatory Rules from Noisy Data. *Journal of Artificial Intelligence Research*, 61:1–64, Jan. 2018.

[6] Z. Jiang and S. Luo. Neural Logic Reinforcement Learning. In *International Conference on Machine Learning*, pages 3110–3119. PMLR, May 2019.

[7] S. Muggleton and L. de Raedt. Inductive logic programming: Theory and methods. *The Journal of Logic Programming*, 19-20:629–679, 1994. Special Issue: Ten Years of Logic Programming.

[8] S. Muggleton, L. D. Raedt, D. Poole, I. Bratko, P. A. Flach, K. Inoue, and A. Srinivasan. ILP turns 20 - biography and future challenges. *Mach. Learn.*, 86(1):3–23, 2012.

[9] M. Nickles. Differentiable SAT/ASP. In E. Bellodi and T. Schrijvers, editors, *Proceedings of the 5th International Workshop on Probabilistic Logic Programming, PLP 2018, co-located with the 28th International Conference on Inductive Logic Programming (ILP 2018), Ferrara, Italy, September 1, 2018*, volume 2219 of *CEUR Workshop Proceedings*, pages 62–74. CEUR-WS.org, 2018.

[10] A. Payani. *Differentiable neural logic networks and their application onto inductive logic programming*. PhD thesis, Georgia Institute of Technology, Atlanta, GA, USA, 2020.

[11] T. Rocktäschel and S. Riedel. Learning knowledge base inference with neural theorem provers. In J. Pujara, T. Rocktäschel, D. Chen, and S. Singh, editors, *Proceedings of the 5th Workshop on Automated Knowledge Base Construction, AKBC@NAACL-HLT 2016, San Diego, CA, USA, June 17, 2016*, pages 45–50. The Association for Computer Linguistics, 2016.

[12] T. Rocktäschel and S. Riedel. End-to-end differentiable proving. In I. Guyon, U. von Luxburg, S. Bengio, H. M. Wallach, R. Fergus, S. V. N. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 3788–3800, 2017.

[13] D. Xu and F. Fekri. Interpretable Model-based Hierarchical Reinforcement Learning using Inductive Logic Programming. *arXiv:2106.11417 [cs]*, June 2021.

[14] Y. Yang and L. Song. Learn to explain efficiently via neural logic inductive learning. In *International Conference on Learning Representations*, 2020.

A   Problems with Unrestricted Negation — Examples

Negation causes problems for forward chaining inference even in systems (such as ∂ILP) where interpretations assign real values from the interval [0,1] to atoms. In the following examples, we only need to consider the extreme case where 0 and 1 are used. Where $\mathcal{I}$ is an interpretation, we will use $\mathcal{I}(a \wedge b) = \mathcal{I}(a) * \mathcal{I}(b)$ and $\mathcal{I}(\neg a) = 1 - \mathcal{I}(a)$. For a clause c, the truth value of the clause head is the truth value of the body. That is, $\mathcal{I}(head(c)) = \mathcal{I}(body(c))$. This is a slight abuse of notation, since multiple clauses can have the same head, but it is justified below.

T_Π is defined in essentially the same way as in the classical case: In $T_\Pi(\mathcal{I})$, the truth value of each atom a is the maximum truth value (according to $\mathcal{I}$) of the clauses having a as head. Note that this is equivalent to combining the rules for a given atom into a single rule, using $\vee$ to join the original rule bodies together. Here $\mathcal{I}(b_1 \vee \ldots \vee b_n) = max(\mathcal{I}(b_1), \ldots, \mathcal{I}(b_n))$.

A.1   Example 1

Let Π be the following program. We assume `true` always has the value 1. The program is stratified, and though there are cycles, they are indirect. The basic structure of the program is consistent with the restrictions on rules specified in ∂ILP extended with negation.

```
a :- true.
b :- ¬a.
c :- b.
c :- d.
d :- b.
d :- c.
```

The sequence of stepwise interpretations is given below. $\mathcal{I}_2$ is a fixpoint. Neither c nor d should derivable, but they are.

$\mathcal{I}_0 = \{a = 0, b = 0, c = 0, d = 0\}$
$\mathcal{I}_1 = T_\Pi(\mathcal{I}_0) = \{a = 1, b = 1, c = 0, d = 0\}$
$\mathcal{I}_2 = T_\Pi(\mathcal{I}_1) = \{a = 1, b = 0, c = 1, d = 1\}$
$\mathcal{I}_3 = T_\Pi(\mathcal{I}_2) = \{a = 1, b = 0, c = 1, d = 1\}$

Note that this result is obtained using simple stepwise forward chaining. If we amalgamate the interpretations using either $\mathcal{I}_{t+1} = max(\mathcal{I}_t, T_\Pi(\mathcal{I}_t))$ or probabilistic sum $\mathcal{I}_{t+1} = \mathcal{I}_t + T_\Pi(\mathcal{I}_t) - \mathcal{I}_t * T_\Pi(\mathcal{I}_t))$ as Evans and Grefenstette suggest, then b would also be derivable, which is arguably a worse result. In the absence of stratification, because iterating T_Π from $\varnothing$ is no longer guaranteed to be monotonic, amalgamating interpretations as ∂ILP does will sometimes lead to unsound inferences.

Note that Π is stratified in this example (the first clause should be in a lower stratum than the others). Using the semantics for stratified negation, we would conclude that the value of a is 1 before we ever consider the value for b. Ultimately, the values for b, c, and d are 0, which is intuitively correct.

We should stress that we are not saying that what Evans and Grefenstette are doing is incorrect. ∂ILP learns definite clauses. We're merely pointing out that adding negation necessitates making alterations elsewhere in order to avoid making inferences most people would say are incorrect.

A.2   Example 2

```
a :- ¬b.
b :- ¬a.
```

The stepwise sequence defined using T_Π will alternate between interpretations $\{a = 0, b = 0\}$ and $\{a = 1, b = 1\}$. If we instead combine interpretations using probabilistic sum or max, then $\{a = 1, b = 1\}$ is the fixpoint reached, meaning both a and b are derivable. Note that in this example, Π is not stratified and so has no model according to the semantics for stratified programs. In our view, that's an intuitively better result than concluding that both a and b.

B Semantics for Stratified Normal Logic Programs

The following account is based in part on Apt et al. [1]. Here, Π is a stratified normal logic program.

Given a fixed vocabulary of constants, function symbols, and predicate symbols for Π, the set of all ground terms definable over that vocabulary is the Herbrand universe H_Π of Π, and the set of all ground atoms is the Herbrand base B_Π. An Herbrand interpretation $\mathcal{I}$ of Π is any subset of B_Π. $\mathcal{I}$ is a *model* of a ground rule r iff $head(r)$ is true in $\mathcal{I}$ or some element of $body(r)$ is false in $\mathcal{I}$. $\mathcal{I}$ is a *model* of a non-ground rule r iff it is a model of every rule in $G(r)$, where $G(r)$ is the ground instantiation of r. Similarly, $\mathcal{I}$ is a *model* of Π if it is a model of every rule of Π.

Herbrand interpretations can be ordered using subset inclusion ($\mathcal{I}_1 \leq \mathcal{I}_2$ iff $\mathcal{I}_1 \subseteq \mathcal{I}_2$). If Π is definite, there is a unique minimal model $MM(\Pi)$ of Π that coincides with the ground atoms entailed by Π and which can be computed via T_Π. We define a sequence of interpretations using some $\mathcal{I}$ as basis.

- $T_\Pi \uparrow 0(\mathcal{I}) = \mathcal{I}$
- $T_\Pi \uparrow \alpha(\mathcal{I}) = T_\Pi(T_\Pi \uparrow \alpha - 1(\mathcal{I})) \cup T_\Pi \uparrow \alpha - 1(\mathcal{I})$ for all successor ordinals α
- $T_\Pi \uparrow \beta(\mathcal{I}) = \bigcup_{\alpha < \beta} T_\Pi \uparrow \alpha(\mathcal{I})$ for all limit ordinals β.

For definite programs, if $\mathcal{I} = \varnothing$, the sequence is non-decreasing and reaches $MM(\Pi)$ at $T_\Pi \uparrow \omega(\varnothing)$, a fixpoint. If Π is normal, there might not be a unique minimal model, but a model with with desirable properties can be obtained by defining a new sequence based on a stratification $\Pi_1, \ldots, \Pi_k$ of Π.

- $M_1 = T_{\Pi_1} \uparrow \omega(\varnothing)$
- $M_i = T_{\Pi_i} \uparrow \omega(M_{i-1})$ for all $1 < i \leq k$

The final interpretation M_k is the perfect model of the program and taken as defining the ground atomic consequences of Π. It is a minimal model of Π [1], and it is supported (each $a \in M_k$ is either a fact or the head of a ground rule whose body is true in the model).

C Additional details on experimental results

Figure 1: Convergence across different experiments.Each plot shows the loss value across training epochs. Number of runs converged defined as loss $\leq 10^{-3}$ were identified as convergent.

Example Prime with Entropy Regularization ($\gamma = 0.001$)

Example Prime without Entropy Regularization ($\gamma = 0.0$)

Figure 2: Effect of regularization on entropy in prime problem. A. Average entropy of rule weights for experiments on Prime problem with and without regularization, taken after training (1000 steps). B. Example distribution of the rule weight for one trial with regularization (and without), shows several rules had high weights for run without regularization.

The figure 1 shows the loss plotted against training epochs for various experiments. We ran 20 trials for each of the problem. The figures shows the different convergence behaviour of the problems. Number of runs converged defined as loss $\leq 10^{-3}$ were identified as convergent. Loss is computed as incorrect classifications of training examples. As mentioned in the method section, we introduced entropy as a regularizer in the loss, we examined the distribution of weights after convergence (Figure 2) and found that including regularization term to loss reduced entropy resulted in only one of the clause to have high weight for each of the learned head predicates. In contrast, when the regularization term was not used, even in case when loss converged, many clauses contributed to the output which is used as prediction and increase the ambiguity of the program learned by the framework.

We then tested if stratification was required for solving problem with negation. In case of unconnected and monopoly problem, which required 2 and 3 strata respectively, we tested convergence and program learned for stratified and unstratified (all clauses in same strata). We found that the loss was higher than 10^{-3} for most the unstratified condition (Figure 3) and the programs identified were incorrect. Finally, we varied the noise for the birdfly problem, whose results are presented in Figure 4.

D   Clause generation

This section discusses the generation of safe and stratified clauses.

D.1   Stratification

Stratification involves assigning predicates to strata and is a well understood method to prevent inconsistencies when negation is introduced. Below we demonstrate how stratification is introduced

Figure 3: Stratification is required for convergence. Trials with and without stratification run for Monopoly and Unconnected problems. For experiments without stratification, all the predicates were made to be at same (0) strata.

Figure 4: Effect of noise in Bird fly problem. Noise was introduced by changing percentage of positive examples to negative example for training. In all these cases, the program fly(X):- birds(X), ¬ penguin(X) was correctly identified, even in case of 75% noise. Loss value was higher for higher noise level, since the learned program did not predict the correct response for dataset. Higher noise level did not converge.

in different programs. We start with assigning lowest strata to background, positive and negative. Then, the invented predicates are assigned the subsequent strata and final output or target predicate is given the highest strata. Below, we illustrate the reason for this assignment using examples.

Consider the program :
```
unconn(X,Y) :- ¬path(X, Y)
path(X,Y) :- edge(X,Y)
path(X,Y) :- edge(X,Z), path(Z,Y)
```

This can be stratified as follows:
stratum(`edge`) = 1
stratum(`path`) = 1 (or $n \geq 1$)
stratum(`unconn`) = 2 (or $m > n$)

`path` can call itself recursively, since stratification allows predicates of the same stratum as head to be used positively in the body. However, `unconn` uses path negatively, and so `unconn` has to be of a higher stratum than path.
Consider another example :
```
p(X):-q(X)
```

```
306  q(X):-p(X).
```
307 is also stratified as `p` and `q` can have same stratum.

308 However,
```
309  p(X) :- ¬p(X)
```
310 cannot be stratified, as stratum(p) in head should be greater than stratum(p) in body.

311 Similarly,
```
312  p(X):-q(X)
313  q(X):- ¬p(X)
```
314 is not.

D.2 Safety

316 Safety as in ∂ILP: For each clause, the set of variables in the head should be a subset of the variables
317 in the body. For instance,
```
318  p(X,Y) :- q(X,Z), p(Y,Y).
```

319 However, `p(X,Y) :- q(X,Z), p(X,Z).` is not safe as y is present in the head but not the body.

320 Safety with negation: The set of variables present in negatively occurring predicates in a clause must
321 be a subset of the variables present in positively occurring clauses. Since the head is a negative
322 predicate, this is just a generalization of the rule above.

323 Example: `p(X,Y) :- q(X,Y), ¬r(X,X).` is safe.

324 However, `p(X,Y) :- q(X,Y), ¬r(X,Z).` is not safe.

D.3 Some consequences

326 Given the safety conditions, and the binary restrictions from ∂ILP (specifically that each clause has 2
327 predicates), there can be at most one negated predicate in the body of any clause. Since each program
328 can have at most 2 clauses, a recursive program has one base clause and one recursive clause. Further,
329 if the recursive call does not contain a variable not in the head, then a terminating recursion can be
330 unfolded to a fixed finite number of steps. This later consequence happens in ∂ILP as well.

E ILPs learned

E.1 Birds fly, except for penguins

333 The task here is to (ideally) learn the program `fly(X):- birds(X),¬ penguin(X)` from back-
334 ground knowledge consisting of instances of birds, given as $bird(X), \forall X \in C$, C is a set of constants,
335 type of bird, given as $type(X)$, where $type \in$ eagle, sparrow, owl, parrot, hawk, penguin and ability
336 of fly as positive and negative examples given as $fly(X)$ which is $True$ for all birds and $False$ when
337 X is penguin.

E.2 $A \wedge \neg B$

339 The task is to learn `target(X) :- a(X), ¬b(X)` from background knowledge consisting of in-
340 stances of `a` and `b` and positive examples being the constants that are in `a` but not `b`.

E.3 Prime

342 The task here is to learn a program for primes. The constants included $\{2, 3, 4, 5, 6, 7, 8, 9\}$. We do
343 not include 1 as a constant since it is neither prime nor composite. In this setting, a prime number has
344 only itself as a factor. Background included equal and divisible, as `div(x,y)` for any constant x that
345 is a multiple of the constant y and `eq(x,x)` for every constant x. The positive and negative examples
346 were prime and composite numbers among the constants.
347 Other programs found include:
```
348  prime(X) :- ¬pred(X), div(x,x).
349  pred(X) :- div(X,y), ¬eq(x,y).
```
350

E.4 Relatively Prime

The task here is to learn a program for relative primes from background knowledge consisting of the binary predicate factor and equality. We also need a guard-predicate that includes all pairs of numbers to meet our safety requirements. As before we do not include 1. Program: `relPrime(X,Y):- ¬ commonFactor(X,Y). commonFactor(X,Y):-factor(X,Z), factor(Y,Z).`

E.5 Unconnected

The task here is to learn the graph problem of unconnected. The background knowledge encodes a directed graph with the constants being the vertices, and a binary predicate giving the directed edges. The positive examples included the pairs (x, y) of unconnected vertices, and the negative examples included the connected ones. The intended program requires an invented recursive predicate, e.g., `unConn(X,Y):- ¬ path(X,Y), guard(X,Y)` and the base case for path being `path(X,Y):-edge(X,Y)` and the recursive case for path being `path(X,Y):-edge(X,Z), path(Z,Y).`

Instead of giving an external guard predicate, we made our examples such that given any pair of vertices x and y, either there was a path from x to y or there was a path from y to x. The system was able to find this and use it as a guard, i.e., `unConn(X,Y):- ¬ path(X,Y), path(Y,X).`

The predicate for the path varied with different runs, e.g., the recursive case could be `path(X,Y):-path(X,Z), path(Z,Y).`

E.6 Monopoly

The task here is to learn the graph problem of monopoly: given a directed, edge coloured graph, $mon(x, y)$ holds iff there is a green path from x to y but no red path from x to y. The constants were vertices of a graph, and the background (binary) predicates were `red` and `green` encoding red and greed edges. The positive examples included pairs of vertices satisfying the property mon above.

Even when the system had difficulty finding the correct target programs, it was able to learn the correct auxiliary predicates for red and green path.

E.7 Not element

The task here is to learn a program for $\notin$. The constants include $\{p, q, r, 1, 2, 3, 4\}$ with p, q and r intended to represent sets and 1, 2, 3 and 4 representing elements. The background knowledge included binary predicates $\in$ and `guard`. This problem is similar to $A \wedge \neg B$, but has the added complexity of two types and multiple tokens of each type.

E.8 Not Subset

The task here is to learn the program $\not\subseteq$. The constants and background knowledge are as above. Positive examples are pairs of sets X and Y such that $X \not\subseteq Y$, i.e., $\exists z. Z \in X \wedge Z \notin Y$. The indented program uses the background predicate $\in$ and a learned predicate $\notin$.

The relation $\subseteq$ is defined using implication, i.e. $X \subseteq Y$ holds iff $\forall Z. Z \in X \rightarrow Z \in Y$. As a program this would be `sub(X,Y) :- ¬ ele(Z,X) OR ele(Z,Y)`. The issue is the use of OR here that connects the two occurrences of Z. A more straight forward program would be to learn $\not\subseteq$ and then use it negatively. Thus, $\not\subseteq$ is more basic than $\subset$ in this setting.

E.9 Not Element of a list

The task here is to learn the program 'not a member of the list'. Th constants are $\{p_1, p_2, q_1, q_2, 0, 1, 2, 3, \}$ where p_i, q_i and 0 are lists and 1, 2, 3 are elements of the list. (0 represents the NULL list). The background predicates are $head$ and $tail$ (e.g., the list [1,2] would be $head(p_1, 1), tail(p_1, p_2), head(p_2, 2)$ and $tail(p_2, 0)$. Thus, to find is a given element is the member of a list, a recursive predicate is needed. The ILP problem to find the member of a list was done in the original ∂ILP. Our positive examples included non-members, i.e., pairs X and Y where Y is NOT a member of the list X.