CycleGen: Closing the Loop in Long-Form Text Generation via Loop-Aware Refinement

Abstract

Long-Form text generation is critical for applications ranging from creative writing to technical documentation, yet large language models (LLMs) struggle to maintain structural integrity and logical coherence over extended outputs. Existing linear generation paradigms inadequately capture cyclic semantic dependencies, in which subsequent content retroactively constrains preceding segments. To address this, we propose **CycleGen**, a framework that reformulates long-form text generation as a graph-based cyclic synthesis process. CycleGen comprises: (1) a data engine that constructs dependency graphs, applies a MinFAS-inspired algorithm to resolve logical cycles, and encodes backward constraints via closed-loop correction; and (2) a progressive alignment strategy that decouples optimization objectives through multi-stage training with Graph-Critical IPO, DPO, and SimPO. We further introduce **CycleBench** for evaluating long-range cyclic reasoning capabilities. Experiments on WritingBench, LongGenBench, and CycleBench demonstrate that CycleGen outperforms similarly sized models and achieves performance rivaling significantly larger models. We have released our code and CycleBench at the anonymous repository: **CycleGen Repo**.

1 Introduction

Recent years have seen significant advances in long-context understanding, with LLMs now processing up to 1M tokens (Su et al., 2024). However, long-form generation remains a challenge (Liu et al., 2024; Anil et al., 2022). Users often require multi-dimensional constraints like length, structure, and style, but existing models struggle to maintain coherence over extended outputs (Guan et al., 2021). As shown in Figure 1 (Left), linear generation's unidirectionality prevents anticipating backward constraints, causing logical breaks. As length increases, models exhibit contradictions and catastrophic forgetting (Bai et al., 2024; Becker et al.,

Figure 1: Comparison between unidirectional linear generation and CycleGen's refinement-based cyclic generation. (Left) Traditional models fail to anticipate backward constraints, leading to logical inconsistencies. (Right) CycleGen models cyclic dependencies and uses refinement to achieve a global logical closed loop and successful payoff of foreshadowing.

2024). These issues stem from an inability to model cyclic semantic dependencies, where future content retroactively constrains earlier segments—such as aligning a revelation in Chapter B with foreshadowing in Chapter A.

While modern LLMs process contexts up to 1M tokens (Su et al., 2024), long-form generation still faces significant hurdles (Liu et al., 2024; Anil et al., 2022). Models often fail to meet multi-dimensional constraints (e.g., length, style) or maintain coherence over extended outputs (Guan et al., 2021). As Fig.1 (Left) illustrates, linear generation lacks the foresight to handle backward constraints, causing logical breaks. This degradation manifests as contradictions and catastrophic forgetting as length increases(Bai et al., 2024; Becker et al., 2024). Primarily, models struggle with cyclic semantic dependencies where subsequent content constrains preceding segments. For example, aligning a revelation with earlier foreshadowing requires bidirectional modeling that linear generation lacks.

Prior work attributes this bottleneck to distributional bias in SFT data (Bai et al., 2024) or adopts

plan-then-write paradigms to decompose generation into hierarchical sub-tasks (Wan et al., 2025; Xia et al., 2025). However, these methods remain grounded in linear topologies and fail to capture the complex cyclic dependencies ubiquitous in high-quality text.

Bridging this gap requires addressing three core challenges: (1) Modeling cyclic semantic dependencies. Human writing involves non-linear planning where future content retroactively constrains earlier passages. Current paradigms forcibly linearize these structures, discarding essential backward constraints. (2) Internalizing explicit planning. Explicit reasoning like Chain-of-Thought (Wei et al., 2022) is unstable in ultra-long contexts. Models must internalize planning-backtracking-revision into implicit parameter-space capabilities for one-pass generation. (3) Balancing multi-objective optimization. Long-form generation must simultaneously satisfy length, consistency, and quality. Naive reinforcement learning often drives models toward single-dimension extrema, such as increasing length via redundancy.

To address these, we propose CycleGen, a framework reformulating long-form generation as a graph-based cyclic synthesis process. As illustrated in Figure 1 (Right), CycleGen models cyclic dependencies and uses a refinement mechanism to retroactively revise content based on future constraints, achieving a logical closed loop. CycleGen includes two components: (1) Data Engine. We build directed dependency graphs where cycles represent inter-chapter relationships. We frame decycling as a Minimum Feedback Arc Set (MinFAS) problem, using a greedy algorithm to convert graphs into Directed Acyclic Graphs (DAGs). For narrative tasks, a Loop-Aware Refinement mechanism reincorporates removed cyclic edges via bidirectional rewriting, ensuring self-consistency. For hierarchical tasks, the framework reverts to efficient linear generation. (2) Progressive Alignment Strategy. We design a multi-phase pipeline, first injecting long-form capabilities via supervised fine-tuning. We then use a three-stage reinforcement learning scheme (Graph-Critical IPO, DPO, and SimPO) to transition from length control to complex joint constraints, internalizing planning into one-pass generation.

Our main contributions are summarized as follows:

- We propose CycleGen, a graph-based framework that models cyclic semantic dependencies via MinFAS decoupling and loop aware refinement, overcoming the limitations of linear generation paradigms.

- We design a progressive multi-stage alignment strategy that decouples optimization objectives for logical coherence, length control, and narrative quality, distilling explicit graph-planning into one-pass generation capabilities.

- We introduce CycleBench, a benchmark for evaluating long-range cyclic reasoning. Experiments show that CycleGen outperforms similarly sized models on WritingBench, LongGenBench, and CycleBench, achieving performance rivaling significantly larger models.

2 Related Work

2.1 Long-Form Text Generation Bottlenecks

Despite recent progress in scaling context windows to millions of tokens, LLMs continue to struggle with long-form text generation. LongWriter (Bai et al., 2024) identifies the core bottleneck as distributional bias in supervised fine-tuning data: the scarcity of ultra-long training samples (with the majority under 2K tokens) prevents models from acquiring semantic consistency and structural control across extended outputs. While architectural innovations like RoPE (Su et al., 2024), FlashAttention (Dao et al., 2022), and Mamba (Gu and Dao, 2024) enable efficient processing of long contexts, they do not directly address generation quality. Building on this data bottleneck hypothesis, we synthesize high-quality long-form training data with explicit cyclic dependencies to better support generation capabilities.

2.2 Controllable Text Generation

Controllable text generation (CTG) aims to produce text satisfying specific attributes such as length, sentiment, or structure. Existing approaches include learning-free methods like FreeCtrl (Feng et al., 2024), which adjusts FFN weights to control keywords, and prompt-based methods like Plan-and-Write (Akinfaderin et al., 2025) for length control. MARKERGEN (Yuan et al., 2025) adopts plug-and-play strategies with external tools, while LDPE (Butcher et al., 2025) injects positional information to internalize length constraints. While

effective for short texts or specific tasks, these methods remain limited for long-form text generation: learning-free approaches focus on surface-level constraints and cannot control complex narrative structures, while prompt-based methods rely on linear planning and fail to model cyclic dependencies such as foreshadowing and payoff. In contrast, CycleGen internalizes controllability by constructing training data with explicit non-linear logical dependencies and applying progressive alignment, thereby enabling joint control over length and deep logical consistency.

2.3 Planning-Based Long-Form Text Generation

To address logical discontinuities in long-form text generation, the plan-then-generate paradigm has emerged as an alternative to pure autoregressive decoding. Early hierarchical methods like Re3 (Yang et al., 2022) and DOC (Yang et al., 2023) produce high-level outlines followed by expansion, while recent agent-based approaches like Story-Writer (Xia et al., 2025) and SuperWriter (Wu et al., 2025a) employ multi-agent collaboration and Monte Carlo Tree Search to simulate human writing cycles. Despite improving local coherence, these methods remain constrained by linear or tree-structured topologies that assume unidirectional information flow and cannot model bidirectional dependencies, such as plot twists retroactively constraining earlier descriptions. CycleGen addresses this by modeling plans as directed graphs that explicitly permit cycles and applying Loop-Aware Refinement to handle non-linear logical revisions, achieving global self-consistency.

3 Problem Formulation

3.1 Problem Definition

We formulate the task of long-form text generation as follows: given instruction I, generate an ordered sequence of N semantic blocks (e.g., chapters or key events).

$$\mathcal{S} = \{S_1, S_2, \ldots, S_N\}, \tag{1}$$

with total length $L \gg 10k$ tokens. Standard LLMs model this via autoregressive decomposition.

$$P(\mathcal{S} \mid I) \approx \prod_{t=1}^{N} P_\theta(S_t \mid S_{<t}, I). \tag{2}$$

This assumes each block S_t depends only on historical context $S_{<t}$. While this assumption works well

for short texts, it fails in long-form narratives with complex non-local dependencies. Purely forward generation then produces outputs that are locally coherent but globally inconsistent.

3.2 Cyclic Semantic Dependencies

To characterize dependencies in long-form text, we distinguish two types of relationships between semantic blocks S_i and S_j $(i < j)$:

Forward Causal Dependency: $P(S_j \mid S_i) \neq P(S_j)$. This follows temporal order, where preceding conditions determine subsequent outcomes (e.g., "obtaining a key" enables "opening a chest"). Autoregressive models naturally capture such dependencies.

Backward Teleological Constraint: $P(S_i \mid S_j) \neq P(S_i)$. This reflects authorial intent, where a desired ending S_j retroactively constrains earlier content S_i. For instance, if S_j introduces an unexpected twist, earlier blocks must include appropriate foreshadowing to maintain consistency.

During autoregressive generation of S_i, future blocks S_j remain unobserved, acting as latent variables. The model cannot evaluate $P(S_i \mid S_j, S_{<i})$ and must rely on $P(S_i \mid S_{<i})$. This invisibility of future information limits global planning: without backward constraints, early decisions risk logical conflicts with future developments, causing narrative inconsistency.

4 Methodology

To address the structural mismatch between linear autoregressive generation and cyclic logical dependencies in long-form text, CycleGen introduces a graph-based closed-loop data engine in Phase I. The engine explicitly models cross-section dependencies and emulates the human writing workflow of planning, drafting, and revision through cycle decoupling and recovery.

4.1 Phase I: Cycle Graph Data Engine

As shown in Figure 2, Phase I aims to construct high-quality training data by explicitly manipulating graph structures to resolve logical consistency issues in long texts. This process involves three steps: graph construction, cycle decoupling, and bi-directional refinement.

Semantic Dependency Graph Construction and Decoupling. Given an instruction and an outline $\mathcal{O} = \{v_1, \ldots, v_N\}$, we construct a directed

Figure 2: Workflow of the CycleGen data engine (Phase I), illustrating cycle decoupling for linear generation and cycle recovery via bi-directional refinement.

weighted graph G to model the logical dependencies between sections. To balance efficiency and accuracy, we adopt a hybrid "retrieve-then-reason" strategy that explicitly decouples semantic relevance from causal inference. First, we compute pairwise cosine similarities s_{ij} using a pretrained embedding model (Qwen3-Embedding-4B) solely to filter candidate pairs that exhibit high semantic overlap ($s_{ij} > 0.4$). This similarity score indicates potential relatedness but implies no causal direction.

Subsequently, for each filtered candidate pair, a LLM is employed to **explicitly infer the causal direction** based on logical context (e.g., determining the flow from "foreshadowing" to "revelation"). This two-stage process ensures that edge directions are derived from reasoning rather than mere semantic proximity.

Since autoregressive generation requires a topological order, we must convert the cyclic graph G into a DAG. We model this as the Minimum Weight Feedback Arc Set problem, identifying and removing the minimal feedback arc set E_{FAS} by weight:

$$E_{FAS} = \arg \min_{E' \subset E} \sum_{(u,v) \in E'} w_{uv},$$
$$\text{s.t. } G' = (V, E \setminus E') \text{ is a DAG.} \quad (3)$$

The resulting G_{DAG}, after removing E_{FAS}, establishes the topological order for section generation, enabling the model to parallelly generate an initial draft $\mathcal{Y}_{raw}$ based on summaries of predecessors and optional RAG retrieval.

Bi-Directional Refinement and Data Synthesis. The initial draft $\mathcal{Y}_{raw}$ inevitably contains logical discontinuities due to the removal of strong dependency edges (E_{cut}). As depicted on the right side of Figure 2, we exploit the cyclic in-

formation in the original graph G to perform bi-directional refinement. For each removed dependency $(v_j \rightarrow v_i) \in E_{cut}$, we jointly input the drafts y_i and y_j into the refinement model. The model restores logical coherence by either amending y_i (e.g., adding a missing prerequisite) or revising y_j (e.g., adjusting a subsequent development), ultimately generating a logically self-consistent text $\mathcal{Y}_{refined}$. This process not only produces high-quality text but also naturally constructs the preference data pairs $(\mathcal{Y}_{refined}, \mathcal{Y}_{raw})$ for the subsequent alignment stage.

4.2 Phase II: Progressive Alignment Strategy

Long-Form text generation involves multiple, often conflicting objectives: micro-level logical consistency, macro-level length compliance, and overall narrative quality. Naive end-to-end optimization (e.g., applying standard DPO across all objectives simultaneously) suffers from severe gradient conflicts and objective mismatch. For instance, optimizing for length often degrades logical coherence via redundant babbling, while optimizing for quality naturally introduces a length bias.

To disentangle these conflicts, CycleGen proposes a progressive alignment strategy. Rather than heuristically stacking algorithms, we match the unique mathematical properties of different RLHF variants with specific optimization requirements. The sequence of the pipeline strictly follows a dependency chain of text generation: first establishing semantic correctness (logic), then defining structural boundaries (length), and finally refining textual aesthetics (quality). As shown in Figure 3, this staged pipeline sequentially addresses different constraint dimensions.

Stage 0: Supervised Fine-Tuning (SFT). We first perform supervised fine-tuning on high-quality corpora $\mathcal{D}_{sft}$ synthesized by the data engine, enabling the model to adapt to long-context attention patterns and basic formatting conventions:

$$\mathcal{L}_{\text{SFT}} = -\mathbb{E}_{(x,y) \sim \mathcal{D}_{sft}} \sum_{t=1}^{|y|} \log P_\theta(y_t \mid y_{<t}, x).$$
$$(4)$$

Stage 1: Graph-Critical IPO for Logical Consistency. The first alignment stage establishes logical coherence before strict length limits are imposed. The preference pairs (y_w, y_l) represent loop-aware corrected drafts vs. original linear drafts. A profound challenge here is Gradient Dilution:

Figure 3: Architecture of the Progressive Alignment Strategy (Phase II). To resolve objective conflicts, we establish a rigid dependency chain: Stage 1 (GC-IPO) applies bounded regularization for local logical repairs; Stage 2 (DPO) enforces global length constraints; and Stage 3 (SimPO) optimizes narrative aesthetics while inherently preventing length inflation via normalization.

y_w and y_l share over 90% token overlap. Standard DPO is ill-suited here; its sigmoid-based loss pushes preference margins toward infinity, which causes severe over-optimization and degradation when applied to highly overlapping sequences. Instead, we design *Graph-Critical IPO*. We first define a localized masked log-probability utilizing graph structure to isolate bifurcation points:

$$\log \pi_\theta(y|x) = \sum_{t=1}^{T} w_t \cdot \log P_\theta(y_t|y_{<t},x), \quad (5)$$

where $w_t = 1$ for critical difference regions and $w_t = \lambda \ (\lambda = 0.1)$ otherwise. we adopt the IPO objective (Gheshlaghi Azar et al., 2024):

$$\mathcal{L}_{\text{GC-IPO}} = \mathbb{E}_{\mathcal{D}} \left[\left(\log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} \right. \right.$$
$$\left. \left. - \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} - \frac{\tau}{2} \right)^2 \right]. \quad (6)$$

IPO utilizes a squared loss that introduces an inherent margin regularization bounded by τ. This prevents the model from aggressively over-fitting to minor local token variations, making it the theoretically optimal choice for micro-level consistency alignment.

Stage 2: DPO for Strict Length Compliance. Unlike local logical edits, length compliance is a global, sequence-wide attribute evaluated as a binary state (within bounds vs. out of bounds). Standard DPO's sequence-level likelihood comparison aligns with this global pacing requirement, forcing the model to adjust its narrative rhythm rather than relying on truncation. Once logical coherence is established, Stage 2 enforces rigid macro-level boundaries (L_{target}). Preference pairs $\mathcal{D}_{len}$ are constructed where $y_w \in [0.9L_{target}, 1.2L_{target}]$ and y_l falls outside.

Formally, we adopt the standard DPO objective (Rafailov et al., 2023):

$$\mathcal{L}_{\text{DPO}} = -\mathbb{E}_{(x,y_w,y_l)\sim\mathcal{D}_{len}} \left[\log \sigma \left(\beta \log \frac{\pi_\theta(y_w|x)}{\pi_{\text{ref}}(y_w|x)} \right. \right.$$
$$\left. \left. - \beta \log \frac{\pi_\theta(y_l|x)}{\pi_{\text{ref}}(y_l|x)} \right) \right] \quad (7)$$

Stage 3: SimPO for Structure–Quality Joint Optimization. The final stage refines the overall narrative aesthetics. A critical risk at this stage is undoing the length constraints achieved in Stage 2. Standard DPO calculates implicit rewards by summing log-probabilities, which inherently biases the model to generate longer texts to achieve higher rewards (Length Bias). To prevent this catastrophic forgetting of length constraints, we adopt SimPO (Meng et al., 2024). Its core theoretical advantage is length normalization:

$$\mathcal{L}_{\text{SimPO}} = -\mathbb{E}_{(x,y_w,y_l)\sim\mathcal{D}} \left[\log \sigma \left(\frac{\beta}{|y_w|} \log \pi_\theta(y_w|x) \right. \right.$$
$$\left. \left. - \frac{\beta}{|y_l|} \log \pi_\theta(y_l|x) - \gamma \right) \right]. \quad (8)$$

By normalizing the reward by sequence length $|y|$, SimPO forces the model to maximize the average

generation quality per token rather than blindly expanding length. This specifically targets the structure-quality trade-off, ensuring that the stylistic improvements do not violate the length boundaries established in Stage 2.

Through these progressive stages, CycleGen disentangles multi-dimensional constraints, resulting in a one-pass long-from text generator that simultaneously achieves logical closure, strict length adherence, and high narrative quality.

5 Experiments

We evaluate the proposed CycleGen through various experiments to demonstrate its effectiveness. Before presenting the experimental results, we first describe the experimental setup.

5.1 Experimental Setup

Model Configurations. We evaluate two settings: CycleGen-8B, built on Qwen3-8B and trained with 21k samples synthesized by our Phase I Data Engine, and CycleGen-Agent-32B, using Qwen3-32B as the backbone with our cycle graph construction and bi-directional refinement mechanisms.

Training Details. Experiments are conducted on $8 \times$ NVIDIA H200 GPUs (141GB). SFT uses 15k samples (1k test/val) with a batch size of 16, 10^{-4} learning rate, and 3 epochs. RL alignment utilizes a 6k preference dataset with a 10^{-6} learning rate for 2 epochs.

Benchmarks and Metrics. We adopt three benchmarks to assess long-form generation.

WritingBench (Wu et al., 2025c) evaluates quality across 6 domains and 3 requirements (Style, Format, Length) using a 1–10 scale, focusing on expressiveness and instruction adherence. It is distributed under the Apache-2.0 license.

LongGenBench (Wu et al., 2025b) tests planning up to 16k tokens under structural constraints, measured by metrics like Completion Rate and Average Accuracy. The data is available for research purposes; both benchmarks comply with original source terms and exclude sensitive personal information.

CycleBench is our benchmark of 100 tasks (50 Chinese, 50 English) featuring 2–4 cyclic logical dependencies. It evaluates if models resolve circular constraints where future content retroactively constrains earlier passages, assessing global planning and consistency. Metrics include Pass Rate,

Score thresholds (Score $\geq 6, \geq 8$), Length Satisfaction (LS), and Length Deviation (LD).

5.2 Main Results

Results on WritingBench. We evaluate one-shot generation performance on WritingBench, Table 1 shows the results. CycleGen-8B achieves an average score of 7.57, substantially outperforming similar-scale baselines including LongWriter-7B, Qwen-2.5-7B-filtered, and Qwen3-8B. Notably, CycleGen-8B even surpasses the larger Qwen3-32B at 7.48, demonstrating that our Data Engine substantially enhances long-form text generation capabilities in smaller models.

For the agent framework, CycleGen-Agent-32B achieves 7.76, outperforming the reasoning-enhanced Deepseek-R1 at 7.70 and ranking second only to Claude-3.7-thinking at 7.91. This further validates the effectiveness of graph-structured guidance in raising the upper bound of long-form writing quality.

Results on LongGenBench. We evaluate agent planning capabilities on LongGenBench, which requires generating extremely long texts under strict structural constraints. Table 2 shows the results.

CycleGen-Agent-32B achieves competitive performance across all metrics. On range-based accuracy, CycleGen-Agent-32B reaches 0.86, substantially outperforming GPT-4o + CogWriter (Wan et al., 2025) at 0.76, demonstrating superior length control through our structure-guided refinement mechanism. For single-shot instruction adherence, CycleGen-Agent-32B achieves 0.85 compared to 0.76 for Llama-3.3-70B + CogWriter (Wan et al., 2025), validating the effectiveness of our progressive alignment strategy. Overall, CycleGen-Agent-32B attains an average accuracy of 0.75, exceeding existing agent frameworks. Overall, these results indicate that graph-based planning with Loop-Aware Refinement provides more precise control than conventional planning approaches.

Results on CycleBench. We further evaluate model performance under highly complex constraints on CycleBench. Table 3 presents the results.

CycleGen-8B demonstrates strong long-range logical consistency, achieving a Pass Rate of 0.50, compared to 0.34 for the base Qwen3-8B and 0.46 for the larger Qwen3-32B. It also attains a higher high-quality generation rate (Score ≥ 8) of 0.56. These results suggest that internalizing graph-based

Model	Avg	Languages		Domains						Requirements					
		ZH	EN	D1	D2	D3	D4	D5	D6	R1	C	R2	C	R3	C
Proprietary LLMs															
Claude-3.7-thinking	**7.91**	7.9	**7.9**	**7.9**	7.8	**7.8**	**8.0**	**8.0**	**8.1**	**7.9**	**8.7**	**8.0**	8.4	**8.0**	**8.1**
Qwen-Max	7.16	7.2	7.1	7.1	6.9	7.0	7.3	7.4	7.5	7.2	8.3	7.3	7.8	7.2	7.5
GPT-4o	6.81	6.9	6.7	6.8	6.6	6.7	6.8	7.0	7.1	6.9	8.0	7.0	7.5	6.8	6.8
Open-source LLMs															
Deepseek-R1 (Guo et al., 2025)	7.70	**8.0**	7.5	7.6	7.4	7.6	7.8	7.8	**8.1**	7.7	8.4	7.9	8.3	7.7	7.5
Deepseek-V3 (DeepSeek-AI et al., 2025)	6.35	6.3	6.4	6.4	6.1	6.2	6.3	6.6	6.8	6.4	7.6	6.5	7.1	6.5	6.4
Qwen3-32B (Yang et al., 2025)	7.48	7.7	7.2	7.4	7.3	7.5	7.5	7.5	7.8	7.6	8.2	7.5	8.3	7.5	7.3
Qwen3-8B (Yang et al., 2025)	6.65	6.8	6.5	6.7	6.7	6.6	6.4	6.9	6.8	6.7	7.2	6.8	7.9	6.5	6.7
Qwen2.5-72B (Qwen et al., 2025)	6.53	6.5	6.5	6.5	6.3	6.5	6.5	6.7	6.7	6.7	7.2	6.7	7.8	6.8	6.9
Capability-enhanced LLMs															
LongWriter-7B (Bai et al., 2024)	6.27	6.2	6.4	6.4	6.4	6.3	6.0	6.5	6.0	6.3	7.4	6.3	6.7	6.3	6.8
Qwen-2.5-7B-filtered (Wu et al., 2025c)	7.44	7.7	7.2	7.4	7.2	7.5	7.3	7.7	7.7	7.5	8.4	7.6	8.1	7.4	7.2
CycleGen-8B(Ours)	7.57	7.4	7.4	7.5	7.9	7.4	7.3	7.8	7.8	7.7	8.0	7.5	**8.5**	7.4	7.5
Agent Framework															
CycleGen-Agent-32B(Ours)	7.76	7.8	7.7	**7.9**	**8.0**	7.7	7.5	7.8	7.7	7.7	7.9	7.8	7.7	7.4	6.4

Table 1: WritingBench performance of different LLMs across 6 domains and 3 writing requirements evaluated with our critic model (scale: 1-10). The six domains include: (D1) Academic & Engineering, (D2) Finance & Business, (D3) Politics & Law, (D4) Literature & Art, (D5) Education, and (D6) Advertising & Marketing. The three writing requirements assessed are: (R1) Style, (R2) Format, and (R3) Length. Here, "C" indicates category-specific score.

Model / Agent Framework	Comp. Rate	Acc. Once	Acc. Range	Acc. Periodic	Avg. Acc.
Llama-3.1-70B-Instruct (Touvron et al., 2023)	0.79	0.50	0.51	0.18	0.39
GPT-4o	0.63	0.47	0.45	0.20	0.37
Mixtral-8x7B-Instruct-v0.1	0.83	0.42	0.45	0.24	0.37
Qwen2-7B-Instruct	0.40	0.48	0.39	0.19	0.35
GPT-4o-mini	0.97	0.42	0.34	0.18	0.31
Qwen3-8B	0.27	0.15	0.09	0.10	0.11
Llama-3.3-70B-Instruct + CogWriter	**1.00**	0.76	0.79	0.55	0.70
GPT-4o + CogWriter	0.91	0.80	0.76	**0.67**	0.74
CycleGen-Agent-32B(Ours)	0.96	**0.85**	**0.86**	0.53	**0.75**

Table 2: Agent capability evaluation on LongGenBench. We focus on comparing agent frameworks. The results show that CYCLEGEN achieves higher control precision and task success rates in long-form text generation compared to existing agent frameworks such as CogWriter.

planning into model parameters substantially improves long-form text generation.

We further analyze agent-based variants. CycleGen-Agent-32B (Refine) improves the Pass Rate from 0.58 to 0.65, validating the effectiveness of Loop-Aware Refinement in repairing logical inconsistencies and strengthening cyclic closure in generated texts.

5.3 Ablation Study

To quantify the contributions of different stages in the CycleGen framework, we conducted an ablation study. The results are presented in Table 4.

The results in Table 4 (Rows 1–4) demonstrate the performance trajectory across the three alignment stages. Although the baseline SFT model (Row 1) is already trained on the full synthesized dataset, the subsequent stages facilitate further refinement:

- Introducing logical constraints in Stage 1 (GC-IPO) improves the Score ≥ 6 rate from 0.79 to 0.86. This indicates that contrastive preference optimization on graph-critical regions enhances the model's ability to handle logical bifurcation points more effectively than standard supervised learning.

- Stage 2 (DPO) primarily addresses structural requirements, yielding a stable length satisfaction rate (LS 0.11) and lower deviation compared to the intermediate result in Row 2.

- Stage 3 (SimPO) further optimizes the narrative quality, achieving the highest high-quality output rate (Score $\geq 8 = 0.56$) while maintaining consistency across other metrics.

Comparison with Mixed DPO Training. To assess the necessity of the multi-stage pipeline, we compare it with a Mixed DPO baseline (Row 5), where all optimization objectives are addressed simultaneously. Despite using the same dataset, the Mixed DPO baseline underperforms in high-quality

Model	Pass Rate	Score ≥ 6	Score ≥ 8	LS(%)	LD(words)	Len.
LongWriter-7B	0.27	0.34	0.09	0.10	7,565	0.61
Qwen-2.5-7B-filtered	0.22	0.35	0.21	0.01	12,823	0.09
Qwen3-8B	0.34	0.38	0.20	0.17	6,388	0.70
Qwen3-32B	0.46	0.56	0.32	0.07	6,914	0.58
CycleGen-8B	0.50	0.84	0.56	0.11	6,581	0.59
Agent Framework						
CycleGen-Agent-32B (Raw)	0.58	0.97	0.68	0.23	3,879	0.83
CycleGen-Agent-32B (Refine)	**0.65**	**0.99**	**0.74**	**0.21**	**3,933**	**0.84**

Table 3: Evaluation results on CycleBench. **LS** denotes the average length satisfaction rate, and **LD** represents the average length deviation (in word count).

Configuration	Pass Rate	Score ≥ 6	Score ≥ 8	LS (%)	LD (words)	Len.
Model Training						
(1) CycleGen-SFT (Baseline)	0.51	0.79	0.49	**0.09**	6,681	6,420
(2) + Stage 1 (GC-IPO)	0.53	**0.86**	0.42	0.17	6,547	6,510
(3) + Stage 2 (DPO)	0.48	0.81	0.53	0.11	6,472	6,550
(4) + Stage 3 (SimPO)	0.50	0.84	**0.56**	0.11	6,581	6,580
(5) Mixed DPO	**0.55**	0.70	0.46	0.18	6,873	6,750
Agent Framework						
(6) CycleGen-Agent-32B (Raw)	0.58	0.97	0.68	0.23	3,879	3,950
(7) CycleGen-Agent-32B (Refine)	**0.65**	**0.99**	**0.74**	**0.21**	3,933	4,020

Table 4: Ablation study on CycleBench. We compare the base SFT model, the effects of progressive RL stages, a mixed training baseline, and the agent-based refinement mechanism.

generation (Score ≥ 8 of 0.46 vs. 0.56) and length control (LS 0.18 vs. 0.11). This suggests that decoupling the complex objectives of logical consistency, length constraints, and stylistic quality into sequential stages reduces optimization conflicts in long-form text generation.

Impact of the Refinement Mechanism. In the agent-based setting (Rows 6 and 7), incorporating the Loop-Aware Refinement mechanism increases the overall Pass Rate from 0.58 to 0.65. This improvement demonstrates the effectiveness of explicit iterative revision in resolving complex cyclic dependencies that may not be fully addressed in a single-pass generation, even by a model with internalized graph-aware capabilities.

6 Conclusion

This work tackles the fundamental tension between the inherently linear decoding process of LLMs and the circular logical dependencies common in long-form text generation. We introduce Cycle-Gen, a framework that explicitly models backward dependencies via a cycle graph data engine, and employs a progressive alignment strategy to mitigate multi-objective optimization challenges. To comprehensively evaluate structured reasoning and coherence in long narratives, we also release Cy-cleBench, a benchmark for assessing bidirectional logical consistency in long-form texts. Empirical results demonstrate that CycleGen substantially improves structural control and logical coherence even in small parameter models, highlighting the effectiveness of graph-guided generation and bidirectional refinement for long-text writing.

Limitations

Despite its effectiveness, this study has several limitations. First, while constructing a directed acyclic graph enables maximal parallelism of logical dependencies, the LLM-driven verification and iterative refinement steps incur substantial computational overhead. Second, the current graph modeling is restricted to chapter-level granularity, leaving finer-grained intra-chapter dependencies largely overlooked. Finally, the framework's performance is limited by the teacher model's reasoning capabilities. Mistakes in causal relationship identification during graph construction can propagate into the synthesized training data. Future work will aim to improve synthesis efficiency and extend graph modeling to finer-grained textual hierarchies, further enhancing the quality and consistency of long-form text generation.

References

Ayomide Akinfaderin, Sriram Subramanian, and Anurag Sehwag. 2025. Plan-and-write: Structure-guided length control for llms without model retraining. In *First International KDD Workshop on Prompt Optimization*.

Cem Anil, Yuhuai Wu, Anders Andreassen, Bo Dai, Yanzhi Li, Jure Leskovec, Daniel Johnson, and 1 others. 2022. Exploring length generalization in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 38546–38556.

Y. Bai, J. Zhang, X. Lv, and 1 others. 2024. Longwriter: Unleashing 10,000+ word generation from long-context llms. *arXiv preprint arXiv:2408.07055*.

Jonas Becker, Jan Philip Wahle, Bela Gipp, and Terry Ruas. 2024. Text generation: A systematic literature review of tasks, evaluation, and challenges. *arXiv preprint arXiv:2405.15604*.

Benjamin Butcher, Michael O'Keefe, and James Titchener. 2025. Precise length control for large language models. *Natural Language Processing Journal*, 11:100143.

Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. 2022. Flashattention: Fast and memory-efficient exact attention with io-awareness. In *Advances in Neural Information Processing Systems*, volume 35, pages 16344–16359.

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, and 181 others. 2025. Deepseek-v3 technical report. *Preprint*, arXiv:2412.19437.

Zihan Feng, Hao Zhou, Kai Mao, Yuhui Li, and Jie Zhang. 2024. Freectrl: Constructing control centers with feedforward layers for learning-free controllable text generation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7627–7640.

Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. 2024. A general theoretical paradigm to understand learning from human preferences. In *Proceedings of The 27th International Conference on Artificial Intelligence and Statistics*, volume 238 of *Proceedings of Machine Learning Research*, pages 4447–4455. PMLR.

Albert Gu and Tri Dao. 2024. Mamba: Linear-time sequence modeling with selective state spaces. In *First Conference on Language Modeling*.

Jian Guan, Xiaoxi Mao, Changjie Fan, Zitao Liu, Wenbiao Ding, and Minlie Huang. 2021. Long text generation by modeling sentence-level and discourse-level coherence. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 6379–6393, Online. Association for Computational Linguistics.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, and 175 others. 2025. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638.

Nelson F. Liu, Kevin Lin, John Hewitt, Bhargav Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.

Yu Meng, Mengzhou Xia, and Danqi Chen. 2024. Simpo: Simple preference optimization with a reference-free reward. In *Advances in Neural Information Processing Systems*, volume 37, pages 124198–124235. Curran Associates, Inc.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, volume 36, pages 53728–53741. Curran Associates, Inc.

J. Su, M. Ahmed, Y. Lu, and 1 others. 2024. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. Llama: Open and efficient foundation language models. *Preprint*, arXiv:2302.13971.

Kaiyang Wan, Honglin Mu, Rui Hao, Haoran Luo, Tianle Gu, and Xiuying Chen. 2025. A cognitive writing perspective for constrained long-form text generation. *arXiv preprint arXiv:2502.12568*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837. Curran Associates, Inc.

Yuhan Wu, Yuxin Bai, Zhen Hu, Jie Zhang, and Yuhui Li. 2025a. Superwriter: Reflection-driven long-form generation with large language models. *arXiv preprint arXiv:2506.04180*.

Yuhan Wu, Min Seok Hee, Zhen Hu, Yuxin Bai, Jie Zhang, and Yuhui Li. 2025b. Longgenbench: Benchmarking long-form generation in long context llms. In *The Thirteenth International Conference on Learning Representations*.

Yuning Wu, Jiahao Mei, Ming Yan, Chenliang Li, Shaopeng Lai, Yuran Ren, Zijia Wang, Ji Zhang, Mengyue Wu, Qin Jin, and Fei Huang. 2025c. Writingbench: A comprehensive benchmark for generative writing. *Preprint*, arXiv:2503.05244.

Haotian Xia, Hao Peng, Yunjia Qi, Xiaozhi Wang, Bin Xu, Lei Hou, and Juanzi Li. 2025. Storywriter: A multi-agent framework for long story generation. *arXiv preprint arXiv:2506.16445*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Kevin Yang, Dan Klein, Nanyun Peng, and Yuandong Tian. 2023. DOC: Improving long story coherence with detailed outline control. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3378–3465, Toronto, Canada. Association for Computational Linguistics.

Kevin Yang, Yuandong Tian, Nanyun Peng, and Dan Klein. 2022. Re3: Generating longer stories with recursive reprompting and revision. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 4393–4479, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Peng Yuan, Chuan Tan, Shuo Feng, Yuhui Li, and Jie Zhang. 2025. From sub-ability diagnosis to human-aligned generation: Bridging the gap for text length control via markergen. *arXiv preprint arXiv:2502.13544*.

A Appendix

A.1 CycleGen Data Synthesis Pipeline

Algorithm 1 CycleGen Data Synthesis Pipeline

Require: User instruction I, structured outline $\mathcal{O} = \{v_1, \ldots, v_N\}$, similarity threshold τ
Ensure: Preference pair $(\mathcal{Y}_{raw}, \mathcal{Y}_{refined})$
1: $V \leftarrow \mathcal{O}, E \leftarrow \emptyset$
2: $\mathbf{E} \leftarrow \text{EMBEDDING}(\mathcal{O})$
3: **for all** $(v_i, v_j) \in V \times V$ **do**
4:     $s_{ij} \leftarrow \cos(\mathbf{e}_i, \mathbf{e}_j)$
5:     **if** $s_{ij} > \tau$ **then**
6:         $(u, v, w) \leftarrow \text{LLM-VERIFY}(v_i, v_j)$
7:         **if** dependency exists **then**
8:             $E \leftarrow E \cup \{(u \rightarrow v, w)\}$
9:         **end if**
10:     **end if**
11: **end for**
12: $G \leftarrow (V, E)$
13: $E_{cut} \leftarrow \text{MINFAS}(G)$
14: $G_{DAG} \leftarrow (V, E \setminus E_{cut})$
15: Initialize array $\mathcal{Y}_{raw}$ of size N
16: $Batches \leftarrow \text{LAYEREDTOPOLOGICALSORT}(G_{DAG})$
17: **for all** $batch \in Batches$ **do**
18:     **parallel for** $v_i \in batch$ **do**
19:     $C_i \leftarrow \text{RETRIEVER}(\text{Predecessors}_{G_{DAG}}(v_i), \mathcal{Y}_{raw})$
20:     $y_i \leftarrow \text{LLM-GEN}(I, v_i, C_i)$
21:     $\mathcal{Y}_{raw}[i] \leftarrow y_i$
22:     **end parallel**
23: **end for**
24: $\mathcal{Y}_{refined} \leftarrow \mathcal{Y}_{raw}$
25: **for all** $(v_j \rightarrow v_i) \in E_{cut}$ **do**
26:     $(y_i', y_j') \leftarrow \text{LLM-REFINE}(\mathcal{Y}_{refined}[i], \mathcal{Y}_{refined}[j])$
27:     $\mathcal{Y}_{refined}[i] \leftarrow y_i'$
28:     $\mathcal{Y}_{refined}[j] \leftarrow y_j'$
29: **end for**
30: **return** $(\mathcal{Y}_{raw}, \mathcal{Y}_{refined})$

Algorithm 1 summarizes how CycleGen constructs preference pairs by detecting logical dependencies in an outline, enabling parallel DAG-based generation, and subsequently refining broken cyclic relations to restore global coherence.

A.2 Prompt Design Details

Figure 4: Generate Outline prompt.

Figure 4 shows the outline-generation prompt, which guides the model to produce a coherent, multi-level global structure rather than detailed text.

Figure 5: Generate Task prompt.

Figure 5 presents the task-generation prompt that maps the global outline into chapter-level writing objectives aligned with the overall plan.

Figure 6: Judge prompt.

Figure 6 illustrates the judge prompt used to infer directed dependency or refinement relations between chapter plans for graph construction.

Figure 7: Generate Chapter prompt.

Figures 7 and 8 depict the chapter generation and refinement prompts, which respectively produce draft content conditioned on predecessors and revise cyclically related chapters to improve global coherence.

Figure 8: Refine Chapter prompt.

A.3 Additional Experimental Analysis

As illustrated in Figure 9, CYCLEGEN achieves consistent improvements over baseline models across almost evaluation dimensions on Writing-Bench, indicating the robustness of the proposed framework.

Figure 9: Radar chart comparison of CYCLEGEN models across different dimensions on WritingBench. The left panel compares against open-source Qwen models, while the right panel compares against closed-source SOTA models.