GSURE-Based Diffusion Model Training with Corrupted Data

Abstract

Diffusion models have demonstrated impressive results in both data generation and down-stream tasks such as inverse problems, text-based editing, classification, and more. However, training such models usually requires large amounts of clean signals which are often difficult or impossible to obtain. In this work, we propose a novel training technique for generative diffusion models based only on corrupted data. We introduce a loss function based on the Generalized Stein's Unbiased Risk Estimator (GSURE), and prove that under some conditions, it is equivalent to the training objective used in fully supervised diffusion models. We demonstrate our technique on face images as well as Magnetic Resonance Imaging (MRI), where the use of undersampled data significantly alleviates data collection costs. Our approach achieves generative performance comparable to its fully supervised counterpart without training on any clean signals. In addition, we deploy the resulting diffusion model in various downstream tasks beyond the degradation present in the training set, showcasing promising results.

1 Introduction

Denoising diffusion probabilistic models (DDPMs) (Sohl-Dickstein et al., 2015; Ho et al., 2020; Song & Ermon, 2019), or diffusion models for short, are a family of generative models that has recently risen to prominence. They have achieved state-of-the-art performance in image generation (Song et al., 2020b; Vahdat et al., 2021; Dhariwal & Nichol, 2021; Rombach et al., 2022; Kim et al., 2022), as well as impressive generative modeling capabilities in other modalities (Ho et al., 2022; Singer et al., 2023; Kong et al., 2021; Popov et al., 2021; Gong et al., 2023; Li et al., 2022; Tevet et al., 2022), including protein structures (Watson et al., 2022; Qiao et al., 2022; Schneuing et al., 2022; Yim et al., 2023) and medical data (Song et al., 2023; Chung & Ye, 2022; Jalal et al., 2021; Xie & Li, 2022; Chung et al., 2023; Li et al., 2023; Adib et al., 2023). The prowess and flexibility of DDPMs have enabled their profound impact on downstream applications (Kawar et al., 2022; Theis et al., 2022; Blau et al., 2022; Pinaya et al., 2022; Wyatt et al., 2022; Kawar et al., 2023; Zimmermann et al., 2021).

Training a diffusion model to learn an unknown data distribution is a complex task. It usually requires training parameter-heavy neural networks on large amounts of pristine data. For instance, diffusion models' success in image generation was in part enabled by large curated datasets, containing millions or even billions of images (Deng et al., 2009; Schuhmann et al., 2022). However, such large-scale datasets of pristine samples may often be expensive, difficult, or even impossible to obtain, especially in the medical domain (Mullainathan & Obermeyer, 2022). In this work, we present GSURE-Diffusion, a method for training generative diffusion models based on data corrupted by linear degradations and Gaussian noise. This setting can make data collection for deep learning significantly faster and less expensive.

GSURE-Diffusion operates on a datasets of noisy linear measurements of signals, and assumes the signal acquisition process is randomized within a fixed general structure, which is the case in many real-world applications. In this setting, we present a novel loss function to learn the underlying data distribution. First, we use the Singular Value Decomposition (SVD) of the degradation operators to decouple the measurement equation, following DDRM (Kawar et al., 2022). Then, we add synthetic noise to the SVD-transformed

Figure 1: Training sets samples of the different degradation settings in CelebA (Liu et al., 2015) experiments.

measurements, likening them to the noisy samples used in the DDPM (Ho et al., 2020) framework. Finally, we use the ensemble version of the Generalized Stein's Unbiased Risk Estimator (GSURE) (Aggarwal et al., 2022; Eldar, 2008) to learn to denoise samples without access to ground-truth clean signals. Our proposed GSURE-based loss function is general to all randomized linear measurement settings, and we prove its equivalence to the fully supervised denoising diffusion loss under some conditions.

To empirically evaluate our technique, we apply it on a downsized grayscale version of CelebA (Liu et al., 2015), a dataset of celebrity face images. We train a GSURE-Diffusion model on noisy images with randomly missing patches, and compare its generative output with an oracle model that trained on the full clean images. We observe that GSURE-Diffusion results in comparable generative performance to the oracle, despite having trained solely on corrupted data.

Furthermore, we use GSURE-Diffusion for Magnetic Resonance Imaging (MRI), a ubiquitous medical imaging modality providing vital diagnostic information. Generative models for MRI are usually trained on datasets of fully sampled MR images, which can be expensive to obtain. In contrast, we train a generative model on noisy undersampled data obtained from accelerated MRI scans. By utilizing GSURE-Diffusion, we train a model with performance comparable to an oracle version while significantly reducing the time and resources required to collect the training dataset. Then, we showcase the flexibility of the generative diffusion model we obtain. We use this model for accelerated MRI reconstruction, extending its applicability to acceleration factors beyond those encountered during training. Moreover, this model may serve as a foundational framework for addressing various tasks. We demonstrate its capabilities in MRI reconstruction for different subsampling strategies and uncertainty quantification, and compare its results with an oracle version.

In conclusion, we present GSURE-Diffusion, a novel method for training generative diffusion models based on corrupted measurements of the underlying data. We demonstrate the capabilities of the method through several experiments, and show its applicability to real-world problems. We hope that GSURE-Diffusion will facilitate future work on generative modelling for challenging settings, generalizing for more complex scenarios and various modalities.

2 Background

2.1 Denoising Diffusion Probabilistic Models

Denoising Diffusion Probabilistic Models (DDPMs) (Ho et al., 2020) are a family of generative models that learn a distribution $p_\theta(\mathbf{x})$, approximating a data distribution $q(\mathbf{x})$ from a dataset $\mathcal{D}$ of samples. DDPMs follow a Markov chain structure $\mathbf{x}_T \rightarrow \mathbf{x}_{T-1} \rightarrow \cdots \rightarrow \mathbf{x}_1 \rightarrow \mathbf{x}_0$ that reverses a forward noising process from $\mathbf{x}_0$ to $\mathbf{x}_T$. In the forward process, $\mathbf{x}_0$ is set to be $\mathbf{x}$, and the intermediate variables $\mathbf{x}_t$ are defined by $q^{(t)}(\mathbf{x}_t|\mathbf{x}_{t-1})$, usually chosen to be a simple Gaussian $\mathcal{N}\left(\sqrt{1-\beta_t}\mathbf{x}_{t-1}, \beta_t\boldsymbol{I}\right)$. This leads to a useful property, $q^*(\mathbf{x}_t|\mathbf{x}_0) = \mathcal{N}\left(\sqrt{\bar{\alpha}_t}\mathbf{x}_0, (1-\bar{\alpha}_t)\boldsymbol{I}\right)$ with $\bar{\alpha}_t = \prod_{s=1}^{t}(1-\beta_t)$, which facilitates model training. In the reverse and more challenging process, the learned distribution $p_\theta^{(t)}(\mathbf{x}_{t-1}|\mathbf{x}_t)$ is also modeled as Gaussian, with a

No degradation $p=0.2, \sigma_0=0.01$ $p=0.4, \sigma_0=0.02$ $p=0.6, \sigma_0=0.03$

Figure 2: Generated samples (with 50 DDIM (Song et al., 2020a) steps) from models trained on different degradation settings in CelebA (Liu et al., 2015) experiments.

learned mean dependent on a neural network $f_\theta^{(t)}(\mathbf{x}_t)$ and a fixed (Ho et al., 2020) or learned (Nichol & Dhariwal, 2021) covariance.

The diffusion model $f_\theta^{(t)}(\mathbf{x}_t)$ is trained to optimize an evidence lower bound (ELBO) on the log-likelihood objective (Sohl-Dickstein et al., 2015). The ELBO can be simplified into the following denoising objective:

$$\sum_{t=1}^{T} \gamma_t \mathbb{E}\left[\left\|f_\theta^{(t)}(\mathbf{x}_t) - \mathbf{x}_0\right\|_2^2\right], \tag{1}$$

where the γ_t assign weights to different t (different noise levels), and the expectation is over some $\mathbf{x}_t \sim q(\mathbf{x}_t|\mathbf{x}_0)$, $\mathbf{x}_0 \sim q(\mathbf{x})$. Please refer to (Ho et al., 2020; Song et al., 2020a) for derivations. After training, diffusion models synthesize data by starting with a sample $\mathbf{x}_T \sim \mathcal{N}(0, \boldsymbol{I})$, following the learned distributions $p_\theta^{(t)}$ along the Markov chain, sampling from each, and outputting $\mathbf{x}_0$ as the final sample. Diffusion models have had incredible success in image generation (Song et al., 2020b; Vahdat et al., 2021; Dhariwal & Nichol, 2021; Rombach et al., 2022; Kim et al., 2022), as well as generation of other modalities (Ho et al., 2022; Singer et al., 2023; Kong et al., 2021; Popov et al., 2021; Gong et al., 2023; Li et al., 2022; Tevet et al., 2022). They have also been deployed in a myriad of related tasks (Kawar et al., 2022; Theis et al., 2022; Blau et al., 2022; Pinaya et al., 2022; Wyatt et al., 2022; Kawar et al., 2023; Zimmermann et al., 2021). In this work, we revisit DDPMs and seek a way to train them using only corrupted data.

2.2 Generalized Stein's Unbiased Risk Estimator (GSURE)

Given noisy measurements $\mathbf{y} = \mathbf{x} + \mathbf{z}$ (where $\mathbf{x}, \mathbf{y}, \mathbf{z} \in \mathbb{R}^n$) with noise $\mathbf{z} \sim \mathcal{N}(0, \sigma^2 \boldsymbol{I})$, and a function $f(\mathbf{y})$ aiming to estimate $\mathbf{x}$ from $\mathbf{y}$, Stein's unbiased risk estimator (SURE) (Stein, 1981) is an unbiased estimator for the mean squared error (MSE) of $f(\mathbf{y})$, formulated as

$$\mathbb{E}\left[\|f(\mathbf{y}) - \mathbf{x}\|_2^2\right] = \mathbb{E}\left[\|f(\mathbf{y}) - \mathbf{y}\|_2^2\right] + 2\sigma^2 \mathbb{E}\left[\nabla_\mathbf{y} \cdot f(\mathbf{y})\right] - n\sigma^2. \tag{2}$$

Crucially, SURE provides the ability to estimate the MSE of a denoiser $f(\mathbf{y})$ without access to clean signals $\mathbf{x}$. As a result, many researchers have used SURE for unsupervised learning of denoisers (Zhang & Desai, 1998; Blu & Luisier, 2007; Metzler et al., 2018; Soltanayev & Chun, 2018; Nguyen et al., 2020; Jo et al., 2021), even extending to training diffusion models based on (fully sampled) noisy data (Xiang et al., 2023; Aali et al., 2023).

In the context of inverse problems, SURE has been generalized for corrupted measurements beyond additive white Gaussian noise (Eldar, 2008). The Generalized SURE (GSURE) considers $\mathbf{y} = \boldsymbol{H}\mathbf{x} + \mathbf{z}$ (where $\mathbf{x} \in \mathbb{R}^n$, $\boldsymbol{H} \in \mathbb{R}^{m \times n}$, $\mathbf{y}, \mathbf{z} \in \mathbb{R}^m$, and $\mathbf{z} \sim \mathcal{N}(0, \boldsymbol{C})$), and a function $f(\mathbf{y})$ estimating $\mathbf{x}$. In this case, GSURE provides an unbiased estimate for the projected MSE:

$$\mathbb{E}\left[\|\boldsymbol{P}(f(\mathbf{y}) - \mathbf{x})\|_2^2\right] = \mathbb{E}\left[\|\boldsymbol{P}(f(\mathbf{y}) - \mathbf{x}_{\text{ML}})\|_2^2\right] + 2\mathbb{E}\left[\nabla_{\boldsymbol{H}^\top \boldsymbol{C}^{-1}\mathbf{y}} \cdot \boldsymbol{P}f(\mathbf{y})\right] + c, \tag{3}$$

where $\boldsymbol{H}^{\dagger}$ is the Moore-Penrose pseudo-inverse of $\boldsymbol{H}$, $\boldsymbol{P} = \boldsymbol{H}^{\dagger}\boldsymbol{H}$ is a projection matrix onto the range-space of $\boldsymbol{H}$, $\mathbf{x}_{\mathrm{ML}} = \left(\boldsymbol{H}^{\top}\boldsymbol{C}^{-1}\boldsymbol{H}\right)^{\dagger}\boldsymbol{H}^{\top}\boldsymbol{C}^{-1}\mathbf{y}$, and c is a constant that does not depend on $f(\mathbf{y})$. Several works have utilized GSURE for solving inverse problems by training only on corrupted measurements (Metzler et al., 2018; Zhussip et al., 2019; Liu et al., 2020; Abu-Hussein et al., 2022). However, when $\boldsymbol{H}$ causes significant information loss, the projected MSE stops being a good proxy for the full MSE. Ensemble SURE (ENSURE) (Aggarwal et al., 2022) learns from a dataset of measurements, each corrupted by a different operator $\boldsymbol{H}$. Therefore, the expectation over the projected MSE is taken over $\boldsymbol{H}$ as well as the data and noise. This constitutes a more accurate proxy for the full MSE without relying on clean signals. In this work, we extend the ENSURE framework for training a diffusion model using corrupted data.

3 GSURE-Diffusion: Mathematical Formulation

3.1 Problem Formulation

We are interested in training a generative diffusion model that can sample from an unknown data distribution $q(\mathbf{x})$. However, we only have access to a dataset $\mathcal{D}$ of corrupted measurements

$$\mathbf{y} = \boldsymbol{H}\mathbf{x} + \mathbf{z}, \tag{4}$$

where $\mathbf{y} \in \mathbb{R}^m$, $\mathbf{x} \in \mathbb{R}^n$, $\boldsymbol{H} \in \mathbb{R}^{m \times n}$, and $\mathbf{z} \sim \mathcal{N}(0, \sigma_0^2 \boldsymbol{I})$ is additive white Gaussian noise (AWGN).[1] Equation 4 refers to a single instance of an ideal image and its corresponding measurement, and more generally, different measurements $\mathbf{y}$ in the dataset may relate to different signals $\mathbf{x}$, different degradation procedures $\boldsymbol{H}$, and different noise realizations $\mathbf{z}$. We assume $\mathbf{x}$, $\mathbf{z}$, and $\boldsymbol{H}$ are randomly and independently sampled from their respective distributions.

In order to decouple the mathematical relationship between the observed measurements and the underlying data, we follow (Kawar et al., 2022) and utilize the singular value decomposition (SVD) of $\boldsymbol{H}$,

$$\boldsymbol{H} = \boldsymbol{U}\boldsymbol{\Sigma}\boldsymbol{V}^{\top}, \tag{5}$$

where $\boldsymbol{U} \in \mathbb{R}^{m \times m}$ and $\boldsymbol{V} \in \mathbb{R}^{n \times n}$ are orthogonal matrices, and $\boldsymbol{\Sigma} \in \mathbb{R}^{m \times n}$ is a rectangular diagonal matrix containing the singular values of $\boldsymbol{H}$. We define $\bar{\mathbf{x}} = \boldsymbol{V}^{\top}\mathbf{x}$, $\bar{\mathbf{y}} = \boldsymbol{\Sigma}^{\dagger}\boldsymbol{U}^{\top}\mathbf{y}$, and $\bar{\mathbf{z}} = \boldsymbol{\Sigma}^{\dagger}\boldsymbol{U}^{\top}\mathbf{z}$. Using these definitions and the SVD, Equation 4 becomes

$$\bar{\mathbf{y}} = \boldsymbol{P}\bar{\mathbf{x}} + \bar{\mathbf{z}}, \tag{6}$$

where $\boldsymbol{P} = \boldsymbol{\Sigma}^{\dagger}\boldsymbol{\Sigma}$ is a diagonal subsampling matrix with zeroes and ones, and $\bar{\mathbf{z}} \sim \mathcal{N}(0, \sigma_0^2 \boldsymbol{\Sigma}^{\dagger}\boldsymbol{\Sigma}^{\dagger\top})$ constitutes anisotropic uncorrelated Gaussian noise.

We make the following assumptions on the training dataset $\mathcal{D}$: (i) The sampling matrices $\boldsymbol{H}$ and noise levels σ_0 are known; (ii) All matrices $\boldsymbol{H}$ share the same right-singular vectors $\boldsymbol{V}^{\top}$; and (iii) The different $\boldsymbol{H}$ across the dataset jointly cover the signal space $\mathbb{R}^n$, *i.e.*, $\mathbb{E}[\boldsymbol{P}]$ is a positive definite matrix.[2] These assumptions are satisfied in many real-world applications such as Magnetic Resonance Imaging (MRI) – measurements are acquired in a similar fashion for all data points (upholding (ii)), and the subsampling pattern can be randomly chosen for each point (upholding (iii)). $\boldsymbol{H}$ and σ_0 are derived from the physics of the signal acquisition procedure, thus upholding (i).

Under the transformed measurement equation presented in Equation 6, we aim to train a generative model for $\bar{\mathbf{x}}$, which can easily translate to $\mathbf{x}$ through the orthogonal transformation $\mathbf{x} = \boldsymbol{V}\bar{\mathbf{x}}$.

3.2 GSURE-Based Denoising Diffusion Loss Function

In order to train a diffusion model for $\bar{\mathbf{x}}$, we aim to obtain noisy training samples $\bar{\mathbf{x}}_t$ that satisfy the marginal distribution $q^*(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}) = \mathcal{N}\left(\sqrt{\bar{\alpha}_t}\bar{\mathbf{x}}, (1 - \bar{\alpha}_t)\boldsymbol{I}\right)$, as in traditional diffusion models. However, we only have

---

[1]Our method can also handle anisotropic uncorrelated noise. We only consider AWGN to simplify notations.

[2]Under these notations, $\mathbb{E}[\boldsymbol{P}]$ is measured for a fixed $\boldsymbol{V}^{\top}$, and the values in $\boldsymbol{\Sigma}$ are not necessarily ordered.

access to corrupted measurements $\bar{\mathbf{y}}$ as in Equation 6. For a given t, we perturb these measurements with additional noise according to

$$\bar{\mathbf{x}}_t = \sqrt{\bar{\alpha}_t}\bar{\mathbf{y}} + \left((1 - \bar{\alpha}_t)\,\boldsymbol{I} - \bar{\alpha}_t \sigma_0^2 \boldsymbol{\Sigma}^\dagger \boldsymbol{\Sigma}^{\dagger\top}\right)^{\frac{1}{2}} \boldsymbol{\epsilon}_t, \tag{7}$$

where $\boldsymbol{\epsilon}_t \sim \mathcal{N}(0, \boldsymbol{I})$ is independently sampled. Intuitively, $\sqrt{\bar{\alpha}_t}\bar{\mathbf{y}}$ includes noise with a diagonal covariance $\bar{\alpha}_t \sigma_0^2 \boldsymbol{\Sigma}^\dagger \boldsymbol{\Sigma}^{\dagger\top}$. We increase the noise level in each entry by an appropriate amount to reach a variance of $1 - \bar{\alpha}_t$ in all entries. This way, we obtain samples $\bar{\mathbf{x}}_t$ suitable for training a diffusion model, as they follow the marginal distribution

$$q(\bar{\mathbf{x}}_t | \bar{\mathbf{x}}, \boldsymbol{P}) = \mathcal{N}\left(\sqrt{\bar{\alpha}_t}\boldsymbol{P}\bar{\mathbf{x}}, (1 - \bar{\alpha}_t)\,\boldsymbol{I}\right). \tag{8}$$

This resembles the ideal distribution of training samples $q^*(\bar{\mathbf{x}}_t|\bar{\mathbf{x}})$, differing only in the mean value for entries dropped by $\boldsymbol{P}$. In the following, we derive a loss function that uses $\bar{\mathbf{x}}_t$ satisfying Equation 8, and utilizes an expectation over $\bar{\mathbf{x}}$, $\bar{\mathbf{z}}$, and $\boldsymbol{P}$ yielding samples $\bar{\mathbf{x}}_t \sim \mathbb{E}_{\boldsymbol{P}}[q(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}, \boldsymbol{P})]$. This results in an estimate for denoising ideal samples from $q^*(\bar{\mathbf{x}}_t|\bar{\mathbf{x}})$. The estimate assumes that the model has the ability to generalize for samples from $q^*(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}) = q(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}, \boldsymbol{P} = \boldsymbol{I})$, despite having trained only on signals with an undersampled $\boldsymbol{P}$. We validate our model's ability to denoise samples from $q^*(\bar{\mathbf{x}}_t|\bar{\mathbf{x}})$ in subsection D.3.

Ideally, we would like to train a diffusion model $f_\theta^{(t)}(\bar{\mathbf{x}}_t)$ using the traditional denoising diffusion loss function in Equation 1. However, as we only have access to undersampled measurements, we consider a weighted expected projected MSE objective (similar to ENSURE (Aggarwal et al., 2022)):

$$\sum_{t=1}^{T} \gamma_t \mathbb{E}\left[\left\|\boldsymbol{W}\boldsymbol{P}\left(f_\theta^{(t)}(\bar{\mathbf{x}}_t) - \bar{\mathbf{x}}\right)\right\|_2^2\right], \tag{9}$$

where the expectation is taken over $\bar{\mathbf{x}}_t \sim q(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}, \boldsymbol{P})$, $\bar{\mathbf{x}} \sim q(\bar{\mathbf{x}})$, and $\boldsymbol{P}$ is independently sampled. In practice, this expectation is realized through $\bar{\mathbf{y}}$ sampled from the dataset $\mathcal{D}$ and Equation 7.

Proposition 3.1. *For* $\mathbf{x} \sim q(\mathbf{x})$, $\bar{\mathbf{x}} = \boldsymbol{V}^\top \mathbf{x}$, $\bar{\mathbf{x}}_t$ *sampled from Equation 8, and the diagonal weight matrix* $\boldsymbol{W} = \mathbb{E}[\boldsymbol{P}]^{-\frac{1}{2}} \succ 0$ *(positive definite), if* $\boldsymbol{P}$ *and* $\left(f_\theta^{(t)}(\bar{\mathbf{x}}_t) - \bar{\mathbf{x}}\right)$ *are statistically independent, then Equation 9 equals Equation 1.*

We place the proof in Appendix A. The proof relies on the aforementioned assumptions made in ENSURE (Aggarwal et al., 2022). We assess the validity of this assumption for our trained networks in subsection D.4, and find that the assumption approximately holds for half the range of timesteps used in the denoiser. Nevertheless, even though the assumption is violated for some timesteps, the algorithm's performance remains similar to the oracle model, as shown in Figure **??**. The expected projected MSE term in Equation 9 measures the squared error of the denoiser $f_\theta^{(t)}(\bar{\mathbf{x}}_t)$ only in entries kept by $\boldsymbol{P}$. This fact makes the loss easier to measure, as we do not have access to the entries dropped by $\boldsymbol{P}$. However, we still cannot accurately measure this loss, because we lack access to noiseless signals $\boldsymbol{P}\bar{\mathbf{x}}$. To mitigate this, we utilize GSURE to estimate Equation 9 using only $\bar{\mathbf{x}}_t$ with the loss

$$\sum_{t=1}^{T} \gamma_t \mathbb{E}\left[\left\|\boldsymbol{W}\boldsymbol{P}\left(f_\theta^{(t)}(\bar{\mathbf{x}}_t) - \frac{1}{\sqrt{\bar{\alpha}_t}}\bar{\mathbf{x}}_t\right)\right\|_2^2 + 2\lambda_t\left(\nabla_{\bar{\mathbf{x}}_t} \cdot \boldsymbol{P}\boldsymbol{W}^2 f_\theta^{(t)}(\bar{\mathbf{x}}_t)\right) + c\right], \tag{10}$$

where c is a constant that does not depend on θ, and λ_t is a scalar hyperparameter. The expectation is over the same random variables from Equation 9.

Proposition 3.2. *For* $\mathbf{x} \sim q(\mathbf{x})$, $\bar{\mathbf{x}} = \boldsymbol{V}^\top \mathbf{x}$, $\bar{\mathbf{x}}_t$ *sampled from Equation 8, and* $\lambda_t = 1 - \bar{\alpha}_t$, *it holds that Equation 10 equals Equation 9.*

We place the proof in the Appendix A. Proposition 3.1 and Proposition 3.2 present a principled method to train a denoising diffusion model based only on corrupted data $\bar{\mathbf{y}}$. By minimizing the loss function in Equation 10, we obtain a trained diffusion model that can be utilized in the same fashion as a fully supervised one, for both generation and downstream applications.

When our proposed training scheme is applied in practice, the expectation term in Equation 10 is replaced by an average over training batches, $\frac{1}{\sqrt{\bar{\alpha}_t}}\bar{\mathbf{x}}_t$ is replaced by $\bar{\mathbf{y}}$ to alleviate the high variance of the loss function, and

the divergence term is calculated using an unbiased Monte Carlo estimator (Ramani et al., 2008; Hutchinson, 1989). We defer these pragmatic implementation details to Appendix D.

4 Experiments

In the following, we demonstrate the capabilities of our method for training a diffusion model using corrupted data. To obtain corrupted data, we simulate several corruptions on datasets containing clean images. Then, we train a diffusion model based only on the corrupted data, and compare its results against an *oracle* model (with identical training hyperparameters) which is trained on the pristine data with the traditional diffusion loss function from Equation 1.

4.1 Human Face Images

To empirically evaluate GSURE-Diffusion, we apply it on 32×32-pixel grayscale face images from CelebA (Liu et al., 2015). We simulate a corrupted measurement process by splitting the images into 4×4-pixel non-overlapping patches, and randomly erasing each patch with probability p. We also perturb the data with AWGN with standard deviation σ_0. This degradation matches our assumptions in subsection 3.1 (see Appendix B), and we provide samples of it in Figure 1. We adapt the U-Net (Ronneberger et al., 2015) architecture from DDPM (Ho et al., 2020) to match the image dimensions, and train diffusion models for increasing levels of degradation on the CelebA training set. Training hyperparameters and more details are provided in Appendix C.

After training, we generate images from the models using the deterministic DDIM (Song et al., 2020a) sampling schedule. We measure the generative performance using the Fréchet Inception Distance (FID) (Heusel et al., 2017) between 10000 generated images and the CelebA validation set. As can be seen in Table 1 and Figure 2, our GSURE-Diffusion models achieve generative performance comparable to the oracle model, despite having trained only on corrupted data. As expected, the performance deteriorates when more severe degradations are applied to the training data. We note that in the few timesteps regime, GSURE-Diffusion slightly outperforms the oracle model, possibly due to the regularization effect of training on corrupted measurements. However, once we increase the number of timesteps used for generation, the oracle model benefits from the more fine-grained process, whereas GSURE-Diffusion struggles to do so.

4.2 Magnetic Resonance Imaging (MRI)

Magnetic Resonance Imaging (MRI) is a ubiquitous non-invasive medical imaging modality that can provide life-saving diagnostic information. MRI measurements are obtained in the Fourier spectrum (also called k-space) of an object with magnetic fields. However, measuring the entire k-space can be time-consuming and expensive. Therefore, inferring the scanned object image based on partial, possibly randomized and noisy, k-space measurements from accelerated MRI scans is a highly relevant and challenging inverse problem,

Table 1: FID (Heusel et al., 2017) results for diffusion models trained on increasing levels of degradation for 32×32-pixel CelebA (Liu et al., 2015) images, with different DDIM (Song et al., 2020a) steps at generation time. Models were trained with (top) or without (bottom) GSURE-Diffusion, on degraded data.

Training Scheme	Data Degradation	10 Steps	20 Steps	50 Steps	100 Steps
Regular	No degradation (oracle)	21.99	13.09	08.15	06.84
	$p = 0.2$, $\sigma_0 = 0.01$	86.25	108.56	119.30	123.08
	$p = 0.4$, $\sigma_0 = 0.02$	216.74	229.28	236.61	240.03
	$p = 0.6$, $\sigma_0 = 0.03$	273.62	279.17	280.89	281.60
GSURE-Diffusion	$p = 0.2$, $\sigma_0 = 0.01$	18.77	12.25	08.84	08.82
	$p = 0.4$, $\sigma_0 = 0.02$	19.26	14.98	14.03	15.14
	$p = 0.6$, $\sigma_0 = 0.03$	34.51	27.74	26.42	28.31

Figure 3: Accelerated MRI reconstruction results for $R = 4$ and $\sigma_0 = 0.01$.

drawing considerable research attention (Wang et al., 2016; Hammernik et al., 2018; Lee et al., 2018; Han et al., 2019; Weiss et al., 2021; Wang et al., 2022).

The accelerated MRI procedure satisfies the assumptions we introduced in subsection 3.1 (see Appendix B), with the discrete Fourier transform as $V^\top$, and the random subsampling mask as Σ. We use this fact and train a generative diffusion model for MRI based solely on accelerated scans. We train on $24,853$ scanned slices from the fastMRI (Knoll et al., 2020; Zbontar et al., 2019) single-coil knee MRI dataset, center-cropped to a spatial size of 320×320. The accelerated MRI subsampling process is simulated following (Jalal et al., 2021) with an acceleration factor $R = 4$, randomized subsampling of high frequencies, and AWGN with $\sigma_0 = 0.01$. To facilitate training, real and imaginary elements of complex numbers are treated as separate input/output channels. We use the same U-Net (Ronneberger et al., 2015; Ho et al., 2020) architecture from our CelebA (Liu et al., 2015) experiments, slightly modified to match the data dimensions, and train a diffusion model on the corrupted measurements. A separate oracle model is trained with the same hyperparameters (detailed in Appendix C) on the fully sampled data.

To evaluate the validity of our approach, we measure the mean squared error (MSE) of both models in denoising 1024 fully sampled MR images from the fastMRI (Knoll et al., 2020; Zbontar et al., 2019) validation set for different diffusion timesteps. In Figure 4, we observe that the denoising ability of GSURE-Diffusion resembles that of the oracle model. This supports our claim that GSURE-Diffusion can be a suitable replacement for the oracle model despite having trained exclusively on corrupted data. To test this claim in real-world applications, we substitute the oracle model for its GSURE-Diffusion counterpart in accelerated MRI reconstruction – restoring MR images from noisy subsampled versions. We use the general-purpose

Figure 4: Left: Denoising MSE (on fully sampled noisy images) for the GSURE-Diffusion and oracle models across diffusion timesteps. Right: Qualitative denoising examples for both models.

diffusion-based inverse problem solver DDRM (Kawar et al., 2022) for this task with $\eta = 0$ and 100 steps. In Figure 3, we observe that GSURE-Diffusion achieves similar performance to the oracle for $R = 4$. In all MRI experiments, we also present the "zero-filled" result (showing the MR image with zeroes in the missing frequencies) as a baseline.

Moreover, since we train a foundational MRI generative model, it is not restricted to the degradation setting present in its training data. For instance, the model can generalize well for higher acceleration factors, as we show in Figure 5. GSURE-Diffusion can also be utilized to reconstruct MR images corrupted by subsampling masks of different characteristics, such as 1-dimensional Gaussian random sampling and variable density Poisson disc sampling, as we show in Figure 6. Furthermore, as a generative model, GSURE-Diffusion can provide uncertainty estimates for its outputs. We follow (Chung & Ye, 2022) and quantify the uncertainty using the standard deviation of 8 stochastic outputs made by the model. We add synthetic Gaussian noise to MR images with $\sigma_0 = 0.4$, and show uncertainty quantification results using GSURE-Diffusion and the oracle model in Figure 7. This uncertainty quantification technique can potentially aid medical practitioners, providing clues towards anomalous regions in MRI scans. These results present evidence that a generative model trained on corrupted data can be deployed in various applications. By loosening the requirements on the quality of the training data, we significantly reduce the cost of data acquisition for model training.

5 Limitations

While GSURE-Diffusion achieves impressive results, it suffers from a few limitations. First, the assumptions over the available dataset and its acquisition procedure listed in subsection 3.1, which are satisfied in accelerated MRI, may not always hold in other real-world scenarios. Second, if the measurement noise $\bar{\mathbf{z}}$ has high variance in at least one entry, the minimum noise level in the diffusion process, $\bar{\alpha}_1$, would also need to be high. This may lead to poor performance, as the final step of the generative diffusion process will need to clean significant noise. Third, if the distribution of $\boldsymbol{P}$ in the dataset is heavily biased towards certain regions, or has high variance in terms of $\boldsymbol{P}$'s rank, this can break the diffusion model's ability to infer $\boldsymbol{P}$ from $\bar{\mathbf{x}}_t$, and thus degrade the generative performance.

The latter two limitations can be mitigated in future work by designing a diffusion model architecture that is explicitly aware of the "mask" $\boldsymbol{P}$ for each input, and can handle $\bar{\mathbf{x}}_t$ with a diagonal covariance with different values in the main diagonal. Similar ideas (input masks and diagonal covariance) have been suggested in fully supervised diffusion modeling literature (Bao et al., 2022; Gao et al., 2023), and would be interesting to explore in the corrupted data setting.

Figure 5: Accelerated MRI reconstruction results for $R \in \{6, 8, 10, 12\}$ and $\sigma_0 = 0.01$. GSURE-Diffusion can generalize well across different acceleration factors.

6 Related Work

There has been a rich vein of works on unsupervised learning from datasets of corrupted data (Lehtinen et al., 2018; Batson & Royer, 2019; Hendriksen et al., 2020; Chen et al., 2022), including several SURE- and GSURE-based approaches (Soltanayev & Chun, 2018; Nguyen et al., 2020; Jo et al., 2021; Metzler et al., 2018; Zhussip et al., 2019; Aggarwal et al., 2022; Abu-Hussein et al., 2022; Liu et al., 2020). While they achieve impressive results, these efforts are mostly focused on learning a specific task. In contrast, our approach learns a foundational generative model, making it suitable for a wide range of applications.

Recent advances in diffusion-based generative modeling (Ho et al., 2020; Dhariwal & Nichol, 2021) have enabled subsequent work to adapt these models for medical imaging (*e.g.*, MRI) (Song et al., 2023; Chung & Ye, 2022; Jalal et al., 2021; Xie & Li, 2022; Chung et al., 2023). These diffusion models can serve a multitude of tasks, but can be expensive to train as they require fully sampled noiseless training data. Notably, DDM^2 (Xiang et al., 2023) and the concurrent work of SURE-Score (Aali et al., 2023) offer ways to train a diffusion model based on noisy data, which is often the case in practical settings. However, collected data can also be undersampled or corrupted by other transformations. Our proposed framework is more general, as it can handle both Gaussian noise and linear corruptions.

Diffusion models have permeated various research areas, including online decision making (Hsieh et al., 2023). In that context, obtaining full noiseless data may often be impossible. The authors of (Hsieh et al., 2023) suggest a diffusion loss function that learns a diffusion-based prior from noisy data with missing elements, similar to an image inpainting problem. They note that their proposed loss function could be of independent

Figure 6: MRI reconstruction results for 1-dimensional Gaussian random sampling ($R = 8$) and variable density Poisson disc sampling ($R = 15$), both with $\sigma_0 = 0.01$. Our method generalizes well for different sampling schemes.

Figure 7: Uncertainty quantification for MR image denoising with GSURE-Diffusion and oracle models. Means and standard deviations are calculated for 8 stochastic diffusion reconstructions.

interest in future work. Our loss function closely resembles theirs, albeit generalizing for linear corruptions beyond inpainting by utilizing the singular value decomposition (SVD).

7 Conclusion

We have introduced GSURE-Diffusion, a technique for training generative diffusion models based on data corrupted by linear degradations and additive Gaussian noise. Using the SVD of the degradation operator, GSURE (Eldar, 2008), and an ensemble of degradations (Aggarwal et al., 2022), we introduce a novel training scheme that approximates the underlying data distribution from corrupted measurements. We perform experiments on CelebA (Liu et al., 2015) to demonstrate the validity of our proposed framework. Additionally, we show the applicability of GSURE-Diffusion to real-world problems by training a model on accelerated (undersampled and noisy) MRI scans from fastMRI (Zbontar et al., 2019; Knoll et al., 2020). We then use the resulting diffusion model to address several downstream tasks.

We hope that our proposed framework will enable future work to train generative models on similar problems such as multi-coil accelerated MRI, sparse-view Computed Tomography (CT), and more. Future work may also address additional challenging measurement acquisition scenarios, as dictated by the data modality. We emphasize the fact that our results are obtained on simulated corruptions. More extensive experiments on real data should be conducted before GSURE-Diffusion can be relied upon for diagnostics in clinical settings.

References

Asad Aali, Marius Arvinte, Sidharth Kumar, and Jonathan I Tamir. Solving inverse problems with score-based generative priors learned from noisy data. *arXiv preprint arXiv:2305.01166*, 2023.

Shady Abu-Hussein, Tom Tirer, Se Young Chun, Yonina C Eldar, and Raja Giryes. Image restoration by deep projected GSURE. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 3602–3611, 2022.

Edmond Adib, Amanda Fernandez, Fatemeh Afghah, and John Jeff Prevost. Synthetic ecg signal generation using probabilistic diffusion models. *arXiv preprint arXiv:2303.02475*, 2023.

Hemant Kumar Aggarwal, Aniket Pramanik, Maneesh John, and Mathews Jacob. ENSURE: A general approach for unsupervised training of deep image reconstruction algorithms. *IEEE Transactions on Medical Imaging*, 2022.

Fan Bao, Chongxuan Li, Jiacheng Sun, Jun Zhu, and Bo Zhang. Estimating the optimal covariance with imperfect mean in diffusion probabilistic models. In *International Conference on Machine Learning*, pp. 1555–1584. PMLR, 2022.

Joshua Batson and Loic Royer. Noise2self: Blind denoising by self-supervision. In *International Conference on Machine Learning*, pp. 524–533. PMLR, 2019.

Tsachi Blau, Roy Ganz, Bahjat Kawar, Alex Bronstein, and Michael Elad. Threat model-agnostic adversarial defense using diffusion models. *arXiv preprint arXiv:2207.08089*, 2022.

Thierry Blu and Florian Luisier. The sure-let approach to image denoising. *IEEE Transactions on Image Processing*, 16(11):2778–2786, 2007.

Dongdong Chen, Julián Tachella, and Mike E Davies. Robust equivariant imaging: a fully unsupervised framework for learning to image from noisy and partial measurements. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5647–5656, 2022.

Hyungjin Chung and Jong Chul Ye. Score-based diffusion models for accelerated MRI. *Medical Image Analysis*, 80:102479, 2022.

Hyungjin Chung, Dohoon Ryu, Michael T McCann, Marc L Klasky, and Jong Chul Ye. Solving 3D inverse problems using pre-trained 2D diffusion models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255, 2009.

Prafulla Dhariwal and Alexander Nichol. Diffusion models beat GANs on image synthesis. *Advances in Neural Information Processing Systems*, 34:8780–8794, 2021.

Yonina C Eldar. Generalized SURE for exponential families: Applications to regularization. *IEEE Transactions on Signal Processing*, 57(2):471–481, 2008.

Shanghua Gao, Pan Zhou, Ming-Ming Cheng, and Shuicheng Yan. Masked diffusion transformer is a strong image synthesizer. *arXiv preprint arXiv:2303.14389*, 2023.

Shansan Gong, Mukai Li, Jiangtao Feng, Zhiyong Wu, and Lingpeng Kong. DiffuSeq: Sequence to sequence text generation with diffusion models. In *International Conference on Learning Representations*, 2023.

Kerstin Hammernik, Teresa Klatzer, Erich Kobler, Michael P Recht, Daniel K Sodickson, Thomas Pock, and Florian Knoll. Learning a variational network for reconstruction of accelerated mri data. *Magnetic resonance in medicine*, 79(6):3055–3071, 2018.

Yoseo Han, Leonard Sunwoo, and Jong Chul Ye. {k}-space deep learning for accelerated mri. *IEEE transactions on medical imaging*, 39(2):377–386, 2019.

Allard Adriaan Hendriksen, Daniël Maria Pelt, and K Joost Batenburg. Noise2inverse: Self-supervised deep convolutional denoising for tomography. *IEEE Transactions on Computational Imaging*, 6:1320–1335, 2020.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Jonathan Ho, William Chan, Chitwan Saharia, Jay Whang, Ruiqi Gao, Alexey Gritsenko, Diederik P Kingma, Ben Poole, Mohammad Norouzi, David J Fleet, et al. Imagen video: High definition video generation with diffusion models. *arXiv preprint arXiv:2210.02303*, 2022.

Yu-Guan Hsieh, Shiva Prasad Kasiviswanathan, Branislav Kveton, and Patrick Blöbaum. Thompson sampling with diffusion generative prior. *arXiv preprint arXiv:2301.05182*, 2023.

Michael F Hutchinson. A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines. *Communications in Statistics-Simulation and Computation*, 18(3):1059–1076, 1989.

Ajil Jalal, Marius Arvinte, Giannis Daras, Eric Price, Alexandros G Dimakis, and Jon Tamir. Robust compressed sensing mri with deep generative priors. *Advances in Neural Information Processing Systems*, 34:14938–14954, 2021.

Yeonsik Jo, Se Young Chun, and Jonghyun Choi. Rethinking deep image prior for denoising. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 5087–5096, 2021.

Bahjat Kawar, Michael Elad, Stefano Ermon, and Jiaming Song. Denoising diffusion restoration models. In *Advances in Neural Information Processing Systems*, 2022.

Bahjat Kawar, Shiran Zada, Oran Lang, Omer Tov, Huiwen Chang, Tali Dekel, Inbar Mosseri, and Michal Irani. Imagic: Text-based real image editing with diffusion models. In *Conference on Computer Vision and Pattern Recognition 2023*, 2023.

Dongjun Kim, Yeongmin Kim, Wanmo Kang, and Il-Chul Moon. Refining generative process with discriminator guidance in score-based diffusion models. *arXiv preprint arXiv:2211.17091*, 2022.

Florian Knoll, Jure Zbontar, Anuroop Sriram, Matthew J. Muckley, Mary Bruno, Aaron Defazio, Marc Parente, Krzysztof J. Geras, Joe Katsnelson, Hersh Chandarana, Zizhao Zhang, Michal Drozdzalv, Adriana Romero, Michael Rabbat, Pascal Vincent, James Pinkerton, Duo Wang, Nafissa Yakubova, Erich Owens, C. Lawrence Zitnick, Michael P. Recht, Daniel K. Sodickson, and Yvonne W. Lui. fastMRI: A publicly available raw k-space and DICOM dataset of knee images for accelerated MR image reconstruction using machine learning. *Radiology: Artificial Intelligence*, 2(1):e190007, 2020.

Zhifeng Kong, Wei Ping, Jiaji Huang, Kexin Zhao, and Bryan Catanzaro. Diffwave: A versatile diffusion model for audio synthesis. In *International Conference on Learning Representations*, 2021.

Dongwook Lee, Jaejun Yoo, Sungho Tak, and Jong Chul Ye. Deep residual learning for accelerated mri using magnitude and phase networks. *IEEE Transactions on Biomedical Engineering*, 65(9):1985–1995, 2018.

Jaakko Lehtinen, Jacob Munkberg, Jon Hasselgren, Samuli Laine, Tero Karras, Miika Aittala, and Timo Aila. Noise2noise: Learning image restoration without clean data. In *International Conference on Machine Learning*, pp. 2965–2974. PMLR, 2018.

Huayu Li, Gregory Ditzler, Janet Roveda, and Ao Li. DeScoD-ECG: Deep score-based diffusion model for ecg baseline wander and noise removal. *IEEE Journal of Biomedical and Health Informatics*, 2023.

Xiang Lisa Li, John Thickstun, Ishaan Gulrajani, Percy Liang, and Tatsunori Hashimoto. Diffusion-LM improves controllable text generation. In *Advances in Neural Information Processing Systems*, 2022.

Jiaming Liu, Yu Sun, Cihat Eldeniz, Weijie Gan, Hongyu An, and Ulugbek S Kamilov. RARE: Image reconstruction using deep priors learned without groundtruth. *IEEE Journal of Selected Topics in Signal Processing*, 14(6):1088–1099, 2020.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3730–3738, 2015.

Christopher A Metzler, Ali Mousavi, Reinhard Heckel, and Richard G Baraniuk. Unsupervised learning with stein's unbiased risk estimator. *arXiv preprint arXiv:1805.10531*, 2018.

Sendhil Mullainathan and Ziad Obermeyer. Solving medicine's data bottleneck: Nightingale open science. *Nature Medicine*, 28(5):897–899, May 2022.

Han V Nguyen, Magnus O Ulfarsson, and Johannes R Sveinsson. Hyperspectral image denoising using sure-based unsupervised convolutional neural networks. *IEEE Transactions on Geoscience and Remote Sensing*, 59(4):3369–3382, 2020.

Alexander Quinn Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In *International Conference on Machine Learning*, pp. 8162–8171. PMLR, 2021.

Walter HL Pinaya, Mark S Graham, Robert Gray, Pedro F Da Costa, Petru-Daniel Tudosiu, Paul Wright, Yee H Mah, Andrew D MacKinnon, James T Teo, Rolf Jager, et al. Fast unsupervised brain anomaly detection and segmentation with diffusion models. In *Medical Image Computing and Computer Assisted Intervention–MICCAI 2022: 25th International Conference, Singapore, September 18–22, 2022, Proceedings, Part VIII*, pp. 705–714. Springer, 2022.

Vadim Popov, Ivan Vovk, Vladimir Gogoryan, Tasnima Sadekova, and Mikhail Kudinov. Grad-TTS: A diffusion probabilistic model for text-to-speech. In *International Conference on Machine Learning*, pp. 8599–8608. PMLR, 2021.

Zhuoran Qiao, Weili Nie, Arash Vahdat, Thomas F Miller III, and Anima Anandkumar. Dynamic-backbone protein-ligand structure prediction with multiscale generative diffusion models. *arXiv preprint arXiv:2209.15171*, 2022.

Sathish Ramani, Thierry Blu, and Michael Unser. Monte-carlo sure: A black-box optimization of regularization parameters for general denoising algorithms. *IEEE Transactions on image processing*, 17(9):1540–1554, 2008.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-Net: Convolutional networks for biomedical image segmentation. In *Medical Image Computing and Computer-Assisted Intervention–MICCAI 2015: 18th International Conference, Munich, Germany, October 5-9, 2015, Proceedings, Part III 18*, pp. 234–241. Springer, 2015.

Arne Schneuing, Yuanqi Du, Charles Harris, Arian Jamasb, Ilia Igashov, Weitao Du, Tom Blundell, Pietro Lió, Carla Gomes, Max Welling, Michael Bronstein, and Bruno Correia. Structure-based drug design with equivariant diffusion models. *arXiv preprint arXiv:2210.13695*, 2022.

Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade W Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, et al. Laion-5b: An open large-scale dataset for training next generation image-text models. In *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2022.

Uriel Singer, Adam Polyak, Thomas Hayes, Xi Yin, Jie An, Songyang Zhang, Qiyuan Hu, Harry Yang, Oron Ashual, Oran Gafni, Devi Parikh, Sonal Gupta, and Yaniv Taigman. Make-A-Video: Text-to-video generation without text-video data. In *International Conference on Learning Representations*, 2023.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pp. 2256–2265. PMLR, 2015.

Shakarim Soltanayev and Se Young Chun. Training deep learning based denoisers without ground truth data. *Advances in neural information processing systems*, 31, 2018.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2020a.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in Neural Information Processing Systems*, 32, 2019.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2020b.

Yang Song, Liyue Shen, Lei Xing, and Stefano Ermon. Solving inverse problems in medical imaging with score-based generative models. In *International Conference on Learning Representations*, 2023.

Charles M Stein. Estimation of the mean of a multivariate normal distribution. *The annals of Statistics*, pp. 1135–1151, 1981.

Guy Tevet, Sigal Raab, Brian Gordon, Yonatan Shafir, Amit H Bermano, and Daniel Cohen-Or. Human motion diffusion model. *arXiv preprint arXiv:2209.14916*, 2022.

Lucas Theis, Tim Salimans, Matthew D Hoffman, and Fabian Mentzer. Lossy compression with Gaussian diffusion. *arXiv preprint arXiv:2206.08889*, 2022.

Arash Vahdat, Karsten Kreis, and Jan Kautz. Score-based generative modeling in latent space. *Advances in Neural Information Processing Systems*, 34:11287–11302, 2021.

Shanshan Wang, Zhenghang Su, Leslie Ying, Xi Peng, Shun Zhu, Feng Liang, Dagan Feng, and Dong Liang. Accelerating magnetic resonance imaging via deep learning. In *IEEE 13th International Symposium on Biomedical Imaging (ISBI)*, pp. 514–517. IEEE, 2016.

Zi Wang, Chen Qian, Di Guo, Hongwei Sun, Rushuai Li, Bo Zhao, and Xiaobo Qu. One-dimensional deep low-rank and sparse network for accelerated mri. *IEEE Transactions on Medical Imaging*, 42(1):79–90, 2022.

Joseph L Watson, David Juergens, Nathaniel R Bennett, Brian L Trippe, Jason Yim, Helen E Eisenach, Woody Ahern, Andrew J Borst, Robert J Ragotte, Lukas F Milles, et al. Broadly applicable and accurate protein design by integrating structure prediction networks and diffusion generative models. *bioRxiv*, pp. 2022–12, 2022.

Tomer Weiss, Ortal Senouf, Sanketh Vedula, Oleg Michailovich, Michael Zibulevsky, Alex Bronstein, et al. Pilot: Physics-informed learned optimized trajectories for accelerated mri. *Machine Learning for Biomedical Imaging*, 1(April 2021 issue):1–23, 2021.

Julian Wyatt, Adam Leach, Sebastian M Schmon, and Chris G Willcocks. AnoDDPM: Anomaly detection with denoising diffusion probabilistic models using simplex noise. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 650–656, 2022.

Tiange Xiang, Mahmut Yurt, Ali B Syed, Kawin Setsompop, and Akshay Chaudhari. DDM^2: Self-supervised diffusion MRI denoising with generative diffusion models. In *The Eleventh International Conference on Learning Representations*, 2023.

Yutong Xie and Quanzheng Li. Measurement-conditioned denoising diffusion probabilistic model for under-sampled medical image reconstruction. In *Medical Image Computing and Computer Assisted Intervention–MICCAI 2022: 25th International Conference, Singapore, September 18–22, 2022, Proceedings, Part VI*, pp. 655–664. Springer, 2022.

Jason Yim, Brian L Trippe, Valentin De Bortoli, Emile Mathieu, Arnaud Doucet, Regina Barzilay, and Tommi Jaakkola. Se(3) diffusion model with application to protein backbone generation. *arXiv preprint arXiv:2302.02277*, 2023.

Jure Zbontar, Florian Knoll, Anuroop Sriram, Tullie Murrell, Zhengnan Huang, Matthew J. Muckley, Aaron Defazio, Ruben Stern, Patricia Johnson, Mary Bruno, Marc Parente, Krzysztof J. Geras, Joe Katsnelson, Hersh Chandarana, Zizhao Zhang, Michal Drozdzal, Adriana Romero, Michael Rabbat, Pascal Vincent, Nafissa Yakubova, James Pinkerton, Duo Wang, Erich Owens, C. Lawrence Zitnick, Michael P. Recht, Daniel K. Sodickson, and Yvonne W. Lui. fastMRI: An open dataset and benchmarks for accelerated MRI, 2019.

Xiao-Ping Zhang and Mita D Desai. Adaptive denoising based on sure risk. *IEEE signal processing letters*, 5 (10):265–267, 1998.

Magauiya Zhussip, Shakarim Soltanayev, and Se Young Chun. Training deep learning based image denoisers from undersampled measurements without ground truth and without image prior. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10255–10264, 2019.

Roland S Zimmermann, Lukas Schott, Yang Song, Benjamin A Dunn, and David A Klindt. Score-based generative classifiers. *arXiv preprint arXiv:2110.00473*, 2021.