COUNTERFACTUAL GENERATIVE NETWORKS

ABSTRACT

Neural networks are prone to learning shortcuts – they often model simple correlations, ignoring more complex ones that potentially generalize better. Prior works on image classification show that instead of learning a connection to object shape, deep classifiers tend to exploit spurious correlations with low-level texture or the background for solving the classification task. In this work, we take a step towards more robust and interpretable classifiers that explicitly expose the task's causal structure. Building on current advances in deep generative modeling, we propose to decompose the image generation process into independent causal mechanisms that we train without direct supervision. By exploiting appropriate inductive biases, these mechanisms disentangle object shape, object texture, and background; hence, they allow for generating *counterfactual images*. We demonstrate the ability of our model to generate such images on MNIST and ImageNet. Further, we show that the counterfactual images can improve out-of-distribution robustness with a marginal drop in performance on the original classification task, despite being synthetic. Lastly, our generative model can be trained efficiently on a single GPU, exploiting common pre-trained models as inductive biases.

1 INTRODUCTION

Deep neural networks (DNNs) are the main building blocks of many state-of-the-art machine learning systems that address diverse tasks such as image classification (He et al., 2016), natural language processing (Brown et al., 2020), and autonomous driving (Ohn-Bar et al., 2020). Despite the considerable successes of DNNs, they still struggle in many situations, e.g., classifying images perturbed by an adversary (Szegedy et al., 2013), or failing to recognize known objects in unfamiliar contexts (Rosenfeld et al., 2018) or from unseen poses (Alcorn et al., 2019).

Many of these failures can be attributed to dataset biases (Torralba & Efros, 2011) or shortcut learning (Geirhos et al., 2020). The DNN learns the simplest correlations and tends to ignore more complex ones. This characteristic becomes problematic when the simple correlation is spurious, i.e., not present during inference. The motivational example of (Beery et al., 2018) considers the setting of a DNN that is trained to recognize cows in images. A real-world dataset will typically depict cows on green pastures in most images. The most straightforward correlation a classifier can learn to predict the label "cow" is hence the connection to a green, grass-textured background. Generally, this is not a problem during inference as long as the test data follows the same distribution. However, if we provide the classifier an image depicting a purple cow on the moon, the classifier should still confidently assign the label "cow." Thus, if we want to achieve robust generalization beyond the training data, we need to disentangle possibly spurious correlations from causal relationships.

Distinguishing between spurious and causal correlations is one of the core questions in causality research (Pearl, 2009; Peters et al., 2017; Schölkopf, 2019). One central concept in causality is the assumption of *independent mechanism* (IM), which states that a causal generative process is composed of autonomous modules that do not influence each other. In the context of image classification (e.g., on ImageNet), we can interpret the generation of an image as a causal process. We decompose this process into separate IMs, each controlling one factor of variation (FoV) of the image. Concretely, we consider three IMs: one generates the object's shape, the second generates the object's texture, and the third generates the background. With access to these IMs, we can produce *counterfactual images*, i.e., images of unseen combinations of FoVs. We can then train an ensemble of invariant classifiers on the generated counterfactual images, such that every classifier relies on only a single one of those factors. The main idea is illustrated in Figure 1. By exploiting concepts from

Real Image		Generated Counterfactual Image	

Classifier:
An ostrich.

Invariant Classifier Ensemble:
An ostrich shape
with ostrich texture
on an ostrich background.

Classifier:
A strawberry.

Invariant Classifier Ensemble:
An ostrich shape
with strawberry texture
on a diving background.

Figure 1: **Out-of-Domain (OOD) Classification.** A classifier focuses on all factors of variation (FoV) in an image. For OOD data, this can be problematic: a FoV might be a spurious correlation, hence, impairing the classifier's performance. An ensemble, e.g., a classifier with a common backbone and multiple heads, each head invariant to all but one FoV, increases OOD robustness.

causality, this paper links two previously distinct domains: disentangled generative models and robust classification. This allows us to scale our experiments beyond small toy datasets typically used in either domain. The main contributions of our work are as follows: (i) We present an approach for generating high-quality counterfactual images with direct control over shape, texture, and background. Supervision is only provided by the class label and certain inductive biases we impose on the learning problem. (ii) We demonstrate the usefulness of the generated counterfactual images for the downstream task of image classification on both MNIST and ImageNet. Our model improves the classifier's out-of-domain robustness while only marginally degrading its overall accuracy. (iii) We show that our generative model demonstrates interesting emerging properties, such as generating high-quality binary object masks and unsupervised image inpainting. We will open-source our trained models, data, and code upon publication.

2   STRUCTURAL CAUSAL MODELS FOR IMAGE GENERATION

In this section, we first introduce our ideas on a conceptual level. Concretely, we form a connection between the areas of causality, disentangled representation learning, and invariant classifiers, and highlight that domain randomization (Tobin et al., 2017) is a particular instance of these ideas. In section 3, we will then formulate a concrete model that implements these ideas for image classification. Our goals are two-fold: (i) We aim at generating counterfactual images with previously unseen combinations like a cat with elephant texture or the proverbial "bull in a china shop." (ii) We utilize these images to train a classifier invariant to chosen factors of variation.

In the following, we first formalize the problem setting we address. Second, we describe how we can address this setting by structuring a generator network as a structural causal model (SCM). Third, we show how to use the SCM for training robust classifiers.

2.1   PROBLEM SETTING

Consider a dataset comprised of (high-dimensional) observations $\mathbf{x}$ (e.g. images), and corresponding labels y (e.g. classes). A common assumption is that each $\mathbf{x}$ can be described by lower-dimensional, semantically meaningful factors of variation $\mathbf{z}$ (e.g., color or shape of objects in the image). If we can *disentangle* these factors, we are able to control their influence on the classifier's decision. In the disentanglement literature, the factors are often assumed to be statistically independent, i.e., $\mathbf{z}$ is distributed according to $p(\mathbf{z}) = \Pi_{i=1}^{n}(z_i)$ (Locatello et al., 2018). However, assuming independence is problematic because certain factors might be correlated in the training data, or the combination of some factors may not exist. Consider the colored MNIST dataset (Kim et al., 2019), where both the digit's color and its shape correspond to the label. The simplest decision rule a classifier can learn is to count the number of pixels of a specific color value; no notion of the digit's shape is required. This kind of correlation is not limited to constructed datasets – classifiers trained on ImageNet (Deng et al., 2009) strongly rely on texture for classification, significantly more than on the object's shape (Geirhos et al., 2018). While texture or color is a powerful classification cue, we do not want the classifier to ignore shape information completely. Therefore, we advocate a generative viewpoint. However, simply training a disentangled β-VAE (Higgins et al., 2017) on this dataset does not allow for generating data points of unseen combinations – the VAE is not able to generate green zeros if all zeros in the training data are red (see Appendix A for a visualization). We therefore propose a

novel generative model which enables full control over several FoVs relevant for classification. We then train a classifier on these images while randomizing all factors but one. The classifier focuses on the non-randomized factor and becomes invariant wrt. the randomized ones.

2.2 Structural Causal Models

In representation learning, it is commonly assumed that a potentially complex function f generates images from a small set of high-level semantic variables (e.g., position or color of objects) (Bengio et al., 2013). Most previous work (Goyal et al., 2019; Suter et al., 2019) imposes no restrictions on f, i.e., a neural network is trained to map directly from a low-dimensional latent space to images. We follow the argument that rather than training a monolithic network to map from a latent space to images, the mapping should be decomposed into several functions. Each of these functions is autonomous, e.g., we can modify the background of an image while keeping all other aspects of the image unchanged. These demands coincide with the concept of structural causal models (SCMs) and independent mechanisms (IMs). An SCM $\mathfrak{C}$ is defined as a collection of d (structural) assignments

$$S_j := f_j\left(\mathbf{PA}_j, U_j\right), \quad j = 1, \ldots, d \tag{1}$$

where each random variable S_j is a function of its parents $\mathbf{PA}_j \subseteq \{S_1, \ldots, S_d\} \setminus \{S_j\}$ and a noise variable U_j. The noise variables $U_1, \ldots, U_d$ are jointly independent. The functions f_i are independent mechanisms, intervening on one mechanism f_j does not change the other mechanisms $\{f_1, \ldots, f_d\} \setminus \{f_j\}$. The SCM $\mathfrak{C}$ defines a unique distribution over the variables $\mathbf{S} = (S_1, \ldots, S_d)$ which is referred to as the *entailed distribution* $P_{\mathbf{S}}^{\mathfrak{C}}$. If one or more structural assignments are replaced, i.e., $S_k := \tilde{f}(\tilde{\mathbf{PA}}_k, \tilde{U}_k)$, this is called an intervention. We consider the case of *atomic interventions*, when $\tilde{f}(\tilde{\mathbf{PA}}_k, \tilde{U}_k)$ puts a point mass on a real value a. The entailed distribution then changes to the intervention distribution $P_{\mathbf{S}}^{\mathfrak{C};do(S_k:=a)}$, where the do refers to the intervention. A thorough review of these concepts can be found in (Peters et al., 2017). Our goal is to represent the image generation process with an SCM. If we learn a sensible set of IMs, we can intervene on a subset of them and generate *counterfactual images* $\mathbf{x}_{CF}$. These images were not part of the training data $\mathbf{x}$ as they are generated from the intervention distribution $P_{\mathbf{S}}^{\mathfrak{C};do(S_k:=a)}$. In our case, a corresponds to a class label that we provide as input, denoted as y_{CF} in the following.

2.3 Training an Invariant Classifier

To train an invariant classifier, we generate counterfactual images $\mathbf{x}_{CF}$, by intervening on all f_j simultaneously. Towards this goal, we draw labels uniformly from the set of possible labels $\mathcal{Y}$ for each f_j, i.e., each IM is conditioned on a different label. We denote the domain of images generated by all possible label permutations as $\mathcal{X}_{CF}$. The task of the invariant classifier $r : \mathcal{X}_{CF} \rightarrow \mathcal{Y}_{CF,k}$ is then to predict the label $\mathbf{y}_{CF,k}$ that was provided to one specific IM f_k – rendering r invariant wrt. all other IMs. This type of invariance is reminiscent of the idea of domain randomization (Tobin et al., 2017). Here, the goal is to solve a robotics task while randomizing all task-irrelevant attributes. The randomization improves the performance of the learned policy in the real-world. In domain randomization, we commonly assume access to the true generative model (the simulator). This assumption is not feasible if we do not have access to this model. Similar connections of causality and data augmentation have been made in (Ilse et al., 2020). From a causal perspective, we maximize the average causal effect (ACE) of one IM on the classifier's decision, while minimizing the ACE of all other IMs.

3 Counterfactual Generative Networks

In this section, we apply our ideas outlined above to the particular problem of image classification. Our goal is to decompose the image generation process into several IMs. In image classification, there is generally one principal object in the image. Hence, we assume three IMs for this specific task: object shape, object texture, and background. Our goal is to train the generator consisting of these mechanisms in an end-to-end manner. The inherent structure of the model allows us to generate meaningful counterfactuals by construction. In the following, we describe the inductive biases we use (network architectures, losses, pre-trained models) and how to train the invariant classifier. We refer to the entire generative model using IMs as a Counterfactual Generative Network (CGN).

Figure 2: **Counterfactual Generative Network (CGN).** Here, we illustrate the architecture used for the ImageNet experiments. The CGN is split into four mechanisms, the shape mechanism f_{shape}, the texture mechanism f_{text}, the background mechanism f_{bg}, and the composer C. Components with trainable parameters are blue, components with fixed parameters are green. The primary supervision is provided by an unconstrained conditional GAN (cGAN) via the reconstruction loss $\mathcal{L}_{rec}$. The cGAN is only used for training, as indicated by the dotted lines. Each mechanism takes as input the noise vector $\mathbf{u}$ (sampled from a spherical Gaussian) and the label y (drawn uniformly from the set of possible labels $\mathcal{Y}$). and minimizes its respective loss ($\mathcal{L}_{shape}$, $\mathcal{L}_{text}$, and $\mathcal{L}_{bg}$). To generate counterfactual images, we randomize $\mathbf{u}$ and y for each mechanism.

3.1 Independent Mechanisms

The type and number of IMs differ depending on the task. For example, for experiments on colored MNIST, we assume two learned IMs – one representing the color distribution and the other the shape distribution. For ImageNet, we consider three learned IMs for generating shape, texture, and background, respectively. In both cases, the learned IMs feed into another, fixed, IM: the composer. An overview of our CGN is shown in Figure 2. All IM-specific losses are optimized jointly end-to-end. For the experiments on ImageNet, we initialize each IM backbone with weights from a pre-trained BigGAN-deep-256 (Brock et al., 2018), the current state-of-the-art for conditional image generation. BigGAN has been trained as a single monolithic function; hence, it cannot generate images of only texture or only background, since these would be outside of the training domain.

Composition Mechanism. The function of the composer is not learned but defined analytically. For this work, we build on common assumptions from compositional image synthesis (Yang et al., 2017) and deploy a simple image formation model. Given the generated masks, textures and backgrounds, we composite the image $\mathbf{x}_{gen}$ using alpha blending, denoted as C:

$$\mathbf{x}_{gen} = C(\mathbf{m}, \mathbf{f}, \mathbf{b}) = \mathbf{m} \odot \mathbf{f} + (1 - \mathbf{m}) \odot \mathbf{b} \qquad (2)$$

where $\mathbf{m}$ is the mask (or alpha map), $\mathbf{f}$ is the foreground, and $\mathbf{b}$ is the background. The operator $\odot$ denotes elementwise multiplication. While, in general, IMs may be stochastic (Eq. 1), we did not find this to be necessary for the composer; therefore, we leave this mechanism deterministic. This fixed composition is an inductive bias in itself – the generator needs to generate realistic images through this bottleneck. To optimize the composite image, we could use an adversarial loss between real and composite images. While applicable to simple datasets such as MNIST, we found that an adversarial approach does not scale well to more complex datasets like ImageNet. To get a stronger and more stable supervisory signal, we, therefore, use an unconstrained, conditional GAN (cGAN) to generate pseudo-ground-truth images $\mathbf{x}_{gt}$ from noise $\mathbf{u}$ and label y. We feed the same $\mathbf{u}$ and y into the IMs to generate $\mathbf{x}_{gen}$ and minimize a reconstruction loss $\mathcal{L}_{rec}(\mathbf{x}_{gt}, \mathbf{x}_{gen})$. We find a combination of L1 loss and perceptual loss (Johnson et al., 2016) to work well. Note that during training, we utilize the same noise $\mathbf{u}$ and label y to reconstruct the image generated by the cGAN. However, at inference time, we generate counterfactual images by randomizing both $\mathbf{u}$ and y separately per mechanism.

Shape Mechanism. We model the shape using a binary mask predicted by shape IM f_{shape}, where 0 corresponds to the background and 1 to the object. Effectively, this mechanism implements fore-

ground segmentation. The loss is comprised of two terms: $\mathcal{L}_{binary}$ and $\mathcal{L}_{mask}$. $\mathcal{L}_{binary}$ is the pixel-wise binary entropy of the mask; hence, minimizing it forces the output to be close to either 0 or 1. $\mathcal{L}_{mask}$ prohibits trivial solutions, i.e., masks with all 0's or 1's that are outside of a defined interval (see Appendix B for details). As we utilize a BigGAN backbone for our ImageNet-Experiments, we need to extract a binary mask from the backbone's output. Therefore, we add a pre-trained U2-Net (Qin et al., 2020) as a head on top of the BigGAN backbone. The U2-Net was trained for salient object detection on DUTS-TR (10553 images) (Wang et al., 2017). Hence, it is class agnostic; it generates an object mask for a salient object in the image. While the U2-Net presents a strong bias towards binary object masks, it does not fully solve the task at hand as it captures non-class specific parts (e.g., parts of trees in an elephant-class picture, see Figure 5). By fine-tuning the BigGAN backbone, we learn to generate images of the relevant part with exaggerated features to increase saliency. We refer to these as pre-masks $\tilde{\mathbf{m}}$.

Texture Mechanism. The texture mechanism f_{text} is responsible for generating the foreground object's appearance, while not capturing any object shape or background cues. For MNIST, we use an architectural bias – an additional layer before the final output. This layer spatially divides its input into patches and randomly rearranges them, similar to a shuffled sliding puzzle. This conceptually simple idea does not work on ImageNet, as we want to preserve local object structure, e.g., the position of an eye. We, therefore, sample patches from the full composite image and concatenate them into a grid. The patches are sampled from regions where the mask values are highest (hence, the object is likely located). We then minimize a perceptual loss $\mathcal{L}_{text}$ between the output of f_{text} and the patch grid. Over training, the background gradually transforms into object texture, resulting in texture maps, as shown in Figure 5. More details can be found in Appendix B.

Background Mechanism. The background mechanism f_{bg} needs to capture the background's global structure while the object must be removed and inpainted realistically. However, we found that we cannot use standard inpainting techniques because classical methods (Barnes et al., 2009) slow down training too much, and deep learning methods (Liu et al., 2018) do not work well on synthetic data because of the domain shift. Instead, we exploit the same U2-Net as used for the shape mechanism f_{shape}. Again, we feed the output of the BigGAN backbone through the U2-Net with fixed weights. However, this time, we *minimize* the predicted saliency. Over the progress of training, this leads to the object shrinking and finally disappearing, while the model learns to inpaint the object region (see Figure 5 and Appendix D). We refer to this loss as $\mathcal{L}_{bg}$. We attribute this loss's success mainly the powerful generation abilities of the pre-trained backbone network. Big-GAN is already able to generate objects on realistic backgrounds; it only needs to unlearn the object generation.

3.2 GENERATING COUNTERFACTUALS TO TRAIN CLASSIFIERS

After training our CGN, each IM network has learned a class-conditional distribution over shapes, textures, or backgrounds. By randomizing the label input y and noise u of each network, we can generate counterfactual images. The number of possible combinations is the number of classes to the power of the number of IM's. For ImageNet, this is 1000^3. The amount of possible images is even larger since we learn distributions, i.e., we can generate a nearly unlimited variety of shapes, textures, and backgrounds, per class. For MNIST, we directly train on the synthetic data. For ImageNet, Ravuri & Vinyals (2019) demonstrate that training on synthetic data alone leads to substantially inferior performance. We, therefore, follow an augmentation strategy, i.e., we augment ImageNet with additional counterfactual images.

4 EXPERIMENTS

Our experiments aim to answer the following questions: (i) Does our approach reliably disentangle IMs on datasets of different complexity? (ii) Which inductive biases are necessary to achieve this? (iii) Do counterfactual images enable training invariant classifiers? We first apply our approach to different versions of MNIST: colored-, double-colored- and Wildlife-MNIST (details about their generation are in Appendix A.2). The label is encoded in the digit shape, foreground color or texture, and the background color or texture, see Figure 3. We then scale our approach to ImageNet and demonstrate that we can improve the robustness of ImageNet classifiers. Implementation details about architectures, loss parameters, and hyperparameters can be found in Appendix B.

Figure 3: **MNISTs.** Left: Samples of the different MNIST variations (for brevity, we show only the first four classes). Right: Counterfactual samples generated by our CGN. Note that the CGN learned class-conditional *distributions*, i.e., it generates varying shapes, colors, and textures.

Shape	red wine	cottontail rabbit	pirate ship	triumphal arch	mushroom	hyena dog
Texture	carbonara	head cabbage	banana	Indian elephant	barrel	school bus
Background	baseball	valley	bittern (bird)	viaduct	grey whale	snorkel

Figure 4: **ImageNet Counterfactuals.** The CGN successfully disentangles shape, texture, and background, and enables the generation of numerous permutations thereof.

4.1   DOES OUR APPROACH DISENTANGLE THE INDEPENDENT MECHANISMS?

Standard metrics like the Inception Score (IS) (Salimans et al., 2016) are not applicable since the counterfactual images are outside of the natural image domain. We thus focus on qualitative results in this section. For a quantitative analysis, we refer the reader to Section 4.3 where we analyze the accuracy, robustness, and invariance of classifiers trained on the generated counterfactual data.

MNISTs. The generated counterfactual images are shown in Figure 3 (right). None of the counterfactual combinations were present in the training data. We can see that CGN successfully generates high-quality counterfactuals. The results on Wildlife MNIST are surprisingly good, considering that the object texture is only observable on the relatively thin digits. Nevertheless, the texture IM learns to generate realistic textures. All experiments on MNIST are done without pre-training any network.

ImageNet. As shown in Figure 4, our CGN generates counterfactuals of high visual fidelity. The intermediate and direct outputs of each IM of different class types are shown in Appendix C. We train a single CGN for all 1000 classes. We also find an unexpected benefit of our approach. In some instances, the composite images eliminate structural artifacts of the original BigGAN images, such as surplus legs, as shown in Figure 5. We hypothesize that f_{shape} learns a general shape concept per class, resulting in outliers, like elephants with eight legs, being smoothed out. The CGN can fail to produce high-quality texture maps for very small objects, e.g., for a bird high up in the sky, the texture map will still show large portions of the sky. Also, in some instances, a residue of the object is left on the background, e.g., a dog snout. For generating counterfactual images, this is not a problem as a different object will cover the residue. We show examples in Appendix E.

4.2   WHICH INDUCTIVE BIASES ARE NEEDED TO ACHIEVE DISENTANGLEMENT?

We employ two kinds of biases: pre-training of modules and IM-specific losses. We find that pre-training is not necessary for our experiments on MNIST. However, when scaling to ImageNet, powerful pre-trained models are key for achieving good results. Furthermore, this allows to train the whole CGN on a single NVIDIA GTX 1080Ti within 12 hours, in contrast to BigGAN, which was trained on a Google TPU v3 Pod with 512 cores for up to 48 hours. To investigate each loss' influence, we disable one loss at a time and measure its influence on the quality of the composite images. The composite images are on the image manifold, hence, we can calculate their Inception score (IS). As we train with pseudo ground truth, the performance of the unconstrained BigGAN is a natural upper bound. The used model reaches an IS of 202.9. To measure if the CGN collapsed during training, we monitor the mean value of the generated mask μ_{mask}. A μ_{mask} close to 1 means that

Figure 5: **Individual IM Outputs over Training.** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$. The initial output of the pre-trained models is gradually transformed.

f_{text} is not training. Instead, it generates the output of the pre-trained BigGAN, hence, a mask of 1's trivially minimizes the reconstruction loss $\mathcal{L}_{rec}(\mathbf{x}_{gt}, \mathbf{x}_{gen})$. The same is true for μ_{mask} close to 0 and f_{bg}. The results in Table 1 indicate that each loss is necessary, and jointly optimizing all of them end-to-end is needed for a high IS without a collapse of μ_{mask}. Removing $\mathcal{L}_{shape}$, leads to bad quality masks (non-binary, only partially capturing the object). This results in a low IS since object texture and background get mixed in the composited image. Not using either $\mathcal{L}_{text}$ or $\mathcal{L}_{bg}$ results in a high IS (as the output is close to the original BigGAN output), but a collapse of μ_{mask}. The mechanisms do not disentangle their respective signal. Finally, disabling $\mathcal{L}_{rec}$ leads to a very low IS, since the IMs can optimize their respective loss without any constraint on the composite image. We show the evolution and collapse of the masks over training in Appendix F.

4.3 DO COUNTERFACTUAL IMAGES ENABLE TRAINING OF INVARIANT CLASSIFIERS?

The following experiments investigate if we can instill invariance into a classifier. We perform experiments on the MNIST variants, a cue-conflict dataset, and an OOD version of ImageNet.

MNIST Classification. In the training domain, shapes, colors, and textures are correlated with the class label. In the test domain, only the shapes correspond to the correct class. We compare to current approaches for training invariant classifiers: IRM (Arjovsky et al., 2019) and Learning-not-to-learn (LNTL) (Kim et al., 2019). For a detailed description we refer to Appendix B. *CGN data* is trained on counterfactual data to predict the input labels of the shape IM. *GAN data* is a baseline that is trained on non-counterfactual samples. IRM considers a signal to be causal if it is stable across several environments; hence, we train IRM on several datasets with varying correlation. LNTL considers color to be spurious, whereas we assume (complementary) that shapes are causal. The results in Table 2 confirm that training on counterfactual data leads to classifiers that are invariant to the spurious signals. LNTL and IRM were both proposed for colored MNIST. (IRM for a simpler, binary variant). Our results indicate that both have trouble scaling to more complex data. We, therefore, do not consider them in our following experiments.

Texture vs. Shape Bias. The Cue Conflict dataset consists of images generated using iterative style transfer (Gatys et al., 2015) between a texture and a content image. A high shape bias corresponds to classification according to the content label and vice versa for texture. Their approach is trained on stylized ImageNet (SIN), either as a drop-in for ImageNet (IN) or as augmentation. We use a classifier ensemble, i.e., a classifier with a common backbone and multiple heads, each head invariant to all but one FoV. We average the predicted log-probabilies of each head for the final output of the ensemble. We conduct all experiments using a Resnet-50 architecture. As shown in Table 3, we can influence the individual bias of each classifier head without significant degradation in the ensemble's performance.

Invariance over Backgrounds. Xiao et al. (2020) propose the *BG-Gap* to measure a classifier's dependence on the background signal. Based on ImageNet-9 (IN-9), a subset of ImageNet with 9 coarse-grained classes, they build synthetic datasets. For *Mixed-Rand*, the backgrounds are randomized, while the object remains unchanged, hence background an class are decorrelated. For *Mixed-Same* they sample class-consistent backgrounds. The BG-Gap is the difference in performance between the two. Training on IN or SIN does not make it possible to disentangle and omit the background signal, as shown in Table 4. Directly training on Mixed-Rand leads to a drop in performance on the original data which might be due to the smaller training dataset. We can generate unlimited data of this type, hence, we are able to reduce the gap while achieving high accuracy on IN-9. However, a gap to a fully invariant classifier remains. We partially attribute this to the general remaining domain gap between generated and real images.

$\mathcal{L}_{shape}$	$\mathcal{L}_{text}$	$\mathcal{L}_{bg}$	$\mathcal{L}_{rec}$	IS ⇑	μ_{mask}
✗	✓	✓	✓	85.9	$0.2 \pm 0.2\%$
✓	✗	✓	✓	198.4	$0.9 \pm 0.1\%$
✓	✓	✗	✓	195.6	$0.1 \pm 0.1\%$
✓	✓	✓	✗	38.39	$0.3 \pm 0.2\%$
✓	✓	✓	✓	130.2	$0.3 \pm 0.2\%$
BigGAN (Upper Bound)				202.9	-

Table 1: **Loss Ablation Study.** We turn off one loss at a time. Values indicating mask collapse are red.

	colored MNIST		double-colored MNIST		Wildlife MNIST	
	Train Acc ⇑	Test Acc ⇑	Train Acc ⇑	Test Acc ⇑	Train Acc ⇑	Test Acc ⇑
Original	99.5 %	35.9 %	**100.0** %	10.3 %	**100.0** %	10.1 %
IRM	99.6 %	59.8 %	**100.0** %	67.7 %	99.9 %	11.3 %
LNTL	99.3 %	81.8 %	98.7 %	69.9 %	99.9 %	11.5 %
GAN data	**99.8** %	40.7 %	**100.0** %	10.8 %	**100.0** %	10.4 %
CGN data	99.7 %	**86.4** %	97.4 %	**85.3** %	99.2 %	**80.5** %

Table 2: **MNISTs Classification.** In the test set, colors and textures are randomized, only the digit's shape corresponds to the class label. Random performance is at 10%.

Trained on	Shape Bias	top-1 IN Acc ⇑	top-5 IN Acc ⇑
IN	21.39 %	76.13 %	92.86 %
SIN	81.37 %	60.18 %	82.62 %
IN + SIN	34.65 %	74.59 %	90.03 %
IN + CGN/Shape	54.82 %		
IN + CGN/Text	16.67 %	73.98 %	91.71 %
IN + CGN/Bg	22.89 %		

Table 3: **Shape vs. Texture.** We can control the classifier's shape or texture preference.

	Top-1 Test Accuracies			
Trained on	IN-9 ⇑	Mixed-Same ⇑	Mixed-Rand ⇑	BG-Gap ⇓
IN	95.6%	86.2%	78.9%	7.3%
SIN	89.2 %	73.1 %	63.7 %	9.4 %
IN + SIN	94.7 %	85.9 %	78.5 %	7.4 %
Mixed-Rand	73.3%	71.5%	71.3%	0.2%
IN + CGN	93.5 %	82.2 %	78.9 %	3.2 %

Table 4: **Accuracies on IN-9.** The reported accuracies are all obtained using a Resnet-50.

5 RELATED WORK

Our work is related to disentangled representation learning and the training of invariant classifiers.

Disentangled Representation Learning. A recent line of work in image synthesis aims to learn disentangled features for controlling the image generation process (Chen et al., 2016; Higgins et al., 2017; Liao et al., 2020). The challenge of the task is that the underlying factors can be highly correlated. Closely related to our work is (Li et al., 2020), which aims to disentangle background, shape, pose, and texture, using object bounding boxes for supervision. Their methods assumes images of a single object category (e.g. birds). We scale our approach to all classes of ImageNet which enables us to generate inter-class counterfactuals. A recent research direction explores the discovery of interpretable directions in GANs trained on ImageNet (Plumerault et al., 2020; Voynov & Babenko, 2020; Peebles et al., 2020). These approaches do not allow for generating counterfactual images. Besserve et al. (2019) also leverage the idea of independent mechanisms to discover modularity in pre-trained generative models. Their approach does not allow for direct control of image attributes. Lastly, methods for causal generative modeling utilizing competing experts (von Kügelgen et al., 2020) have been demonstrated on toy datasets only. Further, none of the works above aim to use the generated images to improve upon a downstream task such as image classification.

Invariant Classification. Current approaches do not take an underlying causal model into account. Instead, they rely on different assumptions. Arjovsky et al. (2019) assume that the training data is collected into separate environments (e.g. different measurement circumstances). Correlations that are stable across environments are considered to be causal. Kim et al. (2019) aim to learn features that are uninformative of a given bias (spurious) signal. As mentioned above, attaining labels for shape or texture is expensive and not straight-forward. A recent strand of work is concerned with data augmentation for improving invariance against spurious correlations. Shetty et al. (2020) propose to train object detectors on generated semantic adversarial data, effectively reducing the texture dependency of their model. Their finding is in line with (Geirhos et al., 2018) that proposes to transfer the style of paintings onto images and use them for data augmentation. These approaches, however, do not allow to choose the specific signal we want invariance for, e.g., the background.

6 CONCLUSION

In this work, we apply ideas from causality to generative modeling and the training of invariant classifiers. We structure a generative network into independent mechanisms to generate counterfactual images useful for training classifiers. With the use of several inductive biases, we demonstrate our approach on various MNIST variants as well as ImageNet. Our ideas are orthogonal to advances in generative modeling - with advances therein, our obtained results will further improve.

REFERENCES

Michael A Alcorn, Qi Li, Zhitao Gong, Chengfei Wang, Long Mai, Wei-Shinn Ku, and Anh Nguyen. Strike (with) a pose: Neural networks are easily fooled by strange poses of familiar objects. In *CVPR*, 2019.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Connelly Barnes, Eli Shechtman, Adam Finkelstein, and Dan B Goldman. Patchmatch: A randomized correspondence algorithm for structural image editing. In *ACM TOG*, 2009.

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *ECCV*, 2018.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *TPAMI*, 2013.

Michel Besserve, Arash Mehrjou, Rémy Sun, and Bernhard Schölkopf. Counterfactuals uncover the modular structure of deep generative models. In *ICLR*, 2019.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis. In *ICLR*, 2018.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *NeurIPS*, 2016.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *CVPR*, 2014.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *CVPR*, 2009.

Leon A Gatys, Alexander S Ecker, and Matthias Bethge. A neural algorithm of artistic style. *arXiv preprint arXiv:1508.06576*, 2015.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. In *ICLR*, 2018.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A Wichmann. Shortcut learning in deep neural networks. *arXiv preprint arXiv:2004.07780*, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *NeurIPS*, 2014.

Yash Goyal, Amir Feder, Uri Shalit, and Been Kim. Explaining classifiers with causal concept effect (CACE). *arXiv preprint arXiv:1907.07165*, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

Maximilian Ilse, Jakub M Tomczak, and Patrick Forré. Designing data augmentation for simulating interventions. *arXiv preprint arXiv:2005.01856*, 2020.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *ECCV*, 2016.

Byungju Kim, Hyunwoo Kim, Kyungsu Kim, Sungjin Kim, and Junmo Kim. Learning not to learn: Training deep neural networks with biased data. In *CVPR*, 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Yuheng Li, Krishna Kumar Singh, Utkarsh Ojha, and Yong Jae Lee. Mixnmatch: Multifactor disentanglement and encoding for conditional image generation. In *CVPR*, 2020.

Yiyi Liao, Katja Schwarz, Lars Mescheder, and Andreas Geiger. Towards unsupervised learning of generative models for 3d controllable image synthesis. In *CVPR*, 2020.

Guilin Liu, Fitsum A Reda, Kevin J Shih, Ting-Chun Wang, Andrew Tao, and Bryan Catanzaro. Image inpainting for irregular holes using partial convolutions. In *ECCV*, 2018.

Francesco Locatello, Stefan Bauer, Mario Lucic, Sylvain Gelly, Bernhard Schölkopf, and Olivier Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *ICML*, 2018.

Eshed Ohn-Bar, Aditya Prakash, Aseem Behl, Kashyap Chitta, and Andreas Geiger. Learning situational driving. In *CVPR*, 2020.

Judea Pearl. *Causality*. Cambridge University Press, 2009.

William Peebles, John Peebles, Jun-Yan Zhu, Alexei A. Efros, and Antonio Torralba. The hessian penalty: A weak prior for unsupervised disentanglement. In *ECCV*, 2020.

Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference*. The MIT Press, 2017.

Antoine Plumerault, Hervé Le Borgne, and Céline Hudelot. Controlling generative models with continuous factors of variations. In *ICLR*, 2020.

Xuebin Qin, Zichen Zhang, Chenyang Huang, Masood Dehghan, Osmar R Zaiane, and Martin Jagersand. U2-net: Going deeper with nested u-structure for salient object detection. *Pattern Recognition*, 2020.

Suman Ravuri and Oriol Vinyals. Seeing is not necessarily believing: Limitations of biggans for data augmentation. In *ICLR Workshop LLD*, 2019.

Amir Rosenfeld, Richard Zemel, and John K Tsotsos. The elephant in the room. *arXiv preprint arXiv:1808.03305*, 2018.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *NeurIPS*, 2016.

Bernhard Schölkopf. Causality for machine learning. *arXiv preprint arXiv:1911.10500*, 2019.

Rakshith Shetty, Mario Fritz, and Bernt Schiele. Towards automated testing and robustification by semantic adversarial data generation. In *ECCV*, 2020.

Raphael Suter, Djordje Miladinovic, Bernhard Schölkopf, and Stefan Bauer. Robustly disentangled causal mechanisms: Validating deep representations for interventional robustness. In *ICML*, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *IROS*, 2017.

Antonio Torralba and Alexei A Efros. Unbiased look at dataset bias. In *CVPR*, 2011.

Julius von Kügelgen, Ivan Ustyuzhaninov, Peter Gehler, Matthias Bethge, and Bernhard Schölkopf. Towards causal generative scene models via competition of experts. In *ICLR Workshop CLDM*, 2020.

Andrey Voynov and Artem Babenko. Unsupervised discovery of interpretable directions in the gan latent space. *arXiv preprint arXiv:2002.03754*, 2020.

Lijun Wang, Huchuan Lu, Yifan Wang, Mengyang Feng, Dong Wang, Baocai Yin, and Xiang Ruan. Learning to detect salient objects with image-level supervision. In *CVPR*, 2017.

Kai Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. *arXiv preprint arXiv:2006.09994*, 2020.

Jianwei Yang, Anitha Kannan, Dhruv Batra, and Devi Parikh. Lr-gan: Layered recursive generative adversarial networks for image generation. *arXiv preprint arXiv:1703.01560*, 2017.

APPENDIX A   MNIST VARIANTS

A.1   VARIATIONAL AUTOENCODERS ON COLORED MNIST

Figure 6 shows the latent space of a β-VAE (Higgins et al., 2017) trained on colored MNIST. The VAE disentangles the data into different clusters present in the data. However, the axes do not correspond to color and shape, i.e., color *and* shape vary when traversing one latent. We used only two latent dimensions for visualization purposes; the problem is not resolved by adding more dimensions. The same behaviour can be observed for unconstrained GANs (Goodfellow et al., 2014), as a GAN also approximates the training distribution.

Figure 6: **Colored MNIST.** (left) Examples of data points. (right) Training a disentangled VAE with two latent dimensions on colored MNIST.

A.2   MNISTS GENERATION

Colored MNIST. This dataset was proposed by Kim et al. (2019). They select ten distinct colors and and assign each of them to a class. For each training image, they sample a color from a normal distribution with the class color as the mean. In test setting, the colors are randomly assigned. The variance σ of the normal distribution can be used to control the amount of bias. We evaluate on the hardest, i.e., most biased, setting with $\sigma = 0.02$.

Double-Colored MNIST. We follow the same procedure as for colored MNIST. We additionally encode the class label in the background color.

Wildlife MNIST. To build a version of MNIST closer to an ImageNet setting, we add a texture bias to the data. We follow the same procedure as for double-colored MNIST. We take textures from (Cimpoi et al., 2014) and use ten images of the texture class "striped" to encode the label in the foreground. Similarly, we encode the label in the background with textures of the texture class "veiny." We do not add noise to texture to add stochasticity. Instead, we sample a patch from a texture image, which is larger than the 32x32 resolution used for the MNIST experiments. The textures are multi-modal; hence, these patches can look quite different.

APPENDIX B   IMPLEMENTATION DETAILS

B.1   SHAPE LOSS DETAILS

The full shape loss is as follows:

$$
\begin{aligned}
\mathcal{L}_{shape}(f_s) &= \mathcal{L}_{binary}(f_s) + \mathcal{L}_{mask}(f_s) \\
&= \mathbb{E}_{p(\mathbf{u},y)}\left[\sum_{i=1}^{N} -m_i \log_2(m_i) - (1-m_i) * \log_2(1-m_i)\right] \\
&+ \mathbb{E}_{p(\mathbf{u},y)}\left[\max\left(0, \tau - \frac{1}{N}\sum_{i=1}^{N} m_i\right) + \max\left(0, \frac{1}{N}\sum_{i=1}^{N} m_i - \tau\right)\right]
\end{aligned}
\tag{3}
$$

where $\mathcal{L}_{binary}$ is the pixel-wise binary entropy, $\mathcal{L}_{mask}$ is the mask loss, $\mathbf{m} = f_{shape}(\mathbf{z}, y)$ is the mask generated by f_{shape} and τ is a scalar threshold. $\mathcal{L}_{binary}$ enforces the output to be close to either 0 or 1. $\mathcal{L}_{mask}$ prohibits trivial solutions, i.e., masks with all 0's or 1's, that are outside the interval defined by τ. We set $\tau = 0.1$ in all experiments.

B.2   TEXTURE LOSS DETAILS

The sampling procedure for $\mathcal{L}_{text}$ is as follows: we sample 36 patches of size 15×15 from the regions where the mask is closest to 1. Out of these 36 patches, we build a 6×6 patch grid. Finally, we upscale the grid to the full 256×256 resolution, we denote this grid as $\mathbf{pg}$. We then minimze a perceptual loss between the foreground $\mathbf{f}$ (the output of f_{text}) and the patchgrid: $\mathcal{L}_{perc}(\mathbf{f}, \mathbf{pg})$.

B.3   HYPERPARAMETER SETTING FOR CGN TRAINING ON IMAGENET.

For training the CGN, we jointly optimize the following loss:

$$
\begin{aligned}
\mathcal{L} &= \mathcal{L}_{rec} + \mathcal{L}_{shape} + \lambda_5 \mathcal{L}_{text} + \lambda_6 \mathcal{L}_{bg} \\
&= \lambda_1 \mathcal{L}_{L1} + \lambda_2 \mathcal{L}_{perc} + \lambda_3 \mathcal{L}_{binary} + \lambda_4 \mathcal{L}_{mask} + \lambda_5 \mathcal{L}_{text} + \lambda_6 \mathcal{L}_{bg}
\end{aligned}
\tag{4}
$$

We use the following lambdas: $\lambda_1 = 100, \lambda_2 = 5, \lambda_3 = 300, \lambda_4 = 500, \lambda_5 = 5, \lambda_6 = 2000$. For the optimization we use Adam (Kingma & Ba, 2014), and set the learning rate of f_{shape} to 8e-6, and for both f_{text} and f_{bg} to 1e-5. We do not use real data for training the CGN so we do not need to any data loading. We sample a single image from BigGAN and the CGN, and accumulate the loss gradients for 4000 steps before we take a gradient step. Accumulating large pseudo-batches proved to be crucial for high-quality gradients. This fits the observation of (Brock et al., 2018). Further, using a batch size of one makes it possible to train on a single GPU. For the perceptual losses, i.e., $\mathcal{L}_{perc}$ and $\mathcal{L}_{text}$, we use pretrained VGG16 with batch normalization layers. We calculate the style reconstruction loss (Johnson et al., 2016) of the features after the first four max-pooling layers.

B.4   CGN VARIANTS

MNIST. For colored MNIST we assume two mechanisms: f_{shape} and f_{text}. As color is a special case of a texture, we can use the texture mechanism as described. On both double-colored MNIST and Wildlife MNIST, we assume three mechanisms: f_{shape} and two f_{shape}. The background mechanism f_{bg} is only necessary for our experiments on ImageNet. For real images, the background still to be globally coherent. This global coherence is not necessary for the MNIST variants. Hence, we use two texture mechanisms, one responsible for the foreground texture and the background texture.

ImageNet. We use the pre-trained BigGAN models from `https://github.com/huggingface/pytorch-pretrained-BigGAN`. We experiment with different values for the truncation value of the truncated normal distribution used to sample the input noise. However, we find it does not impact the performance of the CGN. Also, a low value leads to worse performance of the trained classifiers; hence, we leave the truncation value at 1.

B.5 Classifier Training

MNIST. We use the same CNN architecture for all experiments and approaches. For IRM, we produce versions of double-colored MNIST and Wildlife MNIST with a 90% correlation between the label and the foreground colors/textures and background colors/textures. We then train IRM on both environments. We schedule the gradient norm penalty weight, starting from 0, then linearly increasing it over the training episodes. We find the scheduling to be crucial for IRM to converge and achieve good performance.

ImageNet. We use a ResNet-50 from PyTorch. We share the weight up to the last layer as a common backbone and add three fully-connected heads (shape, texture, background). Each of the heads is provided its respective label when training on the counterfactual images. On the real images, we average the logits of all heads. This approach allows the single classifiers to focus on its assigned FoV while the ensemble performs well overall. Similarly to the experiments by (Geirhos et al., 2018), we begin the training with pre-trained weights from ImageNet. We train for 70 episodes with Stochastic Gradient Descent using a batch size of 512. Of the 512 images, 256 are real images, 256 are counterfactual images. We find that an even ratio between real and counterfactual images leads to the best results in terms of optimization stability and performance. We use a momentum of 0.9, weight decay (1e-4), and a learning rate of 0.1, multiplied by a factor of 0.001 after 30 and 60 epochs.

APPENDIX C MORE SAMPLES AND INTERPOLATIONS

C.1 INDIVIDUAL IM OUTPUTS FOR DIFFERENT CLASS TYPES

Figure 7: **(Intermediate) Outputs for the class 'bullfrog'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

Figure 8: **(Intermediate) Outputs for the class 'barn'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

Figure 9: **(Intermediate) Outputs for the class 'speedboat'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

Figure 10: **(Intermediate) Outputs for the class 'wool'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

Figure 11: **(Intermediate) Outputs for the class 'bellpepper'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

Figure 12: **(Intermediate) Outputs for the class 'geyser'.** From top to bottom: pre-masks, masks, texture maps, background. We set the truncation parameter for the noise to 0.5.

C.2 LATENT INTERPOLATIONS

Figure 13: **Interpolating Shapes.** We interpolate between u and y pairs.

Figure 14: **Interpolating Textures.** We interpolate between u and y pairs.

Figure 15: **Interpolating Backgrounds.** We interpolate between u and y pairs.

C.3 MORE COUNTERFACTUAL SAMPLES

Figure 16: **MNIST Counterfactuals.** From Left to Right: colored, double-colored-, and Wildlife MNIST.

Row	Column	Shape	Texture	Background	Row	Column	Shape	Texture	Background
1	1	school bus	panda	geyser	3	4	offshore rig	ambulance	breakwater
1	2	hyena dog	chello	strawberry	3	5	mushroom	sand viper	ostrich
1	3	robin	lipstick	diving	4	1	snowmobile	French Loaf	Arabian camel
1	4	Indian cobra	analog clock	green lizard	4	2	katamaran	cheetah	garden spider
1	5	race car	piggy bank	fig	4	3	bald eagle	strawberry	spike
2	1	hyena dog	breastplate	cock	4	4	triumphal arc	standard poodle	bullfrog
2	2	German shepherd	king penguin	bittern	4	5	forklift	theater curtain	valley
2	3	beaker	busby	pineapple	5	1	whine bottle	pill bottle	alp
2	4	Indian Cobra	orange	spider web	5	2	pirate ship	trench coat	beaver
2	5	teddy	beer glass	rock crab	5	3	submarine	race car	hay
3	1	malinois	reel	viaduct	5	4	wood rabbit	jack-o'-lantern	water ouzel
3	2	ibex	upright piano	sand bank	5	5	teapot	military uniform	baseball
3	3	hourglass	lemon	hornbill					

Figure 17: **ImageNet Counterfactuals.** Top: Counterfactual Labels. Bottom: ImageNet labels.

APPENDIX D   IM OUTPUTS OVER THE COURSE OF TRAINING

Figure 18: **IM Outputs over Training for the class 'dalmatian'** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$.

Figure 19: **IM Outputs over Training for the class 'cauliflower'** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$.

Figure 20: **IM Outputs over Training for the class 'castle'** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$.

Figure 21: **IM Outputs over Training for the class 'ringtailed lemur'** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$.

Figure 22: **IM Outputs over Training for the class 'mushroom'** We show pre-masks $\tilde{\mathbf{m}}$, masks $\mathbf{m}$, foregrounds $\mathbf{f}$, and backgrounds $\mathbf{b}$.

APPENDIX E   FAILURE CASES OF CGN

Figure 23: **Failure Cases.** Left: The shown texture map of the class 'vulture' is not fully textured; parts of the sky are still visible. Right: In the middle of the image, the dog's snout is still (faintly) visible.

APPENDIX F   COLLAPSING MASKS

Figure 24: **Masks when disabling different losses.** From left to right: the beginning of training, training without $\mathcal{L}_{shape}$, training without $\mathcal{L}_{text}$, training without $\mathcal{L}_{bg}$, training with all losses. The third and fourth rows show the collapse of the masks, as described in section 4.2.