CDQuant: Accurate Post-training Weight Quantization of LLMs using Greedy Coordinate Descent

Abstract

Large language models (LLMs) have recently demonstrated remarkable performance across diverse language tasks. But their deployment is often constrained by their substantial computational and storage requirements. Quantization has emerged as a key technique for addressing this challenge, enabling the compression of large models with minimal impact on performance. The recent GPTQ algorithm, a post-training quantization (PTQ) method, has proven highly effective for compressing LLMs, sparking a wave of research that leverages GPTQ as a core component. Recognizing the pivotal role of GPTQ in the PTQ landscape, we introduce CDQuant, a simple and scalable alternative to GPTQ with improved performance. CDQuant uses greedy coordinate descent to minimize the layer-wise reconstruction loss to achieve high-quality quantized weights. Our algorithm is easy to implement and scales efficiently to models with hundreds of billions of parameters. We perform extensive evaluation on Gemma, and PaLM2 model families, and demonstrate that CDQuant consistently outperforms GPTQ in 2-4 bit weight quantization. Moreover, CDQuant improves the performance of state-of-the-art PTQ techniques such as QuIP and FrameQuant when used as a replacement for their GPTQ component, resulting in further gains in quality.

1 Introduction

Large language models (LLMs) have shown remarkable ability to handle various language tasks (Touvron et al., 2023; OpenAI, 2023; Google, 2023), but their widespread adoption is hampered by their substantial computational and memory demands. To tackle this challenge, researchers have explored techniques like quantization, pruning, and distillation, with quantization being a particularly promising avenue for reducing model size and inference time without significantly sacrificing performance (Miao et al., 2023). Quantization techniques broadly fall into two categories: post-training quantization (PTQ) and quantization-aware training (QAT). QAT, while potentially yielding better results, poses a significant challenge for LLMs due to the immense resources required to train these large models. As a result, a growing body of research has focused on PTQ, which is generally less computationally intensive and can be applied to large, pre-trained models.

A seminal work in PTQ for LLMs is GPTQ (Frantar et al., 2022), which introduced a one-shot weight quantization approach that minimizes the following layer-wise output reconstruction loss: $\|X(W - \hat{W})\|_F^2$, where $X = [\mathbf{x}_1, \mathbf{x}_2 \ldots \mathbf{x}_n]$ represents the layer inputs and $W, \widehat{W} \in \mathbb{R}^{d_{in} \times d_{out}}$ are the original and quantized weight matrices, respectively. This method has sparked a wave of research in PTQ. Subsequent works have built upon GPTQ, addressing its limitations and improving it's performance. For instance, SpQR (Dettmers et al., 2023) and OWQ (Lee et al., 2023) improve GPTQ by explicitly addressing outlier weights, maintaining them in full precision, while quantizing the remaining weights using GPTQ. This hybrid approach improves quantization accuracy, particularly at lower bit-widths. Another line of research focuses on transforming the weight space before applying GPTQ. For instance, QuIP (Chee et al., 2024), FrameQuant (Adepu et al., 2024) transform the weights into a more quantization-friendly space and apply GPTQ in the transformed space. AWQ (Lin et al., 2023), SmoothQuant (Xiao et al., 2023) reduce the effect of activation outliers by performing feature scaling before quantizing the weights using standard techniques.

Given the central role GPTQ plays in the landscape of PTQ methods for LLMs, improving its quality directly translates to better quantization across numerous techniques that build upon it. Consequently, in this work, we revisit the core optimization problem addressed by GPTQ and introduce a novel coordinate descent based algorithm, CDQuant, to minimize the objective. CDQuant is an iterative optimization technique that greedily selects coordinates to descend along in each iteration. This approach contrasts with GPTQ, which cycles through the coordinates only *once*, in a predetermined order, often leading to suboptimal solutions for the layer-wise objective (see Section 2 for more details). CDQuant is simple to implement and scales effectively to models with billions of parameters. We further extend CDQuant to group/sub-channel quantization, a technique gaining popularity of late (Dettmers et al., 2021; Dettmers & Zettlemoyer, 2023).

Extensive experiments on Gemma (Mesnard et al., 2024; Gemma-Team, 2024), and PaLM2 (Anil et al., 2023) model families demonstrate that CDQuant consistently outperforms GPTQ across various model sizes and quantization precision levels (2-4 bits). Notably, for INT2 quantization of PaLM2-Otter, CDQuant achieves a 10% perplexity reduction compared to GPTQ. Furthermore, integrating CDQuant with QuIP (Chee et al., 2024) and FrameQuant (Adepu et al., 2024) improves their performance by $\sim 5\%$ for INT2 quantization of the Gemma-2 27B model, showcasing its potential as a drop-in replacement for GPTQ in existing PTQ techniques.

2 RELATED WORK

The literature on quantization is huge. In this section, we only review the works that are related to quantization of large pre-trained models, and those that are related to our work.

GPTQ. Inspired by the Optimal Brain Surgeon (OBS) framework for pruning (LeCun et al., 1989), Optimal Brain Quantization (OBQ) (Frantar & Alistarh, 2022) emerged as a promising post-training quantization (PTQ) technique. However, OBQ remains computationally expensive and struggles to scale effectively to large language models (LLMs). This is because of a complicated step involved in OBQ which requires updating all the unquantized coordinates in each step (see Equation 2 in Frantar et al. (2022)). Implementing this step in GPUs is extremely slow because of the sheer number of gathers/scatters that need to be performed at each step. Frantar et al. (2022) subsequently introduced GPTQ, which employs heuristics to accelerate the OBQ algorithm. Specifically, GPTQ updates coordinates once in a cyclic manner rather than the greedy approach used in OBQ. This modification significantly speeds up the algorithm but comes at the cost of reduced quality. In our work, we address this performance drop by proposing greedy coordinate descent algorithms that are both straightforward and easy to implement.

Other Weight-only Quantization Techniques. Recent works on post-training quantization have sought to improve upon GPTQ. One popular strategy here is to identify and isolate problematic weights before applying GPTQ. For example, SpQR (Dettmers et al., 2023) isolates outlier weights and keeps them at full precision, quantizing only the remaining values using GPTQ. Similarly, OWQ (Lee et al., 2023) identifies weights that are highly sensitive to small perturbations and excludes them from the GPTQ quantization process. JSQ (Guo et al., 2024) clips activations (where the clipping thresholds are searched through simulated annealing), following which a combination of activation range and weight saliency are used to sparsify the weight matrix before quantizing it with GPTQ. SqueezeLLM (Kim et al., 2024) also preserves outliers in floating point, however, employs non-uniform quantization by performing K-means clustering on the final end-to-end loss (where the gradient is approximated with zero,and the Hessain with the Fisher information matrix). Any-Precision LLM (Park et al., 2024) improves SqueezeLLM by allowing several nested precisions through a control over the number of cluster centers. However, both these approaches involve storing a codebook, hence making hardware and software compatibility tricky.

Another promising direction involves transforming the weights into a different basis before quantization. QuIP (Chee et al., 2024), and FrameQuant (Adepu et al., 2024), SpinQuant (Liu et al., 2024), QuaRot (Ashkboos et al., 2024) take this route and perform quantization in the transformed space using GPTQ. In all these approaches, we could potentially substitute GPTQ with CDQuant and expect to see further improvements in performance (see Section 4 for empirical evidence). Other promising methods such as AWQ (Lin et al., 2023), AffineQuant (Ma et al., 2024), suppress the effect of outliers in input activations by adjusting their scale and transferring it to weights. They then perform the standard MinMax quantization on the rescaled weights. One could replace MinMax with

GPTQ, CDQuant to improve the performance of these techniques (see Table 4 for a comparison of CDQuant with AWQ).

While working on our paper, we came across QuantEase (Behdin et al., 2023), a parallel research effort sharing similar goals as ours for improving GPTQ. While both methods leverage the concept of coordinate descent, QuantEase adopts a cyclic approach for weight updates, whereas our work employs a greedy strategy. Although our experiments (Appendix D) indicate comparable performance between the two methods, our work extends beyond QuantEase by introducing specialized algorithms for group/sub-channel quantization, not just full-channel quantization. Additionally, we develop novel block coordinate descent algorithms that further improve the performance. That being said, both these works (QuantEase and ours) collectively highlight the potential of coordinate descent algorithms in outperforming GPTQ.

Vector Quantization. AQLM (Egiazarian et al., 2024) generalizes Additive Quantization to LLMs by introducing input-adaptiveness (through calibration data) and jointly optimizing the codebooks across transformer blocks. QuIP# (Tseng et al., 2024) improves QuIP's incoherence processing through random Hadamard matrices, introduces vector quantization, and adds an additional layer of finetuning to improve model quality. However, in this work, our focus is methods that improve scalar quantization.

Weight+Activation Quantization. SmoothQuant (Xiao et al., 2023), OS+(Wei et al., 2023; 2022) have a similar flavour as AWQ, but quantize both weights and activations after scaling them appropriately. OmniQuant (Shao et al., 2023) performs quantization of the entire transformer block in a single shot. This encompasses both activation and weight quantization. Furthermore, it subsumes SmoothQuant, OS+ by using both feature scaling and outlier suppression. QLLM (Liu et al., 2023) tackles the issue of outliers in the activations by splitting the outlier features into multiple sub-channels and then recombining them, effectively reducing their influence. QLLM also incorporates a fine-tuning step at the end, introducing low-rank weights into each layer of the LLM. LLM.int8() (Dettmers et al., 2022) quantizes both acativations and weights to 8-bits and also identifies outliers and stores them in full precision. LQER (Zhang et al., 2024) approximates the weight quantization error with the product of two low rank matrices.

Efficient End-to-End Quantization. To recover the drop in performance from quantization Chai et al. (2023); Dettmers et al. (2024); Hu et al. (2021) perform low-rank parameter-efficient fine-tuning.

3 CDQUANT

Notation. Throughout the paper, we denote vectors by bold faced letters ($\mathbf{a}$), and matrices by capital letters (A). $\|\mathbf{a}\|_2 = \sqrt{\sum_i \mathbf{a}_i^2}$ is the Euclidean norm and $\|A\|_F = \sqrt{\sum_{i,j} A_{ij}^2}$ is the Frobenius norm of a matrix. $\text{diag}(\mathbf{a})$ represents a diagonal matrix with $\mathbf{a}$ as its diagonal entries. $d_{\text{in}}, d_{\text{out}}$ denote the input, output dimensions of a layer. $W \in \mathbb{R}^{d_{\text{in}} \times d_{\text{out}}}$ is the weight matrix of the layer, and $X = [\mathbf{x}_1, \mathbf{x}_2 \ldots \mathbf{x}_n] \in \mathbb{R}^{n \times d_{\text{in}}}$ is the matrix containing n datapoints that are sent as input to the layer. $H = X^T X$ is the Hessian matrix for our objective in Equation (1). c denotes the number of bits of precision used in quantization. In quantization, we aim to represent W as $Q \times \text{diag}(\mathbf{a}) + \mathbf{1}\mathbf{b}^T$, where $\mathbf{a}, \mathbf{b} \in \mathbb{R}^{d_{\text{out}}}$ represent the scale and bias parameters and $Q \in \{0, 1, \ldots 2^c - 1\}^{d_{\text{in}} \times d_{\text{out}}}$ is the quantized matrix.

Many existing PTQ techniques, including GPTQ, aim to solve the following layer-wise optimization objective: $\min_{\mathbf{a},\mathbf{b},Q} \|X(W - Q \times \text{diag}(\mathbf{a}) - \mathbf{1}\mathbf{b}^T)\|_F^2$. Observe that this problem breaks down into d_{out} independent problems across the output dimension. So, in the sequel, we focus on the following problem of quantizing a d_{in}-dimensional vector

$$\min_{a,b,\mathbf{q}} \|X(\mathbf{w} - a\mathbf{q} - b)\|_2^2. \tag{1}$$

For a fixed (a, b), this problem is called *Integer Linear Regression* problem. It turns out, finding optimal solutions to this problem is NP-hard (Chrétien & Corset, 2009; Park & Boyd, 2018). So, several works have designed heuristics to solve this problem (Nagel et al., 2020; Li et al., 2021; Frantar & Alistarh, 2022; Frantar et al., 2022; Hubara et al., 2021). Within the context of LLMs, GPTQ is perhaps the most popular among these techniques, as it scales efficiently to models with billions of parameters (Frantar et al., 2022). In this work, we aim to improve upon GPTQ by designing better

---

Algorithm 1 Greedy Coordinate Descent (CD)

1: **Input:** T - coordinate descent steps, X - input data matrix, $\mathbf{w}$ - vector to be quantized, a - scale, b - bias, $\mathbf{q}_0$ - initial estimate
2: Compute Hessian H as: $H \leftarrow X^T X$
3: Compute gradient $\mathbf{g}$ at $\mathbf{q}_0$ as: $\mathbf{g} \leftarrow 2H(\mathbf{q}_0 - a^{-1}(\mathbf{w} - b))$
4: **for** $t \in [1 : T]$ **do**
5:    Find the coordinate that leads to the largest reduction in loss

$$i^*, r^* = \underset{i \in \{0,1,\dots d_{\text{in}}-1\}, r \in \{0,1,\dots 2^c-1\}}{\arg\min} (r - q_{t-1,i})^2 H_{i,i} + (r - q_{t-1,i})\mathbf{g}_i$$

6:    Update gradient $\mathbf{g}$ as

$$\mathbf{g} \leftarrow \mathbf{g} + 2(r^* - q_{t-1,i^*})H_{i^*,\cdot},$$

   where $H_{i^*,\cdot}$ is the i^* column of H
7:    Update $\mathbf{q}_{t-1}$ as

$$\mathbf{q}_t \leftarrow \mathbf{q}_{t-1} + (r^* - q_{t-1,i^*})\mathbf{e}_{i^*},$$

   where $\mathbf{e}_{i^*}$ is the standard basis vector with 1 in i^* position and 0 everywhere else
8: **end for**

---

heuristics, while maintaining its scalability aspect. To this end, we rely on performing coordinate descent on objective (1), which we describe below.

3.1 GREEDY COORDINATE DESCENT

In this section, we assume we have suitable values for scale (a) and bias (b) parameters already at hand, and focus on optimizing $\mathbf{q}$. For a more in-depth discussion of how we determine these values, please refer to the final part of the section. As the name suggests, in greedy coordinate descent, at each round, we find the coordinate that leads to the biggest reduction in the objective and descend along that coordinate. Letting $\mathcal{L}(\mathbf{q}) := \|X(\mathbf{w} - a\mathbf{q} - b)\|_2^2$ be the objective in Equation (1), we try to find a coordinate i and value r, such that updating the i^{th} coordinate to r gives the biggest reduction in loss

$$\min_{i,r} \mathcal{L}(\mathbf{q} + (r - q_i)\mathbf{e}_i) - \mathcal{L}(\mathbf{q}),$$

where q_i is the i^{th} element of $\mathbf{q}$, and $\mathbf{e}_i$ is the standard basis vector with 1 in i position and 0 everywhere else. Luckily for us, this can be implemented extremely efficiently as we have analytical expressions for the objective. In particular, one can easily show that

$$\mathcal{L}(\mathbf{q} + (r - q_i)\mathbf{e}_i) - \mathcal{L}(\mathbf{q}) = (r - q_i)^2 H_{i,i} + (r - q_i)\mathbf{g}_i,$$

where $H, \mathbf{g}$ are the Hessian and gradient of $\mathcal{L}$ evaluated at $\mathbf{q}$. This follows from the fact that $\mathcal{L}$ is a quadratic function in $\mathbf{q}$. Algorithm 1 describes this procedure (note that line 5 is the key step which identifies the descent direction).

Remark 1 (Comparison with OBQ). *Similar to our technique, OBQ also updates its coodinates in a greedy manner. But it differs from our algorithm in one crucial step: it updates all the unquantized coordinates in each step (see Equation 2 in Frantar et al. (2022)). Implementing this step on accelerators such as GPUs/TPUs is extremely slow because of the sheer number of gathers/scatters that need to be performed at each step. In contrast, our algorithm only requires updating one coordinate at a time.*

Extension to Block Coordinate Descent. A natural extension to Algorithm 1 is block coordinate descent (BCD), where multiple coordinates are updated simultaneously in each iteration. While a greedy approach to BCD could, in principle, optimize the objective much better, the computational cost becomes prohibitive. Specifically, updating k coordinates at a time necessitates evaluating $(d_{\text{in}} \times 2^c)^k$ possible combinations of coordinates and their corresponding values. To address this, we propose a randomized BCD strategy (see Algorithm 2), which partitions the coordinates into random d_{in}/k blocks and searches only over these blocks. This significantly reduces the search space to a more manageable $d_{\text{in}}/k \times 2^{kc}$ possibilities, making the algorithm practical for larger models. In our experiments, we primarily use $k = 2$ and $c \in \{2, 3, 4\}$. Note that Algorithm 2 with $k = 1$ recovers Algorithm 1.

Algorithm 2 Block Coordinate Descent with Random Blocks (BCD)

1: **Input:** T - coordinate descent steps, k - block size, X - input data matrix, $\mathbf{w}$ - vector to be quantized, a - scale, b - bias, $\mathbf{q}_0$ - initial estimate
2: Compute Hessian H as: $H \leftarrow X^T X$
3: Compute gradient $\mathbf{g}$ as: $\mathbf{g} \leftarrow 2H(\mathbf{q}_0 - a^{-1}(\mathbf{w} - b))$
4: **for** $t \in [1 : T]$ **do**
5:     Randomly partition the set $\{0, 1, \dots d_{\text{in}} - 1\}$ into d_{in}/k blocks, each of size k
6:     Find the block that leads to the largest reduction in loss

$$i^*, \mathbf{r}^* = \underset{\substack{i \in \{0,1,\dots d_{\text{in}}/k-1\}, \\ \mathbf{r} \in \{0,1,\dots 2^c-1\}^k}}{\arg\min} (\mathbf{r} - \mathbf{q}_{t-1,i})^T H_{i,i} (\mathbf{r} - \mathbf{q}_{t-1,i}) + (\mathbf{r} - \mathbf{q}_{t-1,i})^T \mathbf{g}_i,$$

where $\mathbf{q}_{t-1,i}, H_{i,i}$ are the sub-vector, sub-matrix of $\mathbf{q}_{t-1}, H$ corresponding to block i.
7:     Update gradient $\mathbf{g}$ as

$$\mathbf{g} \leftarrow \mathbf{g} + 2H_{i^*,\cdot}(\mathbf{r}^* - \mathbf{q}_{t-1,i^*}),$$

8:     Update $\mathbf{q}_{t-1}$ as

$$\mathbf{q}_{t-1,i^*} \leftarrow \mathbf{r}^*, \quad \mathbf{q}_t \leftarrow \mathbf{q}_{t-1},$$

9: **end for**

Initializing $a, b, \mathbf{q}$. To initialize $a, b, \mathbf{q}$ in Algorithms 1, 2, we introduce a technique called Optimal Weight Clipping (OWC), which draws inspiration from the Learnable Weight Clipping (LWC) mechanism used in OmniQuant (Shao et al., 2023). In OWC, we quantize weight $\mathbf{w}$ as follows

$$\mathbf{q} = \text{clamp}\left(\left\lfloor \frac{\mathbf{w} - b}{a} \right\rceil, 0, 2^c - 1\right), \quad a = \frac{\gamma(\max(\mathbf{w}) - \min(\mathbf{w}))}{2^c - 1}, \quad b = \min(\mathbf{w}). \quad (2)$$

Here, $\gamma \in [0, 1]$ represents the clipping strength. We determine the optimal γ by minimizing the following layer-wise loss:

$$\min_{\gamma \in [0,1]} \|X(\mathbf{w} - a\mathbf{q} - b)\|_2^2.$$

Note that while not explicitly stated, both $\mathbf{q}, a$ in the above objective are implicitly dependent on γ. This optimization can be efficiently solved using a simple grid search. In contrast, LWC (Shao et al., 2023) optimizes a different objective function, focusing on end-to-end quantization of entire transformer block using gradient-based techniques. It is worth noting that setting $\gamma = 1$ in OWC recovers the widely used MinMax quantization scheme, which is used in many existing quantization methods, including GPTQ (Frantar et al., 2022), SmoothQuant(Xiao et al., 2023). However, MinMax quantization is susceptible to outlier weights, and a smaller γ often yields superior results. In our experiments, we observed that OWC provides a much better initialization compared to MinMax quantization, for both GPTQ and CDQuant, suggesting its broader applicability.

3.2 EXTENSION TO SUB-CHANNEL QUANTIZATION

In this section, we consider sub-channel (or group) quantization, which is a more fine-grained quantization that divides the weight vector $\mathbf{w}$ into multiple groups and assigns a quantization scale to each group (Dettmers et al., 2021; Dettmers & Zettlemoyer, 2023). Letting g be the group size, we divide weight $\mathbf{w}$ into d_{in}/g groups $\{\mathbf{w}^{(0)}, \mathbf{w}^{(1)}, \dots \mathbf{w}^{(d_{\text{in}}/g-1)}\}$ each of size g, and quantize $\mathbf{w}^{(i)}$ as $a^{(i)}\mathbf{q}^{(i)} + b^{(i)}$. To learn the optimal parameters for this sub-channel quantization, we solve the following optimization problem:

$$\min_{\{a^{(i)}, b^{(i)}, \mathbf{q}^{(i)}\}_{i=0}^{d_{\text{in}}/g-1}} \left\| \sum_{i=0} X^{(i)}(\mathbf{w}^{(i)} - a^{(i)}\mathbf{q}^{(i)} - b^{(i)}) \right\|_2^2. \quad (3)$$

Here, $X^{(i)}$ represents the columns of X corresponding to the indices within group i. To solve this optimization problem, we employ a coordinate descent approach, similar to Algorithms 1 and 2 described earlier. That is, given initial values for the scaling and bias parameters, we iteratively optimize the quantized representation $\mathbf{q}$ using coordinate descent. Due to space constraints, we present the resulting algorithms in Appendix E (see Algorithms 4, 5).

Algorithm 3 Coordinate Descent for Optimal Weight Clipping (OWC-CD)

1: **Input:** T - coordinate descent steps, g - group size, X - input data matrix, $\mathbf{w}$ - weight vector, Γ- grid of possible values for clipping strength
2: **for** $\beta \in \Gamma$ **do**
3:     **for** $i \in [0 : d_{\text{in}}/g - 1]$ **do**
4:         Compute quantization *residual* $\Delta(i, \beta)$ for group i with clipping strength β as:

$$\Delta(i, \beta) \leftarrow \mathbf{w}^{(i)} - a^{(i)}(\beta)\mathbf{q}^{(i)}(\beta) - b^{(i)}(\beta),$$

        where $a^{(i)}(\beta), b^{(i)}(\beta), \mathbf{q}^{(i)}(\beta)$ are as defined in Equation (2).
5:     **end for**
6: **end for**
7: Initialize clipping strengths for each group $\gamma^{(0)}, \dots \gamma^{(d_{\text{in}}/g - 1)}$
8: Compute Hessian H as: $H \leftarrow X^T X$
9: $\mathbf{v}_i \leftarrow -2H_i(a\mathbf{q} + b - w)$ where H_i is the sub-matrix of H corresponding to the columns of group i.
10: **for** $t \in [1 : T]$ **do**
11:     Find the group that leads to the largest reduction in loss

$$i^*, \beta^* = \underset{\substack{i \in \{0,1,\dots d_{\text{in}}/g-1\}, \\ \beta \in \Gamma}}{\arg \min} \ (\Delta(i, \gamma^{(i)}) - \Delta(i, \beta))^T H_{i,i}(\Delta(i, \gamma^{(i)}) - \Delta(i, \beta))$$

$$+ \mathbf{v}_i^T(\Delta(i, \gamma^{(i)}) - \Delta(i, \beta))$$

    where $H_{i,i}$ is the block diagonal element of H corresponding to group i.
12:     Update $\mathbf{v} \leftarrow \mathbf{v} + 2(\Delta(i^*, \gamma^{(i^*)}) - \Delta(i^*, \beta^*))^T H_{i^*}$
13:     Update $\gamma^{(i^*)} \leftarrow \beta^*$
14: **end for**

Initialization. Next, we tackle the initialization of parameters $\{a^{(i)}, b^{(i)}, \mathbf{q}^{(i)}\}_{i=0}^{d_{\text{in}}/g-1}$ for our coordinate descent procedure. Our approach draws inspiration from the OWC algorithm described above, adapting its core idea to this problem. In essence, we reframe the initialization problem as one of selecting optimal clipping strengths $\{\gamma^{(i)}\}_{i=0}^{d_{\text{in}}/g-1}$ for groups $\{0, \dots d_{\text{in}}/g - 1\}$. This leads us to the following problem

$$\min_{\gamma^{(0)}, \dots \gamma^{(d_{\text{in}}/g-1)}} \big|\big| \sum_{i=0} X^{(i)}(\mathbf{w}^{(i)} - a^{(i)}\mathbf{q}^{(i)} - b^{(i)})\big|\big|_2^2, \tag{4}$$

where

$$\mathbf{q}^{(i)} = \text{clamp}\left(\left\lfloor \frac{\mathbf{w}^{(i)} - b^{(i)}}{a^{(i)}} \right\rceil, 0, 2^c - 1\right), \ a^{(i)} = \frac{\gamma^{(i)}(\max(\mathbf{w}^{(i)}) - \min(\mathbf{w}^{(i)}))}{2^c - 1}, \ b^{(i)} = \min(\mathbf{w}^{(i)}).$$

While not explicitly stated, both $\mathbf{q}^{(i)}, a^{(i)}$ implicitly depend on the clipping strength $\gamma^{(i)}$. We use greedy coordinate descent to optimize Equation (4). In each iteration, we update the $\gamma^{(i)}$ that leads to biggest drop in loss (lines 10-14 of Algorithm 3). This procedure, which we call OWC-CD, is described in Algorithm 3.

4 EXPERIMENTS

In this section, we first establish that CDQuant achieves superior quantization quality compared to GPTQ. Subsequently, we show its versatility by successfully integrating it as a drop-in replacement for GPTQ within existing PTQ methods such as AWQ (Lin et al., 2023), QuIP (Chee et al., 2024), FrameQuant (Adepu et al., 2024).

4.1 COMPARISON WITH GPTQ

We first present the experimental setup and then move on to our results. In all the experiments in this section, the attention layers are quantized to INT8 using MinMax quantization, and low-

Table 1: Table presents the perplexity evaluations for GPTQ, CD, BCD for INT2 quantization of FFN weights.

Method	Epochs	Gemma-1 7B	Gemma-2 9B	Gemma-2 27B	PaLM2-Otter	PaLM2-Bison
w16a16		10.384	10.683	8.682	5.984	5.298
w2a16g128						
GPTQ	-	375.153	13.785	12.181	10.816	7.230
CD	1	75.55	13.709	11.966	9.917	7.123
BCD(k=2)	1	**68.732**	**13.662**	**11.873**	**9.822**	**7.094**

bit quantization schemes are only applied to the feed-forward layers (FFN). See Appendix F for experiments with quantized attention and FFN layers.

Models. Our experiments leverage two families of language models: the open-source Gemma models (Mesnard et al., 2024) and the proprietary PaLM 2 models (Anil et al., 2023). Specifically, we use Gemma-1 7B, Gemma-2 9B, and Gemma-2 27B from the Gemma family, and PaLM2-Gecko, PaLM2-Otter, and PaLM2-Bison from the PaLM2 family. Within the PaLM 2 family, the models increase in size from Gecko to Otter to Bison.

Baselines. Since our primary goal is to demonstrate that CDQuant gets improved performance over GPTQ, we have chosen it as the primary baseline in most of our experiments in this section. For all our experiments, we initialize GPTQ with OWC, and run GPTQ for $T = d_{\text{in}}$ steps. To ensure stability and generalization, GPTQ regularizes its Hessian matrix by adding a scaled identity matrix (λI). Tuning this λ for every (model, layer) pair is infeasible. So, we determine a single optimal value using the PaLM2-Gecko model, and apply it universally.

CDQuant. We evaluate both the coordinate descent variants described in Section 3.1: CD (Algorithm 1), BCD (Algorithm 2). For per-channel quantization, we initialize CD with Optimal Weight Clipping (OWC), and for sub-channel quantization, we additionally include initialization with OWC-CD. BCD is always initialized with CD in our experiments. Unless otherwise stated, both CD and BCD are run for $T = d_{\text{in}}$ iterations, OWC-CD is run for d_{in}/g iterations, where g is the group size. Similar to GPTQ, we regularize the Hessian matrix used in CD, BCD by adding λI. We determine a reasonable value for λ using the PaLM2-Gecko model, and use it in all our experiments.

Evaluation. Following recent works (Frantar et al., 2022; Ma et al., 2024), we evaluate all algorithms using two key metrics: perplexity and downstream task performance. For Gemma models, following Frantar et al. (2022), we calculate perplexity on C4's (Raffel et al., 2019) validation set. For PaLM2 models, we calculate perplexity using a 100 million token subset derived from the PaLM2 training mixture. We use TriviaQA (Joshi et al., 2017), SQuAD (Rajpurkar et al., 2018), NaturalQuestions (Kwiatkowski et al., 2019) and WebQuestions (Berant et al., 2013) to evaluate *generation* capabilities of the quantized models, and to evaluate their *reasoning* capabilities, we test on ARC-c, ARC-e (Clark et al., 2018), HellaSwag (Zellers et al., 2019), BoolQ (Clark et al., 2019), PIQA (Bisk et al., 2020) and WinoGrande (Sakaguchi et al., 2020). For downstream evaluations, we consider the *zero-shot* setting. Finally, to determine which optimization technique is most effective at solving the layer-wise objective in Equation (1), we evaluate the final solution's objective value using the same 100 million tokens that we used to compute perplexity.

Training. All techniques are calibrated using 1280 data points, where each data point has 2048 tokens. For OWC, we use a grid size of 50 to find the most optimal γ. We used 8 Nvidia H100 GPUs for quantizing the models.

Results for 2 bit quantization. Table 1 presents the INT2 perplexity numbers for different quantization techniques applied to FFN layers. It can be seen that both our CD and BCD methods have a clear advantage over GPTQ, leading to lower perplexity scores for all models and quantization levels. For example, on PaLM-2 Otter, we see almost 10% improvement in perplexity over GPTQ.

Results for 3,4 bit quantization. Table 2 presents the perplexity numbers for different quantization techniques on 3,4 bit quantization. It can be seen that both our CD and BCD methods have a clear advantage over GPTQ, leading to lower perplexity scores for all models and quantization levels. The difference is more pronounced for lower bit quantization.

Table 2: Table presents the perplexity evaluations for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights. wx, ay, gz in the config column corresponds to x-bit weights, y-bit activations and group/sub-channel size of z.

Config	Method	Gemma-1 7B	Gemma-2 9B	Gemma-2 27B	PaLM2 Gecko	PaLM2 Otter	PaLM2 Bison
w16a16	-	10.348	10.683	8.682	7.948	5.984	5.298
w3a16	OWC	$2.885e4$	11.666	11.823	12.570	17.928	6.169
	GPTQ	48.157	11.382	9.681	11.347	7.176	5.774
	CD	19.614	11.301	9.551	10.920	7.002	5.739
	BCD(k=2)	**18.552**	**11.284**	**9.526**	**10.898**	**6.979**	**5.733**
w3a16g128	OWC	21.815	11.338	9.655	11.597	8.342	5.847
	GPTQ	15.561	11.193	9.260	10.414	6.635	5.677
	CD	13.496	11.182	9.237	10.273	6.655	5.656
	BCD(k=2)	13.501	11.180	9.214	10.259	6.545	5.654
	OWC-CD	14.827	11.220	9.290	10.706	6.635	5.686
	OWC-CD + CD	13.042	11.131	**9.194**	10.143	6.528	5.650
	OWC-CD + BCD(k=2)	**13.004**	**11.131**	9.199	**10.138**	**6.527**	**5.647**
w4a16	OWC	26.438	10.929	9.252	8.946	6.693	5.475
	GPTQ	13.355	10.896	8.923	8.764	6.249	5.417
	CD	12.142	**10.860**	8.910	8.694	6.195	5.407
	BCD(k=2)	**12.048**	10.863	**8.899**	**8.691**	**6.192**	**5.405**
w4a16g128	OWC	11.598	10.82	8.870	8.613	6.264	5.401
	GPTQ	11.086	10.784	8.786	8.498	6.112	5.377
	CD	10.838	10.777	8.781	8.456	6.097	5.373
	BCD(k=2)	10.797	**10.775**	8.786	8.454	6.097	5.372
	OWC-CD	10.981	10.786	8.802	8.519	6.106	5.377
	OWC-CD + CD	10.766	10.776	8.778	8.436	6.092	5.371
	OWC-CD + BCD(k=2)	**10.760**	10.780	**8.774**	**8.434**	**6.091**	**5.371**

Table 3: Table presents the perplexity evaluations for INT2 per-channel quantization of FFN weight with QuIP and FrameQuant, where, GPTQ, CD and BCD are used as subroutines.

	Method	Gemma-1 7B	Gemma-2 9B	Gemma-2 27B
	w16a16	10.384	10.683	8.682
QuIP	GPTQ	25.941	13.695	11.909
	CD	24.025	13.172	**11.479**
	BCD(k=2)	**19.167**	**13.144**	11.547
FrameQuant	GPTQ	26.262	12.941	10.958
	CD	19.726	12.748	10.785
	BCD(k=2)	**18.242**	**12.674**	**10.608**

Downstream Evals. Downstream evaluations for the PaLM2 and Gemma model families are presented in Tables 7 and 8, respectively. These tables report the average performance across generation and ranking tasks. For a detailed per-task breakdown of the results please refer to Appendix F.2. These results demonstrate that our models achieve comparable, if not superior, performance to GPTQ across all tasks. Notably, our techniques exhibit significant improvements over GPTQ for smaller models like PaLM2-Gecko and Gemma-1 7B.

Layer-wise objective. Finally, in our experiments we also observe that coordinate descent techniques are better at optimizing the layer-wise objective in Equation (1), than GPTQ. For instance, for INT3 per-channel quantization of Gemma-2 9B, the average objective value (relative to all 0's solution) for GPTQ, for the 1^{st} feed-forward layer is 0.1449, whereas for CD it is 0.1362, and for BCD(k=2) it is 0.1357 (which translates to $\sim 6\%$ reduction in the objective value).

4.2 VERSATILITY OF CDQUANT

A major strength of our algorithm is its versatility. It seamlessly replaces GPTQ in any quantization technique that relies on it. To illustrate this, we focus on the AWQ, QuIP and FrameQuant (the latter

Table 4: Table presents perplexity for GPTQ, CD, BCD for INT3 quantization of FFN layers with AWQ.

Method	Gemma-1 7B		Gemma-2 9B		PaLM2-Otter	
	w3a16	w3a16g128	w3a16	w3a16g128	w3a16	w3a16g128
GPTQ + AWQ	25.695	14.539	11.331	11.158	7.381	6.519
CD + AWQ	19.703	13.254	**11.255**	11.123	7.244	6.475
BCD(k=2) + AWQ	**18.137**	**13.205**	11.265	**11.119**	**7.211**	**6.474**

two are state-of-the-art PTQ techniques). We demonstrate that our algorithm, when layered on top of the aforementioned algorithms, surpasses the performance of GPTQ layered on top of them. Table 3 presents the results for QuIP, FrameQuant, and Table 4 presents the results for AWQ. It can be seen that both CD and BCD provide $\sim 5\%$ boost in performance for QuIP and FrameQuant. For AWQ, we observe that CD, BCD always outperform GPTQ, for both per-channel and sub-channel quantization (the performance of AWQ on PaLM2-Bison is much worse than not performing AWQ. Hence, in Table 4, we only present results for PaLM2-Otter from the PaLM2 family of models).

Table 5: Runtime (in minutes using 8 H100s) comparison of CDQuant, GPTQ for Gemma-2 27B. Note that FFN1 and FFN1-Gate have the same runtimes, hence we report only FFN1's runtime.

Config	Method	FFN1	FFN2	Attn.
	GPTQ	0.3	7.37	1.18
w3a16	CD	1.23	14.1	0.51
	BCD(k=2)	6.03	54.94	2.11
	GPTQ	0.3	7.35	1.18
w4a16	CD	1.65	17.87	0.64
	BCD(k=2)	14.54	133.34	4.64

Table 6: Table presents the perplexity evaluations for INT3 quantization with BCD wherein the FFN2 may be quantized either with CD or BCD, while rest of the FFN parameters are quantized with BCD.

Config	Method	Gemma-1 7B	Gemma-2 9B
w16a16		10.384	10.683
w3a16	CD, FFN2	19.709	11.288
	BCD(k=2), FFN2	18.552	11.284
w3a16g128	CD, FFN2	13.512	11.179
	BCD(k=2), FFN2	13.501	11.180

5 RUNTIME

Table 5 shows the runtime of GPTQ, CD and BCD for quantization of FFN1, FFN2, and attention weights of Gemma-2 27B model using 8 H100s (see Appendix F.4 for 1 GPU runtime). For attention weight quantization, CD is comparable to GPTQ in speed, while BCD is $2\times$ slower. For FFN1 (FFN2) quantization, CD is $5\times$ $(2\times)$ slower than GPTQ, whereas BCD is an order of magnitude slower than GPTQ. It can be seen that FFN2 quantization is the most time-consuming step (because the quantization axis is of size d_{hidden} which is much larger than the quantization axis of other layers). Consequently, CD (BCD) is twice (order of magnitude) as slow as GPTQ for whole-model quantization. We now provide two simple strategies to speed up both CD and BCD.

Speeding up BCD. To speed up BCD, we quantize FFN2 with CD, and rest of the layers with BCD (where the quantization axis is of size d_{model}). Results for this setting can be found in Table 6. It can be seen that quantizing FFN2 with CD leads to negligible to no drop in performance especially for the larger, and better Gemma-2 9B. With this setup, BCD's runtime is reduced significantly and is comparable to that of CD.

Speeding up CD. We find that CD converges to an optimal solution in much fewer iterations than d_{in} iterations used in our experiments. Based on this finding, we run CD for lesser number of iterations. As shown in Table 22 in Appendix, even with a drastically reduced iteration count (e.g., $d_{\text{in}}/8$), CD maintains near-optimal performance with negligible quality loss, surpassing the performance of GPTQ. This reduction in iterations allows CD to achieve a runtime faster than/comparable to GPTQ.

6 CONCLUSION AND FUTURE WORK

In this work, we developed a coordinate descent framework (CDQuant) for quantization of LLMs. CDQuant is a simple and effective alternative to GPTQ, that consistently outperformed it on PaLM2 models. The simplicity of our algorithm makes it a seamless substitute for GPTQ in various algorithmic contexts where GPTQ currently functions as a sub-routine. Our future work aims to further improve the performance of CDQuant. In particular, we would like to use ideas from

CDQuant to improve Quantized Aware Training (QAT). Furthermore, we will focus on developing layer-wise loss functions that are more closely aligned with end-to-end loss, thereby reducing the performance gap between full-precision and quantized models.

REFERENCES

Harshavardhan Adepu, Zhanpeng Zeng, Li Zhang, and Vikas Singh. Framequant: Flexible low-bit quantization for transformers. *arXiv preprint arXiv:2403.06082*, 2024.

Rohan Anil, Andrew M Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, et al. Palm 2 technical report. *arXiv preprint arXiv:2305.10403*, 2023.

Saleh Ashkboos, Amirkeivan Mohtashami, Maximilian L. Croci, Bo Li, Martin Jaggi, Dan Alistarh, Torsten Hoefler, and James Hensman. Quarot: Outlier-free 4-bit inference in rotated llms. *CoRR*, abs/2404.00456, 2024. doi: 10.48550/ARXIV.2404.00456. URL https://doi.org/10.48550/arXiv.2404.00456.

Kayhan Behdin, Ayan Acharya, Aman Gupta, Qingquan Song, Siyu Zhu, Sathiya Keerthi, and Rahul Mazumder. Quantease: Optimization-based quantization for language models. *arXiv preprint arXiv:2309.01885*, 2023.

Jonathan Berant, Andrew Chou, Roy Frostig, and Percy Liang. Semantic parsing on freebase from question-answer pairs. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing, EMNLP 2013, 18-21 October 2013, Grand Hyatt Seattle, Seattle, Washington, USA, A meeting of SIGDAT, a Special Interest Group of the ACL*, pp. 1533–1544. ACL, 2013. URL https://aclanthology.org/D13-1160/.

Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. PIQA: reasoning about physical commonsense in natural language. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 7432–7439. AAAI Press, 2020. doi: 10.1609/AAAI.V34I05.6239. URL https://doi.org/10.1609/aaai.v34i05.6239.

Yuji Chai, John Gkountouras, Glenn G Ko, David Brooks, and Gu-Yeon Wei. Int2. 1: Towards fine-tunable quantized large language models with error correction through low-rank adaptation. *arXiv preprint arXiv:2306.08162*, 2023.

Jerry Chee, Yaohui Cai, Volodymyr Kuleshov, and Christopher M De Sa. Quip: 2-bit quantization of large language models with guarantees. *Advances in Neural Information Processing Systems*, 36, 2024.

Stéphane Chrétien and Franck Corset. Using the eigenvalue relaxation for binary least-squares estimation problems. *Signal processing*, 89(11):2079–2091, 2009.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. In Jill Burstein, Christy Doran, and Thamar Solorio (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*, pp. 2924–2936. Association for Computational Linguistics, 2019. doi: 10.18653/V1/N19-1300. URL https://doi.org/10.18653/v1/n19-1300.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the AI2 reasoning challenge. *CoRR*, abs/1803.05457, 2018. URL http://arxiv.org/abs/1803.05457.

Tim Dettmers and Luke Zettlemoyer. The case for 4-bit precision: k-bit inference scaling laws. In *International Conference on Machine Learning*, pp. 7750–7774. PMLR, 2023.

Tim Dettmers, Mike Lewis, Sam Shleifer, and Luke Zettlemoyer. 8-bit optimizers via block-wise quantization. *arXiv preprint arXiv:2110.02861*, 2021.

Table 7: Table presents *downstream evaluation* (zero-shot) numbers for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights for the PaLM2 family of models. *Gen*, *Rank* columns correspond to generation and ranking tasks.

Config	Method	PaLM2-Gecko			PaLM2-Otter			PaLM2-Bison		
		Gen.	Rank	Avg.	Gen.	Rank	Avg.	Gen.	Rank	Avg.
w16a16	-	20.1	63.02	43.84	36.23	79.51	58.57	44.29	85.44	64.55
w3a16	OWC	15.45	55.73	39.62	15.06	59.29	41.60	39.58	75.45	61.10
	GPTQ	13.08	56.92	39.39	31.80	71.94	55.88	41.42	76.70	62.58
	CD	15.82	58.19	41.24	32.34	72.03	56.16	41.66	76.71	62.69
	BCD(k=2)	16.16	57.85	41.17	32.04	72.22	56.15	41.37	76.78	62.62
w3a16g128	OWC	18.54	56.95	41.59	26.62	68.09	51.50	41.54	76.51	62.52
	GPTQ	17.96	58.30	42.16	33.43	72.98	57.16	43.47	76.65	63.38
	CD	16.81	58.10	41.58	32.73	72.62	56.66	42.95	77.03	63.4
	BCD(k=2)	16.33	57.81	41.22	32.13	72.67	56.46	42.67	76.85	63.18
	OWC-CD	16.73	57.74	41.34	32.90	72.40	56.60	42.23	77.02	63.11
	OWC-CD + CD	16.37	58.22	41.48	33.53	72.64	56.99	43.09	76.91	63.38
	OWC-CD + BCD(k=2)	16.47	58.45	41.66	33.71	72.73	57.12	43.07	76.70	63.25
w4a16	OWC	16.07	59.42	42.08	33.76	72.22	56.83	43.59	77.13	63.71
	GPTQ	18.77	59.5	43.21	34.03	73.53	57.73	44.16	77.54	64.19
	CD	18.20	59.95	43.25	35.01	73.42	58.06	43.97	77.55	64.12
	BCD(k=2)	17.89	59.64	42.94	35.10	73.31	58.02	43.95	77.77	64.24
w4a16g128	OWC	19.00	60.42	43.85	34.52	72.83	57.5	44.45	77.71	64.41
	GPTQ	19.07	60.40	43.87	35.34	73.60	58.29	44.25	77.65	64.29
	CD	20.35	60.94	44.70	36.20	73.67	58.68	44.21	77.72	64.31
	BCD(k=2)	20.44	60.69	44.59	36.11	73.54	58.57	44.17	77.56	64.2
	OWC-CD	19.80	60.39	44.15	36.33	73.62	58.71	44.75	77.70	64.52
	OWC-CD + CD	20.47	60.85	44.70	35.98	73.59	58.54	44.77	77.52	64.42
	OWC-CD + BCD(k=2)	20.15	60.49	44.36	36.00	73.62	58.57	44.70	77.70	64.50

Table 8: Table presents *downstream evaluation* (zero-shot) numbers for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights for both, Gemma-1 and Gemma-2 models. *Gen*, *Rank* columns correspond to generation and ranking tasks.

Config	Method	Gemma-1 7B			Gemma-2 9B			Gemma-2 27B		
		Gen.	Rank	Avg.	Gen.	Rank	Avg.	Gen.	Rank	Avg.
w16a16		40.6	76.96	58.35	49.34	82.6	64.36	52.57	77.53	67.55
w316	OWC	0.76	43.95	26.6	45.84	73.51	62.44	47.29	75.21	64.04
	GPTQ	19.58	58.33	40.87	45.82	73.11	62.19	49.91	75.53	65.28
	CD	27.83	69.75	50.2	46.48	73.4	62.63	50.09	75.98	65.62
	BCD(k=2)	28.21	70.08	50.51	46.23	73.34	62.49	50.34	76.03	65.75
w3a16g128	OWC	28.47	66.85	48.65	46.9	73.35	62.77	50.77	76.81	66.39
	GPTQ	32.94	73.23	53.82	46.62	73.52	62.76	51.26	76.49	66.4
	CD	34.22	73.03	54.08	46.59	73.34	62.64	51.32	77.1	66.78
	BCD(k=2)	34.52	73.82	54.65	46.65	73.35	62.67	51.22	77.22	66.82
	OWC-CD	32.76	72.61	53.39	46.64	73.03	62.48	50.99	76.97	66.57
	OWC-CD + CD	34.3	73.8	54.57	46.7	73.46	62.75	51.55	77.07	66.86
	OWC-CD + BCD(k=2)	34.59	74.21	54.9	46.7	73.47	62.76	51.49	77.12	66.87
w4a16	OWC	30.69	68.82	50.5	48.49	74.1	63.85	51.63	76.9	66.79
	GPTQ	35.95	74.94	55.75	48.5	74.39	64.03	52.12	76.98	67.04
	CD	37.95	75.6	56.74	48.74	74.27	64.05	51.85	77.2	67.06
	BCD(k=2)	38.11	75.95	57	48.72	74.3	64.06	51.9	77.11	67.03
w4a16g128	OWC	38.51	75.35	56.76	49.22	73.98	64.08	52.05	77.6	67.38
	GPTQ	39.85	76.68	57.96	48.9	73.98	63.95	52.12	77.63	67.43
	CD	40.01	76.79	58.08	48.9	74.05	63.99	52.29	77.6	67.47
	BCD(k=2)	40.14	76.61	58.01	49.02	73.98	64	52.22	77.65	67.48
	OWC-CD	39.44	75.99	57.43	49.26	74.21	64.23	52.15	77.75	67.51
	OWC-CD + CD	40.19	76.89	58.19	49.06	74.13	64.1	52.24	77.71	67.52
	OWC-CD + BCD(k=2)	39.94	76.52	57.89	49.1	74.17	64.14	52.14	77.69	67.47

Tim Dettmers, Mike Lewis, Younes Belkada, and Luke Zettlemoyer. Gpt3. int8 (): 8-bit matrix multiplication for transformers at scale. *Advances in Neural Information Processing Systems*, 35: 30318–30332, 2022.

Tim Dettmers, Ruslan Svirschevski, Vage Egiazarian, Denis Kuznedelev, Elias Frantar, Saleh Ashkboos, Alexander Borzunov, Torsten Hoefler, and Dan Alistarh. Spqr: A sparse-quantized representation for near-lossless llm weight compression. *arXiv preprint arXiv:2306.03078*, 2023.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. Qlora: Efficient finetuning of quantized llms. *Advances in Neural Information Processing Systems*, 36, 2024.

Vage Egiazarian, Andrei Panferov, Denis Kuznedelev, Elias Frantar, Artem Babenko, and Dan Alistarh. Extreme compression of large language models via additive quantization. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=5mCaITRTmO.

Elias Frantar and Dan Alistarh. Optimal brain compression: A framework for accurate post-training quantization and pruning. *Advances in Neural Information Processing Systems*, 35:4475–4488, 2022.

Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. Gptq: Accurate post-training quantization for generative pre-trained transformers. *arXiv preprint arXiv:2210.17323*, 2022.

Gemma-Team. Gemma 2: Improving open language models at a practical size. *ArXiv*, abs/2408.00118, 2024. URL https://api.semanticscholar.org/CorpusID:270843326.

Gemini Team Google. Gemini: A family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Jinyang Guo, Jianyu Wu, Zining Wang, Jiaheng Liu, Ge Yang, Yifu Ding, Ruihao Gong, Haotong Qin, and Xianglong Liu. Compressing large language models by joint sparsification and quantization. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=sCGRhnuMUJ.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Itay Hubara, Yury Nahshan, Yair Hanani, Ron Banner, and Daniel Soudry. Accurate post training quantization with small calibration sets. In *International Conference on Machine Learning*, pp. 4466–4475. PMLR, 2021.

Mandar Joshi, Eunsol Choi, Daniel S. Weld, and Luke Zettlemoyer. Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics, ACL 2017, Vancouver, Canada, July 30 - August 4, Volume 1: Long Papers*, pp. 1601–1611. Association for Computational Linguistics, 2017. doi: 10.18653/V1/P17-1147. URL https://doi.org/10.18653/v1/P17-1147.

Sehoon Kim, Coleman Hooper, Amir Gholami, Zhen Dong, Xiuyu Li, Sheng Shen, Michael W. Mahoney, and Kurt Keutzer. Squeezellm: Dense-and-sparse quantization. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=0jpbpFia8m.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur P. Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: a benchmark for question answering research. *Trans. Assoc. Comput. Linguistics*, 7:452–466, 2019. doi: 10.1162/TACL_A_00276. URL https://doi.org/10.1162/tacl_a_00276.

Yann LeCun, John Denker, and Sara Solla. Optimal brain damage. *Advances in neural information processing systems*, 2, 1989.

Changhun Lee, Jungyu Jin, Taesu Kim, Hyungjun Kim, and Eunhyeok Park. Owq: Lessons learned from activation outliers for weight quantization in large language models. *arXiv preprint arXiv:2306.02272*, 2023.

Yuhang Li, Ruihao Gong, Xu Tan, Yang Yang, Peng Hu, Qi Zhang, Fengwei Yu, Wei Wang, and Shi Gu. Brecq: Pushing the limit of post-training quantization by block reconstruction. *arXiv preprint arXiv:2102.05426*, 2021.

Ji Lin, Jiaming Tang, Haotian Tang, Shang Yang, Xingyu Dang, and Song Han. Awq: Activation-aware weight quantization for llm compression and acceleration. *arXiv preprint arXiv:2306.00978*, 2023.

Jing Liu, Ruihao Gong, Xiuying Wei, Zhiwei Dong, Jianfei Cai, and Bohan Zhuang. Qllm: Accurate and efficient low-bitwidth quantization for large language models. *arXiv preprint arXiv:2310.08041*, 2023.

Zechun Liu, Changsheng Zhao, Igor Fedorov, Bilge Soran, Dhruv Choudhary, Raghuraman Krishnamoorthi, Vikas Chandra, Yuandong Tian, and Tijmen Blankevoort. Spinquant: LLM quantization with learned rotations. *CoRR*, abs/2405.16406, 2024. doi: 10.48550/ARXIV.2405.16406. URL https://doi.org/10.48550/arXiv.2405.16406.

Yuexiao Ma, Huixia Li, Xiawu Zheng, Feng Ling, Xuefeng Xiao, Rui Wang, Shilei Wen, Fei Chao, and Rongrong Ji. Affinequant: Affine transformation quantization for large language models. *arXiv preprint arXiv:2403.12544*, 2024.

Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, Pouya Tafti, Léonard Hussenot, Aakanksha Chowdhery, Adam Roberts, Aditya Barua, Alex Botev, Alex Castro-Ros, Ambrose Slone, Amélie Héliou, Andrea Tacchetti, Anna Bulanova, Antonia Paterson, Beth Tsai, Bobak Shahriari, Charline Le Lan, Christopher A. Choquette-Choo, Clément Crepy, Daniel Cer, Daphne Ippolito, David Reid, Elena Buchatskaya, Eric Ni, Eric Noland, Geng Yan, George Tucker, George-Cristian Muraru, Grigory Rozhdestvenskiy, Henryk Michalewski, Ian Tenney, Ivan Grishchenko, Jacob Austin, James Keeling, Jane Labanowski, Jean-Baptiste Lespiau, Jeff Stanway, Jenny Brennan, Jeremy Chen, Johan Ferret, Justin Chiu, and et al. Gemma: Open models based on gemini research and technology. *CoRR*, abs/2403.08295, 2024. doi: 10.48550/ARXIV.2403.08295. URL https://doi.org/10.48550/arXiv.2403.08295.

Xupeng Miao, Gabriele Oliaro, Zhihao Zhang, Xinhao Cheng, Hongyi Jin, Tianqi Chen, and Zhihao Jia. Towards efficient generative large language model serving: A survey from algorithms to systems. *arXiv preprint arXiv:2312.15234*, 2023.

Markus Nagel, Rana Ali Amjad, Mart Van Baalen, Christos Louizos, and Tijmen Blankevoort. Up or down? adaptive rounding for post-training quantization. In *International Conference on Machine Learning*, pp. 7197–7206. PMLR, 2020.

OpenAI. Gpt-4 technical report. Technical report, 2023. URL https://cdn.openai.com/papers/gpt-4.pdf.

Jaehyun Park and Stephen Boyd. A semidefinite programming method for integer convex quadratic minimization. *Optimization Letters*, 12:499–518, 2018.

Yeonhong Park, Jake Hyun, SangLyul Cho, Bonggeun Sim, and Jae W. Lee. Any-precision LLM: low-cost deployment of multiple, different-sized llms. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=u09gadH3BU.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv e-prints*, 2019.

Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for squad. In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics, ACL 2018, Melbourne, Australia, July 15-20,*

2018, Volume 2: Short Papers, pp. 784–789. Association for Computational Linguistics, 2018. doi: 10.18653/V1/P18-2124. URL https://aclanthology.org/P18-2124/.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 8732–8740. AAAI Press, 2020. doi: 10.1609/AAAI.V34I05.6399. URL https://doi.org/10.1609/aaai.v34i05.6399.

Wenqi Shao, Mengzhao Chen, Zhaoyang Zhang, Peng Xu, Lirui Zhao, Zhiqian Li, Kaipeng Zhang, Peng Gao, Yu Qiao, and Ping Luo. Omniquant: Omnidirectionally calibrated quantization for large language models. *arXiv preprint arXiv:2308.13137*, 2023.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Albert Tseng, Jerry Chee, Qingyao Sun, Volodymyr Kuleshov, and Christopher De Sa. Quip#: Even better LLM quantization with hadamard incoherence and lattice codebooks. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=9BrydUVcoe.

Xiuying Wei, Yunchen Zhang, Xiangguo Zhang, Ruihao Gong, Shanghang Zhang, Qi Zhang, Fengwei Yu, and Xianglong Liu. Outlier suppression: Pushing the limit of low-bit transformer language models. *Advances in Neural Information Processing Systems*, 35:17402–17414, 2022.

Xiuying Wei, Yunchen Zhang, Yuhang Li, Xiangguo Zhang, Ruihao Gong, Jinyang Guo, and Xianglong Liu. Outlier suppression+: Accurate quantization of large language models by equivalent and optimal shifting and scaling. *arXiv preprint arXiv:2304.09145*, 2023.

Guangxuan Xiao, Ji Lin, Mickael Seznec, Hao Wu, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models. In *International Conference on Machine Learning*, pp. 38087–38099. PMLR, 2023.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? In Anna Korhonen, David R. Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- August 2, 2019, Volume 1: Long Papers*, pp. 4791–4800. Association for Computational Linguistics, 2019. doi: 10.18653/V1/P19-1472. URL https://doi.org/10.18653/v1/p19-1472.

Cheng Zhang, Jianyi Cheng, George Anthony Constantinides, and Yiren Zhao. LQER: low-rank quantization error reconstruction for llms. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL https://openreview.net/forum?id=dh8k41g775.

A BROADER IMPACT

We introduce a Coordinate Descent based approach, CDQuant, for compressing Large Language Models. Our method uses only a small amount of data for calibration. We do not foresee any ethical implications arising from the technical aspects of our approach. However, compressing LLMs may give rise to bias effects, a study of which seems essential given the extensive use of LLMs. Our work may be of assistance to such studies. Also, since quantization allows for easier deployment of LLMs, it could have potential societal implications which seem difficult to predict.

B LIMITATIONS

- While both CD and BCD outperformed GPTQ in our experiments, BCD achieves slightly better performance than CD. However, BCD is not as fast as CD and can be expensive for large models. In future, we aim to develop techniques to speed up BCD.

- Our algorithms still don't bridge the gap between QAT and PTQ, especially on smaller models. To bridge this gap, we believe one should move away from the ℓ_2^2 surrogate loss that is being considered by most of the existing work. Instead, we should design surrogate losses that are more closely aligned with end-to-end loss.

C RELATED WORK

In this section, we provide a more thorough comparison of our technique with OBQ and GPTQ.

Detailed comparison with OBQ. At a high level, both OBQ, and our technique use greedy strategies to quantize the weights. However, OBQ is extremely slow and doesn't even scale to models with a few billion parameters. The primary reason for this unreasonable slowness is because of a more complicated step involved in OBQ which requires updating all the unquantized coordinates in each step (please refer to equation 2 in Frantar & Alistarh (2022)). Implementing this step in GPUs is extremely slow because of the sheer number of gathers/scatters that need to be performed at each step. In contrast, CDQuant doesn't have this step. At each step of coordinate descent, we only update the single coordinate that leads to the biggest drop in performance. As a result, CDQuant is orders of magnitude faster than OBQ. To quantify this last statement, note that GPTQ paper only ran OBQ for models with a few hundred millions of parameters and showed that OBQ is almost 120x slower than GPTQ (note that this difference will only grow with larger models because OBQ will require even more gathers/scatters). In fact, in the OBQ paper (Frantar & Alistarh, 2022), in Table 6, OBQ takes 65 minutes to quantize a ResNet50 model with 25M parameters. That being said, scaling it to models with billions of parameters seems extremely difficult.

Detailed comparison with GPTQ. GPTQ, as discussed in Section 2, is a heuristic designed to accelerate OBQ by replacing its greedy strategy with a single, predetermined cycle through all coordinates. While this approach improves speed, it often sacrifices accuracy. Although multiple cycles could potentially mitigate this performance drop, our experiments revealed no significant improvement in quality. In contrast, we propose a simple yet effective greedy coordinate descent strategy that achieves superior accuracy while maintaining the computational efficiency of GPTQ.

D COMPARISON TO QUANTEASE

In this section, we compare our per-channel quantization results with those of QuantEase, a parallel study to ours. It's important to note that QuantEase does not have a publicly available implementation. So, we implemented the cyclic coordinate descent strategy used by QuantEase, and used the same initialization and regularization strength as our algorithms (although the QuantEase paper doesn't provide these details). We then ran QuantEase for the recommended number of iterations specified in the paper (20 epochs or $T = 20d_{\text{in}}$ iterations). The findings are presented in Table 9. On PaLM2-Gecko, PaLM2-Otter, and PaLM2-Bison, both these approaches have similar performance. These results collectively highlight the potential of coordinate descent algorithms in outperforming GPTQ, especially for low bit quantization.

Table 9: Comparison of QuantEase with CD and BCD for FFN quantization.

Config	Method	PaLM2-Gecko	PaLM2-Otter	PaLM2-Bison
	GPTQ	11.347	7.176	5.774
w3a16	QuantEase (epochs=20)	10.731	6.996	5.741
	CD	10.920	7.002	5.739
	BCD(k=2)	10.898	6.979	5.733
	GPTQ	8.764	6.249	5.417
w4a16	QuantEase (epochs=20)	8.670	6.197	5.408
	CD	8.694	6.195	5.407
	BCD(k=2)	8.691	6.192	5.405

E   CDQUANT FOR SUB-CHANNEL QUANTIZATION

To simplify the explanation in this section, we introduce a slightly modified notation. Given a weight vector $\mathbf{w}$, we represent it's sub-channel quantization as $\mathbf{a} \odot \mathbf{q} + \mathbf{b}$, where $\odot$ is the elementwise multiplication, and $\mathbf{a}, \mathbf{b} \in \mathbb{R}^{d_{\text{in}}}$ are the scale, and bias parameters that satisfy the following constraints: $\mathbf{a}_k = \mathbf{a}_l, \mathbf{b}_k = \mathbf{b}_l$, for any two indices k, l that fall in the same group. With this notation, for any given $\mathbf{a}, \mathbf{b}$, the optimization problem in Equation (3) can be rewritten as

$$\min_{\mathbf{q}} \|X(\mathbf{w} - \mathbf{a} \odot \mathbf{q} - \mathbf{b})\|_2^2. \tag{5}$$

Letting $D_{\mathbf{a}} = \text{diag}(\mathbf{a}), \tilde{X} = XD_{\mathbf{a}}, \tilde{\mathbf{w}} = D_{\mathbf{a}}^{-1}\mathbf{w}, \tilde{\mathbf{b}} = D_{\mathbf{a}}^{-1}\mathbf{b}$, the above problem can be further rewritten as

$$\min_{\mathbf{q}} \|\tilde{X}(\tilde{\mathbf{w}} - \mathbf{q} - \tilde{\mathbf{b}})\|_2^2. \tag{6}$$

Observe that this problem is the same as the per-channel quantization problem described in Equation (1), but with modified parameters $\tilde{X}, \tilde{\mathbf{w}}, \tilde{\mathbf{b}}$. So extending CDQuant to sub-channel quantization simply involves running Algorithms 1, 2 with these modified parameters. Algorithms 4, 5 present the resulting algorithms.

Algorithm 4 Greedy Coordinate Descent (CD)

1: **Input:** T - coordinate descent steps, X - input data matrix, $\mathbf{w}$ - vector to be quantized, a - scale, b - bias, $\mathbf{q}_0$ - initial estimate
2: $\tilde{X} \leftarrow X\text{diag}(\mathbf{a}), \tilde{\mathbf{w}} = \text{diag}(\mathbf{a})^{-1}\mathbf{w}, \tilde{\mathbf{b}} = \text{diag}(\mathbf{a})\mathbf{b}$
3: Compute Hessian H as: $H \leftarrow \tilde{X}^T\tilde{X}$
4: Compute gradient $\mathbf{g}$ as: $\mathbf{g} \leftarrow 2H(\mathbf{q}_0 - (\tilde{\mathbf{w}} - \tilde{\mathbf{b}}))$
5: **for** $t \in [1:T]$ **do**
6:     Find the coordinate that leads to the largest reduction in loss

$$i^*, r^* = \operatorname*{arg\,min}_{i \in \{0,1,\dots d_{\text{in}}-1\}, r \in \{0,1,\dots 2^c-1\}} (r - \mathbf{q}_{t-1,i})^2 H_{i,i} + (r - \mathbf{q}_{t-1,i})\mathbf{g}_i$$

7:     Update gradient $\mathbf{g}$ as
$$\mathbf{g} \leftarrow \mathbf{g} + 2(r^* - \mathbf{q}_{t-1,i^*})H_{i^*,\cdot},$$
    where $H_{i^*,\cdot}$ is the i^* column of H
8:     Update $\mathbf{q}_{t-1}$ as
$$\mathbf{q}_t \leftarrow \mathbf{q}_{t-1} + (r^* - \mathbf{q}_{t-1,i^*})\mathbf{e}_{i^*},$$
    where $\mathbf{e}_{i^*}$ is the standard basis vector with 1 in i^* position and 0 everywhere else
9: **end for**

F   ADDITIONAL EXPERIMENTAL RESULTS

This section presents additional experimental results:

Algorithm 5 Block Coordinate Descent with Random Blocks (BCD)

1: **Input:** T - coordinate descent steps, k - block size, X - input data matrix, $\mathbf{w}$ - vector to be quantized, a - scale, b - bias, $\mathbf{q}_0$ - initial estimate
2: $\tilde{X} \leftarrow X \text{diag}(\mathbf{a}), \tilde{\mathbf{w}} = \text{diag}(\mathbf{a})^{-1}\mathbf{w}, \tilde{\mathbf{b}} = \text{diag}(\mathbf{a})\mathbf{b}$
3: Compute Hessian H as: $H \leftarrow \tilde{X}^T \tilde{X}$
4: Compute gradient $\mathbf{g}$ as: $\mathbf{g} \leftarrow 2H(\mathbf{q}_0 - (\tilde{\mathbf{w}} - \tilde{\mathbf{b}}))$
5: **for** $t \in [1:T]$ **do**
6:     Randomly partition the set $\{0, 1, \ldots d_{\text{in}} - 1\}$ into d_{in}/k blocks, each of size k
7:     Find the block that leads to the largest reduction in loss

$$i^*, r^* = \underset{\substack{i \in \{0,1,\ldots d_{\text{in}}/k-1\}, \\ r \in \{0,1,\ldots 2^c-1\}^k}}{\arg\min} (r - \mathbf{q}_{t-1,i})^T H_{i,i}(r - \mathbf{q}_{t-1,i}) + (r - \mathbf{q}_{t-1,i})^T \mathbf{g}_i,$$

   where $\mathbf{q}_{t-1,i}, H_{i,i}$ are the sub-vector, sub-matrix of $\mathbf{q}_{t-1}, H$ corresponding to block i.
8:     Update gradient $\mathbf{g}$ as
$$\mathbf{g} \leftarrow \mathbf{g} + 2H_{i^*,\cdot}(r^* - \mathbf{q}_{t-1,i^*}),$$
9:     Update $\mathbf{q}_{t-1}$ as
$$\mathbf{q}_{t-1,i^*} \leftarrow r^*, \quad \mathbf{q}_t \leftarrow \mathbf{q}_{t-1},$$
10: **end for**

---

1. In Appendix F.1, we present the effects of a larger block size and multiple epochs on BCD.

2. In Appendix F.2, we present a detailed breakdown of downstream evaluation results on various datasets.

3. In Appendix F.3, we present results for the setting where we quantize both attention and FFN layers.

4. In Appendix F.4, we present runtime numbers for CD and BCD algorithms

F.1 ADDITIONAL ABLATIONS FOR BCD

We investigate the effects of a large block size and multiple epochs on BCD, where each epoch corresponds to d_{in} iterations. Results for this experiment are presented in Table 10. For BCD with $k = 2$, additional epochs enhance performance. However, for BCD with $k = 4$, multiple epochs appear to lead to overfitting, indicating a need for stronger regularization.

Table 10: Table presents the perplexity evaluations BCD for INT2 quantization of FFN weights when run with a larger block size and multiple epochs.

Method	Epochs	Gemma-1 7B	Gemma-2 9B	Gemma-2 27B	PaLM2-Otter	PaLM2-Bison
w16a16		10.384	10.683	8.682	5.984	5.298
w2a16g128						
GPTQ	-	375.153	13.785	12.181	10.816	7.230
CD	1	75.55	13.709	11.966	9.917	7.123
BCD(k=2)	1	**68.732**	**13.662**	**11.873**	**9.822**	**7.094**
	2	67.766	13.665	11.888	9.760	**7.088**
	3	72.330	13.674	11.878	9.719	7.094
BCD(k=4)	1	68.785	**13.645**	**11.857**	**9.708**	7.099
	2	67.390	13.640	11.867	9.752	7.099
	3	67.590	13.664	11.869	9.749	7.099

F.2 DETAILED DOWNSTREAM EVALUATION RESULTS

Table 11: Table presents *downstream evaluation* (zero-shot) numbers of PaLM2-Gecko - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	PaLM2-Gecko									
		NatualQ.	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16	-	4.68	43.17	27.46	5.07	35.24	65.66	60.24	60.69	74.7	61.48
w3a16	OWC	2.55	47.57	9.81	1.87	29.69	56.73	64.8	53.28	69.59	60.3
	GPTQ	3.35	44.13	3.97	0.89	30.2	62.12	63.79	56.33	71.22	57.85
	CD	3.55	45.71	11.32	2.71	30.63	60.56	66.45	57.2	71.87	62.43
	BCD(k=2)	3.63	47.04	11.22	2.76	30.29	60.52	65.32	57.33	71.82	61.8
w3a16g128	OWC	3.68	55.38	12.5	2.61	31.66	60.14	66.12	53.19	71.71	58.88
	GPTQ	4.02	50.04	14.64	3.15	32.42	61.91	66.64	56.05	73.01	59.75
	CD	3.38	52.01	9.62	2.21	31.23	63.13	65.9	55.98	72.47	59.91
	BCD(k=2)	3.1	50.95	9.36	1.92	31.14	62.25	65.41	56.16	72.91	58.96
	OWC-CD	3.6	51.69	9.33	2.31	31.83	61.74	65.02	56.23	72.2	59.43
	OWC-CD + CD	3.82	50.39	9.5	1.77	32.51	62.25	66.33	56.91	71.27	60.06
	OWC-CD + BCD(k=2)	3.63	49.87	10.26	2.12	32.76	62.88	66.24	56.79	71.82	60.22
w4a16	OWC	4.02	46.96	10.63	2.66	33.19	61.99	66.7	59.26	73.67	61.72
	GPTQ	4.46	48.69	18.84	3.1	34.47	62.96	64.77	60.09	73.61	61.09
	CD	4.13	48.88	16.64	3.15	33.53	63.89	66.79	60.31	73.78	61.4
	BCD(k=2)	4.24	48.31	15.73	3.3	33.28	63.34	66.39	60.26	73.56	61.01
w4a16g128	OWC	4.99	46.1	20.62	4.28	34.73	64.48	67.83	59.91	74.32	61.25
	GPTQ	5.18	49.79	18.17	3.15	35.15	64.6	66.24	60.21	74.32	61.88
	CD	5.73	46.96	24.17	4.53	36.18	66.04	67.8	60.7	73.67	61.25
	BCD(k=2)	5.79	47.28	24.11	4.58	36.01	65.7	67.06	60.73	73.61	61.01
	OWC-CD	5.54	47.24	21.71	4.72	34.3	64.73	68.01	60.72	73.56	61.01
	OWC-CD + CD	5.62	47.6	24	4.68	35.49	66.16	67.06	60.78	74.1	61.48
	OWC-CD + BCD(k=2)	5.57	47.17	23.05	4.82	35.24	65.82	66.02	60.9	73.23	61.72

Table 12: Table presents *downstream evaluation* (zero-shot) numbers of PaLM2-Otter - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	PaLM2-Otter									
		NatualQ.	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16	-	12.85	65.27	58.34	8.46	51.79	76.09	81.8	79.3	79.6	72.22
w3a16	OWC	2.27	49.45	8.02	0.49	41.98	60.14	48.78	66.91	71.87	66.06
	GPTQ	9.09	64.53	46.38	7.19	49.83	73.99	81.96	76.87	78.89	70.09
	CD	10.72	64.01	48.03	6.59	50.77	76.6	81.01	75.77	77.97	70.09
	BCD(k=2)	10.55	64.31	47.25	6.05	50.85	76.43	81.41	75.91	78.45	70.24
w3a16g128	OWC	6.18	66.37	30.48	3.44	47.44	70.16	69.63	74.61	76.88	69.85
	GPTQ	10.17	66.53	49.29	7.73	51.37	75.93	82.35	77	79.11	72.14
	CD	7.17	68.73	49.42	5.61	50.26	76.18	82.39	76.79	78.13	71.98
	BCD(k=2)	6.68	68.18	48.39	5.27	50.26	75.93	81.41	76.84	79	72.61
	OWC-CD	8.98	68.37	48.33	5.91	50.51	75.46	81.35	76.83	78.18	72.06
	OWC-CD + CD	9.72	67.87	49.87	6.64	51.37	76.68	81.59	76.78	77.91	71.51
	OWC-CD + BCD(k=2)	9.94	68.26	49.91	6.74	50.85	76.22	81.68	76.99	78.89	71.74
w4a16	OWC	11.19	66.67	49.56	7.63	50	73.91	80	77.36	79.11	72.93
	GPTQ	12.27	66.65	48.72	8.46	51.71	75.84	82.02	78.2	80.09	73.32
	CD	12.52	66.85	53.16	7.53	52.3	76.43	81.28	78.3	79.6	72.61
	BCD(k=2)	12.33	67	53.45	7.63	51.96	75.97	80.92	78.47	80.47	72.06
w4a16g128	OWC	11.33	65.98	53.57	7.19	49.66	74.92	82.17	78.22	79.54	72.45
	GPTQ	11.5	65.81	56.36	7.68	51.71	76.52	82.08	78.86	79.27	73.16
	CD	11.72	66.85	57.63	8.61	51.19	76.6	82.51	78.89	79.49	73.32
	BCD(k=2)	11.66	66.73	57.5	8.56	51.19	76.3	82.29	78.88	79.27	73.32
	OWC-CD	12.27	66.28	58.21	8.56	51.62	76.85	82.32	78.85	79.49	72.61
	OWC-CD + CD	11.63	66.28	58.06	7.92	51.62	76.94	82.45	78.72	79.11	72.69
	OWC-CD + BCD(k=2)	11.72	65.96	58.29	8.02	51.79	76.77	82.17	78.8	79.49	72.69

Table 13: Table presents *downstream evaluation* (zero-shot) numbers of PaLM2-Bison - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	PaLM2-Bison									
		NatualQ.	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16	-	21.36	72.92	70	12.89	55.38	81.27	87.86	82.72	82.97	78.14
w3a16	OWC	15.87	73.01	58.86	10.58	52.47	76.43	86.91	79.76	81.01	76.09
	GPTQ	17.31	71.25	65.53	11.56	54.44	79.25	87.22	80.78	81.61	76.87
	CD	17.84	71.24	64.76	12.8	54.44	79.17	87.58	80.79	82.1	76.16
	BCD(k=2)	17.81	71.3	64.29	12.06	53.5	79.08	87.65	80.91	82.21	77.35
w3a16g128	OWC	15.98	71.28	68.02	10.88	53.58	79.55	86.73	80.9	81.61	76.72
	GPTQ	18.95	71.49	69.67	13.78	53.24	79.84	86.79	81.05	82.05	76.95
	CD	18.31	71.81	68.56	13.14	53.41	79.8	87.55	81.31	82.43	77.66
	BCD(k=2)	18.53	71.55	67.62	12.99	53.58	79.59	87.49	81.14	82.81	76.48
	OWC-CD	17.26	71.79	67.53	12.35	54.69	80.85	85.72	81.02	81.88	77.98
	OWC-CD + CD	18.75	72.05	68.35	13.19	54.1	80.18	86.36	80.86	82.48	77.51
	OWC-CD + BCD(k=2)	19.36	71.47	68.45	12.99	53.58	80.47	86.02	81.15	82.26	76.72
w4a16	OWC	20	72.51	69.34	12.5	54.61	80.39	87.06	81.5	82.05	77.19
	GPTQ	21.25	72.39	70.6	12.4	55.2	80.64	87.58	81.98	82.26	77.58
	CD	21.5	71.57	70.04	12.8	55.29	80.56	88.07	81.78	82.59	77.03
	BCD(k=2)	21.16	71.92	70.01	12.7	55.63	81.19	87.77	81.82	82.81	77.43
w4a16g128	OWC	21.22	73.06	70.07	13.44	55.8	80.47	87.77	82.08	82.64	77.51
	GPTQ	20.72	73.17	70.12	12.99	55.38	80.89	87.55	82.14	82.59	77.35
	CD	21.8	73.37	69.06	12.6	54.78	80.72	87.25	82.16	83.19	78.22
	BCD(k=2)	21.5	73.06	69.34	12.8	55.29	80.98	87.31	82.14	82.54	77.11
	OWC-CD	21.36	73.85	70.07	13.73	55.12	81.23	87.71	82.27	82.59	77.27
	OWC-CD + CD	21.41	73.32	71.46	12.89	54.18	81.4	87.28	82.17	82.37	77.74
	OWC-CD + BCD(k=2)	21.19	73.24	71.64	12.75	55.03	81.52	87.28	82.06	82.64	77.66

Table 14: Table presents *downstream evaluation* (zero-shot) numbers of Gemma-1 7B - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	Gemma-1 7B									
		NaturalQ	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16		15.04	71.94	62.38	13.04	43.69	65.53	80.43	78.55	80.79	72.14
w3l6	OWC	0.03	2.87	0.15	0	30.55	38.8	63.09	29	52.61	48.86
	GPTQ	2.24	58.68	14.35	3.05	35.15	53.16	63.76	53.84	64.58	59.91
	CD	6.04	68.77	32.22	4.28	41.04	62.37	76.51	68.95	74.76	67.01
	BCD(k=2)	6.76	69.03	33.32	3.74	40.7	62.21	76.91	69.1	75.24	68.11
w3a16g128	OWC	6.51	71.04	30.86	5.46	38.14	60.1	70.7	64.51	75.3	63.85
	GPTQ	10.03	71.66	42.25	7.82	41.64	64.06	80.83	72.37	78.18	69.38
	CD	10.08	71.94	46.39	8.46	40.7	62.75	80.43	73.88	78.56	67.64
	BCD(k=2)	10.78	71.99	46.65	8.66	42.32	63.01	81.25	74.17	78.18	69.46
	OWC-CD	9.7	71.62	41.44	8.27	41.47	64.44	79.94	72.19	77.53	67.32
	OWC-CD + CD	10.66	71.78	46.73	8.02	42.41	64.73	80.46	74.29	78.94	67.64
	OWC-CD + BCD(k=2)	10.69	71.84	47.05	8.76	42.41	65.36	80.03	74.47	79.49	68.9
w4a16	OWC	7.09	63.51	44.98	7.19	41.38	59.34	77.06	67.29	73.29	63.85
	GPTQ	10.66	70.95	52.63	9.55	44.11	64.56	79.39	75.9	79.16	70.56
	CD	12.71	70.41	57.39	11.27	43.69	65.11	79.66	77.98	79.98	70.17
	BCD(k=2)	12.44	70.5	57.55	11.96	45.14	65.4	79.79	76.66	79.54	71.03
w4a16g128	OWC	13.55	71.61	56.09	12.8	42.49	63.85	80.92	76.77	79.22	70.32
	GPTQ	13.88	71.94	59.45	14.12	43.52	66.12	81.96	77.54	79.98	71.11
	CD	15.26	71.73	59.81	13.24	45.05	65.45	81.25	77.52	80.58	70.88
	BCD(k=2)	15.54	71.94	59.83	13.24	43.69	64.6	80.89	77.68	81.23	71.43
	OWC-CD	14.43	72.08	58.69	12.55	43.52	64.94	80.46	77.46	79.49	70.64
	OWC-CD + CD	14.82	72.32	59.98	13.63	45.05	65.82	80.43	77.46	80.96	71.43
	OWC-CD + BCD(k=2)	14.93	72.39	59.49	12.94	44.45	66.08	80.21	77.6	80.03	70.8

Table 15: Table presents *downstream evaluation* (zero-shot) numbers of Gemma-2 9B - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	Gemma-2 9B									
		NaturalQ	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16		26.76	72.06	76.83	21.7	58.96	77.57	83.33	77.31	81.12	67.96
w316	OWC	21.02	74.18	69.76	18.41	56.23	76.52	84.37	75.24	80.79	67.88
	GPTQ	21.22	74	69.99	18.06	57	77.19	82.35	74.96	80.69	66.46
	CD	22.24	73.41	70.67	19.59	56.91	77.74	84.13	75.27	79.82	66.61
	BCD(k=2)	21.77	73.33	71	18.8	57.08	77.69	83.18	75.04	80.03	67.01
w3a16g128	OWC	23.1	73.42	71.79	19.29	56.31	76.6	83.94	75.28	80.74	67.25
	GPTQ	22.33	72.77	71.68	19.69	56.66	77.44	83.46	75.19	80.74	67.64
	CD	22.8	71.94	72.24	19.39	56.74	77.36	84.13	75.27	80.14	66.38
	BCD(k=2)	23.02	72.3	71.99	19.29	56.57	77.06	84.37	75.36	80.3	66.46
	OWC-CD	22.55	72.69	72.13	19.19	55.46	76.85	82.81	75.36	80.79	66.93
	OWC-CD + CD	22.99	72.42	72.28	19.09	56.91	77.36	82.75	75.48	80.52	67.72
	OWC-CD + BCD(k=2)	23.27	72.39	72.23	18.9	57	77.31	83.27	75.49	80.41	67.32
w4a16	OWC	25.48	73.21	74.93	20.32	58.45	76.81	83.94	76.58	80.69	68.11
	GPTQ	25.29	72.9	74.65	21.16	58.7	77.27	83.55	76.6	81.23	68.98
	CD	25.57	73.03	75.42	20.92	58.36	77.61	83.79	76.75	80.41	68.67
	BCD(k=2)	25.6	72.86	75.35	21.06	58.62	77.4	83.73	76.74	80.69	68.59
w4a16g128	OWC	26.26	73.33	75.73	21.56	58.7	77.4	83.33	76.76	80.85	66.85
	GPTQ	26.12	72.53	75.75	21.21	58.53	77.65	83.06	76.72	81.28	66.61
	CD	26.23	72.57	75.83	20.96	58.28	77.53	83.15	76.83	81.12	67.4
	BCD(k=2)	26.4	72.62	75.94	21.11	58.36	77.4	83.09	76.72	80.85	67.48
	OWC-CD	26.15	73.46	75.88	21.56	59.3	77.74	82.81	76.72	80.96	67.72
	OWC-CD + CD	26.15	72.7	75.98	21.41	58.62	77.78	82.94	76.86	81.07	67.48
	OWC-CD + BCD(k=2)	26.32	72.75	76.13	21.21	59.13	77.48	83	76.92	81.01	67.48

Table 16: Table presents *downstream evaluation* (zero-shot) numbers of Gemma-2 27B - for GPTQ, CD, BCD for INT3, INT4 quantization of FFN weights.

Config	Method	Gemma-2 27B									
		NaturalQ	SQuAD	TriviaQA	WebQ	ARC-c	ARC-e	BoolQ	HellaSwag	PIQA	WinoGrande
w16a16		30.42	75.04	81.5	23.33	60.49	78.96	83.18	82.24	84.6	75.69
w316	OWC	23.3	73.28	73.2	19.39	56.66	77.53	81.01	79.82	83.24	73.01
	GPTQ	26.09	75.08	76.62	21.85	57.51	78.96	77.4	80.57	83.73	74.98
	CD	26.51	75.57	77.21	21.06	59.13	79.76	78.29	80.1	83.95	74.66
	BCD(k=2)	26.7	75.67	77.34	21.65	58.45	79.34	78.47	79.93	83.41	76.56
w3a16g128	OWC	26.7	75.95	78.61	21.8	58.45	79.63	83.55	80.49	82.75	76.01
	GPTQ	27.48	75.97	78.72	22.88	59.56	80.05	80.28	81.03	83.68	74.35
	CD	27.98	76.15	78.59	22.54	59.73	79.88	81.77	80.99	84.11	76.09
	BCD(k=2)	27.78	75.99	78.62	22.49	59.56	80.01	81.99	81.08	84.11	76.56
	OWC-CD	26.87	76.03	79	22.05	58.96	80.18	81.28	80.94	83.79	76.64
	OWC-CD + CD	27.87	76.36	79.62	22.34	59.3	80.05	81.59	80.97	83.79	76.72
	OWC-CD + BCD(k=2)	27.7	76.45	79.38	22.44	59.73	80.05	81.83	80.98	83.57	76.56
w4a16	OWC	29	75.51	80.05	21.95	59.39	79.04	81.13	81.93	84.39	75.53
	GPTQ	29.5	75.7	80.41	22.88	59.47	78.7	81.62	81.91	84.33	75.85
	CD	29.36	75.23	80.23	22.59	59.9	79.67	81.53	81.84	84.49	75.77
	BCD(k=2)	29.42	75.34	80.31	22.54	59.3	79.46	81.83	81.72	84.44	75.93
w4a16g128	OWC	29.25	75.41	80.91	22.64	59.98	79.46	83.76	82.14	84.22	76.01
	GPTQ	29.53	75.61	80.85	22.49	60.41	79.59	83.61	82.14	84.66	75.37
	CD	29.58	75.38	81.05	23.13	59.98	79.42	83.73	82.08	84.44	75.93
	BCD(k=2)	29.61	75.44	80.91	22.93	60.32	79.71	83.85	82.06	84.44	75.53
	OWC-CD	29.11	75.93	80.85	22.69	60.75	79.67	83.33	82.2	84.87	75.69
	OWC-CD + CD	29.36	75.66	80.96	22.98	59.9	79.59	83.82	82.05	85.15	75.77
	OWC-CD + BCD(k=2)	29.34	75.41	80.86	22.93	59.9	79.84	83.94	82.14	84.93	75.37

F.3   ATTENTION + FFN QUANTIZATION

Before presenting the results for quantization of both attention and FFN layers, we first explain why quantizing the attention weights does not yield inference latency gains.

F.3.1   ATTENTION QUANTIZATION DOESN'T YIELD LATENCY GAINS

In Table 17, we present the end-to-end prefix and decode latency for Gemma-2 27B with three different prefix lengths. The latencies are obtained by running Gemma-2 27B on 4 TPUv5 chips with a per TPU batch size of 4 and no model parallelism.

Prefix phase. During the prefix phase, neither FFN nor attention quantization yielded significant latency improvements, likely due to the compute-bound nature of the prefix.

Decode phase. In the decode phase, quantizing attention weights from 16 bits to 8 bits provided marginal gains, as attention compute is primarily memory-bound by the KV cache size, which typically exceeds attention weight size for moderate-to-large context lengths. Further reduction to 4-bit quantization offered negligible latency improvement while incurring a non-trivial drop in quality (Table 18 and Table 2), thus questioning the utility of attention weight quantization. Conversely, FFN layers, processing only a single token activation during decoding, are memory-bound by the significantly larger FFN weights (9x the size of attention weights in Gemma-2 27B). Consequently, FFN weight quantization effectively reduces memory transfers and improves latency. We observed a $32\% - 35\%$ latency reduction when quantizing from 16 bits to 8 bits, with an additional 10% reduction when using 4-bit quantization.

These results clearly highlight that quantization of attention weights doesn't yield any inference latency gains.

Table 17: Table presents the prefix and decode time inference latency of Gemma-2 27B with three different prefix lengths. In the Attention-only setting, only the attention parameters are quantized and rest of the model is in 16 bits. Similarly, in the FFN-only setting, only the FFN parameters are quantized.

Quantization Setting	Prefix Length	Config	Prefix time (ms)	Decode per step time (ms)
Attention-only	1024	w16a16	299.958	26.178
		w8a16	302.199	25.710
		w4a16	301.899	25.595
	2048	w16a16	616.460	26.532
		w8a16	616.080	26.117
		w4a16	615.601	25.964
	4096	w16a16	1296.000	27.254
		w8a16	1290.000	26.685
		w4a16	1286.000	26.653
FFN-only	1024	w16a16	299.958	26.178
		w8a16	292.630	17.410
		w4a16	284.680	15.635
	2048	w16a16	616.460	26.532
		w8a16	604.941	17.868
		w4a16	602.306	16.006
	4096	w16a16	1296.000	27.254
		w8a16	1276.000	18.521
		w4a16	1273.000	16.626

F.3.2 RESULTS FOR ATTENTION + FFN QUANTIZATION

We now perform FFN + Attention weight quantization, results for which are presented in Table 18. We use the same experimental setting as the one described in Section 4. In our experiments we noticed that the inputs to the attention layer are often aligned in a handful of directions. Consequently, performing quantization using such a data leads to a huge drop in performance, as the algorithms would primarily focus on a few directions and ignore the rest. To mitigate this, we clip the largest eigenvalues of the Hessian to ensure a more balanced Hessian. This technique, reminiscent of the weight clipping in OmniQuant (Shao et al., 2023), improves the performance of both GPTQ and CDQuant[1]. For instance, for PaLM2-Gecko, the perplexity for w3a16-GPTQ improves from 34.872 to 24.054 with clipping, and for w4a16-GPTQ, it improves from 10.966 to 10.005. Table 18 presents the results from this experiment, where we run all the algorithms on the clipped Hessian. We once again notice that in almost all the settings, our coordinate descent algorithms outperform GPTQ. For instance, we see $5 - 10\%$ improvement in perplexity for 3-bit per-channel quantization of Gemma-2, and PaLM2 Gecko models.

---

[1]One could also rely on existing techniques such as AWQ and SmoothQuant to reduce the effect of outliers. But in our experiments we noticed that both AWQ and SmoothQuant performed poorly compared to the simple eigenvalue clipping technique.

Table 18: Table presents the perplexity evaluations for GPTQ, CD, BCD for INT3, INT4 quantization of both FFN and attention weights.

Config	Method	Gemma-1 7B	Gemma-2 9B	Gemma-2 27B	PaLM2 Gecko	PaLM2 Otter	PaLM2 Bison
w16a16	-	10.348	10.683	8.682	7.948	5.984	5.298
w3a16	OWC	1.89e6	12.558	15.736	41.751	54.499	6.446
	GPTQ	91.586	11.849	11.423	24.054	**11.384**	5.801
	CD	36.102	11.808	10.941	19.692	11.542	5.770
	BCD(k=2)	**32.850**	**11.784**	**10.926**	**19.312**	11.392	**5.762**
w3a16g128	OWC	33.710	11.792	10.486	20.301	9.785	5.973
	GPTQ	20.045	11.491	9.766	15.042	7.501	5.698
	CD	15.850	11.500	9.689	14.757	7.454	5.679
	BCD(k=2)	15.466	11.487	9.657	14.691	**7.438**	5.673
	OWC-CD	18.599	11.583	9.820	16.268	7.617	5.746
	OWC-CD + CD	15.792	11.465	**9.559**	14.285	7.466	5.675
	OWC-CD + BCD(k=2)	**15.777**	**11.463**	9.564	**14.242**	7.458	**5.670**
w4a16	OWC	40.563	11.100	9.706	10.683	7.194	5.508
	GPTQ	15.805	11.021	9.217	10.005	6.645	5.425
	CD	14.379	**10.979**	9.177	9.991	6.627	5.415
	BCD(k=2)	**14.056**	10.982	**9.167**	**9.965**	**6.621**	**5.413**
w4a16g128	OWC	12.222	10.919	9.027	9.402	6.415	5.420
	GPTQ	11.548	10.863	8.888	9.160	6.241	5.381
	CD	11.306	10.856	8.890	9.124	6.226	5.377
	BCD(k=2)	11.105	**10.853**	8.892	9.120	**6.225**	5.376
	OWC-CD	11.342	10.876	8.924	9.241	6.261	5.387
	OWC-CD + CD	11.149	10.863	8.873	9.094	6.244	5.375
	OWC-CD + BCD(k=2)	**11.140**	10.866	**8.873**	**9.093**	6.242	**5.374**

F.4 RUNTIME ANALYSIS

In Tables 19 20, we present the quantization runtime of GPTQ, CD and BCD on Gemma models using H100s (in one setting we used 1 H100 and in another we used 8H100s). In particular, in Table 19, we present runtime for quantizing all the attention and FFN layers (which includes FFN1, FFN1-gate, FFN2) in the model. Table 20 presents a more detailed breakdown; we present the per-layer runtime for quantizing FFN1 and FFN2 layers.

Runtime on 8 **H100's.** With 8 H100s, CD is as fast as GPTQ for quantizing attention weights, whereas BCD is $2\times$ slower. However, for FFN1 (FFN2) quantization, CD is $5\times$ ($2\times$) slower than GPTQ, whereas BCD is an order of magnitude slower than GPTQ. For quantization of the entire model, CD is $2\times$ slower than GPTQ (because quantizing FFN2 takes up most of the time). We attribute the slowness of CD and BCD to the numerous scatters and gathers involved in finding the most optimal coodrinate/block of coordinate to update, and then eventually updating it. Since ML accelerators are slow with gather and scatter operations, we are bound by the time it takes to do them. Performing these operations on the CPU should help speed up CD and BCD.

Runtime on 1 **H100.** With a single H100, GPTQ is 2x-3.8x faster than CD for the smaller, attention weights, and is an order of magnitude faster than BCD. For the larger, FFN weights, GPTQ is an order of magnitude faster than CD, and in most cases is two orders of magnitude than BCD. As stated previously, both CD and BCD are bound by the time it takes to do gathers and scatters.

Speeding up BCD. To algorithmically speed up BCD, we propose to use CD for FFN2 quantization, and use BCD for the rest of the layers. We find that BCD spends most of its time quantizing the FFN2 weight matrix (as can be seen in Table 20) where the quantization axis is of size d_{hidden}. In most cases, the time it takes to FFN2 is 10x the time it takes to quantize FFN1. Thus, to speed up BCD, we quantize FFN2 with CD, and FFN1 and FFN1-gate with BCD (where the quantization axis is of size d_{model}. Results for this setting can be found in Table 21. It can be seen that quantizing FFN2 with CD leads to negligible to no drop in performance especially for the larger, and better Gemma-2 9B. In fact, it improves the performance of BCD for w3a16g128. With this setup, BCD's runtime is reduced significantly and is comparable to that of CD.

Speeding up CD. We find that CD converges to an optimal solution significantly before d_{in} iterations. Based on this finding, we run CD for lesser number of iterations. In Table 22, one can see that there is negligible quality drop for CD, and even with $d_{in}/8$ iterations, CD outperforms GPTQ. Also, one can see that in Figure 1, CD's activation reconstruction error converges in $d_{in}/8$ iterations across all settings. With lesser number of iterations, CD's runtime can be made faster than/comparable to that of GPTQ.

Table 19: Table presents the per-channel quantization runtime (in minutes) of GPTQ, CD, BCD (where each run is for d_{in} iterations). FFN includes the combined runtime of quantizing FFN1, FFN1-gate and FFN2 layers.

Config	Method	8 H100s						1 H100					
		Gemma-1 7B		Gemma-2 9B		Gemma-2 27B		Gemma-1 7B		Gemma-2 9B		Gemma-2 27B	
		FFN (mins.)	Attn. (mins.)	FFN (mins.)	Attn. (mins.)	FFN (mins.)	Attn. (mins.)	FFN (mins.)	Attn. (mins.)	FFN (mins.)	Attn. (mins.)	FFN (mins.)	Attn. (mins.)
w3a16	GPTQ	1.68	0.67	1.15	1.05	7.98	1.18	2.13	0.65	1.36	1.04	10.31	1.32
	CD	3.03	0.19	2	0.31	16.55	0.51	22.3	1.2	13.31	1.87	122.35	3.2
	BCD(k=2)	8.52	0.71	5.95	1.18	66.97	2.11	88.14	3.85	61.5	7.24	541.03	13.62
w4a16	GPTQ	1.69	0.77	1.15	1.06	7.95	1.18	2.1	0.63	1.36	0.98	10.16	1.12
	CD	3.9	0.22	2.53	0.36	21.16	0.64	29.27	1.47	17.66	2.25	163.78	4.27
	BCD(k=2)	26.2	1.76	18.51	2.66	162.43	4.64	218.25	12.89	163.64	20.12	1296.36	36.68

Table 20: Table presents the *per-layer*, per-channel quantization runtime (in seconds) of GPTQ, CD, BCD (where each run is for d_{in} iterations) for the FFN layer. Note that FFN1 and FFN1-Gate have the exact same runtimes for all compared methods, hence we report only FFN1's runtime.

Config	Method	8 H100s						1 H100					
		Gemma-1 7B		Gemma-2 9B		Gemma-2 27B		Gemma-1 7B		Gemma-2 9B		Gemma-2 27B	
		FFN1 (sec.)	FFN2 (sec.)	FFN1 (sec.)	FFN2 (sec.)	FFN1 (sec.)	FFN2 (sec.)	FFN1 (sec.)	FFN2. (sec.)	FFN1 (sec.)	FFN2 (sec.)	FFN1 (sec.)	FFN2 (sec.)
w3a16	GPTQ	0.34	2.93	0.35	0.94	0.39	9.61	0.43	3.69	0.39	1.16	0.81	11.64
	CD	0.46	5.57	0.41	2.04	1.6	18.38	3.34	41.11	2.86	13.31	12.24	135.11
	BCD(k=2)	1.4	15.46	1.27	5.96	7.86	71.67	12.55	163.74	11.95	63.95	57.38	590.89
w4a16	GPTQ	0.35	2.93	0.36	0.94	0.4	9.58	0.42	3.68	0.39	1.14	0.81	11.63
	CD	0.53	7.28	0.46	2.71	2.15	23.31	3.94	54.85	3.22	18.81	17.24	179.15
	BCD(k=2)	4.54	47.07	3.71	19.02	18.97	173.92	35.95	395.78	30.34	173.09	151.36	1388.19

Table 21: Table presents the perplexity evaluations for INT3 quantization with BCD wherein the FFN2 may be quantized either with CD or BCD, while rest of the FFN parameters are quantized with BCD.

Config	Method	Gemma-1 7B	Gemma-2 9B
w16a16		10.384	10.683
w3a16	CD, FFN2	19.709	11.288
	BCD(k=2), FFN2	18.552	11.284
w3a16g128	CD, FFN2	13.512	11.179
	BCD(k=2), FFN2	13.501	11.180

Table 22: Table presents the perplexity evaluations for INT3 quantization with CD, wherein instead of running CD for d_{in} iterations, we run it for $d_{in}/2$, $d_{in}/4$, and $d_{in}/8$ iterations.

Config	Method	Epochs	Gemma-1 7B	Gemma-2 9B
	w16a16		10.384	10.683
w3a16	GPTQ	-	48.157	11.382
	CD	1	19.614	11.301
		1/2	19.614	11.301
		1/4	19.621	11.301
		1/8	19.597	11.305
w3a16g128	GPTQ	-	15.561	11.193
	CD	1	13.496	11.182
		1/2	13.488	11.189
		1/4	13.480	11.189
		1/8	13.560	11.188

Figure 1: The Figure presents the variation of the L2 activation reconstruction error with iterations for for Gemma-2 9B with CD. One could see that across settings, CD converges in $d_{\text{in}}/8$ iterations