Constrained-CNN losses for
weakly supervised segmentation

Hoel Kervadec
ÉTS Montréal
`hoel.kervadec.1@etsmtl.net`

Jose Dolz
ÉTS Montréal

Meng Tang
University of Waterloo
Department of computer science

Éric Granger
ÉTS Montréal

Yuri Boykov
University of Waterloo
Department of computer science

Ismail Ben Ayed
ÉTS Montréal

Abstract

Weak supervision, e.g., in the form of partial labels or image tags, is currently attracting significant attention in CNN segmentation as it can mitigate the lack of full and laborious pixel/voxel annotations. Enforcing high-order (global) inequality constraints on the network output, for instance, on the size of the target region, can leverage unlabeled data, guiding training with domain-specific knowledge. Inequality constraints are very flexible because they do not assume exact prior knowledge. However, constrained Lagrangian dual optimization has been largely avoided in deep networks, mainly for computational tractability reasons. To the best of our knowledge, the method of Pathak et al. [17] is the only prior work that addresses deep CNNs with linear constraints in weakly supervised segmentation. It uses the constraints to synthesize fully-labeled training masks (proposals) from weak labels, mimicking full supervision and facilitating dual optimization.

We propose to introduce a differentiable term, which enforces inequality constraints directly in the loss function, avoiding expensive Lagrangian dual iterates and proposal generation. From constrained-optimization perspective, our simple approach is not optimal as there is no guarantee that the constraints are satisfied. However, surprisingly, it yields *substantially* better results than the Lagrangian-based constrained CNNs in [17], while reducing the computational demand for training. In the context of cardiac images, we reached a segmentation performance close to full supervision using a fraction of the full ground-truth labels (0.1%). While our experiments focused on basic linear constraints such as the target-region size and image tags, our framework can be easily extended to other non-linear constraints, e.g., invariant shape moments [5] or other region statistics [8]. Therefore, it has the potential to close the gap between weakly and fully supervised learning in semantic medical image segmentation. Our code is publicly available.

1   Introduction

In the recent years, deep convolutional neural networks (CNNs) have been dominating semantic segmentation problems, both in computer vision and medical imaging, achieving ground-breaking performances when full-supervision is available [10, 11]. In semantic segmentation, full supervision requires laborious pixel/voxel annotations, which may not be available in a breadth of applications, more so when dealing with volumetric data. Therefore, weak supervision with partial labels, for instance, bounding boxes [19], points [1], scribbles [22, 21, 9], or image tags [17, 14], is attracting significant research attention. Imposing prior knowledge on the the network's output in the form

1st Conference on Medical Imaging with Deep Learning (MIDL 2018), Amsterdam, The Netherlands.

of unsupervised loss terms is a well-established approach in machine learning [23, 3]. Such priors can be viewed as regularization terms that leverage unlabeled data, embedding domain-specific knowledge. For instance, the recent studies in [22, 21] showed that direct regularization losses, e.g., dense conditional random field (CRF) or pairwise clustering, can yield outstanding results in weakly supervised segmentation, reaching almost full-supervision performances in natural image segmentation; see the results in [22]. Surprisingly, such a principled direct-loss approach is not common in weakly supervised segmentation. In fact, most of the existing techniques synthesize fully-labeled training masks (proposals) from the available partial labels, mimicking full supervision [19, 14, 9, 6]. Typically, such proposal-based techniques iterate two steps: CNN learning and proposal generation facilitated by dense CRFs and fast mean-field inference [7], which are now the de-facto choice for pairwise regularization in semantic segmentation algorithms.

Our purpose here is to embed high-order (global) inequality constraints on the network output directly in the loss function, so as to guide learning. For instance, assume that we have some prior knowledge on the size (or volume) of the target region, e.g., in the form of lower and upper bounds on size, a common scenario in medical image segmentation [13, 4]. Let $I : \Omega \subset \mathbb{R}^{2,3} \to \mathbb{R}$ denotes a given training image, with Ω a discrete image domain and $|\Omega|$ the number of pixels/voxels in the image. $\Omega_L \subseteq \Omega$ is a weak (partial) ground-truth segmentation of the image, taking the form of a partial annotation of the target region, e.g., a few points (see Fig. 2). In this case, one can optimize a cross-entropy loss subject to inequality constraints on the network outputs [17]:

$$\min_{\boldsymbol{\theta}} \; \mathcal{H}(S) \quad \text{s.t} \quad a \leq \sum_{p \in \Omega} S_p \leq b \tag{1}$$

where $S = (S_1, \ldots, S_{|\Omega|}) \in [0,1]^{|\Omega|}$ is a vector of softmax probabilities[1] generated by the network at each pixel p and $\mathcal{H}(S) = -\sum_{p \in \Omega_L} Y_p \log(S_p)$, where Y_p denotes one-hot encoding of ground-truth of the labeled pixels. Priors a and b denote the given upper and lower bounds on the size (or cardinality) of the target region. Inequality constraints of the form in (1) are very flexible because they do not assume exact knowledge of the target size, unlike [25, 2]. Also, multiple instance learning (MIL) constraints [17], which enforce image-tag priors, can be handled by constrained model (1). Image tags are a form of weak supervision, which enforce the constraints that a target region is present or absent in a given training image [17]. They can be viewed as particular cases of the inequality constraints in (1). For instance, a suppression constraint, which takes the form $\sum_{p \in \Omega} S_p \leq 0$, enforces that the target region is not in the image. $\sum_{p \in \Omega} S_p > 1$ enforces the presence of the region.

Even though constraints of the form (1) are linear (and hence convex) with respect to the network outputs, constrained problem (1) is very challenging due to the non-convexity of CNNs. One possibility would be to minimize the corresponding Lagrangian dual. However, as pointed out in [17, 12], this is computationally intractable for semantic segmentation networks involving millions of parameters; one has to optimize a CNN within each dual iteration. In fact, constrained optimization has been largely avoided in deep networks [20], even thought some Lagrangian techniques were applied to neural networks a long time before the deep learning era [24, 18]. These constrained optimization techniques are not applicable to deep CNNs as they solve large linear systems of equations. The numerical solvers underlying these constrained techniques would have to deal with matrices of very large dimensions in the case of deep networks [12].

To the best of our knowledge, the method of Pathak et al. [17] is the only prior work that addresses constrained deep CNNs in weakly supervised segmentation. It uses the constraints to synthesize fully-labeled training masks (proposals) from the available partial labels, mimicking full supervision, which avoids intractable dual optimization of the constraints when minimizing the loss function. The main idea of [17] is to model the proposals via a latent distribution. Then, they minimize a KL divergence, encouraging the softmax output of the CNN to match the latent distribution as closely as possible. Therefore, they impose constraints on the latent distribution rather than on the network output, which facilitates Lagrangian dual optimization. This decouples stochastic gradient descent learning of the network parameters and constrained optimization: The authors of [17] alternate between optimizing w.r.t the latent distribution, which corresponds to proposal generation subject to the constraints[2], and standard stochastic gradient descent for optimizing w.r.t the network parameters.

---

[1]The softmax probabilities take the form: $S_p(\boldsymbol{\theta}, I) \propto \exp f_p(\boldsymbol{\theta}, I)$, where $f_p(\boldsymbol{\theta}, I)$ is a real scalar function representing the output of the network for pixel p. For notation simplicity, we omit the dependence of S_p on $\boldsymbol{\theta}$ and I as this does not result in any ambiguity in the presentation.

[2]This sub-problem is convex when the constraints are convex.

We propose to introduce a differentiable term, which enforces inequality constraints (1) directly in the loss function, avoiding expensive Lagrangian dual iterates and proposal generation. From constrained optimization perspective, our simple approach is not optimal as there is no guarantee that the constraints are satisfied. However, surprisingly, it yields *substantially* better results than the Lagrangian-based constrained CNNs in [17], while reducing the computational demand for training. In the context of cardiac image segmentation, we reached a performance close to full supervision while using a fraction of the full ground-truth labels (0.1%). Our framework can be easily extended to non-linear inequality constraints, e.g., invariant shape moments [5] or other region statistics [8]. Therefore, it has the potential to close the gap between weakly and fully supervised learning in semantic medical image segmentation. Our code is publicly available [3].

2 Proposed loss function

We propose the following loss for weakly supervised segmentation:

$$-\sum_{p \in \Omega_L} Y_p \log(S_p) + \lambda \mathcal{C}(V_S), \tag{2}$$

where $V_S = \sum_{p \in \Omega} S_p$, λ weights the importance of the constraints and function $\mathcal{C}$ given by (See the illustration in Fig. 1):

$$\mathcal{C}(V_S) = \begin{cases} (V_S - a)^2, & \text{if } V_S \leq a \\ (V_S - b)^2, & \text{if } V_S \geq b \\ 0, & \text{otherwise} \end{cases} \tag{3}$$

Now, our differentiable term $\mathcal{C}$ accommodates standard stochastic gradient descent. During back-propagation, the term of gradient-descent update corresponding to $\mathcal{C}$ can be written as follows:

$$-\frac{\partial \mathcal{C}(V_S)}{\partial \boldsymbol{\theta}} \propto \begin{cases} (a - V_S) \frac{\partial S_p}{\partial \boldsymbol{\theta}}, & \text{if } V_S < a \\ (b - V_S) \frac{\partial S_p}{\partial \boldsymbol{\theta}}, & \text{if } V_S > b \\ 0, & \text{otherwise} \end{cases} \tag{4}$$

where $\frac{\partial S_p}{\partial \boldsymbol{\theta}}$ denotes the standard derivative of the softmax outputs of the network. The gradient in (4) has a clear interpretation. During back-propagation, when the current constraints are satisfied, i.e., $a \leq V_S \leq b$, observe that $\frac{\partial \mathcal{C}(V_S)}{\partial \boldsymbol{\theta}} = 0$. Therefore, in this case, the gradient stemming from our term has no effect on the current update of the network parameters. Now, suppose without loss of generality that the current set of parameters $\boldsymbol{\theta}$ corresponds to $V_S < a$, which means the current target region is smaller than its lower bound a. In this case of constraint violation, term $(a - V_S)$ is positive and, therefore, the first line of (4) performs a gradient *ascent* step on softmax outputs, increasing S_p. This makes sense because it increases the size of the current region, V_S, so as to satisfy the constraint. The case $V_S > b$ has a similar interpretation.

Figure 1: Illustration of our differentiable loss for imposing soft size constraints on the target region.

The next section details the dataset, the weak annotations and our implementation. Then, we report comprehensive evaluations of the effect of our constrained-CNN losses on segmentation performance. We also report comparisons to the Lagrangian-based constrained CNN method in [17] and to the fully supervised setting.

---

[3]The code can be found at https://github.com/LIVIAETS/SizeLoss_WSS

3 Experiments

3.1 Dataset

Our experiments focused on left ventricular endocardium segmentation. We used the training set from the publicly available data of the 2017 ACDC Challenge[4]. This set consists of 100 cine magnetic resonance (MR) exams covering well defined pathologies: dilated cardiomyopathy, hypertrophic cardiomyopathy, myocardial infarction with altered left ventricular ejection fraction and abnormal right ventricle. It also included normal subjects. The exams were acquired in breath-hold with a retrospective or prospective gating and a SSFP sequence in 2-chambers, 4-chambers and in short-axis orientations. A series of short-axis slices cover the LV from the base to the apex, with a thickness of 5 to 8 mm and an inter-slice gap of 5 mm. The spatial resolution goes from 0.83 to 1.75 mm^2/pixel.

For all the experiments, we employed the same 75 exams for training and the remaining 25 for validation. To increase the variability of the data, we augmented the dataset by randomly rotating, flipping, mirroring and scaling the images.

3.2 Weakly-annotated labels

To generate the weak labels, we employed binary erosion on the fully annotations with a kernel of size 10×10. If the resulted label disappeared, we repeated the operation with a smaller kernel (i.e., 7×7) until we get a small contour. Thus, the total number of annotated pixels represented the 0.1% of the labeled pixels in the fully supervised scenario. Figure 2 depicts some examples of fully annotated images and the corresponding weak labels.

Figure 2: Examples of different levels of supervision. In the fully labeled images (*top*), all pixels are annotated, with red depicting the background and green the object of interest). In the weakly supervised cases (*bottom*), only the labels of the green pixels are known. The images were cropped for a better visualization of the weak labels. The original images are of size 256×256 pixels.

To compute lower and upper bounds on the size of the target region, we used the manual segmentation of a single subject. Specifically, we computed the minimum and maximum values of the size of left ventricular endocardium over all the slices, and multiplied by a factor of 0.9 and 1.1 the minimum and maximum value, respectively, to account for size variations across exams.

3.3 Several levels of supervision

Training models with diverse levels of supervision requires defining appropriate objectives for each case. In this section, we introduce the different models, each with different levels of supervision.

---

[4]https://www.creatis.insa-lyon.fr/Challenge/acdc/

First, we trained a segmentation network from weakly annotated images with no additional information, which served as baseline. Training this model relies on computing the cross-entropy only on labeled pixels, i.e., *partial cross-entropy (CE)*. Then, we trained several models using the same weakly annotated images with different levels of constraint supervision. First, similar to MIL scenarios, we used image-tag priors by enforcing the presence or absence of a the target in a given training image, as introduced earlier. This reduces to enforcing that the size of the predicted region is less or equal to 0 if the target is absent from the image, or larger than 0 otherwise. Afterwards, we imposed an upper-bound constraint on the size of the target when the latter is present in the image. In this case, a in Eqs. 3 and 4 is set equal to 0. Thus, the CNN is constrained to generate segmentations whose sizes must be below an upper bound b. If the target is not present on the image, we set the upper bound b equal to 0, similarly to the MIL case for suppression constraints.

Finally, we imposed both upper- and lower-bound constraints of the size of the target regions

Forward and backward pass are defined by eq. 3 and 4, where a and b are computed from one training subject following the steps described in Sec 3.2. The lower and upper size bounds have a value of 98 and 1723 pixels, respectively. In all these cases, cross-entropy on annotated pixels and the proposed size loss are jointly minimized. Last, as upper bound baseline, we consider the class labels are known for every pixel during training, where the CNN training results on optimizing the sum of per-pixel cross-entropy.

The Lagrangian proposals method [17] reuses the same network and loss function than the fully supervised setting. At each iteration, a synthetic ground truth $\tilde{Y}$ is generated using a projected gradient ascent, before computing the cross entropy between $\tilde{Y}$ and S. We found that limiting the number of iterations for the PGA to 500 (instead of the original 3000) saved time without impacting significantly the results. We use the same bounds as in the proposed direct loss.

3.4 Training and implementation details

For all the proposed experiments we employ ENet [15] network, as it has shown a good trade-off between accuracy and inference time. Nevertheless, the proposed high-order size loss is general and it can be applied on any CNN. The network is trained from scratch by employing Adam optimizer and a batch size of 1. The initial learning rate was set to 5×10^{-3} and it was decreased by 2 after 100 epochs. The weight of the size loss in (2) was empirically set to 1×10^{-2} and its influence on the performance has not been investigated in this work. Input images had a size of 256×256 pixels.

For evaluation purposes, since each method has a different loss function, we resort to the common Dice index $= \frac{2|S \bigcap Y|}{|S|+|Y|}$ to compare them.

We used a combination of PyTorch [16] and NumPy for our implementations, and ran the experiments on a machine equipped with a NVIDIA GTX 1080 Ti GPU (11GBs of memory). The code is available at https://github.com/LIVIAETS/SizeLoss_WSS.

4 Results

This section introduces the experimental results of this paper. First, in Sec. 4.1 we evaluate the impact of including additional losses during training in a weakly supervised setting. We show that by incorporating the proposed high-order size term directly into the loss yields a highly significant boost on performance with regards to the baseline. Then, in Sec. 4.2 we compare the effect of using direct loss and generating proposals in training in an iterative scheme [17]. Compared to this strategy, our proposed method achieved state-of-the-art performance on weakly supervised segmentation with small blobby regions as labels. We also provide the results for the fully supervised setting in Sec. 4.3. After that, qualitative evaluation is assessed in Sec. 4.4. In addition, we compare the different learning strategies in terms of efficiency (Sec. 4.5), showing that the direct introduction of the proposed loss during learning does not affect training times.

4.1 Weakly supervised segmentation with size loss

Table 1 reports results on the validation set for all the models trained with both the Lagrangian proposals approach in [17] and our proposed direct loss. The lower bound baseline is the network

with cross entropy loss only on labeled pixels. As can be seen, this baseline achieves poor results, since no other information rather than the annotated pixels is given. As such, there is no regularization term that can give some hints on the desired segmentation. Evaluation on this baseline reported mean DSC values below 0.10, which are considered unsatisfactory. On the other hand, enforcing constraints based on image tags as in the MIL scenarios led to a substantial improvement in terms of DSC, obtaining a mean value of 0.7122. More interestingly, we can also observe that by constraining the CNN prediction with the proposed direct size loss significantly increased the performance of the network, as can be seen on both Table 1 and Fig 3. Regarding the proposed size loss term, imposing both lower and upper bounds on the size of the predicted region demonstrated to help on the training, resulting in better performance. Specifically, if we employ only a superior bound b, we achieve a mean DSC value of 0.8189, whereas if a lower bound a is also considered, mean DSC increases up to 0.8415.

Table 1: Segmentation results with diverse levels of supervision.

Model		Method	DSC (Val)
Weakly supervised	Partial CE		0.0721
	CE + Tags	Lagrangian Proposals [17]	0.6157
	Partial CE + Tags	Direct loss (Ours)	0.7122
	CE + Tags + Size*	Lagrangian Proposals [17]	0.6175
	Partial CE + Tags + Size*	Direct loss (Ours)	0.8189
	CE + Tags + Size**	Lagrangian Proposals [17]	0.6526
	Partial CE + Tags + Size**	Direct loss (Ours)	**0.8415**
Fully supervised	Cross-entropy		0.9284

*Upper bound / ** Lower and upper bounds

Figure 3: Evolution of DSC on validation samples for the weakly supervised learning models and strategies analyzed and full supervision. We analyze difference on performances when employing only tags and when adding bounds on the size of the prediction.

4.2 Implicit loss against segmentation proposals

In this section we compare the implicit inclusion of the proposed high-order size loss during training to segmentation proposals generation [17]. From Table 1 and Fig. 3 we observe that, for all the models of weak supervision, generating proposals gives inferior segmentation performance compared to our direct loss under the same conditions. First, we observe that if only image tags are considered as suppression/presence constraints, enforcing these constraints with image proposals achieved a mean DSC of 0.6157, while our direct loss obtained an increase of 15%, with a mean DSC equal to 0.7122. This difference becomes more significant when the proposed high-order size loss term is included during training. In these cases, direct loss outperforms the Lagrangian proposals approach by a margin of 30%, which can be considered as a highly significant difference. Another observation from Fig. 3 is that training with Lagrangian proposals typically achieves its pick of performance

faster than the proposed loss term, not bringing any improvement after few epochs. Furthermore, it has been shown to be more unstable than the direct loss approach.

4.3 Pixel-level annotations

Finally, we compared the weakly supervised strategies to a network trained on fully labeled images. Training the network with strong pixel-level annotations achieved a mean DSC of 0.9284 on the validation set. This result represents an increase of a 10% with respect to the best proposed method. Nevertheless, it is noteworthy to mention that the performance achieved by the proposed weakly supervised learning approach with size loss constraints approaches the fully supervised setting with only 0.1 % of the annotated pixels. This indicates that the current work shortens the gap between fully and weakly supervised learning for semantic segmentation, pushing the bounds of the latter.

4.4 Qualitative results

To get some intuition about the different learning strategies and their effects on the segmentation we visualize some results in Fig. 4. Particularly, the model containing the partial cross-entropy and size loss constraints with lower and upper bounds is investigated. For the three learning methods –i.e., full supervised, Lagrangian proposals generation and the proposed direct loss– we selected the best performing model to display these images. Even though generating proposals during training actually improved the segmentation performance compared to the baseline (Table 1), looking at the examples on Fig. 4 (*third column*) we can observe that these segmentations are far from being satisfactory. Nevertheless, integrating the proposed size-constrained loss directly in the back-propagation increases substantially the accuracy of the network, as can be seen in the last column of Fig. 4. An interesting observation is that, in some cases (*last row*), weakly supervised learning produces more reliable segmentations than training with full supervision.

4.5 Efficiency

In this section we compare the several learning approaches in terms of efficiency (Table 2). The weakly supervised baseline and the fully supervised model need to compute only one loss per pass. This is reflected in the lowest training times reported in the table. Including the size loss does not affect the computational time, as can be seen in these results. As expected, the iterative process introduced by [17] at each forward pass cause a non negligible overhead during training. To generate their synthetic ground truth, they need to optimize the Lagragian function of their constrained loss with respect to its λ-parameters, which requires alternating between computing softmax probabilities and gradients of those probabilities. Even in simple optimization case (with only one constraint) where this parameter converge fast, it adds a few milliseconds at each iteration.

Table 2: Training times for the diverse supervised learning strategies, using tags and size constraints.

Method	Training time (ms/image)
Partial CE	10
Direct loss	10
Lagragian proposals	15
Fully supervised	10

5 Conclusion

We presented a novel loss function for weakly supervised image segmentation, which despite its simplicity reach almost full supervision performances. We perform significantly better than the other proposed methods for this task, achieving 90% of full supervision performance with only 0.1% of annotated pixels, while having negligible computation overhead.

Acknowledgments

This work is supported by the National Science and Engineering Research Council of Canada (NSERC), discovery grant program, and by the ETS Research Chair on Artificial Intelligence in Medical Imaging.

Figure 4: Qualitative comparison of the different methods. Each row represents a 2D slice from different scans. We can easily see that our method achieves results comparable to full supervision. (Best viewed in colors)

References

[1] Amy L. Bearman, Olga Russakovsky, Vittorio Ferrari, and Fei-Fei Li. What's the point: Semantic segmentation with point supervision. In *European Conference on Computer Vision (ECCV)*, pages 549–565, 2016.

[2] Yuri Boykov, Hossam N. Isack, Carl Olsson, and Ismail Ben Ayed. Volumetric bias in segmentation and reconstruction: Secrets and solutions. In *IEEE International Conference on Computer Vision (ICCV)*, pages 1769–1777, 2015.

[3] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

[4] Lena Gorelick, Frank R. Schmidt, and Yuri Boykov. Fast trust region for segmentation. In *2013 IEEE Conference on Computer Vision and Pattern Recognition, Portland, OR, USA, June 23-28, 2013*, pages 1714–1721, 2013.

[5] Maria Klodt and Daniel Cremers. A convex framework for image segmentation with moment constraints. In *IEEE International Conference on Computer Vision, ICCV 2011, Barcelona, Spain, November 6-13, 2011*, pages 2236–2243, 2011.

[6] Alexander Kolesnikov and Christoph H Lampert. Seed, expand and constrain: Three principles for weakly-supervised image segmentation. In *European Conference on Computer Vision*, pages 695–711. Springer, 2016.

[7] Philipp Krahenbuhl and Vladlen Koltun. Efficient inference in fully connected CRFs with Gaussian edge potentials. In *NIPS*, 2011.

[8] Yongsub Lim, Kyomin Jung, and Pushmeet Kohli. Efficient energy minimization for enforcing label statistics. *IEEE Trans. Pattern Anal. Mach. Intell.*, 36(9):1893–1899, 2014.

[9] Di Lin, Jifeng Dai, Jiaya Jia, Kaiming He, and Jian Sun. Scribblesup: Scribble-supervised convolutional networks for semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3159–3167, 2016.

[10] Geert J. S. Litjens, Thijs Kooi, Babak Ehteshami Bejnordi, Arnaud Arindra Adiyoso Setio, Francesco Ciompi, Mohsen Ghafoorian, Jeroen A. W. M. van der Laak, Bram van Ginneken, and Clara I. Sánchez. A survey on deep learning in medical image analysis. *Medical Image Analysis*, 42:60–88, 2017.

[11] Jonathan Long, Evan Shelhamer, and Trevor Darrell. Fully convolutional networks for semantic segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3431–3440, 2015.

[12] Pablo Márquez-Neila, Mathieu Salzmann, and Pascal Fua. Imposing hard constraints on deep networks: Promises and limitations. *CoRR*, abs/1706.02025, 2017.

[13] Marc Niethammer and Christopher Zach. Segmentation with area constraints. *Medical Image Analysis*, 17(1):101–112, 2013.

[14] George Papandreou, Liang-Chieh Chen, Kevin Murphy, and Alan L Yuille. Weakly-and semi-supervised learning of a dcnn for semantic image segmentation. *arXiv preprint arXiv:1502.02734*, 2015.

[15] Adam Paszke, Abhishek Chaurasia, Sangpil Kim, and Eugenio Culurciello. Enet: A deep neural network architecture for real-time semantic segmentation. *arXiv preprint arXiv:1606.02147*, 2016.

[16] Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

[17] Deepak Pathak, Philipp Krahenbuhl, and Trevor Darrell. Constrained convolutional neural networks for weakly supervised segmentation. In *Proceedings of the IEEE international conference on computer vision*, pages 1796–1804, 2015.

[18] J. C. Platt and A. H. Barr. Constrained differential optimization. Technical report, California Institute of Technology, 1988.

[19] Martin Rajchl, Matthew CH Lee, Ozan Oktay, Konstantinos Kamnitsas, Jonathan Passerat-Palmbach, Wenjia Bai, Mellisa Damodaram, Mary A Rutherford, Joseph V Hajnal, Bernhard Kainz, et al. Deepcut: Object segmentation from bounding box annotations using convolutional neural networks. *IEEE transactions on medical imaging*, 36(2):674–683, 2017.

[20] Vishnu Sai Rao Lokhande Vikas Singh Sathya N. Ravi, Tuan Dinh. Constrained deep learning using conditional gradient and applications in computer vision. *arXiv:1803.0645*, 2018.

[21] Meng Tang, Abdelaziz Djelouah, Federico Perazzi, Yuri Boykov, and Christopher Schroers. Normalized Cut Loss for Weakly-supervised CNN Segmentation. In *IEEE conference on Computer Vision and Pattern Recognition (CVPR)*, Salt Lake City, June 2018.

[22] Meng Tang, Federico Perazzi, Abdelaziz Djelouah, Ismail Ben Ayed, Christopher Schroers, and Yuri Boykov. On regularized losses for weakly-supervised cnn segmentation. *arXiv preprint arXiv:1803.09569*, 2018.

[23] Jason Weston, Frédéric Ratle, Hossein Mobahi, and Ronan Collobert. Deep learning via semi-supervised embedding. In *Neural Networks: Tricks of the Trade*, pages 639–655. Springer, 2012.

[24] S. Zhang and A. Constantinides. Lagrange programming neural networks. *IEEE Transactions on Circuits and Systems II: Analog and Digital Signal Processing*, 39(7):441–452, 1992.

[25] Yang Zhang, Philip David, and Boqing Gong. Curriculum domain adaptation for semantic segmentation of urban scenes. In *IEEE International Conference on Computer Vision (ICCV)*, pages 2039–2049, 2017.