Aligned Diffusion Schrödinger Bridges

Abstract

Diffusion Schrödinger bridges (DSBs) have recently emerged as a powerful framework for recovering stochastic dynamics via their marginal observations at different time points. Despite numerous successful applications, existing algorithms for solving DSBs have so far failed to utilize the structure of *aligned* data, which naturally arises in many biological phenomena. In this paper, we propose a novel algorithmic framework that, for the first time, solves DSBs while respecting the data alignment. Our approach hinges on a combination of two decades-old ideas: The classical Schrödinger bridge theory and Doob's *h-transform*. Compared to prior methods, our approach leads to a simpler training procedure with lower variance, which we further augment with principled regularization schemes. This ultimately leads to sizeable improvements across experiments on synthetic and real data, including the tasks of rigid protein docking and temporal evolution of cellular differentiation processes.

1 INTRODUCTION

Interpolation, the task of transforming one given distribution into another, lies at the heart of many modern machine learning applications such as single-cell genomics (Tong et al., 2020; Schiebinger et al., 2019; Bunne et al., 2022a), meteorology (Fisher et al., 2009), and robotics (Chen et al., 2021a). To this end, *Diffusion Schrödinger bridges* (DSBs) (De Bortoli et al., 2021; Chen et al., 2022a; Vargas et al., 2021; Liu et al., 2022b) have recently emerged as a powerful paradigm due to their ability to generalize prior deep diffusion-based models, notably score matching with Langevin dynamics (Song and Ermon, 2019; Song et al., 2021) and denoising diffusion probabilistic models (Ho et al., 2020), which have achieved the state-of-the-art on many generative modelling problems.

Figure 1: Overview of SBALIGN: In biological tasks such as protein docking, one is naturally provided with *aligned* data in the form of unbound and bound structures of participating proteins. Our goal is to therefore recover a stochastic trajectory from $\mathbf{x}_0$ to $\mathbf{x}_1$. To achieve this, we connect the characterization of a SDE conditioned on $\mathbf{x}_0$ and $\mathbf{x}_1$ (utilizing the Doob's *h-transform*) with that of a Brownian bridge between $\mathbf{x}_0$ and $\mathbf{x}_1$ (classical Schrödinger bridge theory). We show that this leads to a simpler training procedure with lower variance and strong empirical results.

Despite the wide success, a significant limitation of existing frameworks for solving DSBs is that they fail to capture the *alignment* of data: If $\hat{\mathbb{P}}_0, \hat{\mathbb{P}}_1$ are two (empirical) distributions between which we wish to interpolate, then a tacit assumption in the literature is that the dependence of $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$ is unknown and somehow has to be recovered. Such an assumption, however, ignores important scenarios where the data is *aligned*, meaning that the samples from $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$ naturally come in pairs $(\mathbf{x}_0^i, \mathbf{x}_1^i)_i^N$, which is common in many biological phenomena. Proteins, for instance undergo conformational changes upon interactions with other biomolecules (protein docking, see Fig. 1), and the goal is to model conformational changes by recovering a (stochastic) trajectory $\mathbf{x}_t$ based on the positions observed at two time points $(\mathbf{x}_0, \mathbf{x}_1)$. Failing to incorporate this alignment would mean that we completely ignore information of the correspondence between initial and final points of the molecules, resulting in a much harder problem than necessary. Beyond,

the recent use of SBs has been motivated by an important task in molecular biology: Cells change their molecular profile throughout developmental processes (Schiebinger et al., 2019; Bunne et al., 2022b) or in response to perturbations such as cancer drugs (Lotfollahi et al., 2019; Bunne et al., 2021). As most measurement technologies are destructive assays, i.e., the same cell cannot be observed twice nor fully profiled over time, these methods aim at reconstructing cell dynamics from *unpaired* snapshots. Recent developments in molecular biology, however, aim at overcoming this technological limitation. For example, Chen et al. (2022b) propose a transcriptome profiling approach that preserves cell viability. Weinreb et al. (2020) capture cell differentiation processes by clonally connecting cells and their progenitors through barcodes (see illustrative Figure in Supplement).

Motivated by these observations, the goal of this paper is to propose a novel algorithmic framework for solving DSBs with (partially) *aligned* data. Our approach is in stark contrast to existing works which, due to the lack of data alignment, all rely on some variants of *iterative proportional fitting* (IPF) (Fortet, 1940; Kullback, 1968) and are thus prone to numerical instability. On the other hand, via a combination of the original theory of Schrödinger bridges (Schrödinger, 1931; Léonard, 2013) and the key notion of Doob's h-*transform* (Doob, 1984; Rogers and Williams, 2000), we design a novel loss function that completely bypasses the IPF procedure and can be trained with much lower variance.

To summarize, we make the following contributions:

- To our best knowledge, we consider, for the first time, the problem of interpolation with *aligned* data. We rigorously formulate the problem in the DSB framework.

- Based on the theory of Schrödinger bridges and h-transform, we derive a new loss function that, unlike prior work on DSBs, does not require an IPF-like procedure to train. We also propose principled regularization schemes to further stabilize training.

- We describe how interpolating aligned data can provide better reference processes for use in classical DSBs, paving the way to hybrid aligned/non-aligned Schrödinger bridges (SBs).

- We evaluate our proposed framework on both synthetic and real data. For experiments utilizing real data, we consider two tasks where such aligned data is naturally available. The first is the task of developmental processes in single-cell biology, and the second is (*rigid*) protein docking, where the goal is to predict the 3D structure of the bound complex formed by two proteins, given their unbound 3D structures. Our method demonstrates a considerable improvement over prior methods across various metrics, thereby substantiating the importance of taking the data alignment into account.

Related work. Solving DSBs is a subject of significant interest in recent years and has flourished in a number of different algorithms (De Bortoli et al., 2021; Chen et al., 2022a; Vargas et al., 2021; Bunne et al., 2023; Liu et al., 2022a). However, all these previous approaches focus on the *unaligned* data, and therefore the methodologies all rely on IPF and are hence drastically different from ours. In the experiments, we will demonstrate the importance of taking the alignment of data into consideration by comparing our method to these baselines.

An important ingredient in our theory is Doob's h-transform, which has recently also been utilized by Liu et al. (2023) to solve the problem of constrained diffusion. However, their fundamental motivation is different from ours. Liu et al. (2023) focus on learning the drift of the diffusion model and the h-transform *together*, whereas ours is to read off the drift *from* the h-transform with the help of *aligned data*. Consequently, there is no overlap between the two algorithms, and their intended applications.

To the best of our knowledge, the concurrent work of Tong et al. (2023) is the only existing framework which can tackle aligned data, which, however, is not the original motivation of Tong et al. (2023). In the context of solving DSBs, their algorithm can be seen as learning a vector field that generates the correct *marginal* probability; see (Tong et al., 2023, Proposition 4.3). Importantly, this is different from our aim of finding the *pathwise* optimal solution of DSBs: If $(\mathbf{x}_{0,\text{test}}^i)_{i=1}^m$ is a test data set which we wish to predict their destinations, then the framework of Tong et al. (2023) can only ensure that the marginal distribution $(\mathbf{x}_{1,\text{test}}^i)_{i=1}^m$ is correct, whereas ours is capable of predicting that $\mathbf{x}_{1,\text{test}}^i$ is precisely the destination of $\mathbf{x}_{0,\text{test}}^i$ for each i. This latter property is highly desirable in tasks like ML-accelerated protein docking.

2 BACKGROUND

Problem formulation. Suppose that we are given access to i.i.d. *aligned* data $(\mathbf{x}_0^i, \mathbf{x}_1^i)_{i=1}^N$, where the marginal distribution of $\mathbf{x}_0^i$'s is $\hat{\mathbb{P}}_0$ and of $\mathbf{x}_1^i$'s is $\hat{\mathbb{P}}_1$. Typically, we view $\hat{\mathbb{P}}_0$ as the empirical marginal distribution of a stochastic process observed at time $t = 0$, and likewise $\hat{\mathbb{P}}_1$ the empirical marginal observed at $t = 1$. The goal is to reconstruct the stochastic process $\mathbb{P}_t$ based on $(\mathbf{x}_0^i, \mathbf{x}_1^i)_{i=1}^N$, i.e., to *interpolate* between $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$.

Such a task is ubiquitous in biological applications. For instance, understanding how proteins dock to other biomolecules is of significant interest in biology and has become a topic of intense study in recent years (Ganea et al., 2022; Tsaban et al., 2022; Corso et al., 2023). In the protein docking task, $\mathbf{x}_0^i$ represents the 3D structures of the unbound proteins, while $\mathbf{x}_1^i$ represents the 3D structure of the bound complex. Reconstructing a stochastic process

that diffuses $\mathbf{x}_0^i$'s to $\mathbf{x}_1^i$'s is tantamount to recovering the energy landscape governing the docking process. Similarly, in molecular dynamics simulations, we have access to trajectories $(\mathbf{x}_t^i)_{t \in [0,1]}$, where $\mathbf{x}_0^i$ and $\mathbf{x}_1^i$ represent the initial and final positions of the i-th molecule respectively. Any learning algorithm using these simulations should be able to respect the provided alignment.

Diffusion Schrödinger Bridges. To solve the interpolation problem, in Section 3, we will invoke the framework of *Diffusion Schrödinger bridges* (DSBs), which are designed to solve interpolation problems with *unaligned* data. More specifically, given two marginals $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$, the DSB framework proceeds by first choosing a reference process $\mathbb{Q}_t$ using prior knowledge, for instance a simple Brownian motion, and then solve the entropy-minimization problem over all stochastic processes $\mathbb{P}_t$:

$$\min_{\mathbb{P}_0=\hat{\mathbb{P}}_0,\ \mathbb{P}_1=\hat{\mathbb{P}}_1} D_{\mathrm{KL}}(\mathbb{P}_t \| \mathbb{Q}_t). \tag{SB}$$

Despite the fact that many methods exist for solving (SB) (De Bortoli et al., 2021; Chen et al., 2022a; Vargas et al., 2021; Bunne et al., 2023), none of these approaches are capable of incorporating *alignment* of the data. This can be seen by inspecting the objective (SB), in which the coupling information $(\mathbf{x}_0^i, \mathbf{x}_1^i)$ is completely lost as only its individual marginals $\hat{\mathbb{P}}_0, \hat{\mathbb{P}}_1$ play a role therein. Unfortunately, it is well-known that tackling the marginals separately necessitates a forward-backward learning process known as the *iterative proportional fitting* (IPF) procedure (Fortet, 1940; Kullback, 1968), which constitutes the primary reason of high variance training, thereby confronting DSBs with numerical and scalability issues. Our major contribution, detailed in the next section, is therefore to devise the first algorithmic framework that solves the interpolation problem with aligned data *without* resorting to IPF.

3 ALIGNED DIFFUSION SCHRÖDINGER BRIDGES

In this section, we derive a novel loss function for DSBs with aligned data by combining two classical notions: The theory of Schrödinger bridges (Schrödinger, 1931; Léonard, 2013; Chen et al., 2021b) and Doob's h-transform (Doob, 1984; Rogers and Williams, 2000). We then describe how solutions to DSBs with aligned data can be leveraged in the context of classical DSBs.

3.1 LEARNING ALIGNED DSBs

Static SB and aligned data. Our starting point is the simple and classical observation that (SB) is the continuous-time analogue of the *entropic optimal transport*, also known as the *static* Schrödinger bridge problem (Léonard, 2013;

Chen et al., 2021b; Peyré and Cuturi, 2019):

$$\pi^\star := \underset{\mathbb{P}_0=\hat{\mathbb{P}}_0,\ \mathbb{P}_1=\hat{\mathbb{P}}_1}{\arg\min}\ D_{\mathrm{KL}}(\mathbb{P}_{0,1} \| \mathbb{Q}_{0,1}) \tag{1}$$

where the minimization is over all *couplings* of $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$, and $\mathbb{Q}_{0,1}$ is simply the joint distribution of $\mathbb{Q}_t$ at $t = 0, 1$. In other words, if we denote by $\mathbb{P}_t^\star$ the stochastic process that minimizes (SB), then the joint distribution $\mathbb{P}_{0,1}^\star$ necessarily coincides with the $\pi^\star$ in (1). Moreover, since in DSBs, the data is always assumed to arise from $\mathbb{P}_t^\star$, we see that:

> The *aligned* data $(\mathbf{x}_0^i, \mathbf{x}_1^i)_{i=1}^N$ constitutes samples of $\pi^\star$.

This simple but crucial observation lies at the heart of all derivations to come.

Our central idea is to represent $\mathbb{P}_t^\star$ via two different, but equivalent, characterizations, both of which involve $\pi^\star$: That of a *mixture* of reference processes with pinned end points, and that of conditional *stochastic differential equations* (SDEs).

$\mathbb{P}_t^\star$ from $\pi^\star$: $\mathbb{Q}_t$ with pinned end points. For illustration purposes, from now on, we will assume that the reference process $\mathbb{Q}_t$ is a Brownian motion with diffusion coefficient g_t:[1]

$$\mathrm{d}\mathbb{Q}_t = g_t\, \mathrm{d}\mathbb{W}_t. \tag{2}$$

In this case, it is well-known that $\mathbb{Q}_t$ *conditioned* to start at $\mathbf{x}_0$ and end at $\mathbf{x}_1$ can be written in another SDE (Mansuy and Yor, 2008; Liu et al., 2023):

$$\mathrm{d}X_t = g_t^2 \frac{\mathbf{x}_1 - X_t}{\beta_1 - \beta_t}\, \mathrm{d}t + g_t\, \mathrm{d}\mathbb{W}_t \tag{3}$$

where $X_0 = \mathbf{x}_0$ and

$$\beta_t := \int_0^t g_s^2\, \mathrm{d}s. \tag{4}$$

We call the processes in (3) the *scaled Brownian bridges* as they generalize the classical Brownian bridge, which corresponds to the case of $g_t \equiv 1$.

The first characterization of $\mathbb{P}_t^\star$ is then an immediate consequence the following classical result in Schrödinger bridge theory: Draw a sample $(\mathbf{x}_0, \mathbf{x}_1) \sim \pi^\star$ and connect them via (3). The resulting path is a sample from $\mathbb{P}_t^\star$ (Léonard, 2013; Chen et al., 2021b). In other words, $\mathbb{P}_t^\star$ is a *mixture* of scaled Brownian bridges, with the mixing weight given by $\pi^\star$.

---

[1]Extension to more involved reference processes is conceptually straightforward but notationally clumsy. Furthermore, reference processes of the form (2) are dominant in practical applications (Song et al., 2021; Bunne et al., 2023), so we omit the general case.

$\mathbb{P}_t^\star$ from $\pi^\star$: SDE representation. Another characterization of $\mathbb{P}_t^\star$ is that it is itself given by an SDE of the form (Léonard, 2013; Chen et al., 2021b)

$$\mathrm{d}X_t = g_t^2 b_t(X_t)\,\mathrm{d}t + g_t\,\mathrm{d}\mathbb{W}_t. \tag{5}$$

Here, $b_t : \mathbb{R}^d \to \mathbb{R}^d$ is a time-dependent drift function that we wish to learn.

Now, by Doob's h-transform, we know that the SDE (5) *conditioned* to start at $\mathbf{x}_0$ and end at $\mathbf{x}_1$ is given by another SDE (Doob, 1984; Rogers and Williams, 2000):

$$\mathrm{d}X_t = g_t^2[b_t(X_t) + \nabla \log h_t(X_t)]\,\mathrm{d}t + g_t\,\mathrm{d}\mathbb{W}_t \tag{6}$$

where $h_t(\mathbf{x}) := \mathbb{P}(X_1 = \mathbf{x}_1 | X_t = \mathbf{x})$ is the *Doob's h function*. Notice that we have suppressed the dependence of h_t on $\mathbf{x}_0$ and $\mathbf{x}_1$ for notational simplicity.

Loss function. Since both (3) and (6) represent $\mathbb{P}_t^\star$, the solution of the DSBs, the two SDEs must coincide. In other words, suppose we parametrize b_t as b_t^θ, then, by matching terms in (3) and (6), we can learn the optimal parameter $\theta^\star$ via optimization of the loss function

$$L(\theta) := \mathbb{E}\left[\int_0^1 \left\| \frac{\mathbf{x}_1 - X_t}{\beta_1 - \beta_t} - \nabla \log h_t^\theta(X_t) \right\|^2 \mathrm{d}t\right] \tag{7}$$

where h_t^θ is determined by b_t^θ as well as the drawn samples $(\mathbf{x}_0, \mathbf{x}_1)$. In short, assuming that, for each θ, we can compute h_t^θ *based only on b_t^θ*, we can then backprop through (7) and optimize it using any off-the-shelf algorithm.

A slightly modified (7). Even with infinite data and a neural network with sufficient capacity, the loss function defined in (7) does converge to 0. For the purpose of numerical stability, we instead propose to modify (7) to:

$$L(\theta) := \mathbb{E}\left[\int_0^1 \left\| \frac{\mathbf{x}_1 - X_t}{\beta_1 - \beta_t} - \left(b_t^\theta + \nabla \log h_t^\theta(X_t)\right) \right\|^2 \mathrm{d}t\right] \tag{8}$$

which is clearly equivalent to (7) at the true solution of b_t. Notice that (8) bears a similar form as the popular score-matching objective employed in previous works (Song and Ermon, 2019; Song et al., 2021):

$$L(\theta) := \mathbb{E}\left[\int_0^1 \left\| \nabla \log p(\mathbf{x}_t | \mathbf{x}_0) - s^\theta(X_t, t) \right\|^2 \mathrm{d}t\right], \tag{9}$$

where the term $\frac{\mathbf{x}_1 - X_t}{\beta_1 - \beta_t}$ is akin to $\nabla \log p(\mathbf{x}_t | \mathbf{x}_0)$, while $\left(b_t^\theta + \nabla \log h_t^\theta(X_t)\right)$ corresponds to $s^\theta(X_t, t)$.

Computing h_t^θ. Inspecting h_t in (6), we see that, given $(\mathbf{x}_0, \mathbf{x}_1)$, it can be written as the conditional expectation of an indicator function:

$$h_t(\mathbf{x}) = \mathbb{P}(X_1 = \mathbf{x}_1 | X_t = \mathbf{x}) = \mathbb{E}\big[\mathbb{1}_{\{\mathbf{x}_1\}} | X_t = \mathbf{x}\big] \tag{10}$$

where the expectation is over (5). Functions of the form (10) lend itself well to computation since it solves simulating

---

Algorithm 1 SBALIGN

Input: Aligned data $(\mathbf{x}_0^i, \mathbf{x}_1^i)_{i=1}^N$, learning rates $\gamma_\theta, \gamma_\phi$, number of iterations K

Initialize $\theta \leftarrow \theta_0$, $\phi \leftarrow \phi_0$.
for $k = 1$ **to** K **do**
    Draw a mini-batch of samples from $(\mathbf{x}_0^i, \mathbf{x}_1^i)_{i=1}^N$
    Compute empirical average of (12) with mini-batch.
    Update $\phi \leftarrow \phi - \gamma_\phi \nabla L(\theta, \phi)$
    Update $\theta \leftarrow \theta - \gamma_\theta \nabla L(\theta, \phi)$
end for

---

the *unconditioned* paths. Furthermore, in order to avoid overfitting on the given samples, it is customary to replace the "hard" constraint $\mathbb{1}_{\{\mathbf{x}_1\}}$ by its *smoothed* version (Zhang and Chen, 2021; Holdijk et al., 2022):

$$h_{t,\tau}(\mathbf{x}) := \mathbb{E}\left[\exp\left(-\frac{1}{2\tau}\|X_1 - \mathbf{x}_1\|^2\right) | X_t = \mathbf{x}\right]. \tag{11}$$

Here, τ is a regularization parameter that controls how much we "soften" the constraint, and we have $\lim_{\tau \to 0} h_{t,\tau} = h_t$.

Although the computation of (11) can be done via a standard application of the Feynman–Kac formula (Rogers and Williams, 2000), an altogether easier approach is to parametrize $h_{t,\tau}$ by a second neural network m^ϕ and perform alternating minimization steps on b_t^θ and m^ϕ. This way, we can also avoid simulating even the unconditional paths of (5), and thereby further reducing the variance in training.

Regularization. Since it is well-known that $\nabla \log h_t$ typically explodes when $t \to 1$ (Liu et al., 2023), it is important to regularize the behavior of m^ϕ for numerical stability, especially when $t \to 1$. Moreover, in practice, it is desirable to learn a drift b_t^θ that respects the data alignment *in expectation*: If $(\mathbf{x}_0, \mathbf{x}_1)$ is an input pair, then multiple runs of the SDE (5) starting from $\mathbf{x}_0$ should, on average, produce samples that are in the proximity of $\mathbf{x}_1$. This observation implies that we should search for drifts whose corresponding h-transforms are diminishing.

A simple way to simultaneously achieve the above two requirements is to add an ℓ^2-regularization term, resulting in the loss function:

$$L(\theta, \phi) := \mathbb{E}\left[\int_0^1 \left\| \frac{\mathbf{x}_1 - X_t}{\beta_1 - \beta_t} - \left(b_t^\theta + m^\phi(X_t)\right) \right\|^2 \right.$$
$$\left. + \lambda_t \|m^\phi(\mathbf{x}_t)\|^2 \,\mathrm{d}t\right] \tag{12}$$

where λ_t can either be constant or vary with time. The overall algorithm is depicted in Algorithm 1.

Figure 2: Experimental results on the Moon dataset (**a-c**) and T-dataset (**d-f**). The top row shows the trajectory sampled using the learned drift, and the bottom row shows the matching based on the learnt drift. Compared to other baselines, SBALIGN is able to learn an appropriate drift respecting the true alignment. (**f**) further showcases the utility of SBALIGN's learnt drift as a suitable reference process to improve other training methods.

3.2 PAIRED SBs AS PRIOR PROCESSES

Classical SBs are unsuitable in cases where the alignments are known, because they only consider samples from $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$ and disregard those drawn from the (optimal) coupling $\pi^\star$. However, the reliance of our method on this crucial knowledge is critical to avoid the necessity of IPF-like iterates but may become a limitation when insufficient information on alignments is available.

In such a situation, while it is unrealistic to hope for an accurate solution to the aligned SB problem, the interpolation between $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$ learned by SBALIGN (5) can potentially still be leveraged to obtain a better reference process, when solving a classical SB on the same marginals — i.e. the term $b_t(X_t)$ learned via SBALIGN can, in fact, be used —as is— to construct a data-informed alternative $\tilde{\mathbb{Q}}_t$ to the standard Brownian motion (2).

Improved reference processes, either using pre-trained or data-informed ones, have been previously considered in the literature. For instance, both De Bortoli et al. (2021) and Chen et al. (2022a) use a pre-trained reference process for challenging image interpolation tasks. This approach, however, relies on DSBs trained using the classical score-based generative modeling objective between a Gaussian and the data distribution. It therefore pre-trains the reference process on a related —but different— process, i.e., the one mapping Gaussian noise to data rather than $\hat{\mathbb{P}}_0$ to $\hat{\mathbb{P}}_1$. An alternative, proposed by Bunne et al. (2023), draws on the closed-form solution of SBs between two Gaussian distributions, which are chosen to approximate $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$, respectively. Unlike our method, these alternatives construct better prior drifts by falling back to simpler and related tasks, or approximations of the original problem. We instead propose to shape a

coarse-grained description of the drift based on alignments sampled directly from $\mathbb{P}_{0,1}$.

4 EXPERIMENTS

In this section, we evaluate SBALIGN in different settings involving 2-dimensional synthetic datasets, the task of reconstructing cellular differentiation processes, as well as predicting the conformation of a protein structure and its ligand formalized as rigid protein docking problem.

4.1 SYNTHETIC EXPERIMENTS

We run our algorithm on two synthetic datasets (figures in § B), and compare the results with classic Schrödinger bridge models, i.e., the forward-backward SB formulation proposed by Chen et al. (2022a), herein referred to as FBSB. We equip the baseline with prior knowledge, as elaborated below, to further challenge SBALIGN.

Moon dataset. The first synthetic dataset (Fig. 2a-c) consists of two distributions, each supported on two semi-circles ($\hat{\mathbb{P}}_0$ drawn in *blue* and $\hat{\mathbb{P}}_1$ in *red*). $\hat{\mathbb{P}}_1$ was obtained from $\hat{\mathbb{P}}_0$ by applying a clockwise rotation around the center, i.e., by making points in the upper blue arm correspond to those in the right red one. This transformation is clearly not the most likely one under the assumption of Brownian motion of particles and should therefore not be found as the solution of a classical SB problem. This is confirmed by FBSB trajectories (Fig. 2a), which tend to map points to their closest neighbor in $\hat{\mathbb{P}}_1$ (e.g., some points in the upper arm of $\hat{\mathbb{P}}_0$ are brought towards the left rather than towards the right). While being a minimizer of (SB), such a solution completely disregards our prior knowledge on the alignment of parti-

Figure 3: Cell differentiation trajectories based on (**a**) the ground truth and (**b-d**) learned drifts. SBALIGN is able to learn an appropriate drift underlying the true differentiation process while respecting the alignment. (**d**) Using the learned drift from SBALIGN as a reference process helps improve the drift learnt by other training methods.

cles, which is instead reliably reproduced by the dynamics learned by SBALIGN (Fig. 2b).

One way of encoding this additional information on the nature of the process is to modify $\mathbb{Q}_t$ by introducing a clockwise radial drift, which describes the prior tangential velocity of particles moving circularly around the center. Solving the classical SB with this updated reference process indeed generates trajectories that respect most alignments (Fig. 2b), but requires a hand-crafted expression of the drift that is only possible in very simple cases.

T dataset. In most real-world applications, it is very difficult to define an appropriate reference process $\mathbb{Q}_t$, which respects the known alignment without excessively distorting the trajectories from a solution to (SB). This is already visible in simple examples like (Fig. 2d-f), in which the value of good candidate prior drifts at a specific location needs to vary wildly in time. In this dataset, $\hat{\mathbb{P}}_0$ and $\hat{\mathbb{P}}_1$ are both bi-modal distributions, each supported on two of the four extremes of an imaginary T-shaped area. We target alignments that connect the two arms of the T as well as the top cloud with the bottom one. We succeed in learning them with SBALIGN (Fig. 2e) but unsurprisingly fail when using the baseline FBSB (Fig. 2d) with a Brownian motion prior.

In this case, however, attempts at designing a better reference drift for FBSB must take into account the additional constraint that the horizontal and vertical particle trajectories intersect (see Fig. 2e), i.e., they cross the same area at times t_h and t_v (with $t_h > t_v$). This implies that the drift b_t, which initially point downwards (when $t < t_v$), should swiftly turn rightwards (for $t > t_h$). Setting imprecise values for one of

t_h and t_v when defining custom reference drifts for classical SBs would hence not lead to the desired result and, worse, would actively disturb the flow of the other particle group.

As described in § 3.2, in presence of hard-to-capture requirements on the reference drift, the use of SBALIGN offers a remarkably easy and efficient way of learning a parametrization of it. For instance, when using the drift obtained by SBALIGN as reference drift for the computation of the SB baseline (FBSB), we find the desired alignments (Fig. 2f).

4.2 CELL DIFFERENTIATION

Biological processes are determined through heterogeneous responses of single cells to external stimuli, i.e., developmental factors or drugs. Understanding and predicting the dynamics of single cells subjected to a stimulus is thus crucial to enhance our understanding of health and disease and is the focus of this application. Most single-cell high-throughput technologies are destructive assays —i.e., they destroy cells upon measurement— allowing us to only measure *unaligned* snapshots of the evolving cell population. Recent methods address this limitation by proposing (lower-throughput) technologies that keep cells alive after transcriptome profiling (Chen et al., 2022b) or that genetically tag cells to obtain a clonal trace upon cell division (Weinreb et al., 2020).

Dataset. To showcase SBALIGN's ability to make use of such (partial) alignments when inferring cell differentiation processes, we take advantage of the genetic barcoding system developed by Weinreb et al. (2020). With a focus on

Figure 4: Cell type prediction on the differentiation dataset. All distributions are plotted on the first two principal components. **a-b:** Ground truth cell types on day 2 and day 4 respectively. **c-d:** FBSB and SBALIGN cell type predictions on day 4. SBALIGN is able to better model the underlying differentiation processes and capture the diversity in cell types.

Table 1: **Cell differentiation prediction results.** Shown are distributional metrics (MMD, W_ϵ), alignment based metrics (ℓ_2, RMSD), and cell type classification accuracy for different methods on the cell differentiation dataset.

| Methods | \multicolumn{5}{c}{Cell Differentiation} |
	MMD $\downarrow$	$W_\varepsilon \downarrow$	ℓ_2(PS) $\downarrow$	RMSD $\downarrow$	Class. Acc. $\uparrow$
FBSB	1.58e-2	12.6	4.07	9.63e-1	58.0%
FBSB with SBALIGN	5.15e-3	10.6	0.95	9.88e-1	49.0%
SBALIGN	9.77e-3	11.2	1.24	9.28e-1	56.0%

fate determination in hematopoiesis, Weinreb et al. (2020) use expressed DNA barcodes to clonally trace single-cell transcriptomes over time. The dataset consists of two snapshots: the first, recorded on day 2, when most cells are still undifferentiated (see Fig. 4a), and a second, on day 4, comprising many different mature cell types (see Fig. 4b). Using SBALIGN as well as the baseline FSSB, we attempt to reconstruct cell evolution between day 2 and day 4, all while capturing the heterogeneity of emerging cell types. For details on the dataset, see § B.

Baselines. We benchmark SBALIGN against previous DSBs such as (Chen et al., 2022a, FBSB). Beyond, we compare SBALIGN in the setting of learning a prior reference process. Naturally, cell division processes and subsequently the propagation of the barcodes are very noisy. While this genetic annotation provides some form of assignment, it does not capture the full developmental process. We thus test SBALIGN in a setting where it learns a prior from such partial alignments and, plugged into FBSB, is fine-tuned on the full dataset.

Evaluation metrics. To assess the performance of SBALIGN and the baselines, we monitor several metrics, which include distributional distances (MMD (Gretton et al., 2012) and W_ϵ (Cuturi, 2013)) as well as average scores (ℓ_2(PS) and RMSD). Moreover, we also train a simple neural network-based classifier to annotate the cell type on day 4 and we report the accuracy on the predicted vs. true cell type for all the models. See § C.1 for further details.

Results. SBALIGN accurately predicts cellular differentiation processes in hematopoiesis from day 2 to day 4, as visible from the (2D projections of the) learned trajectories and alignments (Fig. 3c) and the quantitative evaluation in Table 1. SBALIGN outperforms FBSB in all but the cell-type accuracy metric: Remarkably, our method exceeds the performances of the baseline also on distributional metrics and not uniquely on alignment-based ones. Further, we evaluate how well SBALIGN recovers the heterogeneity of emerging cell-types throughout the developmental process on day 4. The results are displayed in Fig. 4d and show that, while capturing the overall differentiation trend, SBALIGN (as well as FBSB) struggles to isolate rare cell types. Lastly, we employ SBALIGN to learn a prior process from noisy alignments based on genetic barcode annotations. When using this reference process within FBSB, we learn a SB which compensates for inaccuracies stemming from the stochastic nature of cell division and barcode redistribution and which achieves better scores on distributional metrics (see Tab. 1). Further results can be found in § A.

4.3 PROTEIN DOCKING

In (*computational*) protein docking, the goal is to predict the 3D structure of the bound (docked) state of a protein pair, given the unbound states of the corresponding proteins. These proteins are denoted (arbitrarily) as the ligand and receptor respectively. For the scope of this paper, and following previous work, we focus on the rigid docking setup. However, our algorithm can also be applied towards flexible protein docking, and we leave a full treatment of this problem to future work.

Experimental setup. Our setup follows a similar convention as EQUIDOCK (Ganea et al., 2022). To summarize, the unbound structure of the ligand is derived by applying a random rotation and translation to the corresponding bound structure, while the receptor is held fixed w.l.o.g. Applying a different rotation and translation to each ligand can however result in a different Brownian bridge for each complex, resulting in limited meaningful signal for learning b_t^θ. To

a. Ground Truth
1QA9

b. SBALIGN
Ours

c. EQUIDOCK
Ganea et al., (2022)

Figure 5: Ground truth and predicted bound structures for the complex with PDB ID: 1QA9. SBALIGN is able to find the true binding interface compared to EQUIDOCK.

avoid this, we sample a rotation and translation at the start of training, and apply the same rotation and translation to all complexes across training, validation and testing. Additional details regarding this setup can be found in § B.

Dataset. We use the DB5.5 dataset (Vreven et al., 2015) for our empirical evaluation. The DB5.5 dataset is a standard dataset used in protein-protein docking, however it only has 253 complexes. We utilize the same splits as EquiDock (Ganea et al., 2022), with 203 complexes in the training set, 25 complexes in the validation set and 25 complexes in the test set. For the evaluation in Table 2, we use the full DB5.5 test set. For ligands in the test set, we generate the corresponding unbound versions by applying the rotation and translation sampled during training.

Baselines. We compare our method to the GNN-based model EQUIDOCK as well as traditional docking software including ATTRACT (Schindler et al., 2017; de Vries et al., 2015), HDOCK (Yan et al., 2020), CLUSPRO (Desta et al., 2020; Kozakov et al., 2017) and PATCHDOCK (Mashiach et al., 2010; Schneidman-Duhovny et al., 2005). As mentioned in the paragraph above, for ligands in the test set, we generate the corresponding unbound versions by applying the rotation and translation sampled during training. We evaluate the trained model from EQUIDOCK and SBALIGN on these unbound structures, and report corresponding evaluation metrics. For the remaining baselines, we include the numbers from (Ganea et al., 2022). These baselines typically sample millions of candidate complexes by considering a discretized space of rotations. We expect this makes them somewhat invariant to arbitrary initialization, and the corresponding docking scores to not be severely impacted.

Evaluation metrics. We report two metrics, Complex Root Mean Square Deviation (Complex RMSD), and Interface Root Mean Square Deviation (Interface RMSD). Following (Ganea et al., 2022), the ground truth and predicted complex structures are first superimposed using the Kabsch algorithm (Kabsch, 1976), and the Complex RMSD is then computed between the superimposed versions. A similar procedure is used for computing Interface RMSD, but only using the residues from the two proteins that are within 8Å of each other. More details in § C.1.

Table 2: **Rigid docking results.** Complex and interface RMSD between predicted and true bound structures (after Kabsch alignment). * denotes methods for which we use values directly from (Ganea et al., 2022). All other results show the performance on our test set.

| | **DB5.5 Test Set** | | | | | |
| | Complex RMSD | | | Interface RMSD | | |
Methods	Median	Mean	Std	Median	Mean	Std
ATTRACT*	9.55	10.09	9.88	7.48	10.69	10.90
HDOCK*	0.30	5.34	12.04	0.24	4.76	10.83
CLUSPRO*	3.38	8.25	7.92	2.31	8.71	9.89
PATCHDOCK*	18.26	18.00	10.12	18.88	18.75	10.06
EQUIDOCK*	14.13	14.72	5.31	11.97	13.23	4.93
EQUIDOCK	14.12	14.73	5.31	11.97	13.23	4.93
SBALIGN	6.59	6.69	2.04	7.69	8.11	2.39

Results. The model performance is summarized in Table 2. Our method SBALIGN considerably outperforms EQUIDOCK across all metrics. SBALIGN also achieves comparable or better performance than traditional docking software without relying on extensive candidate sampling and re-ranking, or learning surface templates from parts of the current test set. An example of docked structures, in direct comparison with EQUIDOCK is displayed Figs. 5. Further visualizations and results can be found in § A.

5 CONCLUSION

In this paper, we propose a new framework to tackle the interpolation task with aligned data via Diffusion Schrödinger bridges. Our central contribution is a novel algorithmic framework derived from the Schrödinger bridge theory and Doob's h-transform. Via a combination of the two notions, we derive novel loss functions which, unlike all prior methods for solving Diffusion Schrödinger bridges, do not rely on the iterative proportional fitting procedure and are hence numerically stable. We verify our proposed algorithm on various synthetic and real-world tasks and demonstrate noticeable improvement over the previous state-of-the-art, thereby substantiating the claim that data alignment is a highly relevant feature that warrants further research.

References

Charlotte Bunne, Stefan G Stark, Gabriele Gut, Jacobo Sarabia del Castillo, Kjong-Van Lehmann, Lucas Pelkmans, Andreas Krause, and Gunnar Ratsch. Learning Single-Cell Perturbation Responses using Neural Optimal Transport. *bioRxiv*, 2021.

Charlotte Bunne, Andreas Krause, and Marco Cuturi. Supervised Training of Conditional Monge Maps. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022a.

Charlotte Bunne, Laetitia Meng-Papaxanthos, Andreas Krause, and Marco Cuturi. Proximal Optimal Transport Modeling of Population Dynamics. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 25, 2022b.

Charlotte Bunne, Ya-Ping Hsieh, Marci Cuturi, and Andreas Krause. The Schrödinger Bridge between Gaussian Measures has a Closed Form. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2023.

Tianrong Chen, Guan-Horng Liu, and Evangelos A Theodorou. Likelihood Training of Schrödinger Bridge using Forward-Backward SDEs Theory. In *International Conference on Learning Representations (ICLR)*, 2022a.

Wanze Chen, Orane Guillaume-Gentil, Pernille Yde Rainer, Christoph G Gäbelein, Wouter Saelens, Vincent Gardeux, Amanda Klaeger, Riccardo Dainese, Magda Zachara, Tomaso Zambelli, et al. Live-seq enables temporal transcriptomic recording of single cells. *Nature*, 608, 2022b.

Yongxin Chen, Tryphon T Georgiou, and Michele Pavon. Optimal Transport in Systems and Control . *Annual Review of Control, Robotics, and Autonomous Systems*, 4, 2021a.

Yongxin Chen, Tryphon T Georgiou, and Michele Pavon. Stochastic control liaisons: Richard Sinkhorn meets Gaspard Monge on a Schrödinger bridge. *SIAM Review*, 63 (2), 2021b.

Gabriele Corso, Hannes Stärk, Bowen Jing, Regina Barzilay, and Tommi Jaakkola. Diffusion Steps, Twists, and Turns for Molecular Docking. In *International Conference on Learning Representations (ICLR)*, 2023.

Marco Cuturi. Sinkhorn Distances: Lightspeed Computation of Optimal Transport. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 26, 2013.

Marco Cuturi, Laetitia Meng-Papaxanthos, Yingtao Tian, Charlotte Bunne, Geoff Davis, and Olivier Teboul. Optimal Transport Tools (OTT): A JAX Toolbox for all things Wasserstein. *arXiv Preprint arXiv:2201.12324*, 2022.

Valentin De Bortoli, James Thornton, Jeremy Heng, and Arnaud Doucet. Diffusion Schrödinger bridge with applications to score-based generative modeling. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, 2021.

Sjoerd J de Vries, Christina EM Schindler, Isaure Chauvot de Beauchêne, and Martin Zacharias. A web interface for easy flexible protein-protein docking with attract. *Biophysical journal*, 108(3):462–465, 2015.

Israel T Desta, Kathryn A Porter, Bing Xia, Dima Kozakov, and Sandor Vajda. Performance and its limits in rigid body protein-protein docking. *Structure*, 28(9):1071–1081, 2020.

Joseph Doob. *Classical potential theory and its probabilistic counterpart*, volume 549. Springer, 1984.

Mike Fisher, Jorge Nocedal, Yannick Trémolet, and Stephen J Wright. Data assimilation in weather forecasting: a case study in PDE-constrained optimization. *Optimization and Engineering*, 10(3), 2009.

Robert Fortet. Résolution d'un systeme d'équations de m. schrödinger. *J. Math. Pure Appl. IX*, 1:83–105, 1940.

Octavian-Eugen Ganea, Xinyuan Huang, Charlotte Bunne, Yatao Bian, Regina Barzilay, Tommi S. Jaakkola, and Andreas Krause. Independent SE(3)-equivariant models for end-to-end rigid protein docking. In *iclr*, 2022.

Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A Kernel Two-Sample Test. *Journal of Machine Learning Research*, 13, 2012.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising Diffusion Probabilistic Models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Lars Holdijk, Yuanqi Du, Ferry Hooft, Priyank Jaini, Bernd Ensing, and Max Welling. Path integral stochastic optimal control for sampling transition paths. *arXiv preprint arXiv:2207.02149*, 2022.

Wolfgang Kabsch. A solution for the best rotation to relate two sets of vectors. *Acta Crystallographica Section A: Crystal Physics, Diffraction, Theoretical and General Crystallography*, 32(5):922–923, 1976.

Dima Kozakov, David R Hall, Bing Xia, Kathryn A Porter, Dzmitry Padhorny, Christine Yueh, Dmitri Beglov, and Sandor Vajda. The cluspro web server for protein–protein docking. *Nature protocols*, 12(2):255–278, 2017.

Solomon Kullback. Probability densities with given marginals. *The Annals of Mathematical Statistics*, 39 (4):1236–1243, 1968.

Christian Léonard. A survey of the Schrödinger problem and some of its connections with optimal transport. *arXiv preprint arXiv:1308.0215*, 2013.

Guan-Horng Liu, Tianrong Chen, Oswin So, and Evangelos Theodorou. Deep generalized schrödinger bridge. In *Advances in Neural Information Processing Systems*, 2022a.

Guan-Horng Liu, Tianrong Chen, Oswin So, and Evangelos A Theodorou. Deep Generalized Schrödinger Bridge. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022b.

Xingchao Liu, Lemeng Wu, Mao Ye, and qiang Liu. Learning Diffusion Bridges on Constrained Domains. *International Conference on Learning Representations (ICLR)*, 2023.

Mohammad Lotfollahi, F Alexander Wolf, and Fabian J Theis. scGen predicts single-cell perturbation responses. *Nature Methods*, 16(8), 2019.

Roger Mansuy and Marc Yor. *Aspects of Brownian motion*. Springer Science & Business Media, 2008.

Efrat Mashiach, Dina Schneidman-Duhovny, Aviyah Peri, Yoli Shavit, Ruth Nussinov, and Haim J Wolfson. An integrated suite of fast docking algorithms. *Proteins: Structure, Function, and Bioinformatics*, 78(15):3197–3204, 2010.

Gabriel Peyré and Marco Cuturi. Computational Optimal Transport. *Foundations and Trends in Machine Learning*, 11(5-6), 2019. ISSN 1935-8245.

L Chris G Rogers and David Williams. *Diffusions, Markov processes and martingales: Volume 2, Itô calculus*, volume 2. Cambridge university press, 2000.

Geoffrey Schiebinger, Jian Shu, Marcin Tabaka, Brian Cleary, Vidya Subramanian, Aryeh Solomon, Joshua Gould, Siyan Liu, Stacie Lin, Peter Berube, et al. Optimal-Transport Analysis of Single-Cell Gene Expression Identifies Developmental Trajectories in Reprogramming. *Cell*, 176(4), 2019.

Christina EM Schindler, Isaure Chauvot de Beauchêne, Sjoerd J de Vries, and Martin Zacharias. Protein-protein and peptide-protein docking and refinement using attract in capri. *Proteins: Structure, Function, and Bioinformatics*, 85(3):391–398, 2017.

Dina Schneidman-Duhovny, Yuval Inbar, Ruth Nussinov, and Haim J Wolfson. Patchdock and symmdock: servers for rigid and symmetric docking. *Nucleic Acids Research*, 33, 2005.

Erwin Schrödinger. *Über die Umkehrung der Naturgesetze*. Verlag der Akademie der Wissenschaften in Kommission bei Walter De Gruyter u. Company, 1931.

Yang Song and Stefano Ermon. Generative Modeling by Estimating Gradients of the Data Distribution. In *arXiv Preprint*, 2019.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-Based Generative Modeling through Stochastic Differential Equations. In *International Conference on Learning Representations (ICLR)*, volume 9, 2021.

Vasileios Stathias, Anna M Jermakowicz, Marie E Maloof, Michele Forlin, Winston Walters, Robert K Suter, Michael A Durante, Sion L Williams, J William Harbour, Claude-Henry Volmar, et al. Drug and disease signature integration identifies synergistic combinations in glioblastoma. *Nature Communications*, 9(1), 2018.

Alexander Tong, Jessie Huang, Guy Wolf, David Van Dijk, and Smita Krishnaswamy. TrajectoryNet: A Dynamic Optimal Transport Network for Modeling Cellular Dynamics. In *International Conference on Machine Learning (ICML)*, 2020.

Alexander Tong, Nikolay Malkin, Guillaume Huguet, Yanlei Zhang, Jarrid Rector-Brooks, Kilian Fatras, Guy Wolf, and Yoshua Bengio. Conditional flow matching: Simulation-free dynamic optimal transport. *arXiv preprint arXiv:2302.00482*, 2023.

Tomer Tsaban, Julia K Varga, Orly Avraham, Ziv Ben-Aharon, Alisa Khramushin, and Ora Schueler-Furman. Harnessing protein folding neural networks for peptide–protein docking. *Nature communications*, 13(1):176, 2022.

Francisco Vargas, Pierre Thodoroff, Neil D Lawrence, and Austen Lamacraft. Solving Schrödinger Bridges via Maximum Likelihood. *arXiv Preprint*, 2021.

Thom Vreven, Iain H Moal, Anna Vangone, Brian G Pierce, Panagiotis L Kastritis, Mieczyslaw Torchala, Raphael Chaleil, Brian Jiménez-García, Paul A Bates, Juan Fernandez-Recio, et al. Updates to the integrated protein–protein interaction benchmarks: docking benchmark version 5 and affinity benchmark version 2. *Journal of Molecular Biology*, 427(19), 2015.

Caleb Weinreb, Alejo Rodriguez-Fraticelli, Fernando D Camargo, and Allon M Klein. Lineage tracing on transcriptional landscapes links state to fate during differentiation. *Science*, 367, 2020.

Yumeng Yan, Huanyu Tao, Jiahua He, and Sheng-You Huang. The hdock server for integrated protein–protein docking. *Nature protocols*, 15(5):1829–1852, 2020.

Qinsheng Zhang and Yongxin Chen. Path integral sampler: a stochastic control approach for sampling. *arXiv preprint arXiv:2111.15141*, 2021.