Continual adaptation for efficient machine communication

Abstract

To communicate with new partners in new contexts, humans rapidly form new linguistic conventions. Recent language models trained with deep neural networks are able to comprehend and produce the existing conventions present in their training data, but are not able to flexibly and interactively adapt those conventions on the fly as humans do. We introduce a repeated reference task as a benchmark for models of adaptation in communication and propose a regularized continual learning framework that allows an artificial agent initialized with a generic language model to more accurately and efficiently understand their partner over time. We evaluate this framework through simulations on COCO and in real-time reference game experiments with human partners.

Figure 1. Reference game task, listener architecture, and continual learning approach.

1. Introduction

Linguistic communication depends critically on shared knowledge about the meanings of words (Lewis, 1969). However, the real-world demands of communication often require speakers and listeners to go *beyond* dictionary meanings to understand one another (Clark, 1996; Stolk et al., 2016). The social world continually presents new communicative challenges, and agents must continually coordinate on new meanings to meet them.

For example, consider a nurse visiting a bed-ridden patient in a cluttered home. The first time they ask the nurse to retrieve a particular medication, the patient must painstakingly refer to unfamiliar pills, e.g. "my vasoprex-tecnoblek meds for blood pressure, in a small bluish bottle, on the bookcase in my bathroom." After a week of care, however, they may just ask for their "Vasotec."

This type of flexible language use poses a challenge for models of language in machine learning. Approaches based

on deep neural networks typically learn a monolithic meaning function during training, with fixed weights during use. For an in-home robot to communicate as flexibly and efficiently with patients as a human nurse, it must be equipped with a continual learning mechanism. Such a mechanism would present two specific advantages for interaction and communication applications. First, to the extent that current models have difficulty communicating in a new setting, an adaptive approach can quickly improve performance on the relevant subset of language. Second, for human-robot contexts, an adaptive model enables speakers to communicate more efficiently as they build up common ground, remaining understandable while expending significantly fewer words as humans naturally do (Clark & Wilkes-Gibbs, 1986).

In this paper, we introduce a general framework for transforming neural language models into *adaptive* models that can be deployed in real-time interactions with other agents.

Our key insight is that through continual interactions with the same partner in a shared context, a listener can adapt and more efficiently communicate with its partner (Fig. 1).

We are motivated by hierarchical Bayesian approaches to task-specific adaptation. Our approach integrates two core components: (i) a loss function combining speaker and listener information to understand descriptions of natural images in context, and (ii) a regularization scheme for fine-

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

tuning the weights of this model based on previous interactions with a partner. We show that these components enable more effective communication with human partners over repeated interactions.

2. Approach

We begin by recasting communication as a multi-task problem for meta-learning. Each context and communicative partner can be regarded as a related but distinct task making its own demands on the agent's language model. To be effective across many such tasks, a communicative agent must both (1) have a good prior representation they can use to understand novel partners and contexts, and (2) have a mechanism to rapidly update this representation from a small number of interactions.

2.1. Repeated reference game task

As a benchmark for studying this problem, we introduce the *repeated reference game* task (Fig. 1), which has been widely used in cognitive science to study partner-specific adaptation in communication (Krauss & Weinheimer, 1964; Clark & Wilkes-Gibbs, 1986; Wilkes-Gibbs & Clark, 1992). This task is a special case of the more general family of reference games, where a speaker agent is given a context of N images (a target object o among $N-1$ distractors) and must produce an utterance u that allows their partner, a listener agent, to identify o with high probability. In a *repeated reference game*, each image in context appears as the target multiple times, allowing us to evaluate how communication about a particular image changes as the speaker and listener build up a shared history.

2.2. Continual adaptation with Hierarchical Bayes

Before formalizing our algorithm as a generic update rule for neural networks, we describe the theoretical Bayesian foundations of our approach. At the core of any communication model is a notion of the *semantics* of language, which supplies the relationship between utterances and states of the world. Under a Bayesian approach, this representation can be viewed probabilistically: we represent some uncertainty over meanings. In a hierarchical Bayesian model, this uncertainty is structured over different partners and contexts.

At the highest level is a *task-general* variable Θ which parameterizes the agent's task-specific prior expectations $P(\theta_i|\Theta)$ where θ_i represents the semantics used by a novel partner i. Given observations D_i from communicative interactions in that context, an agent can update their *task-specific* model using Bayes rule:

$$P(\theta_i|D_i, \Theta) \propto P(D_i|\theta_i)P(\theta_i|\Theta) \qquad (1)$$

The Bayesian formulation thus decomposes the problem of task-specific adaptation into two terms, a prior term $P(\theta_i|\Theta)$ and a likelihood term $P(D_i|\theta_i)$. The prior captures the idea that different language tasks share some task-general structure in common: in the absence of strong information about usage departing from this common structure, the agent ought to be regularized toward their task-general knowledge.

The likelihood term accounts for needed deviations from general knowledge due to evidence from the current situation. The form of the likelihood depends on the task at hand. For the referential communication task we consider here, $D_i = \{(u, o)_t\}$ contains paired observations of utterances u and their objects of reference o at time t. These data can be viewed from the point of view of a speaker (generating u given o) or a listener (choosing o from a context of options, given u) (Smith et al., 2013; Hawkins et al., 2017); these yield different likelihoods that update the semantics in complementary ways. The generative model of a *speaker* uses the task-specific semantics θ_i to sample utterances u proportional to how well they apply to o:

$$P_S(u|o, \theta_i) \propto \exp f_{\theta_i}(u, o) \qquad (2)$$

A *listener* can be modeled as inverting this speaker model to evaluate how well an utterance u describes each object o *relative to the others* in a context $\mathcal{C}$ of objects by normalizing (Frank & Goodman, 2012; Vedantam et al., 2017; Cohn-Gordon et al., 2018; Monroe et al., 2017):

$$P_L(o|u, \mathcal{C}, \theta_i) \propto P_S(u|o, \theta_i)P(o) \qquad (3)$$

Because these views of the data from past interactions D_i provide complementary statistical information about the task-specific semantics θ_i, we will combine them in our loss.

2.3. Continual adaptation for neural language models

There is a deep theoretical connection between the hierarchical Bayesian framework presented in the previous section and recent deep learning approaches to multi-task learning (Nagabandi et al., 2018; Grant et al., 2018; Jerfel et al., 2018). Given a task-general initialization, regularized gradient descent on a particular task is equivalent to conditioning on new data under a Bayesian prior. We exploit this connection to propose an online continual learning scheme for a neural listener model that can adapt to a human speaker in a challenging referential communication task.

Concretely, we consider an image-captioning network that combines a convolutional visual encoder (ResNet-152) with an LSTM decoder (Vinyals et al., 2015). The LSTM takes a 300-dimensional embedding as input for each word in an utterance and then uses a softmax layer to linearly project back to a distribution over the vocabulary size. An adapter replacing the final fully connected layer of the encoder was

Algorithm 1 Update step for adaptive language model

Input: θ_t: weights at time t
Output: θ_{t+1}: updated weights
Data: (u_t, o_t): observed utterance and object at time t
for step **do**
  sample augmented batch of sub-utterances $\mathbf{u} \sim \mathcal{P}(u)$
  update $\theta_t \leftarrow \theta_t + \beta\nabla[P(\mathbf{u}|o) + P(o|\mathbf{u}) + \mathrm{reg}(o, u)]$
end for

jointly pre-trained with the decoder on the COCO training captions and then frozen as our task-general initialization Θ. For each utterance-object data point observed in the current task, we take a small number of gradient steps fine-tuning the decoder's weights to better account for the speaker's usage (see Algorithm 1). We consider several loss terms and techniques to do so.

Speaker and listener likelihood. The primary signal available for adaptation is the (log-) probability of the new data under speaker and listener likelihoods given in Eqns. 2-3. Our speaker likelihood serves to make the observed utterance more likely for the target in *isolation*, while our listener likelihood makes it more likely *relative* to other objects in context. The speaker and listener likelihoods can be computed directly from the neural captioning model, where each word is distributed according to a softmax over the LSTM output given the sentence so far.

Regularization. We introduce three kinds of regularization terms to approximate the Bayesian prior on task-specific learning. First, rather than directly regularizing weights, a *speaker KL regularization* term minimizes the divergence between the captioning model's output probabilities before and after fine-tuning (Yu et al., 2013; Galashov et al., 2018). Since the support for our distribution of captions are infinite, we approximate the divergence incrementally by expanding from the maximum a posteriori (MAP) word at each step according to P, where P represents the model at initialization and Q_t represents the model at time t. This loss is then averaged across random images from the full domain $\mathcal{O}$, not just those in context:

$$\sum_{o \sim \mathcal{O}} \sum_i D_{\mathrm{KL}}\left(P(w_i|o, w_{i-1}^{\mathrm{MAP}})||Q_t(w_i|o, w_{i-1}^{\mathrm{MAP}})\right) \quad (4)$$

Second, we derive a *listener KL regularization* term which compares the initial listener distribution over objects in context $o \in \mathcal{C}$ with the fine-tuned model's distribution: $D_{\mathrm{KL}}\left(P(o|u)||Q_t(o|u)\right)$. The third form of regularization we consider is *local rehearsal*. We evaluate our listener likelihood over prior observations $(u, o) \in D_i$ to prevent overfitting to the most recent observation. To capture how the likelihood overwhelms the prior with increasing data in Bayesian updating, we anneal the listener regularization and rehearsal over the course of interaction while reverse-

annealing the listener likelihood.

Data augmentation. A final component of our algorithm is the introduction of a data augmentation step on the new utterance u. Ideally, an adaptive agent should learn that sub-components of the observed utterance are compositionally responsible for this meaning. We thus derive a small training dataset $D(u)$ from u; for simplicity, we take the (ordered) powerset $D(u) = \mathcal{P}(u)$ of all sub-utterances.[1]

3. Evaluations

To evaluate our model, we implemented a repeated reference game using images from the validation set of COCO (Lin et al., 2014) as the targets of reference. To construct challenging contexts $\mathcal{C}$, we used our pre-trained visual encoder to find sets of highly similar images. We extracted feature vectors for each image, partitioned the images into 100 groups using a k-means algorithm, sampled one image from each cluster, and took its 3 nearest neighbors in feature space, yielding 100 unique contexts of 4 images each[2].

3.1. Human baselines

We first investigated the baseline performance of human speakers and listeners. We recruited 113 participants from Amazon Mechanical Turk and automatically paired them into an interactive environment with a chatbox. For each of these 56 pairs, we sampled a context and constructed a sequence of 24 trials structured into 6 repetition blocks, where each of the 4 images appeared as the target once per block. We prevented the same target appearing twice in a row and scrambled the order of the images on each player's screen on each trial.

We found that pairs of humans were remarkably accurate at this task, with performance near ceiling on every round. At the same time, they grew increasingly efficient in their communication: the utterance length decreased from an average of 7 words per image on the first repetition to only 3 words on the last. A mixed-effects regression with random slopes and intercepts accounting for variability at the pair- and context-level found a significant decrease in utterance length across repetitions, $t = -5.8, p < 0.001$ (Fig. 2A).

3.2. Model evaluation with human partner

Next, we evaluated how our adaptive listener performed in *real-time interaction* with human speakers. We recruited 45 additional participants from Amazon Mechanical Turk who were told they would be paired with an artificial agent

---

[1]Grammatical acceptability could in principle be taken into account using alternative sets derived from a syntactic parse.

[2]Using pre-trained VGG as the encoder gave qualitatively similar contexts.

Figure 2. (A) Human speakers grow more efficient and accurate as our model adapts. Curves show regression fits. (B) Speaker KL regularization prevents catastrophic forgetting. (C) Lesions reveal the contributions of each loss term. Error bars and ribbons are bootstrapped 95% CIs.

learning how they talk. This task was identical to the one performed by humans, except participants were only allowed to enter a single message through the chatbox on each trial. This message was then sent to a GPU where the model weights from the previous trial were loaded, used to generate a response, and updated in real-time for the next round. The approximate latency for the model to respond was 6-8 seconds.

We used a batch size of 8, learning rate of 0.0005, and took 8 gradient steps after each trial. For our loss objective, we used a linear combination of the speaker likelihood loss, listener likelihood loss, and all three regularization terms. We found that a listener based on a pre-trained neural captioning model—the initialization for our adapting model—performs much less accurately than humans due to the challenging nature of the reference task. Yet our model rapidly improves in accuracy as it coordinates on appropriate meanings with human speakers. Similarly, while speakers did not simplify their utterances to the same extent as they did with other humans, perhaps due to early feedback about errors, they nonetheless became significantly more efficient over time, $b = -19, t = -5$ (see Fig. 2A).

4. Analysis

We proceed to a series of lesion analyses that analyze the role played by each component of our approach.

4.1. Preventing catastrophic forgetting

Fine-tuning repeatedly on a small number of data points presents a clear risk of catastrophic forgetting (Robins, 1995), losing our ability to produce utterances for other images. Our speaker KL regularization (Eqn. 4) was intended to play the same role as a Bayesian prior, preventing catastrophic forgetting by tethering task-specific behavior to the task-general model. To test the effectiveness of this term, we examined the likelihood of different captions before and after adaptation to the human baseline utterances.

First, we sampled a random set of images from COCO that were not used in our experiment as *control* images, and used the initialized state of the LSTM to greedily generate a caption for each. We also generated initial captions for the *target* objects in context. We recorded the likelihood of all of these sampled captions under the model at the beginning and at each step of adaptation until the final round. Finally, we greedily generated an utterance for each target at the end and retrospectively evaluated its likelihood at earlier states. These likelihood curves are shown with and without speaker KL regularization in Fig. 2B. The final caption becomes more likely in both cases; without the KL term, the initial captions for both targets and unrelated controls are (catastrophically) lost.

4.2. Lesioning loss terms

We next simulated our adaptive listener's performance hearing utterances from the human baseline under lesioned losses (Fig. 2C). We found that rehearsal on previous rounds had the largest qualitative benefit, allowing for faster adaptation on early rounds, while data augmentation and the non-rehearsal listener terms provided small boosts later in the game. Compared to a non-adapting baseline, however, even a simple loss only containing the speaker likelihood and speaker KL regularization performed better over time—successfully adapting to human language use.

5. Conclusions

Human language use is flexible, continuously adapting to the needs of the current situation. In this paper, we introduced a challenging repeated reference game benchmark for artificial agents, which requires such adaptability to succeed. We proposed a continual learning approach that forms context-specific conventions by adapting general-purpose semantic knowledge. Even when models based on general-purpose knowledge perform poorly, our approach allows human speakers working with adapted variants of such models to become more accurate and more efficient over time.

References

Clark, H. H. *Using language*. Cambridge university press, 1996.

Clark, H. H. and Wilkes-Gibbs, D. Referring as a collaborative process. *Cognition*, 22(1):1–39, 1986.

Cohn-Gordon, R., Goodman, N., and Potts, C. Pragmatically Informative Image Captioning with Character-Level Reference. *arXiv preprint arXiv:1804.05417*, 2018.

Frank, M. C. and Goodman, N. D. Predicting pragmatic reasoning in language games. *Science*, 336(6084):998–998, 2012.

Galashov, A., Jayakumar, S. M., Hasenclever, L., Tirumala, D., Schwarz, J., Desjardins, G., Czarnecki, W. M., Teh, Y. W., Pascanu, R., and Heess, N. Information asymmetry in KL-regularized RL. In *ICLR*, 2018.

Grant, E., Finn, C., Levine, S., Darrell, T., and Griffiths, T. Recasting Gradient-Based Meta-Learning as Hierarchical Bayes. *arXiv preprint arXiv:1801.08930*, 2018.

Hawkins, R. X. D., Frank, M. C., and Goodman, N. D. Convention-formation in iterated reference games. In *Proceedings of the 39th annual meeting of the cognitive science society*, 2017.

Jerfel, G., Grant, E., Griffiths, T. L., and Heller, K. Online gradient-based mixtures for transfer modulation in meta-learning. *arXiv:1812.06080*, 2018.

Krauss, R. M. and Weinheimer, S. Changes in reference phrases as a function of frequency of usage in social interaction: A preliminary study. *Psychonomic Science*, 1(1-12):113–114, 1964.

Lewis, D. *Convention: A philosophical study*. Harvard University Press, 1969.

Lin, T.-Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., and Zitnick, C. L. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Monroe, W., Hawkins, R. X. D., Goodman, N. D., and Potts, C. Colors in Context: A Pragmatic Neural Model for Grounded Language Understanding. *arXiv preprint arXiv:1703.10186*, 2017.

Nagabandi, A., Finn, C., and Levine, S. Deep Online Learning via Meta-Learning: Continual Adaptation for Model-Based RL. *arXiv:1812.07671*, 2018.

Robins, A. Catastrophic forgetting, rehearsal and pseudorehearsal. *Connection Science*, 7(2):123–146, 1995.

Smith, N. J., Goodman, N., and Frank, M. Learning and using language via recursive pragmatic reasoning about other agents. In *Advances in neural information processing systems*, pp. 3039–3047, 2013.

Stolk, A., Verhagen, L., and Toni, I. Conceptual alignment: How brains achieve mutual understanding. *Trends in cognitive sciences*, 20(3):180–191, 2016.

Vedantam, R., Bengio, S., Murphy, K., Parikh, D., and Chechik, G. Context-aware Captions from Context-agnostic Supervision. *arXiv preprint arXiv:1701.02870*, 2017.

Vinyals, O., Toshev, A., Bengio, S., and Erhan, D. Show and Tell: A Neural Image Caption Generator. In *CVPR*, pp. 3156–3164, 2015.

Wilkes-Gibbs, D. and Clark, H. H. Coordinating beliefs in conversation. *Journal of memory and language*, 31(2): 183–194, 1992.

Yu, D., Yao, K., Su, H., Li, G., and Seide, F. Kl-divergence regularized deep neural network adaptation for improved large vocabulary speech recognition. In *2013 IEEE International Conference on Acoustics, Speech and Signal Processing*, pp. 7893–7897. IEEE, 2013.