COSFORMER : RETHINKING SOFTMAX IN ATTENTION

ABSTRACT

Transformer has shown great successes in natural language processing, computer vision, and audio processing. As one of its core components, the softmax attention helps to capture long-range dependencies yet prohibits its scale-up due to the quadratic space and time complexity to the sequence length. Kernel methods are often adopted to reduce the complexity by approximating the softmax operator. Nevertheless, due to the approximation errors, their performances vary in different tasks/corpus and suffer crucial performance drop when comparing with the vanilla softmax attention. In this paper, we propose a linear transformer called COS-FORMER that can achieve comparable or better accuracy to the vanilla transformer in both casual and cross attentions with linear space and time complexity. We achieve this by replacing the softmax operator with a linear operator and applying a *cosine*-based distance re-weighting mechanism on the attention matrix. Extensive experiments on language modeling and text understanding tasks demonstrate the effectiveness of our method. We further exam our method on long sequences and achieve state-of-the-art performance on the *Long-Range Arena* benchmark.

1 INTRODUCTION

With years of development, the transformer model (Vaswani et al., 2017) and its variants (Zaheer et al., 2020; Wang et al., 2020; Tay et al., 2020a) have been successfully adapted to three most popular artificial intelligence (AI) fields: *ie.,* natural language processing (Devlin et al., 2019; Liu et al., 2019), computer vision (Dosovitskiy et al., 2020; Carion et al., 2020; Liu et al., 2021) and audio processing (Schneider et al., 2019; Baevski et al., 2020). Compared with conventional recurrent (Hochreiter & Schmidhuber, 1997) and convolutional

Figure 1: Performance (*y* axis), speed (*x* axis), and memory footprint (circle sizes) of efficient transformers. The proposed *CosFormer* achieves an all-around supremacy over competing methods in the top left quadrant.

architectures (He et al., 2016), transformer-based architectures are generally more scalable to data volumes (Brown et al., 2020) and stronger in capturing global information with less inductive bias, thus excelling on many tasks and applications.

Dot-product attention with softmax normalization is the cornerstone of the transformer to capture long-range dependencies. However, its quadratic space and time complexity with regard to the length of the sequence make its computational overhead prohibitive, especially for long inputs. To address this issue, numerous methods are proposed recently, such as the sparse attention matrix (Zaheer et al., 2020; Beltagy et al., 2020; Tay et al., 2020a; Kitaev et al., 2020; Child et al., 2019),low-rank representations (Wang et al., 2020) or kernel-based methods (Peng et al., 2020; Choromanski et al., 2020; Katharopoulos et al., 2020), among many others. These methods achieve reduced computational complexity with comparable performances when compared with the vanilla attention architecture.

However, the improved efficiency is usually achieved via introducing additional yet often impractical assumptions on the attention matrix (Wang et al., 2020) or with valid approximation of softmax operation only within constrained theoretical bounds (Choromanski et al., 2020; Peng et al., 2020) Therefore, when their assumptions are unsatisfied or when approximation errors get accumulated, these methods may not always be advantageous over the vanilla architecture (Narang et al., 2021). Consequently, performance deficiencies in a broad application spectrum are often observed in these transformer variants, especially those with linear complexity. For example, the Performer (Choromanski et al., 2020), RFA (Peng et al., 2020) and Reformer (Kitaev et al., 2020) show less satisfactory performance on the GLUE benchmark (Wang et al., 2018) when compared with the vanilla architecture as suggested in our preliminary experiments (Tab. 2). Furthermore, many of these aforementioned methods are not applicable to casual attentions, which are critical for auto-regressive training. For example, techniques proposed in Linformer (Wang et al., 2020) and BigBird (Zaheer et al., 2020) are specific to cross attentions.

Since the softmax operator appears to be the main hurdle while efficient yet accurate approximation to softmax is difficult to achieve, one question naturally arises: "*Can we replace the softmax operator with a linear function instead, while maintaining its key properties?*". By digging into the softmax attention, we find two key properties that affect its empirical performance: (i) elements in the attention matrix are non-negative; (ii) the non-linear re-weighting scheme acts as a stabilizer for the attention weights (Titsias, 2016; Gao & Pavel, 2017; Jang et al., 2016). These findings reveal some new insights of the current approaches. For example, the linear transformer (Katharopoulos et al., 2020) achieves property (i) using an exponential linear unit (Clevert et al., 2016) activation function. However, due to lack of the re-weighting scheme, it underperforms other efficient transformer variants on the Long-Range Arena benchmark as shown in Figure 1 as well as the language modeling task (Table 2) based on our controlled experiments.

In this paper, we propose a new variant of linear transformer called COSFORMER that satisfies both of the above properties. Specifically, we enforce the non-negative property by passing the features to a ReLU (Agarap, 2018) activation function before computing the similarity scores. In this way, we encourage the model to avoid aggregating negatively-correlated contextual information. Further, we adopt a *cos* re-weighting scheme to stabilize the attention weights. This helps the model to amplify local correlations, which usually contain more relevant information for natural language tasks. Thanks to the Ptolemy's theorem, our attention can be *exactly* decomposed into a linear form. We perform extensive experiments on both autoregressive language models and bidirectional models on five public benchmarks, including WikiText-103 (Merity et al., 2017), GLUE (Wang et al., 2018), IMDB (Maas et al., 2011), AMAZON (Ni et al., 2019) and Long-Range Arena benchmark (Tay et al., 2020b). Our model shows much better inference speed and smaller memory footprint, while achieving on par performance with the vanilla transformer. It is noteworthy that our method ranks 1[st] on the Long-Range Arena benchmark, showing favorable performance than other competitors, some with even non-linear complexity, which well demonstrates its strong capacity in modeling long sequence inputs.

2 RELATED WORK

This section will introduce the existing works on improving the efficiency of Transformers, they can be broadly divided into two categories, *Pattern based methods* and *Kernel based methods*.

Pattern based method Pattern based methods sparsify the attention matrix with handcrafted or learnable patterns. Child et al. (2019) reduces the complexity by applying combination of strided pattern and local pattern to the vanilla attention matrix. Longformer (Beltagy et al., 2020) designs fixed diagonal sliding windows combined with global window, and the sliding window pattern can also be extended with dilation to enlarge the receptive field. Zaheer et al. (2020) presents a more powerful and expressive sparse attention mechanism, which combines multiple types of attention patterns and gives a thorough study of sparse attention mechanism. Instead of fixed patterns, Kitaev et al. (2020) group the attention computation process into buckets by local sensitive hashing. Nevertheless, *Pattern based methods* can only cope with sequences up to a certain length, and the computational complexity still grows rapidly when the input sequence becomes longer.

Kernel based method When faced with longer input sequences, it is more efficient to directly reduce the complexity of the theoretical calculation method. *Kernel based methods* speed up self-attention by reducing the computation complexity of self-attention from quadratic to linear. Peng et al. (2020) chooses to use the production of Gaussian kernel functions to approximate *Softmax*, changing the order of scale dot product calculation, thus reducing the theoretical time to linear complexity and (Choromanski et al., 2020) uses Haar measurement based kernel instead. (Wang et al., 2020) imports the low-rank prior for attention matrix and approximate *softmax* with SVD decomposition manner. (Katharopoulos et al., 2020) formalizes the transformer layer as a recurrent neural network.

Here, we show that the approximation to *Softmax* is unneccessary for Linearization of self-attention module. We instead propose a new method to replace *Softmax* with a linear operation with reweight matrix, which reduces both time complexity and space complexity to $O(N)$ while ensuring the validity of the results.

3 OUR METHOD

In this section, we provide technique details of our linear transformer called COSFORMER . The key insight of the COSFORMER is to replace the non-decomposable non-linear softmax operation by a linear operation with decomposable non-linear re-weighting mechanism. Our model is applicable to both casual and cross attentions with a linear time and space complexity with regard to the input sequence length, thus exhibiting strong capacity in modeling long-range dependencies.

3.1 THE GENERAL FORM OF TRANSFORMER

Given an input sequence x with length of N, we first represent it in the embedding space $x \in \mathbb{R}^{N \times d}$ with feature dimension of d. A transformer block $\mathcal{T} : \mathbb{R}^{N \times d} \to \mathbb{R}^{N \times d}$ with input x is defined as:

$$\mathcal{T}(x) = \mathcal{F}(\mathcal{A}(x) + x), \tag{1}$$

where $\mathcal{F}$ is a feedforward network that contains a residual connection; $\mathcal{A}$ is the self-attention function that computes the attention matrix A, which has quadratic space and time complexity with respect to N, thus becoming the computation bottleneck of $\mathcal{T}$ on long inputs.

There are three key components in $\mathcal{A}$, namely, *query* (Q), *key* (K), *value* (V) computed through three learnable linear matrices W_Q, W_K, W_V: $Q = xW_Q, K = xW_K, V = xW_V$. We use M_i to represent the i-th row of a matrix M, then the output $\mathcal{O} \in \mathbb{R}^{N \times d}$ of $\mathcal{A}(x)$ can be computed as:

$$\mathcal{O} = \mathcal{A}(x) = [\mathcal{O}_1, \dots, \mathcal{O}_N]^T, \quad \mathcal{O}_i = \sum_j \frac{\mathcal{S}(Q_i, K_j)}{\sum_j \mathcal{S}(Q_i, K_j)} V_j, \tag{2}$$

where $\mathcal{S}(\cdot)$ measures the similarity between queries. If $\mathcal{S}(Q, K) = \exp(QK^T)$, the Eq. 2 becomes the dot-product attention with softmax normalization. In this case, the space and time complexity to compute one row of the output $\mathcal{O}_i$ is $O(N)$. Therefore, the total space and time complexity for computing $\mathcal{O}$ grows quadratically with respect to the input length.

3.2 LINEARIZATION OF SELF-ATTENTION

According to Eq. 2, we can select any similarity functions to compute the attention matrix. In order to maintain a linear computation budget, one solution is to adopt a decomposable similarity function such that:

$$\mathcal{S}(Q_i, K_j) = \phi(Q_i)\phi(K_j)^T, \tag{3}$$

where ϕ is a kernel function that maps the queries and keys to their hidden representations. Then one can rewrite Eq. 2 in the form of kernel functions as:

$$O_i = \frac{\sum_{j=1}^{N}(\phi(Q_i)\phi(K_j)^T)V_j}{\sum_{j=1}^{N}(\phi(Q_i)\phi(K_j)^T)} ., \tag{4}$$

After that, attention operation in linear complexity is achieved via the matrix product property:

$$(\phi(Q)\phi(K)^T)V = \phi(Q)(\phi(K)^T V). \tag{5}$$

Figure 2: Illustration of the computations for vanilla self attention (left) and linearized attention (right). The input length is N and feature dimension is d, with $d \ll N$. Tensors in the same box are associated for computation. The linearized formulation allows $O(N)$ time and space complexity.

In this form (Eq. 5), instead of explicitly computing the attention matrix $A = QK^T \in \mathbb{R}^{N \times N}$, we calculate the $\phi(K)^T V \in \mathbb{R}^{d \times d}$ first, and then multiplying $\phi(Q) \in \mathbb{R}^{N \times d}$. By using this trick, we only incurs a computation complexity of $O(Nd)$. Note that in typical natural language tasks, the feature dimension of one head d is always much smaller than the input sequence length N ($d \ll N$), so we can safely omit d and achieve computation complexity of $O(N)$, as illustrated in Figure 2.

Previous Solutions As aforementioned, the key to the linear attentions is to find a decomposable similarity function $\mathcal{S}(\cdot)$ that generalizes well to different tasks. Most existing linear transformers are trying to find an unbiased estimation of the softmax attention. For example, RFA (Peng et al., 2020) approximates the softmax operation with random feature maps using theorem of random fourier features (Rahimi & Recht, 2008) and the Performer (Choromanski et al., 2020) utilizes positive random features to approximate it. However, we empirically find that these methods are sensitive to the selection of sampling rate and becomes unstable if the sampling rate gets too high. Also, to accommodate recency bias, gating mechanisms are employed to better exploit more recent context.

Another group of works attempt to directly replace the softmax with a linear operation. For example, the linear transformer (Katharopoulos et al., 2020) model replaces the softmax similarity function with a pure dot product $\mathcal{S} = QK^T$, and use a non-linear activation function $\phi(\cdot) = \mathrm{elu}(\cdot) + 1$ to model the pairwise relation between features. However, our controlled experiments show that their solution does not necessarily generalize well on many downstream tasks (Tab. 2) or the Long-Range Arena benchmark (Tab. 4). In this paper, we propose a new replacement of softmax that not only achieves comparable or better performance than the softmax attention in a wide range of tasks, but also enjoys linear space and time complexity.

3.3 ANALYSIS OF SOFTMAX ATTENTION

In the vanilla transformer architecture, when $\mathcal{S}(Q, K) = \exp(QK^T)$, the softmax operation is applied to obtain row-wise normalization on the attention matrix $A \in \mathbb{R}^{N \times N}$ as shown in the Eq. 2. In other words, we normalize the relations of each element in the input sequence to all other elements in order to obtain a weighted aggregation of contextual information. However, apart from the good empirical performance of softmax attention, what are the crucial and necessary characteristics of it remain only loosely determined in the original transformer paper and follow-up works.

In this work, we empirically identify two key properties of the softmax operation that may play important roles for its performance: 1) it ensures all values in the attention matrix A to be non-negative; 2) it provides a non-linear re-weighting mechanism to concentrates the distribution of attention connections and stabilizes the training(Titsias, 2016; Gao & Pavel, 2017; Jang et al., 2016).

To validate these assumptions, we design the following preliminary studies as shown in Table 1. First, to validate the importance of non-negativity, we compare two instantiations of the function ϕ: an identify mapping $\phi_{\mathbf{I}} = \mathbf{I}$ that does

Table 1: Analysis of the softmax properties. All attention variants are implemented in the RoBERTa (Liu et al., 2019) architecture and are pre-trained on the WikiText-103 (Merity et al., 2017) dataset. The Loss represents the validation loss. We then fine-tune these variants on each downstream datasets and show the accuracy (the higher the better).

	Loss	QQP	SST-2	MNLI
$\phi_{\mathbf{I}}$	2.343	84.23	76.26	58.27
ϕ_{ReLU}	1.993	88.86	89.90	77.86
softmax	1.915	88.41	92.31	79.15

not preserve the non-negativity, and the other variant $\phi_{\mathrm{ReLU}(\cdot)} = \mathrm{ReLU}(\cdot)$ that retains only positive input values while replacing negative values to zeros. We use identity mapping as the similarity function for this controlled setup in order to localize sources of performance difference. Second, to demonstrate the effect of non-linear re-weighting, we compare the models using only $\phi_{\mathrm{ReLU}(\cdot)}$ without any re-weighting and those with softmax operations. From Table 1, the superior results of ϕ_{ReLU} over $\phi_{\mathbf{I}}$ demonstrate the benefit of retaining non-negative values. Our conjecture is that by retaining only positive values in the similarity matrices, the model ignores features with negative correlations, thus effectively avoiding aggregating irrelevant contextual information. By comparing the results of ϕ_{ReLU} with and without softmax, we observe that models with softmax re-weighting converge faster and generalize better to downstream tasks. This might be explained as softmax normalization amplifies the correlated pairs, which might be useful to identify useful patterns.

3.4 COSFORMER

Based on the observations above, we propose our model COSFORMER , which discards entirely the softmax normalization while still features the non-negativity and re-weighting mechanism. Our COSFORMER consists two main components: a linear projection kernel ϕ_{linear} and a *cos*-Based Re-weighting mechanism. Below we describe details of each components:

Linear projection kernel $\phi_{\mathbf{linear}}$ Recall the general form of the attention in Eq. 2, let us define a linear similarity as:

$$\mathcal{S}(Q, K) = \mathrm{s}(\phi_{\mathrm{linear}}(Q), \phi_{\mathrm{linear}}(K)) = \mathrm{s}(Q^{'}, K^{'}) \tag{6}$$

where ϕ_{linear} is the transformation function that map queries Q and keys K to our desired representations $Q^{'}$ and $K^{'}$, and s is a function that can be linearly decomposed to measure the similarity between $Q^{'}$ and $K^{'}$. Specifically, in order to ensure a full positive attention matrix A and avoid aggregating negatively-correlated information, we adopt $\mathrm{ReLU}(\cdot)$ as the transformation functions and therefore effectively eliminate negative values:

$$\phi_{\mathrm{linear}}(x) = \mathrm{ReLU}(x) \tag{7}$$

As $Q^{'}$ and $K^{'}$ contain only non-negative values, we directly take their dot-product $s(x, y) = xy^T, x, y \in \mathbb{R}^{1 \times d}$ followed by a row-wise normalization to compute attention matrices:

$$\mathcal{O}_i = \frac{\sum_{j=1}^N f(\phi_{\mathrm{linear}}(Q_i), \phi_{\mathrm{linear}}(K_j)) V_j}{\sum_{j=1}^N f(\phi_{\mathrm{linear}}(Q_i), \phi_{\mathrm{linear}}(K_j))} = \frac{\sum_{j=1}^N (\mathrm{ReLU}(Q_i) \mathrm{ReLU}(K_j)^T) V_j}{\sum_{j=1}^N (\mathrm{ReLU}(Q_i) \mathrm{ReLU}(K_j)^T)} \tag{8}$$

Based on Eq. 4, we rearrange the order of dot-product and obtain the formulation of the proposed attention in linear complexity as:

$$\mathcal{O}_i = \frac{\mathrm{ReLU}(Q_i) \sum_{j=1}^N \mathrm{ReLU}(K_j)^T V_j}{\mathrm{ReLU}(Q_i) \sum_{j=1}^N \mathrm{ReLU}(K_j)^T} \tag{9}$$

***cos*-Based Re-weighting Mechanism** The non-linear re-weighting mechanism introduced by the softmax attention can concentrate the distribution of the attention weights and therefore stabilize the training process (Titsias, 2016; Gao & Pavel, 2017; Jang et al., 2016). It also means that, to some extent, it will punish far-away connections and enforce locality. In fact, such locality bias, *ie.,* a large portion of contextual dependencies are from neighboring tokens, is commonly observed on downstream natural language tasks (Clark et al., 2019; Kovaleva et al., 2019), as shown in Figure 3 (1).

Based on the assumption above, what we need to fulfill the second property of softmax may be a decomposable re-weighting mechanism that can introduce recency bias to the attention matrix. Here, we propose a *cos*-based re-weighting mechanism as it perfectly fit our purpose: 1). the Ptolemy's theorem ensures the cos weights can be decomposed into two summations; 2). as shown in Figure 3 (4), the cos will put more weights on the neighbouring tokens and therefore enforces locality. Also, by comparing the attention matrices in Figure 3 (2) and (3), the COSFORMER enforces more locality than the one without the re-weighting mechanism.

Specifically, by combining with Eq 6, the model with cosine re-weighting is defined as:

$$s(Q_i^{'}, K_j^{'}) = Q_i^{'} K_j^{'T} \cos\left(\frac{\pi}{2} \times \frac{i-j}{M}\right) \tag{10}$$

| (1)Vanilla Transformer | (2)cosFormer | (3)cosFormer (w/o re-weighting) | (4)*cos* re-weighting matrix |

Figure 3: (1): Attention matrix of vanilla transformer.(2):Attention matrix of COSFORMER .(3): Attention matrix of COSFORMER without re-weighting. (4): Visualization of the *cos*-based distance matrix. After re-weighting, we can see a smoother attention distribution along the diagonal region of attention matrix, exhibiting a similar pattern to the vanilla transformer, which assists to stabilize the training.

By leveraging the Ptolemy's theorem, we decompose this formulation as:

$$Q_i^{'}K_j^{'T}\cos\left(\frac{\pi}{2}\times\frac{i-j}{M}\right) = Q_i^{'}K_j^{'T}\left(\cos\left(\frac{\pi i}{2M}\right)\cos\left(\frac{\pi j}{2M}\right)+\sin\left(\frac{\pi i}{2M}\right)\sin\left(\frac{\pi j}{2M}\right)\right)$$

$$= \left(Q_i^{'}\cos\left(\frac{\pi i}{2M}\right)\right)\left(K_j^{'}\cos\left(\frac{\pi j}{2M}\right)\right)^T + \left(Q_i^{'}\sin\left(\frac{\pi i}{2M}\right)\right)\left(K_j^{'}\sin\left(\frac{\pi j}{2M}\right)\right)^T$$

where $i, j = 1, ..., N, M \geq N$, and $Q^{'} = \text{ReLU}(Q), K^{'} = \text{ReLU}(K)$. Let $Q_i^{\cos} = Q_i^{'}\cos\left(\frac{\pi i}{2M}\right)$, $Q_i^{\cos} = Q_i^{'}\cos\left(\frac{\pi i}{2M}\right)$, $K_j^{\cos} = K_j^{'}\cos\left(\frac{\pi j}{2M}\right)$, $K_j^{\sin} = K_j^{'}\sin\left(\frac{\pi j}{2M}\right)$, the output of the proposed attention module can be expressed as:

$$O_i = \frac{\sum_{j=1}^{N}f(Q_i^{'}, K_j^{'})V_j}{\sum_{j=1}^{N}f(Q_i^{'}, K_j^{'})} = \frac{\sum_{j=1}^{N}\bar{Q}_i^{\cos}\left(\left(\bar{K}_j^{\cos}\right)^T V_j\right) + \sum_{j=1}^{N}\tilde{Q}_i^{\sin}\left(\left(\tilde{K}_j^{\sin}\right)^T V_j\right)}{\sum_{j=1}^{N}\bar{Q}_i^{\cos}\left(\bar{K}_j^{\cos}\right)^T + \sum_{j=1}^{N}\tilde{Q}_i^{\sin}\left(\tilde{K}_j^{\sin}\right)^T}, \quad (11)$$

where O_i is the output at the i^{th} position of the sequence from the attention module. Detailed derivation are included in the Appendix. Without losing the generality, our method achieves a linear complexity as:

$$\mathcal{O} = \mathcal{S}(Q, K)V = (Q^{\cos}K^{\cos} + Q^{\sin}K^{\sin})V = Q^{\cos}(K^{\cos}V) + Q^{\sin}(K^{\sin}V) \quad (12)$$

4 EXPERIMENTS

In this section, we experimentally validate the effectiveness of the proposed method in multiple settings. The purposes of the experiments are three-fold. First, we validate the capacity of COS-FORMER in language modeling through autogressive (Sec. 4.1) and bidirectional (Sec. 4.2) setups using WikiText-103 (Merity et al., 2017). In this way, we validate the effectiveness of the proposed linear attention module in both causal and non-causal cases. Second, we investigate the generalization ability of COSFORMER on downstream tasks by comparisons with other existing transformer variants. This is achieved by performing comparative finetuning experiments on five datasets, including GLUE (QQP, SST-2, MNLI) (Wang et al., 2018), IMDB (Maas et al., 2011) and AMAZON (Ni et al., 2019) (Sec. 4.3). We further compare COSFORMER with other transformer variants on the long-range-arena benchmark (Tay et al., 2020b) to understand its ability in modeling long-range dependencies (Sec. 4.4) and show comparative analysis into model efficiency (Sec. 4.5). Third, we conduct ablation studies to understand each component in COSFORMER (Sec. 4.6).

4.1 AUTOREGRESSIVE LANGUAGE MODELING

In autoregressive or left-to-right language modeling, we estimate the probability distribution of a token given its previous tokens. We use (Baevski & Auli, 2018) as our baseline model. Specifically, we adopt their large model which has 16 cascaded layers with a projected dimensions of 1024, and replace the self-attention module with our proposed linear attention module. We train our model on 8 Nvidia Tesla A100 GPUs with a sequence length of 512 for 150K updates on the WikiText-103 (Merity et al., 2017) and report perplexity on the validation and test splits in Table 2.

Figure 4: Training loss (left) and validation loss (right) of the bidirectional language modeling pre-train. In both training and validation, the proposed COSFORMER has a faster converge speed than vanilla transformer.

We observe that although the baseline model is a powerful standard transformer which requires quadratic computation complexity, COS-FORMER outperforms it with a clear margin in linear computation complexity. Besides, we achieve comparable perplexity to other methods on the validation set, and significantly outperform all competing methods on the test set by a clear gap, which further demonstrates the effectiveness of COSFORMER .

Table 2: Perplexity (lower is better) results of bidirectional pre-training task on validation set and test set of the WikiText-103 (Merity et al., 2017) dataset.

	ppl(val) ↓	ppl(test) ↓
Vanilla Transformer	24.5	26.2
Linear Transformer	28.7	30.2
RFA-Gaussian	25.8	27.5
RFA-across	26.4	28.1
RFA-Gate-across	24.8	26.3
RFA-Gate-Gaussian	**23.2**	25.0
COSFORMER	23.5	**23.1**

4.2 BIDIRECTIONAL LANGUAGE MODEL

For bidirectional language modeling, we adopt RoBERTa (Liu et al., 2019) as the baseline model. Similarly, we replace the self-attention module in the RoBERTa by the proposed linear attention module, and keep other structures unchanged. We train this bidirectional task on 2 Nvidia Tesla A100 GPUs for 50K iterations with a input sequence length 512. As shown in Figure 4, COS-FORMER converges faster than vanilla transformer on both training and validation sets with a comparable or smaller loss values, despite it only consumes linear space and time computation complexity. In addition, the COSFORMER variant with re-weighting mechanism has both notably better converge speed and final results over the counterpart without re-weighting, which further validates the effectiveness of our *cos*-based distance matrix and also demonstrates the effectiveness of recency bias on natural language data.

4.3 DOWNSTREAM FINE-TUNING TASKS

In this section, we fine-tune the pre-trained model on downstream tasks to demonstrate the generalization ability of COSFORMER on downstream tasks. We use the pre-trained bidirectional model and fine-tune it on three downstream text classification tasks: GLUE (QQP, SST-2, MNLi) (Wang et al., 2018), IMDB (Maas et al., 2011) and AMAZON (Ni et al., 2019). For fair comparison, we first pre-train all the competing efficient transformer variants for the same 50K iterations on WikiText-103 (Merity et al., 2017) under the same setting, then we follow the same fine-tuning protocol as RoBERTa (Liu et al., 2019) to fine-tune these methods on the downstream tasks. From Table 3, we can see that COSFORMER outperforms baseline (Liu et al., 2019) on three out of five datasets, and achieves either best or secondary place on all five downstream datasets compared to competing efficient transformers. It is worth noting that despite Longformer (Beltagy et al., 2020) achieve better results on MNLI than COSFORMER , it requires a computation complexity of $O(Nw)$, where w is window size. As shown in Figure 1, Longformer is slower and requires more memory overhead than COSFORMER . Other competing methods(Peng et al., 2020; Choromanski et al., 2020; Kitaev et al., 2020) are all based on kernel functions and have substantial performance gaps compared with our model. This validates the effectiveness of the proposed COSFORMER model compared with other efficient transformer variants.

Table 3: Results on fine-tuned downstream tasks based on pre-trained bidirectional model. Best result is in boldface and second best is underlined. The proposed COSFORMER achieves superb performances over competing efficient transformers and is approaching vanilla transformer.

	QQP ↑	SST-2 ↑	MNLI ↑	IMDB ↑	AMAZON ↑	Avg ↑
Vanilla Transformer (Liu et al., 2019)	88.41	92.31	79.15	92.86	75.79	85.70
Performer (Choromanski et al., 2020)	69.92	50.91	35.37	60.36	64.84	56.28
Reformer (Kitaev et al., 2020)	63.18	50.92	35.47	50.01	64.28	52.77
Longformer (Beltagy et al., 2020)	85.51	88.65	**77.22**	91.14	73.34	83.17
RFA (Peng et al., 2020)	75.28	76.49	57.6	78.98	68.15	71.30
COSFORMER	**89.26**	**91.05**	76.70	**92.95**	**76.30**	**85.25**

Table 4: Results on Long-range-area benchmark (Tay et al., 2020b). Best result is in boldface and second best is underlined. COSFORMER achieves the best average score across 5 different tasks on Long-range-arena benchmark.

Model	ListOps ↑	Text↑	Retrieval↑	Image↑	Pathfinder↑	Avg ↑
Local Attention (Tay et al., 2020b)	15.82	52.98	53.39	41.46	66.63	46.06
Linear Trans. (Katharopoulos et al., 2020)	16.13	**65.9**	53.09	42.34	75.3	50.55
Reformer (Kitaev et al., 2020)	37.27	56.1	53.4	38.07	68.5	50.67
Sparse Trans.(Child et al., 2019)	17.07	63.58	59.59	**44.24**	71.71	51.24
Sinkhorn Trans.(Tay et al., 2020a)	33.67	61.2	53.83	41.23	67.45	51.29
Linformer(Wang et al., 2020)	35.7	53.94	52.27	38.56	76.34	51.36
Performer(Choromanski et al., 2020)	18.01	65.4	53.82	42.77	**77.05**	51.41
Synthesizer (Tay et al., 2021)	36.99	61.68	54.67	41.61	69.45	52.88
Longformer(Beltagy et al., 2020)	35.63	62.85	56.89	42.22	69.71	53.46
Transformer (Vaswani et al., 2017)	36.37	64.27	57.46	42.44	71.4	54.39
BigBird (Zaheer et al., 2020)	36.05	64.02	59.29	40.83	74.87	55.01
COSFORMER	**37.9**	63.41	**61.36**	43.17	70.33	**55.23**

4.4 RESULTS ON LONG-RANGE-ARENA BENCHMARK

To further evaluate the generalization ability of the proposed method, we train our model from scratch on Long-range-arena benchmark 2020b. Long-range-arena (Tay et al., 2020b) is a benchmark specifically designed for efficient transformers with long input sequences, thus serving as a suitable testbed to assess the quality of efficient transformer variants comparatively. To ensure fair comparison, we first implement our method on Jax (Bradbury et al., 2018), then carefully follow their preprocessing, data split, model structure and training protocol. We evaluate our method on a variety of tasks including Long sequence ListOps (Nangia & Bowman, 2018), Byte-level text classification (Maas et al., 2011), document retrieval using the ACL Anthology Network (Radev et al., 2013), image classification on sequence of pixels on CIFAR-10 (Krizhevsky et al., 2009), and Pathfinder (Linsley et al., 2018). As shown in Table 4, COSFORMER overall achieves competitive results across all the tasks while achieving best performance on ListOps and Document Retrieval. It is worth mentioning that COSFORMER achieves the best overall scores on Long-range-arena benchmark, being one of the only two models that surpass vanilla transformer architecture.

Table 5: Speed (higher is better) comparison on Long-range-arena benchmark in both training and inference varying sequence lengths (1-4k). If a method runs out of memory when sequence gets longer, we mark it with a cross.

	Inference Speed(steps per second)↑				Train Speed(steps per second)↑			
model	1K	2K	3K	4k	1K	2K	3K	4K
Transformer(Vaswani et al., 2017)	25.37	7.83	✗	✗	6.95	2.23	✗	✗
Local Attention(Tay et al., 2020b)	57.73	33.19	23.36	17.79	13.45	6.71	4.32	3.09
Linformer(Wang et al., 2020)	70.09	39.1	27.05	20.62	14.75	7.09	4.52	3.21
Reformer(Kitaev et al., 2020)	44.21	21.58	12.74	8.37	11.58	4.98	2.94	1.95
Sinkhorn Trans. (Tay et al., 2020a)	43.29	23.58	16.53	12.7	11.09	5.57	3.68	2.68
Synthesizer (Tay et al., 2021)	20.89	6.24	✗	✗	6.36	2.01	✗	✗
BirBird (Zaheer et al., 2020)	20.96	11.5	8.12	6.15	6.46	3.2	2.13	1.53
Linear Trans. (Katharopoulos et al., 2020)	67.85	38.24	26.28	19.98	11.86	5.54	3.53	2.56
Performer (Choromanski et al., 2020)	74.15	42.31	29.5	22.44	14	6.49	4.1	2.94
Longformer (Beltagy et al., 2020)	22.99	6.72	✗	✗	4.4	1.3	✗	✗
Sparse Trans. Child et al. (2019)	24.87	7.5	✗	✗	6.77	2.2	✗	✗
COSFORMER	58.82	33.45	22.77	17.42	12.27	5.72	3.62	2.64

4.5 EFFICIENCY COMPARISON

In this section, we compare the efficiency of COSFORMER with other models, with a focus on long sequences as inputs. With the proposed linear attention module, we expect that COSFORMER scales comparably with other linear variants while significantly surpassing the vanilla transformer architecture. For a fair and comprehensive comparison, we implement our method and competing methods on Jax (Bradbury et al., 2018). We use the byte-level text classification benchmark and report runtime speed during both training and inference under different sequence lengths (1k-4k). We conduct experiments on one Nvidia A6000 GPU and also report the corresponding inference-time memory foot prints as shown in Figure 1. As shown in Table 5 and Figure 1, most pattern based methods (Beltagy et al., 2020; Zaheer et al., 2020; Tay et al., 2020a; 2021) and vanilla transformer (Vaswani et al., 2017) are much slower and require greater memory than COSFORMER prevents them from extending to longer sequence. Further, the kernel based methods like (Narang et al., 2021; Choromanski et al., 2020; Tay et al., 2020a) have comparable speed and memory overheads, but their performances are less satisfactory compared to COSFORMER across above metrics. In summary, our model COSFORMER achieves overall better efficiency than other linear variants while maintain superior modeling and generalization ability.

4.6 ABLATION: cos-BASED RE-WEIGHTING

By introducing cos-based re-weighting, we provide a non-linear mechanism to concentrate the distribution of attention connections and stabilizes the training. In this way, we encourage the model to better take into account the locality inductive biases commonly observed on many natural language tasks. In particular, we investi-

Table 6: Performance comparison of COSFORMER with and without cos-based re-weighting. We evaluate on two compositive metrics. Bidirectional finetune$_{avg}$: average score across 5 datasets reported in Table 3. LRA$_{avg}$: average score across 5 tasks reported in Table 4.

Model	Bidirectional finetune$_{avg}$ ↑	LRA$_{avg}$ ↑
w/o re-weighting	85.12	54.20
COSFORMER	**85.25**	**55.23**

gate the effect of the cos-based re-weighting in two aspects. First, as shown in Figure 4, by adding cos-based re-weighting, we obtain both notably better converge speed and final results in autoregressive language modeling. Further, in Table 6, we present a comparison between COSFORMER models with and without re-weighting mechanism. We use two composite metrics which comprehensively include 10 different datasets from bidirectional downstream fine-tuning tasks and long-range-arena (Tay et al., 2020b). COSFORMER achieves overall better results over the counterpart without re-weighting, improving the average scores on bidirectional finetuning and long-range-arena by a clear margin. This verifies that the proposed re-weighting effectively incorporates the locality inductive biases for natural language tasks.

5 CONCLUSION

We presented COSFORMER , a new efficient transformer that has linear time and space complexity. Our COSFORMER is based on two key properties of the original softmax attention: (i) every element in the attention matrix are non-negative, such that negatively-correlated information are not included for contextual information aggregation; (ii) the non-linear re-weighting scheme concentrates the distribution of the attention matrix, in order to better exploit the locality inductive biases on sequence modeling. To fulfill these properties in our COSFORMER , we utilized the RuLU function as our linear operation to ensure the non-negative property; a new cos-based re-weighting mechanism was proposed to enforce the locality bias in the original softmax attention. Since our COSFORMER is naturally decomposable, it does not suffer the accumulated approximation error that usually happens in previous linear transformers. On causal pre-training, bidirectional pre-training, and multiple downstream text understanding tasks, COSFORMER achieves comparable or even better performances than the vanilla transformer. On long sequence benchmark, COSFORMER achieved state-of-the-art performance over five different tasks. Further, COSFORMER obtains a significant overall advantage in terms of time and memory efficiency over all existing efficient transformers, facilitating the transformers to easily scale to longer input sequence.

REFERENCES

Abien Fred Agarap. Deep learning using rectified linear units (relu). *arXiv preprint arXiv:1803.08375*, 2018.

Alexei Baevski and Michael Auli. Adaptive input representations for neural language modeling. In *International Conference on Learning Representations*, 2018.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. *Advances in Neural Information Processing Systems*, 33, 2020.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, and Skye Wanderman-Milne. Jax: composable transformations of python+ numpy programs. *Version 0.1*, 55, 2018.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. 2020.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229. Springer, 2020.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. *arXiv preprint arXiv:2009.14794*, 2020.

Kevin Clark, Urvashi Khandelwal, Omer Levy, and Christopher D Manning. What does bert look at? an analysis of bert's attention. In *Proceedings of the 2019 ACL Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 276–286, 2019.

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (elus). In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR, San Juan, Puerto Rico*, 2016.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Bolin Gao and Lacra Pavel. On the properties of the softmax function with application in game theory and reinforcement learning. *arXiv preprint arXiv:1704.00805*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In *International Conference on Machine Learning*, pp. 5156–5165. PMLR, 2020.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer, 2020. URL http://arxiv.org/abs/2001.04451. cite arxiv:2001.04451Comment: ICLR 2020.

Olga Kovaleva, Alexey Romanov, Anna Rogers, and Anna Rumshisky. Revealing the dark secrets of bert. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4365–4374, 2019.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Drew Linsley, Junkyung Kim, Vijay Veerabadran, Charlie Windolf, and Thomas Serre. Learning long-range spatial dependencies with horizontal gated recurrent units. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 152–164, 2018.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *arXiv preprint arXiv:2103.14030*, 2021.

Andrew Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th annual meeting of the association for computational linguistics: Human language technologies*, pp. 142–150, 2011.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *5th International Conference on Learning Representations, ICLR, Toulon, France*, 2017.

Nikita Nangia and Samuel Bowman. Listops: A diagnostic dataset for latent tree learning. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Student Research Workshop*, pp. 92–99, 2018.

Sharan Narang, Hyung Won Chung, Yi Tay, William Fedus, Thibault Fevry, Michael Matena, Karishma Malkan, Noah Fiedel, Noam Shazeer, Zhenzhong Lan, et al. Do transformer modifications transfer across implementations and applications? *arXiv preprint arXiv:2102.11972*, 2021.

Jianmo Ni, Jiacheng Li, and Julian McAuley. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 188–197, 2019.

Hao Peng, Nikolaos Pappas, Dani Yogatama, Roy Schwartz, Noah Smith, and Lingpeng Kong. Random feature attention. In *International Conference on Learning Representations*, 2020.

Dragomir R Radev, Pradeep Muthukrishnan, Vahed Qazvinian, and Amjad Abu-Jbara. The acl anthology network corpus. *Language Resources and Evaluation*, 47(4):919–944, 2013.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In J. Platt, D. Koller, Y. Singer, and S. Roweis (eds.), *Advances in Neural Information Processing Systems*, volume 20. Curran Associates, Inc., 2008. URL https://proceedings.neurips.cc/paper/2007/file/013a006f03dbc5392effeb8f18fda755-Paper.pdf.

Steffen Schneider, Alexei Baevski, Ronan Collobert, and Michael Auli. wav2vec: Unsupervised pre-training for speech recognition. In *INTERSPEECH*, 2019.

Yi Tay, Dara Bahri, Liu Yang, Donald Metzler, and Da-Cheng Juan. Sparse sinkhorn attention. In *International Conference on Machine Learning*, pp. 9438–9447. PMLR, 2020a.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena: A benchmark for efficient transformers. In *International Conference on Learning Representations*, 2020b.

Yi Tay, Dara Bahri, Donald Metzler, Da-Cheng Juan, Zhe Zhao, and Che Zheng. Synthesizer: Rethinking self-attention for transformer models. In *International Conference on Machine Learning*, pp. 10183–10192. PMLR, 2021.

Michalis K Titsias. One-vs-each approximation to softmax for scalable estimation of probabilities. *arXiv preprint arXiv:1609.07410*, 2016.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pp. 353–355, 2018.

Sinong Wang, Belinda Z Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. Big bird: Transformers for longer sequences. In *NeurIPS*, 2020.

A APPENDIX

A.1 MATHEMATICAL DERIVATION OF cos-BASED RE-WEIGHTING

Following Equation 11, we give a detailed deviation of how to obtain output at position i^{th} position:

$$
\begin{aligned}
O_i &= \frac{\sum_{j=1}^{N} f(Q_i', K_j') V_j}{\sum_{j=1}^{N} f(Q_i', K_j')} \\
&= \frac{\sum_{j=1}^{N} \left(\bar{Q}_i^{cos} \left(\bar{K}_j^{cos} \right)^T + \tilde{Q}_i^{sin} \left(\tilde{K}_j^{sin} \right)^T \right) V_j}{\sum_{j=1}^{N} \left(\bar{Q}_i^{cos} \left(\bar{K}_j^{cos} \right)^T + \tilde{Q}_i^{sin} \left(\tilde{K}_j^{sin} \right)^T \right)} \\
&= \frac{\sum_{j=1}^{N} \bar{Q}_i^{cos} \left(\bar{K}_j^{cos} \right)^T V_j + \sum_{j=1}^{N} \tilde{Q}_i^{sin} \left(\tilde{K}_j^{sin} \right)^T V_j}{\sum_{j=1}^{N} \bar{Q}_i^{cos} \left(\bar{K}_j^{cos} \right)^T + \sum_{j=1}^{N} \tilde{Q}_i^{sin} \left(\tilde{K}_j^{sin} \right)^T} \\
&= \frac{\sum_{j=1}^{N} \bar{Q}_i^{\cos} \left(\left(\bar{K}_j^{\cos} \right)^T V_j \right) + \sum_{j=1}^{N} \tilde{Q}_i^{\sin} \left(\left(\tilde{K}_j^{\sin} \right)^T V_j \right)}{\sum_{j=1}^{N} \bar{Q}_i^{\cos} \left(\bar{K}_j^{\cos} \right)^T + \sum_{j=1}^{N} \tilde{Q}_i^{\sin} \left(\tilde{K}_j^{\sin} \right)^T}
\end{aligned} \tag{13}
$$

where $i, j = 1, ..., N, M \geq N$, and $Q' = \text{ReLU}(Q), K' = \text{ReLU}(K)$. Let $Q_i^{cos} = Q_i' \cos\left(\frac{\pi i}{2M}\right)$, $Q_i^{cos} = Q_i' \cos\left(\frac{\pi i}{2M}\right)$, $K_j^{cos} = K_j' \cos\left(\frac{\pi j}{2M}\right)$, $K_j^{sin} = K_j' \sin\left(\frac{\pi j}{2M}\right)$. It presents that the output of the proposed COSFORMER attention can be obtained in a linear manner.

A.2 PSEUDO CODE OF COSFORMER

Algorithm 1 describe the way to compute COSFORMER attention

Algorithm 1 COSFORMER attention

Input: $Q \in \mathbb{R}^{N \times d_1}, K \in \mathbb{R}^{M \times d_1}, V \in \mathbb{R}^{M \times d_2}$;
Output: $O \in \mathbb{R}^{N \times d_2}$;
Use M_i to represent the i-th row of matrix M;
Initialize $A[i] = \frac{\pi i}{2N}, O[i][j] = 0, i = 1, \ldots, N, j = 1, \ldots, d_2$;
Initialize $S^{\cos}[i][j] = 0, S^{\sin}[i][j] = 0, T^{\cos}[i] = 0, T^{\sin}[i] = 0, i = 1, \ldots, d_1, j = 1, \ldots, d_2$;
for i in $1, \ldots, M$ **do**:
    $K_i^{\cos} = K_i \cos\left(\frac{\pi i}{2M}\right), K_i^{\sin} = K_i \sin\left(\frac{\pi i}{2M}\right)$;
    $S^{\cos} += \left(K_i^{\cos}\right)^T V_i$;
    $S^{\sin} += \left(K_i^{\sin}\right)^T V_i$;
    $T^{\cos} += K_i^{\cos}$;
    $T^{\sin} += K_i^{\sin}$;
end for
for i in $1, \ldots, N$ **do**:
    $Q_i^{\cos} = Q_i \cos\left(\frac{\pi i}{2M}\right), Q_i^{\sin} = Q_i \sin\left(\frac{\pi i}{2M}\right)$;
    $O_i = \frac{Q_i^{\cos} S^{\cos} + Q_i^{\sin} S^{\sin}}{Q_i^{\cos} T^{\cos} + Q_i^{\sin} T^{\sin}}$;
end for

A.3 ALGORITHM TO VISUALIZE ATTENTION MATRIX

Algorithm 2 describe the way to visualize attention matrix as Figure 3

Algorithm 2 Algorithm to visualize attention matrix

Input: $M_k \in \mathbb{R}^{d \times d}, k = 1, \ldots, n; threshold \in [0, 1]$;
Output: $M \in \mathbb{R}^{d \times d}$;
Initialize $M[i][j] = 0, i \in 1, \ldots, d, j \in 1, \ldots, d$;
for k in $1, \ldots, n$ **do**:
    for i in $1, \ldots, d$ **do**:
        index = argsort($M_k[i]$) (in descending order)
        $p = 0$
        for j in $1, \ldots, d$ **do**:
            $l = \text{index}[j]$
            $p \mathrel{+}= M_k[i][l]$
            $M[i][l] \mathrel{+}= 1$
            if $p > threshold$ **then**: break
            end if
        end for
    end for
end for
$M \mathrel{/}= n$;
Use heatmap to visualize M;

A.4 INTRODUCTION OF DATASET

We train both models on autoregressive language modeling and bidirectional modeling by Wikitext-103 dataset, it is split by tokens and its statistics as Table 7.Then we fine-tune the pre-trained bidirectional modeling on several text classification tasks.

QQP dataset contain thousands of sentence pair from community question-answering website Quora.Network need to determine pairs of question are semantically equivalent. SST-2 and IMDB are collections of movie reviews. The task is to determine whether a review is positive or not. AMAZON dataset contains millions of product reviews from Amazon.The requirement of this task is to infer the scoring of the product from the review text.MNLI is a crow-source collections of sentence pairs. The network must distinguish which of the three categories entailment, contradiction and neutral the given sentences belong to.

The long-range-aren benchmark contains 5 different datasets.ListOps contains some designed clever mathematical problem to clarify the parsing ability of neural models.IMDB is also used in this benchmark to examine the text classification ability of neural models. CIFAR-10 is a image collection of various of object, this task require models capture 2D spatial relations between flatten pixels.In pathfinder task, models need to determine the connection of two points in the picture, so as to examine the model's ability to acquire 2D spatial relationships.AAN dataset is used to evaluate the ability for models to encode and store compressed representations for retrieving.

Data	Train	Valid	Test
WikiText-103	103M	218K	246K
QQP	364K	-	391K
SST-2	67K	-	1.8K
MNLI	393K	-	20K
IMDB	25K	-	25K
AMAZON	3M	168K	168K
ListOps	90K	-	10K
AAN	147K	18K	17K
CIFAR-10	50K	-	10K
Pathfinder	160K	-	20K

Table 7: Statistics for the datasets.A subset of "Small" amazon subset on electronics category is used for experiment