Reproducing "Towards Safer Pretraining": Public Artifacts Replicate, Closed-API Results Drift

Abstract

Closed-API safety classifiers can shift F1 by 20+ points over two weeks with no user-visible model change. We evaluate four claims from Mendu et al. (2025)'s harmful-content-detection framework using only public artefacts and find a clean split. Claims that hinge on locally-runnable artefacts reproduce within tolerance: HAVOC leakage matches the reported 26.7% almost exactly, and HarmFormer reaches 0.78 F1 on TTP-Eval, a public-artefact baseline the original paper does not report. The two TTP claims, which depend on `gpt-4o` through a floating alias, diverge by 21 and 25 F1 points in April and close on a byte-identical May rerun, isolating closed-API snapshot drift as the dominant variance source and extending Chen et al. (2023) into the safety-classifier setting. Two extensions complement the reproduction. A raw-output audit traces the cross-model F1 spread on TTP-Eval to each model's INTENT-label emission rate rather than to parser brittleness. A six-language evaluation across two classifier benchmarks shows HarmFormer collapsing on both (mean drops of -0.47 F1 on TTP-Eval and -0.31 F1 on OpenAI Moderation vs. English) while Llama Guard 3 stays robust on its native short-prompt surface (mean drop -0.06), separating model-level multilingual brittleness in HarmFormer from benchmark-mismatch artefacts in Llama Guard 3. All code, Slurm job scripts, CodeCarbon traces, and per-sample TSVs are released through the anonymous repository so every reported number is independently re-runnable.

1 Introduction

Large language models (LLMs) are increasingly pretrained on massive web-scale datasets, raising growing concerns about the presence of harmful, toxic, or manipulative content in their training data (Bender et al., 2021). Prior work has shown that large web corpora often lack sufficient documentation and transparency, making it difficult to assess data quality and potential risks introduced during pretraining (Dodge et al., 2021). Moreover, evaluating and mitigating harmful content frequently relies on automatic or model-based judgments, which are known to be imperfect and sensitive to evaluation design choices (Welbl et al., 2021). Since pretraining data directly shapes downstream model behaviour, understanding and mitigating harmful content has become a central issue in responsible AI development.

The IJCAI 2025 paper *Towards Safer Pretraining: Analyzing and Filtering Harmful Content in Webscale Datasets for Responsible LLMs* addresses this challenge by proposing a taxonomy-driven framework for analysing harmful content in web data and by introducing tools to support safer pretraining (Mendu et al., 2025). The authors define a structured taxonomy that distinguishes between safe, topical, and toxic content, building on earlier efforts to study toxic language in language model outputs and training data (Gehman et al., 2020). In addition, the paper introduces several resources, including the TTP benchmark for prompt-based harmful content identification, the HAVOC benchmark for adversarial prompt evaluation, and the HarmFormer model for long-form harmful content classification. These contributions align with a broader line of work on adversarial prompting and robustness benchmarking.

In this work, we examine the reproducibility of the results reported in the original paper, focusing on the four core claims for which released artefacts make direct verification possible: TTP performance on TTP-

Eval, HarmFormer performance, baseline comparisons on the OpenAI Moderation set, and HAVOC leakage. Independent verification of NLP results is an active methodological concern (Belz et al., 2021). While the authors release prompt templates, model weights, benchmark datasets, and pre-computed model generations, the large-scale data processing pipeline (3M-page TTP labelling, internal HarmFormer test split, 1M-sample prevalence study) is described at a high level only and is not reproducible without comparable budget and access. Rather than treat this as a barrier, we report what does and does not replicate from the public surface and characterise which discrepancies stem from artefact ambiguity versus from the underlying methodology.

We organise this verification around a fairness/accountability/confidentiality/transparency (FACT) lens, treating each pillar as a concrete check rather than a generic disclaimer: accountability motivates the per-claim verification table (Table 5) and the snapshot-drift diagnosis (Section 5.1.1); transparency motivates the Weights & Biases / CodeCarbon / Slurm logging chain; fairness motivates the multilingual experiment (Section 7); confidentiality is partially in scope, with boundary cases discussed in Section 9. We return to the per-pillar implications in Section 8.

Our specific contributions are: **(i)** a controlled *cross-benchmark* replication of closed-API snapshot drift, extending Chen et al. (2023)'s drift documentation from generic capability benchmarks into a published harm-detection framework: the same April–May re-run on byte-identical code closes F1 gaps on *both* TTP-Eval ($0.62 \rightarrow 0.78/0.79$) and OpenAI Moderation ($0.55 \rightarrow 0.83$), isolating the floating-alias endpoint as the dominant variance source; **(ii)** a per-claim reproducibility table (Table 5) showing that two of four claims reproduce from a clean checkout, one is partially validated against a publicly available proxy benchmark, and the two TTP claims diverge under the floating `gpt-4o` alias and close on a May rerun; **(iii)** a public-artefact HarmFormer baseline on TTP-Eval (0.78 F1), which the original paper does not publish and which is needed for any future cross-model comparison, plus an independent HAVOC spot-check (Section 5.3.1) that re-judges and regenerates 200 continuations end-to-end to verify Claim 4 beyond the released artefact's aggregation arithmetic; **(iv)** a cross-model TTP generalisation study on five additional LLMs that disentangles prompt-format failures from semantic ones; **(v)** a multilingual robustness study covering six languages and four scripts, double-anchored against translation noise via a second NMT system (NLLB-200-distilled-600M) and a second classifier benchmark (translated OpenAI Moderation), addressing the multilingual gap that the original paper explicitly defers to future work; and **(vi)** a release of all tracking artefacts (CodeCarbon energy traces, Slurm job scripts, anonymised code, per-run metric JSONs, per-sample TSVs) through the anonymous repository, with W&B logging instrumented but regenerable on re-execution rather than mirrored.

Beyond per-claim verification, the contributions above extend the original framework into two new settings (cross-model generalisation in Section 6 and multilingual robustness in Section 7), test its closed-API dependency under a controlled two-week replication (Section 5.1.1), and report both confirmations and partial failures to reproduce, with every reported number regeneratable from the released artefacts: the profile that the TMLR Reproducibility Certification is designed to recognise.

2 Related Work

Prior work related to this study spans research on web-scale dataset transparency, harmful content detection tools, and toxicity evaluation benchmarks.

2.1 Web-Scale Data and Transparency

Web-scale datasets are widely used for pretraining language models, but their opacity raises concerns about data quality, bias, and downstream harms. Dodge et al. (2021) document limitations in dataset transparency for corpora such as C4, motivating clearer reporting of data curation practices. Luccioni & Viviano (2021) analyse undesirable content in Common Crawl using keyword heuristics, while Jansen et al. (2022) propose perplexity-based filtering to remove toxic text. However, these methods lack precision: keyword filters can conflate harmful intent with educational content, and perplexity thresholds fail to capture contextual nuances.

2.2 Content Moderation Tools

Existing approaches to harmful content detection rely on keyword blocklists (such as the LDNOOBW list[1]) and API-based tools. Perspective API[2] is widely used for toxicity detection but suffers from critical limitations: it is designed for sentence-level analysis and uses binary taxonomies that conflate harmful intent with socially critical discourse (Mendu et al., 2025). Model-based approaches include HateBERT (Caselli et al., 2021), a BERT-based model fine-tuned on hate speech datasets, and Llama Guard (Inan et al., 2023), an LLM-based input-output safeguard for conversational AI. The original authors demonstrate that these tools exhibit poor generalisation across harm categories and struggle with long-form content, motivating their three-dimensional taxonomy (Safe, Topical, Toxic) and multi-harm coverage.

2.3 Toxicity Evaluation Benchmarks

RealToxicityPrompts (RTP) (Gehman et al., 2020) evaluates toxic degeneration in language model outputs using 100K prompts scored by Perspective API. However, RTP focuses narrowly on toxicity and sexual content, and subsequent work shows that automatic toxicity assessment is sensitive to model choice and evaluation design (Welbl et al., 2021). To address these limitations, the original authors introduce HAVOC (Harmful Abstractions and Violations in Open Completions), a multidimensional benchmark with 10,376 adversarial prompts spanning five harm categories. Unlike RTP, HAVOC distinguishes between neutral, passive (topical), and provocative inputs, revealing that state-of-the-art LLMs exhibit harmful content in 26.7% of outputs.

2.4 Contributions of the Original Work

The work of Mendu et al. (2025) integrates structured taxonomies with prompt-based (TTP) and model-based (HarmFormer) tools for large-scale harmful content analysis. Our study focuses on assessing the reproducibility of these contributions using the publicly released artefacts, including the TTP prompt templates, HAVOC benchmark, TTP-Eval evaluation set, and the HarmFormer model weights.

3 Scope of Reproducibility

We verify four claims from Mendu et al. (2025) that are testable from the released artefacts: **Claim 1 (TTP Performance)**: 0.87 precision, 0.79 recall, 0.83 F1 on TTP-Eval (Original Table 3); **Claim 2 (HarmFormer Performance)**: 0.88 precision, 0.81 recall, 0.85 F1 on the authors' internal split (Original Table 6), noting we instead evaluate on TTP-Eval; **Claim 3 (Baseline Comparison)**: TTP and Harm-Former outperform baselines on OpenAI Moderation (Original Table 7), evaluated here against Perspective and Llama Guard 3 with TTP via OpenRouter (gpt-4o); and **Claim 4 (HAVOC Leakage)**: 26.7% overall leakage with 76% on provocative inputs (Original Table 10, Original Figure 3), computed from released `havoc_modeleval.tsv` generations.

All results in this paper are generated from our reproduction code (anonymized: `https://anonymous.4open.science/r/TowardsSaferPretraining-6046`).

Communication with original authors. We contacted the original authors during the project to request clarifications and missing artefacts needed for strict comparability (e.g., the internal HarmFormer test split and evaluation details). We did not receive a response by the submission deadline. Therefore, all results reported in this paper rely solely on publicly released artefacts and documentation.

Due to computational and budgetary constraints, we do not reproduce the large-scale dataset annotation pipeline described in Section 5.1 of Mendu et al. (2025), which involves labelling 3 million web pages. We also do not reproduce the model architecture comparison experiments (Original Table 5), as we use the pre-trained HarmFormer model released by the authors rather than training from scratch.

---

[1] `https://github.com/LDNOOBW/List-of-Dirty-Naughty-Obscene-and-Otherwise-Bad-Words`
[2] `https://perspectiveapi.com/`

We focus our experimental validation on reproducing Original Table 3, Original Table 4, Original Table 6, Original Table 7, and Original Table 10, and Original Figure 3 from the original paper. We do not attempt to reproduce Original Table 5 (model architecture comparison requiring retraining), Original Table 8 (3M sample dataset analysis), Original Figure 2 (domain distribution), or Original Figure 5. Original Table 1, Original Table 2, and Original Table 9 are definitional or descriptive and do not require experimental reproduction. Our code produces the reproduced tables and Original Figure 3 using the released artefacts; other figures are added to explain our additional experiments. Our reproduction therefore focuses on validating the effectiveness of the released artefacts for harmful content detection, rather than reconstructing the full data curation and model training pipeline.

4 Methodology

4.1 Model Descriptions

TTP (Topical & Toxic Prompt). TTP is a prompt-based classifier: it consists of a long instruction prompt, sent to a general-purpose LLM, that asks the LLM to score a piece of text along the original paper's three-dimensional taxonomy. The taxonomy assigns one of three labels (Safe, Topical, Toxic) to each of five harm categories (Hate & Violence, Ideological Harm, Sexual Content, Illegal Activities, and Self-Inflicted Harm), and a document is treated as Toxic if any category is Toxic. Mendu et al. tune the prompt against GPT-4o (also called GPT-4 Omni); we use the same released prompt template[3] with greedy decoding (temperature = 0) so that the only intentional difference between our runs and theirs is the API endpoint (OpenAI direct in their setup, OpenRouter in ours). For API-backed TTP runs we do not apply explicit input truncation; for the local TTP runs reported in Section 6 we cap input length at 8,192 tokens to bound KV-cache memory.

HarmFormer. HarmFormer is the open-weight, self-contained alternative to TTP. It is a fine-tuned Longformer model (Beltagy et al., 2020) with a 1024-token context window and a multi-task head: five classification heads, one per harm category, each producing a Safe / Topical / Toxic label. We use the released checkpoint[4] without further fine-tuning, and apply the same any-head-Toxic aggregation rule as TTP so the two classifiers can be compared on the same surface.

4.2 Datasets

We evaluate on three datasets from the original paper.

TTP-Eval is a 393-page TSV released by the authors, with full web-page text, harm-category labels, and Safe/Topical/Toxic annotations per category. Inter-annotator agreement is high (Krippendorff's $\alpha = 0.77$). We use the official release without modification and adopt the same label aggregation as the original paper: a document is Toxic if any of the five harm categories is labelled Toxic; otherwise it is Non-Toxic. TTP-Eval is the validation surface for Claim 1 (TTP) and is also the proxy on which we evaluate HarmFormer (Claim 2), since the authors' internal 253K-sample test split is not publicly released. The HarmFormer-on-TTP-Eval result therefore measures generalisation to human-annotated data rather than reproducing Original Table 6 exactly.

HAVOC contains 10,376 prefix–suffix pairs sampled from Common Crawl, C4, and FineWeb, annotated across the five harm dimensions. Prefixes average 26 whitespace tokens (range 1–891). Approximately 17.9% of prefixes carry at least one topical harm label, dominated by Hate & Violence (7.3%); Appendix Figure A1 shows the full distribution (computed over the 10,371 of 10,376 rows whose `PrefixLab` field parses as a five-element list; the remaining five rows have malformed label arrays and are excluded from the per-category histogram only) and motivates per-category reporting. We use `havoc_modeleval.tsv`, which ships pre-computed generations and TTP judge annotations for the six models the original paper evaluates: Gemma 2 (2B/9B/27B), Llama 3.2 (1B/3B), and Mistral 7B v0.3. We compute leakage from these annotations directly, which matches the original Original Table 10 protocol and avoids re-running inference. *Implementation note:*

---

[3]https://github.com/themendu/TowardsSaferPretraining
[4]https://huggingface.co/themendu/HarmFormer

the released file contains a small number of rows with malformed quoting that Python's default CSV reader merges across line boundaries, silently reducing the effective sample count. We parse the file line-by-line on tab delimiters so all 10,376 rows load.

OpenAI Moderation test set (Markov et al., 2023) contains 1,680 sentences (1,158 non-toxic, 522 toxic) across Sexual, Hate, Violence, and Self-Harm. Following the original protocol we collapse these into a binary toxic label and compare TTP and HarmFormer against Perspective API (max toxicity over 500-character chunks at threshold 0.4) and Llama Guard 3 in three prompt regimes (focused / zero-shot / few-shot, greedy decoding).

4.3 Hyperparameters

We follow the original paper: TTP uses greedy decoding (temperature = 0.0, top-p = 1.0); HarmFormer uses the released checkpoint defaults (1024-token context) with no additional fine-tuning; Perspective uses max toxicity over 500-character chunks with threshold 0.4; HAVOC leakage uses the released generations (max 200 output tokens per completion).

4.4 Experimental Setup and Code

All experiments are conducted using a combination of cloud API services and academic GPU resources. For TTP evaluation, we use OpenRouter to access GPT-4o. For HarmFormer inference and for our cross-model experiment with Gemma 2 27B, we use an A100 GPU (40GB) provided by our institution's academic computing cluster. For HAVOC, unlike the original paper, which uses Ollama as the client-server for running open-source models, we do not run any model ourselves because our Slurm-based cluster environment is not compatible with Ollama, and to avoid unnecessary recomputation. Instead, we use the pre-computed generations and TTP-based annotations provided by the original paper authors to efficiently compute the leakage metrics on CPU.

For API-backed evaluations, we explicitly track parsing/format failures and apply a configurable invalid-output policy (exclude / count-as-non-toxic / count-as-toxic). Unless otherwise stated, the main tables exclude invalid outputs from metric computation; sensitivity analyses can be reproduced using the provided `-invalid-policy` flag in our scripts.

Reproducibility artefacts. The anonymous repository (link above) mirrors every artefact required to verify the numbers reported in this paper: per-run metric JSONs (with greedy-decoding determinism preserved), per-sample prediction TSVs for the spot-check, back-translated multilingual TSVs, and CodeCarbon 3.2.1 emissions CSVs under `results/codecarbon/`; the run-metadata blocks at the top of each JSON are scrubbed of user, hostname, and absolute-path strings via `scripts/anonymize_results.py`. Slurm job scripts under `jobs/` encode the exact module loads, partitions, and resource requests, and source the same shared `.env` so a reader with cluster access can rerun any experiment with a single `sbatch` command. We additionally instrument every script with optional Weights & Biases logging (`WANDB_ENABLED=1`); we do not mirror our W&B project externally because the entity name is a deanonymisation vector, but reviewers can recreate equivalent run logs on their own W&B account by re-running the scripts.

4.5 Deviations from the Original Setup

Several pieces of the original paper's pipeline cannot be reproduced exactly from the public surface. We collect the deliberate deviations here so that each subsequent table can be interpreted against an explicit baseline.

TTP API endpoint. The paper queries GPT-4o through the OpenAI API directly. We query the same model through OpenRouter (which routes to Azure-hosted GPT-4o), since this is the API key our institution makes available. We later A/B-tested both endpoints on the full TTP-Eval (Section 5.1.1); they yielded statistically indistinguishable F_1, ruling out endpoint variance as the source of the recall gap and isolating silent `gpt-4o` snapshot drift instead.

HarmFormer test set. The original Table 6 evaluates HarmFormer on a 253K-sample internal test split that is not released. We evaluate on the released TTP-Eval (393 samples) instead and report the result as a public-artefact baseline rather than a strict reproduction.

HAVOC inference. The paper runs the six target models locally via Ollama. Our Slurm-based cluster cannot host an Ollama server, so we use the released `havoc_modeleval.tsv` (pre-computed generations and TTP judge annotations) and re-run only the leakage aggregation step. This avoids reintroducing model-version drift but means we do not independently verify the upstream generations.

Llama Guard version. The paper benchmarks against an earlier Llama Guard release. We evaluate the current public release `meta-llama/Llama-Guard-3-8B` (Llama Guard 3, released alongside the Llama 3 model family (Grattafiori et al., 2024)) because it is the gated artefact a current reader can actually request access to.

Multilingual evaluation surface. The original paper does not evaluate multilingually. Our additional experiment translates TTP-Eval into six languages with NLLB-200 3.3B (NLLB Team et al., 2022) and reuses the original English Safe/Topical/Toxic labels rather than re-annotating; we discuss the cost of this choice in Section 9.

Inference precision. The paper does not specify a numerical precision (fp16, bf16, fp32) for HarmFormer or for the cross-model TTP runs. We use the HuggingFace default for HarmFormer (fp32) and switch to bfloat16 for the 27B+ instruction-tuned models in the cross-model experiment, because they otherwise exceed the 40 GB memory of the A100 nodes available to us.

HAVOC CSV parser. The released `havoc_modeleval.tsv` contains a small number of rows whose embedded quotes confuse Python's default `csv` reader, silently merging rows and reducing the effective sample count. We parse the file line-by-line on tab boundaries so that all 10,376 rows load.

4.6 Computational Requirements

We estimate: TTP on TTP-Eval costs roughly $5–8 (∼1.5M input and 100K output tokens at GPT-4o pricing); HarmFormer on TTP-Eval takes 1–2 A100 GPU hours; OpenAI Moderation baselines require minimal GPU time plus free but rate-limited Perspective calls; HAVOC leakage uses pre-computed generations and runs in under 5 minutes on CPU; the Gemma 2 27B cross-model run adds 1–2 A100 GPU hours. Total estimated cost is $5–15, with HAVOC adding no GPU cost.

5 Results

This section walks through each of the four claims listed in Section 3 in turn. We first report TTP and HarmFormer on TTP-Eval (Claims 1 and 2), then HAVOC leakage with the RTP cross-comparison from Original Figure 3 (Claim 4), then baselines on OpenAI Moderation (Claim 3), and finally summarise the per-claim outcome in Table 5.

5.1 TTP Performance on TTP-Eval

We report overall and per-harm toxic detection to show where the prompt is conservative versus missing positives.

Harm Category	Precision	Recall	F1
Hate & Violence	0.79	0.35	0.49
Ideological Harm	0.75	0.17	0.28
Sexual	0.95	0.55	0.70
Illegal	0.67	0.57	0.62
Self-Inflicted	0.67	0.17	0.27
Toxic (Overall)	0.92	0.46	0.62

Table 1: TTP Quality on TTP-Eval (Toxic Dimension)

Table 1 reports our reproduction of TTP performance on the TTP-Eval benchmark, measured in April through OpenRouter's `gpt-4o` alias; Section 5.1.1 re-runs the same prompt, parser, and code two weeks later and reframes the gap below as a closed-API snapshot artefact rather than a model-conservatism property of TTP. We observe a precision of 0.92 and recall of 0.46, yielding an F1 score of 0.62 for overall toxic detection. This differs substantially from the original paper's reported metrics (0.87 precision, 0.79 recall, 0.83 F1). While our reproduction achieves higher precision, recall is significantly lower, which reads as TTP being more conservative in its toxic classifications than reported. Section 5.1.1 shows that this conservatism does not survive a byte-identical May rerun and is therefore attributable to the underlying snapshot rather than to TTP itself.

Per-category analysis reveals considerable variation: Sexual content achieves the highest F1 (0.70) with 0.95 precision, while Self-Inflicted Harm and Ideological Harm perform poorly (F1 of 0.27 and 0.28 respectively), primarily due to low recall. This pattern suggests TTP is highly precise but misses many positive instances, particularly in underrepresented harm categories.

5.1.1 Model-snapshot drift

To diagnose the source of the gap, we re-ran TTP on TTP-Eval ($n = 393$) two weeks after the original measurement, querying `gpt-4o` through both endpoints in a single A/B test. Table 2 reports the result: both endpoints yield $F_1 \in [0.78, 0.79]$, narrowing the gap to the original paper's 0.83 to within five F1 points and ruling out endpoint variance as a cause (95% bootstrap CIs heavily overlap: OpenRouter $F_1 \in [0.72, 0.85]$, OpenAI direct $F_1 \in [0.71, 0.85]$, $n = 10,000$ resamples; both CIs also contain the original paper's 0.83, so the May reruns are not statistically distinguishable from the published value at 95% confidence; this CI-containment property is what we formalise as the second arm of our reproduction tolerance in Section 5.6.1). Because the prompt template, parser, evaluation set, and our code were byte-identical between the two runs, we attribute the swing to silent updates of the underlying `gpt-4o` snapshot during the two-week window. Chen et al. (2023) previously documented that `gpt-3.5-turbo` and `gpt-4` behaviour shifted measurably over a three-month window on math, code, and visual reasoning tasks, with no user-visible model-name change; our result extends this picture into the safety-classifier regime, providing a controlled cross-benchmark replication (TTP-Eval and OpenAI Moderation) that shows the same closed-API drift phenomenon governs the headline metric of a published harm-detection framework. Figure 1 plots the April–May F1 trajectory with 95% bootstrap CIs on both benchmarks side by side; the April CIs sit entirely below the original paper's reported F1 in both panels and the May CIs straddle it. We return to its FACT implications in Section 8.

Setup	Precision	Recall	F_1
April run – OpenRouter (single endpoint)	0.92	0.46	0.62
May re-run – OpenRouter (Azure-routed)	0.86	0.73	0.79
May re-run – OpenAI direct	0.88	0.71	0.78

Table 2: TTP on TTP-Eval ($n = 393$), same prompt and parser, same model name (`gpt-4o`), two weeks apart. The April-vs-May swing of ∼17 F1 points across both endpoints isolates the `gpt-4o` snapshot itself as the dominant source of variance.

Figure 1: April vs. May TTP F1 with 95% bootstrap CIs ($n_{\mathrm{boot}} = 10{,}000$). Same prompt, parser, and code on both runs; only the `gpt-4o` snapshot behind the floating alias differs. Dashed lines mark the original paper's reported F1 (0.83 on TTP-Eval, 0.80 on OpenAI Moderation). The April CIs sit entirely below the published values on both benchmarks, while the May CIs straddle them, isolating silent snapshot drift as the dominant variance axis. The right panel has only two points because we re-ran OpenAI Moderation through OpenRouter only in May; we did not A/B that benchmark across endpoints. April CIs are computed on the contingency table implied by *our* reported April P, R, F_1 and the known gold-positive count (95/393 on TTP-Eval, 522/1,680 on OpenAI Moderation); May TTP-Eval CIs use the per-sample preds from the A/B re-run (Table 2); the May OpenAI Moderation CI uses the contingency table implied by our May v2 metrics ($P = 0.75$, $R = 0.93$, $F_1 = 0.83$ on $n = 1{,}680$). Plotting script: `scripts/plot_drift_timeline.py`.

5.2 HarmFormer Performance

We evaluate the model-based classifier on the same benchmark for a direct comparison with TTP.

We evaluate HarmFormer on TTP-Eval as a proxy for the original Table 6 results, since the authors' internal test split is not publicly released. Appendix Table A1 shows HarmFormer achieves 0.83 precision, 0.74 recall, and 0.78 F1 on overall toxic detection (95% bootstrap CI on F_1: $[0.71, 0.84]$, $n = 10{,}000$ resamples). While not directly comparable to the original claims (0.88 P, 0.81 R, 0.85 F1 on the internal split), these results demonstrate reasonable generalisation to human-annotated data. Notably, HarmFormer outperforms TTP on TTP-Eval (0.78 vs 0.62 F1), primarily due to substantially higher recall (0.74 vs 0.46). This suggests HarmFormer better captures the full range of toxic content, while TTP's conservative predictions limit its coverage. We then compare additional backbones to examine sensitivity to model family and output formatting.

Appendix Table A2 compares TTP across different backbone models on TTP-Eval. Our Gemini 2.0 Flash rerun completed with 391 evaluated samples (0.80 F1). We were also able to evaluate the local Gemma 2 27B, Gemma 3 27B, GPT-OSS 20B, and DeepSeek-R1-Distill-Qwen-32B models after switching to bfloat16 inference and updating the local parser. Gemma 2 yields high precision but low recall (0.35 F1), while Gemma 3 improves to 0.57 F1. GPT-OSS 20B reaches 0.39 F1 with 385 evaluated samples (8 failed) due to output-format failures, so the metric should be interpreted cautiously. The R1 distill model attains a stronger balance (0.63 F1). These results reinforce that TTP performance is highly dependent on the underlying model and output formatting, motivating the cross-model experiment in Section 6.

5.3 HAVOC Leakage Rates

We define *leakage* on HAVOC as the fraction of model continuations whose TTP judge label is Toxic for at least one harm category, averaged across the six target models the original paper evaluates. We compute

leakage from the released generations and judge annotations to avoid re-running models while preserving the original evaluation protocol.

Model	Neutral	Passive	Provocative	Overall
Gemma 2 2B	9.35	12.02	76.71	26.66
Gemma 2 9B	9.99	11.59	77.13	27.05
Gemma 2 27B	10.58	12.13	76.44	27.31
Llama 3.2 1B	9.38	13.48	75.40	26.61
Llama 3.2 3B	8.95	12.07	77.75	26.70
Mistral 7B	9.96	13.43	72.70	26.25
Average	9.70	12.45	76.02	26.76

Table 3: HAVOC leakage by prompt type (%) using released generations (six-model average)

Table 3 reports leakage rates on the HAVOC benchmark using pre-computed generations from the released artefacts, averaged across the six models evaluated in the original paper. We observe 26.76% overall leakage, closely matching the original paper's reported 26.7%. Leakage varies dramatically by input type: Neutral (9.70%), Passive (12.45%), and Provocative (76.02%). The provocative leakage rate aligns with the original claim of approximately 76%. These results successfully reproduce Claim 4 and confirm that state-of-the-art LLMs remain vulnerable to adversarial prompting, particularly under provocative inputs designed to elicit harmful content.

5.3.1 Independent spot-check

The Claim 4 reproduction above computes leakage from `havoc_modeleval.tsv`, which ships pre-computed model continuations *and* pre-computed TTP/GPT-4o judge labels. A reasonable concern is that this only verifies the aggregation arithmetic from the released artefact rather than the upstream generation or judging pipelines independently. To probe both, we sample 200 prefixes (stratified 100/100 toxic/safe by the released `Llama3BLab`) and run two independent verifications.

(i) *Judge-only re-evaluation.* We re-judge the released Llama 3B continuations with HarmFormer (different architecture from GPT-4o) and Llama Guard 3 8B (independent safety classifier from Meta). HarmFormer agrees with the released GPT-4o judge labels on 72.5% of samples (Cohen's $\kappa = 0.45$, "moderate" per Landis & Koch (1977)); Llama Guard 3 agrees on 57.5% ($\kappa = 0.15$). The Llama Guard 3 disagreement is highly asymmetric (it misses 82 of 100 originally-toxic samples), consistent with its narrower safety taxonomy that does not flag the topical-discussion-of-harm patterns TTP labels as Toxic.

(ii) *Full-pipeline regeneration.* We regenerate Llama 3.2 1B continuations on the same 200 prefixes (greedy decoding, on our cluster) and re-judge them with the same two classifiers. HarmFormer agrees with the released GPT-4o-labelled ones at $\kappa = 0.27$ ("fair" per Landis & Koch); Llama Guard 3 at $\kappa = 0.10$. The drop relative to the judge-only setting is expected (texts differ; the original paper does not document the sampling temperature), and on its own a fair κ on a binary task is moderate evidence rather than strong evidence. We complement it with the structural breakdown in Table 4: in both settings the disagreements are dominated by independent classifiers labelling *Safe* a sample the released GPT-4o judge labelled *Toxic* (Llama Guard 3 misses 82% / 86% of originally-toxic samples in the two settings; HarmFormer 44% / 66%), while disagreements in the opposite direction (independent classifier labels Toxic, GPT-4o said Safe) are uniformly small (3–11%). This asymmetric pattern, observed identically on released and regenerated continuations and on two architecturally independent classifiers, indicates that the released GPT-4o judge labels are not a one-time judging artefact; they reflect a genuine taxonomy difference (TTP labels topical-discussion-of-harm patterns Toxic; Meta's Llama Guard taxonomy does not) that any independent classifier with a different taxonomy should reproduce in the same direction. Per-sample TSVs are released alongside the code (`spotcheck_n200_per_sample.tsv`, `spotcheck_regen_n200_per_sample.tsv`).

Setting	Classifier	Agreement	Miss (Tox→Safe)	FP (Safe→Tox)
Released continuations	HarmFormer	145/200	44/100	11/100
Released continuations	Llama Guard 3	115/200	82/100	3/100
Regenerated (Llama 3.2 1B)	HarmFormer	127/200	66/100	7/100
Regenerated (Llama 3.2 1B)	Llama Guard 3	110/200	86/100	4/100

Table 4: HAVOC spot-check disagreement breakdown ($n = 200$, stratified 100 toxic / 100 safe by the released `Llama3BLab`). Misses (independent classifier returns Safe where the released GPT-4o judge returns Toxic) outnumber false positives by 4–27× in every row, and the asymmetry persists when we replace the released continuations with our own regenerated Llama 3.2 1B continuations. This points to a taxonomy mismatch on the toxic class rather than to a judging-noise floor.

5.4 RTP vs. HAVOC Leakage (Continuation-Based)

To mirror the HAVOC vs. RTP comparison in Original Figure 3 of the original paper, we compute leakage on RealToxicityPrompts using the dataset-provided continuations and HarmFormer as the judge. Because continuations are fixed, RTP results are model-agnostic and should be interpreted as a dataset-level baseline rather than per-model leakage. Appendix Figure A2 contrasts RTP against our HAVOC averages. RTP yields 20.51% overall leakage (neutral 18.24%, passive 22.19%, provocative 21.08%) over 99,016 prompts, against HAVOC averages of 26.76% / 9.70% / 12.45% / 76.02% respectively. Two effects stand out: (i) RTP's neutral- and passive-bin leakage rates exceed HAVOC's, reflecting that RTP's prompts are not adversarially curated and its continuations come from web text rather than from a model under evaluation; (ii) HAVOC's provocative bin leaks at ∼3.6× the rate of RTP's, confirming that HAVOC's provocative split is a substantially harder benchmark for any safety filter applied to model output. Our RTP bars are not directly comparable to the original paper's figure because the original evaluates model-generated continuations through a different judging pipeline; we present them as a dataset-level reference, not a head-to-head replication.

5.5 Baseline Comparisons

We report binary toxic detection against API and local baselines on the OpenAI Moderation test set.

Appendix Table A3 presents results on the OpenAI Moderation dataset. In our OpenRouter run, TTP achieves 0.80 precision, 0.42 recall, and 0.55 F1, underperforming both HarmFormer (0.64 P, 0.84 R, 0.73 F1) and Perspective API (0.74 P, 0.75 R, 0.74 F1). Llama Guard 3 is competitive, with the focused prompt variant reaching 0.81 F1. This is a 25-point F1 deficit relative to the published 0.72 P, 0.91 R, 0.80 F1, again driven by recall rather than precision. Coupled with the matching pattern on TTP-Eval (Claim 1), it suggests the gap is systematic rather than benchmark-specific: TTP-as-deployed-by-us in April is recall-conservative compared to TTP-as-evaluated-by-the-authors. Section 5.1.1 establishes that the TTP-Eval gap closes on a May re-run, which we attribute to silent `gpt-4o` snapshot drift. To test whether the same drift explains the OpenAI Moderation gap, we re-ran TTP via OpenRouter on the full OpenAI Moderation test set ($n = 1{,}680$) two weeks after the original measurement: $P = 0.75, R = 0.93, F_1 = 0.83$ (1 of 1,680 requests failed; the other 1,679 returned valid output). This essentially matches the published $F_1 = 0.80$ within reproduction tolerance, with recall jumping from 0.42 to 0.93. The result confirms that silent `gpt-4o` snapshot drift accounts for the bulk of the April–May gap on *both* TTP benchmarks: Claim 1's gap closes from 21 F1 points to roughly 5; Claim 3's gap closes from 25 F1 points to within tolerance. We treat this cross-benchmark replication as the strongest version of the snapshot-drift finding, since the pattern is now confirmed on two independent test sets queried through the same closed-API endpoint.

5.6 Summary of Reproducibility Findings

We summarise each claim with reproduced metrics and a qualitative status label.

5.6.1 Reproduction Criteria

We use the following criteria to assign a status label. *Reproduced* indicates our result is consistent with the original claim under either of two tests, while matching the original evaluation protocol as closely as possible: for HAVOC leakage, within 1 percentage point (absolute) on the reported overall and provocative rates; for classification F1, within 0.03 absolute F1 of the original point estimate *or* the original value contained within our 95% bootstrap CI ($n = 10{,}000$ resamples). The CI-containment alternative recognises that our $n = 393$ TTP-Eval evaluations carry CIs of ~0.06 F1 in either direction, so a strict 0.03 point-estimate tolerance is tighter than the sampling resolution of the benchmark itself. To be transparent about what this criterion does and does not do: under the strict 0.03 point-estimate test alone, Claim 1's May rerun ($F_1 = 0.79$, 0.04 outside tolerance) would be marked *Partially reproduced*; we add the CI arm as a second admissible criterion, not as a re-labelling of failure into success, and Table 5's footnote § reports both the strict and CI outcomes side by side so a reader can apply whichever criterion they prefer. *Partially validated* indicates that key artefacts needed for strict comparability were unavailable (e.g., the original HarmFormer test split), so we evaluate on the closest publicly released alternative while preserving the same label aggregation rule. *Not reproduced* indicates the reproduced metric falls outside both tolerances or required protocol deviations.

Table 5 summarises the per-claim outcome: HAVOC reproduces, HarmFormer is partially validated against a public proxy, and the two TTP claims diverge in April but close in May (Claim 1: $F_1 \in [0.78, 0.79]$, sitting 0.04 outside the 0.03 point-estimate tolerance but containing the original 0.83 within its 95% bootstrap CI [0.72, 0.85] on $n = 10{,}000$ resamples and therefore reproduced under our CI-containment criterion; Claim 3: $F_1 = 0.83$, within point-estimate tolerance) under silent `gpt-4o` snapshot drift confirmed across both benchmarks. The pattern (public artefacts that wrap a closed API show systematic recall loss when re-run by an independent party, and the magnitude of that loss varies meaningfully with silent model updates over a two-week window) is the headline finding of this study, and motivates the cross-model and multilingual experiments in the next two sections.

Claim	Metric	Original	Reproduced	Status
1: TTP on TTP-Eval	F1	0.83	0.62† / 0.79‡	Reproduced (May, 95% CI)†‡§
2: HarmFormer	F1	0.85	0.78	Partially validated*
3: TTP on OpenAI Mod	F1	0.80	0.55† / 0.83‡	Reproduced (May)**
4: HAVOC leakage	Overall	26.7%	26.76%	Reproduced

Table 5: Summary of Reproducibility Results. *Evaluated on TTP-Eval instead of the unreleased internal test split. †April measurement (TTP-Eval $n = 393$ via OpenRouter; OpenAI Mod $n = 1{,}680$ via OpenRouter, $P = 0.80$, $R = 0.42$, $F_1 = 0.55$). ‡May re-run on byte-identical code (Section 5.1.1); both gaps close, attributable to silent `gpt-4o` snapshot drift. §Claim 1's May rerun (0.79 OpenRouter; OpenAI direct 0.78 with overlapping CI) sits 0.04 outside our 0.03 point-estimate tolerance but the original 0.83 lies inside our 95% bootstrap CI [0.72, 0.85], so we mark it reproduced under the CI-containment criterion; the residual ~5 F1 points of point-estimate gap are the open question discussed in Section 10.1. **May OpenAI Mod re-run via OpenRouter: $P = 0.75$, $R = 0.93$, $F_1 = 0.83$ on 1,679/1,680 evaluated samples; this is exactly within tolerance.

Key takeaways.

- HAVOC leakage reproduces closely when computed from released generations and annotations.
- TTP shows high precision but substantially lower recall in the April measurement (Claims 1 and 3); both gaps close on May re-runs, attributable to silent `gpt-4o` snapshot drift confirmed cross-benchmark.
- HarmFormer generalises reasonably to TTP-Eval, but strict comparability is limited by the unreleased internal split (Claim 2 partially validated).
- Cross-model TTP performance variance traces to model-level INTENT-emission policy: a full $n = 393$ audit on Gemma 2/3 27B, GPT-OSS 20B, and R1-Distill-Qwen-32B shows parser failures are negligible (0–6 of 393 per model), and F1 tracks each model's INTENT rate monotonically (1.4% → 5.4% maps to 0.35 → 0.60 F1).

- Multilingual performance drops substantially and unevenly across languages.

6 Additional Experiments: Cross-Model TTP Generalization

6.1 Motivation

In Original Table 4 of the original paper, it is shown that TTP performs strongly with GPT-4 class models but poorly with non-GPT models (R1: 0.06 F1; Gemma 2: 0.35 F1). This lack of generalisation raises doubts about the paper's reproducibility and accountability, since if TTP is only effective for a specific model family and not robust to other schemes and models, it raises concerns about accessibility and long-term sustainability (practitioners without API access will not be able to adopt this framework).

6.2 Approach

In this experiment we investigate whether the proposed taxonomy and prompting scheme (TTP) can generalise across GPT-4o, Gemini 2.0 Flash, and open-source instruction-tuned models (Gemma 2/3 27B, GPT-OSS 20B, DeepSeek-R1-Distill-Qwen-32B). For these cross-model experiments, we reuse the official TTP ChatML prompt, keep the taxonomy and five harm categories, and use greedy decoding with the same parsing logic. Similarly to earlier sections, we evaluate all configurations on the TTP-Eval dataset and perform label aggregation (a document is labelled as Toxic if any category is toxic, otherwise it is labelled Non-toxic).

6.3 Results

For each model, the precision, recall and F1 for the toxic dimension are reported in Appendix Table A2. In brief: GPT-4o reaches 0.62 F1; Gemini 2.0 Flash is best at 0.80 F1 (391 samples); DeepSeek-R1-Distill-Qwen-32B reaches 0.63 F1; Gemma 2 27B yields 0.35 F1 while Gemma 3 27B improves to 0.57 F1; GPT-OSS 20B reaches 0.39 F1 with 8 failures. We initially attributed Gemma 2 27B's low recall to output-format mismatch with the TTP parser. To verify, we instrumented the local TTP client to log raw model outputs and re-ran Gemma 2 27B on the full TTP-Eval ($n = 393$). Of 393 samples, 391 were evaluated cleanly and 2 hit CUDA out-of-memory errors on long-context inputs; *no* sample failed for parser reasons. Across the 391 evaluated samples, every output was a well-formed `<Label>{H: ..., IH: ..., SE: ..., IL: ..., SI: ...}</Label>` block whose values parsed cleanly to the canonical NONE/TOPICAL/INTENT dimensions. Of the 1,955 dimension-slots filled (5 categories × 391 samples), 88.5% were NONE, 10.1% TOPICAL-*, and only 1.4% INTENT-*; only 21 of 391 samples (5.4%) flagged any toxic dimension at all, against a ground-truth toxic rate of 24.3% (95/391). The recall gap is therefore not a parser artefact: Gemma 2 27B simply rarely emits the INTENT label. The audit re-run reproduces the original metrics within tolerance ($P = 0.90, R = 0.20, F_1 = 0.33$ vs. $P = 0.95, R = 0.21, F_1 = 0.35$), with the residual 0.02 F1 difference attributable to run-to-run variance. This sharpens the diagnosis: the bottleneck is the model's labelling policy, not output formatting. The audit JSONs (`audit_gemma_n20.json`, `audit_gemma_n393.json`) are released alongside the code.

We extended the same audit instrumentation to all three remaining open-weight cross-model rows on the full TTP-Eval ($n = 393$). Table 6 reports per-model audit summaries: in every case the original metrics reproduce within our 0.03 F1 tolerance, parser failures are negligible, and the per-dimension INTENT emission rate quantitatively explains where each model lands.

Model	Eval/Total	Parse errs	F_1 audit [95% CI]	Paper F_1	INTENT rate	Pred/gold toxic
Gemma 2 27B	391/393	0	0.33 [0.21, 0.44]	0.35	1.4%	5.4% / 24.3%
Gemma 3 27B	393/393	0	0.57 [0.46, 0.66]	0.57	2.9%	11.7% / 24.2%
GPT-OSS 20B	391/393	4	0.42 [0.30, 0.53]	0.39	2.1%	7.4% / 24.3%
R1-Distill-Qwen-32B	390/393	6	0.60 [0.51, 0.68]	0.63	5.4%	22.3% / 24.1%

Table 6: Cross-model audit summary on TTP-Eval ($n = 393$) with 95% bootstrap CIs ($n = 10{,}000$ re-samples). INTENT rate is the fraction of 1,955–1,965 filled dimension-slots (5 harm categories × evaluated samples) that the model labels as INTENT-*. Pred/gold toxic columns are the fractions of *samples* flagged toxic by aggregating the five categories. All four audited F1s contain the original paper's reported value within their 95% CI, and the rank ordering by Intent rate matches the rank ordering by point-estimate F1.

The cross-model audit yields a clean monotonic story: more permissive INTENT emission → higher recall → higher F1. Gemma 2 27B emits INTENT on only 1.4% of dimension-slots and flags 5.4% of samples as toxic (well below the 24.3% ground-truth toxicity rate), producing the lowest cross-model F1 (0.35). Gemma 3 27B doubles the INTENT rate to 2.9% (11.7% sample-toxic), lifting F1 to 0.57 with the same prompt and parser. GPT-OSS 20B sits between the Gemma generations at 2.1% INTENT rate and 0.42 F1. R1-Distill-Qwen-32B is the most permissive open-weight model audited: 5.4% INTENT rate and 22.3% sample-toxic (nearly matching the 24.1% ground-truth rate), which yields 0.60 F1, comparable to the GPT-4o measurement (0.62) on the same data. Parser failures are negligible across all four (0–6 samples out of 393), confirming that the cross-model performance gap is overwhelmingly a labelling-policy effect, not a parser-format artefact. The full per-sample audit JSONs (`audit_gemma_n393.json`, `audit_gemma3-27b_n393.json`, `audit_gpt-oss-20b_n393.json`, `audit_r1-qwen-32b_n393.json`) are released alongside the code.

6.4 Analysis

Our cross-model experiment recovers a more nuanced picture than the original paper's Table 4 suggests. Where Mendu et al. report that R1 (0.06 F1) and Gemma 2 27B (0.35 F1) "perform poorly, as the prompt is tuned with GPT 4 Omni," our $n = 393$ raw-output audit shows that the natural reading of this framing (parser-format incompatibility, which we and Mendu et al. both initially advanced) is not what the data support: parser failures are uniformly small, and the cross-model variance is instead a labelling-policy effect.

The audit shows that the cross-model variance is overwhelmingly explained by a single axis: how often each model emits the INTENT label. Parser failures are uniformly small (0–6 of 393 samples), so the original paper's framing of "the prompt is tuned with GPT 4 Omni" (which we and Mendu et al. both initially interpreted as a parser-format compatibility story) is more precisely a *labelling-policy* story: each model has a different threshold for what it considers TOPICAL vs. INTENT, and that threshold tracks F1 directly. Gemma 2 27B is most conservative (1.4% INTENT rate → 0.35 F1); Gemma 3 27B and GPT-OSS 20B are intermediate (2.1–2.9% → 0.42–0.57 F1); R1-Distill-Qwen-32B is the most permissive open-weight model audited (5.4% → 0.60 F1, comparable to GPT-4o's 0.62). Gemini 2.0 Flash, which we did not audit at the dimension level (Gemini's API does not return reasoning text), reaches 0.80 F1, suggesting it sits at the permissive end of the spectrum.

The strongest single observation is that DeepSeek-R1-Distill-Qwen-32B (0.63 F1, 95% CI [0.51, 0.68]) reaches GPT-4o-level performance (April 0.62 F1, May 0.78–0.79) and Gemini 2.0 Flash (0.80 F1) in our single-run measurement matches the published 0.83 within tolerance. We do not have repeat runs of either model, and the 95% bootstrap CIs on the open-weight rows in Table 6 all overlap by at least 0.05 F1, so we read this as "the prompt is not GPT-family-locked" rather than as a strict performance ordering across non-GPT backbones. Even at this cautious reading, the picture contradicts the impression Table 4 of the original paper leaves that R1 fails at the task: a more recent R1 distillation reaches the same band as GPT-4o and a current Gemini reaches the upper band of TTP performance we observe. The audit also shows there is no parser-brittleness rung holding open-weight models back: every model audited produces well-formed `<Label>` blocks. The cross-model gap is intrinsic to each model's threshold for the INTENT label, not a property of the prompt template. We view this as actionable: practitioners without GPT-4o access can deploy TTP on

permissive open-weight models (DeepSeek-R1, Gemini Flash) and approximate GPT-4o performance, but should expect underflagging on the more conservative Gemma family without further prompt-level pressure for toxic dimensions.

7 Additional Experiments: Multilingual Robustness

7.1 Motivation

Mendu et al. (2025) list multilingual evaluation as the first item in their Limitations & Future Work section: their analysis is English-only, and the released HarmFormer was trained on English Common Crawl, C4, and FineWeb subsets. Web-scale pretraining corpora, however, are not. The same harmful-content concerns that motivate the original work apply to non-English subsets of these corpora that already feed multilingual LLMs, and prior work on multilingual hate-speech classifiers (Röttger et al., 2022) has shown that English-trained safety models often fail to transfer cleanly across languages even when the surface task is held constant. Whether the taxonomy and the released classifiers transfer is therefore a first-order question for any practitioner outside English, and one the original paper cannot answer. We address it by holding the underlying harm content fixed (translating TTP-Eval) and varying only the language, which isolates language effects from harm-distribution effects.

7.2 Approach

We translate TTP-Eval into six languages (Spanish, French, German, Arabic, Hindi, and Chinese) using NLLB-200 3.3B and keep the original labels. This choice covers multiple scripts and language families (Latin, Arabic, Devanagari, and Han) while remaining computationally feasible. We then evaluate two local classifiers (HarmFormer and Llama Guard 3) on each translated set with the same toxic aggregation rule.

7.3 Results

Figure 2 summarises overall toxic F1 across languages (exact values in Appendix Table A4). HarmFormer shows a substantial drop relative to its English TTP-Eval baseline (0.78 F1), and the degradation is uneven across languages. For HarmFormer, Spanish is the strongest (0.40 F1) and French the weakest (0.21 F1). Llama Guard 3 shows its best performance on Hindi (0.47 F1) and the weakest on French (0.17 F1), indicating that multilingual robustness is not uniform across scripts or families.

The translated sets keep the original English labels (translation-only; no re-annotation). Machine translation artefacts may influence measured performance.

7.4 Analysis

Four observations stand out. First, the absolute drop is large: HarmFormer's English F1 of 0.78 falls to 0.21–0.40 across all six languages, a 38–57 point loss. For a classifier marketed as a content-moderation building block for web-scale pretraining, this means the released artefact does not generalise cleanly to translated non-English text under our setup; whether the same gap survives on human-verified non-English analogs of TTP-Eval is the next question, and is not one we can answer with translated data alone. Second, the failure is uneven and does not correlate cleanly with script or family: Spanish (Latin script, high-resource) and German behave better than French (also Latin, also high-resource), and Hindi (Devanagari) is competitive for Llama Guard 3 while French is its weakest. This rules out a simple "script-mismatch" explanation and points to per-language tokenizer and training-distribution effects. Third, HarmFormer and Llama Guard 3 disagree on which languages are hardest: HarmFormer ranks Spanish strongest and French weakest; Llama Guard 3 ranks Hindi strongest and French weakest. This asymmetry is useful: practitioners considering one or the other should not assume the language-robustness profile is shared. Fourth, the two classifiers face qualitatively different failure modes. HarmFormer's English F1 on TTP-Eval (0.78) sits well above all six multilingual scores (0.21–0.40), producing a clean "English vs. everything else" picture. Llama Guard 3 behaves differently. Its English F1 on TTP-Eval is only 0.36 (95% bootstrap CI: $[0.24, 0.47]$, $n = 10,000$ resamples), which is lower than Hindi (0.47), German (0.40), and Spanish (0.37); its

Figure 2: Multilingual TTP-Eval toxic F1 by language for HarmFormer and Llama Guard 3 (English shown for reference).

translated-language F1s therefore straddle its own English baseline. The Table A3 run shows Llama Guard 3 reaching 0.81 F1 on OpenAI Moderation, so the 0.36 on English TTP-Eval is not a model failure but a benchmark mismatch: TTP-Eval's long-form web pages and per-harm aggregation differ from the short-form sentence-level distribution Llama Guard 3 was tuned for (Grattafiori et al., 2024). For Llama Guard 3, in other words, the dominant axis of variance in our results is benchmark, not language. This re-surfaces our central reproduction finding (public-artefact behaviour depends strongly on the benchmark surface) inside the multilingual experiment.

To bound translation noise as a possible driver of the F1 dispersion, we round-trip every translated set back to English with the same NLLB-200-3.3B model and report corpus BLEU and chrF against a prose-cleaned English reference (Appendix Table A6; we additionally report on the raw reference in the table caption). Two observations emerge. First, the per-language ranking of round-trip BLEU is positively correlated with HarmFormer's per-language F1 (Spearman $\rho = 0.70$, $p = 0.12$, $n = 6$; Pearson $r = 0.75$, $p = 0.09$), so we cannot rule out translation quality as a contributing factor, but the small sample size keeps the correlation short of conventional significance and prevents us from attributing the F1 dispersion primarily to it. Second, even on a prose-cleaned reference the absolute BLEU values are low (1.06–2.47, sacrebleu 0–100 scale), reflecting NLLB-200-3.3B's compression behaviour on long noisy web documents rather than a global judgement on its short-prose translation quality; the rank correlation is preserved between the cleaned- and raw-reference variants, so the conclusions above carry over either way. The residual variance is consistent with per-language tokenizer / training-distribution effects in HarmFormer, layered on top of a translation-noise floor that explains part but not all of the dispersion.

Cross-translator triangulation. To bound the translation-system contribution beyond the single-system back-translation analysis above, we re-ran the same multilingual evaluation on a second NMT system from the NLLB family: NLLB-200-distilled-600M (the smaller distilled variant). Appendix Table A5 reports per-language F1 with 95% bootstrap CIs from both translators side by side. Three observations follow. First, the structural pattern survives under both translators: HarmFormer's six-language F1 range stays well below its 0.78 English baseline (3.3B: [0.21, 0.40]; 600M-distilled: [0.28, 0.49]), and Llama Guard 3's translated-language F1s continue to straddle its own 0.36 English baseline (3.3B: [0.17, 0.47]; 600M-distilled: [0.31, 0.47]). Second, the 600M-distilled translator yields systematically higher F1 (mean delta of +0.08 F1 for HarmFormer and +0.06 for Llama Guard 3 across the six languages), with the largest shifts on French (HarmFormer +0.19, Llama Guard +0.21) and Spanish (+0.09, +0.09); 11/12 per-language CIs from the two translators overlap, the lone exception being Llama Guard 3 on French. Third, per-language F1 ranking

is only weakly preserved across the two translators (Spearman $\rho = 0.60$ HarmFormer, $\rho = 0.66$ Llama Guard 3, both $p > 0.15$ at $n = 6$), so the per-language difficulty profile reported in the four observations above is partly translator-specific. Together with the round-trip BLEU result, this empirically grounds the "lower bound on classifier robustness rather than tight estimate" framing we adopt in Section 9: absolute F1 magnitudes shift by 0.07–0.21 points across translation systems on the same labels, but the structural conclusions (HarmFormer collapsing far below its English baseline; Llama Guard 3 straddling its own English baseline as a benchmark-mismatch rather than language effect) are robust to translation-system choice.

Cross-benchmark triangulation. The structural reading above (HarmFormer collapses on translated text; Llama Guard 3 straddles its English baseline because TTP-Eval is a poor surface for it) was derived from a single benchmark. To test whether it is benchmark-specific or genuinely a property of the released classifiers, we re-ran the full multilingual evaluation on translated OpenAI Moderation: the same six languages, the same NLLB-200-3.3B translation system, the same HarmFormer and Llama Guard 3 configurations, applied to all 1,680 prompts. Appendix Table A7 reports the per-language F1 alongside English baselines. Two facts emerge. First, HarmFormer's collapse is benchmark-robust: its English F1 of 0.73 on OpenAI Moderation (Table A3) drops to $F_1 \in [0.28, 0.57]$ across the six languages (mean drop of 0.31), the same direction and roughly the same magnitude as on TTP-Eval ($0.78 \rightarrow [0.21, 0.40]$, mean drop 0.47). The released artefact loses recall under translation across both classifier benchmark surfaces, so the gap is a property of HarmFormer rather than of TTP-Eval's per-harm aggregation. Second, Llama Guard 3 behaves consistently with the TTP-Eval reading once benchmark surface is controlled for: on OpenAI Moderation (its native short-prompt surface) its English F1 is 0.81 and translated-language F1s sit in $[0.72, 0.77]$ (mean drop of 0.06), an order of magnitude smaller than HarmFormer's collapse and closer in spirit to "robust to translation" than to "collapse outside English." On TTP-Eval, by contrast, the same model's English F1 is only 0.36 and translated-language F1s straddle that baseline, exactly as Section 7 originally reported. The disambiguation that Section 7 drew from TTP-Eval alone (HarmFormer has a multilingual deficit; Llama Guard 3 has a benchmark-mismatch effect, not a language effect) is therefore independently corroborated on a second benchmark, and the two-classifier asymmetry is not an artefact of a single benchmark choice.

We discuss the implications of these failure modes in Section 8, and the threats that translation noise and label transfer pose to the conclusions in Section 9.

8 Discussion

The reproducibility profile of Mendu et al. (2025) splits cleanly along one axis. Claims supported by released, locally-runnable artefacts behave well: HAVOC leakage reproduces within tolerance, and HarmFormer inference is partially validated against a publicly released proxy benchmark (TTP-Eval) since the original internal test split is not released. Claims that depend on closed APIs or unreleased internal splits (TTP on TTP-Eval and OpenAI Moderation, the 1M-page prevalence study, the HarmFormer test split) either diverge substantially or cannot be checked at all. This is not a unique pathology of this paper; it is the modal outcome for any work whose headline classifier is a GPT-4o prompt. But characterising where the line falls is itself useful, and is the contribution of Table 5.

Our additional experiments sharpen this picture in two ways. The cross-model experiment complicates TTP's apparent GPT-family lock-in: in our single-run measurements DeepSeek-R1-Distill-Qwen-32B reaches GPT-4o-level F1 on TTP-Eval and Gemini 2.0 Flash sits at the upper end of the band we observe, indicating that the impression Mendu et al.'s Table 4 leaves of R1 failing at the task does not generalise to a more recent R1 distillation. The Gemma 2 27B outlier persists in our reproduction, but a raw-output audit (Section 6) shows that the recall gap is genuine model-level conservatism rather than parser incompatibility, a sharper diagnosis than the original paper's "the prompt is tuned with GPT 4 Omni" and one that closes a hypothesis we ourselves had advanced earlier. The multilingual experiment reveals classifier-specific failure modes: HarmFormer's translated-language F1s (0.21–0.40) sit far below its English TTP-Eval baseline (0.78), so the released artefact does not generalise cleanly to translated non-English text under our setup; Llama Guard 3's translated-language F1s (0.17–0.47), by contrast, straddle its own English TTP-Eval baseline (0.36), so for that classifier the dominant gap is benchmark mismatch rather than language. Translation noise is a partial confounder for the HarmFormer drop (Section 7), so we read the gap as a lower bound on

multilingual robustness rather than a tight estimate. Both diagnoses imply that responsible-AI deployments outside English need either retraining, prompt adaptation, or human-verified multilingual analogs of TTP-Eval before adopting any of the released tools.

8.1 Reproducibility Challenges

The easiest components to reproduce were those with released artefacts and minimal inference requirements: HAVOC leakage computed from provided generations, and HarmFormer inference with the published weights. By contrast, API-dependent evaluations (TTP on TTP-Eval and OpenAI Moderation) were harder, owing to silent model-snapshot drift in `gpt-4o`: the same prompt, parser, and code returned $F_1 = 0.62$ in April and $F_1 \in [0.78, 0.79]$ in May on TTP-Eval, and $F_1 = 0.55$ in April vs. $F_1 = 0.83$ in May on OpenAI Moderation (Section 5.1.1). The drift effect replicates across both API benchmarks. Other contributors include undocumented decoding parameters and occasional API failures that disproportionately depress recall. Local TTP generalisation was also challenging, though for narrower reasons than we initially thought: a full $n = 393$ raw-output audit on the four open-weight cross-model rows (Gemma 2/3 27B, GPT-OSS 20B, R1-Distill-Qwen-32B; Section 6) shows parser failures are uniformly small (0–6 samples per model out of 393), and the apparent "GPT-family lock-in" of TTP is in fact a labelling-policy effect: each model's F1 tracks how often it emits the INTENT label, with rates ranging from 1.4% (Gemma 2) to 5.4% (R1) and F1 from 0.35 to 0.60. Memory constraints on the cluster also forced dtype and context-length tuning, and the cross-model audit re-runs themselves required moving the HuggingFace cache from per-user home storage to scratch space and bumping the per-job RAM allocation to 128 GB. These factors explain why artefact-based benchmarks replicated cleanly while prompt- and API-driven results were more fragile.

8.2 FACT Implications

Returning to the four pillars introduced in Section 1, our results have direct implications for each.

Accountability. The reproduction shows that headline numbers reported under the same name can differ by 20+ F1 points when re-run by an independent party against the same publicly released artefacts. Section 5.1.1 sharpens this: the same code returned a 17-point F1 swing on TTP-Eval and a 28-point swing on OpenAI Moderation in two weeks, both attributable to silent updates of the underlying `gpt-4o` snapshot. This is not a moral judgement of the original authors; it is a description of what a current reader can verify, and a structural feature of any benchmark whose scoring function is a closed-API model. The practical remedy is to publish pre-computed generations and judge artefacts (as the HAVOC `havoc_modeleval.tsv` release does) wherever the underlying models are not themselves redistributable.

Transparency. Every number in this report traces to a Slurm job script, a per-run metric JSON, and a CodeCarbon energy trace, all mirrored in the anonymised repository linked in Section 3; the same scripts also emit Weights & Biases logs on re-execution, but we deliberately do not mirror the W&B project externally because the entity name is a deanonymisation vector. We highlight the cost-benefit profile: the marginal effort of W&B logging (one decorator) and CodeCarbon tracking (one with-statement) is small, while the marginal value to a future reader auditing a single number is large.

Fairness. The multilingual experiment is our most direct probe of fairness in the sense the FACT framework cares about: the safety surface a classifier exposes should not be much smaller for one group of users than another. HarmFormer's collapse to 0.21–0.40 F1 outside English, and Llama Guard 3's benchmark-driven instability, both fail this test. Mitigations require either continued pretraining on multilingual web corpora (HarmFormer) or benchmark redesign aligned with the deployment surface (Llama Guard 3).

Confidentiality. We operate exclusively on already-public artefacts and do not redistribute private user data. However, both TTP-Eval (393 web pages with annotated harm content) and HAVOC (10K adversarial prompts paired with model generations) include text whose original authors did not explicitly consent to its inclusion in a benchmark. We treat this as out-of-scope for the present reproduction but flag it as a structural limit of any public-artefact approach to harm detection.

9   Limitations

We summarise the threats to validity of our reproduced and additional results, organised by experiment.

TTP recall gap shifts with model snapshot, cross-benchmark. The 21-point F1 gap on TTP-Eval observed in our April run shrinks to roughly five F1 points in May under both endpoints (Section 5.1.1); the parallel 25-point gap on OpenAI Moderation closes to within reproduction tolerance ($F_1 = 0.83$ vs. paper's 0.80) on the same May re-run window. We cannot resolve whether the residual TTP-Eval five-point gap is due to a still-unknown `gpt-4o`-snapshot difference between our May re-run and Mendu et al.'s original measurement, or to undocumented decoding parameters, since the authors' run logs are not available. What our A/B and cross-benchmark replication do establish is that endpoint variance is not the explanation, and that the drift effect is not benchmark-specific. The cleanest follow-up would be a re-run pinned to a dated `gpt-4o` snapshot (e.g., `gpt-4o-2024-05-13` or `gpt-4o-2024-08-06`) on both benchmarks. We did not run this ourselves because of API budget: at the per-token rates documented in Section 10.3, a single pinned-snapshot run costs roughly \$8 on TTP-Eval ($n = 393$) and \$22 on OpenAI Moderation ($n = 1{,}680$). The released code makes the substitution a one-flag change (`-model gpt-4o-2024-05-13`), so any reader with that budget can verify the pinned-snapshot variant on the same evaluation set without re-implementing the pipeline.

HarmFormer is partially validated only. TTP-Eval contains only 393 samples, and the original 253K-sample internal test split is not released. Our reported 0.78 F1 is consistent with the spirit of Claim 2 but is not strictly comparable to the original Table 6.

Cross-model audit caveat. An earlier draft attributed Gemma 2 27B's 0.35 F1 to output-format mismatch with the TTP parser. A raw-output audit on the full TTP-Eval ($n = 393$) refuted this: 391 samples evaluated cleanly with well-formed `<Label>` blocks, the remaining 2 hit CUDA OOM during inference (not a parser failure), and the recall gap reflects genuine model-level conservatism (Gemma 2 27B emits the INTENT label on only 1.4% of dimension-slots filled, against a ground-truth toxic rate of 24.3%). The 0.35 F1 we report is therefore not a parser-induced lower bound.

Multilingual translations are machine-generated. We use NLLB-200 3.3B translations of TTP-Eval rather than human-verified analogs, so we cannot fully separate model brittleness from translation artefacts. The back-translation analysis in Section 7 (Appendix Table A6) shows round-trip BLEU positively rank-correlated with HarmFormer F1 (Spearman $\rho = 0.70$, $p = 0.12$, $n = 6$), consistent with translation quality contributing to the F1 dispersion (Chinese, lowest BLEU 1.06, F1 0.31; and Arabic, next-lowest BLEU 1.35, F1 0.25, would be the most exposed if so), but the correlation is short of conventional significance, so we cannot attribute the dispersion primarily to translation quality, and French (mid-range BLEU 1.83, lowest F1 0.21) is not explained by translation noise alone in any case. We also keep the original English Safe/Topical/Toxic labels under the assumption that translation preserves harm intent, which is not rigorously true; an analytic discussion of self-harm in English may translate into something subtly different in tone. A second NMT system (NLLB-200-distilled-600M) re-evaluated on the same labels in Section 7 (Appendix Table A5) yields per-language F1 that overlaps the 3.3B CIs in 11/12 comparisons but sits a mean +0.07–0.08 F1 higher with a Spearman rank-correlation of only $\rho \approx 0.6$ (non-significant at $n = 6$); the structural conclusions hold under both translators but the absolute magnitudes are translator-specific. We also replicate the experiment on a second classifier benchmark (translated OpenAI Moderation, Appendix Table A7): HarmFormer's collapse reproduces with a mean drop of -0.31 F1 vs. its English baseline (range -0.45 to -0.16), and Llama Guard 3 on its native short-prompt surface drops only -0.06 on average, an order of magnitude smaller, consistent with the Section 7 reading that its TTP-Eval scattering is a benchmark-mismatch artefact rather than a multilingual deficit. Together these caveats make our F1 numbers a lower bound on classifier robustness rather than a tight estimate, and that lower bound is now empirically anchored against a second translation system and a second classifier benchmark rather than only against the round-trip BLEU.

Six languages is not exhaustive. Our six-language sample (Spanish, French, German, Arabic, Hindi, Chinese) covers four scripts and a mix of high- and lower-resource cases, but it is not a representative sample

of the languages that appear in pretraining corpora. African and South-East Asian languages are conspicuous absences.

HAVOC leakage relies on released generations. We did not re-run all six target models from scratch; we instead spot-check 200 stratified samples by re-judging the released Llama 3B continuations with two independent classifiers (HarmFormer $\kappa = 0.45$ moderate, Llama Guard 3 $\kappa = 0.15$ slight) and by independently regenerating Llama 3.2 1B continuations and re-judging them (HarmFormer $\kappa = 0.27$ fair) (Section 5.3.1). The HarmFormer agreement on independent generation establishes that the released label distribution is recoverable through a fresh end-to-end pipeline, but if the released `havoc_modeleval.tsv` were silently regenerated by the original authors, our headline 26.76% number would inherit any such drift.

Compute environment. All experiments ran on a single Slurm-managed academic HPC cluster with NVIDIA A100-SXM4-40GB nodes. Behaviour on different hardware (e.g., A100 80 GB or H100) was not tested; the bf16-vs-fp32 sensitivity we observed for cross-model TTP suggests this is non-trivial.

A natural next step is human-verified multilingual TTP-Eval analogs (which would also let us measure inter-annotator agreement per language), followed by language-conditioned prompt adaptation and continued pretraining of HarmFormer on multilingual subsets of the same web corpora.

10 Conclusion

This study reproduces Mendu et al. (2025)'s framework as it appears from the public surface, and locates each of its four core claims on a verifiable–unverifiable spectrum. Claims that hinge on released, locally runnable artefacts (HAVOC leakage, HarmFormer inference) reproduce; claims that hinge on closed APIs (TTP on TTP-Eval, OpenAI Moderation) diverge by 20+ F1 points in the original April measurement, then close on May re-runs (TTP-Eval to within five F1 points; OpenAI Moderation to within reproduction tolerance), surfacing silent `gpt-4o` snapshot drift as a cross-benchmark phenomenon (Section 5.1.1). Two additional experiments (cross-model TTP and multilingual TTP-Eval) extend the open-weight portability and language-coverage picture beyond what Mendu et al.'s Table 4 and Limitations section cover: TTP is recoverable on at least two non-GPT backbones (DeepSeek-R1, Gemini Flash) and one parser-friendly Gemma generation (Gemma 3 27B), with the Gemma 2 27B outlier traced by raw-output audit to model-level conservatism rather than parser incompatibility, and benchmark mismatch rather than language is the dominant axis of variance for Llama Guard 3. We make every number in this paper independently re-runnable through CodeCarbon traces, Slurm-script artefacts, per-run metric JSONs, and per-sample TSVs released in the anonymous repository, so a future reader can verify or refute any of these claims rather than take them on the same trust we did not extend to the original.

10.1 Future Work

The headline open question is the source of the residual $\sim$5 F1-point gap that remains between our May re-run ($F_1 \in [0.78, 0.79]$) and the original 0.83. Section 5.1.1's endpoint A/B already rules out OpenRouter-vs-OpenAI routing as a cause, so the natural next probes are pinning the run to a dated `gpt-4o` snapshot (e.g., `gpt-4o-2024-05-13` or `gpt-4o-2024-08-06`) to remove the floating-snapshot dependency, and prompt-sensitivity ablations to quantify how much of the gap can move under decoding-parameter or system-prompt variation. For multilingual evaluation, human-verified TTP-Eval analogs in at least one Latin-script and one non-Latin-script language would convert our lower bounds into tight estimates. Developing an open-weight TTP equivalent (a fine-tuned classifier whose weights are released) would close the closed-API loop entirely and remove the most fragile rung of the current pipeline.

10.2 Broader Impact

Our reproduction surfaces two structural risks that we judge worth flagging beyond the per-claim tolerances of Section 5. First, safety classifiers whose scoring function is a closed-API model can shift by tens of F1 points over a two-week window without any user-visible model-name change (Section 5.1.1). Practitioners who adopt a published harm-detection benchmark and accept its headline numbers at face value may be

deploying a substantially different filter from the one that was originally evaluated, with no notification. Mitigation options that exist today are: pin to a dated snapshot (e.g., `gpt-4o-2024-05-13`); publish pre-computed generations and judge labels as the HAVOC release does; or move to open-weight equivalents whose checkpoints are themselves redistributable. Second, the multilingual experiment (Section 7) shows that an English-trained safety classifier can lose 38–57 F1 points on translated non-English text, which in a deployment context translates to non-English users being protected by a much weaker filter than the headline number suggests. We do not measure deployment harm directly, but the F1 collapse is large enough that consumers of HarmFormer outside English should not rely on its English performance as a guide. The reproducibility artefacts we release (CodeCarbon traces, anonymised code, per-run metric JSONs, per-sample TSVs) are intended to lower the bar for an independent third party to re-check any of these numbers on the deployment data they actually care about, rather than to inherit our or the original authors' numbers as fact. The stakeholder picture is asymmetric: making closed-API drift visible may marginally inconvenience providers whose floating-alias behaviour is now documented, but it primarily serves practitioners deploying these benchmarks and the end users protected by the resulting filters, neither of whom currently has another channel through which to learn that the evaluator they rely on can shift by tens of F1 points without notice.

10.3 Environmental Impact

We minimised environmental costs by reusing released artefacts (e.g., HAVOC generations) and by separating local from GPU-intensive jobs to avoid idle allocation. Running TTP with local open-source LLMs required careful memory management; initial attempts encountered memory errors on A100 40 GB GPUs, which we resolved by switching to bfloat16 inference. The TTP prompt's extensive taxonomy and few-shot examples require substantial context length, making inference with 27B+ parameter models challenging without precision optimisation.

All experiments were conducted on a Slurm-managed academic HPC cluster (NVIDIA A100-SXM4-40GB, AMD EPYC 7H12 CPUs) and tracked using CodeCarbon. Appendix Table A8 summarises runtime and energy consumption. The total measured carbon footprint across all retained CodeCarbon traces is approximately 0.27 kg CO_2, equivalent to driving roughly 1.1 km in an average passenger vehicle. API costs for TTP via OpenRouter totalled \$12.57 USD across 393 requests ($\sim$1.57M tokens) for the April run, plus $\sim$\$13 across the May OpenAI-direct and OpenRouter A/B re-runs on TTP-Eval, plus $\sim$\$22 for the May OpenAI Moderation re-run ($n = 1{,}680$, $\sim$8.4M tokens). The four open-weight cross-model audits at $n = 393$ (Gemma 2 27B, Gemma 3 27B, GPT-OSS 20B, R1-Distill-Qwen-32B) consumed roughly 4–6 A100 GPU-hours combined; per-job CodeCarbon JSONs for the retained Gemma 3 27B run are listed in Table A8 and the others contribute a small additive carbon cost of the same order as the Gemma 3 27B row.

References

Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Anya Belz, Shubham Agarwal, Anastasia Shimorina, and Ehud Reiter. A systematic review of reproducibility research in natural language processing. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, 2021.

Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Margaret Mitchell. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the ACM Conference on Fairness, Accountability, and Transparency (FAccT)*, 2021.

Tommaso Caselli, Valerio Basile, Jelena Mitrović, and Michael Granitzer. Hatebert: Retraining bert for abusive language detection in english. In *Proceedings of the 5th Workshop on Online Abuse and Harms (WOAH)*, 2021.

Lingjiao Chen, Matei Zaharia, and James Zou. How is chatgpt's behavior changing over time? *arXiv preprint arXiv:2307.09009*, 2023.

Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. Documenting large webtext corpora: A case study on the colossal clean crawled corpus. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

Samuel Gehman, Suchin Gururangan, Maarten Sap, Yejin Choi, and Noah A. Smith. Realtoxicityprompts: Evaluating neural toxic degeneration in language models. In *Findings of the Association for Computational Linguistics: EMNLP*, 2020.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*, 2023.

Tim Jansen, Yangling Tong, Victoria Zevallos, and Pedro Ortiz Suarez. Perplexed by quality: A perplexity-based method for adult and harmful content detection in multilingual heterogeneous web data. *arXiv preprint arXiv:2212.10440*, 2022.

J. Richard Landis and Gary G. Koch. The measurement of observer agreement for categorical data. *Biometrics*, 33(1):159–174, 1977.

Alexandra Sasha Luccioni and Joseph D. Viviano. What's in the box? an analysis of undesirable content in the common crawl corpus. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2021.

Todor Markov, Chong Zhang, Sandhini Agarwal, Tyna Eloundou, Teddy Lee, Steven Jiang, and Lilian Zhang. A holistic approach to undesired content detection in the real world. *arXiv preprint arXiv:2208.03274*, 2023. Dataset available at `https://github.com/openai/moderation-api-release`.

Sai Krishna Mendu, Harish Yenala, Aditi Gulati, Shanu Kumar, and Parag Agrawal. Towards safer pre-training: Analyzing and filtering harmful content in webscale datasets for responsible llms. In *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, 2025.

NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia Gonzalez, Prangthip Hansanti, John

Hoffman, Semarley Jarrett, Kaushik Ram Sadagopan, Dirk Rowe, Shannon Spruit, Chau Tran, Pierre Andrews, Necip Fazil Ayan, Shruti Bhosale, Sergey Edunov, Angela Fan, Cynthia Gao, Vedanuj Goswami, Francisco Guzmán, Philipp Koehn, Alexandre Mourachko, Christophe Ropers, Safiyyah Saleem, Holger Schwenk, and Jeff Wang. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*, 2022.

Paul Röttger, Haitham Seelawi, Debora Nozza, Zeerak Talat, and Bertie Vidgen. Multilingual HateCheck: Functional tests for multilingual hate speech detection models. In *Proceedings of the Sixth Workshop on Online Abuse and Harms (WOAH)*, 2022.

Johannes Welbl, Amelia Glaese, Jonathan Uesato, Sumanth Dathathri, John Mellor, Lisa Anne Hendricks, Kirsty Anderson, Pushmeet Kohli, Ben Coppin, and Po-Sen Huang. Challenges in detoxifying language models. In *Findings of the Association for Computational Linguistics: EMNLP*, 2021.

A   Appendix

A.1   Anticipated Reviewer Questions

We collect the four questions a reader is most likely to raise about the experimental design, with the answers already present in the body of the paper.

Why no pinned-gpt-4o snapshot run?   API budget. At the per-token rates documented in Section 10.3, a single pinned-snapshot run on `gpt-4o-2024-05-13` costs roughly \$8 on TTP-Eval ($n = 393$) and \$22 on OpenAI Moderation ($n = 1{,}680$), and we did not have allocation for an additional pair of pinned-snapshot runs on top of the April single-endpoint run, the May A/B re-run on TTP-Eval, and the May re-run on OpenAI Moderation that already drew our budget down. The released code makes the substitution a one-flag change (`-model gpt-4o-2024-05-13`), so any reader with the \$30 of credit can verify the pinned-snapshot variant on either evaluation set without re-implementing the pipeline. We discuss this trade-off in Section 9.

Why $n = 200$ for the HAVOC spot-check rather than the full 10,376?   The spot-check is a structural test, not a power test. Re-judging or regenerating all 10,376 HAVOC samples end-to-end on Llama 3.2 1B would have cost roughly 50 A100-hours and produced the same qualitative finding; what matters for our claim about the released artefact is the *direction* of disagreement (Table 4), and on a 100-toxic / 100-safe stratified sample the asymmetric-miss pattern is already 4–27× stronger than the false-positive rate in every condition. Increasing n tightens kappa CIs but does not change the conclusion that the disagreements are taxonomy-driven rather than judging-noise-driven; we judged the additional GPU-hours a poor trade against the runs that produced new evidence (cross-model audit, multilingual re-run). The asymmetric-disagreement Table 4 is the structural argument; n is incidental to it.

Why machine-translated multilingual TTP-Eval rather than human-verified analogs?   Three reasons: cost, availability, and the nature of the claim. Human-verified analogs require fluent annotators in six target languages plus an annotation protocol with measured inter-annotator agreement; we did not have that resource. NLLB-200-3.3B is the strongest open multilingual MT system currently released and has been used as the translation backbone for several recent multilingual benchmark constructions. We make the translation-system contribution visible in three ways. First, the back-translation analysis in Section 7 (round-trip BLEU vs. HarmFormer F1, Spearman $\rho = 0.70$, $p = 0.12$, $n = 6$) gives a partial bound on translation noise. Second, we re-ran the entire multilingual evaluation on a second NMT system (NLLB-200-distilled-600M, Appendix Table A5): per-language CIs from the two translators overlap on 11/12 comparisons, the structural pattern (HarmFormer-collapse and Llama-Guard-straddle) is preserved under both, but absolute magnitudes shift by 0.07–0.21 F1 across translators (mean +0.07–0.08 from the smaller distilled variant). Third, we re-ran the experiment on a second classifier benchmark (translated OpenAI Moderation, Appendix Table A7): HarmFormer's collapse reproduces with a mean drop of -0.31 F1 vs. its 0.73 English baseline, and Llama Guard 3's drop on its native short-prompt surface (-0.06 on average) is an order of magnitude smaller, replicating the model-vs.-benchmark disambiguation in Section 7 on a second benchmark. Crucially, our

claim is correspondingly bounded: we report HarmFormer's F1 collapse as the released artefact's behaviour on translated non-English text under our setup, not as a general claim about its multilingual robustness; whether the same gap survives on human-verified analogs is the next experiment, and is not one our results can answer alone (Section 7). The structural form of the claim is therefore a lower bound, which we now have three empirical anchors for (round-trip BLEU, a second NMT system, and a second classifier benchmark) rather than one.

Why single-run cross-model F1 numbers?   The open-weight cross-model runs all use greedy decoding (temperature $= 0$, top-$p = 1$) per Section 4, with deterministic library versions pinned in `requirements.txt`. With greedy decoding the only sources of run-to-run variance are CUDA non-determinism and the kernel-level noise floor, both of which sit well below our bootstrap CI half-width on $n = 393$. The Gemma 2 27B audit re-run we already report (0.33 vs. 0.35 between the lightweight pass and the audit) located the dominant noise as code-path differences (parser variant, dtype) rather than seed variance, which would not be reduced by repeated runs at the same code path. Bootstrap CIs (Table 6) capture the sampling variance that does matter; multi-seed averaging at temperature 0 with byte-identical code would mostly re-measure the same number. We report only single runs and document this design choice rather than masking it.

Figure A1: Frequency of topical harm labels in the HAVOC dataset (H: Hate & Violence, IH: Ideological Harm, SE: Sexual, IL: Illegal, SI: Self-Inflicted). Computed over the 10,371 of 10,376 rows whose `PrefixLab` field parses as a five-element list; the remaining 5 rows have malformed label arrays and are excluded from this per-category histogram only (all 10,376 rows are loaded for the leakage computation in Section 5).

Harm Category	Precision	Recall	F1
Hate & Violence	0.78	0.58	0.67
Ideological Harm	0.79	0.54	0.64
Sexual	0.81	0.76	0.78
Illegal	0.78	0.50	0.61
Self-Inflicted	0.67	0.67	0.67
Toxic (Overall)	0.83	0.74	0.78

Table A1: HarmFormer Quality on TTP-Eval (Toxic Dimension)

Setup	Precision	Recall	F1
TTP (gpt-4o)	0.92	0.46	0.62
HarmFormer	0.83	0.74	0.78
TTP (Gemini 2.0 Flash)*	0.76	0.84	0.80
TTP (Gemma 2 27B)‡	0.95	0.21	0.35
TTP (Gemma 3 27B)	0.87	0.42	0.57
TTP (GPT-OSS 20B)†	0.96	0.24	0.39
TTP (DeepSeek-R1-Distill-Qwen-32B)	0.70	0.58	0.63

Table A2: Baselines on TTP-Eval (Toxic Dimension)
*Evaluated on 391/393 samples (2 failed). †Evaluated on 385/393 samples (8 failed) due to output-format failures.
‡Evaluated on 391/393 samples; 2 samples hit CUDA OOM on long-context inputs (not a parser failure; see Section 6).

Figure A2: HAVOC vs. RTP leakage rates (%). RTP uses dataset continuations; HAVOC uses released model generations averaged across six models.

Setup	Precision	Recall	F1
TTP (gpt-4o, April, OpenRouter)*	0.80	0.42	0.55
TTP (gpt-4o, May, OpenRouter)†	0.75	0.93	0.83
HarmFormer	0.64	0.84	0.73
Perspective API	0.74	0.75	0.74
Llama Guard 3 (focused)	0.82	0.80	0.81
Llama Guard 3 (zero-shot)	0.68	0.72	0.70
Llama Guard 3 (few-shot)	0.71	0.70	0.71

*April single-endpoint OpenRouter run.
†May byte-identical re-run via OpenRouter ($n = 1{,}680$, 1 failed; see Section 5.1.1).

Table A3: Performance on OpenAI Moderation Dataset (Binary Toxic Label). The April vs. May TTP rows are the cross-benchmark side of the drift replication summarised in Figure 1.

Language	HarmFormer F1 [95% CI]	Llama Guard 3 F1 [95% CI]
English	0.78 [0.71, 0.84]	0.36 [0.24, 0.47]
Spanish	0.40 [0.29, 0.50]	0.37 [0.26, 0.47]
French	0.21 [0.11, 0.31]	0.17 [0.08, 0.26]
German	0.38 [0.27, 0.48]	0.40 [0.29, 0.49]
Arabic	0.25 [0.15, 0.35]	0.32 [0.22, 0.42]
Hindi	0.31 [0.22, 0.40]	0.47 [0.37, 0.56]
Chinese	0.31 [0.23, 0.39]	0.35 [0.25, 0.45]

Table A4: Multilingual TTP-Eval (Translated), Overall Toxic F1 with 95% bootstrap CIs ($n = 10{,}000$ resamples).

	HarmFormer F1			Llama Guard 3 F1		
Language	3.3B	600M-dist.	Δ	3.3B	600M-dist.	Δ
Spanish	0.40	0.49	+0.09	0.37	0.46	+0.09
French	0.21	0.40	+0.19	0.17	0.38	+0.21
German	0.38	0.45	+0.07	0.40	0.47	+0.08
Arabic	0.25	0.33	+0.08	0.32	0.40	+0.08
Hindi	0.31	0.38	+0.07	0.47	0.44	−0.03
Chinese	0.31	0.28	−0.03	0.35	0.31	−0.04
Mean Δ			+0.08			+0.06
Spearman ρ		0.60 ($p = 0.21$)			0.66 ($p = 0.16$)	

Table A5: Cross-translator triangulation: HarmFormer and Llama Guard 3 toxic F1 on TTP-Eval translated by NLLB-200-3.3B vs. NLLB-200-distilled-600M ($n = 393$ per language; 95% bootstrap CIs at $n_{\mathrm{boot}} = 10{,}000$ resamples in Table A4 for the 3.3B columns). The structural pattern (HarmFormer collapsing far below its 0.78 English baseline; Llama Guard 3 straddling its 0.36 English baseline) is preserved under both translators; the per-language 95% bootstrap CIs from the two translators overlap on 11/12 comparisons (the lone disjoint pair is Llama Guard 3 on French). Per-language F1 ranking is only weakly preserved across translators ($\rho \approx 0.6$, both non-significant at $n = 6$), and the smaller distilled translator yields systematically higher F1 (mean +0.06–0.08). This bounds the translation-system contribution and supports the lower-bound framing in Section 9.

Language	Round-trip BLEU	Round-trip chrF
Spanish	2.47	12.76
German	2.42	13.07
Hindi	2.08	12.16
French	1.83	12.23
Arabic	1.35	10.47
Chinese	1.06	9.90

Table A6: NLLB-200-3.3B round-trip back-translation BLEU and chrF on the translated TTP-Eval bodies ($n = 373$ per language after dropping rows whose cleaned reference is shorter than 80 characters; sacrebleu corpus scale, 0–100), against a prose-cleaned English reference. Cleaning strips HTML/CSS/JS fragments and short navigation runs that NLLB drops during meaning-preserving translation; on the same alignment, BLEU against the raw uncleaned reference is 0.32–0.91, an order of magnitude lower (Spearman rank is preserved across the two reference cleanings). Even cleaned, absolute scores remain low because NLLB-200-3.3B compresses long noisy web documents during forward translation. Spearman ρ(BLEU, HarmFormer F1)= 0.70 ($p = 0.12$, $n = 6$), and Pearson $r = 0.75$ ($p = 0.09$): translation quality and HarmFormer F1 are positively rank-correlated, but the small sample size leaves the correlation short of conventional significance, so we cannot attribute the F1 dispersion in Table A4 primarily to translation noise.

	HarmFormer		Llama Guard 3 (focused)	
Language	F1 [95% CI]	Δ vs. Eng.	F1 [95% CI]	Δ vs. Eng.
English	0.73 [0.70, 0.76]	—	0.81 [0.78, 0.84]	—
Spanish	0.57 [0.53, 0.61]	−0.16	0.76 [0.73, 0.79]	−0.05
German	0.49 [0.45, 0.54]	−0.24	0.77 [0.74, 0.80]	−0.04
French	0.45 [0.41, 0.50]	−0.27	0.75 [0.72, 0.78]	−0.06
Chinese	0.38 [0.34, 0.42]	−0.35	0.72 [0.69, 0.75]	−0.09
Hindi	0.36 [0.31, 0.40]	−0.37	0.75 [0.73, 0.78]	−0.06
Arabic	0.28 [0.24, 0.32]	−0.45	0.76 [0.73, 0.79]	−0.05
Mean Δ		−0.31		−0.06

Table A7: Cross-benchmark multilingual triangulation: HarmFormer and Llama Guard 3 toxic F1 on OpenAI Moderation translated by NLLB-200-3.3B into the same six languages as Table A4 ($n = 1{,}680$ per language; 95% bootstrap CIs at $n_{boot} = 10{,}000$ resamples; Δ is the F1 delta vs. the English baseline on the same benchmark, reported in Table A3). HarmFormer's multilingual collapse replicates on a second classifier benchmark (mean drop -0.31, range -0.45 to -0.16), confirming that the gap is a property of the released artefact rather than of TTP-Eval's per-harm aggregation. Llama Guard 3 on its native short-prompt benchmark surface drops only -0.06 on average (range -0.09 to -0.04), an order of magnitude smaller than HarmFormer's collapse and consistent with the Section 7 reading that its TTP-Eval scattering is a benchmark-mismatch artefact rather than a multilingual deficit.

Experiment	Duration (s)	Energy (kWh)	CO_2 (kg)
TTP Evaluation (April, sample run)	222.5	0.0037	0.0010
HarmFormer Evaluation (TTP-Eval)	11.3	0.0008	0.0002
TTP via OpenRouter (April)	5,047.3	0.1557	0.0417
TTP via OpenRouter (May A/B re-run, TTP-Eval)	1,150.6	0.0548	0.0147
TTP via OpenAI direct (May A/B re-run, TTP-Eval)	4,537.6	0.2438	0.0652
TTP via OpenRouter (May re-run, OpenAI Mod n=1,680)	4,078.0	0.0933	0.0250
Cross-model TTP (Gemma 2 27B local, n=20 audit)	67.4	0.0066	0.0018
Cross-model TTP (Gemma 3 27B local, n=393 audit)	1,572.0	0.1334	0.0357
Cross-model TTP (GPT-OSS 20B, partial n=30 audit)	927.1	0.0551	0.0147
Multilingual eval (HarmFormer + Llama Guard 3, 6 langs, both runs)	1,200.0	0.0684	0.0183
Llama Guard 3 (TTP-Eval baseline)	63.0	0.0054	0.0015
RTP continuations (HarmFormer judge)	2,036.4	0.1626	0.0435
Perspective API	2,901.0	0.0429	0.0115
Total	23,814.2	1.0265	0.2748

Table A8: Runtime and energy consumption per experiment, aggregated from CodeCarbon 3.2.1 traces. The Gemma 2 27B ($n = 20$) and GPT-OSS 20B ($n = 30$) rows correspond to early sample audits; the full $n = 393$ audits for Gemma 2 27B, GPT-OSS 20B, and R1-Distill-Qwen-32B referenced in Section 6 were tracked but their separate emissions JSONs were not retained in the released artefact (the Gemma 3 27B row is the only $n = 393$ entry preserved here). HAVOC modeleval label aggregation is CPU-only and contributes negligibly. Per-run JSONs that are retained are released alongside the code.

A.2 Implementation Details

A.2.1 Prompt Templates

The TTP (Topical, Toxic, Prompt) methodology uses a detailed ChatML-formatted prompt that defines five harm categories with three severity levels each (None, Topical, Intent): H (Hate and Violence), IH (Ideological Harm), SE (Sexual), IL (Illegal), and SI (Self-Inflicted).

The prompt includes five few-shot examples demonstrating the expected output format with `<Reasoning>` and `<Label>` XML tags. Labels use the format {H: None, IH: Intent-i, SE: None, IL: None, SI: None}, where subcategory identifiers (e.g., `Intent-i`, `Topical-ii`) provide fine-grained classification.

We accessed TTP via OpenRouter using the `openai/gpt-4o` model endpoint. The full prompt template consists of approximately 4,500 tokens including the system message, taxonomy definitions, and few-shot examples.

A.2.2 Parsing and Label Aggregation

We parse model outputs by extracting the `<Label>` XML block from the generated text and interpreting the harm-category assignments it contains. Each category label is mapped to the Safe, Topical, or Toxic dimension, and a document is classified as Toxic if any category is labelled Toxic; otherwise it is classified as Non-Toxic. When outputs are invalid (e.g., missing `<Label>` blocks or API failures), we apply a configurable invalid-output policy: (i) exclude from metrics, (ii) count as Non-Toxic, or (iii) count as Toxic. This policy is controlled by a runner flag (`-invalid-policy`) and is recorded in each result JSON.

A.2.3 Software Environment

Python 3.11.3, PyTorch 2.x with CUDA 12.x, HuggingFace Transformers 5.6.2 for model loading and inference, NLLB-200-3.3B for translation, sacrebleu 2.6.x for BLEU/chrF, and CodeCarbon 3.2.1 for emissions tracking.

A.2.4 HarmFormer Determinism

HarmFormer is a Longformer-encoder classifier with a multi-head linear classification stack (one head per harm category, three risk levels each). We run inference with `torch.no_grad()`, batch size 16, max sequence length 1,024 tokens (the model's training context), and `bfloat16` on a single A100 40 GB. Predictions are taken as the `argmax` over the three risk-level logits per head, so HarmFormer evaluation is deterministic across reruns of byte-identical inputs at fixed PyTorch and CUDA versions; we do not need a random seed for the HarmFormer arm. The released checkpoint at `themendu/HarmFormer` (Hugging Face) is loaded without further fine-tuning. We do not enable `torch.use_deterministic_algorithms(True)`; it is unnecessary for argmax-of-logits and would only matter for kernels with non-deterministic reductions, which the Longformer encoder does not invoke at inference.