OPTIMAL TRANSPORT-BASED SUPERVISED GRAPH SUMMARIZATION

ABSTRACT

Graph summarization is the problem of producing smaller graph representations of an input graph dataset, in such a way that the smaller "compressed" graphs capture relevant structural information for downstream tasks. One graph summarization method, recently proposed in Garg & Jaakkola (2019), formulates an optimal transport-based framework that allows prior information about node, edge, and attribute importance to be incorporated into the graph summarization process. We extend the optimal transport framework to a supervised graph summarization setting, wherein we seek to preserve relevant information about a class label. We first formulate the problem in terms of maximizing the mutual information between the summarized graph and the class label. We then propose a method that incorporates mutual information estimates between random variables associated with sample graphs and class labels into the optimal transport compression framework from Garg & Jaakkola (2019). We empirically show performance improvements over the previous work by Garg & Jaakkola (2019) in terms of classification and compression on synthetic and real datasets. We then theoretically show limitations of the optimal transport approach: e.g., that it fails to satisfy a certain desirable information monotonicity property.

1 INTRODUCTION

Machine learning involving graphs has a wide range of applications in artificial intelligence Scarselli et al. (2008); Dessì et al. (2020), network analysis, and biological interactions Han et al. (2019); Chen et al. (2020). Graph classification problems use the network structure of the underlying data to improve predictive decision outcomes. However, graph datasets are often enormous, and the algorithms used to extract relevant information from graphs are frequently computationally expensive. Graph summarization addresses these scalability issues by computing reduced representations of graph datasets while retaining relevant information. As with numerous other problems in machine learning, the precise meaning of "reduced representation" does not have one single mathematical definition, and there is no single objective function being optimized. There are thus various approaches to this problem. For a survey, see Liu et al. (2018). The particular type of approach of interest in this paper takes a dataset of graphs and a number k as input and outputs, for each graph G in the dataset, a subgraph H of G is induced by k vertices.

One approach to this problem that allows for the incorporation of user-engineered prior information is the *optimal transport* approach of Garg & Jaakkola (2019). Their approach is as follows: a graph G, a target number k of vertices, a probability distribution ρ_0 on the vertices of G, and a cost function $c : E(G) \to \mathbb{R}$, where $E(G)$ denotes the set of edges of G, are given as input. A probability distribution ρ_1 is computed by minimizing the Wasserstein distance on G between ρ_0 and ρ_1 with respect to the cost function c, with the constraint, that the number of vertices in the support of ρ_1 is at most k. The output subgraph H is the one induced by the vertices in the support of ρ_1. According to Garg & Jaakkola (2019), prior information can be incorporated into the method via appropriately choosing ρ_0 and c. In the present work, we extend this optimal transport approach to graph summarization to a supervised learning context. We propose a novel supervised summarization algorithm, which we show empirically to surpass state-of-the-art performance (including the performance of the specific method proposed in Garg & Jaakkola (2019)) on selected real and synthetic datasets. We propose a natural information-theoretic, such as mutual information (MI) Cover & Thomas (1991); Yasaei Sekeh et al. (2018), objective function by which we may measure the quality of a summarization. Using

this, we explore the limitations of the optimal transport-based approach, both theoretically and empirically. Another aspect that distinguishes our novel perspective from the optimal transport approach in Garg & Jaakkola (2019)) is that we take advantage of the node attributes' information toward the class variables. Our graph compression framework as maximizing the MI between attribute-graph variable and the class variable also introduces new challenges that are relevant to information monotonicity between graphs, node attributes, and the class variable. For example, solving the MI maximizing problem in practice would inspire a new subproblem of estimating MI between an attributed graph and a class variable. This extends the well-studied problem of information-theoretic measure estimation Kraskov et al. (2004); Moon et al. (2017); Noshad et al. (2017). Our approach in this paper leads to a new estimator for MI between attributed graph and class and is inspired by EDGE's fast and relatively accurate implementation Noshad et al. (2019).

Contribution We summarize our contribution in this paper as follows: We *propose* a novel information-theoretic attributed graph summarization framework by incorporating MI between sample graphs and class labels into an optimal transport graph compression approach in a supervised setting. We *theoretically* prove that the problem of maximization MI between attributed graph and class variable with the knowledge of the data distribution is NP-hard. We *address* the limitations of the optimal transport graph compression approach in Garg & Jaakkola (2019). We *experimentally* show that our new supervised graph summarization framework outperforms the baseline (no compression) and the unsupervised OT method in terms of post-compression classification time and test accuracy.

2 PROBLEM FORMULATION: SUPERVISED GRAPH SUMMARIZATION

We formulate the supervised graph summarization problem as follows. We fix a compression ratio $\kappa \in (0, 1)$. A probability distribution $\mathcal{D}$ over tuples (G, X, C) is fixed. Here, the graphs G are defined on a single common set V of vertices, X is a $|V| \times d$ matrix whose rows are d-dimensional feature vectors corresponding to the vertices of G, and C is a class label coming from some fixed set $\mathcal{C}$. A dataset $D \sim \mathcal{D}^m$ consisting of independent and identically distributed (iid) samples from $\mathcal{D}$ is presented to us. Our task is, given D but no knowledge of $\mathcal{D}$, to select a subset $W \subseteq V$ of vertices satisfying the following:

$$W = \underset{U \subseteq V, |U| \leq \kappa |V|}{\arg \max} I((G_U, X_U); C). \tag{1}$$

Here, G_U is the subgraph of G induced by the vertices in U, and X_U is the matrix of corresponding feature vectors. The function $I(\cdot; \cdot)$ is the *Shannon mutual information* Cover & Thomas (2006), defined as follows: for random variables X and Y on a common probability space,

$$I(X; Y) = \mathbb{E}_{P(X,Y)} \left[\log \frac{P(X, Y)}{P(X)P(Y)} \right], \tag{2}$$

where the expectation is taken with respect to the joint distribution of X and Y.

3 PROBLEM FORMULATION: SUPERVISED GRAPH SUMMARIZATION

We formulate the supervised graph summarization problem as follows. We fix a compression ratio $\kappa \in (0, 1)$. A probability distribution $\mathcal{D}$ over tuples (G, X, C) is fixed. Here, the graphs G are defined on a single common set V of vertices, X is a $|V| \times d$ matrix whose rows are d-dimensional feature vectors corresponding to the vertices of G, and C is a class label coming from some fixed set $\mathcal{C}$. A dataset $D \sim \mathcal{D}^m$ consisting of independent and identically distributed (iid) samples from $\mathcal{D}$ is presented to us. Our task is, given D but no knowledge of $\mathcal{D}$, to select a subset $W \subseteq V$ of vertices satisfying the following:

$$W = \underset{U \subseteq V, |U| \leq \kappa |V|}{\arg \max} I((G_U, X_U); C). \tag{3}$$

Here, G_U is the subgraph of G induced by the vertices in U, and X_U is the matrix of corresponding feature vectors. The function $I(\cdot; \cdot)$ is the *Shannon mutual information* Cover & Thomas (2006), defined as follows: for random variables X and Y on a common probability space,

$$I(X; Y) = \mathbb{E}_{P(X,Y)} \left[\log \frac{P(X, Y)}{P(X)P(Y)} \right], \tag{4}$$

where the expectation is taken with respect to the joint distribution of X and Y. To justify (3), as we observe in (4) the mutual information measures the nonlinear dependency between input graphs and class variable, therefore an optimal subset of vertices that provides the maximum such dependency is desired subgraph. While this is a very natural formulation of supervised graph summarization, we immediately run into computational complexity difficulties, as our first main result shows.

Theorem 1 (NP-hardness of supervised graph summarization). *The problem of maximizing W in (3) with knowledge of the data distribution $\mathcal{D}$ is NP-hard.*

Proof: We prove this via a reduction from the k-clique problem to ours. Given a graph G, we would like to determine whether or not it has a k-clique. We will do this by constructing an instance of the supervised graph summarization problem above. We let the class label be $C \sim \text{Bernoulli}(1/2)$. We construct a complete graph G' on the same node set as G. We assign an event E_e to each (undirected) edge e in G' as follows: if e is in G, then we set $E_{v,w}$ to be $E_{v,w} \sim \text{Bernoulli}(p)$, where $p = C/2$, independent of any other edge weight. If, on the other hand, e is not present in G, then we set E_e to be 0. We set all node features to 1. Note that, with this distribution, we have that the mutual information between the subgraph H induced by any set of k nodes in G' is given by

$$I((H, X_H); C) = I(H; C) = \sum_{v \neq w \in H} I(E_{v,w}; C). \tag{5}$$

This is $\binom{k}{2}$ if and only if H is a k-clique in G, and it is less if there are missing edges. Thus, if we could solve our optimization problem in polynomial time, then we could solve the k-clique problem in polynomial time. This completes the proof.

In fact, the reduction that we exhibited yields a stronger result: our approximation problem is, in general, NP-hard to approximate within a constant factor of the optimum. This follows from the NP-hardness of approximation of the max clique problem.

Thus, in the search for practical approaches to graph summarization in a supervised setting, we must be more modest in our expectations, and we do not solve the above optimization problem, though it remains the intuitive motivator of our approach. In Section 4, we describe our approach via optimal transport, which extends the framework of Garg & Jaakkola (2019).

4 SUPERVISED GRAPH SUMMARIZATION VIA OPTIMAL TRANSPORT

In this section, we first describe how optimal transport graph compression is developed and secondly propose a new method that summarizes supervised graphs using MI between the class variable via an optimal transport approach.

4.1 OPTIMAL TRANSPORT ON GRAPHS

We first describe the framework of optimal transport on graphs. Fix a graph G on n vertices $[n] = \{1, 2, ..., n\}$ with edge set $E(G)$. We let $\widehat{E}(G)$ denote the *directed* edge set of G, given by

$$\widehat{E}(G) = \{(v, w) \mid \{v, w\} \in E(G)\}. \tag{6}$$

Let ρ_0, ρ_1 be two probability distributions on $[n]$, viewed as vectors. Let $c : E(G) \to \mathbb{R}$ be an arbitrary *cost function*. A *flow* on G is a function $J : \widehat{E}(G) \to [0, \infty)$. The *cost* of a flow is defined:

$$W(J) = \sum_{e \in \widehat{E}(G)} c(e) J(e). \tag{7}$$

The *result* of a flow J with initial distribution ρ_0 is defined by $R(J) = \rho_0 + F \cdot J$. Finally, the set of flows from ρ_0 with the result ρ_1 is denoted by $\mathcal{F}_G(\rho_0, \rho_1)$. Next we define the Wasserstein distance between ρ_0 and ρ_1 which is the minimum cost of any flow transporting ρ_0 to ρ_1 on G as follows:

$$W_G(\rho_0, \rho_1) = \inf_{J \in \mathcal{F}_G(\rho_0, \rho_1)} W(J). \tag{8}$$

The method proposed in Garg & Jaakkola (2019) takes G, ρ_0, c, and a compression ratio κ as input and finds a ρ_1 with support size $\leq \kappa |V(G)|$ with minimal Wasserstein distance to ρ_0. The

summarizing graph H is then the one induced by the vertices in the support of ρ_1. The selling point of their method is that prior information about "node/edge importance" can be encoded in ρ_0 and c. They perform experiments in which ρ_0 assigns a probability to node v proportional to its degree (so ρ_0 is the stationary distribution of the random walk on G, if it is ergodic) and c assigns a higher cost to edges connecting nodes with different attributes (all of their experiments are on graphs with categorical attributes). Unlike the framework that we develop in the present paper, their framework is not a priori supervised. Furthermore, no justification is given for their choice of ρ_0 and c. In addition, their framework ignores dataset-level statistics (since their setting of ρ_0 and c is entirely dependent on the individual graph being compressed) and ignores the absence of edges, which can be informative.

4.2 OUR METHOD: SUPERVISED OT VIA INFORMATION THEORETIC MEASURES

In this section, we extend the above framework to the supervised setting. The core idea is to use the training dataset to learn measures of informativeness about the class label of node features and edges. We then use these to construct the initial distribution and cost function, which can then be used in the framework of the previous work applied to the complete graph on n nodes to find a subset H of nodes such that the subgraphs induced by H in the test set are informative about the class label while being a small subset of the original vertex set. We note that we run the OT compression algorithm on the complete graph because we wish to take into account the informativeness of edges. The method proposed in the prior work only does this indirectly. We define the initial distribution ρ_0 as follows:

$$\rho_0(v) = \frac{I(X_v; C)}{\sum_{w \in [n]} I(X_w; C)}, \tag{9}$$

where $I(\cdot; \cdot)$ is the MI defined in (4). Next, we propose the cost function $c(\cdot, \cdot)$ as follows:

$$c(v, w) = D_{KL}(E_{v,w} \mid C = 0 \parallel E_{v,w} \mid C = 1) + R_{v,w}, \quad \text{where} \tag{10}$$

$$R_{v,w} = I(X_v; C \mid X_w) + I(X_w; C \mid X_v), \tag{11}$$

and $D_{KL}(A \| B)$ denotes the KL-divergence Cover & Thomas (2006) from a random variable A to a random variable B. The intuition for this definition of ρ_0 is that we consider nodes to be important if their features carry a significant amount of information about the class label.

The intuition behind the definition of c is as follows: in optimal transport, we want a large amount of flow across an edge if and only if the edge itself is not too informative about C, and the feature of one of the vertices incident on the edge is not too informative about C, conditioned on the value of the other vertex's feature (in other words, the vertices contain redundant information about C). In this case, we want the edge cost to be small.

Running the optimal transport compression routine of Garg & Jaakkola (2019) on the complete graph K_n with ρ_0, c, κ as parameters results in a subset H of nodes of cardinality (approximately) κn. To compress a graph G in the test set, we simply take the subgraph of G induced by H.

Crucial to the performance of our method is the ability to estimate the mutual information and KL divergence quantities in the expressions for ρ_0 and c directly without estimating the distributions Yasaei Sekeh & Hero (2018). We chose EDGE Noshad et al. (2019) because it has been shown that it achieves optimal computational complexity $O(N)$ where N is the sample size. This is significantly faster than its plug-in competitors Kraskov et al. (2004); Moon et al. (2017). It is proved that in addition to fast implementation EDGE has the optimal parametric MSE rate of $O(1/N)$ under a specific condition. The KL divergences are estimated via the plug-in method. In Section 6, we evaluate our method on synthetic and generated graphs from real datasets. We show that it empirically outperforms significantly the previous work on all datasets considered.

4.3 MUTUAL INFORMATION FOR A CLASS OF RANDOM GRAPHS

Attributed graphs consider both the topology of the graph and a set of feature attributes that are attached to each node. In this section, we propose mutual information of attributed graph and class label variable. Let $g : (0, \infty) \to \mathbb{R}$ be a convex function with $g(1) = 0$. Given graph G_V with fixed set of vertices $V = \{v_1, \dots, v_k\}$ and features set $X_V = \{X_{v_1}, \dots, X_{v_k}\}$, the mutual information

between (G_V, X_V) and class variable C with prior probability π_C is given by

$$I(G_V, X_V; C) = \mathbb{E}_{P_G, \pi_C} \left[g\left(\frac{P(G_V, X_V, C)}{P(G_V, X_V)\pi_C} \right) \right] = \mathbb{E}_{P_G, \pi_C} \left[g\left(\frac{P(G_V, X_V|C)}{P(G_V, X_V)} \right) \right], \quad (12)$$

where $P_G := P(G_V, X_V)$ and π_C is the prior probability of class C. We assume that the random node attributes are independent i.e. $P(X_V|C) = \prod_{v \in V} P(X_v|C)$:

$$P(G_V, X_V, C) = \pi_C P(G_V, X_V|C) = \pi_C P(X_V|C) P(G_V|X_V, C)$$

$$= \pi_C \cdot \prod_{v \in V} P(X_v|C) \cdot \prod_{\substack{E_{u,v} \in G_V \\ u,v \in V}} P(E_{u,v}|X_u, X_v, C) \cdot \prod_{\substack{E_{u,v} \in G_V \\ u,v \in V}} (1 - P(E_{u,v}|X_u, X_v, C)). \quad (13)$$

5 LIMITATIONS OF THE OPTIMAL TRANSPORT APPROACH

In this section, we explore the limitations of the optimal transport approach for the purposes of maximizing the mutual information of graphs (G, X) with a class label C. To solve this optimization problem via OT we require initial distribution ρ_0 and cost function c. Here, we first specify the kinds of initial distribution and cost function we propose in (9) and (10).

Definition 1 (Data distribution-dependent parameters). *Fix a graph size n. An edge cost function is a function c from the joint distribution of (G, X_G, C) (call this the **data distribution**) and pairs of vertices (i.e., numbers in $[n]$) to non-negative real numbers or ∞. If the data distribution is given, then c is just a mapping from pairs of vertices to $[0, \infty]$.*

Similarly, an initial distribution map L is a mapping from the data distribution to probability distributions on $[n]$ (which are meant to be values for p_0). If the data distribution is given, then p_0 is a function mapping vertices to probabilities (which must sum to 1).

Below we define a property of OT parameter pairs called *information monotonicity*, which guarantees that using a pair with this property, flow cost decreases as the mutual information between the resulting compressed subgraph and the class label increases. We will study to what exent OT parameter pairs satisfy this property.

Definition 2 (Information monotonicity). *An OT parameter pair (c, L) is said to be* information monotone *for a data distribution (G, X_G, C) if, for any two flows $f^{(0)}, f^{(1)}$ on G resulting in subgraphs $H^{(0)}, H^{(1)}$, respectively, we have*

$$W(f^{(0)}) \leq W(f^{(1)}) \iff I((H^{(0)}, X_{H^{(0)}}); C) \geq I((H^{(1)}, X_{H^{(1)}}); C). \quad (14)$$

5.1 A MONOTONICITY COUNTEREXAMPLE

In this section, we construct an example graph for which the Wasserstein distance between p_0 and p_1 is not monotone with respect to the mutual information between the graph and the class label random variable. Let us suppose that all vertex features are independent of the graph structure and of the class label, so they provide no information about either. In this case, p_0 is the uniform distribution over all n vertices. Furthermore, let's suppose that the edges are generated as follows: the class label $C \sim \text{Bernoulli}(p)$, and then, conditioned on $C = c$, each edge e appears with probability $q_e^{(c)}$, independent of everything else. Intuitively, those edges with large $|q_e^{(0)} - q_e^{(1)}|$ provide more information about the value of C.

Set $n = 3$, so we have a triangle. We can cook up settings of $q_e^{(c)}$ such that the costs of the three edges are proportional to $3, 4, 5$ i.e we have the cost function $c(1, 2) = 3$, $c(1, 3) = 4$, $c(2, 3) = 5$ scaled appropriately.

To be more explicit about the calculation of the cost of one edge e, we write:

$$c(e) = D_{KL}(E_e \mid C = 0 \parallel E_e \mid C = 1) = q_e^{(0)} \log\left(\frac{q_e^{(0)}}{q_e^{(1)}}\right) + (1 - q_e^{(0)}) \log\left(\frac{1 - q_e^{(0)}}{1 - q_e^{(1)}}\right). \quad (15)$$

(Note that the R_e term vanishes in our example because of our independence assumption.) The cost $c(e)$ can take any value between 0 and ∞, if suitable values of $q_e^{(0)}$ and $q_e^{(1)}$ are chosen. We thus can cook up choices of these parameters that give exactly the values $3, 4, 5$. Let us consider two flows:

- In one, we set $J(1,2) = J(1,3) = 1/6$ and set the flow across all other edges to 0. The cost of this flow is $3 \cdot 1/6 + 4 \cdot 1/6 = 7/6$. The distribution $p_1 = (0, 1/2, 1/2)$. This leaves in the compressed graph the edge $\{2, 3\}$, which had cost 5 (so, the highest possible mutual information with the class label).
- In the other, we set $J(2,1) = 1/3$ and set all other flows to 0. The cost of this flow is $3 \cdot 1/3 = 1$. The distribution $p_1 = (2/3, 0, 1/3)$. This leaves the edge $\{1, 3\}$, which had cost 4 (so, *not* the highest possible mutual information with the class label).

Discussion: In this counterexample, we used a specific choice of cost function and showed that there is a fundamental limitation of the OT approach in Garg & Jaakkola (2019) for classification problems.

Now, we have the following theorem regarding non-monotonicity of optimal transport solutions with respect to mutual information, which generalizes the above example.

Theorem 2 (Non-monotonicity). *Let $c(\cdot, \cdot)$ be a cost function satisfying the following properties:*

• $c(u, v)$ is strictly monotone increasing with the mutual information between $E_{u,v}$ and C and is 0 when the two are independent.
Let L be an initial distribution map satisfying the following properties:

• if X_G is independent of C, both unconditionally and conditioned on G, then p_0 is the uniform distribution.

Then there exist data distributions for which (c, L) is not information-monotone.

Proof: We will prove this by explicit construction. We first describe the data distribution that leads to our counterexample: Let us suppose that all vertex features are independent of the graph structure and of the class label, so they provide no information about either. In this case, p_0 is the uniform distribution over all n vertices. Furthermore, let's suppose that the edges are generated as follows: the class label $C \sim \text{Bernoulli}(p)$, and then, conditioned on $C = c$, each edge e appears with probability $q_e^{(c)}$, independent of everything else. Intuitively, those edges with large $|q_e^{(0)} - q_e^{(1)}|$ provide more information about the value of C (this is true regardless of what the cost function is). Let e_* denote the edge for which $|q_{e_*}^{(0)} - q_{e_*}^{(1)}|$ is maximized. Suppose that the vertices of e_* are v_0, w_0. Let $e = \{v_1, w_1\}$ denote some arbitrary non-information-optimal edge. We will construct two flows: $f^{(0)}$ will move all probability mass to e_*, while $f^{(1)}$ will move all mass to e.
(i) for any $u \notin \{v_0, w_0\}$, f_0 sends all $1/n$ of the mass on u to $z_0(u) = \underset{x \in \{v_0, w_0\}}{\arg\min} \ c(u, x)$.
(ii) for any $u \notin \{v_1, w_1\}$, f_1 sends all $1/n$ of the mass of u to $z_1(u) = \underset{x \in \{v_1, w_1\}}{\arg\min} \ c(u, x)$.
The resulting total cost of $f^{(b)}$, for $b \in \{0, 1\}$, is $W(f^{(b)}) = \frac{1}{n} \sum_{u \notin \{v_b, w_b\}} c(u, z_b(u))$.

Now, it remains to show that $W(f^{(0)}) \geq W(f^{(1)})$, for *some* choice of model parameters $q_e^{(b)}$, $b \in \{0, 1\}$. This is easy to guarantee since the edge sets of which the two sums indexed are disjoint, and we can make the costs arbitrarily close to 0 for the edges in f_1 by decreasing $|q_{u,x}^{(0)} - q_{u,x}^{(1)}|$ sufficiently. Since we only decrease this quantity for edges that are not e_*, this does not affect the optimal edge. This completes the proof.

The above counterexample suggests the following intuition behind the shortcomings of the optimal transport approach: an edge may be very informative, but it may be isolated from the rest of the graph by high-cost (informative) edges. That is, the informativeness of an edge may have nothing to do with the cost of its surrounding edges. In this case, optimal transport might find it hard to pick it out, simply because there is a lower cost associated with flowing elsewhere. Hence, there's a tension: if an informative edge has a high cost, then it may be costly to flow to it. If an informative edge has a low cost, then it may be too cheap to direct flow out of it.

6 Experimental Study

We conducted several experiments to demonstrate how our method outperforms the OT approach and baseline (no-compression). We use graph summarization methods on the graph classification dataset, then use the resulting summarized datasets to train and test a classifier. We evaluate our work using both real and synthetic datasets. All the datasets have binary class labels.

Image-based Dataset: The real vision datasets that we are using here are based on MNIST Deng (2012) and CIFAR-10 Krizhevsky (2009) datasets. Each pixel in an image is assigned to a node in a graph and each image is a graph of attributed nodes where the edges between the nodes are based on their spatial relationships. It is notable that the number of nodes for each graph would be tremendous since images are 784×784 pixels and we have a huge adjacency matrix for each graph. So, compressing the nodes here would be necessary specifically when considering a lot of non-useful pixels that don't play any role in classification.

Transport-based Dataset: As a non-vision real dataset the New York Taxi Data (2010-2013) Donovan & Work (2016) is used to generate an attributed graph dataset with a fixed node size among all samples. In the raw data, there are about 7 million trips by Taxis in New York City (NYC), and 703 graph samples are extracted out of them with the pre-processing as the following. Firstly, incorrect trips are eliminated and then the "vendor_id"s are considered as the labels. So, the trips are divided into two categories based on their vendor ids. In each category, the trips of each day are considered as one single sample, and the nodes, edges, and nodes' attributes are generated for each sample. For generating the nodes, each element of a grid over the NYC map is assigned to a node. So, each node in each sample shows a neighborhood on the map in a day. The attributes of these nodes are calculated as the summation of the time that taxis spend on a trip when they pickup and drop off people only in that neighborhood. There is an edge between two nodes if there was at least a trip on that day between those two nodes. Since the nodes are the elements of a grid over the map the number of nodes is the square of a real number.

Synthetic Dataset: The invoked synthetic data has class-label-dependent node features and edges. Features are generated randomly on Gaussian distribution with standard deviations and means (j/node-size)$\times 5$ for class 0 and (j/node-size)$\times 4$ for class 1 and j is node index. Edges are randomly added to the graphs using the probability assigned to the class label.

Experimental design: For the classification accuracy experiments, for each dataset and method, we train the summarization method on a training set, then apply the summarization method with the learned parameters to a test set. We then use the resulting summarized dataset as input to a classification pipeline: this pipeline is trained/tested using 5-fold cross validation. We report the average and standard deviation of the test accuracy over 10 trials of the entire experiment. We also report the running time of the training (when applicable) and testing phase of the compression time, as well as the running time of the classification pipeline on the summarized dataset. We note that the latter running time is important because one of the central purposes of graph summarization is to make subsequent tasks, such as classification, more computationally efficient while not sacrificing too much accuracy. These statistics are *not* reported in prior work Garg & Jaakkola (2019). The same experiment is performed with multiple compression ratios. For the classification model, we apply a support vector machine (SVM) with the GraphHopper kernel Feragen et al. (2013). We use this kernel because of its ability to handle continuous node attributes.

6.1 Performance Analysis on graph classification datasets

To evaluate our method and analyze its performance we compared the test accuracy of our method, OT approach, Graph Coarsening Jin et al. (2020), and baseline. Among other methods, we focused on only Graph Coarsening as this paper is developed to mainly discuss Garg & Jaakkola (2019) which has already shown performance improvements against several existing works but we believe additional comparison against Graph Coarsening method would provide further insight on how our method plays a key role in graph summarization when reducing the computational load by summarization while attempting to maintain the basic structural properties of the original graph. For CIFAR10, to reduce complexity, we tag best out of (20,40,60,80)% of nodes as sensitive using $\rho := \mathbb{E}_{(X_v, C) \sim D}[P(X_v|C)/P(X_V)]$ and then apply our method on the rest of the nodes. Table 1 summarizes the performances for each compression ratio. Clearly, as the numbers in bold indicate, our method outperformed the other methods across the datasets on most compression ratios. Here "baseline" means a classification performance on a non-summarized graph. Figure 1 demonstrates that our method outperforms the OT approach in terms of both compression and classification times.

Table 1: *Real data and synthetic Experiments* - This table demonstrates the accuracy of OT, Ours, Ours+(ρ), and Graph Coarsening Jin et al. (2020) methods on several real and synthetic datasets for some compression ratios. The methods with the best performance are indicated in bold font in each case. Here Ours+(ρ) is our method when we tag the best of $\rho = 20, 40, 60, 80\%$ of sensitive nodes.

Dataset	Acc@0.2	Acc@0.3	Acc@0.4	Acc@0.5	Acc@0.6	Acc@0.7	Acc@0.8
MNIST	.556±.049	.544±.065	.496±.097	.516±.094	.508±.072	.484±.058	.492±.072
Graphs: 300	.944±.060	.896±.060	.944±.054	.976±.048	.96±.062	.96±.044	.968±.064
Nodes: 100	**.969±0.055**	**1.0±.0**	**1.0±.0**	**1.0±.0**	**.987±.027**	**1.0±.0**	**.993±.018**
Edges: 163.44				Baseline	.984±.032		
CIFAR10	.475±.020	.525±.020	.475±.020	.475±.020	.5167±.028	.516±.028	.475±.020
Graphs: 300	.568±.047	**.568±.047**	.56±.036	.56±.036	.56±.051	.576±.041	.584±.032
Nodes: 200	**.569±.048**	.558±.047	**.58±.039**	.576±.034	.58±.034	.585±.039	.58±.028
Edges: 424.02	.568±.050	.564±.044	.572±.041	**.582±.037**	**.586±.037**	**.588±.038**	**.586±.038**
				Baseline	.584±.032		
NYC	.524±.048	.529±.077	.522±.037	.520±.064	.510±.088	.525±.062	.5256±.041
Graphs: 703	N/A	.874±.051	.922±.031	**.952±.02**	.918±.025	.888±.03	**.918±.038**
Nodes: 100	N/A	**.96±.017**	**.955±.020**	.943±.026	**.929±.031**	**.907±.047**	.889±.059
Edges:: 418.13				Baseline	.871±.04		
Synthetic	.625±.026	.655±.053	.656±.013	.708±.031	.732±.035	.734±.026	.763±.027
Graphs: 1500	.886±.039	.918±.016	.957±.011	.966±.013	.984±.005	.986±.004	.992±.003
Nodes: 100	**.909±.014**	**.950±.01**	**.981±0005**	**.984±.007**	**.986±.014**	**.994±.003**	**.993±.004**
Edges:: 4017.41				Baseline	.992±.005		

Figure 1: *Comparison on compression and classification time between our method, OT approach (OTC), and baseline* The compression, and classification time is shown for both CIFAR-10 and NYC. Our method substantially outperforms OTC in terms of compression time and classification accuracy and outperforms the baseline in terms of both accuracy and classification time. The classification time for the compression ratio with the best accuracy is less than half of that of the baseline.

6.2 HOW MUCH IS INFORMATION MONOTONICITY VIOLATED?

In order to investigate information monotonicity, we first propose a new estimator for MI and apply it to summarized graphs. **Estimator $\widehat{I}(G_V, X_V; C)$:** Consider N i.i.d samples $\left\{(X_u, X_v)\right\}_{n=1}^{N}$ drawn from $P_{u,v}$ with adjacency values $e_{u_1,v_1}, \ldots, e_{u_N,v_N}$ from adjacency matrices $A_1, \ldots, A_N$. Note that $e_{u,v}$ takes values either 0 or 1. We map each point in the sets $\mathbf{X_u} = \{X_{u1}, \ldots, X_{uN}\}$, and $\mathbf{X_v} = \{X_{v1}, \ldots, X_{vN}\}$, to the nodes in the sets W_u and Z_v respectively, using the hash function H. Then let $H(x) = H_2(H_1(x))$, where the vector valued hash function $H_1 : \mathbb{R}^d \mapsto \mathbb{Z}^d$ is defined $H_1(x) = [h_1(x), \ldots, h_1(x_d)]$, for $x = [x_1, \ldots, x_d]$ and $h_1(x_i) = \lfloor \frac{x_i+b}{\epsilon} \rfloor$, for a fixed $\epsilon > 0$, and

random variable $b \in [0, \epsilon]$. The random hash function $H_2 : \mathbb{Z}^d \mapsto \mathcal{F}$ is uniformly distributed on the output $\mathcal{F} = \{1, 2, \dots, F\}$ where for a fixed tunable integer c_H, $F = c_H N$. Define

$$N^e_{i_u j_v} = \#\{(X_{un}, X_{vn}) \ s.t. \ H(X_{un}) = i_u, H(X_{vn}) = j_v \text{ and } e_{un,vn} = 1\}, \quad (16)$$

which is the number of joint collisions of the nodes (X_{un}, X_{vn}) at the pair (w_{i_u}, z_{j_v}). Let N_{i_u}, $N_{i_u j_v}$ be the number of collisions at the vertices (w_{i_u}), and (w_{i_u}, z_{j_v}) respectively, where

$$N_{i_u j_v} = \#\{(X_{un}, X_{vn}) \ s.t. \ H(X_{un}) = i_u, H(X_v) = j_v\}, \quad (17)$$

By using $N^e_{i_u j_v}$, $N_{i_u j_v}$, and N_{i_u} we define $r^e_{i_u j_v} := \frac{N^e_{i_u j_v}}{N}$, $r_{i_u j_v} := \frac{N_{i_u j_v}}{N}$, $r_{i_u} := \frac{N_{i_u}}{N}$, and

$$\widehat{P}_{i_u, j_v}(.|c) := \prod_{u \in V} r^c_{i_u} \cdot \prod_{u,v \in V} \frac{r^{e,c}_{i_u j_v}}{r^c_{i_u j_v}} \left(1 - \frac{r^{e,c}_{i_u j_v}}{r^c_{i_u j_v}} \right), \quad \widehat{P}_{i_u, j_v}(.) := \prod_{u \in V} r_{i_u} \cdot \prod_{u,v \in V} \frac{r^e_{i_u j_v}}{r_{i_u j_v}} \left(1 - \frac{r^e_{i_u j_v}}{r_{i_u j_v}} \right)$$
$$(18)$$

where $r^c_{i_u}$ is r_{i_u} with class label c. Further $r^{e,c}_{i_u j_v}$ and $r^c_{i_u j_v}$ are $r^e_{i_u j_v}$ and $r_{i_u j_v}$ with samples from class label c. Let $p_c = \frac{N_c}{N}$, where N_c is total number of sample with class label c. We propose a Hash-based estimator of $I(G_V, X_V; C)$ in (12) denoted by $\widehat{I}(G_V, X_V; C)$ as follows:

$$\widehat{I}(G_V, X_V; C) = \sum_c p_c \cdot \sum_{i_u, u \in V} \widehat{P}_{i_u, j_v}(.) \cdot g\left(\frac{\widehat{P}_{i_u, j_v}(.|c)}{\widehat{P}_{i_u, j_v}(.)} \right). \quad (19)$$

In particular, we use $g(x) = x \log x$. Note that $\sum_{i_u, u \in V} := \sum_{i_{v_1}, i_{v_2}, \dots i_{v_{|V|}}} = \sum_{i_{v_1}} \sum_{i_{v_2}} \cdots \sum_{i_{v_{|V|}}}$, where $|V|$ is cardinality of vertices. An important assumption on the proposed estimator is that for all vertex pairs $u, v \in V$ we have $r^{e,c}_{i_u j_v} \neq 0$ and $r^e_{i_u j_v} \neq 0$. This is coincident with using a dependence graph in MI estimator as the nodes and edges with zero collisions do not show up in the dependence graph. In practice if there exist a pair (u, v) such that $N^e_{i_u, j_v} = 0$, we eliminate the node from collision counts. Figure 2 demonstrates the MI values using (19) estimation and shows that our method outperforms OTC for smaller compression ratios but not for large ones which is a potential future investigation.

7 CONCLUSION

We have introduced a theoretical formulation of supervised graph summarization in terms of maximization of the mutual information between the class labels and graphs to be classified. We showed that the solution to this problem, even approximately, is NP-hard, and so we took a different approach: in particular, we showed how the unsupervised optimal transport graph summarization framework of Garg & Jaakkola (2019) can be adapted – nontrivially – to a supervised setting via estimation of information-theoretic measures incorporating both graph structure and node features. This is in contrast to the parameter settings of the previous work, which only took into account the degree distribution of the graph and compressed graphs in isolation, failing to take into account dataset-wide statistics. We also elucidated limitations of the optimal transport solution for maximization of the mutual information objective in our summarization framework.

Looking ahead - Further work is necessary to elucidate the precise power/limitations of the optimal transport approach to graph summarization. For instance, its connections to other methods, such as graph clustering-based methods deserve further examination. Moreover, our adaptation of the OT method to the supervised setting requires further development to accommodate graph datasets in which different graphs do not share a common vertex set.

Figure 2: *MI Comparison for Synthetic Dataset* MI is shown for different compression ratios with each point color showing the performance on Synthetic data (100 samples and 5o nodes). We applied noise injection that is averaging over features of graph node neighbors randomly to provide a complex classification problem. We observe that our method outperforms OT approach (OTC) over accuracy and has higher MI after compression, however, this is slightly violated when the compression starts to grow.

REFERENCES

Xin Chen, Xien Liu, and Ji Wu. Gcn-bmp: Investigating graph representation learning for ddi prediction task. *Methods*, 179:47–54, 2020.

T. Cover and J. Thomas. *Elements of information theory*. 1st edn. John Wiley & Sons, Chichester, 1991.

Thomas M. Cover and Joy A. Thomas. *Elements of Information Theory (Wiley Series in Telecommunications and Signal Processing)*. Wiley-Interscience, USA, 2006. ISBN 0471241954.

Li Deng. The mnist database of handwritten digit images for machine learning research. *IEEE Signal Processing Magazine*, 29(6):141–142, 2012.

Danilo Dessì, Francesco Osborne, Diego Reforgiato Recupero, Davide Buscaldi, Enrico Motta, and Harald Sack. Ai-kg: an automatically generated knowledge graph of artificial intelligence. In *International Semantic Web Conference*, pp. 127–143. Springer, 2020.

Brian Donovan and Dan Work. New york city taxi trip data (2010-2013), 2016. URL https://doi.org/10.13012/J8PN93H8.

Aasa Feragen, Niklas Kasenburg, Jens Petersen, Marleen de Bruijne, and Karsten Borgwardt. Scalable kernels for graphs with continuous attributes. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL https://proceedings.neurips.cc/paper/2013/file/a2557a7b2e94197ff767970b67041697-Paper.pdf.

Vikas Garg and Tommi Jaakkola. Solving graph compression via optimal transport. In *Advances in Neural Information Processing Systems 32*, 2019.

Peng Han, Peng Yang, Peilin Zhao, Shuo Shang, Yong Liu, Jiayu Zhou, Xin Gao, and Panos Kalnis. Gcn-mf: disease-gene association identification by graph convolutional networks and matrix factorization. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 705–713, 2019.

Yu Jin, Andreas Loukas, and Joseph JaJa. Graph coarsening with preserved spectral properties. In *International Conference on Artificial Intelligence and Statistics*, pp. 4452–4462. PMLR, 2020.

Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. *Physical review E*, 69(6):066138, 2004.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Yike Liu, Tara Safavi, Abhilash Dighe, and Danai Koutra. Graph summarization methods and applications: A survey. *ACM Comput. Surv.*, 51(3), June 2018. ISSN 0360-0300. doi: 10.1145/3186727. URL https://doi.org/10.1145/3186727.

Kevin R Moon, Kumar Sricharan, and Alfred O Hero. Ensemble estimation of mutual information. In *2017 IEEE International Symposium on Information Theory (ISIT)*, pp. 3030–3034. IEEE, 2017.

Morteza Noshad, Kevin R Moon, Salimeh Yasaei Sekeh, and Alfred O Hero. Direct estimation of information divergence using nearest neighbor ratios. In *2017 IEEE International Symposium on Information Theory (ISIT)*, pp. 903–907. IEEE, 2017.

Morteza Noshad, Yu Zeng, and Alfred O Hero. Scalable mutual information estimation using dependence graphs. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 2962–2966. IEEE, 2019.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

S Yasaei Sekeh and A O Hero. Geometric estimation of multivariate dependency. *Entropy (Special Issue on Women in Information Theory)*, 21(8):787–841, 2018.

S. Yasaei Sekeh, B. Oselio, and A. O. Hero. A dimension-independent discriminant between distributions. In *proc. IEEE Int. Conf. on Image Processing (ICASSP)*, 2018.