GRAM: Fast Fine-tuning of Pre-trained Language Models for Content-based Collaborative Filtering

Abstract

Content-based collaborative filtering (CCF) provides personalized item recommendations based on both users' interaction history and items' content information. Recently, pre-trained language models (PLM) have been used to extract high-quality item encodings for CCF. However, it is resource-intensive to finetune PLM in an end-to-end (E2E) manner in CCF due to its multi-modal nature: optimization involves redundant content encoding for interactions from users. For this, we propose GRAM (GRadient Accumulation for Multi-modality): (1) Single-step GRAM which aggregates gradients for each item while maintaining theoretical equivalence with E2E, and (2) Multi-step GRAM which further accumulates gradients across multiple training steps, with less than 40% GPU memory footprint of E2E. We empirically confirm that GRAM achieves a remarkable boost in training efficiency based on five datasets from two task domains of Knowledge Tracing and News Recommendation, where single-step and multi-step GRAM achieve 4x and 45x training speedup on average, respectively. Code and dataset are available here.

1 Introduction

Collaborative filtering(CF) (Smith and Linden, 2017; Bennett et al., 2007; Melville et al., 2002), the task of mining relationship between item and user(i.e. knowledge tracing and recommender systems), utilize explicit records on user-item pairs. Content-based Collaborative Filtering (CCF) brought significant improvement (Wu et al., 2019, 2021; Lu et al., 2018) in performance by utilizing item text. As high quality item representations are built upon the underlying semantics of their text, recent approaches in CCF leverage content data through fine-tuning a pre-trained language model (PLM) (Devlin et al., 2019; Brown et al., 2020). Along with increase in overall performance, the ability to create a representation for individual items via texts alone, makes the approach suitable for difficult cold-start problems (Lam et al., 2008).

However, fine-tuning PLMs for CCF has intensely high computational cost in terms of (1) training time and (2) GPU memory footprint. In a real world News Recommendation dataset, it has been reported (Xiao et al., 2021) that over 2,400 hrs of training time is required to fully train 12 layer PLM in an end-to-end(E2E) fashion with 4 V100 GPUs, which cost over 24,000$ with Google GCP on-demand resources. This issue rises due to multi-modal nature of CCF setting: converging user records with item contents, items on user's entire history needs to be encoded every time, learning from each data point of the user. Moreover, the need of storing intermediate activations for hundreds of millions of parameters in PLM requires high GPU memory footprint (Wang et al., 2020).

To that end, we propose Single-step GRAM, **Gr**adient **A**ccumulation for **M**ulti-modality, which alternately trains the task specific module and content encoder module. Accumulating gradients for repeated items in a training step, Single-step GRAM provides 4 times faster training while maintaining theoretically guaranteed equivalence to standard E2E training.

By adding another layer of gradient accumulation across *multiple training steps*, we also propose Multi-step GRAM which (1) provides an even higher ratio of acceleration without significant performance loss and (2) consumes less than 40% GPU memory of E2E. Results show that the computational speed can increase up to 146 times (45 times on avg.) with less than 1% drop in AUC.

Specifically, this work's contributions are:

- A new method to accelerate training of multi-modal prediction using a pre-trained language model (Single-step & Multi-step GRAM).

- Extensive evaluation of the method in a variety of settings on 5 real-world datasets.

2 Related Works

2.1 Collaborative Filtering and Content-based Filtering

Collaborative filtering(CF) (Su and Khoshgoftaar, 2009) attempts to predict user-item interaction based on past history. CF alone disregards any user-specific or item-specific information, leading to its two major disadvantages: (1) low performance on cold-start users and items, and (2) inability to extract useful features from user information or item content. Various content-based filtering methods (Van Meteren and Van Someren, 2000; Basilico and Hofmann, 2004) have been proposed to mitigate these issues through labeled meta-data. However these approaches require manual labelling and lack the extensive usage of the content itself, which have been a popular source in natural language models (Young et al., 2018).

2.2 Content-based Collaborative Filtering

Content-based Collaborative Filtering (CCF) incorporates content into CF in order to unify the strengths of CF and content-based filtering. For instance, Topical Attention Regularized Matrix Factorization (TARMF) (Lu et al., 2018) uses Matrix Factorization (MF) as CF and attention-based GRU network as CE to incorporate review data in predicting user-item ratings. Major task domains where items' raw textual content may significantly aid CF include News Recommendation (NR) and Knowledge Tracing (KT).

News Recommendation (NR): NR predicts whether a user will click an article among others, provided with the user's past interactions. NRMS(Wu et al., 2019) applied Glove(Pennington et al., 2014) word representation and Multi-head Self-attention (MHSA)(Vaswani et al., 2017) to encode the article's text to the item representation, as also adopted in SASRec(Kang and McAuley, 2018). Later, NRMS-PLM(Wu et al., 2021) further enhanced its performance by replacing the word embedding with larger pre-trained language models (Devlin et al., 2019).

Knowledge Tracing (KT): KT task predicts whether a user correctly responds to a question or not based on the user's past correctness to other questions. DKT(Piech et al., 2015) and SAKT(Pandey and Karypis, 2019) applied LSTM(Hochreiter and Schmidhuber, 1997) and MHSA to the task, respectively. These approaches did not incorporate questions' content information, initializing each question (item) representation as a random embedding vector. More recently, EERNN(Su et al., 2018) used BiLSTM(Huang et al., 2015) to process Word2Vec(Mikolov et al., 2013) representations of question text into question representation. The representation is then fed into another LSTM layer to make final prediction on the user response.

2.3 Fine-tuning Large PLMs

Large PLMs are capable of extracting generic features that are useful for various downstream tasks, but E2E fine-tuning of the PLMs along with the downstream task-specific head can be critically expensive. Although it is possible to use PLM's output as fixed features for downstream tasks, numerous studies (Devlin et al., 2019; Reimers et al., 2019) emphasize such feature-based approach cannot match the performance of E2E fine-tuning. Thus, researchers have considered fine-tuning subset of the PLM architecture (Devlin et al., 2019) and adding task-specific parameters (Houlsby et al., 2019) to reduce cost and performance degradation.

However, the computational complexity deteriorates under multi-modal settings like content-based collaborative filtering. In such cases, PLM is called numerous times for a single-user, adding a new dimension of computational load, making E2E training almost impossible. SpeedyFeed (Xiao et al., 2021) was proposed to accelerate the fine-training of PLM for news recommendation through combination of several methods. However, they are mainly engineering heavy implementations with domain dependencies. To that end, we propose a novel method that can be applied in an orthogonal manner to aforementioned techniques like (Houlsby et al., 2019) and (Xiao et al., 2021), while achieving remarkable speed boost in such multi-modal settings.

3 Preliminaries

In this section, we formally setup CCF framework and its notations for efficient discussion. CCF framework consists of two major components: content-encoder (CE) and collaborative filter (CF) components connected in an end-to-end fashion.

CF component predicts user u's response r to an arbitrary item based on the user's past interactions $I^u = (I_1^u, I_2^u, ..., I_{|I^u|}^u)$ where each n-th interaction $I_n^u = (e_n^u, r_n^u)$ is represented as a tuple of item representation e_n^u and the user's response to the

Notation	Description
I^u	Interaction sequence of user u
c_i	Content of item i
$I_n^u = (e_n^u, r_n^u)$	n-th interaction of user u
$e_n^u = CE(c_n^u)$	Embedding of content c_n^u from CE
$B^{(t)}$	Mini-batch B at update time-step t
$[B_i, B_u]$	Set of unique [users, items] in B
$[l_t, l_I]$	Length of [tokens, interactions] in $[c, I]$
d	Content embedding dimension
$\mathcal{L}$	CCF minimization objective

Table 1: Notations for Content-based CF(CCF)

item r_n^u. In other words, the CF module aims to estimate the probability:

$$CF(I^u; e_{|I^u|+1}^u) = P(r_{|I^u|+1}^u | I_1^u, I_2^u, ..., I_{|I^u|}^u; e_{|I^u|+1}^u)$$

CE component outputs the item representation e: $e_n^u = CE(c_n^u)$ where c_n^u is the token sequence of the corresponding item. The model parameters θ_{CE} and θ_{CF} of the CE-CF pipeline is then trained in an end-to-end fashion based on cross-entropy loss for response prediction. The summary of notation used for CCF is provided in Table 1. The existing approaches to tackle CCF are formatted and presented in Table 2, along with the pipeline we adopt for our later experiments.

Task	Model	CE	CF
NR	NRMS	Glove, MHSA	MHSA
	NRMS-PLM	BERT	MHSA
	Our Experiments	BERT	MHSA
KT	DKT	None	LSTM
	EERNN	W2V, BiLSTM	LSTM
	Our Experiments	BERT	LSTM

Table 2: CE-CF Pipeline Choice for CCF

4 Proposed Method

We first point out the source of computational complexity in the multi-modal end-to-end training. We then illustrate our novel solution to resolve the inefficiency and identify the difference between our method and others.

4.1 E2E Training Inefficiency in CCF

In CCF, end-to-end fine-tuning of the CE(PLM) suffers from cubic computational complexity in terms of sequence length, due to the data multi-modality. Let's assume average text token length of l_t and average interaction record length of l_I with each mini-batch B containing users B_u. Attention-based CE module would be called l_I times, pro-

ducing forward/backward-pass computational complexity of $O(|B_u| \cdot l_I(l_t^2 d + l_t d^2))$ where d represents embedding dimension. Under similar average sequence length of per-item tokens and per-user interactions $l_t \approx l_I$, the resulting cubic complexity in terms of sequence length significantly increases space and time complexity of model training and becomes the limiting bottleneck factor.

4.2 GRadient Accumulation for Multi-modality

We propose GRadient Accumulation for Multi-modality, namely GRAM (Single-step). GRAM trains CE module and CF module *separately* to reduce CE's algorithmic complexity to $O(|B_i| \cdot (l_t d^2 + l_t^2 d))$ per mini-batch update, reusing the notation from 4.1. GRAM repeats the following steps: (illustration provided in figure 3 in the Appendix B):

[1] For unique items i in the mini-batch $B^{(t)}$, CE produces their representation $h_i^{(t)}$ for CF module to complete the forward-pass.

$$h_i^{(t)} \leftarrow CE(c_i; \theta_{CE}^{(t)}), \quad \forall i \in B_i^{(t)} \quad (1)$$

[2] Updates the CF module's parameters using standard back-propagation with training objective $\mathcal{L}$, while simultaneously updating the content representation (output from CE module) by **treating it as trainable embedding** $\tilde{h}_i^{(t)}$. The gradient is processed to update via an optimization algorithm opt.

$$\mathcal{L} := \sum_{u \in B_u^{(t)}} L(I^u, \{h_i^{(t)} | \forall i \in B_i^{(t)}\}; \theta_{CF}^{(t)}) \quad (2)$$

$$\theta_{CF}^{(t+1)} \leftarrow \theta_{CF}^{(t)} - opt\left(\frac{\delta\mathcal{L}}{\delta\theta_{CF}^{(t)}}\right) \quad (3)$$

$$\tilde{h}_i^{(t)} \leftarrow h_i^{(t)} - \frac{\delta\mathcal{L}}{\delta h} \quad (4)$$

[3] Then for items of which embedding are modified in [2], the CE module is trained to follow/regress towards the modification with respect to pseudo-target $\tilde{h}_i^{(t)}$ and pseudo-loss $\tilde{L}$.

$$\tilde{\mathcal{L}} := \frac{1}{2} \sum_{i \in B_i^{(t)}} (\tilde{h}_i^{(t)} - CE(c_i; \theta_{CE}^{(t)}))^2 \quad (5)$$

$$\theta_{CE}^{(t+1)} \leftarrow \theta_{CE}^{(t)} - opt\left(\frac{\delta\tilde{\mathcal{L}}}{\delta\theta_{CE}^{(t)}}\right), \quad \forall i \in B_i^{(t)} \quad (6)$$

[4] Based on item representation updated in step [3], repeat [1] with $t \leftarrow t + 1$.

Figure 1: Comparison to E2E Training: Let's assume a mini-batch B of 12 interactions consisting of 3 users and 5 unique items. For the content encoder, E2E computes 12 gradients from each *interaction*, while GRAM computes 5 only, based on accumulated gradient signal in pseudo-target $\tilde{h}_i$ from each *item* i.

4.3 Comparison to E2E Training

Figure 1 shows how gradients are applied to PLM in standard E2E training and GRAM. Yielding identical outcome of E2E back-propagation with fewer gradient computation, GRAM enables efficient training under hierarchical multi-modal setting like CCF by accumulating gradient buffer in Eq.4 for items that are updated multiple times in a mini-batch. Given a mini-batch B of $|B_u|$ users' interaction sequences, the standard E2E back-propagation updates CE module for $\sum_{u \in B_u} |I^u|$ (i.e. number of total interactions), while GRAM updates CE module for $|B_i|$ (i.e. number of unique items) times only. Since PLM based CE modules are usually significantly larger than the head (CF module) attached for downstream task (News Recommendation), the following ratio of speed boost for CE module applies in a close to directly proportionate manner for the entire training procedure.

$$\mathcal{R} := \frac{\sum_{u \in B_u} |I^u|}{|B_i|} = \frac{\#\text{interactions}(B)}{\#\text{items}(B)} \quad (7)$$

The ratio $\mathcal{R}$ monotonically increases as mini-batch size becomes larger. Thus, larger mini-batch size would yield larger efficiency boost via GRAM. Lemma 1 in Appendix A proves that parameter updates of GRAM (Single-step) and E2E training are theoretically equivalent.

4.4 Multi-step GRAM

Accumulating gradient buffers for *multiple* mini-batch updates, instead of a single update, Multi-step GRAM would further increase speed boost ratio $\mathcal{R}$. In other words, CF / CE modules may separately update multiple times across multiple mini-batches, via repeating steps [1]-[2] / [3], respectively. This relaxation of GRAM's alternating period/frequency no longer guarantees equivalence with the model parameters updated via E2E back-propagation. (i.e. $\theta_f \neq \theta'_f$ in (10)) In the following section's experiments, (i) training efficiency boost and (ii) performance degradation from different alternating frequency are closely monitored on various GRAM alternating periods (Single-Step, 10-Step, Half-Epoch, Full-Epoch).

4.5 Comparison of GRAM to Existing Methods

4.5.1 SpeedyFeed: SpeedyFeed (Xiao et al., 2021) implemented various domain specific methods to achieve speed boost in News Recommendation. Most relevant method to GRAM in SpeedyFeed is central batching and the cache mechanism. Although central batching collects unique items in the forward pass, it still requires gradient computations for PLM's weights on every interaction during backpropagation, having limited speed gain. Also, cache mechanism fails to optimize news representations that were generated in recent time steps, unlike GRAM. SpeedyFeed's other methods (Central Batching, Autoregressive, BusLM) are orthogonal with GRAM, which can be used simultaneously.

4.5.2 TARMF: Analogous to GRAM, TARMF (Lu et al., 2018) alternately updates CF module and CE module. There are two major points that differ-

Dataset	Users	Total Items	Total Interactions	CS Items	CS Interactions	Average l_t
Spanish	2,643	4,628	279,747	200	3,191	5.32
French	1,202	4,078	174,749	200	1,970	5.24
POJ	22,110	2,597	898,384	200	10,523	271.34
TOEIC	1,240,955	9,336	94,264,845	684	321,933	147.47
MIND	750,434	104,150	3,760,125			11.52(639.57)

Table 3: Dataset Information. For MIND, both average l_t of title alone and l_t of title + abstract + body are reported.

entiate the optimization schemes of GRAM and TARMF. First, while E2E methods and GRAM directly use content-encoder's output as item vectors, TARMF uses content-encoder's output to regularize item vectors. Second, GRAM uses item vectors to produce user vectors in user-encoder, making user encoder intrinsically hierarchical. Such hierarchical user encoder allows online/sequential recommendation without model retraining as the user generates more log(rating) data, whereas TARMF's content-encoder and user vector should go through additional iterations of optimization.

5 Experimental Settings

We first define the scope of tasks and metrics used in the experiments. Detailed description of datasets and methods are provided in section 5.1 and section 5.2, respectively.

Tasks: Experiments are conducted on two major task domains of CCF: Knowledge Tracing(KT) and News Recommendation(NR), where models predict whether a student/reader will solve/click an question/article, as a classification task.

Metrics: Overall AUC and cold-start item AUC (CSAUC) are measured for KT. AUC, MRR, nDCG@5, nDCG@10 are measured for NR. As cold start problem is intrinsically abundant in news recommendation environment Wu et al. (2019), we did not measure CSAUC separately. Wall-clock training time until convergence is reported for all experiments. For fair comparison of training time, all models are run on equivalent device (NVIDIA A100 GPU) in an isolated manner.

5.1 Experimental Details

To evaluate our model, we used five real-world datasets: four datasets in KT, and one dataset in NR, on which both textual content data and user interaction data are available. Experiments on Duolingo French and Spanish dataset are done with single NVIDIA A100 GPU, and those on POJ, TOEIC, and MIND are done with eight NVIDIA A100

GPUs, in distributed data parallel training. [1]

Detailed per-dataset description is written below, and specification is in Table 3. [2] Dataset collection methods are mentioned in Appendix F.

5.1.1 Datasets

(KT) Duolingo (Spanish, French): Language Translation (Settles et al., 2018) contains questions and responses for Duolingo users. Following (Srivastava and Goodman, 2021), we collapsed the original token level mistakes to question level binary labels. We used Spanish and French dataset.

(KT) POJ: Computer Programming was collected from Peking online platform and consists of computer programming questions.

(KT) TOEIC: Language Comprehension from EdNet (Choi et al., 2020) is the largest publicly available benchmark dataset in education domain consisting of student interaction logs.

(NR) MIND: Microsoft News Dataset is one of the largest English dataset for monolingual news recommendation. MIND dataset provides news articles' title, abstract, and body text for news content modeling. For comparison with other models, we only utilized the news title, following Wu et al. (2019, 2021). As Multi-step GRAM's significant speed boost allowed us to utilize more features, we also provide results on utilizing all textual features for Multi-step GRAM as well.

5.2 Methods

5.2.1 Baseline Model Architecture

To fairly compare GRAM's training methodology against the standard E2E, we apply GRAM/E2E on an identical model architecture, defined for KT and NR respectively. Model choices are shown in Table 2. To the best of our knowledge, this work is

---

[1] All experiments are ran 3 times and averaged results are reported except TOEIC E2E and MIND E2E, due to high computational cost mentioned in the result section. The results were shown to be statistically significant (p < 0.05).

[2] Train / Test set were randomly split in 8:2 ratio. 10% of train dataset were randomly chosen for validation set.

the first study to incorporate BERT to KT. Detailed model architectures are described in Appendix D.

Based on this model architecture, we compare: **E2E** training, single-step **GRAM 1S**, 10-Step **GRAM 10S**, 0.5-Epoch **GRAM 0.5E**, and 1-Epoch **GRAM 1E** on the aforementioned metrics. We also provide benchmarks for other existing approaches, as elaborated in the following section 5.2.2. Note that E2E training in NR has the same structure as NRMS-PLM in (Wu et al., 2021).

5.2.2 Other Architectures

In addition to the shared CCF model architecture defined above, we also include other approaches for extensive comparison.

NoFinetune approach directly adopts fixed item representation encoded from PLM without fine-tuning. Only the CF component is trained, receiving PLM's fixed output as the input.

NoContent approach does not incorporate any textual content at all. Each item representation is randomly initialized before being trained along with the standalone CF component.

(KT) Content Regularized CF (CRCF) is our implementation of the proposed regularization in TARMF with equivalent CF and CE modules of GRAM. In CRCF, the output of the CE module regularizes the item representations of the CF module.

(KT) LM-KT formulates KT as auto-regressive modeling task to fine-tune pre-trained GPT-2. The method's major bottleneck to other sequential recommendation domains is that the model's sequence length has to increase in a multiplicative fashion: $O(l_t \times l_I)$ in Table 1. [3]

(KT) EERNN is a specific instance of CE-CF pipeline where Bi-directional LSTM (CE) encodes question text's W2V representation into question embedding. CF consists of another LSTM layer.

(NR) NRMS is another specific instance of CE-CF pipeline where CE uses Glove word embedding and Multi-Head Self-Attention layers. Its CF component is also based on MHSA layers.

(NR) SpeedyFeed used (i) auto-regressive modeling, (ii) BusLM, (iii) Dynamic Batching, and (iv) Cache mechanism to speedup PLM-based news recommendation. For fair comparison, we used equivalent CE module for both GRAM and SpeedyFeed.

Further experimental details are in Appendix D, and source code of GRAM is in this link.

---

[3] LM-KT baseline was only tested on Duolingo datasets as other datasets' large average token length prevents LM-KT from considering more than a few items per each user.

Dataset	Method	AUC	CSAUC	Speed-up
TOEIC	E2E	75.7	64.2	1(135hr)
	GRAM 1S	**76.0**	63.0	5.7
	GRAM 10S	75.8	**65.1**	1.7
	GRAM 0.5E	75.7	64.7	26
	GRAM 1E	75.3	64.6	**146**
	EERNN	75.8	62.3	10
	NoFinetune	69.1	64.3	343
	NoContent	74.4	49.4	2547
POJ	E2E	69.0	65.4	1(123m)
	GRAM 1S	69.0	65.5	4.5
	GRAM 10S	**69.1**	65.0	3.8
	GRAM 0.5E	68.7	64.7	9.1
	GRAM 1E	68.8	64.5	**12.5**
	EERNN	68.6	64.0	1.3
	NoFinetune	68.3	**65.8**	41.0
	NoContent	63.8	50.9	30.8
Spanish	E2E	**75.1**	**68.7**	1(74m)
	GRAM 1S	**75.1**	68.3	3.5
	GRAM 10S	74.4	67.2	2.1
	GRAM 0.5E	74.4	67.0	2.8
	GRAM 1E	74.7	67.0	**5.7**
	CRCF 1S	74.9	66.2	1.2
	CRCF 1E	74.3	66.3	2.1
	EERNN	74.3	66.3	1.6
	LM-KT	74.6	68.7	0.5
	NoFinetune	72.5	66.2	24.7
	NoContent	67.0	49.3	37.0
French	E2E	74.8	74.7	1(39m)
	GRAM 1S	**75.0**	**75**	3.3
	GRAM 10S	74.2	73.2	3.5
	GRAM 0.5E	74.1	73.2	4.3
	GRAM 1E	74.4	73.3	**7.8**
	CRCF 1S	74.7	73.0	1.0
	CRCF 1E	74.4	72.9	1.8
	EERNN	74.0	71.3	1.2
	LM-KT	74.3	74.7	0.3
	NoFinetune	71.4	69.4	9.8
	NoContent	67.0	49.5	13.0

Table 4: Prediction Performance / Speed-up in Knowledge Tracing. Training time is reported for E2E training, and best results among content finetuning methods are marked in bold.

6 Results and Discussion

6.1 Knowledge Tracing

Performance Comparison: In general, E2E and GRAM in Table 4[4] shows best performance across datasets. Difference among GRAM variants highlights how Multi-step GRAM's performance gradually deviates from the E2E baseline as alternating period increases. As claimed in the previous section 4.2, GRAM(1S)'s performance most closely matches the E2E baseline. Confidence intervals of the two methods are reported in Appendix E.

NoFinetune and NoContent achieve significantly

---

[4] For CRCF, best result is reported among hyper-parameter ablations in Figure 2.

Figure 2: Comparison between GRAM, E2E, and CRCF. For CRCF, regularization parameter is marked as well.

worse performances on both metrics on all datasets, as compared to the full CCF setting with both CE and CF fine-tuned properly. Also, NoContent does not show any inference power on cold-start items, reporting AUC values around 50. LM-KT and EERNN showed lower performance in AUC and CSAUC than E2E or GRAM(1S), respectively.

As shown in Figure 2, we empirically confirm that standard E2E training converged to better local minima than CRCF, at all regularization hyperparameter values used in (Lu et al., 2018). GRAM 1S even converges faster than all variants of CRCF while maintaining E2E performance. CRCF also showed larger degradation in CSAUC. We noticed that as the degree of regularization increases, time for convergence increases notably.

Speed Comparison: We first highlight the reduction in training time via GRAM. Across 4 datasets, GRAM 1S achieves **4.3x** speedup of the E2E baseline, while GRAM 1E achieves acceleration of **43x**. We observe GRAM 1E achieves most significant training time acceleration as expected, since the boost ratio $\mathcal{R}$ of Eq.(7) is the largest in epoch-wise alternation. The power of GRAM 1E multiplies as the size of dataset increases, achieving remarkable **146x** speed up for the largest dataset, TOEIC. Among all datasets, TOEIC has the largest boost ratio $\mathcal{R}$ based on Table 3 which explains the largest efficiency gain.

GRAM 1E also out-speeds EERNN at all datasets despite the fact that EERNN uses W2V

embeddings and a single LSTM layer for its CE. In terms of GRAM's alternating period, we note that the impact on speed boost is not monotonic on some datasets, potentially due to increased variance of optimization switching between the CE component and the CF component.

Based on GCP GPU cost for ondemand A100 ($2.93/hr), training E2E model in TOEIC costs **$3,161**. GRAM 1E drastically reduces the training cost to **$21**.

Method	AUC	MRR	nDCG @5	nDCG @10	Speed-up
(Title-only)					
E2E	68.9	33.3	36.8	43.2	1(10.4hr)
GRAM 1S	69	33.5	37.1	43.4	2.5
GRAM 10S	68.6	33.7	37.3	43.4	1.9
GRAM 0.5E	68.7	32.9	36.2	42.7	13.5
GRAM 1E	68.7	33.1	36.6	42.8	17.3
NRMS	67.2	33.3	35.5	42	13.9
SpeedyFeed	68.3	33.4	36.6	43	2.0
NoFineTune	66.8	32.4	35.7	41.9	33.5
(Title+Body)					
E2E					1(*202hr)
GRAM 0.5E	**69.6**	34	37.6	**44**	45
GRAM 1E	69.3	**34.1**	**37.8**	**44**	**56**

Table 5: Prediction Performance and Training Speed on MIND Dataset. Training time is reported for E2E training. Overall best results among content finetuning methods are marked in bold, and best results utilizing title only are underlined.

6.2 News Recommendation

Performance Comparison: As shown in Table 5, Single-step GRAM matches performance of E2E training, and Multi-step GRAM shows less than 0.5% performance loss. Multi-step GRAM's capability to incorporate abstract and body of the news article (Title+Body) significantly improved the performance beyond all methods relying on title information alone. SpeedyFeed (Xiao et al., 2021) shows worse performance than all GRAM methods. We also noticed that SpeedyFeed's performance is highly sensitive to its hyper-parameters on the method's cache policy. Increasing max cache step hyper-parameter for faster training easily caused the training loss to spike, deteriorating the model convergence.

Speed Comparison: Multi-step GRAM shows consistent speed boost in MIND dataset, where Title-only GRAM 1E is **17.3x** faster than E2E. SpeedyFeed's acceleration, on the other hand, was lower than that of GRAM 1S. This is partly due to the fact that the method's auto-regressive formulation, the most significant factor of speed boost, was not applicable to MIND dataset, which does not provide negative samples(news impression list) per each positive interaction(news click) step.

While Wu et al. (2019) reported that using all textual information increases model performance significantly in a small version of MIND dataset, baseline results from Wu et al. (2019, 2021) only utilize news title due to computational complexity. With eight A100 GPUs, E2E training with all textual features is estimated to require **202** hours [5] (**\$4,735** of training cost) to converge. For this reason, we were unable to produce result for E2E with all textual information. In contrast, GRAM 1E requires only **3.6** hrs (**\$84**) to converge, requiring **56x** less training time compared with E2E.

| Method | CE Batch Size | GPU Utilization in %, (Gb) | |
		TOEIC	MIND
E2E	N/A	95.2, (38.6)	95.1, (38.4)
GRAM 1E	8	12.1, (4.8)	12.5, (5.1)
	32	16.0, (6.5)	34.9, (14.1)

Table 6: GPU Memory Consumption, with CF batch size of 4 in single NVIDIA A100. E2E doesn't have CE batch size as CE module naturally receives all items included in CF batch size as input.

---

[5]Estimated time is calculated based on per epoch time for E2E with all texts and number of epochs to converge for Title-only E2E.

6.3 GPU Memory Consumption

In E2E training, the entire computational graph as well as activations of all layers should be stored, resulting in a large GPU memory footprint (Wang et al., 2020). In this perspective, splitting CF module and CE module in GRAM brings down the required GPU memory during computation. As (1) the model size of the CF module is relatively small (single LSTM/MHSA) and (2) CE module of Single-step GRAM updates all item representations in a given batch in one step, the memory reduction is not significant in Single-step GRAM.

However, Multi-step GRAM can bring down the memory requirement significantly as its CE module uses multiple steps to update item representations. Table 6 compares the memory consumption between E2E and GRAM 1E with content encoder batch size of 8 and 32, respectively. Overall, GRAM 1E consumes less than 40% of memory compared to E2E. While only GRAM 1E is compared, Multi-step GRAM in general consumes similar memory given the same content encoder batch size.

7 Conclusion and Future Work

In this paper, we proposed GRAM as an efficient method to train on content-based collaborative filtering tasks. GRAM splits the CE module and CF module during training, which reduces the number of CE module's gradient computation and negates the need to store the intermediate activations for both of the modules at once. This core difference contributes to the speed gain and memory reduction compared to standard E2E training. GRAM was empirically evaluated on 5 different tasks to demonstrate its efficiency and comparable prediction power.

Limitation of this research includes Multi-step GRAM's performance deviation and the corresponding need to tune accumulation latency. We expect more sophisticated policy of gradient accumulation based on pseudo-loss trust region would reduce performance deviation while maintaining the speed gain. Another potential extension of this research would be GRAM's application to other multi-modal tasks involving sequences of images or other types of documents, beyond questions and news articles.

References

Justin Basilico and Thomas Hofmann. 2004. Unifying collaborative and content-based filtering. In *Proceedings of the twenty-first international conference on Machine learning*, page 9.

James Bennett, Stan Lanning, et al. 2007. The netflix prize. In *Proceedings of KDD cup and workshop*, volume 2007, page 35. New York, NY, USA.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*.

Youngduck Choi, Youngnam Lee, Dongmin Shin, Junghyun Cho, Seoyon Park, Seewoo Lee, Jineon Baek, Chan Bae, Byungsoo Kim, and Jaewe Heo. 2020. Ednet: A large-scale hierarchical dataset in education. In *International Conference on Artificial Intelligence in Education*, pages 69–73. Springer.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186.

Sepp Hochreiter and Jürgen Schmidhuber. 1997. Long short-term memory. *Neural computation*, 9(8):1735–1780.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. 2019. Parameter-efficient transfer learning for nlp. In *International Conference on Machine Learning*, pages 2790–2799. PMLR.

Zhiheng Huang, Wei Xu, and Kai Yu. 2015. Bidirectional lstm-crf models for sequence tagging. *arXiv preprint arXiv:1508.01991*.

Xiaoqi Jiao, Yichun Yin, Lifeng Shang, Xin Jiang, Xiao Chen, Linlin Li, Fang Wang, and Qun Liu. 2020. Tinybert: Distilling bert for natural language understanding. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: Findings*, pages 4163–4174.

Wang-Cheng Kang and Julian McAuley. 2018. Self-attentive sequential recommendation. In *2018 IEEE International Conference on Data Mining (ICDM)*, pages 197–206. IEEE.

Xuan Nhat Lam, Thuc Vu, Trong Duc Le, and Anh Duc Duong. 2008. Addressing cold-start problem in recommendation systems. In *Proceedings of the 2nd international conference on Ubiquitous information management and communication*, pages 208–211.

Qi Liu, Zhenya Huang, Yu Yin, Enhong Chen, Hui Xiong, Yu Su, and Guoping Hu. 2019. Ekt: Exercise-aware knowledge tracing for student performance prediction. *IEEE Transactions on Knowledge and Data Engineering*, 33(1):100–115.

Yichao Lu, Ruihai Dong, and Barry Smyth. 2018. Co-evolutionary recommendation model: Mutual learning between ratings and reviews. In *Proceedings of the 2018 World Wide Web Conference*, WWW '18, page 773–782, Republic and Canton of Geneva, CHE. International World Wide Web Conferences Steering Committee.

Prem Melville, Raymond J Mooney, Ramadass Nagarajan, et al. 2002. Content-boosted collaborative filtering for improved recommendations. *Aaai/iaai*, 23:187–192.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. 2013. Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pages 3111–3119.

Shalini Pandey and George Karypis. 2019. A self-attentive model for knowledge tracing. In *12th International Conference on Educational Data Mining, EDM 2019*, pages 384–389. International Educational Data Mining Society.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543.

Chris Piech, Jonathan Bassen, Jonathan Huang, Surya Ganguli, Mehran Sahami, Leonidas J Guibas, and Jascha Sohl-Dickstein. 2015. Deep knowledge tracing. *Advances in Neural Information Processing Systems*, 28:505–513.

Nils Reimers, Iryna Gurevych, Nils Reimers, Iryna Gurevych, Nandan Thakur, Nils Reimers, Johannes Daxenberger, Iryna Gurevych, Nils Reimers, Iryna Gurevych, et al. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.

Burr Settles, Chris Brust, Erin Gustafson, Masato Hagiwara, and Nitin Madnani. 2018. Second language acquisition modeling. In *Proceedings of the thirteenth workshop on innovative use of NLP for building educational applications*, pages 56–65.

Brent Smith and Greg Linden. 2017. Two decades of recommender systems at amazon. com. *Ieee internet computing*, 21(3):12–18.

Megha Srivastava and Noah Goodman. 2021. Question generation for adaptive education. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International*

Joint Conference on Natural Language Processing (Volume 2: Short Papers), pages 692–701, Online. Association for Computational Linguistics.

Xiaoyuan Su and Taghi M Khoshgoftaar. 2009. A survey of collaborative filtering techniques. *Advances in artificial intelligence*, 2009.

Yu Su, Qingwen Liu, Qi Liu, Zhenya Huang, Yu Yin, Enhong Chen, Chris Ding, Si Wei, and Guoping Hu. 2018. Exercise-enhanced sequential modeling for student performance prediction. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Robin Van Meteren and Maarten Van Someren. 2000. Using content-based filtering for recommendation. In *Proceedings of the machine learning in the new information age: MLnet/ECML2000 workshop*, volume 30, pages 47–56.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.

Yulin Wang, Zanlin Ni, Shiji Song, Le Yang, and Gao Huang. 2020. Revisiting locally supervised learning: an alternative to end-to-end training. In *International Conference on Learning Representations*.

Chuhan Wu, Fangzhao Wu, Suyu Ge, Tao Qi, Yongfeng Huang, and Xing Xie. 2019. Neural news recommendation with multi-head self-attention. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 6389–6394.

Chuhan Wu, Fangzhao Wu, Tao Qi, and Yongfeng Huang. 2021. Empowering news recommendation with pre-trained language models. *arXiv preprint arXiv:2104.07413*.

Shitao Xiao, Zheng Liu, Yingxia Shao, Tao Di, and Xing Xie. 2021. Training large-scale news recommenders with pretrained language models in the loop.

Tom Young, Devamanyu Hazarika, Soujanya Poria, and Erik Cambria. 2018. Recent trends in deep learning based natural language processing. *ieee Computational intelligenCe magazine*, 13(3):55–75.

A Lemma 1

Lemma 1. *Given a neural network in separable form $y = g(h; \theta_g), h = f(x; \theta_f)$ with parameters (θ_f, θ_g) and loss $L(\theta_f, \theta_g)$, define pseudo-target $\tilde{h}$, pseudo-loss $\tilde{L}(\theta_f)$ for another network $f(x; \theta'_f)$:*

$$\tilde{h} := f(x; \theta_f) - \frac{\delta L}{\delta h}\Big|_{h = f(x; \theta_f)} \tag{8}$$

$$\tilde{L}(\theta_f) := \frac{1}{2}\left(\tilde{h} - f(x; \theta'_f)\right)^2 \tag{9}$$

Then,

$$\frac{\delta L}{\delta \theta_f} = \frac{\delta \tilde{L}}{\delta \theta'_f}\Big|_{\theta'_f = \theta_f} \tag{10}$$

Lemma 1 shows that the gradient of θ_f in E2E back-propagation with respect to final loss L are equivalent to the gradient of θ'_f with respect to the pseudo-loss (9) based on the simulated regression target (8), provided $h = f(x; \theta_f), \theta_f = \theta'_f$, as implemented by Eq.(6) in GRAM.

Proof.

$$\frac{\delta L}{\delta \theta_f} = \frac{\delta L}{\delta h}\frac{\delta h}{\delta \theta_f} = \frac{\delta L}{\delta y}\frac{\delta y}{\delta h}\frac{\delta h}{\delta \theta_f} \tag{11}$$

$$\frac{\delta \tilde{L}}{\delta \theta'_f}\Big|_{\theta'_f = \theta_f} = -\frac{\delta f}{\delta \theta'_f} \cdot \left(f(x; \theta_f) - \frac{\delta L}{\delta y}\frac{\delta y}{\delta h} - f(x; \theta'_f)\right) \tag{12}$$

$$= \frac{\delta L}{\delta y}\frac{\delta y}{\delta h}\frac{\delta h}{\delta \theta_f} \tag{13}$$

$\square$

B Hierarchical illustration of GRAM

Figure 3 is the hierarchical illustration of GRAM. Blue/Orange/Green corresponds to step [1]/[2]/[3] mentioned in 4.2, respectively.

C Validation Performance

Figure 4 shows the validation performance per training time for E2E and GRAM variants. As the graph includes 10 epochs for early stopping patience, some overfitting is witness at the end of the training curve, such as the sudden drop of GRAM 1S in Spanish dataset after marking best performance.

D Experiment Detail

Across all experiments, CE component uses Tiny-BERT(Jiao et al., 2020), a distilled BERT with on-par performance. The architecture contains 6 MHSA layers of dimension 768. CF component for

Figure 3: Gradient on item representations are accumulated on Pseudo-target to mimic E2E training.

KT uses 2-layer LSTM network, following Piech et al. (2015). In NR, we use a single MHSA layer, following Wu et al. (2019, 2021).

In both domains, learning rate of 1e-4 was used for CF module and CE module after learning rate ablation in the scope of [1e-3, 1e-4, 1e-5]. Adam with Noam scheduler was used as the optimizer. Test metrics were measured by the best validation checkpoint after early stopping of patience 10 epochs. As E2E training consumes different amount of memory based on item token length, different batch sizes were used across datasets. Batch sizes per datasets are the following: 32 for Duolingo, POJ, and TOEIC, and 256 for MIND. As Multi-step GRAM requires much less memory compared with E2E, higher batch size was able to be used for large datasets such as TOEIC and MIND. Details are mentioned in Section C.

For NoFinetune experiment, pre-computed item representations from CE were initialized to CF's item embeddings to boost training speed.

Authors of EERNN also proposed EKT(Liu et al., 2019), which explicitly models the student's knowledge state for different knowledge concepts. As knowledge concept labels are not available in most datasets, we do not test EKT.

D.1 Knowledge Tracing

Mean-pooling was used to extract question representation from contextualized token embedding. For relatively small KT datasets (Duolingo and POJ), it was challenging to secure meaningful number of cold-start items (questions) in the test split.

Figure 4: . Validation AUC convergence and training time until early-stopped checkpoint, across different GRAM alternation periods. Color schemes are synchronized across all subplots.

For these datasets, additional cold-start questions were randomly picked and interactions on those questions in the training split were removed to secure meaningful number of cold start interactions. Items with token length over max seq len (512) were truncated. For TOEIC dataset, passage, question, and choices were concatenated as content token sequence for CE component.

D.2 News Recommendation

For NR, we follow (Wu et al., 2021) to use additive attention based pooling to extract news article representation. Title, abstract, body were concatenated for Setting B, with max len of 24 for title, 50 for abstract, and 400 for body. Items with token length over max seq len were truncated.

E Result Detail

E.1 E2E vs Single-step GRAM Confidence Interval

Metrics	E2E	GRAM (1S)
French Total AUC	0.748 (0.001)	0.750 (0.0006)
Spanish Total AUC	0.751 (0.0005)	0.751 (0.0006)
POJ Total AUC	0.654 (0.0009)	0.655 (0.0011)

Table 7

As TOEIC and MIND E2E result is from a single run due to high computational complexity, Test AUCs on remaining three datasets (Duolingo French, Spanish, POJ) are reported with 95% CIs in Table 7

F Dataset Collection Methods

Duolingo: gathered from 2018 Duolingo Shared Task on Second Language Acqui-sition Modeling. **POJ**: publicly available question texts and interaction logs were scraped from their public website. **TOEIC**: content materials for corresponding question IDs in the dataset were collected privately. **MIND**: collected from website Duolingo (French, Spanish), POJ, MIND datasets are free to download for research purposes under respective terms. Interaction data for TOEIC is avilable as well for research purposes.

ACL Reproducibility Guideline	
For all reported experimental results	
A clear description of the mathematical setting, algorithm, and/or model	O
A link to (anonymized, for submission) downloadable source code, with specification of all dependencies, including external libraries	O
A description of the computing infrastructure used	O
The average runtime for each model or algorithm, or estimated energy cost	O
The number of parameters in each model	O
Corresponding validation performance for each reported test result	X
A clear definition of the specific evaluation measure or statistics used to report results	O
For all results involving multiple experiments, such as hyperparameter search	
The exact number of training and evaluation runs	O
The bounds for each hyperparameter	O
The hyperparameter configurations for best-performing models	O
The method of choosing hyperparameter values (e.g., manual tuning, uniform sampling, etc.) and the criterion used to select among them (e.g., accuracy)	O
Summary statistics of the results (e.g., mean, variance, error bars, etc.)	O
For all datasets used	
Relevant statistics such as number of examples and label distributions	O
Details of train/validation/test splits	O
An explanation of any data that were excluded, and all pre-processing steps	O
For natural language data, the name of the language(s)	O
A link to a downloadable version of the dataset or simulation environment	O
For new data collected, a complete description of the data collection process, such as ownership / licensing, informed consent, instructions to annotators and methods for quality control	O

Table 8: Reproducibility Checklist.