From Discrimination to Generation: Knowledge Graph Completion with Generative Transformer

Xin Xie
Zhejiang University
AZFT Joint Lab for Knowledge Engine
Hangzhou, China
xx2020@zju.edu.cn

Ningyu Zhang[*]
Zhejiang University
AZFT Joint Lab for Knowledge Engine
Hangzhou, China
zhangningyu@zju.edu.cn

Zhoubo Li, Shumin Deng
Zhejiang University
AZFT Joint Lab for Knowledge Engine
Hangzhou, China
{nzb,231sm}@zju.edu.cn

Hui Chen
Alibaba Group
Hangzhou, China
weidu.ch@alibaba-inc.com

Feiyu Xiong, Mosha Chen
Alibaba Group
Hangzhou, China
{feiyu.xfy,chenmosha.cms}@alibaba-inc.com

Huajun Chen[*]
Zhejiang University & AZFT Joint
Lab for Knowledge Engine
Hangzhou, China
huajunsir@zju.edu.cn

ABSTRACT

Knowledge graph completion aims to address the problem of extending a KG with missing triples. In this paper, we provide an approach **GenKGC**, which converts knowledge graph completion to sequence-to-sequence generation task with the pre-trained language model. We further introduce relation-guided demonstration and entity-aware hierarchical decoding for better representation learning and fast inference. Experimental results on three datasets show that our approach can obtain better or comparable performance than baselines and achieve faster inference speed compared with previous methods with pre-trained language models. We also release a new large-scale Chinese knowledge graph dataset AliopenKG500 for research purpose[1].

CCS CONCEPTS

• **Computing methodologies → Knowledge representation and reasoning**.

KEYWORDS

Knowledge Graph Completion; Generation; Transformer

ACM Reference Format:
Xin Xie, Ningyu Zhang, Zhoubo Li, Shumin Deng, Hui Chen, Feiyu Xiong, Mosha Chen, and Huajun Chen. 2018. From Discrimination to Generation: Knowledge Graph Completion with Generative Transformer. In *Proceedings of Make sure to enter the correct conference title from your rights confirmation emai (Conference acronym 'XX)*. ACM, New York, NY, USA, 5 pages. https://doi.org/XXXXXXX.XXXXXXX

---

[*]Corresponding author.

[1]Code and datasets are available in https://github.com/zjunlp/PromptKGC/tree/main/GenKGC

---

1 INTRODUCTION

Knowledge Graphs (KGs) treat the knowledge in the real world as fact triples in the form of <subject, predicate, object>, abridged as (s, p, o), where s and o denote entities and p are the relations between entities, which can benefit a wide range of knowledge-intensive tasks. Knowledge graph completion (KGC) aims to complete the knowledge graph by predicting the missing triples. In this paper, we mainly target *link prediction* task for KGC based on the powerful pre-trained language models.

Most previous KG completion methods, such as TransE [2], ComplEx [11], and RotatE [9], are knowledge embedding techniques that embed the entities and relations into a vector space and then obtain the predicted triples by leveraging pre-defined scoring functions to those vectors. Recently, some textual encoding methods (e.g., KG-BERT [14]) have been proposed, which utilize the pre-trained language model to encode triples and output the score for each candidate. Obviously, most previous approaches leverage the discrimination paradigm with a pre-defined scoring function to knowledge embeddings. However, such a discrimination strategy has to costly scoring of all possible triples in inference and suffer from the instability of negative sampling. Moreover, those dense knowledge embedding approaches (e.g., TransE) ignore the fine-grained interactions between entities and relations and have to allocate a large memory footprint for the large-scale real-world knowledge graph. Therefore, it is intuitive to find a new technical solution for knowledge graph completion.

In this paper, we take the first step to model the knowledge graph completion with sequence to sequence generation and propose a novel approach **GenKGC**. To be specific, we represent entities and relations as input sequences and utilize the pre-trained language model to generate target entities. Following GPT-3's naive "in-context learning" paradigm, in which the model can learn correct output answers by concatenating the selected samples relevant to the input, we propose relation-guided demonstration by adding triples of the same relation. Moreover, during generation, we propose entity-aware hierarchical decoding to reduce the time complexity of generation. Experimental results on two datasets WN18RR, FB15k-237 and a newly released large-scale Chinese KG dataset AliopenKG500 demonstrate the effectiveness of the proposed approach. The contributions of our work are as follows:

Figure 1: Architecture of GenKGC. We augment the input text of entity and relation with demonstrations, and introduce entity-aware hierarchical decoding for fast inference.

- We convert link prediction to sequence to sequence generation and propose **GenKGC**, which can reduce the inference time while maintaining the performance.
- We propose relation-guided demonstration and entity-aware hierarchical decoding, which can better represent entities and relations and reduce the time complexity of generation.
- We report results on two datasets and release a new large-scale KG dataset, AliopenKG500, for research purposes.

2 METHOD

2.1 Link Prediction as Seq2Seq Generation

Knowledge graph is defined with entity categories and entity descriptions as a tuple $\mathcal{G} = (\mathcal{E}, \mathcal{R}, \mathcal{T}, C, \mathcal{D})$, where $\mathcal{E}$ represents a set of entities, $\mathcal{R}$ represents relation types, $\mathcal{T}$ refers to a set of triples , C refers to the entity categories and $\mathcal{D}$ refers to the entity descriptions. For each triple $t \in \mathcal{T}$, there is the form (e_i, r_j, e_k) where $e_i, e_k \in \mathcal{E}$ is the head and tail entity respectively. For each entity $e_i \in \mathcal{E}$, there exists category c_i to define the e_i and a text d_i to describe e_i. To complete missing triples in KGs, link prediction aims at predicting the tail entity given the head entity and the query relation, denoted by $(e_i, r, ?)$.

In this paper, we utilize the standard encoder-decoder architecture for sequence-to-sequence generation. Note that we regard each entity and relation as the sequence of tokens. Concretely, we follow [14] to use plain text to represent the entities and relations instead of unique embedding to bridge the gap between the triples in the knowledge graph and pre-trained language models. To be specific, given a triple with tail entity missing $(e_i, r_j, ?)$, we obtain the description $d_{e_i}\, d_{r_j}$ of e_i and r_j respectively, and concatenate them together. For example, as shown in Figure 1, *"Michael Chabon studied at"* (head entity, relation) is the major part of the input sequence, and *"UC, Irvine"* (target entity) is part of the output sequence. Thus, we have the input sequence of $< e_i, r >$ pair and generate the output sequence of e_k. We leverage BART for model training and inference.

Table 1: Inference and training efficiency comparison. $|d|$ is the length of the entity description. $|\mathcal{E}|$ is the numbers of all unique entities in the KG. k is the negative samples for KG-BERT and the beam size for our GenKGC . The time under RTX 3090 is used to estimate the speed of training and inference given a single (entity,relation) pair on AliopenKG500.

For One Triple	Method	Complexity	Time under RTX 3090
	TransE	$O(k+1)$	0.08ms
Training	KG-BERT	$O(|d|^2 \times (k+1))$	72ms
	GenKGC	$O(|d|^2)$	2.35ms
	TransE	$O(|\mathcal{E}|)$	0.02s
Inference	KG-BERT	$O(|d|^2 \times |\mathcal{E}|)$	10100s
	GenKGC	$O(|d|^2 \times |d|^k)$	0.96s

2.2 Relation-guided Demonstration

Inspired by prompt-tuning [18], we propose relation-guided demonstration for the encoder. Note that there exist long-tailed distributions in the KGs, for example, there exist only 37 instances of the relation `film/type_of_appearance` in the FB15k-237 dataset. Previous study [18] illustrates that concatenating randomly sampled instances as demonstrations can yield better few-shot performance. Thus, we construct relation-guided demonstration examples $\{r_{in}, t_{train}\}$. To be specific, we sample those demonstrations with the guidance of relation r_j, which consists of several triples with the same relation of input from training set. Formally, we have the final input sequence as:

$$x = \text{<bos> demonstration}(r_j) \text{ <sep> } d_{e_i}\, d_{r_j} \text{ <sep>}$$

2.3 Entity-aware Hierarchical Decoding

In the vanilla decoding setting, we have to enumerate all entities in the $\mathcal{E}$ and then sort them by the score function. However, this process can be time-consuming, as shown in Table 1 when $\mathcal{E}$ is very large, it is costly scoring of all possible triples. In our approach, we follow [3] to use the Beam Search to obtain top-k entities in the $\mathcal{E}$ (k is the hyperparameter of beam size). Intuitively, there is no need for negative sampling as we directly optimize by predicting

Table 2: Experiment results on WN18RR, FB15k-237 and AliopenKG500. ◇Resulting numbers are reported by [8], we reproduce the model result on AliopenKG500 and take other results from the original papers.

Method	WN18RR			FB15k-237			AliopenKG500		
	Hits@1	Hits@3	Hits@10	Hits@1	Hits@3	Hits@10	Hits@1	Hits@3	Hits@10
Graph embedding approach									
TransE [2] ◇	0.043	0.441	0.532	0.198	0.376	0.441	0.207	0.340	0.513
DistMult [13] ◇	0.412	0.470	0.504	0.199	0.301	0.446	0.049	0.088	0.216
ComplEx [11] ◇	0.409	0.469	0.530	0.194	0.297	0.450	0.053	0.120	0.266
RotatE [9]	0.428	0.492	0.571	0.241	0.375	0.533	-	-	-
TuckER [1]	0.443	0.482	0.526	0.226	0.394	0.544	-	-	-
ATTH [4]	0.443	0.499	0.486	0.252	0.384	0.549	-	-	-
Textual encoding approach									
KG-BERT [14]	0.041	0.302	0.524	-	-	0.420	0.023	0.049	0.241
StAR [12]	0.243	0.491	0.709	0.205	0.322	0.482	-	-	-
GenKGC	0.287	0.403	0.535	0.192	0.355	0.439	0.203	0.280	0.351

the correct entity in decoding. To be more specific, given with a triple with tail or head entity missing $(e_i, r_j, ?)$, **GenKGC** rank each $e \in \mathcal{E}$ by computing a score with an autoregressive formulation:

$$p_\theta(y \mid x) = \prod_{i=1}^{|c|} p_\theta(z_i \mid z_{<i}, x) \prod_{i=|c|+1}^{N} p_\theta(y_i \mid y_{<i}, x), \quad (1)$$

where z is the set of $|C|$ tokens in the category c, y is the set of N tokens in the textual representation of e.

Since KG contains rich semantic information such as entity types, it is intuitive to constrain the decoding for fast inference. We sample the type category with the lowest frequency of occurrence in the training set to constrain the entity decoding since it is challenging to discriminate those low-frequent entities. Then, we add special tokens as types in the vocabulary of pre-trained language model to constrain the decoding. To ensure that the generated entities are inside the entity candidate set, we construct a prefix tree (trie tree) to decode our entity name as shown in Figure 1. Similar to the ordinary sequence-to-sequence model, we optimize **GenKGC** using a standard seq2seq objective function:

$$\mathcal{L} = -\log p_\theta(y \mid x) \quad (2)$$

3 EXPERIMENT

Datasets. We evaluate our method on FB15k-237 [10], WN18RR [5], which are widely used in the link prediction literature, and a new real-world large-scale Chinese KG dataset AliOpenKG500[2]. In FB15k-237, descriptions of entities are obtained from the introduction section of the Wikipedia page of each entity. In WN18RR, each entity corresponds to a word sense, and description is the word definition. In AliOpenKG500, the descriptions of entities and relations come from the e-commerce description page. More details about datasets are listed in Table 3.

---

[2]AliOpenKG500 is a subset of open business KG from https://kg.alibaba.com/.

Table 3: Summary statistics of benchmark datasets.

Dataset	# Ent	# Rel	# Train	# Dev	# Test
WN18RR	40,943	11	86,835	3,034	3,134
FB15k-237	14,541	237	272,115	17,535	20,466
AliOpenKG500	269,658	500	1,242,550	5,000	5,000

Setting. We adopt BART-base as our backbone for comparison with other BERT-based KGC methods like KG-BERT. Following StAR [12], we choose the two kinds of KGE methods as our baseline models, which can be classified as graph embedding approach and textual encoding approach. Grid search is used over the three datasets and the results are reported on the test set with hyperparameters of the best performance determined by the dev set.

Metrics. We evaluate the test set of triples $\mathcal{T}'$ disjoint from the set of training triples $\mathcal{T}$. For inference on a test triple (e_i, r_j, e_k), we make sure predict the entity in the candidate set $\mathcal{E}$. We use the metrics of hits@1, hits@3 and hits@10.

Comparison with Discrimination Method. From Table 2, we notice that **GenKGC** achieves better performance than KG-BERT [14] across all datasets and maintains high speed during inference. The translation-based method like TransE, which treats entities and relations as dense vectors in the same space, will face the memory explosion problem. For the memory cost, TransE has to consume 260M parameters to store the entities and relations for AliopenKG500 with more than 260k entities, while pre-trained models (BERT or BART) only utilize 110M parameters, which demonstrates the memory efficiency of our approach. Note that this problem will be more severe when the entities become more numerous because the space complexity is $O(n)$. For the inference speed, KG-BERT encodes the relational triples with the pre-trained language model and ranks all candidate triples with correct and wrong entities for inference. When the candidate entities set is huge, it is time-consuming for inference; for example, as shown in Table 1, KG-BERT takes about 100100s to the scoring of all possible triples given a single (entity,

Table 4: We list a query and first five entities with their probability predicted by GenKGC w/o entity-aware decoding, and its reranking with GenKGC.

Query: (?, student, Michael Chabon)		
Rank	**GenKGC** w/o hierarchical decoding	Probability
1	University of California	
2	**University of California, Irvine**	
3	University of California, San Francisco	
4	University of California, Davis	
5	University of California, Santa Cruz	
Rank	**GenKGC**	Probability
1	**University of California, Irvine**	
2	University of California, San Francisco	
3	University of California, Davis	
4	University of California, Santa Cruz	
5	University of Calgary	

relation) pair. While our method only needs to generate the top-k entities with entity-aware hierarchical decoding, which **reduces lots of computing resources**.

3.1 Case Study

For different decoding strategies we conduct case study to analyze the result. For **GenKGC** w/o hierarchical decoding, we utilize the normal beam search to decode the text name of the missing entity. From Table 4, we observe that **GenKGC** obtain better entity generation results while in normal beam search, the model may stop early at correct but not precise enough answer. We argue that this is caused by the bias of the pre-trained language model (e.g., common token bias) since high-frequent tokens will lead the pre-trained language model to be biased toward certain answers. Our entity-aware hierarchical decoding can constrain the decoding process and mitigate the bias effect caused by pre-trained language models.

4 RELATED WORK

Knowledge Graph Embedding Models. There are lots of methods of KGC are based on knowledge graph embeddings (KGE), which generally leverage an embedding vector in the continuous embedding space to represent the entity and the relation in KG [17]. One kind of KGE methods is *translation-based*, such as TransE [2], ConE [20], TotatE [9], which consider relations as the mapping function between entities.The other kind of KGE method is *semantic matching* models, where they get the semantic similarity by using the multi-linear or bilinear product.

Pre-trained Language Models for KGC. Recently, since pre-trained language models, such as BERT [6], have shown significant improvement on several natural language processing tasks, several works use the transformer-based models to tackle the KGC problems [15, 16, 19]. KG-BERT [14] first propose to use BERT for KGC by seeing a triple as a sequence and converts KGC into a sequence classification problem with the binary cross-entropy object. [7] proposes to use a transformer encoder-decoder model that takes plain text as input and output a structured triple of the information hide in it.

5 CONCLUSION

In this paper, we propose **GenKGC**, which can reach comparable results while reducing inference and training cost in link prediction with pre-trained models. Experimental results on three benchmark datasets demonstrate the effectiveness of our approach, especially in inference time. The success of **GenKGC** suggests that link prediction as sequence-to-sequence generation can be helpful because entities can be inferred directly rather than costly scoring of all possible triples. Future work should explore how to obtain the suitable categories for each entity in decoding.

ACKNOWLEDGMENTS

This work is funded by NSFC91846204/NSFCU19B2027, National Key R&D Program of China (Funding No.SQ2018YFC000004), Zhejiang Provincial Natural Science Foundation of China (No. LGG22F030011), Ningbo Natural Science Foundation (2021J190), and Yongjiang Talent Introduction Programme (2021A-156-G).

REFERENCES

[1] Ivana Balazevic, Carl Allen, and Timothy M. Hospedales. 2019. TuckER: Tensor Factorization for Knowledge Graph Completion. In *Proc. of EMNLP*.

[2] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. 2013. Translating embeddings for modeling multi-relational data. In *Proc. of NeurIPS*.

[3] Nicola De Cao, Gautier Izacard, Sebastian Riedel, and Fabio Petroni. 2021. Autoregressive Entity Retrieval. In *Proc. of ICLR*.

[4] Ines Chami, Adva Wolf, Da-Cheng Juan, Frederic Sala, Sujith Ravi, and Christopher Ré. 2020. Low-Dimensional Hyperbolic Knowledge Graph Embeddings. In *Proc. of ACL*.

[5] Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. 2018. Convolutional 2D Knowledge Graph Embeddings. In *Proc. of AAAI*.

[6] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proc. of NAACL*.

[7] Martin Josifoski, Nicola De Cao, Maxime Peyrard, and Robert West. 2021. GenIE: Generative Information Extraction. *CoRR* (2021).

[8] Deepak Nathani, Jatin Chauhan, Charu Sharma, and Manohar Kaul. 2019. Learning Attention-based Embeddings for Relation Prediction in Knowledge Graphs. In *Proc. of ACL*.

[9] Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. 2019. RotatE: Knowledge Graph Embedding by Relational Rotation in Complex Space. In *ICLR*.

[10] Kristina Toutanova, Danqi Chen, Patrick Pantel, Hoifung Poon, Pallavi Choudhury, and Michael Gamon. 2015. Representing Text for Joint Embedding of Text and Knowledge Bases. In *Proc. of EMNLP*.

[11] Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. 2016. Complex Embeddings for Simple Link Prediction. In *Proc. of ICML*.

[12] Bo Wang, Tao Shen, Guodong Long, Tianyi Zhou, Ying Wang, and Yi Chang. 2021. Structure-Augmented Text Representation Learning for Efficient Knowledge Graph Completion. In *Proc. of WWW*.

[13] Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. 2015. Embedding Entities and Relations for Learning and Inference in Knowledge Bases. In *Proc. of ICLR*.

[14] Liang Yao, Chengsheng Mao, and Yuan Luo. 2019. KG-BERT: BERT for Knowledge Graph Completion. *CoRR* (2019).

[15] Hongbin Ye, Ningyu Zhang, Shumin Deng, Xiang Chen, Hui Chen, Feiyu Xiong, Xi Chen, and Huajun Chen. 2022. Ontology-enhanced Prompt-tuning for Few-shot Learning. (2022).

[16] Ningyu Zhang, Zhen Bi, Xiaozhuan Liang, Siyuan Cheng, Haosen Hong, Shumin Deng, Jiazhang Lian, Qiang Zhang, and Huajun Chen. 2022. OntoProtein: Protein Pretraining With Gene Ontology Embedding. (2022).

[17] Ningyu Zhang, Shumin Deng, Zhanlin Sun, Jiaoyan Chen, Wei Zhang, and Huajun Chen. 2020. Relation Adversarial Network for Low resource Knowledge Graph Completion. In *Proc. of WWW*.

[18] Ningyu Zhang, Luoqiu Li, Xiang Chen, Shumin Deng, Zhen Bi, Chuanqi Tan, Fei Huang, and Huajun Chen. 2022. Differentiable Prompt Makes Pre-trained Language Models Better Few-shot Learners. In *Proc. of ICLR*.

[19] Ningyu Zhang, Xin Xie, Xiang Chen, Shumin Deng, Chuanqi Tan, Fei Huang, Xu Cheng, and Huajun Chen. 2022. Reasoning Through Memorization: Nearest Neighbor Knowledge Graph Embeddings. *CoRR* abs/2201.05575 (2022).

arXiv:2201.05575 https://arxiv.org/abs/2201.05575

[20] Zhanqiu Zhang, Jie Wang, Jiajun Chen, Shuiwang Ji, and Feng Wu. 2021. ConE:
Cone Embeddings for Multi-Hop Reasoning over Knowledge Graphs. *Proc. of*
NeurIPS (2021).