Few-shot image classification by generating natural language rules

Abstract

The ability to generate rules and hypotheses plays a key role in multiple aspects of human cognition including concept learning and explanation. Previous research has framed this ability as a form of inference via probabilistic program induction. However, this modeling approach often requires careful construction of the right grammar and hypothesis space for a particular task, and cannot easily be transferred to other domains. In this work, we propose an alternative computational account of rule generation and concept learning that sidesteps some of these issues. By leveraging advances in multimodal learning and large language models, we extend the latent language framework from Andreas et al. (2017) to work in a zero-shot manner. Taking naturalistic images as input, our computational model is capable of generating candidate rules that are specified in natural language, and verifying them against the observed data. We show that our model can generate, in a zero-shot manner, plausible rules for visual concepts in two domains.

1 Introduction

Humans have a remarkable ability in generating a wide variety of rules and hypotheses to make sense of the world, ranging from perceptual classification rules to distinguish between when a plant is safe or poisonous to eat, to complex scientific hypotheses that attempt to explain disparate observed phenomena (Schulz, 2012). But where does this ability to generate novel rules or hypotheses come from in the first place? Within the last decade, there has been a resurgence of interest of rule and hypothesis generation, led by accounts positing concept learning as a form of probabilistic program induction (Goodman et al., 2008; Piantadosi and Jacobs, 2016). Such approaches have been successful at capturing human concept learning in domains such as hand-written characters (Lake et al., 2015) and logical concepts (Piantadosi et al., 2016).

However, these approaches have a number of limitations. First, these models are often instantiated with a minimal grammar to construct novel concepts, whereas humans can leverage their knowledge of pre-existing lexical concepts to guide the rule generation process. Second, the grammars used in these with are often *domain-specific*, requiring extensive researcher effort to reverse-engineer from behavioral data and difficult to transfer to different domains.

In this paper, we outline an alternative account of rule-based concept learning that attempts to overcome some of the above limitations. We combine two key ideas in our approach. First, we leverage natural language as a *domain-general* representational medium for rules, inspired by the latent language framework from Andreas et al. (2017). Second, we utilize advances from large-scale neural networks such as CLIP (Radford et al., 2021; Goh et al., 2021) and GPT-3 (Brown et al., 2020), to instantiate a few-shot image classification model via latent language, allowing it to classify images by generating rules specified in natural language, without any additional training required. We demonstrate this across two domains and tasks which have commonly been used in visual concept learning.

2 Related Work

Within cognitive science, our work builds off a long history of research into rule and hypothesis generation (Nosofsky et al., 1994; Goodman et al., 2008; Piantadosi et al., 2016; Bramley et al., 2018; Ellis et al., 2020). Many of these accounts treat concept learning as a form of probabilistic program induction, sampling hypotheses or rules from an grammar-based hypothesis space. However, these models are often specified with a minimal starting representation that is in stark contrast to the vast library of concepts already available from natural language.

Within machine learning, our work is related

Figure 1: **Examples of captions and rules generated by our model in two domains**. In the set completion task (top row), the model generates a single natural language rule to determine the matching item from the query set. In the one vs. two classification task (bottom row), the model generates two rules for each class to classify query examples into.

to models of few-shot visual classification (Lake et al., 2015; Snell et al., 2017; Mu et al., 2020), but especially the work of Andreas et al. (2017), which leverages natural language as a representational bottleneck for performing visual classification. Within few-shot learning, there also exist models that allow the use of auxiliary class information for zero-shot classification (Snell et al., 2017), but in this work our model generates the relevant class label information itself from the support examples. We also take advantage of recent work in multimodal neural networks (Radford et al., 2021; Li et al., 2022) which have been shown to contain extensive knowledge of multimodal concepts (Goh et al., 2021), and can be used to perform tasks like image captioning and zero-shot image classification.

3 Model

Our model extends the *Learning with Latent Language* (L3) approach from Andreas et al. (2017). The L3 model consists of a **proposal model** g_ϕ that generates natural language rules via an image captioning system, and an **interpretation model** h_η that provides a numerical match score between natural language rules and images. Training the L3 model requires a *language learning* phase where domain-specific language annotations are used to train each component separately, which can then be utilized at test time by generating candidate language descriptions for new concepts. In this work, we skip the language learning phase, and instead leverage existing pre-trained multimodal and language models to perform the proposal and interpretation steps. Additionally, the use of natural language as a representational bottleneck in this architecture means that different models that take natural language as input, or generate natural language as output, can be stitched together despite not being trained jointly.

To generate proposals, the L3 model provides the mean embedding across multiple images to an image captioning model to produce the corresponding natural language descriptions. However, pre-trained image captioning models are generally trained to predict captions from a single image, not across multiple images. Furthermore, these captions are typically only applicable to that particular image, and do not describe what might be common amongst multiple images, which is our intended goal.

To alleviate these issues, we split the proposal model into two separate steps in our model, as shown in Figure 1. First, in the **captioning** step, we use BLIP (Li et al., 2022), a recent pre-trained multimodal transformer, to generate captions for each image in the support set separately. Second, in the **abstraction** step, we leverage large language models like GPT-3 (Brown et al., 2020) to propose natural language rules rules that convert these instance-level captions to an abstract rule specified in natural language. Specifically, we provided GPT-3 with a prompt consisting of a task description followed by some examples of descriptions and a natural language rule for how these descriptions were related, and then appended each of the generated captions in a random order to the prompt and asked it to generate a corresponding rule (see Appendix A). Across the experiments reported, we run the captioning step once, and sample multiple rules via prompting GPT-3.

Adapting the **interpretation** step for the zero-shot setting is relatively straightforward. The image-text matching procedure from L3 is very similar to how image-text matching is used to train contrastive image-text models (Radford et al., 2021; Li et al., 2022). For convenience purposes, we re-use the BLIP architecture from the captioning

step, but instead use the separate image-text contrastive head as h_η. The interpretation model takes in an image and text as input, and outputs a cosine similarity score describing the match between the given image and text. The interpretation model is used both to determine the best generated rule via classification over the support set, as well as for prediction on new query examples.

4 Experiments

ShapeWorld. We adapted the ShapeWorld visual reasoning dataset which has been used to investigate few-shot visual concept learning (Kuhnle and Copestake, 2017; Andreas et al., 2017; Mu et al., 2020). While the kinds of images in this dataset are relatively simple abstract shapes of varying colors, one important difference is that our model has not been trained directly on any images from ShapeWorld, and needs to determine the relevant dimensions to generate valid rules from the observed exemplars without any prior experience in this domain.

Using 8 colors and 7 shapes, we generated three types of concepts consisting of either a single primitive **shape** concept (where color could vary), or a primitive **color** concept (where shape could vary), or a conjunction of **shape and color** primitives (e.g. a *blue triangle*, or a *red square*).

Since the concepts generated in this domain consist of a single class of positive examples, we opted to test the model via *set completion* (Andonian et al., 2020) rather than few-shot classification[1]. Given a set of four support images from a given concept, we used the captioning model to generate four captions, which were passed into GPT-3 to generate candidate natural language rules. The best rule was determined by the rule with the highest average cosine similarity to the set of support examples using the interpretation model h_η, and this rule was subsequently used to select the example matching this concept from a separate query set of another four examples, as shown in Figure 1. We sampled 300 concepts roughly split between the three different types for testing.

Results. Results are shown in Table 1. Overall, our model performed quite well at the set completion task in this domain, and allowing the model to generate multiple candidate rules led to a substantial in-

Model	Overall	S	C	S+C
Prototype	89.7	92.9	77.1	98.1
L3 (1 rules)	64.6	70.4	63.5	60.3
L3 (10 rules)	88.3	86.7	89.6	88.7
L3 (oracle)	91.0	90.8	91.7	90.6

Table 1: ShapeWorld set completion results. **S** refers to shape concepts, **C** refers to color concepts, and **S+C** refers to shape and color concepts

crease in accuracy. Qualitatively, the kinds of rules generated were sensible and matched the underlying concepts (e.g. "*a purple triangle*", "*squares on a black background*"), whereas incorrect rules often specified the wrong target feature (such as color instead of shape).

Overall performance was similar to a prototype model, that predicted the matching exemplar based on the cosine similarity of each query example to the mean embedding from the visual representations of the support examples. Breaking down performance for the different rule types showed some interesting differences. While performance in our model was the same across the three types of concepts, the prototype-based model was more accurate at classifying conjunctive concepts, likely because both relevant feature dimensions were correlated. However, its performance on shape versus color was lower, with color concepts being substantially more difficult. This suggests that generating candidate natural language rules might be especially helpful with determining the relevant axis of generalization compared to a model that generalizes from fixed visual representations.

Abstract Rules. In the second experiment, we explored two kinds of more challenging rules using naturalistic images, to see whether our model could generate such rules, and whether using these natural language rules for classification would be more beneficial than image features alone. We filtered a subset of the COCO training dataset (Lin et al., 2014), for images with annotations with either one or two animals. We used this subset to create few-shot classification splits for determining whether images contained **one vs. two** animals, or determining whether an image contained two **same vs. different** animals, an analogue of the same-different task that has been extensively studied in cognitive science (Carstensen and Frank, 2021). Both of these kinds of rules are more challenging

---

[1]More specifically, the cosine similarity for a matching image and text from BLIP is generally below 0.5, making it difficult to pass the result through a sigmoid for classification out-of-the-box.

since they rely on picking up relational properties across objects in a single image.

Out of the 10 animal classes in COCO, we randomly split half to be sampled as images for support examples, and the other half to be sampled as query examples.[2] For both types of rules, we sampled 6 exemplars of each class, and repeated this process to create 10 different instances of each concept split. To evaluate the models, we sampled 6 additional exemplars from each class as query examples. Due to the added complexity of the rules in this experiment, we allowed the model to sample up to 20 rules (one rule for each class separately), and selected the best rule on the basis of classification on the support set. Initial testing showed that the previous prompt to GPT-3 used in the ShapeWorld domain was not sufficient generating rules, and required an adaptation to the original prompt for this task with different examples (see Appendix A for details).

Results. Results are shown in Table 2. Compared to the ShapeWorld domain, we observed more variability in the results for this simulation. Even with the ability to generate 20 candidate rules, performance on both tasks was quite variable, depending on the quality of the rules generated in each separate instance.[3] For the **one vs. two** condition, the model often generalized too strictly, e.g. "*two giraffes*" which led to incorrect classifications on the query set, although overall its performance was similar to the prototype model. Interestingly, for **same vs. different**, the model showed reasonable classification accuracy relative to the chance-level performance observed in the prototype model, and was able to generate plausible rules like "*animals in a pair*", or "*a couple of something*" for the same instances. Furthermore, providing the model with ground truth rules in the oracle model resulted in high classification performance in both tasks, suggesting that classification via natural language rules might provide a better method for generalization of more abstract visual properties, assuming the model can reliably generate good rules, or is provided with such rules from another person in a social context (Chopra et al., 2019; Acquaviva

Model	One vs. Two	Same vs. Diff
Prototype	63.3	52.5
L3 (20 rules)	59.1	70.0
L3 (oracle)	87.5	85.8

Table 2: COCO few-shot classification results.

et al., 2021).

5 Discussion

In this paper, we extended the learning from latent language (L3) framework from Andreas et al. (2017) to enable generation of natural language rules in a zero-shot manner. By combining large-scale pre-trained neural networks to act as proposal and interpretation models, we demonstrated a system that could generate natural language rules across a number of concept learning tasks, demonstrating its ability to generate valid yet interepretable rules in natural language. Our results highlight the *flexibility* of using natural language for generalization: our model was better at generalizing to color concepts than a baseline prototype model that relied on visual features alone, as well as to more abstract relational rules in the second experiment (particularly when it was provided with the underlying rule to use), suggesting that natural language can easily modulate generalization and classification behavior.

One limitation of the current approach is that is reliant on the text captions to generate proposed rules, and thus the quality of the generated rules is dependent on what aspects or features the pre-trained captioning model chooses to highlight and describe. Some ways to overcome this issue might be using a model trained to caption multiple images directly (Hernandez et al., 2022), or incorporating images directly into the abstraction prompt via multimodal few-shot learning (Tsimpoukelli et al., 2021). Second, we prompted GPT-3 to produce rules by performing a comparison *within* exemplars, but it is very likely that adapting the prompt to allow for comparison *across* exemplars would also be beneficial (Williams and Lombrozo, 2010; Edwards et al., 2019). Finally, given the generality of the proposed approach, in future work we hope to test this model more extensively against other kinds of concepts that have been extensively studied in the cognitive science literature, to determine whether natural language rules can explain other kinds of human-like generalization behavior.

---

[2]Any images that contained one animal from the support set, and one from the query set was discarded during this sampling process.

[3]We also noticed that even in the context of a single rule, classification responses demonstrated a graded nature, for example, an image with two animals but one partially occluded would be more confusable than an image with two distinct animals.

References

Samuel Acquaviva, Yewen Pu, Marta Kryven, Catherine Wong, Gabrielle E Ecanow, Maxwell Nye, Theodoros Sechopoulos, Michael Henry Tessler, and Joshua B Tenenbaum. 2021. Communicating natural programs to humans and machines. *arXiv preprint arXiv:2106.07824*.

Alex Andonian, Camilo Fosco, Mathew Monfort, Allen Lee, Rogerio Feris, Carl Vondrick, and Aude Oliva. 2020. We have so much in common: Modeling semantic relational set abstractions in videos. In *European Conference on Computer Vision*, pages 18–34. Springer.

Jacob Andreas, Dan Klein, and Sergey Levine. 2017. Learning with latent language. *arXiv preprint arXiv:1711.00482*.

Neil Bramley, Anselm Rothe, Josh Tenenbaum, Fei Xu, and Todd Gureckis. 2018. Grounding compositional hypothesis generation in specific instances. In *Proceedings of the 40th annual conference of the cognitive science society*.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Alexandra Carstensen and Michael C Frank. 2021. Do graded representations support abstract thought? *Current Opinion in Behavioral Sciences*, 37:90–97.

Sahil Chopra, Michael Henry Tessler, and Noah D Goodman. 2019. The first crank of the cultural ratchet: Learning and transmitting concepts through language. In *CogSci*, pages 226–232.

Brian J Edwards, Joseph J Williams, Dedre Gentner, and Tania Lombrozo. 2019. Explanation recruits comparison in a category-learning task. *Cognition*, 185:21–38.

Kevin Ellis, Catherine Wong, Maxwell Nye, Mathias Sable-Meyer, Luc Cary, Lucas Morales, Luke Hewitt, Armando Solar-Lezama, and Joshua B Tenenbaum. 2020. Dreamcoder: Growing generalizable, interpretable knowledge with wake-sleep bayesian program learning. *arXiv preprint arXiv:2006.08381*.

Gabriel Goh, Nick Cammarata, Chelsea Voss, Shan Carter, Michael Petrov, Ludwig Schubert, Alec Radford, and Chris Olah. 2021. Multimodal neurons in artificial neural networks. *Distill*, 6(3):e30.

Noah D Goodman, Joshua B Tenenbaum, Jacob Feldman, and Thomas L Griffiths. 2008. A rational analysis of rule-based concept learning. *Cognitive science*, 32(1):108–154.

Evan Hernandez, Sarah Schwettmann, David Bau, Teona Bagashvili, Antonio Torralba, and Jacob Andreas. 2022. Natural language descriptions of deep visual features. *arXiv preprint arXiv:2201.11114*.

Alexander Kuhnle and Ann Copestake. 2017. Shapeworld-a new test methodology for multimodal language understanding. *arXiv preprint arXiv:1704.04517*.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. 2015. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. 2022. Blip: Bootstrapping language-image pretraining for unified vision-language understanding and generation. *arXiv preprint arXiv:2201.12086*.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. 2014. Microsoft coco: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer.

Jesse Mu, Percy Liang, and Noah Goodman. 2020. Shaping visual representations with language for few-shot classification. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4823–4830.

Robert M Nosofsky, Thomas J Palmeri, and Stephen C McKinley. 1994. Rule-plus-exception model of classification learning. *Psychological review*, 101(1):53.

Steven T Piantadosi and Robert A Jacobs. 2016. Four problems solved by the probabilistic language of thought. *Current Directions in Psychological Science*, 25(1):54–59.

Steven T Piantadosi, Joshua B Tenenbaum, and Noah D Goodman. 2016. The logical primitives of thought: Empirical foundations for compositional cognitive models. *Psychological review*, 123(4):392.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR.

Laura Schulz. 2012. Finding new facts; thinking new thoughts. *Advances in child development and behavior*, 43:269–294.

Jake Snell, Kevin Swersky, and Richard Zemel. 2017. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30.

Maria Tsimpoukelli, Jacob Menick, Serkan Cabi, SM Eslami, Oriol Vinyals, and Felix Hill. 2021. Multimodal few-shot learning with frozen language models. *Advances in Neural Information Processing Systems*, 34.

Joseph J Williams and Tania Lombrozo. 2010. The role of explanation in discovery and generalization: Evidence from category learning. *Cognitive science*, 34(5):776–806.

A Appendix

A.1 ShapeWorld

The following prompt was used to pass the individual captions into GPT-3 to generate rules:

```
Task:  given a list of
descriptions, predict what they
have in common
List:  a bowl of apples | a
photograph of some cherries |
a person eating a banana |
Rule:  fruit
List:  people on a soccer field |
a cricket game | a basketball |
Rule:  sports that involve a ball
List:  {caption_1} | {caption_2}
| ... | {caption_n} |
Rule:
```

For all concepts we use the `text-davinci-001` version of GPT-3 with a temperature setting of 0.7.

A.2 Abstract Rules

The adapted prompt passed into GPT-3 for both rules in the Abstract Rules simulations was as follows:

```
Task:  given a list of captions,
predict what they have in common
List:  a red apple in a bowl | a
child in a crib | coffee in a mug
|
Rule:  things inside of another
object
List:  a flock of seagulls | a
swarm of bees | a collection of
books
Rule:  things in a collection
List:  {caption_1} | {caption_2}
| ... | {caption_n} |
Rule:
```

For all concepts we use the `text-davinci-001` version of GPT-3 with a higher temperature setting of 1.0 to encourage different rules for each class.