META DOMAIN ADAPTATION: META-LEARNING FOR FEW-SHOT LEARNING UNDER DOMAIN SHIFT

ABSTRACT

Few-Shot Learning (learning with limited labeled data) aims to overcome the limitations of traditional machine learning approaches which require thousands of labeled examples to train an effective model. Considered as a hallmark of human intelligence, the community has recently witnessed several contributions on this topic, in particular through meta-learning, where a model learns how to learn an effective model for few-shot learning. The main idea is to acquire prior knowledge from a set of training tasks, which is then used to perform (few-shot) test tasks. Most existing work assumes that both training and test tasks are drawn from the same distribution, and a large amount of labeled data is available in the training tasks. This is a very strong assumption which restricts the usage of meta-learning strategies in the real world where ample training tasks following the same distribution as test tasks may not be available. In this paper, we propose a novel meta-learning paradigm wherein a few-shot learning model is learnt, which simultaneously overcomes domain shift between the train and test tasks via adversarial domain adaptation. We demonstrate the efficacy the proposed method through extensive experiments.

1 INTRODUCTION

Few-Shot Learning aims to learn a prediction model from very limited amount of labelled data (Lake et al., 2015). Specifically, given a $K-$shot, $N-$class data for a classification task, the aim is to learn a multi-class classification model for $N-$ classes, with $K-$labeled training examples for each class. Here K is usually a small number (e.g. 1, or 5). Considered as one of the hallmarks of human intelligence (Lake et al., 2011), this topic has received considerable interest in recent years (Lake et al., 2015; Koch et al., 2015; Vinyals et al., 2016; Finn et al., 2017). Modern techniques solve this problem through *meta-learning*, using an *episodic* learning paradigm. The main idea is to use a labeled training dataset to effectively acquire prior knowledge, such that this knowledge can be transferred to novel tasks where few-shot learning is to be performed. Different from traditional transfer learning (Pan et al., 2010; Yosinski et al., 2014), here few-shot tasks are simulated using the labeled training data through episodes, in order to acquire prior knowledge that is specifically tailored for performing few-shot tasks. For example, given a set of labeled training data with a finite label space $\mathcal{Y}^{train}$, the epsiodic paradigm is used to acquire prior knowledge which is stored in a model. Each episode is generated i.i.d from an unknown task distribution τ_{train}. This model is then used to do a novel few shot classification task which is drawn from an unknown task distribution τ_{test}. The test task comprises small amount of labeled data with a finite label space $\mathcal{Y}^{test}$, and the sets $\mathcal{Y}^{train}$ and $\mathcal{Y}^{test}$ are (possibly) mutually exclusive. Using this labeled data, and acquired prior knowledge, the goal is to predict the labels of all unlabeled instances in test task.

A very restrictive assumption of the existing meta-learning approaches for few-shot learning is that the training and testing tasks are drawn from the same distribution, i.e., $\tau_{train} = \tau_{test}$. Then the meta-learner's objective is to minimize its expected loss over the tasks drawn from the task distribution τ_{train}. This assumption prohibits the use of meta-learning strategies for real-world applications, where training tasks with ample labeled data, and drawn from the same distribution as the test tasks are very unlikely to be available. Consider the case of a researcher or practitioner who wishes to train a prediction model for their own dataset where labeled data is very limited. It is unreasonable to assume that they would have a large corpus of labeled data for a set of related tasks in the same domain. Without this, they are not able to train effective few-shot models for their task. A more desirable option is to use the training tasks where ample training data is available, and adapt the

model to be effective on test tasks in a different domain. A possible way to tackle this problem could be through the use of domain adaptation techniques (Ganin et al., 2016; Hoffman et al., 2018) that address the domain shift between the training and test data. However, all of these approaches address the single-task scenario, i.e., $\mathcal{Y}^{train} = \mathcal{Y}^{test}$, where the training data and test data are sampled from the same task but there is a domain shift at a data-level. This is in contrast to the meta-learning setting where the training data contains multiple tasks and the goal is to learn new tasks from test data, i.e., domain shift exists at a task-level and $\mathcal{Y}^{train} \cap \mathcal{Y}^{test} = \emptyset$. As a result, these domain adaptation approaches cannot be directly applied. We show an overview of different problem settings in Table 1.

Table 1: Illustration of the differences between our work and the other three lines of work.

	Training	Test	Domain Shift
Standard Supervised Learning	Task 1	Task 1	no
Domain Adaptation	Task 1	Task 1	instance-level shift
Meta Learning	Task 1$\cdots$ Task N	Task $N+1\cdots$	no
Meta Domain Adaptation	Task 1$\cdots$ Task N	Task $N+1\cdots$	task-level shift

In order to solve the few-shot learning problem under a domain shift we propose a novel meta-learning paradigm: *Meta Domain Adaptation*. Existing meta-learning approaches for few-shot learning use only the given training data to learn a model, and as a result they do not account for any domain shift between the training tasks and the few-shot test tasks. In contrast, we assume that the model has access to the unlabeled instances in the few-shot test task (i.e., the instances that need to be labeled) prior to the training procedure, and utilize these instances for incorporating the domain-shift information. We train the model under the episodic-learning paradigm, but in each episode we aim to train a model which achieves two goals: first the model should be good at few-shot learning, and second the model should be unaffected by a possible domain shift. The first goal is achieved by updating the model based on the few-shot learning loss suffered by the model for a given episode. The second goal is achieved by an adversarial domain adaptation approach, where a mapping is used which *styles* the training task to resemble the test task. In this way, the trained model can perform few-shot predictions on the test tasks, and achieve what we term *task-level* domain adaptation.

The episodic update is done via Prototypical Network training protocol (Snell et al., 2017) (as a specific instantiation, though other approaches can be applied), where on a simulated few-shot task (where a "small" support set behaves as training data, and a query set behaves as a test data), an embedding is produced for both support and query instances. The mean of support embedding of each class is taken as the prototype, and the query instances are assigned labels based on their distance to these prototypes. Based on the loss on these query instances, the embedding function is updated. For achieving invariance to domain shift, we follow the principle of adversarial domain adaptation, but we differ from the traditional approaches in that we are performing task-level domain adaptation, whereas they performed data-level domain adaptation. The early approaches to adversarial domain adaptation aimed at obtaining a feature embedding that was invariant to both the training domain and the test domain, as well as learning a prediction model in the training domain (Ganin et al., 2016). However, these approaches possibly learnt a highly unconstrained feature embedding (particularly when the embedding was very high dimensional), and were outperformed by GAN-based approaches (often used for image translation) (Taigman et al., 2017; Zhu et al., 2017; Hoffman et al., 2018). As a result we use a mapping function to style the training tasks to resemble test tasks, and optimize it using a GAN loss. The overall framework delivers a model that uses training tasks from one distribution to meta-learn a few-shot model for a task from another distribution. We perform extensive experiments to show the efficacy of the proposed method.

2 RELATED WORK

2.1 META-LEARNING FOR FEW-SHOT LEARNING

Few-Shot Learning refers to learning a prediction model from small amount of labeled data (Fei-Fei et al., 2006; Lake et al., 2011). Early approaches used a Bayesian model (Fei-Fei et al., 2006), or hand-designed priors (Lake et al., 2015). More recently, meta-learning approaches have become extremely successful for addressing few-shot learning (Vinyals et al., 2016; Finn et al., 2017). Instead of training a model directly on the few-shot data, meta-learning approaches use a corpus of labeled data, and simulate few-shot tasks on them to "learn" how to do few-shot learning. Some approaches follow the non-parametric principle, and develop a differentiable $K-$nearest neighbour solution (Vinyals et al., 2016; Shyam et al., 2017; Snell et al., 2017). The main concept is to learn an embedding space

that is tailored for performing effective K-nearest neighbour. Oreshkin et al. (2018) extend these approaches with metric scaling to condition the embedding based on the given task. Another category of meta-learning aims to learn how to quickly adapt a model in few gradient steps for a few-shot learning task (Finn et al., 2017; Ravi & Larochelle, 2017; Li et al., 2017). These optimization based approaches aim to learn an initialization from a set of training tasks, which can be quickly adapted (e.g. one-step gradient update) when presented with a novel few-shot task. Some other approaches consider using a "memory"-based approach (Santoro et al., 2016; Munkhdalai & Yu, 2017). There have also been approaches that try to enhance meta-learning performance through use of additional information. For example, Ren et al. (2018) use unlabeled data to develop semi supervised few-shot learning. Zhou et al. (2018) use external data to generate concepts, and performs meta-learning in the concept space. However, all of these approaches assume that the training tasks and testing tasks are drawn from the same distribution ($\tau_{train} = \tau_{test}$). If there is a task-level domain shift, the above approaches will fail to perform few-shot learning on novel test tasks. Our approach of meta domain adaptation overcomes this domain shift, to perform few-shot learning on tasks in a different domain.

2.2 DOMAIN ADAPTATION

Domain adaptation has been studied extensively in recent years, particularly for computer vision applications (Saenko et al., 2010). The idea is to exploit labeled data in one domain (called source domain) to perform a prediction task in another domain (called the target domain), which does not have any labels (unsupervised domain adaptation). Most approaches employed two objectives: one to learn a prediction model in the source domain, and second to find an embedding space between the two domains that achieves domain invariance, thus making the model trained on the source domain applicable to the task in the target domain. In the era of deep learning, some early approaches aimed to align feature distribution in some embedding space using statistical measures (e.g. Maximum Mean Discrepancy) (Tzeng et al., 2014; Long et al., 2015). This was followed by several successful efforts for domain adaptation using an adversarial loss (Goodfellow et al., 2014). Ganin & Lempitsky (2015); Ganin et al. (2016) aimed to learn a feature embedding such that a domain classifier would not be able to distinguish whether the instance was drawn from the source or target domain. Consequent efforts tried to learn an embedding on the source data, from which an instance in the target domain could be reconstructed (Ghifary et al., 2016). Tzeng et al. (2017) proposed to train a model in the source domain, and using a GAN loss try to embed the target domain to the same feature distribution (using a GAN loss) as the (now fixed) source domain. Another line of work using GAN-loss is for image-to-image translation, where images in one domain are mapped to appear like images in another domain (Taigman et al., 2017; Liu et al., 2017). Most of these approaches have demonstrated application to domain adaptation tasks as well. Another recently introduced concept is cycle consistency which first maps an instance from the source to target, and then maps this synthetic instance back to the source to get back to original instance (Zhu et al., 2017; Kim et al., 2017; Yi et al., 2017), and this concept has been extended for domain adaptation as well (Hoffman et al., 2018). All of these approaches aim to solve the same task in both domains (i.e., the label space is the same in both domains). They perform domain adaptation at the data-level (and not the task level). This means that they cannot solve a new task with a different label space. In contrast our approach performs a task-level domain adaptation, and can solve new tasks.

There have been some efforts at the intersection of few-shot (and meta-learning) and domain adaptation. Motiian et al. (2017) consider supervised domain adaptation, which is similar to unsupervised domain adaptation setting, except that few labeled instances in the target domain are available. Like the previous approaches, it can not be used for a novel task with a different label space. Kang & Feng (2018)'s problem setting resembles traditional unsupervised domain adaptation, except that the model training is done using a meta-learning principle. Li et al. (2018) use meta-learning to address domain generalization where a single trained model for a given task, can be applied to any new domain with a different data distribution. They too consider solving the same task in a new domain, and do not consider the few-shot setting. A closely related work is Domain Adaptive Meta Learning (Yu et al., 2018), but their problem setting is different (which is more suitable for the problem they address: imitation learning) from what we address in this paper. They consider the scenario where a task has training data drawn from one domain and test data drawn from another domain (independent of whether it has been drawn from τ_{train} or τ_{test}). Thus, they do not violate $\tau_{train} = \tau_{test}$. In their simulated task, ample labeled training data is available for both the source and target domains. In contrast, we consider the scenario where the training tasks and test tasks are drawn from different distributions, and we have very limited labeled data for test tasks (tasks in the target domain).

3 META DOMAIN ADAPTATION

Formally, let $\mathcal{X}$ be an input space and $\mathcal{Y}$ be a discrete label space. Let $\mathcal{D}$ be a distribution over $\mathcal{X} \times \mathcal{Y}$. During meta-training, the meta-learner has access to a large labeled dataset S_{train} that typically contains thousands of instances for a large number of classes C. At the i-th iteration of *episodic* learning paradigm, the meta-learner samples a $K-$shot N-class classification task T_i from S_{train}, which contains a small "training" (assumed to have labels for all instances for this task) set $S_i^{support}$ (with K examples from each class) and a "test" (assumed to not have labels of any instances for this task) set S_i^{query}. Both $S_i^{support}$ and and S_i^{query} are assumed to be generated from an unknown sample distribution $S_i^{support} \sim \mathcal{D}_i^m$ and $S_i^{query} \sim \mathcal{D}_i$ respectively, where $m = NK$ denotes the number of instances. The sample distribution $\mathcal{D}_i$ are assumed to be generated *i.i.d.* from an unknown task distribution τ_{train}, i.e, $((\mathcal{D}^m, \mathcal{D}) \sim \tau_{train})$. It then computes conditional probabilities $p(y|\mathbf{x}, S_i^{support})$ for every point $(\mathbf{x}; y)$ in the test set S_i^{query}. Based on these predictions, meta-learner incurs a loss $L(p(y|\mathbf{x}, S_i^{support}), y)$ for each point in the current S_i^{query}. The meta-learner then back-propagates the gradient of the loss $\sum_{(x,y) \in S^{query}} L(p(y|\mathbf{x}, S^{support}), y)$ for updating the model. In the meta-testing phase, the resulting meta-learner is used to solve the novel $K-$shot N-class classification tasks, which are assumed to be generated *i.i.d.* from an unknown task distribution τ_{test}. The labeled training set and unlabeled test examples are given to the classification algorithm and the algorithm outputs class probabilities.

Existing meta-learning approaches assume that both training and testing tasks are drawn from the same distribution, i.e., $\tau_{train} = \tau_{test}$. However, this may not be the case in several real-world scenarios (i.e., $\tau_{train} \neq \tau_{test}$). Consider the case of a researcher who wants to do few-shot classification on a newly collected image recognition dataset (task drawn from τ_{test}). This researcher must now find a large amount of labeled data from which tasks can be drawn from the same task distribution (τ_{test}), failing which the researcher does not have a clear approach to acquire the relevant prior knowledge. The alternative is for the researcher to find tasks drawn from a different distribution, where ample labeled data is available, and perform task-level domain adaptation in order to learn a few-shot model suitable for their own task. Thus, we make a distinction between the task drawn from τ_{train} and τ_{test}, as $(\mathcal{D}_{train}^m, \mathcal{D}_{train}) \sim \tau_{train}$ and $(\mathcal{D}_{test}^m, \mathcal{D}_{test}) \sim \tau_{test}$. $(\mathcal{D}_{train}^m, \mathcal{D}_{train})$ and $(\mathcal{D}_{test}^m, \mathcal{D}_{test})$ may have tasks whose instances are drawn from different domains ($\mathbf{x}^{train} \in \mathcal{X}^{train}$ and $\mathbf{x}^{test} \in \mathcal{X}^{test}$ respectively), and may also have a mutually exclusive discrete label space (e.g. $\mathcal{Y}^{train} \cap \mathcal{Y}^{test} = \emptyset$). Our overall goal is to learn a meta-learner that can utilize tasks drawn from τ_{train} to acquire a good prior for few-shot learning, and overcome the task-level domain-shift in order to learn unobserved few-shot tasks drawn from τ^{test}. The general setting can be seen in Figure 1. Next, we briefly describe our proposed few-shot learning approach under task-level domain shift.

Figure 1: Problem Setting for Meta Domain Adaptation. Tasks are drawn from τ_{train}, on which meta learning is performed, such that the learner can do effective meta-testing for tasks drawn from a different distribution τ_{test}. The images are adapted from the Omniglot dataset Lake et al. (2011), where the left block has some original instances of hand-written characters in the original domain, and in the right block, we have a set of different omniglot characters (or classes) and the data is also in a different domain.

3.1 Few-Shot Learning under Domain Shift using Meta Domain Adaptation

Here, we give the overview of our proposed learning paradigm: *Meta Domain Adaptation (MDA)*. We have two objectives that need to be optimized simultaneously. First, we want to learn a feature extractor that can learn discriminative features which can be used for few-shot learning on novel tasks. Second, we want these features to be invariant to the train task distribution and test task distribution, i.e., for a task $T_i \sim (\mathcal{D}_{train}^m, \mathcal{D}_{train})$, we want to adapt it to resemble a task drawn from $(\mathcal{D}_{test}^m, \mathcal{D}_{test})$. Specifically, in the meta-learning phase, we consider a feature extractor $\mathbf{F} : \mathcal{X}^{train} \rightarrow \mathbb{R}^d$ which takes an input instance $\mathbf{x} \in \mathcal{X}^{train}$ and returns a $d-$dimensional embedding. This feature extractor in turn is a composition function $\mathbf{F}(\mathbf{x}) = \hat{\mathbf{F}}(\mathbf{G}(\mathbf{x}))$, where $\mathbf{G} : \mathcal{X}^{train} \rightarrow \mathcal{X}^{test}$, and $\hat{\mathbf{F}} : \mathcal{X}^{test} \rightarrow \mathbb{R}^d$. The feature extractor $\mathbf{F}$ is trained to learn a representation suitable for few-shot learning (by optimizing objective $\mathcal{L}_{fs}$). $\mathbf{G}$ aims to achieve task-level domain invariance by translating instances from domain $\mathcal{X}^{train}$ to instances in domain $\mathcal{X}^{test}$. $\mathbf{G}$ is trained using an adversarial loss, inspired by recent success of GAN-based (Goodfellow et al., 2014) domain adapation methods (Tzeng et al., 2017; Zhu et al., 2017; Hoffman et al., 2018). $\mathbf{G}$ (along with the corresponding discriminator D) is trained to achieve domain adaptation (by optimizing objective $\mathcal{L}_{da}$). We also use a mapping $\mathbf{G}' : \mathcal{X}^{test} \rightarrow \mathcal{X}^{train}$ to obtain cyclic consistency, wherein we try to translate generated instance $\mathbf{G}(\mathbf{x})$ to produce the original instance $\mathbf{x}$. The overall objective function is given by:

$$\min_{\hat{\mathbf{F}}, \mathbf{G}, \mathbf{G}'} \max_{D} \mathcal{L}_{fs} + \mathcal{L}_{da} \tag{1}$$

Note that $\mathcal{L}_{fs}$ is optimized using only labeled training data of tasks drawn from τ_{train} and $\mathcal{L}_{da}$ is optimized using unlabeled data of tasks drawn from both τ_{train} and τ_{test}. The overall framework can be seen in Figure 2. Next, we will describe motivation and technical details of these components.

Figure 2: Meta Domain Adaptation (MDA):The proposed method for few-shot learning under task-level domain shift using adversarial domain adaptation. A task sampled from τ_{train} in every episode. This task is used to update the parameters with the aim of achieving 2 goals: 1) It follows a Prototypical Networks learning scheme to acquire few-shot learning ability, and 2) It styles the task to appear indistinguishable from a task drawn from τ_{test}. Task-level domain invariance is achieved through the usage of a GAN loss and a cycle-consistency loss.

3.2 Few-Shot Learning

There have been several approaches for few-shot learning via meta-learning in literature (Vinyals et al., 2016; Finn et al., 2017; Snell et al., 2017). In principle, our proposed paradigm is agnostic to any of these approaches. In our work, we follow a recent state of the art approach: Prototypical Networks (Snell et al., 2017) to instantiate our framework for meta domain adaptation. For a given task $T_i \sim (\mathcal{D}_{train}^m, \mathcal{D}_{train})$, Prototypical Networks use a feature extractor $\mathbf{F} : \mathcal{X}^{train} \rightarrow \mathbb{R}^d$ to compute a $d-$dimensional embedding for each instance. Using this feature extractor, the mean vector embedding is computed for each class $\mathbf{c}_n$ for $n = 1, \dots, N$, which are the prototypes of each class:

$$\mathbf{c}_n = \frac{1}{S_n^{support}} \sum_{(\mathbf{x}_i, y_i) \in S_n^{support}} \mathbf{F}(\mathbf{x}_i) \tag{2}$$

For a given query instance $\mathbf{x}$, Prototypical Network will produce a probability distribution over the classes using:

$$p(y = n | \mathbf{x}) = \frac{\exp(-dist(\mathbf{F}(\mathbf{x}), \mathbf{c}_n))}{\sum_{(j=1)}^{N} \exp(-dist(\mathbf{F}(\mathbf{x}), \mathbf{c}_j))} \tag{3}$$

where $dist : \mathbb{R}^d \times \mathbb{R}^d \to [0, \infty)$ is a function measuring the distance between the embeddings of a query instance and a class prototype. The few-shot loss $\mathcal{L}_{fs}$ is the negative log-probability:

$$\mathcal{L}_{fs} = -\log p(y = k | \mathbf{x}) \tag{4}$$

This loss is evaluated on the query set S_i^{query}, and backpropagated to update the parameters of feature extractor $\mathbf{F}$. In this setup, $\mathbf{F}$ does not account for a domain shift between τ_{train} and τ_{test}. Consequently, we use $\mathbf{F}(\mathbf{x}) = \hat{\mathbf{F}}(\mathbf{G}(\mathbf{x}))$, where $\mathbf{G}$ will help incorporate the domain shift information.

3.3 ADVERSARIAL TASK-LEVEL DOMAIN ADAPTATION

Here, we describe how to perform task-level domain adaptation and learn the mapping parameters $\mathbf{G}$.

3.3.1 GAN LOSS AND CYCLE CONSISTENCY

We use the GAN loss (Goodfellow et al., 2014) to learn the mapping $\mathbf{G} : \mathcal{X}^{train} \to \mathcal{X}^{test}$, and its corresponding discriminator D. The objective function is denoted as:

$$\begin{aligned} \mathcal{L}_{GAN}(\mathbf{G}, D, \mathcal{X}^{train}, \mathcal{X}^{test}) \quad = \quad & \mathbb{E}_{\mathbf{x}^{test} \sim \mathcal{D}_{test}}[\log D(\mathbf{x}^{test})] + \\ & \mathbb{E}_{\mathbf{x}^{train} \sim \mathcal{D}_{train}}[\log(1 - D(\mathbf{G}(\mathbf{x}^{train})))] \end{aligned} \tag{5}$$

Here $\mathbf{G}$ tries to generate instances that appear to be similar to the instances in domain $\mathcal{X}^{test}$, and D tries to distinguish between translated instances $\mathbf{G}(\mathbf{x}^{train})$ and the real samples $\mathbf{x}^{test}$. This objective is minimized under the parameters of $\mathbf{G}$ and maximized under the parameters of D. This effectively leads to translating tasks drawn from τ_{train} to be translated such that they are indistinguishable from tasks drawn from τ_{test}.

Despite the ability of adversarial networks to produce an output indistinguishable from the test domain $\mathcal{X}^{test}$, with a large capacity, it is not inconceivable for the network to map the same set of input images in the train domain $\mathcal{X}^{train}$ to any random permutation of images in the test domain (a form of overfitting). This is because the objective is highly unconstrained. As a result, we use a cycle-consistency loss (Zhu et al., 2017; Hoffman et al., 2018), which uses a new mapping $\mathbf{G}' : \mathcal{X}^{test} \to \mathcal{X}^{train}$ which will take as input the translated instance $\mathbf{G}(\mathbf{x})$ and try to invert this function to get back the original instance, i.e., $\mathbf{x} \to \mathbf{G}(\mathbf{x}) \to \mathbf{G}'(\mathbf{G}(\mathbf{x})) \approx \mathbf{x}$. Using an L1-loss the task-cycle-consistency loss is given as:

$$\mathcal{L}_{cycle} = \mathbb{E}_{\mathbf{x}^{train} \sim \mathcal{D}_{train}}[||\mathbf{G}'(\mathbf{G}(\mathbf{x})) - \mathbf{x}||_1] \tag{6}$$

Combining the objectives from equation 5 and equation 6, we get the domain adaptation objective as $\mathcal{L}_{da} = \mathcal{L}_{GAN} + \mathcal{L}cycle$.

3.3.2 ADDITIONAL IMPROVEMENTS

The objective in equation 1 is the basic objective of our proposed framework. We also consider two advanced variants that help improve the performance of the domain adaptation. First, we consider an *identity* loss where we encourage $\mathbf{G}$ to behave like an identity mapping when it receives an instance from $\mathcal{X}^{test}$, thereby behaving as an identity function for a test task. We also introduce a reverse direction mapping to map instances from test tasks $\mathcal{X}^{test} \to X^{train}$, and a corresponding cycle loss to reconstruct back the instance in $\mathcal{X}^{test}$. All these objectives get tied together to deliver an appropriate task-level domain adaptation for a few-shot learning task. These improvements follow from state of the art image-to-image translation techniques (Taigman et al., 2017; Zhu et al., 2017).

4 EXPERIMENTS

4.1 IMPLEMENTATION AND BASELINES

Being a new problem setting, there have not been any approaches in literature directly addressing this problem. In order to be comparable, we adapt some of the techniques in Meta-Learning and Domain Adaptation, to make them suitable for our setting. We first compare the model against a *Random Guess*. We then consider popular state of the art Meta-Learning approaches *Model Agnostic Meta Learning(MAML)* (Finn et al., 2017) and *Prototypical Networks (PN)* (Snell et al., 2017). However, these approaches do not consider task-level domain shift. We construct a baseline that combines meta-learning with task-level domain shift. It is a combination of Prototypical Networks (Snell et al., 2017) with Gradient Reversal (Ganin et al., 2016), which we call *Meta-RevGrad*. Meta-RevGrad jointly optimizes PN-loss and a domain-confusion loss at the feature level where the embedded features of training tasks are made to appear like embedded features of test tasks resulting in the objective: $\lambda \mathcal{L}_{fs} + (1 - \lambda)\mathcal{L}_{RevGrad}$. Readers are refered to Ganin et al. (2016) for greater detail on $\mathcal{L}_{RevGrad}$. Here $\lambda \in (0, 1)$ is a trade-off parameter between few-shot performance and domain adaptation. We try several values of $\lambda = 0.9, 0.8, 0.7, 0.6, 0.5$ and report the best result. For our proposed method for Meta Domain Adaptation: MDA, we consider three variants: the basic version *MDA* based on equation 1; *MDA+idt*, which considers the previous objective and an identity loss (see Section 3.3.2); and *MDA+idt+revMap* which adds an additional component of (reverse) mapping testing tasks to train tasks (see Section 3.3.2).

Most of our code was implemented in PyTorch (Paszke et al., 2017) (for both baselines and proposed method). We follow the same model size and parameter setting for our models as the ones used in prior work for Prototypical Networks (Snell et al., 2017) and CycleGAN (Zhu et al., 2017). Jointly optimizing the objective in equation 1 can be very noisy (oscillating) and slow. To ease the implementation, we follow a two-step procedure for the optimization. We first optimize the objective with respect to all parameters except $\hat{\mathbf{F}}$. Then, all of these parameters are frozen, and $\hat{\mathbf{F}}$ is learned. Another issue with the GAN-based training is that the task generator lacks randomness, and always maps the same input task to the same output task (which can limit the meta-learning efficacy if the test-task domain is very diverse). To address this, during the GAN training we store intermediate models (e.g. a model saved after every epoch) and generate tasks using each of these models. This is similar to Snapshot Ensembles, where multiple models under one training cycle to increase robustness (Huang et al., 2017). With these baselines, we now discuss how we created new benchmark datasets for our problem setting, and the evaluation of the performance of our proposed method.

4.2 RESULTS ON CHARACTER RECOGNITION

We evaluate the performance using Omniglot dataset, which is popularly used for evaluating few-shot classification. The dataset (often called MNIST transpose) comprises over 1,600 hand written characters, with 20 instances of each. The dataset was further expanded by applying rotations. Inspired by a popular domain adaptation benchmark: MNIST to MNIST-M Ganin et al. (2016), we design a new benchmark, suited for the few-shot learning setting: Omniglot to Omniglot-M. Omniglot-M is constructed in the same manner as MNIST-M, i.e., by randomly blending different Omniglot characters with different color background from BSDS500 (Arbelaez et al., 2011). Following the same training-task and test-task split as previous meta-learning approaches (Santoro et al., 2016; Finn et al., 2017), we construct 4 sets: Omniglot^{train}, Omniglot^{test}, Omniglot-M^{train}, and Omniglot-M^{test}. Omniglot^{train} and Omniglot^{test} have a mutually exclusive label space. Omniglot^{train} and Omniglot-M^{train} share the same label space, and so do Omniglot^{test} and Omniglot-M^{test}. We consider two scenarios to evaluate meta domain shift: 1) Meta-training on Omniglot^{train} and meta-testing on Omniglot-M^{test}; and 2) Meta-training on Omniglot-M^{train} and meta-testing on Omniglot^{test}. For each of them, we evaluate 1-shot, 5-class and 5-shot, 5-class tasks.

The results can be seen in Table 2. We can see that the basic meta-learning approaches MAML and PN are not able to get a very good performance, as they are not able to account for the domain-shift across the tasks. Meta-RevGrad is able to occasionally offer some improvement over the basic techniques, but is outperformed by our proposed MDA method. In general, our proposed approach MDA can outperform all the baselines by a big margin. This can be observed in the case of both Omniglot → Omniglot-M and Omniglot-M → Omniglot. Similar performance trends are observed for both 1-shot and 5-shot tasks. Within the variants of MDA, we see that identity loss, and the

reverse mappings are able to offer substantial boost to the overall performance, indicating better quality task-level domain adaptation.

Table 2: Few-Shot Classification Result via Meta Domain Adaptation on held-out Omniglot characters drawn from a different domain. Best performance is in bold.

	Omniglot → Omniglot-M		Omniglot-M → Omniglot	
Method	1-shot, 5-class	5-shot, 5-class	1-shot, 5-class	5-shot, 5-class
Random	20.00%	20.00%	20.00%	20.00%
MAML	26.22%	30.46%	74.14%	83.41%
PN	27.66%	34.46%	74.23%	88.92%
Meta-RevGrad	28.29%	39.14%	65.63%	89.53%
MDA	52.29%	73.62%	74.49%	90.24%
MDA+idt	55.85%	77.50%	91.45%	98.26%
MDA+idt+revMap	**58.38%**	**79.48%**	**94.88%**	**98.76%**

4.3 RESULTS ON OFFICE-HOME DATASET

We also conducted similar experiments using Office-Home Dataset (Venkateswara et al., 2017), in particular data from two domains: Clipart and Product. There are a total of 65 classes, and we randomly split them into 45 classes for train tasks (Clipart^{train} and Product^{train}) and 20 classes for generating test tasks (Clipart^{test} and Product^{test}). All images were resized to 84x84x3, and all models were trained from scratch (pretrained models were not used). We consider two scenarios to evaluate meta domain shift: 1) Meta-training on Clipart^{train} and meta-testing on Product^{test}; and 2) Meta-training on Product^{train} and meta-testing on Clipart^{test}. For each of them, we evaluate 1-shot, 5-class and 5-shot, 5-class tasks.

The results of the evaluation can be seen in Table 3. The observations here are similar in trend to those observed for the character recognition experiments. The basic meta-learning approaches are quite poor (even though better than random). Meta-RevGrad can offer some improvement, and our proposed MDA gives an even better performance. The performance trend is fairly consistent across the two tasks, and for both 1-shot and 5-shot tasks.

Table 3: Few-Shot Classification Result via Meta Domain Adaptation on Clipart and Product Domains from Office-Home dataset. Best performance is in bold.

	Clipart → Product		Product → Clipart	
Method	1-shot, 5-class	5-shot, 5-class	1-shot, 5-class	5-shot, 5-class
Random	20.00%	20.00%	20.00%	20.00%
MAML	36.94%	48.50%	31.14%	40.22%
PN	37.36%	51.50%	31.82%	44.95%
Meta-RevGrad	37.91%	54.65%	32.18%	45.27%
MDA	39.57%	**58.98%**	32.28%	**51.03%**
MDA+idt	**39.97%**	57.49%	33.48%	50.79%
MDA+idt+revMap	39.05%	57.61%	**34.81%**	51.05%

5 CONCLUSION

In this paper we investigated a novel problem: meta domain adaptation. Existing meta learning paradigm for few-shot learning was designed under the assumption that both training tasks and test tasks were drawn from the same distribution. This may not be the case for real world applications, where researchers may not find ample labeled data to simulate training tasks to be drawn from the same distribution as their test tasks. To alleviate this, we propose a meta domain adaptation paradigm, which performs meta-learning by incorporating few-shot learning and task-level domain adaptation unified into a single meta-learner. We instantiate our few-shot model with Prototypical Networks and adopt an adversarial approach (based on GAN loss) for task level domain adaptation. We perform experiments on modified Omniglot and Office-Home datasets which have been altered for benchmarking few-shot learning under domain-shift. Our proposed technique achieves very promising results on these experiments.

REFERENCES

Pablo Arbelaez, Michael Maire, Charless Fowlkes, and Jitendra Malik. Contour detection and hierarchical image segmentation. *IEEE transactions on pattern analysis and machine intelligence*, 33(5):898–916, 2011.

Li Fei-Fei, Rob Fergus, and Pietro Perona. One-shot learning of object categories. *IEEE transactions on pattern analysis and machine intelligence*, 28(4):594–611, 2006.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pp. 1126–1135, 2017.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *International Conference on Machine Learning*, pp. 1180–1189, 2015.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, Francois Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Muhammad Ghifary, W Bastiaan Kleijn, Mengjie Zhang, David Balduzzi, and Wen Li. Deep reconstruction-classification networks for unsupervised domain adaptation. In *European Conference on Computer Vision*, pp. 597–613. Springer, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alyosha Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *ICML*, 2018.

Gao Huang, Yixuan Li, Geoff Pleiss, Zhuang Liu, John E Hopcroft, and Kilian Q Weinberger. Snapshot ensembles: Train 1, get m for free. In *ICLR*, 2017.

Bingyi Kang and Jiashi Feng. Transferable meta learning across domains. In *UAI*, 2018.

Taeksoo Kim, Moonsu Cha, Hyunsoo Kim, Jung Kwon Lee, and Jiwon Kim. Learning to discover cross-domain relations with generative adversarial networks. In *International Conference on Machine Learning*, pp. 1857–1865, 2017.

Gregory Koch, Richard Zemel, and Ruslan Salakhutdinov. Siamese neural networks for one-shot image recognition. In *ICML Deep Learning Workshop*, volume 2, 2015.

Brenden Lake, Ruslan Salakhutdinov, Jason Gross, and Joshua Tenenbaum. One shot learning of simple visual concepts. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, volume 33, 2011.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M. Hospedales. Learning to generalize: Meta-learning for domain generalization. In *AAAI Conference on Artificial Intelligence (AAAI)*, 2018.

Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. Meta-sgd: Learning to learn quickly for few shot learning. *arXiv preprint arXiv:1707.09835*, 2017.

Ming-Yu Liu, Thomas Breuel, and Jan Kautz. Unsupervised image-to-image translation networks. In *Advances in Neural Information Processing Systems*, pp. 700–708, 2017.

Mingsheng Long, Yue Cao, Jianmin Wang, and Michael I Jordan. Learning transferable features with deep adaptation networks. In *ICML*, 2015.

Saeid Motiian, Quinn Jones, Seyed Iranmanesh, and Gianfranco Doretto. Few-shot adversarial domain adaptation. In *Advances in Neural Information Processing Systems*, pp. 6670–6680, 2017.

Tsendsuren Munkhdalai and Hong Yu. Meta networks. In *International Conference on Machine Learning*, pp. 2554–2563, 2017.

Boris N Oreshkin, Alexandre Lacoste, and Pau Rodriguez. Tadam: Task dependent adaptive metric for improved few-shot learning. In *NIPS*, 2018.

Sinno Jialin Pan, Qiang Yang, et al. A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359, 2010.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *ICLR*, 2017.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. In *ICLR*, 2018.

Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *European conference on computer vision*, pp. 213–226. Springer, 2010.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International conference on machine learning*, pp. 1842–1850, 2016.

Pranav Shyam, Shubham Gupta, and Ambedkar Dukkipati. Attentive recurrent comparators. In *International Conference on Machine Learning*, pp. 3173–3181, 2017.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, pp. 4080–4090, 2017.

Yaniv Taigman, Adam Polyak, and Lior Wolf. Unsupervised cross-domain image generation. In *ICLR*, 2017.

Eric Tzeng, Judy Hoffman, Ning Zhang, Kate Saenko, and Trevor Darrell. Deep domain confusion: Maximizing for domain invariance. *arXiv preprint arXiv:1412.3474*, 2014.

Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *Computer Vision and Pattern Recognition (CVPR)*, volume 1, pp. 4, 2017.

Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *(IEEE) Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Oriol Vinyals, Charles Blundell, Tim Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, pp. 3630–3638, 2016.

Zili Yi, Hao (Richard) Zhang, Ping Tan, and Minglun Gong. Dualgan: Unsupervised dual learning for image-to-image translation. In *ICCV*, pp. 2868–2876, 2017.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? In *Advances in neural information processing systems*, pp. 3320–3328, 2014.

Tianhe Yu, Chelsea Finn, Annie Xie, Sudeep Dasari, Tianhao Zhang, Pieter Abbeel, and Sergey Levine. One-shot imitation from observing humans via domain-adaptive meta-learning. In *Robotics: Science and Systems (RSS)*, 2018.

Fengwei Zhou, Bin Wu, and Zhenguo Li. Deep meta-learning: Learning to learn in the concept space. *arXiv preprint arXiv:1802.03596*, 2018.

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *IEEE International Conference on Computer Vision*, 2017.

6 APPENDIX: DATASET CONSTRUCTION

6.1 OMNIGLOT ↔ OMNIGLOT-M

Here we show the details of the original Omniglot dataset and the statistical details, and some examples of how the characters look in a different domain. The train-test split of classes we used is the same is that used in prior work.

Domain	Split	#Classes	#Images
Omniglot	Train	4,112	82,240
	Test	688	13,760
Omniglot-M	Train	4,112	82,240
	Test	688	13,760

Figure 3: Details on the Omniglot and Omniglot-M dataset used for benchmarking Meta-Domain Adapatation.

6.2 CLIPART ↔ PRODUCT

Here we show details of Office-Home dataset and some examples of how classes look in a different domains (Clipart and Product). The train-test split of classes used by us is shown in Figure 5.

Domain	Split	#Classes	#Images
Office-Product	Train	45	3,111
	Test	20	1,328
Office-Clipart	Train	45	2,996
	Test	20	1,369

Figure 4: Details on the Clipart and Product domains used from the Office-Home Dataset.

HomeOffice train classes					HomeOffice test classes	
Alarm_Clock	Drill	Knives	Pen	Table	Batteries	Monitor
Backpack	Exit_Sign	Lamp_Shade	Pencil	Telephone	Bed	Mop
Bike	Fan	Laptop	Postit_Notes	ToothBrush	Bottle	Ruler
Calculator	File_Cabinet	Marker	Printer	Toys	Bucket	Scissors
Candles	Flowers	Mouse	Push_Pin	TV	Calendar	Screwdriver
Clipboards	Folder	Mug	Radio		Chair	Shelf
Computer	Glasses	Notebook	Refrigerator		Eraser	Sink
Couch	Helmet	Oven	Sneakers		Flipflops	Soda
Curtains	Kettle	Pan	Speaker		Fork	Trash_Can
Desk_Lamp	Keyboard	Paper_Clip	Spoon		Hammer	Webcam

Figure 5: Details split of classes used for training and testing.