GRADIENT DESCENT HAPPENS IN A TINY SUBSPACE

ABSTRACT

We show that in a variety of large-scale deep learning scenarios the gradient dynamically converges to a very small subspace after a short period of training. The subspace is spanned by a few top eigenvectors of the Hessian (equal to the number of classes in the dataset), and is mostly preserved over long periods of training. A simple argument then suggests that gradient descent may happen mostly in this subspace. We give an example of this effect in a solvable model of classification, and we comment on possible implications for optimization and learning.

1 INTRODUCTION

Stochastic gradient descent (SGD) (Robbins & Monro, 1951) and its variants are used to train nearly every large-scale machine learning model. Its ubiquity in deep learning is connected to the efficiency at which gradients can be computed (Rumelhart et al., 1985; 1986), though its success remains somewhat of a mystery due to the highly nonlinear and nonconvex nature of typical deep learning loss landscapes (Bottou et al., 2016). In an attempt to shed light on this question, this paper investigates the dynamics of the gradient and the Hessian matrix during SGD.

In a common deep learning scenario, models contain many more tunable parameters than training samples. In such "overparameterized" models, one expects generically that the loss landscape should have many *flat directions*: directions in parameter space in which the loss changes by very little or not at all (we will use "flat" colloquially to also mean approximately flat). Intuitively, this may occur because the overparameterization leads to a large redundancy in configurations that realize the same decrease in the loss after a gradient descent update.

One local way of measuring the flatness of the loss function involves the Hessian. Small or zero eigenvalues in the spectrum of the Hessian are an indication of flat directions (Hochreiter & Schmidhuber, 1997). In Sagun et al. (2016; 2017), the spectrum of the Hessian for deep learning cross-entropy losses was analyzed in depth.[1] These works showed empirically that along the optimization trajectory the spectrum separates into two components: a *bulk* component with many small eigenvalues, and a *top* component of much larger positive eigenvalues.

Correspondingly, at each point in parameter space the tangent space has two orthogonal components, which we will call the *bulk subspace* and the *top subspace*. The dimension of the top subspace is k, the number of classes in the classification objective. This result indicates the presence of many flat directions, which is consistent with the general expectation above.

In this work we present two novel observations:

- First, the gradient of the loss during training quickly moves to lie within the top subspace of the Hessian.[2] Within this subspace the gradient seems to have no special properties; its direction appears random with respect to the eigenvector basis.

- Second, the top Hessian eigenvectors evolve nontrivially but tend not to mix with the bulk eigenvectors, even over hundreds of training steps or more. In other words, the top subspace is approximately preserved over long periods of training.

---

[1] For other recent work on the spectrum of the Hessian as it relates to learning dynamics, see Pascanu et al. (2014); Dauphin et al. (2014); Chaudhari et al. (2016).

[2] This is similar to Advani & Saxe (2017), who found that a large fraction of the weights in overparameterized linear models remain untrained from their initial values (thus the gradient in those directions vanishes).

These observations are borne out across model architectures, including fully connected networks, convolutional networks, and ResNet-18, and data sets (Figures 1, 2 and Table 1).

Taken all together, despite the large number of training examples and even larger number of parameters in deep-learning models, these results seem to imply that learning may happen in a tiny, slowly-evolving subspace. Indeed, consider a gradient descent step $-\eta g$ where η is the learning rate and g the gradient. The change in the loss to leading order in η is $\delta L = -\eta \|g\|^2$. Now, let g_{top} be the projection of g onto the top subspace of the Hessian. If the gradient is mostly contained within this subspace, then doing gradient descent with g_{top} instead of g will yield a similar decrease in the loss, assuming the linear approximation is valid. Therefore, we think this may have bearing on the question of how gradient descent can traverse such a nonlinear and nonconvex landscape.

To shed light on this mechanism more directly, we also present a toy model of softmax regression trained on a mixture of Gaussians that displays all of the effects observed in the full deep-learning scenarios. We can solve the gradient descent equations exactly in a limit where the Gaussians have zero variance.[3] We find that the gradient is concentrated in the top Hessian subspace, while the bulk subspace has all zero eigenvalues. We then argue and use empirical simulations to show that including a small amount of variance will not change these conclusions, even though the bulk subspace will now contain non-zero eigenvalues.

Finally, we conclude by discussing some consequences of these observations for learning and optimization, leaving the study of improving current methods based on these ideas for future work.

2 THE GRADIENT AND THE TOP HESSIAN SUBSPACE

In this section, we present the main empirical observations of the paper. First, the gradient lies predominantly in the smaller, top subspace. Second, in many deep learning scenarios, the top and bulk Hessian subspaces are approximately preserved over long periods of training. These properties come about quickly during training.

In general, we will consider models with p parameters denoted by θ and a cross-entropy loss function $L(\theta)$. We will generally use $g(\theta) \equiv \nabla L(\theta)$ for the gradient and $H(\theta) \equiv \nabla \nabla^T L(\theta)$ for the Hessian matrix of the loss function at a point θ in parameter space. A gradient descent update with learning rate η at step t is

$$\theta^{(t+1)} = \theta^{(t)} - \eta \, g\big(\theta^{(t)}\big), \tag{1}$$

and for stochastic gradient descent we estimate the gradient using a mini-batch of examples.

2.1 THE GRADIENT CONCENTRATES IN THE TOP SUBSPACE

For a classification problem with k classes, consider a point θ in parameter space where the Hessian spectrum decomposes into a top and bulk components as discussed above. Let V_{top} be the subspace of tangent space spanned by the top k eigenvectors of the Hessian; we will call this the *top subspace*. Let V_{bulk} be the orthogonal subspace. The gradient at this point can be written as a sum $g(\theta) = g_{\text{top}} + g_{\text{bulk}}$ where g_{top} (g_{bulk}) is the orthogonal projection of g onto V_{top} (V_{bulk}). The fraction of the gradient in the top subspace is then given by $f_{\text{top}} \equiv \|g_{\text{top}}\|^2 / \|g\|^2$.

Figure 1 shows this fraction for common datasets and network architectures during the early stages of training. The fraction starts out small, but then quickly grows to a value close to 1, implying that there is an underlying dynamical mechanism that is driving the gradient into the top subspace.

For these experiments, training was carried out using vanilla stochastic gradient descent on a variety of realistic models and dataset combinations. However, measurements of the gradient and Hessian were evaluated using the entire training set. Additionally, all of our empirical results have been replicated in two independent implementations. (See Appendix A for further details on the numerical calculation.)

In the next subsection we provide evidence that this effect occurs in a broader range of models.

---

[3] Other works where the dynamics of gradient descent were analyzed directly include Fukumizu; Saxe et al. (2013); Arora et al. (2018).

Figure 1: Fraction of the gradient in the top subspace f_{top}, along with training loss and accuracy. Only the initial period of training is shown, until the fraction converges. (a,b) Fully-connected network with two hidden layers with 100 neurons each, trained on MNIST using SGD with batch size 64 and $\eta = 0.1$. (c,d) Simple convolutional network (taken from Chollet et al. (2015)) trained on CIFAR10 with the same optimizer. (e,f) ResNet-18 (He et al., 2016) trained on CIFAR10.

2.2 HESSIAN-GRADIENT OVERLAP

In this section, we consider the overlap between the gradient g and the Hessian-gradient product Hg during training, defined by

$$\text{overlap}(g, Hg) \equiv \frac{g^T Hg}{\|g\| \cdot \|Hg\|} . \tag{2}$$

The overlap takes values in the range $[-1, 1]$.

Computing the overlap is computationally much more efficient than computing the leading Hessian eigenvectors. We argue below that the overlap becomes big (of order 1) if the gradient is contained in the top subspace of the Hessian. We can use the overlap as a proxy measurement: if the overlap is large, we take that to be evidence that the gradient lives mostly in the top subspace. We measured the overlap in a range of deep learning scenarios, and the results are shown in Table 1. In these experiments we consider fully-connected networks, convolutional networks, a ResNet-18 (He et al.,

2016), as well as networks with no hidden layers, models with dropout (Srivastava et al., 2014) and batch-norm (201), models with a smooth activation function (e.g. softplus instead of ReLU), models trained using different optimization algorithms (SGD and Adam), models trained using different batch sizes and learning rates, models trained on data with random labels (as was considered by Zhang et al. (2016)), and a regression task. The overlap is large for the gradient and Hessian computed on a test set as well (except for the case where the labels are randomized). In addition, we will see below that the effect is not unique to models with cross-entropy loss; a simpler version of the same effect occurs for linear and deep regression models. In all the examples that we checked, the overlap was consistently close to one after some training.

Let us now show that the overlap tends to be large for a random vector in the top Hessian subspace. Let λ_i be the Hessian eigenvalues in the top subspace of dimension k, with corresponding eigenvectors v_i. Let w be a vector in this subspace, with coefficients w_i in the v_i basis. To get an estimate for the overlap equation 2, we choose w to be at a random vertex on the unit cube, namely choosing $w_i = \pm 1$ at random for each i. The overlap is then given by

$$\text{overlap}(w, Hw) = \frac{\sum_i^k \lambda_i w_i^2}{\sqrt{\left(\sum_j^k w_j^2\right)\left(\sum_l^k \lambda_l^2 w_l^2\right)}} = \frac{\sum_i^k \lambda_i}{\sqrt{k \sum_j^k \lambda_j^2}}. \tag{3}$$

As discussed above, in typical scenarios the spectrum will consist of k positive eigenvalues where k is the number of classes and all the rest close to zero. To get a concrete estimate ,we approximate this spectrum by taking $\lambda_i \propto i$ (a rough approximation, empirically, when $k = 10$), and take k large so that we can compute the sums approximately. This estimate for the overlap is $\sqrt{3/4} \approx 0.87$, which is in line with our empirical observations. This should compared with a generic random vector not restricted to the top subspace, which would have an overlap much less than 1.

We have verified empirically that a random unit vector w in the top Hessian subspace will have a large overlap with Hw, comparable to that of the gradient, while a random unit vector in the full parameter space has negligible overlap. Based on these observations, we will take the overlap equation 2 to be a proxy measurement for the part of the gradient that lives in the top Hessian subspace.

Table 1: Mean overlap results for various cases. FC refers to a fully-connected network with two hidden layers of 100 neurons each and ReLU activations. ConvNet refers to a convolutional network taken from Chollet et al. (2015). By default, no regularization was used. The regression data set was sampled from one period of a sine function with Gaussian noise of standard deviation 0.1. We used SGD with a mini-batch size of 64 and $\eta = 0.1$, unless otherwise specified. All models were trained for a few epochs, and the reported overlap is the mean over the last 1,000 steps of training.

DATASET	MODEL	COMMENT	MEAN OVERLAP
MNIST	Softmax		0.96
MNIST	FC	Softplus activation	0.96
MNIST	FC	$\eta = 0.01$	0.96
MNIST	FC	Batch size 256	0.97
MNIST	FC	Random labels	0.86
CIFAR10	ConvNet	Random labels	0.86
CIFAR10	ConvNet	Dropout, batch-norm, and extra dense layer	0.93
CIFAR10	ConvNet	Optimized using Adam	0.89
Regression	FC	Batch size 100	0.99

2.3 EVOLUTION OF THE TOP SUBSPACE

We now show empirically that the top Hessian subspace is approximately preserved during training. Let the top subspace $V_{\text{top}}^{(t)}$ at training step t be spanned by the top k Hessian eigenvectors $v_1^{(t)}, \ldots, v_k^{(t)}$. Let $P_{\text{top}}^{(t)}$ be the orthogonal projector onto $V_{\text{top}}^{(t)}$. We will define the overlap between a

subspace $V_{\text{top}}^{(t)}$ and a subspace $V_{\text{top}}^{(t')}$ at a later step $t' > t$ as follows.

$$\text{overlap}\left(V_{\text{top}}^{(t)}, V_{\text{top}}^{(t')}\right) \equiv \frac{1}{k}\text{Tr}\left(P_{\text{top}}^{(t)}P_{\text{top}}^{(t')}\right) = \frac{1}{k}\sum_{i=1}^{k}\left\|P_{\text{top}}^{(t)}v_i^{(t')}\right\|^2. \tag{4}$$

It is easy to verify the rightmost equality. Each element in the sum measures the fraction of a late vector $v_i^{(t')}$ that belongs to the early subspace $V_{\text{top}}^{(t)}$. Notice that the overlap of a subspace with itself is 1, while the overlap of two orthogonal subspaces vanishes. Therefore, the overlap measures by how much the top subspace changes during training.

Figure 2 shows the evolution of the subspace overlap for different starting times t_1 and future times t_2, and for classification tasks with $k = 10$ classes. For the subspace spanned by the top k eigenvectors we see that after about $t_1 = 100$ steps the overlap remains significant even when $t_2 - t_1 \gg t_1$, implying that the top subspace does not evolve much after a short period of training. By contrast, the subspace spanned by the next k eigenvectors does not have this property: Even for large t_1 the subspace overlap decays quickly in t_2.

Figure 2: Overlap of top Hessian subspaces $V_{\text{top}}^{(t_1)}$ and $V_{\text{top}}^{(t_2)}$. (a) Top 10 subspace of fully-connected network trained on MNIST. (b) Subspace spanned by the next 10 Hessian eigenvectors. (c) Top 10 subspace of convolutional network trained on CIFAR10. (d) Subspace spanned by the next 10 Hessian eigenvectors. The network architectures are the same as in Figure 1.

This means that the projector $P_{\text{top}}^{(t)}$ is only weakly dependent on time, making the notion of a "top subspace" approximately well-defined during the course of training. It is this observation, in conjunction with the observation that the gradient concentrates in this subspace at each point along the trajectory, that gives credence to the idea that gradient descent happens in a tiny subspace. (Note that this does not mean the actual top eigenvectors are similarly well-defined, indeed we observe that the individual eigenvectors within the subspace tend to rotate quickly.)

3   A TOY MODEL

In order to understand the mechanism behind the effects presented in the previous section, in this section we work out a toy example. We find this to be a useful model as it captures all of the effects we observed in realistic deep learning examples. Although the way we first set it up will be very simple, we can use it as a good starting point for doing small perturbations in which all of the realistic features are present. We will show empirically that such small perturbations do not change the qualitative results, and leave an analytic study of this perturbation theory to future work.

Consider the following 2-class classification problem with n samples $\{(x_a, y_a)\}_{a=1}^n$ with $x_a \in \mathbb{R}^d$ and labels y_a. The samples x_a are chosen from a mixture of two Gaussian distributions $\mathcal{N}(\mu_1, \sigma^2)$ and $\mathcal{N}(\mu_2, \sigma^2)$, corresponding to the two classes. The means $\mu_{1,2}$ are random unit vectors. On this data we train a model of softmax-regression, with parameters $\theta_{y,i}$ where $y = 1, 2$ is the label and $i = 1, \ldots, d$. The cross-entropy loss is given by

$$L(\theta) = -\frac{1}{n} \sum_{a=1}^n \log \left(\frac{e^{\theta_{y_a} \cdot x_a}}{\sum_y e^{\theta_y \cdot x_a}} \right) . \tag{5}$$

(Here we denote by $\theta_y \in \mathbb{R}^d$ the weights that feed into the y logit.) We will now make several simplifying approximations. First, we take the limit $\sigma^2 \to 0$ such that the samples concentrate at μ_1 and μ_2. The problem then reduces to a 2-sample learning problem. Later on we will turn on a small σ^2 and show that our qualitative results are not affected. Second, we will assume that μ_1 and μ_2 are orthogonal. Random vectors on the unit sphere S^{d-1} have overlap $d^{-1/2}$ in expectation, so this will be a good approximation at large d.

With these assumptions, it is easy to see that the loss function has $2d - 2$ flat directions. Therefore the Hessian has rank 2, its two nontrivial eigenvectors are the top subspace, and its kernel is the bulk subspace. The gradient is always contained within the top subspace.

In Appendix C, we use these assumptions to solve analytically for the optimization trajectory. At late-times in a continuous-time approximation, the solution is

$$\theta_{1,2}(t) = \tilde{\theta}_{1,2} + \tilde{\theta}' \pm \frac{\mu_1}{2} \log(\eta t + c_1) \mp \frac{\mu_2}{2} \log(\eta t + c_2), \tag{6}$$

$$g_{\theta_1}(t) = \frac{2(\mu_2 - \mu_1)}{\eta t} + \mathcal{O}(t^{-2}), \qquad g_{\theta_1}(t) = -g_{\theta_2}(t), \tag{7}$$

$$H(t) = \frac{1}{2\eta t} \begin{pmatrix} +1 & -1 \\ -1 & +1 \end{pmatrix} \otimes \left[\mu_1 \mu_1^T + \mu_2 \mu_2^T \right] + \mathcal{O}(t^{-2}). \tag{8}$$

Here η is the learning rate, c_i are arbitrary positive real numbers, $\tilde{\theta}_i \in \mathbb{R}^d$ are two arbitrary vectors orthogonal to both $\mu_{1,2}$, and $\tilde{\theta}' \in \mathbb{R}^d$ is an arbitrary vector in the space spanned by $\mu_{1,2}$.[4] Together, c_i, $\tilde{\theta}_i$, and $\tilde{\theta}'$ parameterize the $2d$-dimensional space of solutions. This structure implies the following.

1. The Hessian has two positive eigenvalues (the top subspace),[5] while the rest vanish. The top subspace is always preserved.

2. The gradient evolves during training but is always contained within the top subspace.

These properties are of course obvious from the counting of flat directions above. We have verified empirically that the following statements hold as well.[6]

- If we introduce small sample noise (*i.e.* set σ^2 to a small positive value), then the bulk of the Hessian spectrum will contain small non-zero eigenvalues (suppressed by σ^2), and the gradient will still evolve into the top subspace.

---

[4] We thank Vladimir Kirilin for pointing out a mistake in an earlier version of this paper.

[5] For the analytically simple form of model chosen here, the two eigenvalues in this top subspace are equal. However, this degeneracy can be broken in a number of ways such as adding a bias.

[6] In our experiments we used $d = 1000$, $k = 2, 5, 10$, and $\sigma = 0, 0.02$. For the means μ_i, we use random unit vectors that are not constrained to be orthogonal.

- If we add biases to our model parameters, then the degeneracy in the top subspace will be broken. During training, the gradient will become aligned with the eigenvector that has the *smaller* of the two eigenvalues.

- All these statements generalize to the case of a Gaussian mixture with $k > 2$ classes. The top Hessian subspace will consist of k positive eigenvalues. If the degeneracy is broken by including biases, there will be $k-1$ large eigenvalues and one smaller (positive) eigenvalue, with which the gradient will become aligned.

3.1 MOSTLY PRESERVED SUBSPACE, EVOLVING GRADIENT

Let us now tie these statements into a coherent picture explaining the evolution of the gradient and the Hessian.

The dynamics of the gradient within the top subspace (and specifically that fact that it aligns with the minimal eigenvector in that subspace) can be understood by the following argument. Under a single gradient descent step, the gradient evolves as

$$g^{(t+1)} = g\left(\theta^{(t)} - \eta g^{(t)}\right) = \left(1 - \eta H^{(t)}\right) g^{(t)} + \mathcal{O}(\eta^2). \tag{9}$$

If we assume the linear approximation holds, then for small enough η this evolution will drive the gradient toward the eigenvector of H that has the minimal, non-zero, eigenvalue. This seems to explain why the gradient becomes aligned with the smaller of the two eigenvectors in the top subspace when the degeneracy is broken. (It is not clear that this explanation holds at late times, where higher order terms in η may become important.)[7]

The reader may wonder why the same argument does not apply to the yet smaller (or vanishing) eigenvalues of the Hessian that are outside the top subspace. Applying the argument naively to the whole Hessian spectrum would lead to the erroneous conclusion that the gradient should in fact evolve into the bulk. Indeed, from equation 9 it may seem that the gradient is driven toward the eigenvectors of $(1 - \eta H)$ with the largest eigenvalues, and these span the bulk subspace of H.

There are two ways to see why this argument fails when applied to the whole parameter space. First, the bulk of the Hessian spectrum corresponds to exactly flat directions, and so the gradient vanishes in these directions. In other words, the loss function has a symmetry under translations in parameter space, which implies that no dynamical mechanism can drive the gradient toward those tangent vectors that point in flat directions. Second, in order to show that the gradient converges to the bulk we would have to trust the linear approximation to late times, but (as mentioned above) there is no reason to assume that higher-order corrections do not become large.

ADDING SAMPLE NOISE

Let us now discuss what happens when we introduce sample noise, setting σ^2 to a small positive value. Now, instead of two samples we have two sets of samples, each of size $n/2$, concentrated around μ_1 and μ_2. We expect that the change to the optimization trajectory will be small (namely suppressed by σ^2) because the loss function is convex, and because the change to the optimal solution is also suppressed by σ^2. The noise breaks some of the translation symmetry of the loss function, leading to fewer flat directions and to more non-zero eigenvalues in the Hessian, appearing in the bulk of the spectrum. The Hessian spectrum then resembles more closely the spectra we find in realistic examples (although the eigenvalues comprising the top subspace have a different structure). Empirically we find that the top subspace still has two large eigenvalues, and that the gradient evolves into this subspace as before. Therefore turning on noise can be treated as a small perturbation which does not alter our analytic conclusions. We leave an analytic analysis of the problem including sample noise to future work. We note that the argument involving equation 9 can again not be applied to the whole parameter space, for the same reason as before. Therefore, there is no contradiction between that equation and saying that the gradient concentrates in the top subspace.

---

[7] We mention in passing that the mechanism above holds exactly for linear regression with quadratic loss. In this setting the Hessian is constant and there are no higher-order corrections, and so the gradient will converge to the leading eigenvector of $(1 - \eta H)$.

4 DISCUSSION

We have seen that quite generally across architectures, training methods, and tasks, that during the course of training the Hessian splits into two slowly varying subspaces, and that the gradient lives in the subspace spanned by the k eigenvectors with largest eigenvalues (where k is the number of classes). The fact that learning appears to concentrate in such a small subspace with all positive Hessian eigenvalues might be a partial explanation for why deep networks train so well despite having a nonconvex loss function. The gradient essentially lives in a convex subspace, and perhaps that lets one extend the associated guarantees to regimes in which they otherwise wouldn't apply.

An essential question of future study concerns further investigation of the nature of this nearly preserved subspace. From Section 3, we understand, at least in certain examples, why the spectrum splits into two blocks as was first discovered by Sagun et al. (2016; 2017). However, we would like to further understand the hierarchy of the eigenvalues in the top subspace and how the top subspace mixes with itself in deep learning examples. We'd also like to investigate more directly the different eigenvectors in this subspace and see whether they have any transparent meaning, with an eye towards possible relevance for feature extraction.

Central to our claim about learning happening in the top subspace was the fact the decrease in the loss was predominantly due to the projection of the gradient onto this subspace. Of course, one could explicitly make this projection onto g_{top} and use that to update the parameters. By the argument given in the introduction, the loss on the current iteration will decrease by almost the same amount if the linear approximation holds. However, updating with g_{top} has a nonlinear effect on the dynamics and may, for example, alter the spectrum or cause the top subspace to unfreeze. Further study of this is warranted.

Similarly, given the nontrivial relationship between the Hessian and the gradient, a natural question is whether there are any practical applications for second-order optimization methods (see Bottou et al. (2016) or Dennis Jr & Schnabel (1996) for a review). Much of this will be the subject of future research, but we will conclude by making a few preliminary comments here.

An obvious place to start is with Newton's method (Dennis Jr & Schnabel, 1996). Newton's method consists of the parameter update $\theta^{(t+1)} = \theta^{(t)} - H^{-1}g^{(t)}$. There are a few traditional criticisms of Newton's method. The most practical is that for models as large as typical deep networks, computation of the inverse of the highly-singular Hessian acting on the gradient is infeasible. Even if one could represent the matrix, the fact that the Hessian is so ill-conditioned makes inverting it not well-defined. A second criticism of Newton's method is that it does not strictly descend, but rather moves towards critical points, whether they are minima, maxima, or saddles (Pascanu et al., 2014; Dauphin et al., 2014). These objections have apparent simple resolutions given our results. Since the gradient predominantly lives in a tiny nearly-fixed top subspace, this suggests a natural low rank approximation to Newton's method

$$\theta^{(t+1)} = \theta^{(t)} - (H_{\text{top}}^{(t)})^{-1} g_{\text{top}}^{(t)}. \tag{10}$$

Inverting the Hessian in the top subspace is well-defined and computationally simple. Furthermore, the top subspace of the Hessian has strictly positive eigenvalues, indicating that this approximation to Newton's method will descend rather then climb. Of course, Newton's method is not the only second-order path towards optima, and similar statements apply to other methods.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning.

Madhu S Advani and Andrew M Saxe. High-dimensional dynamics of generalization error in neural networks. *arXiv preprint arXiv:1710.03667*, 2017.

Sanjeev Arora, Nadav Cohen, and Elad Hazan. On the optimization of deep networks: Implicit acceleration by overparameterization. *arXiv preprint arXiv:1802.06509*, 2018.

Léon Bottou, Frank E Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *arXiv preprint arXiv:1606.04838*, 2016.

Pratik Chaudhari, Anna Choromanska, Stefano Soatto, Yann LeCun, Carlo Baldassi, Christian Borgs, Jennifer Chayes, Levent Sagun, and Riccardo Zecchina. Entropy-sgd: Biasing gradient descent into wide valleys. *arXiv preprint arXiv:1611.01838*, 2016.

François Chollet et al. Keras. `https://keras.io`, 2015.

Yann N Dauphin, Razvan Pascanu, Caglar Gulcehre, Kyunghyun Cho, Surya Ganguli, and Yoshua Bengio. Identifying and attacking the saddle point problem in high-dimensional non-convex optimization. In *Advances in Neural Information Processing Systems 27*, pp. 2933–2941. 2014.

John E Dennis Jr and Robert B Schnabel. *Numerical methods for unconstrained optimization and nonlinear equations*, volume 16. Siam, 1996.

Kenji Fukumizu. Effect of batch learning in multilayer neural networks. *Gen*, 1(04):1E–03.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Flat minima. *Neural Computation*, 9(1):1–42, 1997.

R.B. Lehoucq, D.C. Sorensen, and C. Yang. *ARPACK Users' Guide: Solution of Large-scale Eigenvalue Problems with Implicitly Restarted Arnoldi Methods*. Society for Industrial and Applied Mathematics, 1998.

Razvan Pascanu, Yann N Dauphin, Surya Ganguli, and Yoshua Bengio. On the saddle point problem for non-convex optimization. *arXiv preprint arXiv:1405.4604*, 2014.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. In *NIPS-W*, 2017.

Herbert Robbins and Sutton Monro. A stochastic approximation method. *The annals of mathematical statistics*, pp. 400–407, 1951.

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning internal representations by error propagation. Technical report, California Univ San Diego La Jolla Inst for Cognitive Science, 1985.

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *nature*, 323(6088):533, 1986.

Levent Sagun, Léon Bottou, and Yann LeCun. Eigenvalues of the hessian in deep learning: Singularity and beyond. *arXiv preprint arXiv:1611.07476*, 2016.

Levent Sagun, Utku Evci, V Ugur Guney, Yann Dauphin, and Leon Bottou. Empirical analysis of the hessian of over-parametrized neural networks. *arXiv preprint arXiv:1706.04454*, 2017.

Andrew M Saxe, James L McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *arXiv preprint arXiv:1312.6120*, 2013.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15:1929–1958, 2014.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *arXiv preprint arXiv:1611.03530*, 2016.

A   NUMERICAL METHODS

For the empirical results in this paper, we did not actually have to ever represent the Hessian. For example, to compute the top eigenvectors of the Hessian efficiently, we used the Lanczos method (Lehoucq et al., 1998), which relies on repeatedly computing the Hessian-vector product Hv for some vector v. This product can be computed in common autograd packages such as TensorFlow (Abadi et al.) or PyTorch (Paszke et al., 2017) as follows. Let v be a pre-computed numerical vector (such as the gradient). One first computes the scalar $a = \nabla L^T v$, and then takes the gradient of this expression, resulting in $\nabla a = Hv$.

B   HESSIAN SPECTRUM

Figure 3 shows the full Hessian spectrum for a small network trained on MNIST. The eigenvalues belonging to the top subspace are clearly visible.

Figure 3: Eigenvalues of the Hessian of a fully-connected network with two hidden layers, each with 32 neurons, trained on MNIST for 40 epochs.

Figure 4 shows the eigenvalue density of the right edge of the Hessian spectrum for a small two-layer network trained on CIFAR100 averaged over 200 realizations. The top subspace is clearly visible as a feature.

C   ANALYTIC EXAMPLE: DETAILED CALCULATIONS

For the reduced case of a 2-sample, 2-class problem learned using softmax-regression, the loss function can be written as

$$L(\theta) = \frac{1}{2} \log \left(1 + e^{(\theta_2 - \theta_1) \cdot \mu_1} \right) + \frac{1}{2} \log \left(1 + e^{(\theta_1 - \theta_2) \cdot \mu_2} \right) . \tag{11}$$

At a late stage of training the loss is near its zero minimum value. The exponents in equation 11 must then be small, so we can approximate

$$L(\theta) \approx \frac{1}{2} e^{(\theta_2 - \theta_1) \cdot \mu_1} + \frac{1}{2} e^{(\theta_1 - \theta_2) \cdot \mu_2} . \tag{12}$$

The loss function has $2d - 2$ flat directions,[8] and so the Hessian can have rank at most 2, and the gradient will live inside this non-trivial eigenspace. This is a simple example of the general phenomenon we observed. To gain further understanding, we solve for the optimization trajectory.

---

[8] There are d directions spanned by $\theta_1 + \theta_2$, and $d - 2$ directions spanned by directions of $\theta_1 - \theta_2$ that are orthogonal to μ_1, μ_2.

Figure 4: Histogram of eigenvalue density on the right edge of the Hessian spectrum for a fully-connected two layer (256, 256) model trained on CIFAR100 averaged over 200 realizations.

We train the model using gradient descent, and take the small learning rate limit (continuous time limit) in which the parameters $\theta(t)$ evolve as $\frac{d\theta}{dt} = -\eta \nabla L(\theta(t))$. The general solution of this equation is

$$\theta_1(t) = \tilde{\theta}_1 + \frac{\mu_1}{2} \log(\eta t + c_1) - \frac{\mu_2}{2} \log(\eta t + c_2) , \tag{13}$$

$$\theta_2(t) = \tilde{\theta}_2 - \frac{\mu_1}{2} \log(\eta t + c_1) + \frac{\mu_2}{2} \log(\eta t + c_2) . \tag{14}$$

The space of solutions has $2d - 2$ dimensions and is parameterized by the positive constants $c_{1,2}$ and by $\tilde{\theta}_{1,2}$, which are constant vectors in $\mathbb{R}^d$ orthogonal to both μ_1 and μ_2. The gradient along the optimization trajectory is then given by

$$\nabla_{\theta_1} L(t) = -\nabla_{\theta_2} L(t) = -\frac{\mu_1}{2(\eta t + c_1)} + \frac{\mu_2}{2(\eta t + c_2)} = \frac{2(\mu_2 - \mu_1)}{\eta t} + \mathcal{O}(t^{-2}) . \tag{15}$$

Notice that in the limit $t \to \infty$ the gradient approaches a vector that is independent of the solution parameters.

Next, consider the Hessian. By looking at the loss equation 11 we see there are $2d - 2$ flat directions and $2d$ parameters, implying that the Hessian has at most rank 2. Let us work out its spectrum in more detail. Decomposing the parameter space as $\mathbb{R}^k \otimes \mathbb{R}^d$, the Hessian along the optimization trajectory is given by

$$H = \begin{pmatrix} +1 & -1 \\ -1 & +1 \end{pmatrix} \otimes \left[\frac{\mu_1 \mu_1^T}{2(\eta t + c_1)} + \frac{\mu_2 \mu_2^T}{2(\eta t + c_2)} \right]$$

$$= \frac{1}{2\eta t} \begin{pmatrix} +1 & -1 \\ -1 & +1 \end{pmatrix} \otimes \left[\mu_1 \mu_1^T + \mu_2 \mu_2^T \right] + \mathcal{O}(t^{-2}) . \tag{16}$$

At leading order in the limit $t \to \infty$ we find two non-trivial eigenvectors, given by

$$\begin{pmatrix} \mu_1 \\ -\mu_1 \end{pmatrix} \quad \text{and} \quad \begin{pmatrix} \mu_2 \\ -\mu_2 \end{pmatrix} , \tag{17}$$

both with eigenvalue $(\eta t)^{-1}$. The remaining eigenvalues all vanish. The top Hessian subspace is fixed, and the gradient is contained within this space.