FAIR RESOURCE ALLOCATION IN FEDERATED LEARNING

ABSTRACT

Federated learning involves training statistical models in massive, heterogeneous networks. Naively minimizing an aggregate loss function in such a network may disproportionately advantage or disadvantage some of the devices. In this work, we propose q-Fair Federated Learning (q-FFL), a novel optimization objective inspired by fair resource allocation in wireless networks that encourages a more fair (i.e., more uniform) accuracy distribution across devices in federated networks. To solve q-FFL, we devise a communication-efficient method, q-FedAvg, that is suited to federated networks. We validate both the effectiveness of q-FFL and the efficiency of q-FedAvg on a suite of federated datasets with both convex and non-convex models, and show that q-FFL (along with q-FedAvg) outperforms existing baselines in terms of the resulting fairness, flexibility, and efficiency.

1 INTRODUCTION

Federated learning is an attractive paradigm for fitting a model to data generated by, and residing on, a network of remote devices (McMahan et al., 2017). Unfortunately, naively minimizing an aggregate loss in a large network may disproportionately advantage or disadvantage the model performance on some of the devices. Indeed, although the accuracy may be high on average, there is no accuracy guarantee for individual devices in the network. This is exacerbated by the fact that the data are often heterogeneous in federated networks both in terms of size and distribution, and model performance can thus vary widely. In this work, we therefore ask: Can we devise an efficient federated optimization method to encourage a *more fair (i.e., more uniform) distribution* of the model performance across devices in federated networks?

There has been tremendous recent interest in developing fair methods for machine learning (see, e.g., Cotter et al., 2019; Dwork et al., 2012). However, current approaches do not adequately address concerns in the federated setting. For example, a common definition in the fairness literature is to enforce *accuracy parity* between protected groups[1] (Zafar et al., 2017a). For devices in massive federated networks, however, it does not make sense for the accuracy to be *identical* on each device given the significant variability of data in the network. Recent work has taken a step towards addressing this by introducing *good-intent fairness*, in which the goal is instead to ensure that the training procedure does not overfit a model to any one device at the expense of another (Mohri et al., 2019). However, the proposed objective is rigid in the sense that it only maximizes the performance of the worst performing device/group, and has only be tested in small networks (for 2-3 devices). In realistic federated learning applications, it is natural to instead seek methods that can flexibly trade-off between overall performance and fairness in the network, and can be implemented at scale across hundreds to millions of devices.

In this work, we propose q-FFL, a novel optimization objective that addresses fairness issues in federated learning. Inspired by work in fair resource allocation for wireless networks, q-FFL minimizes an aggregate *reweighted* loss parameterized by q such that the devices with higher loss are given higher relative weight. We show that this objective encourages a device-level definition of fairness in the federated setting, which generalizes standard accuracy parity by measuring the

---

[1]While fairness is typically concerned with performance between "groups", we define fairness in the federated setting at a more granular scale in terms of the devices in the network. We note that devices may naturally combine to form groups, and thus use these terms interchangeably in the context of prior work.

degree of uniformity in performance across devices. Adaptively minimizing such a modified objective results in a flexible framework in which the objective can be tuned depending on the desired amount of fairness. In addition, we propose a lightweight and scalable distributed method, q-FedAvg, to solve q-FFL in massive federated networks. Our distributed method carefully accounts for important characteristics of the federated setting such as communication-efficiency and low participation of devices (Bonawitz et al., 2019; McMahan et al., 2017). Through extensive experiments on federated datasets with both convex and non-convex models, we demonstrate the fairness and flexibility of q-FFL and the efficiency of q-FedAvg compared with existing baselines. In terms of fairness, q-FFL is able to reduce the variance of accuracies across devices by 45% on average while maintaining the same overall average accuracy. In terms of efficiency, our distributed method, q-FedAvg, is capable of solving the proposed objective orders-of-magnitude more quickly than other baselines.

2 RELATED WORK

Fairness in Resource Allocation. Fair resource allocation has been extensively studied in fields such as network management (Ee & Bajcsy, 2004; Hahne, 1991; Kelly et al., 1998; Neely et al., 2008) and wireless communications (Eryilmaz & Srikant, 2006; Nandagopal et al., 2000; Sanjabi et al., 2014; Shi et al., 2014). In these contexts, the problem is defined as allocating a scarce shared resource, e.g., communication time or power, among many users. In these cases, directly maximizing utilities such as total throughput may lead to unfair allocations where some users receive poor service. As a service provider, it is important to improve the quality of service for all users while maintaining overall throughput. For this reason, several popular fairness measurements have been proposed to balance between fairness and total throughput, including Jain's index (Jain et al., 1984), entropy (Rényi et al., 1961), max-min/min-max fairness (Radunovic & Le Boudec, 2007), and proportional fairness (Kelly, 1997). A unified framework is captured through α-fairness (Lan et al., 2010; Mo & Walrand, 2000), in which the network manager can tune the emphasis on fairness by changing a single parameter, α.

To draw an analogy between federated learning and the problem of resource allocation, one can think of the global model as a resource that is meant to serve the users (or devices). In this sense, it is natural to ask similar questions about the fairness of the service that users receive and use similar tools to promote fairness. Despite this, we are unaware of any works that use α-fairness from resource allocation to modify objectives in machine learning. Inspired by the α-fairness metric, we propose a similarly modified objective, q-Fair Federated Learning (q-FFL), to encourage a more fair accuracy distribution across devices in the context of federated training. Similar to the α-fairness metric, our q-FFL objective is flexible enough to enable trade-offs between fairness and other traditional metrics such as accuracy by changing the parameter q. In Section 4, we show empirically that the use of q-FFL as an objective in federated learning enables a more uniform accuracy distribution across devices—significantly reducing variance while retaining the average accuracy.

Fairness in Machine Learning. Fairness is a broad topic that has received much attention in the machine learning community, though the goals often differ from that described in this work. Indeed, *fairness* in machine learning is typically defined as the protection of some specific attribute(s). Two common approaches are to preprocess the data to remove information about the protected attribute, or to post-process the model by adjusting the prediction threshold after classifiers are trained (Feldman, 2015; Hardt et al., 2016). Another set of works optimize an objective subject to some fairness constraints during training time (Agarwal et al., 2018; Cotter et al., 2019; Hashimoto et al., 2018; Woodworth et al., 2017; Zafar et al., 2017a;b; Dwork et al., 2012). Our work also enforces fairness during training, although we define fairness as the uniformity of the accuracy distribution across devices in federated learning (Section 3), as opposed to the protection of a specific attribute. Although some works define accuracy parity to enforce equal error rates among specific groups as a notion of fairness (Zafar et al., 2017a; Cotter et al., 2019), devices in federated networks may not be partitioned by protected attributes, and our goal is not to optimize for identical accuracy across all devices. Cotter et al. (2019) use a notion of 'minimum accuracy', which is conceptually similar to our goal. However, it requires one optimization constraint for each device, which would result in hundreds to millions of constraints in federated networks.

In federated settings, Mohri et al. (2019) recently proposed a minimax optimization scheme, Agnostic Federated Learning (AFL), which optimizes for the performance of the single worst device. This method has only been applied at small scales (for a handful of devices). Compared to AFL, our

proposed objective is more flexible as it can be tuned based on the desired amount of fairness; `AFL` can in fact be seen as a special case of our objective, q-`FFL`, with large enough q. In Section 4, we demonstrate that the flexibility of our objective results in significantly better accuracy vs. fairness trade-offs than `AFL`, and that q-`FFL` can also be solved at scale more efficiently.

Federated Optimization. Federated learning faces challenges such as expensive communication, variability in systems environments in terms of hardware or network connection, and non-identically distributed data across devices (Li et al., 2019). In order to reduce communication and tolerate heterogeneity, optimization methods must be developed to allow for local updating and low participation among devices (McMahan et al., 2017; Smith et al., 2017). We incorporate these key ingredients when designing methods to solve our q-`FFL` objective efficiently in the federated setting (Section 3.3).

3 FAIR FEDERATED LEARNING

In this section, we first formally define the classical federated learning objective and methods, and introduce our proposed notion of fairness (Section 3.1). We then introduce q-`FFL`, a novel objective that encourages a more fair (uniform) accuracy distribution across all devices (Section 3.2). Finally, in Section 3.3, we describe q-`FedAvg`, an efficient distributed method to solve the q-`FFL` objective in federated settings.

3.1 PRELIMINARIES: FEDERATED LEARNING, FEDAVG, AND FAIRNESS

Federated learning algorithms involve hundreds to millions of remote devices learning locally on their device-generated data and communicating with a central server periodically to reach a global consensus. In particular, the goal is typically to minimize:

$$\min_w f(w) = \sum_{k=1}^m p_k F_k(w) \,, \tag{1}$$

where m is the total number of devices, $p_k \geq 0$, and $\sum_k p_k = 1$. The local objective F_k's can be defined by empirical risks over local data, i.e., $F_k(w) = \frac{1}{n_k} \sum_{j_k=1}^{n_k} l_{j_k}(w)$, where n_k is the number of samples available locally. We can set p_k to be $\frac{n_k}{n}$, where $n = \sum_k n_k$ is the total number of samples to fit a traditional empirical risk minimization-type objective over the entire dataset.

Most prior work solves (1) by sampling a subset of devices with probabilities p_k at each round, and then running an optimizer such as stochastic gradient descent (SGD) for a variable number of iterations locally on each device. These *local updating methods* enable flexible and efficient communication compared to traditional mini-batch methods, which would simply calculate a subset of the gradients (Stich, 2019; Wang & Joshi, 2018; Woodworth et al., 2018; Yu et al., 2019). `FedAvg` (McMahan et al., 2017), summarized in Algorithm 2 in Appendix D.1, is one of the leading methods to solve (1) in non-convex settings. The method runs simply by having each selected device apply E epochs of SGD locally and then averaging the resulting local models.

Unfortunately, solving problem (1) in this manner can implicitly introduce highly variable performance between different devices. For instance, the learned model may be biased towards devices with larger numbers of data points, or (if weighting devices equally), to commonly occurring devices. More formally, we define our desired fairness criteria for federated learning below.

Definition 1 (*Fairness of performance distribution*). For trained models w and $\tilde{w}$, we informally say that model w provides a more *fair* solution to the federated learning objective (1) than model $\tilde{w}$ if the performance of model w on the m devices, $\{a_1, \ldots a_m\}$, is more *uniform* than the performance of model $\tilde{w}$ on the m devices.

In this work, we take 'performance', a_k, to be the *testing accuracy* of applying the trained model w on the test data for device k. There are many ways to *mathematically* evaluate the *uniformity* of the performance. In this work, we mainly use the *variance* of the performance distribution as a measure of uniformity. However, we also explore other uniformity metrics, both empirically and theoretically, in Appendix A.1. We note that a tension exists between the *fairness/uniformity* of the final testing accuracy and the *average* testing accuracy across devices. In general, our goal is to impose more *fairness/uniformity* while maintaining the same (or similar) average accuracy.

Remark 2 (Connections to other fairness definitions). *Definition 1 targets device-level fairness, which has finer granularity than the classical attribute-level fairness such as accuracy parity (Zafar et al., 2017a). We note that in certain cases where devices can be naturally clustered into groups with specific attributes, our definition can be seen as a relaxed version of accuracy parity, in that we optimize for similar but not necessarily identical performance across devices.*

3.2 THE OBJECTIVE: q-FAIR FEDERATED LEARNING (q-FFL)

A natural idea to achieve fairness as defined in (1) would be to *reweight* the objective—assigning higher weights to devices with poor performance, so that the distribution of accuracies in the network shifts towards more uniformity. Note that this reweighting must be done dynamically, as the performance of the devices depends on the model being trained, which cannot be evaluated a priori. Drawing inspiration from α-fairness, a utility function used in fair resource allocation in wireless networks, we propose the following objective. For given local non-negative cost functions F_k and parameter $q > 0$, we define the q-Fair Federated Learning (q-FFL) objective as:

$$\min_w \ f_q(w) = \sum_{k=1}^{m} \frac{p_k}{q+1} F_k^{q+1}(w) \,, \tag{2}$$

where $F_k^{q+1}(\cdot)$ denotes $F_k(\cdot)$ to the power of $(q+1)$. Here, q is a parameter that tunes the amount of fairness we wish to impose. Setting $q = 0$ does not encourage fairness beyond the classical federated learning objective (1). A larger q means that we emphasize devices with higher local empirical losses, $F_k(w)$, thus imposing more uniformity to the training accuracy distribution and potentially inducing fairness in accordance with Definition 1. Setting $f_q(w)$ with a large enough q reduces to classical max-min fairness (Mohri et al., 2019), as the device with the worst performance (largest loss) will dominate the objective. We note that while the $(q+1)$ term in the denominator in (2) may be absorbed in p_k, we include it as it is standard in the α-fairness literature and helps to ease notation. For completeness, we provide additional background on α-fairness in Appendix C.

As mentioned previously, q-FFL generalizes prior work in fair federated learning (AFL) (Mohri et al., 2019), allowing for a flexible trade-off between fairness and accuracy as parameterized by q. In our theoretical analysis (Appendix A), we provide generalization bounds of q-FFL that generalize the learning bounds of the AFL objective. Moreover, based on our fairness definition (Definition 1), we theoretically explore how q-FFL results in more *uniform* accuracy distributions with increasing q. Our results suggest that q-FFL is able to impose 'uniformity' of the test accuracy distribution in terms of various metrics such as variance and other geometric and information-theoretic measures.

In our experiments (Section 4.2), on both convex and non-convex models, we show that using the q-FFL objective, we can obtain fairer/more uniform solutions for federated datasets in terms of both the training and testing accuracy distributions.

3.3 THE SOLVER: FEDAVG-STYLE q-FAIR FEDERATED LEARNING (q-FEDAVG)

In developing a functional approach for fair federated learning, it is critical to consider not only what objective to solve but also how to solve such an objective efficiently in a massive distributed network. In this section, we provide methods to solve q-FFL. We start with a simpler method, q-FedSGD, to illustrate our main techniques. We then provide a more efficient counterpart, q-FedAvg, by considering local updating schemes. Our proposed methods closely mirror traditional distributed optimization methods—mini-batch SGD and federated averaging (FedAvg)—but with step-sizes and subproblems carefully chosen in accordance with the q-FFL problem (2).

Achieving variable levels of fairness: tuning q. In devising a method to solve q-FFL (2), we begin by noting that it is crucial to first determine how to set q. In practice, q can be tuned based on the desired amount of fairness (with larger q inducing more fairness). As we describe in our experiments (Section 4.2), it is therefore common to train a *family of objectives* for different q values so that a practitioner can explore the trade-off between accuracy and fairness for the application at hand.

One concern with solving such a family of objectives is that it requires step-size tuning for every value of q. In particular, in gradient-based methods, the step-size inversely depends on the Lipschitz constant of the function's gradient, which will change as we change q. This can quickly cause the search space to explode. To overcome this issue, we propose estimating the local Lipschitz constant for the

---

Algorithm 1 q-`FedAvg`

1: **Input:** $K, E, T, q, 1/L, \eta, w^0, p_k, k = 1, \cdots, m$
2: **for** $t = 0, \cdots, T-1$ **do**
3:      Server selects a subset S_t of K devices at random (each device k is chosen with prob. p_k)
4:      Server sends w^t to all selected devices
5:      Each selected device k updates w^t for E epochs of SGD on F_k with step-size η to obtain $\bar{w}_k^{t+1}$
6:      Each selected device k computes:
$$\Delta w_k^t = w^t - \bar{w}_k^{t+1}$$
$$\Delta_k^t = F_k^q(w^t) \Delta w_k^t$$
$$h_k^t = \frac{q}{L} F_k^{q-1}(w^t) \|\Delta w_k^t\|^2 + F_k^q(w^t)$$

7:      Each selected device k sends Δ_k^t and h_k^t back to the server
8:      Server updates w^{t+1} as:
$$w^{t+1} = w^t - \frac{\sum_{k \in S_t} \Delta_k^t}{\sum_{k \in S_t} h_k^t}$$

9: **end for**

---

family of q-`FFL` objectives by using the Lipschitz constant we infer by tuning the step-size (via grid search) on just one q (e.g., $q = 0$). Formally, if a non-negative function $f(\cdot)$ has a Lipschitz gradient with constant L, then for any $q \geq 0$ and at any point w, $L_q(w) = Lf(w)^q + qf(w)^{q-1}\|\nabla f(w)\|^2$ is upper-bound for the Lipschitz constant of the gradient of $\frac{1}{q+1} f^{q+1}(\cdot)$ at point w. We prove this in Lemma 12, Appendix B. We can use the step-size $1/L_q(w)$ for any $q > 0$ after we estimate L once on $q = 0$, as described below.

A first approach: q-**FedSGD.** Our first fair federated learning method, q-`FedSGD`, is an extension of the well-known federated mini-batch SGD (`FedSGD`) method (McMahan et al., 2017). q-`FedSGD` uses a dynamic step-size instead of the normal fixed step-size of `FedSGD`. Based on Lemma 12, for each local device k, the upper-bound of the local Lipschitz constant is $LF_k(w)^q + qF_k(w)^{q-1}\|\nabla F_k(w)\|^2$. In each step of q-`FedSGD`, ∇F_k and F_k on each selected device k are computed at the current iterate and communicated to the central node. This information is used to compute the step-sizes (weights) for combining the updates from each device. The details are summarized in Algorithm 3, Appendix D.2. Note that q-`FedSGD` is reduced to `FedSGD` when $q = 0$. It is also important to note that to run q-`FedSGD` with different values of q, we only need to estimate L once by tuning the step-size on $q = 0$ and can then reuse it for all values of $q > 0$.

Improving communication-efficiency: q-**FedAvg.** In federated settings, communication-efficient schemes using *local* stochastic solvers (such as `FedAvg`) have been shown to significantly improve convergence speed (McMahan et al., 2017). However, when $q > 0$, the F_k^{q+1} term is not an empirical average of the loss over all local samples due to the $q + 1$ exponent, preventing the use of local SGD as in `FedAvg`. To address this, we propose to generalize `FedAvg` for $q > 0$ using a more sophisticated dynamic weighted averaging scheme. The weights (step-sizes) are inferred from the upper bound of the local Lipschitz constants of the gradients of F_k^{q+1}, similar to q-`FedSGD`. To extend the local updating technique of `FedAvg` to the q-`FFL` objective (2), we propose a heuristic where we replace the gradient ∇F_k in the q-`FedSGD` steps with the local updates that are obtained by running SGD locally on device k. Similarly, q-`FedAvg` is reduced to `FedAvg` when $q = 0$. We provide additional details on q-`FedAvg` in Algorithm 1. As we will see empirically, q-`FedAvg` can solve q-`FFL` objective much more efficiently than q-`FedSGD` due to the local updating heuristic.

4 EVALUATION

We now present empirical results of the proposed objective, q-`FFL`, and proposed methods, q-`FedAvg` and q-`FedSGD`. We describe our experimental setup in Section 4.1. We then demonstrate the improved fairness of q-`FFL` in Section 4.2, and compare q-`FFL` with several baseline fairness objectives in Section 4.3. Finally, we show the efficiency of q-`FedAvg` compared with q-`FedSGD` in Section 4.4. We provide an anonymized version of our code for easy reproducibility.

Figure 1: q-FFL leads to fairer test accuracy distributions. While the average accuracy remains almost identical (see Table 1), by setting $q > 0$, the distributions shift towards the center as low accuracies increase at the cost of potentially decreasing high accuracies on some devices. Setting $q = 0$ corresponds to the original objective (1). The selected q values for $q > 0$ on the four datasets, as well as distribution statistics, are also shown in Table 1.

Table 1: Statistics of the test accuracy distribution for q-FFL. By setting $q > 0$, the accuracy of the worst 10% devices is increased at the cost of possibly decreasing the accuracy of the best 10% devices. While the average accuracy remains similar, the variance of the final accuracy distribution decreases significantly. We provide full results of other uniformity measurements (including variance) in Table 4, Appendix F.1, and show that q-FFL encourages more uniform distributions under all metrics.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance
Synthetic	$q = 0$	$80.8 \pm .9$	18.8 ± 5.0	100.0 ± 0.0	724 ± 72
	$q = 1$	79.0 ± 1.2	$\mathbf{31.1} \pm 1.8$	100.0 ± 0.0	$\mathbf{472} \pm 14$
Vehicle	$q = 0$	$87.3 \pm .5$	43.0 ± 1.0	$\mathbf{95.7} \pm 1.0$	291 ± 18
	$q = 5$	$87.7 \pm .7$	$\mathbf{69.9} \pm .6$	$94.0 \pm .9$	$\mathbf{48} \pm 5$
Sent140	$q = 0$	65.1 ± 4.8	15.9 ± 4.9	100.0 ± 0.0	697 ± 132
	$q = 1$	$66.5 \pm .2$	$\mathbf{23.0} \pm 1.4$	100.0 ± 0.0	$\mathbf{509} \pm 30$
Shakespeare	$q = 0$	$51.1 \pm .3$	39.7 ± 2.8	$\mathbf{72.9} \pm 6.7$	82 ± 41
	$q = .001$	$52.1 \pm .3$	$\mathbf{42.1} \pm 2.1$	69.0 ± 4.4	$\mathbf{54} \pm 27$

4.1 EXPERIMENTAL SETUP

Federated datasets. We explore a suite of federated datasets using both convex and non-convex models in our experiments. The datasets are curated from prior work in federated learning (McMahan et al., 2017; Smith et al., 2017; Li et al., 2018; Mohri et al., 2019) as well as recent federated learning benchmarks (Caldas et al., 2018). In particular, we study: (1) a synthetic dataset using a linear regression classifier, (2) a vehicle dataset collected from a distributed sensor network (Duarte & Hu, 2004) with a linear SVM for binary classification, (3) tweets data curated from Sentiment140 (Go et al., 2009) (Sent140) with an LSTM classifier for text sentiment analysis, and (4) text data built from *The Complete Works of William Shakespeare* (McMahan et al., 2017) and an RNN to predict the next character. When comparing with AFL, we use the two small benchmark datasets (Fashion MNIST and Adult) studied in Mohri et al. (2019). Full dataset details are given in Appendix E.1.

Implementation. We implement all code in Tensorflow (Abadi et al., 2016), simulating a federated network with one server and m devices, where m is determined by the number of partitions in the dataset (Appendix E.1). We provide full details (including all hyperparameter values) in Appendix E.2.

4.2 FAIRNESS OF q-FFL

In our first experiments, we verify that the proposed objective q-FFL leads to more fair solutions (Definition 1) for federated data. In Figure 1, we compare the final testing accuracy distributions of two objectives ($q = 0$ and a tuned value of $q > 0$) averaged across 5 random shuffles of each dataset. We observe that while the average testing accuracy remains fairly consistent, the objectives with $q > 0$ result in more centered (i.e., fair) testing accuracy distributions with lower variance. In particular, *while maintaining roughly the same average accuracy, q-FFL reduces the variance of accuracies across all devices by 45% on average.* We further report the worst and best 10% testing accuracies and the variance of the final accuracy distributions in Table 1. Comparing $q = 0$ and $q > 0$, we

see that the average testing accuracy remains almost unchanged with the proposed objective despite significant reductions in variance. We report full results on all uniformity measurements (including variance) in Table 4 in the appendix, and show that q-FFL encourages more uniform accuracies under other metrics as well. We observe similar results on training accuracy distributions in Figure 4 and Table 5, Appendix F. In Table 1, the average accuracy is with respect to all data points, not all devices; however, we observe similar results with respect to devices, as shown in Table 6, Appendix F.

Choosing q. As discussed in Section 3.3, a natural question is to determine how q should be tuned in the q-FFL objective. Our framework is flexible in that it allows one to choose q to tradeoff between fairness/uniformity and average accuracy. We empirically show that there are a family of q's that can result in variable levels of fairness (and accuracy) on synthetic data in Table 10, Appendix F. In general, this value can be tuned based on the data/application at hand and the desired amount of fairness. Another reasonable approach in practice would be to run Algorithm 1 with multiple q's in parallel to obtain multiple final global models, and then select amongst these based on performance (e.g., accuracy) on the validation data. Rather than using just one optimal q for all devices, for example, each device could pick a device-specific model based on their validation data. We show additional performance improvements with this device-specific strategy in Table 11 in Appendix F. Finally, we note that one potential issue is that increasing the value of q may slow the speed of convergence. However, for values of q that result in more fair results on our datasets, we do not observe significant convergence slowdown, as shown in Figure 7, Appendix F.

4.3 COMPARISON WITH OTHER OBJECTIVES

Next, we compare q-FFL with other objectives that are likely to impose fairness in federated networks. One heuristic is to weight each data point equally, which reduces to the original objective in (1) (i.e., q-FFL with $q = 0$) and has been investigated in Section 4.2. We additionally compare with two alternatives: weighting *devices equally* when sampling devices, and weighting *devices adversarially*, namely, optimizing for the worst-performing device, as proposed in Mohri et al. (2019).

Weighting devices equally. We compare q-FFL with uniform sampling schemes and report testing accuracy in Figure 2. A table with the final accuracies and three fairness metrics is given in the appendix in Table 8. While the 'weighting each device equally' heuristic tends to outperform our method in *training* accuracy distributions (Figure 5 and Table 7 in Appendix F), we see that our method produces more fair solutions in terms of *testing* accuracies. One explanation for this is that uniform sampling is a static method and can easily overfit to devices with very few data points, whereas q-FFL will put less weight on a device once its loss becomes small, potentially providing better generalization performance due to its dynamic nature.

Figure 2: q-FFL ($q > 0$) compared with uniform sampling. In terms of testing accuracy, our objective produces more fair solutions than uniform sampling. Distribution statistics are provided in Table 8 in the appendix. q-FFL achieves similar average accuracies and more fair solutions.

Weighting devices adversarially. We further compare with AFL (Mohri et al., 2019), which is the only work we are aware of that aims to address fairness issues in federated learning. We implement a non-stochastic version of AFL where all devices are selected and updated each round, and perform grid search on the AFL hyperparameters, γ_w and γ_λ. In order to devise a setup that is as favorable to AFL as possible, we modify Algorithm 1 by sampling all devices and letting each of them run gradient descent at each round. We use the same small datasets (Adult and subsampled Fashion MNIST) and the same logistic regression model as in Mohri et al. (2019). Full details of the implementation and hyperparameters (e.g., values of q_1 and q_2) are provided in Appendix E.2.3. We note that, as opposed to AFL, q-FFL is flexible depending on the amount of fairness desired, with larger q leading to more accuracy uniformity. As discussed, q-FFL generalizes AFL in this regard, as AFL is equivalent to

Table 2: Our objective compared with weighing devices adversarially (`AFL` (Mohri et al., 2019)). In order to be favorable to `AFL`, we use the two small, well-behaved datasets studied in (Mohri et al., 2019). q-`FFL` ($q > 0$) outperforms `AFL` on the worst testing accuracy of both datasets. The tunable parameter q controls how much fairness we would like to achieve—larger q induces less variance. Each accuracy is averaged across 5 runs with different random initializations.

	Adult			**Fashion MNIST**			
Objectives	average (%)	PhD (%)	non-PhD (%)	average (%)	shirt (%)	pullover (%)	T-shirt (%)
q-FFL, $q=0$	$83.2_{\pm.1}$	$69.9_{\pm.4}$	$\mathbf{83.3}_{\pm.1}$	$78.8_{\pm.2}$	$66.0_{\pm.7}$	$84.5_{\pm.8}$	$\mathbf{85.9}_{\pm.7}$
AFL	$82.5_{\pm.5}$	$73.0_{\pm2.2}$	$82.6_{\pm.5}$	$77.8_{\pm1.2}$	$71.4_{\pm4.2}$	$81.0_{\pm3.6}$	$82.1_{\pm3.9}$
q-FFL, $q_1{>}0$	$82.6_{\pm.1}$	$\mathbf{74.1}_{\pm.6}$	$82.7_{\pm.1}$	$77.8_{\pm.2}$	$\mathbf{74.2}_{\pm.3}$	$78.9_{\pm.4}$	$80.4_{\pm.6}$
q-FFL, $q_2{>}q_1$	$82.3_{\pm.1}$	$\mathbf{74.4}_{\pm.9}$	$82.4_{\pm.1}$	$77.1_{\pm.4}$	$\mathbf{74.7}_{\pm.9}$	$77.9_{\pm.4}$	$78.7_{\pm.6}$

q-`FFL` with a large enough q. In Table 2, we observe that q-`FFL` can in fact achieve higher testing accuracy than `AFL` on the device with the worst performance (i.e., the problem that the `AFL` was designed to solve) with appropriate q. This also indicates that q-`FFL` obtains the most fair solutions in certain cases. We also observe that q-`FFL` converges faster in terms of communication rounds compared with `AFL` to obtain similar performance (Appendix F), which we speculate is due to the non-smoothness of the `AFL` objective.

4.4 EFFICIENCY OF THE METHOD q-FEDAVG

Figure 3: For a fixed objective (i.e., q-`FFL` with the same q), the convergence of q-`FedAvg` (Alg.1), q-`FedSGD` (Alg.3), and `FedSGD`. For q-`FedAvg` and q-`FedSGD`, we tune a best step-size on $q = 0$ and apply that step-size to solve q-`FFL` with $q > 0$. For q-`FedSGD`, we tune the step-size directly. We observe that (1) q-`FedAvg` converges faster in terms of communication rounds; (2) our proposed q-`FedSGD` solver with a dynamic step-size achieves similar convergence behavior compared with a best-tuned `FedSGD`.

Finally, we show the efficiency of our proposed distributed solver, q-`FedAvg`, by comparing Algorithm 1 with its non-local-updating baseline q-`FedSGD` (Algorithm 3) to solve the same objective (same $q > 0$ as in Table 1). At each communication round, we have each method perform the same amount of computation, with q-`FedAvg` running one epoch of local updates on each selected device while q-`FedSGD` runs gradient descent with the local training data. In Figure 3, q-`FedAvg` achieves potentially orders-of-magnitude faster convergence than q-`FedSGD` in terms of communication rounds (Shakespeare). To demonstrate the optimality of our dynamic step-size strategy in terms of solving q-`FFL`, we also compare our solver q-`FedSGD` with `FedSGD` with a best-tuned step-size. For q-`FedSGD`, we tune a step-size on $q = 0$ and apply that step-size to solve q-`FFL` with $q > 0$. q-`FedSGD` has similar performance with `FedSGD`, which indicates that (the inverse of) our estimated Lipschitz constant on $q > 0$ is as good as a best tuned fixed step-size. We can reuse this estimation for different q's instead of manually re-tuning it when q changes. We show the full results on other datasets in Appendix F. We note that both proposed methods q-`FedAvg` and q-`FedSGD` can be easily integrated into existing implementations of federated learning algorithms such as TensorFlow Federated (TFF).

5 CONCLUSION

In this work, we propose q-`FFL`, a novel optimization objective inspired by fair resource allocation in wireless networks that encourages fairer (more uniform) accuracy distributions across devices in federated learning. We devise a scalable method, q-`FedAvg`, to solve this objective in massive networks. Our empirical evaluation on a suite of federated datasets demonstrates the resulting fairness and flexibility of q-`FFL`, as well as the efficiency of q-`FedAvg` compared with existing baselines.

REFERENCES

Tensorflow federated: Machine learning on decentralized data. URL `https://www.tensorflow.org/federated`.

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. Tensorflow: A system for large-scale machine learning. In *Operating Systems Design and Implementation*, 2016.

Alekh Agarwal, Alina Beygelzimer, Miroslav Dudik, John Langford, and Hanna Wallach. A reductions approach to fair classification. In *International Conference on Machine Learning*, 2018.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konecny, Stefano Mazzocchi, H Brendan McMahan, Timon Van Overveldt, David Petrou, Daniel Ramage, and Jason Roselande. Towards federated learning at scale: System design. In *Conference on Systems and Machine Learning*, 2019.

Sebastian Caldas, Peter Wu, Tian Li, Jakub Konečný, H Brendan McMahan, Virginia Smith, and Ameet Talwalkar. Leaf: A benchmark for federated settings. *arXiv preprint arXiv:1812.01097*, 2018.

Andrew Cotter, Heinrich Jiang, Serena Wang, Taman Narayan, Maya Gupta, Seungil You, and Karthik Sridharan. Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *Journal of Machine Learning Research*, 2019.

Mina Dashti, Paeiz Azmi, and Keivan Navaie. Harmonic mean rate fairness for cognitive radio networks with heterogeneous traffic. *Transactions on Emerging Telecommunications Technologies*, 2013.

Marco F Duarte and Yu Hen Hu. Vehicle classification in distributed sensor networks. *Journal of Parallel and Distributed Computing*, 2004.

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Innovations in Theoretical Computer Science*, 2012.

Cheng Tien Ee and Ruzena Bajcsy. Congestion control and fairness for many-to-one routing in sensor networks. In *International Conference on Embedded Networked Sensor Systems*, 2004.

Atilla Eryilmaz and R Srikant. Joint congestion control, routing, and mac for stability and fairness in wireless networks. *IEEE Journal on Selected Areas in Communications*, 2006.

Michael Feldman. Computational fairness: Preventing machine-learned discrimination. 2015.

Alec Go, Richa Bhayani, and Lei Huang. Twitter sentiment classification using distant supervision. *Stanford CS224N Project Report*, 2009.

Ellen L. Hahne. Round-robin scheduling for max-min fairness in data networks. *IEEE Journal on Selected Areas in communications*, 1991.

Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. In *Advances in Neural Information Processing Systems*, 2016.

Tatsunori Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In *International Conference on Machine Learning*, 2018.

Rajendra K Jain, Dah-Ming W Chiu, and William R Hawe. A quantitative measure of fairness and discrimination. *Eastern Research Laboratory, Digital Equipment Corporation*, 1984.

Frank Kelly. Charging and rate control for elastic traffic. *European Transactions on Telecommunications*, 1997.

Frank P Kelly, Aman K Maulloo, and David KH Tan. Rate control for communication networks: shadow prices, proportional fairness and stability. *Journal of the Operational Research society*, 1998.

Tian Lan, David Kao, Mung Chiang, and Ashutosh Sabharwal. An axiomatic theory of fairness in network resource allocation. In *Conference on Information Communications*, 2010.

Tian Li, Anit Kumar Sahu, Maziar Sanjabi, Manzil Zaheer, Ameet Talwalkar, and Virginia Smith. Federated optimization for heterogeneous networks. *arXiv preprint arXiv:1812.06127*, 2018.

Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *arXiv preprint arXiv:1908.07873*, 2019.

H Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *International Conference on Artificial Intelligence and Statistics*, 2017.

Jeonghoon Mo and Jean Walrand. Fair end-to-end window-based congestion control. *IEEE/ACM Transactions on Networking*, 2000.

Mehryar Mohri, Gary Sivek, and Ananda Theertha Suresh. Agnostic federated learning. In *International Conference on Machine Learning*, 2019.

Thyagarajan Nandagopal, Tae-Eun Kim, Xia Gao, and Vaduvur Bharghavan. Achieving mac layer fairness in wireless packet networks. In *International Conference on Mobile Computing and Networking*, 2000.

Michael J Neely, Eytan Modiano, and Chih-Ping Li. Fairness and optimal stochastic control for heterogeneous networks. *IEEE/ACM Transactions On Networking*, 2008.

Jeffrey Pennington, Richard Socher, and Christopher Manning. Glove: Global vectors for word representation. In *Empirical Methods in Natural Language Processing*, 2014.

Bozidar Radunovic and Jean-Yves Le Boudec. A unified framework for max-min and min-max fairness with applications. *IEEE/ACM Transactions on Networking*, 2007.

Alfréd Rényi et al. On measures of entropy and information. In *Proceedings of the Fourth Berkeley Symposium on Mathematical Statistics and Probability*, 1961.

Maziar Sanjabi, Meisam Razaviyayn, and Zhi-Quan Luo. Optimal joint base station assignment and beamforming for heterogeneous networks. *IEEE Transactions on Signal Processing*, 2014.

Ohad Shamir, Nati Srebro, and Tong Zhang. Communication-efficient distributed optimization using an approximate newton-type method. In *International Conference on Machine Learning*, 2014.

Huaizhou Shi, R Venkatesha Prasad, Ertan Onur, and IGMM Niemegeers. Fairness in wireless networks: Issues, measures and challenges. *IEEE Communications Surveys and Tutorials*, 2014.

Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet S Talwalkar. Federated multi-task learning. In *Advances in Neural Information Processing Systems*, 2017.

Virginia Smith, Simone Forte, Ma Chenxin, Martin Takáč, Michael I Jordan, and Martin Jaggi. Cocoa: A general framework for communication-efficient distributed optimization. *Journal of Machine Learning Research*, 2018.

Sebastian U Stich. Local sgd converges fast and communicates little. In *International Conference on Learning Representations*, 2019.

Jianyu Wang and Gauri Joshi. Cooperative sgd: A unified framework for the design and analysis of communication-efficient sgd algorithms. *arXiv preprint arXiv:1808.07576*, 2018.

Blake Woodworth, Suriya Gunasekar, Mesrob I. Ohannessian, and Nathan Srebro. Learning non-discriminatory predictors. In *Conference on Learning Theory*, 2017.

Blake E Woodworth, Jialei Wang, Adam Smith, Brendan McMahan, and Nati Srebro. Graph oracle models, lower bounds, and gaps for parallel stochastic optimization. In *Advances in Neural Information Processing Systems*, 2018.

Hao Yu, Sen Yang, and Shenghuo Zhu. Parallel restarted sgd for non-convex optimization with faster convergence and less communication. In *AAAI Conference on Artificial Intelligence*, 2019.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rodriguez, and Krishna P Gummadi. Fairness beyond disparate treatment & disparate impact: Learning classification without disparate mistreatment. In *International Conference on World Wide Web*, 2017a.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rogriguez, and Krishna P Gummadi. Fairness constraints: Mechanisms for fair classification. In *International Conference on Artificial Intelligence and Statistics*, 2017b.

Overview of Appendix. Our appendix is organized as follows.

- Appendix A: Our main theoretical results. In particular, we prove that q-FFL can induce more uniformity of the performance distribution in Appendix A.1, and provide our generalization guarantees of q-FFL in Appendix A.2.
- Appendix B: Proof for the relations between Lipschitz constants between the function $f(\cdot)$ and function $\frac{1}{q+1}f^{q+1}(\cdot)$, which is stated informally in Section 3.3. This relation is used when we devise methods q-FedSGD and q-FedAvg to solve q-FFL.
- Appendix C: Additional background on q-FFL and its relations with α-fairness.
- Appendix D: Pseudo-code for FedAvg and q-FedSGD.
- Appendix E: Detailed experiment setups, including datasets, models, implementation, and hyperparameters.
- Appendix F.1: Full results for the experiments in the main text. We report the uniformity induced by q-FFL under all metrics. As a sanity check, we also provide fairness results on training data. For completeness, we show the average testing accuracy with respect to devices (as opposed to average accuracy with respect to samples reported in the main text). We also demonstrate the efficiency of q-FedAvg on all datasets (as opposed to two datasets in the main text). All figures/tables are presented directly after the corresponding text.
- Appendix F.2: Additional experiments to help obtain a more complete understanding of other (less major) properties of the q-FFL objective and the q-FedAvg method. We study the effects of data heterogeneity and the number of devices on unfairness, the variable levels of fairness resulting from a family of q's, the benefits of allowing for device-specific q's, the convergence speed of q-FFL and how it compares with $q = 0$ and AFL, and the convergence of q-FedAvg under different data heterogeneity. Each experiment starts with a separate paragraph (with a heading), and the figures/tables are shown directly below the corresponding text.

A THEORETICAL ANALYSIS OF THE PROPOSED OBJECTIVE q-FFL

A.1 UNIFORMITY INDUCED BY q-FFL

In this section, we theoretically justify that the q-FFL objective can impose more uniformity of the performance/accuracy distribution. As discussed in Section 3.2, q-FFL can encourage more fair solutions in terms of several metrics, including (1) the variance of accuracy distribution (smaller variance), (2) the angle between the accuracy distribution and the all-ones vector $\mathbf{1}$ (smaller angle), and (3) the entropy of the accuracy distribution (larger entropy). We begin by formally defining these fairness notions.

Definition 3 (*Uniformity 1: Variance of the performance distribution*). We say that the performance distribution of m devices $\{F_1(w), \ldots, F_m(w)\}$ is more uniform under solution w than w' if

$$\mathbf{Var}(F_1(w), \ldots, F_m(w)) < \mathbf{Var}(F_1(w'), \ldots, F_m(w')). \tag{3}$$

Definition 4 (*Uniformity 2: Angle between the performance distribution and $\mathbf{1}$*). We say that the performance distribution of m devices $\{F_1(w), \ldots, F_m(w)\}$ is more uniform under solution w than w' if the angle between $\{F_1(w), \ldots, F_m(w)\}$ and $\mathbf{1}$ is smaller than that between $\{F_1(w'), \ldots, F_m(w')\}$ and $\mathbf{1}$, i.e.,

$$\frac{\frac{1}{m}\sum_{k=1}^{m}F_k(w)}{\sqrt{\frac{1}{m}\sum_{k=1}^{m}F_k^2(w)}} \geq \frac{\frac{1}{m}\sum_{k=1}^{m}F_k(w')}{\sqrt{\frac{1}{m}\sum_{k=1}^{m}F_k^2(w')}}. \tag{4}$$

Definition 5 (*Uniformity 3: Entropy of performance distribution*). We say that the performance distribution of m devices $\{F_1(w), \ldots, F_m(w)\}$ is more uniform under solution w than w' if

$$H(F(w)) \geq H(F(w')), \tag{5}$$

where $H(F(w))$ is the entropy of $\{F_1(w), \ldots, F_m(w)\}$ defined as

$$-\sum_{k=1}^{m} \frac{F_k(w)}{\sum_{k=1}^{m}F_k(w)} \log\left(\frac{F_k(w)}{\sum_{k=1}^{m}F_k(w)}\right).$$

To enforce uniformity/fairness (defined in Definition 3, 4, and 5), we propose the q-FFL objective to impose more weights on the devices with worse performance. Throughout the proof, we consider a similar, unweighted objective:

$$\min_w f_q(w) = \left(\frac{1}{m} \sum_{k=1}^{m} F_k^{q+1}(w) \right)^{\frac{1}{q+1}},$$

and we denote w_q^* as the global optimal solution of $\min_w \, f_q(w)$.

We first investigate the special case of $q = 1$ and show that $q = 1$ results in more fair solutions than $q = 0$ based on Definition 3 and Definition 4.

Lemma 6. $q = 1$ *leads to a more fair solution (smaller variance of the model performance distribution) than $q = 0$, i.e.,* $\mathbf{Var}(F_1(w_1^*), \ldots, F_m(w_1^*)) < \mathbf{Var}(F_1(w_0^*), \ldots, F_m(w_0^*))$.

Proof. Use the fact that w_1^* is the optimal solution of $\min_w \, f_1(w)$, and w_0^* is the optimal solution of $\min_w \, f_0(w)$, we get

$$\frac{\sum_{k=1}^{m} F_k^2(w_1^*)}{m} - \left(\frac{1}{m} \sum_{i=1}^{m} F_k(w_1^*) \right)^2 \leq \frac{\sum_{k=1}^{m} F_k^2(w_0^*)}{m} - \left(\frac{1}{m} \sum_{i=1}^{m} F_k(w_1^*) \right)^2$$

$$\leq \frac{\sum_{k=1}^{m} F_k^2(w_0^*)}{m} - \left(\frac{1}{m} \sum_{i=1}^{m} F_k(w_0^*) \right)^2. \qquad (6)$$

$\square$

Lemma 7. $q = 1$ *leads to a more fair solution (smaller angle between the performance distribution and $\mathbf{1}$) than $q = 0$, i.e.,*

$$\frac{\frac{1}{m} \sum_{k=1}^{m} F_k(w_1^*)}{\sqrt{\frac{1}{m} F_k^2(w_1^*)}} \geq \frac{\frac{1}{m} \sum_{k=1}^{m} F_k(w_0^*)}{\sqrt{\frac{1}{m} F_k^2(w_0^*)}}.$$

Proof. As $\frac{1}{m} \sum_{k=1}^{m} F_k(w_1^*) \geq \frac{1}{m} \sum_{k=1}^{m} F_k(w_0^*)$ and $\frac{1}{m} \sum_{k=1}^{m} F_k^2(w_1^*) \geq \frac{1}{m} \sum_{k=1}^{m} F_k^2(w_0^*)$, it directly follows that

$$\frac{\frac{1}{m} \sum_{k=1}^{m} F_k(w_1^*)}{\sqrt{\frac{1}{m} F_k^2(w_1^*)}} \geq \frac{\frac{1}{m} \sum_{k=1}^{m} F_k(w_0^*)}{\sqrt{\frac{1}{m} F_k^2(w_0^*)}}.$$

$\square$

We next provide results based on Definition 5. It states that for arbitrary $q \geq 0$, by increasing q for a small amount, we can get more uniform performance distributions defined over higher-orders of the performance.

Lemma 8. *Let $F(w)$ be twice differentiable in w with $\nabla^2 F(w) > 0$ (positive definite). The derivative of $H(F^q(w_p^*))$ with respect to the variable p evaluated at the point $p = q$ is non-negative, i.e.,*

$$\left. \frac{\partial}{\partial p} H(F^q(w_p^*)) \right|_{p=q} \geq 0,$$

where $H(F^q(w_p^*))$ is defined over the probability distribution of $\frac{1}{\sum_k F_k^q(w_p^*)} (F_1^q(w_p^*), \ldots, F_m^q(w_p^*))$.

Proof.

$$\frac{\partial}{\partial p} H(F^q(w_p^*))\bigg|_{p=q} = -\frac{\partial}{\partial p} \sum_k \frac{F_k^q(w_p^*)}{\sum_\kappa F_\kappa^q(w_p^*)} \ln\left(\frac{F_k^q(w_p^*)}{\sum_\kappa F_\kappa^q(w_p^*)}\right)\bigg|_{p=q} \tag{7}$$

$$= -\frac{\partial}{\partial p} \sum_k \frac{F_k^q(w_p^*)}{\sum_\kappa F_\kappa^q(w_p^*)} \ln\left(F_k^q(w_p^*)\right)\bigg|_{p=q}$$

$$+ \frac{\partial}{\partial p} \ln \sum_\kappa F_\kappa^q(w_p^*)\bigg|_{p=q} \tag{8}$$

$$= -\sum_k \frac{\left(\frac{\partial}{\partial p} w_p^*\big|_{p=q}\right)^\top \nabla_w F_k^q(w_q^*)}{\sum_\kappa F_\kappa^q(w_q^*)} \ln\left(F_k^q(w_q^*)\right)$$

$$-\sum_k \frac{F_k^q(w_q^*)}{\sum_\kappa F_\kappa^q(w_q^*)} \frac{\left(\frac{\partial}{\partial p} w_p^*\big|_{p=q}\right)^\top \nabla_w F_k^q(w_q^*)}{F_k^q(w_q^*)} \tag{9}$$

$$= -\sum_k \frac{\left(\frac{\partial}{\partial p} w_p^*\big|_{p=q}\right)^\top \nabla_w F_k^q(w_q^*)}{\sum_\kappa F_\kappa^q(w_q^*)} \left(\ln\left(F_k^q(w_q^*)\right) + 1\right). \tag{10}$$

Now, let us examine $\frac{\partial}{\partial p} w_p^*\big|_{p=q}$. We know that $\sum_k \nabla_w F_k^p(w_p^*) = 0$ by definition. Taking the derivative with respect to p, we have

$$\sum_k \nabla_w^2 F_k^p(w_p^*) \frac{\partial}{\partial p} w_p^* + \sum_k \left(\ln F_k^p(w_p^*) + 1\right) \nabla_w F_k^p(w_p^*) = 0. \tag{11}$$

Invoking implicit function theorem,

$$\frac{\partial}{\partial p} w_p^* = -\left(\sum_k \nabla_w^2 F_k^p(w_p^*)\right)^{-1} \sum_k \left(\ln F_k^p(w_p^*) + 1\right) \nabla_w F_k^p(w_p^*). \tag{12}$$

Plugging $\frac{\partial}{\partial p} w_p^*\big|_{p=q}$ into (10), we get that $\frac{\partial}{\partial p} H(F^q(w_p^*))\big|_{p=q} \geq 0$ completing the proof. $\qquad\square$

Lemma 8 states that for any p, the performance distribution of $\{F_1^p(w_{p+\epsilon}^*), \ldots, F_m^p(w_{p+\epsilon}^*)\}$ is guaranteed to be more uniform based on Definition 5 than that of $\{F_1^p(w_p^*), \ldots, F_m^p(w_p^*)\}$ for a small enough ϵ. Ideally, we would like to prove that the distribution $\{F_1^q(w_{p+\epsilon}^*), \ldots, F_m^q(w_{p+\epsilon}^*)\}$ is more uniform than $\{F_1^q(w_p^*), \ldots, F_m^q(w_p^*)\}$ for any p, q and small enough ϵ. Next, we formalize this goal under the generalized version of Definition 5 and show its equivalence with a generalized version of Definition 4.

Lemma 9 (*Equivalence between generalized Definition 4 and Definition 5*)**.** *q-FFL encourages more uniform performance distributions under Definition 4 if any only if it encourages more uniform performance distributions under Definition 5, i.e., (a) holds if and only if (b) holds where*
(a) for any $p, q \in \mathbb{R}$, the derivative of $H(F^q(w_p^*))$ with respect to p is non-negative,
(b) for any $0 \leq t \leq r, 0 \leq v \leq u$, $\frac{f_t(w_u^*)}{f_r(w_u^*)} \geq \frac{f_t(w_v^*)}{f_r(w_v^*)}$.

Proof. Definition 5 is a special case of $H(F^q(w_p^*))$ with $q = 1$. If $H(F^q(w_p^*))$ increases with p for any p, q, then we are guaranteed to get more fair solutions based on Definition 5. Similarly, Definition 4 is a special case of $\frac{f_t(w_u^*)}{f_r(w_u^*)}$ with $t = 0, r = 1$. If $\frac{f_t(w_u^*)}{f_r(w_u^*)}$ increases with u for any $t \leq r$, q-FFL can also obtain more fair solutions under Definition 4.

Next, we show that (a) and (b) are equivalent measures of fairness.

For any $r \geq t \geq 0$, and any $u \geq v \geq 0$,

$$\frac{f_t(w_u^*)}{f_r(w_u^*)} \geq \frac{f_t(w_v^*)}{f_r(w_v^*)} \iff \ln \frac{f_t(w_u^*)}{f_r(w_u^*)} - \ln \frac{f_t(w_v^*)}{f_r(w_v^*)} \geq 0 \tag{13}$$

$$\iff \int_v^u \frac{\partial}{\partial \tau} \ln \frac{f_t(w_\tau^*)}{f_r(w_\tau^*)} d\tau \geq 0 \tag{14}$$

$$\iff \frac{\partial}{\partial p} \ln \frac{f_t(w_p^*)}{f_r(w_p^*)} \geq 0, \text{ for any } p \geq 0 \tag{15}$$

$$\iff \frac{\partial}{\partial p} \ln f_r(w_p^*) - \frac{\partial}{\partial p} \ln f_t(w_p^*) \leq 0, \text{ for any } p \geq 0 \tag{16}$$

$$\iff \int_t^r \frac{\partial^2}{\partial p \partial q} \ln f_q(w_p^*) dq \leq 0 \text{ for any } p, q \geq 0 \tag{17}$$

$$\iff \frac{\partial^2}{\partial p \partial q} \ln f_q(w_p^*) \leq 0, \text{ for any } p, q \geq 0 \tag{18}$$

$$\iff \frac{\partial}{\partial p} H(F^q(w_p^*)) \geq 0, \text{ for any } p, q \geq 0. \tag{19}$$

The last inequality is obtained using the fact that by taking the derivative of $\ln f_q(w_p^*)$ with respect to q, we get $-H(F^q(w_p^*))$. $\qquad \square$

Discussions. We give geometric (Definition 4) and information-theoretic (Definition 5) interpretations of our uniformity/fairness notion and provide uniformity guarantees under the q-FFL objective in some cases (Lemma 6, Lemma 7, and Lemma 8). We reveal interesting relations between the geometric and information-theoretic interpretations in Lemma 9. Future work would be to gain further understandings for more general cases indicated in Lemma 9.

A.2 GENERALIZATION BOUNDS

In this section, we first describe the setup we consider in more detail, and then provide generalization bounds of q-FFL. One benefit of q-FFL is that it allows for a flexible trade-off between fairness and accuracy, which generalizes AFL (a special case of q-FFL with $q \to \infty$). We also provide learning bounds that generalize the bounds of the AFL objective, as described below.

Suppose the service provider is interested in minimizing the loss over a distributed network of devices, with possibly unknown weights on each device:

$$L_\lambda(h) = \sum_{k=1}^m \lambda_k \mathbb{E}_{(x,y) \sim D_k}[l(h(x), y)], \tag{20}$$

where λ is in a probability simplex Λ, m is the total number of devices, D_k is the local data distribution for device k, h is the hypothesis function, and l is the loss. We use $\hat{L}_\lambda(h)$ to denote the empirical loss:

$$\hat{L}_\lambda(h) = \sum_{k=1}^m \frac{\lambda_k}{n_k} \sum_{j=1}^{n_k} l(h(x_{k,j}), y_{k,j}), \tag{21}$$

where n_k is the number of local samples on device k and $(x_{k,j}, y_{k,j}) \sim D_k$.

We consider a slightly different, unweighted version of q-FFL:

$$\min_w f_q(w) = \frac{1}{m} \sum_{k=1}^m F_k^{q+1}(w), \tag{22}$$

which is equivalent to minimizing the empirical loss

$$\tilde{L}_q(h) = \max_{\nu, \|\nu\|_p \leq 1} \sum_{k=1}^m \frac{\nu_i}{n_k} \sum_{j=1}^{n_k} l(h(x_{k,j}), y_{k,j}), \tag{23}$$

where $\frac{1}{p} + \frac{1}{q+1} = 1$ ($p \geq 1, q \geq 0$).

Lemma 10 (*Generalization bounds of q-FFL for a specific* λ). *Assume that the loss l is bounded by $M > 0$ and the numbers of local samples are $(n_1, \cdots, n_m)$. Then, for any $\delta > 0$, with probability at least $1 - \delta$, the following holds for any $\lambda \in \Lambda, h \in H$:*

$$L_\lambda(h) \leq A_q(\lambda)\tilde{L}_q(h) + \mathbb{E}\left[\max_{h \in H} L_\lambda(h) - \hat{L}_\lambda(h)\right] + M\sqrt{\sum_{k=1}^{m} \frac{\lambda_k^2}{2n_k} \log \frac{1}{\delta}}, \qquad (24)$$

where $A_q(\lambda) = \|\lambda\|_p$, and $1/p + 1/(q+1) = 1$.

Proof. Similar to the proof in Mohri et al. (2019), for any $\delta > 0$, the following inequality holds with probability at least $1 - \delta$ for any $\lambda \in \Lambda, h \in H$:

$$L_\lambda(h) \leq \hat{L}_\lambda(h) + \mathbb{E}\left[\max_{h \in H} L_\lambda(h) - \hat{L}_\lambda(h)\right] + M\sqrt{\sum_{k=1}^{m} \frac{\lambda_k^2}{2n_k} \log \frac{1}{\delta}}. \qquad (25)$$

Denote the empirical loss on device k $\frac{1}{n_k} \sum_{j=1}^{n_k} l(h(x_{k,j}), y_{k,j})$ as F_k. From Hölder's inequality, we have

$$\hat{L}_\lambda(h) = \sum_{k=1}^{m} \lambda_k F_k \leq \left(\sum_{k=1}^{m} \lambda_k^p\right)^{\frac{1}{p}} \left(\sum_{k=1}^{m} F_k^{q+1}\right)^{\frac{1}{q+1}} = A_q(\lambda)\tilde{L}_q(h), \ \frac{1}{p} + \frac{1}{q+1} = 1.$$

Plugging $\hat{L}_\lambda(h) \leq A_q(\lambda)\tilde{L}_q(h)$ into (25) yields the results. $\qquad \square$

Theorem 11 (*Generalization bounds of q-FFL for any* λ). *Assume that the loss l is bounded by $M > 0$ and the number of local samples is $(n_1, \cdots, n_m)$. Then, for any $\delta > 0$, with probability at least $1 - \delta$, the following holds for any $\lambda \in \Lambda, h \in H$:*

$$L_\lambda(h) \leq \max_{\lambda \in \Lambda} \left(A_q(\lambda)\right) \tilde{L}_q(h) + \max_{\lambda \in \Lambda} \left(\mathbb{E}\left[\max_{h \in H} L_\lambda(h) - \hat{L}_\lambda(h)\right] + M\sqrt{\sum_{k=1}^{m} \frac{\lambda_k^2}{2n_k} \log \frac{1}{\delta}}\right), \quad (26)$$

where $A_q(\lambda) = \|\lambda\|_p$, and $1/p + 1/(q+1) = 1$.

Proof. This directly follows from Lemma 10, by taking the maximum over all possible λ's in Λ. $\quad \square$

B   RELATIONS BETWEEN LIPSCHITZ CONSTANTS FOR $q = 0$ AND $q > 0$

Lemma 12. *If the non-negative function $f(\cdot)$ has a Lipschitz gradient with constant L, then for any $q \geq 0$ and at any point w,*

$$L_q(w) = Lf(w)^q + qf(w)^{q-1}\|\nabla f(w)\|^2 \qquad (27)$$

is an upper-bound for the local Lipschitz constant of the gradient of $\frac{1}{q+1}f^{q+1}(\cdot)$ at point w.

Proof. At any point w, we can compute the Hessian $\nabla^2\left(\frac{1}{q+1}f^{q+1}(w)\right)$ as:

$$\nabla^2\left(\frac{1}{q+1}f^{q+1}(w)\right) = qf^{q-1}(w)\underbrace{\nabla f(w)\nabla^T f(w)}_{\preceq\|\nabla f(w)\|^2 \times I} + f^q(w)\underbrace{\nabla^2 f(w)}_{\preceq L \times I}. \qquad (28)$$

As a result, $\|\nabla^2 \frac{1}{q+1}f^{q+1}(w)\|_2 \leq L_q(w) = Lf(w)^q + qf(w)^{q-1}\|\nabla f(w)\|^2$. $\qquad \square$

C α-FAIRNESS AND q-FFL

As discussed in Section 2, while it is natural to consider the α-fairness framework for machine learning, we are unaware of any work that uses α-fairness to modify machine learning training objectives. We provide additional details on the framework below; for further background on α-fairness and fairness in resource allocation more generally, we defer the reader to Shi et al. (2014); Mo & Walrand (2000).

α-fairness (Lan et al., 2010; Mo & Walrand, 2000) is a popular fairness metric widely-used in resource allocation problems. The framework defines a family of overall utility functions that can be derived by summing up the following function of the individual utilities of the users in the network:

$$U_\alpha(x) = \begin{cases} \ln(x), & \text{if } \alpha = 1 \\ \frac{1}{1-\alpha}x^{1-\alpha}, & \text{if } \alpha \geq 0, \alpha \neq 1 \,. \end{cases}$$

Here $U_\alpha(x)$ represents the individual utility of some specific user given x allocated resources (e.g., bandwidth). The goal is to find a resource allocation strategy to maximize the sum of the individual utilities. This family of functions includes a wide range of popular fair resource allocation strategies. In particular, the above function represents zero fairness with $\alpha = 0$, proportional fairness (Kelly, 1997) with $\alpha = 1$, harmonic mean fairness (Dashti et al., 2013) with $\alpha = 2$, and max-min fairness (Radunovic & Le Boudec, 2007) with $\alpha = +\infty$.

Note that in federated learning, we are dealing with costs and not utilities. Thus, max-min in resource allocation corresponds to min-max in our setting. With this analogy, it is clear that in our proposed objective q-FFL (2), the case where $q = +\infty$ corresponds to min-max fairness since it is optimizing for the worst-performing device, similar to what was proposed in Mohri et al. (2019). Also, $q = 0$ corresponds to zero fairness, which reduces to the original FedAvg objective (1). In resource allocation problems, α can be tuned for trade-offs between fairness and system efficiency. In federated settings, q can be tuned based on the desired level of fairness (e.g., desired variance of accuracy distributions) and other performance metrics such as the overall accuracy. For instance, in Table 2 in Section 4.3, we demonstrate on two datasets that as q increases, the overall average accuracy decreases slightly while the worst accuracies are increased significantly and the variance of the accuracy distribution decreases.

D PSEUDO-CODE OF ALGORITHMS

D.1 THE FEDAVG ALGORITHM

Algorithm 2 Federated Averaging McMahan et al. (2017) (`FedAvg`)

Input: K, T, η, E, w^0, N, p_k, $k = 1, \cdots, N$
for $t = 0, \cdots, T-1$ **do**
    Server randomly chooses a subset S_t of K devices (each device k is chosen with probability p_k)
    Server sends w^t to all chosen devices
    Each device k updates w^t for E epochs of SGD on F_k with step-size η to obtain w_k^{t+1}
    Each chosen device k sends w_k^{t+1} back to the server
    Server aggregates the w's as $w^{t+1} = \frac{1}{K} \sum_{k \in S_t} w_k^{t+1}$
end for

D.2 THE q-FEDSGD ALGORITHM

Algorithm 3 q-FedSGD

1: **Input:** K, T, q, $1/L$, w^0, p_k, $k = 1, \cdots, m$
2: **for** $t = 0, \cdots, T-1$ **do**
3:     Server selects a subset S_t of K devices at random (each device k is chosen with prob. p_k)
4:     Server sends w^t to all selected devices
5:     Each selected device k computes:
$$\Delta_k^t = F_k^q(w^t)\nabla F_k(w^t)$$
$$h_k^t = qF_k^{q-1}(w^t)\|\nabla F_k(w^t)\|^2 + LF_k^q(w^t)$$
6:     Each selected device k sends Δ_k^t and h_k^t back to the server
7:     Server updates w^{t+1} as:
$$w^{t+1} = w^t - \frac{\sum_{k \in S_t} \Delta_k^t}{\sum_{k \in S_t} h_k^t}$$
8: **end for**

E EXPERIMENTAL DETAILS

E.1 DATASETS AND MODELS

We provide full details on the datasets and models used in our experiments. The statistics of four federated datasets are summarized in Table 3. We report the total number of devices, the total number of samples, and mean and deviation in the sizes of total data points on each device. Additional details on the datasets and models are described below.

- **Synthetic:** We follow a similar set up as that in Shamir et al. (2014) and impose additional heterogeneity. The model is $y = argmax(\text{softmax}(Wx+b))$, $x \in \mathbb{R}^{60}, W \in \mathbb{R}^{10 \times 60}, b \in \mathbb{R}^{10}$, and the goal is to learn a global W and b. Samples (X_k, Y_k) and local models on each device k satisfies $W_k \sim \mathcal{N}(u_k, 1), b_k \sim \mathcal{N}(u_k, 1), u_k \sim \mathcal{N}(0, 1); x_k \sim \mathcal{N}(v_k, \Sigma)$, where the covariance matrix Σ is diagonal with $\Sigma_{j,j} = j^{-1.2}$. Each element in v_k is drawn from $\mathcal{N}(B_k, 1), B_k \sim \mathcal{N}(0, 1)$. There are 100 devices in total and the number of samples on each devices follows a power law.

- **Vehicle**[2]**:** We use the same Vehicle Sensor (Vehicle) dataset as Smith et al. (2017), modelling each sensor as a device. This dataset consists of acoustic, seismic, and infrared sensor data collected from a distributed network of 23 sensors Duarte & Hu (2004). Each sample has a 100-dimension feature and a binary label. We train a linear SVM to predict between AAV-type and DW-type vehicles. We tune the hyperparameters in SVM and report the best configuration.

- **Sent140:** This dataset is a collection of tweets curated from 1,101 accounts from Sentiment140 (Go et al., 2009) (Sent140) where each Twitter account corresponds to a device. The task is text sentiment analysis which we model as a binary classification problem. The model takes as input a 25-word sequence, embeds each word into a 300-dimensional space using pretrained Glove (Pennington et al., 2014), and outputs a binary label after two LSTM layers and one densely-connected layer.

- **Shakespeare:** This dataset is built from *The Complete Works of William Shakespeare* (McMahan et al., 2017). Each speaking role in the plays is associated with a device. We subsample 31 speaking roles to train a deep language model for next character prediction. The model takes as input an 80-character sequence, embeds each character into a learnt 8-dimensional space, and outputs one character after two LSTM layers and one densely-connected layer.

Table 3: Statistics of federated datasets

Dataset	Devices	Samples	Samples/device	
			mean	stdev
Synthetic	100	12,697	127	73
Vehicle	23	43,695	1,899	349
Sent140	1,101	58,170	53	32
Shakespeare	31	116,214	3,749	6,912

E.2 IMPLEMENTATION DETAILS

E.2.1 MACHINES

We simulate the federated setting (one server and m devices) on a server with 2 Intel® Xeon® E5-2650 v4 CPUs and 8 NVidia® 1080Ti GPUs.

E.2.2 SOFTWARE

We implement all code in TensorFlow (Abadi et al., 2016) Version 1.10.1. Please see our anonymzied code submission for more details.

---

[2]http://www.ecs.umass.edu/~mduarte/Software.html

E.2.3 Hyperparameters

We randomly split data on each local device into 80% training set, 10% testing set, and 10% validation set. We tune a best q from $\{0.001, 0.01, 0.1, 1, 2, 5, 10, 15\}$ on the validation set and report accuracy distributions on the testing set. We pick up the q value where the variance decreases the most, while the overall average accuracy change (compared with the $q = 0$ case) is within 1%. For each dataset, we repeat this process for five randomly selected train/test/validation splits, and report the mean and standard deviation across these five runs where applicable. For Synthetic, Vehicle, Sent140, and Shakespeare, optimal q values are 1, 5, 1, and 0.001, respectively. For all datasets, we randomly sample 10 devices each round. We tune the learning rate and batch size on `FedAvg` and use the same learning rate and batch size for all q-`FedAvg` experiments of that dataset. The learning rates for Synthetic, Vehicle, Sent140, and Shakespeare are 0.1, 0.01, 0.03, and 0.8, respectively. The batch sizes for Synthetic, Vehicle, Sent140, and Shakespeare are 10, 64, 32, and 10.

In comparing q-`FedAvg`'s efficiency with q-`FedSGD`, we also tune a best learning rate for q-`FedSGD` methods on $q = 0$. For each comparison, we fix devices selected and mini-batch orders across all runs. We stop training when the training loss $F(w)$ does not decrease for 10 rounds. When running `AFL` methods, we search for a best γ_w and γ_λ such that `AFL` achieves the highest testing accuracy on the device with the highest loss within a fixed number of rounds. For Adult, we use $\gamma_w = 0.1$ and $\gamma_\lambda = 0.1$; for Fashion MNIST, we use $\gamma_w = 0.001$ and $\gamma_\lambda = 0.01$. We use the same γ_w as step-sizes for q-`FedAvg` on Adult and Fashion MNIST. In Table 2, $q_1 = 0.01, q_2 = 2$ for q-`FFL` on Adult and $q_1 = 5, q_2 = 15$ for q-`FFL` on Fashion MNIST. The number of local epochs is fixed to 1 whenever we perform local updates.

F   FULL EXPERIMENTS

F.1   FULL RESULTS OF PREVIOUS EXPERIMENTS

Fairness of q-FFL under all uniformity metrics.   We demonstrate the fairness of q-FFL in Table 1 in terms of variance. Here, we report similar results in terms of other uniformity measures (the last two columns).

Table 4: Full statistics of the test accuracy distribution for q-FFL. q-FFL increases the accuracy of the worst 10% devices without decreasing the average accuracies. We see that q-FFL encourages more uniform distributions under all uniformity metrics defined in Appendix A.2: (1) the variance of the accuracy distribution (Definition 3), (2) the geometric angle between the accuracy distribution and the all-ones vector $\mathbf{1}$ (Definition 4), and (3) the KL-divergence between the normalized accuracy vector $\boldsymbol{a}$ and the uniform distribution $\boldsymbol{u}$, which can be directly translated to the entropy of $\boldsymbol{a}$ (Definition 5) .

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|u$)
Synthetic	$q=0$	$80.8 \pm .9$	18.8 ± 5.0	100.0 ± 0.0	724 ± 72	19.5 ± 1.1	$.083 \pm .013$
	$q=1$	79.0 ± 1.2	$\mathbf{31.1} \pm 1.8$	100.0 ± 0.0	$\mathbf{472} \pm 14$	$\mathbf{16.0} \pm .5$	$\mathbf{.049} \pm .003$
Vehicle	$q=0$	$87.3 \pm .5$	43.0 ± 1.0	$\mathbf{95.7} \pm 1.0$	291 ± 18	$11.3 \pm .3$	$.031 \pm .003$
	$q=5$	$87.7 \pm .7$	$\mathbf{69.9} \pm .6$	$94.0 \pm .9$	$\mathbf{48} \pm 5$	$\mathbf{4.6} \pm .2$	$\mathbf{.003} \pm .000$
Sent140	$q=0$	65.1 ± 4.8	15.9 ± 4.9	100.0 ± 0.0	697 ± 132	22.4 ± 3.3	$.104 \pm .034$
	$q=1$	$66.5 \pm .2$	$\mathbf{23.0} \pm 1.4$	100.0 ± 0.0	$\mathbf{509} \pm 30$	$\mathbf{18.8} \pm .5$	$\mathbf{.067} \pm .006$
Shakespeare	$q=0$	$51.1 \pm .3$	39.7 ± 2.8	$\mathbf{72.9} \pm 6.7$	82 ± 41	9.8 ± 2.7	$.014 \pm .006$
	$q=.001$	$52.1 \pm .3$	$\mathbf{42.1} \pm 2.1$	69.0 ± 4.4	$\mathbf{54} \pm 27$	$\mathbf{7.9} \pm 2.3$	$\mathbf{.009} \pm .05$

Fairness of q-FFL with respect to training accuracy.   The empirical results in Section 4 are with respect to testing accuracy. As a sanity check, we show that q-FFL also results in more fair training accuracy distributions in Figure 4 and Table 5.

Figure 4: q-FFL ($q > 0$) results in more centered (i.e., fair) *training* accuracy distributions across devices without sacrificing the average accuracy.

Table 5: More statistics showing that q-FFL results in more fair training accuracy distributions. We see that under the q-FFL ($q > 0$) objective, the worst 10% training accuracy increases, and the variance of training accuracies is smaller. q-FFL is also more fair under other uniformity measurements—(a) the angle between the accuracy distribution and the all-ones vector $\mathbf{1}$, and (b) the KL divergence between the normalized accuracy $\boldsymbol{a}$ and uniform distribution $\boldsymbol{u}$.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|u$)
Synthetic	$q=0$	$81.7 \pm .3$	23.6 ± 1.1	$100.0 \pm .0$	597 ± 10	$17.5 \pm .3$	$.061 \pm .002$
	$q=1$	$78.9 \pm .2$	$\mathbf{41.8} \pm 1.0$	$96.8 \pm .5$	$\mathbf{292} \pm 11$	$\mathbf{12.5} \pm .2$	$\mathbf{.027} \pm .001$
Vehicle	$q=0$	$87.5 \pm .2$	49.5 ± 10.2	$\mathbf{94.9} \pm .7$	237 ± 97	10.2 ± 2.4	$.025 \pm .011$
	$q=5$	$87.8 \pm .5$	$\mathbf{71.3} \pm 2.2$	93.1 ± 1.4	$\mathbf{37} \pm 12$	$\mathbf{4.0} \pm .7$	$\mathbf{.003} \pm .001$
Sent140	$q=0$	$69.8 \pm .8$	36.9 ± 3.1	$\mathbf{94.4} \pm 1.1$	278 ± 44	13.6 ± 1.1	$.032 \pm .006$
	$q=1$	$68.2 \pm .6$	$\mathbf{46.0} \pm .3$	$88.8 \pm .8$	$\mathbf{143} \pm 4$	$\mathbf{10.0} \pm .1$	$\mathbf{.017} \pm .000$
Shakespeare	$q=0$	$72.7 \pm .8$	46.4 ± 1.4	$\mathbf{79.7} \pm .9$	116 ± 8	$9.9 \pm .3$	$.015 \pm .001$
	$q=.001$	66.7 ± 1.2	$\mathbf{48.0} \pm .4$	71.2 ± 1.9	$\mathbf{56} \pm 9$	$\mathbf{7.1} \pm .5$	$\mathbf{.008} \pm .001$

Average testing accuracy with respect to devices. In Section 4.2, we show that q-FFL leads to more fair accuracy distributions while maintaining approximately the same testing accuracies. Note that we report average testing accuracy with respect to *all data points* in Table 1. However, we observe similar results on average accuracy with respect to *all devices* between $q = 0$ and $q > 0$ objectives, as shown in Table 6. This indicates that q-FFL can reduce the variance of the accuracy distribution without sacrificing the average accuracy over devices or over data points.

Table 6: Average testing accuracy under q-FFL objectives. We show that the resulting solutions of $q = 0$ and $q > 0$ objectives have approximately the same average accuracies both with respect to all data points and with respect to all devices.

Dataset	Objective	Accuracy w.r.t. Data Points (%)	Accuracy w.r.t. Devices (%)
Synthetic	$q = 0$	$80.8 \pm .9$	$77.3 \pm .6$
	$q = 1$	79.0 ± 1.2	76.3 ± 1.7
Vehicle	$q = 0$	$87.3 \pm .5$	$85.6 \pm .4$
	$q = 5$	$87.7 \pm .7$	$86.5 \pm .7$
Sent140	$q = 0$	65.1 ± 4.8	64.6 ± 4.5
	$q = 1$	$66.5 \pm .2$	$66.2 \pm .2$
Shakespeare	$q = 0$	$51.1 \pm .3$	61.4 ± 2.7
	$q = .001$	$52.1 \pm .3$	$60.0 \pm .5$

Comparison with uniform sampling. In Figure 5 and Table 7, we show that in terms of training accuracies, the uniform sampling heuristic may outperform q-FFL (as opposed to the testing accuracy results in Section 4). We suspect that this is because the uniform sampling baseline is a static method and is likely to overfit to those devices with few samples. In additional to Figure 2 in Section 4.3, we also report the average testing accuracy with respect to data points, best 10%, worst 10% accuracies, and the variance (along with two other uniformity measures) in Table 8.

Figure 5: q-FFL ($q > 0$) compared with uniform sampling in training accuracy. We see that on some datasets uniform sampling has higher (and more fair) training accuracies due to the fact that it is overfitting to devices with few samples.

Table 7: More statistics comparing the uniform sampling objective with q-FFL in terms of training accuracies. We observe that uniform sampling could result in more fair *training* accuracy distributions with smaller variance in some cases.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|\|u$)
Synthetic	uniform	$83.5 \pm .2$	$\mathbf{42.6} \pm 1.4$	$\mathbf{100.0} \pm .0$	366 ± 17	$13.4 \pm .3$	$.031 \pm .002$
	$q = 1$	$78.9 \pm .2$	41.8 ± 1.0	$96.8 \pm .5$	$\mathbf{292} \pm 11$	$\mathbf{12.5} \pm .2$	$\mathbf{.027} \pm .001$
Vehicle	uniform	$87.3 \pm .3$	$46.6 \pm .8$	$\mathbf{94.8} \pm .5$	261 ± 10	$10.7 \pm .2$	$.027 \pm .001$
	$q = 5$	$87.8 \pm .5$	$\mathbf{71.3} \pm 2.2$	93.1 ± 1.4	$\mathbf{37} \pm 12$	$\mathbf{4.0} \pm .7$	$\mathbf{.003} \pm .001$
Sent140	uniform	$69.1 \pm .5$	42.2 ± 1.1	$\mathbf{91.0} \pm 1.3$	188 ± 19	$11.3 \pm .5$	$.022 \pm .002$
	$q = 1$	$68.2 \pm .6$	$\mathbf{46.0} \pm .3$	$88.8 \pm .8$	$\mathbf{143} \pm 4$	$\mathbf{10.0} \pm .1$	$\mathbf{.017} \pm .000$
Shakespeare	uniform	57.7 ± 1.5	$\mathbf{54.1} \pm 1.7$	$\mathbf{72.4} \pm 3.2$	$\mathbf{32} \pm 7$	$\mathbf{5.2} \pm .5$	$\mathbf{.004} \pm .001$
	$q = .001$	66.7 ± 1.2	$48.0 \pm .4$	71.2 ± 1.9	56 ± 9	$7.1 \pm .5$	$.008 \pm .001$

Table 8: More statistics showing more fair solutions induced by q-FFL compared with the uniform sampling baseline in terms of *test* accuracies. Again, we observe that under q-FFL, the testing accuracy of the worst 10% devices tends to increase compared with uniform sampling, and the variance of the final testing accuracies is smaller. Similarly, q-FFL is also more fair than uniform sampling in terms of other uniformity metrics.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|u$)
Synthetic	uniform	82.2 ± 1.1	$30.0 \pm .4$	$100.0 \pm .0$	525 ± 47	$\mathbf{15.6} \pm .8$	$\mathbf{.048} \pm .007$
	$q = 1$	79.0 ± 1.2	$\mathbf{31.1} \pm 1.8$	100.0 ± 0.0	$\mathbf{472} \pm 14$	$16.0 \pm .5$	$.049 \pm .003$
Vehicle	uniform	$86.8 \pm .3$	$45.4 \pm .3$	$\mathbf{95.4} \pm .7$	267 ± 7	$10.8 \pm .1$	$.028 \pm .001$
	$q = 5$	87.7 ± 0.7	$\mathbf{69.9} \pm .6$	$94.0 \pm .9$	$\mathbf{48} \pm 5$	$\mathbf{4.6} \pm .2$	$\mathbf{.003} \pm .000$
Sent140	uniform	66.6 ± 2.6	21.1 ± 1.9	100.0 ± 0.0	560 ± 19	$19.8 \pm .7$	$.076 \pm .006$
	$q = 1$	$66.5 \pm .2$	$\mathbf{23.0} \pm 1.4$	100.0 ± 0.0	$\mathbf{509} \pm 30$	$\mathbf{18.8} \pm .5$	$\mathbf{.067} \pm .006$
Shakespeare	uniform	$50.9 \pm .4$	41.0 ± 3.7	$\mathbf{70.6} \pm 5.4$	71 ± 38	9.1 ± 2.8	$.012 \pm .006$
	$q = .001$	$52.1 \pm .3$	$\mathbf{42.1} \pm 2.1$	69.0 ± 4.4	$\mathbf{54} \pm 27$	$\mathbf{7.9} \pm 2.3$	$\mathbf{.009} \pm .05$

Efficiency of q-FedAvg on all datasets.   We provide full results to demonstrate the efficiency of q-FedAvg (Algorithm 1) relative to its non-local-updating baseline q-FedSGD (Algorithm 3). At each communication round, q-FedAvg runs one epoch of local updates on each selected device, while q-FedSGD runs gradient descent using the local training data. In Figure 3, q-FedAvg converges faster than q-FedSGD in terms of communication rounds in most cases due to its local updating scheme. The slower convergence of q-FedAvg compared with q-FedSGD on the synthetic dataset may be due to the fact that when local data distributions are highly heterogeneous, local updating schemes may allow local models to move too far away from the initial global model, potentially hurting convergence; see Figure 9 for more details.

Figure 6: For a fixed objective (i.e., the same q), the convergence of q-FedAvg (Alg.1), q-FedSGD (Alg.3), and FedSGD on all datasets. For q-FedAvg and q-FedSGD, we tune a best step-size on $q = 0$ and apply that step-size to solve q-FFL with any $q > 0$. For FedSGD, we tune the step-size directly. We observe that (1) q-FedAvg converges faster in terms of communication rounds; (2) the proposed q-FedSGD solver achieves similar performance compared with a best tuned FedSGD.

F.2   ADDITIONAL EXPERIMENTS

Effects of data heterogeneity and the number of devices on unfairness. To study how data heterogeneity and the total number of devices affect unfairness in a more direct way, we investigate into a set of synthetic datasets where we can quantify the degree of heterogeneity. The results are shown in Table 9 below. We generate three synthetic datasets following the process described in Appendix E.1, but with different parameters to control heterogeneity. In particular, we generate an IID data— Synthetic (IID) by setting the same W and b on all devices and setting the samples $x_k \sim \mathcal{N}(0,1)$ for any device k. We instantiate two non-identically distributed datasets (Synthetic (1, 1) and Synthetic (2, 2)) from Synthetic (α, β) where $u_k \sim \mathcal{N}(0, \alpha)$ and $B_k \sim \mathcal{N}(0, \beta)$. Recall that α, β allows to precisely manipulate the degree of heterogeneity with larger α, β values indicating more statistical heterogeneity. Therefore, from top to bottom in Table 9, data are more heterogeneous. For each dataset, we further create two variants with different number of participating devices. We see that as data become more heterogeneous and as the number of devices in the network increases, the accuracy distribution tends to be less uniform.

Table 9: Effects of data heterogeneity and the number of devices on unfairness. For a fixed number of devices, as data heterogeneity increases from top to bottom, the accuracy distributions become less uniform (with larger variance) for both $q = 0$ and $q > 0$. Within each dataset, the decreasing number of devices results in a more uniform accuracy distribution. In all scenarios (except on IID data), setting $q > 0$ helps to encourage more fair solutions.

Dataset		Objective	Average	Worst 10%	Best 10%	Variance
Synthetic (IID)	100 devices	$q=0$	$89.2 \pm .6$	70.9 ± 3	100.0 ± 0	85 ± 15
		$q=1$	$89.0 \pm .5$	70.3 ± 3	100.0 ± 0	88 ± 19
	50 devices	$q=0$	87.1 ± 1.5	66.5 ± 3	100.0 ± 0	107 ± 14
		$q=1$	86.8 ± 0.8	66.5 ± 2	100.0 ± 0	109 ± 13
Synthetic (1, 1)	100 devices	$q=0$	$83.0 \pm .9$	36.8 ± 2	100.0 ± 0	452 ± 22
		$q=1$	82.7 ± 1.3	$\mathbf{43.5} \pm 5$	100.0 ± 0	$\mathbf{362} \pm 58$
	50 devices	$q=0$	$84.5 \pm .3$	43.3 ± 2	100.0 ± 0	370 ± 37
		$q=1$	$85.1 \pm .8$	$\mathbf{47.3} \pm 3$	100.0 ± 0	$\mathbf{317} \pm 41$
Synthetic (2, 2)	100 devices	$q=0$	82.6 ± 1.1	25.5 ± 8	100.0 ± 0	618 ± 117
		$q=1$	82.2 ± 0.7	$\mathbf{31.9} \pm 6$	100.0 ± 0	$\mathbf{484} \pm 79$
	50 devices	$q=0$	85.9 ± 1.0	36.8 ± 7	100.0 ± 0	421 ± 85
		$q=1$	85.9 ± 1.4	$\mathbf{39.1} \pm 6$	100.0 ± 0	$\mathbf{396} \pm 76$

A family of q's results in variable levels of fairness. In Table 10, we show the accuracy distribution statistics of using a family of q's on synthetic data. Our objective and methods are not sensitive to any particular q since all $q > 0$ values can lead to more fair solutions compared with $q = 0$. In our experiments in Section 4, we report the results using the q values selected following the protocol described in Appendix E.2.3.

Table 10: Test accuracy statistics of using a family of q's on synthetic data. We show results with q's selected from our candidate set $\{0.001, 0.01, 0.1, 1, 2, 5, 10, 15\}$. q-FFL allows for a more flexible trade-off between fairness and accuracy. A larger q results in more fairness (smaller variance), but potentially lower accuracy. Similarly, a larger q imposes more uniformity in terms of other metrics—(a) the angle between the accuracy distribution and the all-ones vector $\mathbf{1}$, and (b) the KL divergence between the normalized accuracy a and a uniform distribution u.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|\|u$)
Synthetic	$q=0$	$80.8 \pm .9$	18.8 ± 5.0	100.0 ± 0.0	724 ± 72	19.5 ± 1.1	$.083 \pm .013$
	$q=0.1$	81.1 ± 0.8	$22.1 \pm .8$	100.0 ± 0.0	666 ± 56	$18.4 \pm .8$	$.070 \pm .009$
	$q=1$	79.0 ± 1.2	31.1 ± 1.8	100.0 ± 0.0	472 ± 14	$16.0 \pm .5$	$.049 \pm .003$
	$q=2$	74.7 ± 1.3	32.2 ± 2.1	$99.9 \pm .2$	410 ± 23	15.6 ± 0.7	$.044 \pm .005$
	$q=5$	67.2 ± 0.9	30.0 ± 4.8	94.3 ± 1.4	369 ± 51	16.3 ± 1.2	$.048 \pm .010$

Device-specific q. In these experiments, we explore a device-specific strategy for selecting q in q-FFL. We solve q-FFL with $q \in \{0, 0.001, 0.01, 0.1, 1, 2, 5, 10\}$ in parallel. After training, each device selects the best resulting model based on the validation data and tests the performance of the model using the testing set. We report the results in terms of testing accuracy in Table 11. Interestingly, using this device-specific strategy the average accuracy in fact increases while the variance of accuracies is reduced, in comparison with $q = 0$. We note that this strategy does induce more local computation and additional communication load at each round. However, it does not increase the number of communication rounds if run in parallel.

Table 11: Effects of running q-FFL with several q's in parallel. We train multiple global models (corresponding to different q's) independently in the network. After the training finishes, each device picks up a best, device-specific model based on the performance (accuracy) on the validation data. While this adds additional local computation and more communication load per round, the device-specific strategy has the added benefit of increasing the accuracies of devices with the worst 10% accuracies and devices with the best 10% accuracies simultaneously. This strategy is built upon the proposed primitive Algorithm 1, and in practice, people can develop other heuristics to improve the performance (similar to what we explore here), based on the method of adaptively averaging model updates proposed in Algorithm 1.

Dataset	Objective	Average (%)	Worst 10% (%)	Best 10% (%)	Variance	Angle (°)	KL($a\|u$)
Vehicle	q=0	$87.3 \pm .5$	43.0 ± 1.0	95.7 ± 1.0	291 ± 18	$11.3 \pm .3$	$.031 \pm .003$
	q=5	$87.7 \pm .7$	$69.9 \pm .6$	$94.0 \pm .9$	48 ± 5	$4.6 \pm .2$	$.003 \pm .000$
	multiple q	$88.5 \pm .3$	70.0 ± 2.0	$95.8 \pm .6$	52 ± 7	$4.7 \pm .3$	$.004 \pm .000$
Shakespeare	q=0	$51.1 \pm .3$	39.7 ± 2.8	72.9 ± 6.7	$82 \pm 41 \pm 41$	9.8 ± 2.7	$.014 \pm .006$
	q=.001	$52.1 \pm .3$	42.1 ± 2.1	69.0 ± 4.4	54 ± 27	7.9 ± 2.3	$.009 \pm .05$
	multiple q	52.0 ± 1.5	41.0 ± 4.3	72.0 ± 4.8	72 ± 32	$10.1 \pm .7$	$.017 \pm .000$

Convergence speed of q-**FFL.** Since q−FFL $(q > 0)$ is more difficult to optimize, a natural question one might ask is: will the q-FFL $q > 0$ objectives slow the convergence compared with FedAvg? We empirically investigate this on the four datasets. We use q-FedAvg to solve q-FFL, and compare it with FedAvg (i.e., solving q-FFL with $q = 0$). As demonstrated in Figure 7, the q values that result in more fair solutions also do not significantly slow down convergence.

Figure 7: The convergence speed of q-FFL compared with FedAvg. We plot the distance to the highest accuracy achieved versus communication rounds. Although q-FFL with $q>0$ is a more difficult optimization problem, for the q values we choose that could lead to more fair results, the convergence speed is comparable to that of $q = 0$.

Efficiency of q-FFL compared with AFL. One added benefit of q-FFL is that it leads to faster convergence than AFL—even when we use *non-local-updating* methods for both objectives. In Figure 8, we show with respect to the final testing accuracy for the single worst device (i.e., the objective that AFL is trying to optimize), q-FFL converges faster than AFL. As the number of devices increases (from Fashion MNIST to Vehicle), the performance gap between AFL and q-FFL becomes larger because AFL introduces larger variance.

Figure 8: q-FFL is more efficient than AFL. With the worst device achieving the same final testing accuracy, q-FFL converges faster than AFL. For Vehicle (with 23 devices) as opposed to Fashion MNIST (with 3 devices), we see that the performance gap is larger. We run full gradient descent at each round for both methods.

Efficiency of q-FedAvg under different data heterogeneity. As mentioned in Appendix F.1, one potential cause for the slower convergence of q-FedAvg on the synthetic dataset may be that local updating schemes could hurt convergence when local data distributions are highly heterogeneous. Although it has been shown that applying updates locally results in significantly faster convergence in terms of communication rounds (McMahan et al., 2017; Smith et al., 2018), which is consistent with our observation on most datasets, we note that when data is highly heterogeneous, local updating may hurt convergence. We validate this by creating an IID synthetic dataset (Synthetic-IID) where local data on each device follow the same global distribution. We call the synthetic dataset used in Section 4 Synthetic-Non-IID. We also create a hybrid dataset (Synthetic-Hybrid) where half of the total devices are assigned IID data from the same distribution, and half of the total devices are assigned data from different distributions. We observe that if data is perfectly IID, q-FedAvg is more efficient than q-FedSGD. As data become more heterogeneous, q-FedAvg converges more slowly than q-FedSGD in terms of communication rounds. For all three synthetic datasets, we repeat the process of tuning a best constant step-size for FedSGD and observe similar results as before — our dynamic solver q-FedSGD behaves similarly (or even outperforms) a best hand-tuned FedSGD.

Figure 9: Convergence of q-FedAvg compared with q-FedSGD under different data heterogeneity. When data distributions are heterogeneous, it is possible that q-FedAvg converges more slowly than q-FedSGD. Again, the proposed dynamic solver q-FedSGD performs similarly (or better) than a best tuned fixed-step-size FedSGD.