PLAN ONLINE, LEARN OFFLINE: EFFICIENT LEARNING AND EXPLORATION VIA MODEL-BASED CONTROL

ABSTRACT

We propose a plan online and learn offline framework for the setting where an agent with an internal model needs to continually act and learn in the world. Our work builds on the synergistic relationship between local trajectory optimization, global value function learning, and exploration. We study how trajectory optimization can cope with approximation errors in the value function, and can stabilize and accelerate value function learning. Conversely, we also study how approximate value functions can help reduce the planning horizon and allow for better policies beyond local solutions. Finally, we also demonstrate how trajectory optimization can be used to perform temporally coordinated exploration in conjunction with estimating uncertainty in value function approximation. Combining these components enable solutions to complex complex control tasks like humanoid locomotion and dexterous in-hand manipulation in the equivalent of a few minutes of experience in the real world.

1 INTRODUCTION

We consider a setting where an agent with limited memory and computational resources is dropped into a world. The agent has to simultaneously act in the world and learn to become proficient in the tasks it encounters. Let us further consider a setting where the agent has some prior knowledge about the world in the form of a nominal dynamics model. However, the state space of the world could be very large and complex, and the set of possible tasks very diverse. This complexity and diversity, combined with the limited computational capability, rules out the possibility of an *omniscient* agent that has experienced all situations and knows how to act optimally in all states, even if the agent knows the dynamics. Thus, the agent has to act in the world while learning to become competent.

Based on the knowledge of dynamics and the computational resources, the agent is imbued with a local search procedure in the form of trajectory optimization. While the agent would certainly benefit from the most powerful of trajectory optimization algorithms, it is plausible that very complex procedures are still insufficient or inadmissible due to the complexity or inherent unpredictability of the environment and computational budget. While the trajectory optimizer may be insufficient by itself, we show that it provides a powerful vehicle for the agent to explore and learn about the world.

Figure 1: Examples of tasks solved with POLO. A 2D point agent navigating a maze without any directed reward signal, a complex 3D humanoid standing up from the floor, pushing a box, and in-hand re-positioning of a cube to various orientations with a five-fingered hand. Video demonstration of our results can be found at: https://sites.google.com/view/polo-mpc.

Due to the limited capabilities of the agent, a natural expectation is for the agent to be moderately competent for new tasks that occur infrequently and skillful in situations that it encounters repeatedly; it should learn from experience. Based on this intuition, we propose the *plan online and learn offline (POLO)* framework for continual acting and learning. POLO is based on the tight synergistic coupling between local trajectory optimization, global value function learning, and exploration.

We first provide intuitions for why there may be substantial performance degradation when acting *greedily* using an approximate value function. However, a trajectory optimization procedure in conjunction with an approximate value function can compute near optimal actions. Conversely, we also show that value function learning can be accelerated and stabilized by utilizing trajectory optimization integrally in the learning process. In addition, exploration is critical to propagate global information in value function learning, and for trajectory optimization to escape local solutions and saddle points. In POLO, the agent forms hypothesis on potential reward regions, and executes temporally coordinated action sequences through trajectory optimization. This is in contrast to most exploration strategies that explore at the granularity of individual timesteps. The use of trajectory optimization enables the agent to perform directed and efficient exploration, which in turn helps to find better global solutions.

The setting studied in the paper models many problems of interest in robotics and artificial intelligence. Local trajectory optimization becomes readily feasible when a nominal model and computational resources are available to an agent, and can accelerate learning of novel task instances. Figure 1 depicts some of the agents and tasks we consider in this work, which correspond to some of the most high dimensional and complex agents studied recently in RL for continuous control. Combining the benefits of local trajectory optimization methods for fast improvement with generalization enabled by learning is critical for robotic agents that live in our physical world and continually learn to perform a diverse set of tasks without aids such as episode resets.

2 THE POLO FRAMEWORK

The POLO framework combines three components: local trajectory optimizer, global value function approximation, and an uncertainty and reward aware exploration strategy. We first present the motivation for each component, followed by the full POLO procedure.

2.1 DEFINITIONS, NOTATIONS, AND SETTING

We model the world as an infinite horizon discounted Markov Decision Process (MDP), which is characterized by the tuple: $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, \mathcal{R}, \mathcal{T}, \gamma\}$. $\mathcal{S} \in \mathbb{R}^n$ and $\mathcal{A} \in \mathbb{R}^m$ represent the continuous (real-valued) state and action spaces respectively. $\mathcal{R} : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ represents the reward function. $\mathcal{T} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}_+$ represents the dynamics model, which in general could be stochastic, and $\gamma \in [0, 1)$ is the discount factor. A policy $\pi : \mathcal{S} \times \mathcal{A} \to \mathbb{R}_+$ describes a mapping from states to actions. The value of a policy at a state is the average discounted reward accumulated by following the policy from the state: $V^\pi(s) = \mathbb{E}[\sum_{t=0}^\infty \gamma^t r(s_t, \pi(s_t)) \mid s_0 = s]$. The overall performance of the policy over some start state distribution β is given by: $J^\beta(\pi) = \mathbb{E}_{s \sim \beta}[V^\pi(s)]$. For notational simplicity, we use s' to denote the next state visited after (from) s.

As described earlier, we consider the setting where an agent is dropped into a complex world. The agent has access to an internal model of the world. To improve its behavior, the agent has to explore and understand relevant parts of the state space while it continues to act in the world. Due to the availability of the internal model, the agent can revisit states it experienced in the world and reason about alternate potential actions and their consequences to learn more efficiently.

2.2 VALUE FUNCTION APPROXIMATION

The optimal value function describes the long term discounted reward the agent receives under the optimal policy. Defining the Bellman operator as: $\mathcal{B}V(s) = \max_a \mathbb{E}[r(s, a) + \gamma V(s')]$, the optimal value function V^* corresponds to the fixed point: $V^*(s) = \mathcal{B}V^*(s) \; \forall s \in \mathcal{S}$. For small, tabular MDPs, classical dynamic programming algorithms like value iteration can be used to obtain the optimal value function. Using this, the optimal policy can be recovered as: $\pi^*(s) = \arg\max_a \mathbb{E}[r(s, a) + \gamma V^*(s')]$. For continuous MDPs, computing the optimal value func-

tion exactly is not tractable except in a few well known cases like the LQR (Åström & Murray, 2004). Thus, various approaches to approximate the value function have been considered in literature. One popular approach is fitted value iteration (Bertsekas & Tsitsiklis, 1996; Munos & Szepesvári, 2008), where a function approximator (e.g. neural network) is used to approximate the optimal value function. The core structure of fitted value iteration considers a collection of states (or a sampling distribution ν), and a parametric value function approximator $\hat{V}_\theta$. Inspired by value iteration, fitted value iteration updates the parameters as:

$$\theta_{k+1} = \arg\min_\theta \mathbb{E}_{s\sim\nu}\left[\left(\hat{V}_\theta(s) - y(s)\right)^2\right] \tag{1}$$

where the targets y are computed as $y(s) := \max_a \mathbb{E}[r(s,a) + \gamma\hat{V}_{\theta_k}(s')]$. After the value function is approximated over sufficient iterations, the policy is recovered from the value function as $\hat{\pi}(s) = \arg\max_a \mathbb{E}[r(s,a) + \gamma\hat{V}_\theta(s')]$. The success of this overall procedure depends critically on at least two components: the capacity of the function approximator and the sampling distribution ν. To understand this, suppose that we are given an approximate value function $\hat{V}$, with approximation error defined as: $\epsilon := \max_s |\hat{V}(s) - V^*(s)|$.

Lemma 1. *(Bertsekas & Tsitsiklis, 1996) In the worst case, for any β, the performance of $\hat{\pi}$ follows:*

$$\Omega\left(\frac{\gamma\epsilon}{1-\gamma}\right) \le J^\beta(\pi^*) - J^\beta(\hat{\pi}) \le \mathcal{O}\left(\frac{\gamma\epsilon}{1-\gamma}\right) \tag{2}$$

Intuitively, this suggests that performance of $\hat{\pi}$ degrades with a dependence on effective problem horizon determined by γ. This can be understood as the policy paying a price of ϵ at every timestep. Due to the use of function approximation, errors may be inevitable. In practice, we are often interested in temporally extended tasks where $\gamma \approx 1$, and hence this possibility is concerning. The $\arg\max$ operation in $\hat{\pi}$ could inadvertently exploit approximation errors to produce a poor policy.

The performance of fitted value iteration based methods also rely critically on the sampling distribution to propagate global information (Munos & Szepesvári, 2008), especially in sparse reward settings. For some applications, it may be possible to specify good sampling distributions using apriori knowledge of where the optimal policy should visit (e.g. based on demonstration data). However, in the setting where an agent is dropped into a new world or task, automatically generating such sampling distributions may be difficult, and is analogous to the problem of exploration.

2.3 TRAJECTORY OPTIMIZATION AND MODEL PREDICTIVE CONTROL

Trajectory optimization and model predictive control (MPC) have a long history in robotics and control systems (Garcia et al., 1989)[1]. In MPC, a locally optimal sequence of actions (up to horizon H) is computed based on local knowledge of the dynamics model as:

$$\hat{\pi}_{MPC}(s) := \arg\max_{a_{0:H-1}|s_0=s} \mathbb{E}\left[\sum_{t=0}^{H-1} \gamma^t r(s_t, a_t) + \gamma^H r_f(s_H)\right]. \tag{3}$$

As the sequence $a_{0:H-1}$ is optimized, the first action from this sequence is executed, and the procedure is repeated again at the next time step. Here $r_f(s_H)$ represents a terminal or final reward function. This approach has led to tremendous success in a variety of control systems such as power grids, chemical process control, and more recently in robotics (Williams et al., 2016). Since MPC looks forward only H steps, it is ultimately a local method unless coupled with a value function that propagates global information. In addition, we also provide intuitions for why MPC may help accelerate the learning of value functions. This synergistic effect between MPC and global value function learning forms a primary motivation for POLO.

Impact of approximation errors in the value function Suppose we are given an approximate value function $\hat{V}$, with approximation error $\epsilon := \max_s |\hat{V}(s) - V^*(s)|$. Let us set the terminal reward as $r_f(s_H) = \hat{V}(s_H)$.

---

[1]In this work, we use the terms trajectory optimization and MPC interchangeably

Lemma 2. *For all MDPs and β, the performance of the MPC policy can be bounded as:*

$$J^\beta(\pi^*) - J^\beta(\hat{\pi}_{MPC}) \leq \mathcal{O}\left(\frac{\gamma^H \epsilon}{1 - \gamma^H}\right) \tag{4}$$

This suggests that MPC is less susceptible to approximation errors than greedy action selection, but can still benefit from broad knowledge of which parts of the state space are more favorable.

Accelerating convergence of value function Furthermore, MPC can also enable faster convergence of the value function approximation. To motivate this, consider the H-step Bellman operator: $\mathcal{B}^H V(s) := \max_{a_{0:H-1}} \mathbb{E}[\sum_{t=0}^{H-1} \gamma^t r_t + \gamma^H V(s_H)]$. In the tabular setting, for any V_1 and V_2, it is easy to verify that $|\mathcal{B}^H V_1 - \mathcal{B}^H V_2|_\infty \leq \gamma^H |V_1 - V_2|_\infty$. Intuitively, $\mathcal{B}^H$ allows for propagation of global information for H steps, thereby accelerating the convergence due to faster mixing. Note that one way to realize $\mathcal{B}^H$ is to simply apply $\mathcal{B}$ H times, with each step providing a contraction by γ. In the general setting, it is unknown if there exists alternate, cheaper ways to realize $\mathcal{B}^H$. However, for problems in continuous control, MPC based on local dynamic programming methods (Jacobson & Mayne, 1970; Todorov & Li, 2005) provide an efficient way to *approximately* realize $\mathcal{B}^H$, which can be used to accelerate and stabilize value function learning.

2.4 PLANNING TO EXPLORE

The ability of an agent to explore the relevant parts of the state space is critical for the convergence of many RL algorithms. Typical exploration strategies like ϵ-greedy and Boltzmann take exploratory actions with some probability on a *per time-step basis*. Instead, by using MPC, the agent can explore in the space of trajectories. The agent considers a hypothesis of potential reward regions in the state space, and then execute the optimal trajectory conditioned on this belief, resulting in a temporally coordinated sequence of actions. By executing such coordinated actions, the agent can cover the state space more rapidly and intentionally, and avoid back and forth wandering that can slow down the learning. We demonstrate this effect empirically in Section 3.1.

To generate the hypothesis of potentially rewarding regions, we take a Bayesian view and approximately track a posterior over value functions. Consider a motivating setting of regression, where we have a parametric function approximator f_θ with prior $\mathbb{P}(\theta)$. The dataset consists of input-output pairs: $\mathcal{D} = (x_i, y_i)_{i=1}^n$, and we wish to approximate $\mathbb{P}(\theta|\mathcal{D})$. In the Bayesian linear regression setting with a Gaussian prior and noise models, Osband et al. (2018) show that solving the following optimization problem generates a sample from the posterior:

$$\arg\min_\theta ||\tilde{y}_i - f_{\hat{\theta}}(x_i) - f_\theta(x_i)||_2^2 + \frac{\sigma^2}{\lambda}||\theta||_2^2 \tag{5}$$

where $\tilde{y}_i \sim (y_i, \sigma^2)$ is a noisy version of the target and $\tilde{\theta} \sim \mathbb{P}(\theta)$ is a sample from the prior. Based on this, Osband et al. (2018) demonstrate the benefits of uncertainty estimation for exploration. Similarly, we use this procedure to obtain samples from the posterior for value function approximation, and utilize them for temporally coordinated action selection using MPC. We consider K value function approximators $\hat{V}_\theta$ with parameters $\theta_1, \theta_2, \ldots \theta_K$ independently trained based on eq. (5). We consider the softmax of the different samples as the value at a state:

$$\hat{V}(s) = \log\left(\sum_i \exp\left(\lambda \hat{V}_{\theta_i}(s)\right)\right). \tag{6}$$

Since the log-sum-exp function approximates mean + variance for small $\lambda > 0$, this procedure encourages the agent to additionally explore parts of the state space where the disagreement between the function approximators is large. This corresponds to the broad notion of optimism in the face of uncertainty (Auer et al., 2002) which has been a successful exploration bonus strategy for a variety of applications (Silver et al., 2016; Li et al., 2010).

2.5 FINAL ALGORITHM

Putting the components together, POLO utilizes a value function approximation scheme, a trajectory optimization subroutine, and an exploration scheme. POLO operates as follows: when acting in the

---

Algorithm 1 Plan Online and Learn Offline (POLO)

1: **Inputs:** planning horizon H, value function parameters $\theta_1, \theta_2, \ldots \theta_K$, mini-batch size n, number of gradient steps G, update frequency Z
2: **for** $t = 1$ **to** ∞ **do**
3:    Select action a_t according to MPC (eq. 3) with terminal reward $r_f(s) \equiv \hat{V}(s)$ from eq. (6)
4:    Add the state experience s_t to replay buffer $\mathcal{D}$
5:    **if** $\mathrm{mod}(t, Z) = 0$ **then**
6:       **for** G times **do**
7:          Sample n states from the replay buffer, and compute targets using eq. (7)
8:          Update the value functions using eq. (1)
9:       **end for**
10:    **end if**
11: **end for**=0

---

world, the agent always picks the optimal action suggested by MPC according to eq. (3). Exploration is implicitly handled by tracking the value function uncertainties and the optimistic evaluation, as specified in eq. (5) and (6). All the experience (visited states) from the world are stored into a replay buffer $\mathcal{D}$, with old experiences discarded if the buffer becomes full. After every Z steps of acting in the world and collecting experience, the value functions are updated according to eqs. (1 and 5). For state s_i in the buffer and value network θ_k, the targets are constructed as:

$$y^k(s_i) = \max_{a_{0:N-1}} \mathbb{E}\left[\sum_{t=0}^{N-1} \gamma^t r(s_t, a_t) + \gamma^N \hat{V}_{\theta_k}(s_N) \mid s_0 = s_i\right] \tag{7}$$

which corresponds to solving a $N-$step trajectory optimization problem. As described earlier, using trajectory optimization to generate the targets for fitting the value approximation accelerates the convergence and makes the learning more stable, as verified experimentally in Section 3.3. The overall algorithmic scheme is summarized in Algorithm 1.

3 EMPIRICAL RESULTS AND DISCUSSION

Through empirical evaluation, we wish to answer the following questions:

1. Does trajectory optimization in conjunction with uncertainty estimation in value function approximation result in temporally coordinated exploration strategies?
2. Can the use of an approximate value function help reduce the planning horizon for MPC?
3. Does trajectory optimization enable faster and more stable value function learning?

Before answering the questions in detail, we first point out that through POLO we are able to scale up to complex high-dimensional continuous control tasks without elaborate cost shaping. These tasks include in-hand manipulation and 3D humanoid locomotion, which are among the most widely studied and complex tasks in RL for continuous control and robotics. Video demonstration can be found at: https://sites.google.com/view/polo-mpc

3.1 TRAJECTORY OPTIMIZATION FOR EXPLORATION

Exploration is critical in tasks where immediate rewards are not well aligned with long-term objectives. As a representative problem, we consider a point mass agent in different 2D worlds illustrated in figure 2: a simple finite size box with no obstacles and a maze. This domain serves to provide an intuitive understanding of the interaction between trajectory optimization and exploration while also enabling visualization of results. In the extreme case of no rewards in the world, an agent with only local information would need to continuously explore. We wish to understand how POLO, with its ensemble of value functions tracking uncertainties, uses MPC to perform temporally coordinated actions. Our baseline is an agent that employs random exploration on a per-time-step basis; MPC without a value function would not move. Second, we consider an agent that estimates value uncertainties and performs greedy action selection, and third, consider an agent that estimates uncertainties with 32-step MPC in the POLO framework. We observe that POLO achieves a more region

(a) Area coverage   (b) Exploration trace

Figure 2: 2D point mass navigation task in a world with *no rewards*. Fig. (a) describes the percentage of an occupancy grid covered by the agent, averaged over 10 random seeds. Fig. (b) depicts an agent over 1000 timesteps; red indicates regions of high value (uncertainty) while blue denotes low. The value function learns to assign the true, low values to regions visited and preserves high values to unexplored regions; uncertainty and long horizons are observed to be critical for exploration.

coverage in both point mass worlds than the alternate approaches, as quantitatively illustrated in Figure 2(a). The ensemble value function in POLO allows the agent to recognize the true, low value of visited states, while preserving an optimistic value elsewhere. Temporally coordinated action is necessary in the maze world; POLO is able to navigate down all corridors.

3.2 VALUE FUNCTION APPROXIMATION FOR TRAJECTORY OPTIMIZATION

Next, we study if value learning helps to reduce the planning horizon for MPC. To this end, we consider two high dimensional tasks: *humanoid getup* where a 3D humanoid needs to learn to stand up from the ground, and *in-hand manipulation* where a five-fingered hand needs to re-orient a cube to a desired configuration that is randomized every 75 timesteps. For simplicity, we use the MPPI algorithm (Williams et al., 2016) for trajectory optimization. In Figure 3, we consider MPC and the full POLO algorithm of the same horizon, and compare their performance after T steps of learning in the world. We find that POLO uniformly dominates MPC, indicating that the agent is consolidating experience from the world into the value function. With a short planning horizon, the humanoid getup task has a local solution where it can quickly sit up, but cannot discover a chain of actions required to stand upright. POLO's exploration allows the agent to escape the local solution, and consolidate the experiences to consistently stand up. To further test if the learned value function is task aligned, we take the value function trained with POLO, and use it with MPC *without any intermediate rewards*. Thus, the MPC is optimizing a trajectory of length $H = 64$ purely using the value function of the state after 64 steps. We observe, in Figure 3, that even in this case, the humanoid is able to consistently increase its height from the floor indicating that the value function has captured task relevant details. We note that a greedy optimization procedure with this value function does not yield good results, indicating that the learned value function is only approximate.

While the humanoid getup task presents a temporal complexity requiring a large planning horizon, the in-hand manipulation task presents a spatial complexity. A large number of time steps are not needed to manipulate the object, and a strong signal about progress is readily achieved. However, since the targets can change rapidly, the variance in gradient estimates can be very high for function approximation methods. Note that the trajectory optimizer is unaware that the targets can change, and attempts to optimize a trajectory for a fixed instance of the task. The value function consolidates experience over multiple target changes, and learns to give high values to states that are not just immediately good but provide a large space of affordances for the possible upcoming tasks.

3.3 TRAJECTORY OPTIMIZATION FOR VALUE FUNCTION LEARNING

Finally, we study if trajectory optimization can aid in accelerating and stabilizing value function learning. To do so, we again consider the humanoid getup task and study different variants of POLO. In particular, we vary the horizon (N) used for computing the value function targets in eq. (7). We

Figure 3: Performance as a function of planning horizon for the humanoid getup (left), and in-hand manipulation task (middle). POLO was trained for 12000 and 2500 environment timesteps, respectively. We test POLO with the learned terminal value function against pure MPC and compare average reward obtained over 3 trials in the getup task and 1000 steps in the manipulation task. On the right, a value function trained with POLO is used by MPC without per-time-step rewards. The agent's height increases, indicating a task-relevant value function. For comparison, we also include the trace of POLO with dense rewards and multiple trials (dashed vertical lines)

(a) POLO learning for different N-step horizons   (b) MPC with imperfect value function

Figure 4: Usefulness of trajectory optimization for value function learning. (a) illustrates that N-step trajectory optimization accelerates the learning of the value function. N=1 corresponds to fitted value iteration. A difference of 0.2 reward to MPC amounts to approximately 50% performance improvement. (b) value function trained for the nominal model (head size of 1.0) used with MPC for models with larger sizes.

observe that as we increase N, the agent learns the value function with fewer interactions with the world, as indicated in Figure 4(a). The benefit of using $N-$step returns for stable value function learning and actor-critic methods have been observed in numerous works (Mnih et al., 2016; Munos et al., 2016; Schulman et al., 2016), and our experiments reinforce these observations. The use of $N-$step returns help to traverse the bias-variance trade-off. Furthermore, due to the discounting, the contribution of $V(s_N)$ is made weaker and thus the targets are more stable. This mirrors ideas such as target networks (Mnih et al., 2015) commonly used to stabilize training.

As discussed earlier, longer horizons make trajectory optimization more tolerant to errors in the value function. To illustrate this, we take the value function trained with POLO on a nominal humanoid model, and perturb the model by changing the size of the head to model value function degradation. Figure 4(b) shows that a longer planning horizon can mitigate this degradation. This presents intriguing future possibility of using MPC to improve transfer learning between tasks or robot platforms.

4   RELATED WORK

Combining planning and learning Combining elements of planning and search with approximate value functions has recently been explored in discrete game domains recently by Silver et al. (2017); Anthony et al. (2017) among others, which use a MCTS planner informed by the value

function. In the domain of continuous control, Atkeson (1993) and Barto et al. (1995) use an offline trajectory library for action selection in real-time, but do not explicitly consider learning value functions. Zhong et al. (2013) consider the setting of learning value function to help MPC and found the contribution of value functions to be weak for the simple tasks considered in their work. Approaches such as cost shaping (Ng et al., 1999) can also be interpreted as hand specifying an approximate value function, and has been successfully employed with trajectory optimization (Tassa et al., 2012). However, this often require careful human design and task specific expertise which may not be available. An alternative set of approaches (Ross et al., 2011; Levine & Koltun, 2013; Mordatch & Todorov, 2014) explore using local trajectory optimization to generate a dataset for training a global policy function via imitation learning. Such approaches employ trajectory optimization as an offline pre-processing procedure and require re-training for novel tasks or environments, although Kahn et al. (2017) propose propose an extension to online setting using MPC. However results from this line of work have been demonstrated predominantly in settings where trajectory optimizer alone can solve the task or has access to demonstration data. In contrast, through our exploration schemes, we are able to solve tasks where trajectory optimization does not succeed by itself.

Planning and exploration Exploration is a well-studied and important problem in reinforcement learning. Strategies such as ϵ-greedy or Gaussian exploration have recently been used to successfully solve a large number of dense reward problems. As the reward becomes sparse or heavily delayed, such strategies become intractable in high-dimensional settings. Parameter-space exploration (Plappert et al., 2017; Fortunato et al., 2017) methods do not explore at each time step, but rather generate correlated behaviors based on explored parameters at the start. However, such approaches do not consider exploration as an intentional act, but is rather a deviation from a well defined objective for the agent. Deep exploration strategies (Osband et al., 2013) sample a value function from the posterior and behave greedily using it. Approaches based on notions of intrinsic motivation and information gain (Chentanez et al., 2005; Stadie et al., 2015; Houthooft et al., 2016; Pathak et al., 2017) also explicitly introduce exploration bonuses into the agent's reward system. However, such approaches critically do not have the element of planning to explore; thus the agent may not actually reach regions of high predicted reward because it does not know how to get there. Our work is perhaps closest to the $E3$ framework of Kearns & Singh (2002) which considers altered MDPs with different reward functions, and executes the optimal action under that MDP. However solving these altered MDPs is expensive and their solution is quickly discarded. MPC on the other hand can quickly solve for local instance-specific solutions in these MDPs.

Model-free Reinforcement Learning Our work investigates how much training times can be reduced when the world model is known over model-free methods. A direct comparison for humanoid model tasks comes from Schulman et al. (2015) for both walking and getup. For walking, policy gradient based methods required 5.8 days of agent experience time, while our walking results were limited to a lifetime of 96 seconds; they do not present specifics but note that their getup required 4x the processing time. This is equivalent to 128 core hours vs POLO's 24. Similar policy gradient methods was applied to in-hand manipulation tasks by OpenAI (2018). Their method imbued a control policy with 3 years of simulated experience for object rotation, while our experiments needed 100 seconds of experience. For training time, they report approximately 500 CPU hours whereas POLO takes less than 1 CPU hour. Of course, model-free methods do not require an internal model, but our results suggest that much less experience may be required for the control aspect of the problem.

5 CONCLUSIONS AND FUTURE WORK

In this work we presented POLO, which combines the strengths of trajectory optimization and value function learning. In addition, we studied the benefits of planning for exploration in setting where we track uncertainties in the value function. Together, these components enabled solutions to complex control tasks like locomotion and hand manipulation, in under the equivalent of a few minutes of real-world experience and few hours of CPU core time. Combining POLO with parametric policy learning and improving the internal model from experience make for interesting future work.

REFERENCES

Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. In *Advances in Neural Information Processing Systems*, pp. 5360–5370, 2017.

Karl Johan Åström and Richard M. Murray. Feedback systems an introduction for scientists and engineers. 2004.

Christopher G. Atkeson. Using local trajectory optimizers to speed up global optimization in dynamic programming. In *NIPS*, 1993.

Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

Andrew G. Barto, Steven J. Bradtke, and Satinder P. Singh. Learning to act using real-time dynamic programming. *Artif. Intell.*, 72:81–138, 1995.

Dimitri Bertsekas and John Tsitsiklis. *Neuro-dynamic Programming*. 1996.

Nuttapong Chentanez, Andrew G Barto, and Satinder P Singh. Intrinsically motivated reinforcement learning. In *Advances in neural information processing systems*, pp. 1281–1288, 2005.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Ian Osband, Alex Graves, Vlad Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, et al. Noisy networks for exploration. *arXiv preprint arXiv:1706.10295*, 2017.

Carlos E. Garcia, David M. Prett, and Manfred Morari. Model predictive control: Theory and practice - a survey. *Automatica*, 25:335–348, 1989.

Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems*, pp. 1109–1117, 2016.

David Jacobson and David Mayne. *Differential Dynamic Programming*. American Elsevier Publishing Company, 1970.

Gregory Kahn, Tianhao Zhang, Sergey Levine, and Pieter Abbeel. Plato: Policy learning using adaptive trajectory optimization. In *Robotics and Automation (ICRA), 2017 IEEE International Conference on*, pp. 3342–3349. IEEE, 2017.

Michael Kearns and Satinder Singh. Near-optimal reinforcement learning in polynomial time. *Machine learning*, 49(2-3):209–232, 2002.

Vikash Kumar. *Manipulators and Manipulation in high dimensional spaces*. PhD thesis, University of Washington, Seattle, 2016. URL https://digital.lib.washington.edu/researchworks/handle/1773/38104.

Sergey Levine and Vladlen Koltun. Guided policy search. In *ICML*, 2013.

Lihong Li, Wei Chu, John Langford, and Robert E. Schapire. A contextual-bandit approach to personalized news article recommendation. In *WWW*, 2010.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *ICML*, 2016.

Igor Mordatch and Emanuel Todorov. Combining the benefits of function approximation and trajectory optimization. In *RSS*, 2014.

Rémi Munos and Csaba Szepesvári. Finite-time bounds for fitted value iteration. *Journal of Machine Learning Research*, 2008.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc G. Bellemare. Safe and efficient off-policy reinforcement learning. In *NIPS*, 2016.

Andrew Y. Ng, Daishi Harada, and Stuart J. Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *ICML*, 1999.

OpenAI. Learning dexterous in-hand manipulation. *CoRR*, abs/1808.00177, 2018.

Ian Osband, Daniel Russo, and Benjamin Van Roy. (more) efficient reinforcement learning via posterior sampling. In *Advances in Neural Information Processing Systems*, pp. 3003–3011, 2013.

Ian Osband, John Aslanides, and Albin Cassirer. Randomized prior functions for deep reinforcement learning. *CoRR*, abs/1806.03335, 2018.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning (ICML)*, volume 2017, 2017.

Matthias Plappert, Rein Houthooft, Prafulla Dhariwal, Szymon Sidor, Richard Y Chen, Xi Chen, Tamim Asfour, Pieter Abbeel, and Marcin Andrychowicz. Parameter space noise for exploration. *arXiv preprint arXiv:1706.01905*, 2017.

Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635, 2011.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *ICLR*, 2016.

David Silver, Aja Huang, Chris J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Vedavyas Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy P. Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *Nature*, 529:484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354, 2017.

Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

Wen Sun, J. Andrew Bagnell, and Byron Boots. Truncated horizon policy search: Combining reinforcement learning imitation learning. *CoRR*, abs/1805.11240, 2018.

Yuval Tassa, Tom Erez, and Emanuel Todorov. Synthesis and stabilization of complex behaviors through online trajectory optimization. In *Intelligent Robots and Systems (IROS), 2012 IEEE/RSJ International Conference on*, pp. 4906–4913. IEEE, 2012.

Emanuel Todorov and Weiwei Li. A generalized iterative lqg method for locally-optimal feedback control of constrained nonlinear stochastic systems. In *ACC*, 2005.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.

Grady Williams, Paul Drews, Brian Goldfain, James M Rehg, and Evangelos A Theodorou. Aggressive driving with model predictive path integral control. In *Robotics and Automation (ICRA), 2016 IEEE International Conference on*, pp. 1433–1440. IEEE, 2016.

Mingyuan Zhong, Mikala Johnson, Yuval Tassa, Tom Erez, and Emanuel Todorov. Value function approximation and model predictive control. In *Adaptive Dynamic Programming And Reinforcement Learning (ADPRL), 2013 IEEE Symposium on*, pp. 100–107. IEEE, 2013.

Figure 5: Overview of POLO framework and its components.

A   APPENDIX: EXPERIMENTAL DETAILS, HUMANOID

The model used for the humanoid experiments was originally distributed with the Todorov et al. (2012) software package and modified for our use. The model nominally has 27 degrees of freedom, including the floating base. It utilizes direct torque actuation for control, necessitating a small timestep of 0.008. The actuation input is limited to ±1.0, but the original gear ratios is left unchanged.

For POLO, the choice of inputs for the value function involves a few design decisions. We take inspiration from robotics, by using only easily observed values.

Dims.	Observation
6	Direction & Normal Vector, Torso
3	Direction Vector, Neck to R. Hand
3	Direction Vector, Neck to L. Hand
3	Direction Vector, Hip to R. Foot
3	Direction Vector, Hip to L. Foot
5	Height, Root, Hands, & Feet
6	Root Velocities
5	Touch Sensors, Head, Hands, & Feet

Value	Parameter
0.99	γ discount Factor
64	Planning Horizon Length
120	MPPI Rollouts
0.2	MPPI Noise σ
1.25	MPPI Temperature

For value function approximation in POLO for the humanoid tasks, we use an ensemble of 6 neural networks, each of which has 2 layers with 16 hidden parameters each; *tanh* is used for non-linearity. Training is performed with 64 gradient steps on minibatches of size 32, using ADAM with default parameters, every 16 timesteps the agent experiences.

In scenarios where the agent resets, we consider a horizon of 600 timesteps with 20 episodes, giving a total agent lifetime of 12000 timesteps or 96 seconds. When we consider no resets, we use the same total timesteps. A control cost is shared for each scenario, where we penalize an actuator's applied force scaled by the inverse of the mass matrix. Task specific rewards are as follows.

A.1   HUMANOID GETUP

In the getup scenario, the agent is initialized in a supine position, and is required to bring its root height to a target of 1.1 meters. The reward functions used are as follows. In the non-sparse case, the difficulty in this task is eschewing the immediate reward for sitting in favor of the delayed reward of standing; this sequence is non-trivial to discover.

$$R(s) = \begin{cases} 1.0 - (1.1 - Root_z), & \text{if } Root_z \leq 1.1 \\ 1.0, & \text{otherwise} \end{cases}, R_{sparse}(s) = \begin{cases} 0.0, & \text{if } Root_z \leq 1.1 \\ 1.0, & \text{otherwise} \end{cases}$$

A.2   HUMANOID WALK

In the walking scenario, the agent is initialized in an upright configuration. We specify a reward function that either penalizes deviation from a target height of 1.1 meters, or penalizes the deviation from both a target speed of 1.0 meters/second and the distance from the world's x-axis to encourage the agent to walk in a straight line. We choose a target speed as opposed to rewarding maximum

speed to encourage stable walking gaits.

$$R(s) = \begin{cases} -(1.1 - Root_z), & \text{if } Root_z \leq 1.1 \\ 1.0 - |1.0 - Vel_x| - |Root_x|, & \text{otherwise} \end{cases}$$

A.3 Humanoid Box

For the box environment, we place a 0.9 meter wide cube in front of the humanoid, which needs to be pushed to a specific point. The friction between the box and ground is very low, however, and most pushes cause the box to go sliding away; POLO learns to better limit the initial push to control the box to the target.

$$R(s) = \begin{cases} -(1.1 - Root_z), & \text{if } Root_z \leq 1.1 \\ 2.0 - ||Box_{xy} - Root_{xy}||_2, & \text{else if } |Box_{xy} - Root_{xy}|_2 > 0.8 \\ 4.0 - 2 * ||Box_{xy} - Target_{xy}||_2, & \text{otherwise} \end{cases}$$

In this setup, the observation vector increases with the global position of the box, and the dimensionality of the system increase by 6. The box initially starts 1.5 meters in front of the humanoid, and needs to be navigated to a position 2.5 meters in front of the humanoid.

B Appendix: Experimental Details, Hand Manipulation

We use the Adroit hand model (Kumar, 2016) and build on top of the hand manipulation task suite of Rajeswaran et al. (2018). The hand is position controlled and the dice is modeled as a free object with 3 transnational degrees of freedom and a ball joint for three rotational degrees of freedom.

B.1 In-hand Manipulation

For the in-hand manipulation task, the base of the hand is not actuated, and the agent controls only the fingers and wrist. The dice is presented to the hand initially in some randomized configuration, and the agent has to reorient the dice to the desired configuration. The desired configuration is randomized every 75 timesteps and the trajectory optimizer does not see this randomization. Thus the randomization can be interpreted as unmodified external disturbances to the system. We use a very simple reward function for the task:

$$R(s) = -0.5\, \ell_1(x_o, x_g) - 0.05\, \ell_{quat}(q_o, q_g) \tag{8}$$

x_o and x_g are the Cartesian positions of the object (dice) and goal respectively. ℓ_1 is the L1 norm. q_o and q_g are the orientation configurations of object and goal, respectively, and expressed as quaternions with ℓ_{quat} being the quaternion difference. If the hand drops the object, since there is no mechanism for it to reach the object, we consider a reset scenario where the dice is again dropped into the hand at a random configuration.

B.2 Pickup and Reorient

In the pickup and reorient setting, we also actuate the base so that the hand can pick up objects and take them to desired positions and orientations. In this setting, we add an additional term to the reward to encourage the hand to reach the object.

$$R(s) = -0.1\, \ell_1(x_o, x_p) - 0.5\, \ell_1(x_o, x_g) - 0.05\, \ell_{quat}(q_o, q_g) \tag{9}$$

where x_p is the cartesian position of the palm of the hand.

B.3 Hyperparameters

We use 80 trajectories in MPPI with temperature of 10. We use an ensemble of 6 networks with 2 layers and 64 units each. The value function is updated every 25 steps of interaction with the world, and we take 16 gradient steps each with a batch size of 16. These numbers were arrived at after a coarse hyperparameter search, and we expect that better hyperparameter settings could exist.

C LEMMA 2

Sun et al. (2018) propose and arrive at the bound in Lemma 2 in the context of imitation learninag and reward shaping. In their proof, they assume that a policy can simultaneously optimize the approximate value function over H steps, which may not be possible for a parametric policy class. Since we consider MPC which is a non-parametric method (in the global sense), MPC can indeed simultaniously optimize for H steps using $\hat{V}$. We provide the proof of the Lemma based on the work of Sun et al. (2018) that is consistent with our notations.

Let $\hat{\tau}$ and τ^* represent the trajectories of length H that would be generated by applying $\hat{\pi}$ and π^* respectively on the MDP. Starting from some state s, we have:

$$V^*(s) - V^{\hat{\pi}}(s) = \mathbb{E}_{\tau^*}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^*(s_H)\right] - \mathbb{E}_{\hat{\tau}}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^{\hat{\pi}}(s_H)\right] \tag{10}$$

Adding and subtracting, $\mathbb{E}_{\hat{\tau}}[\sum_t \gamma^t r_t + \gamma^H V^*(s_H)]$, we have:

$$\begin{aligned}
V^*(s) - V^{\hat{\pi}}(s) = {}& \gamma^H \mathbb{E}_{\hat{\tau}}\left[V^*(s_H) - V^{\hat{\pi}}(s_H)\right] \\
& + \mathbb{E}_{\tau^*}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^*(s_H)\right] - \mathbb{E}_{\hat{\tau}}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^*(s_H)\right].
\end{aligned} \tag{11}$$

Since $\max_s |\hat{V}(s) - V^*(s)| = \epsilon$, we have:

$$\mathbb{E}_{\tau^*}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^*(s_H)\right] \leq \mathbb{E}_{\tau^*}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H \hat{V}(s_H)\right] + \gamma^H \epsilon \tag{12}$$

$$\mathbb{E}_{\hat{\tau}}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H V^*(s_H)\right] \geq \mathbb{E}_{\hat{\tau}}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H \hat{V}(s_H)\right] - \gamma^H \epsilon \tag{13}$$

Furthermore, since $\hat{\tau}$ was generated by applying $\hat{\pi}$ which optimizes the actions using $\hat{V}$ as the terminal value function, we have:

$$\mathbb{E}_{\hat{\tau}}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H \hat{V}(s_H)\right] \geq \mathbb{E}_{\tau^*}\left[\sum_{t=0}^{H-1}\gamma^t r_t + \gamma^H \hat{V}(s_H)\right] \tag{14}$$

using these bounds, we have:

$$\begin{aligned}
V^*(s) - V^{\hat{\pi}}(s) &\leq \gamma^H \mathbb{E}_{\hat{\tau}}\left[V^*(s_H) - V^{\hat{\pi}}(s_H)\right] + 2\gamma^H \epsilon \\
&\leq 2\gamma^H \epsilon \left(1 + \gamma^H + \gamma^2 H + \ldots\right) \\
&= \mathcal{O}\left(\frac{\gamma^H \epsilon}{1 - \gamma^H}\right)
\end{aligned} \tag{15}$$

by recursively applying the first bound to $V^*(s_H) - V^{\hat{\pi}}(s_H)$. This holds for all states, and hence for any distribution over states.