CENSORING REPRESENTATIONS WITH MULTIPLE-ADVERSARIES OVER RANDOM SUBSPACES

ABSTRACT

Adversarial feature learning (AFL) is one of the promising ways for explicitly constrains neural networks to learn desired representations; for example, AFL could help to learn anonymized representations so as to avoid privacy issues. AFL learn such a representations by training the networks to deceive the adversary that predict the sensitive information from the network, and therefore, the success of the AFL heavily relies on the choice of the adversary. This paper proposes a novel design of the adversary *multiple adversaries over random subspaces* (MARS) that instantiate the concept of the *volunerableness*. The proposed method is motivated by an assumption that deceiving an adversary could fail to give meaningful information if the adversary is easily fooled, and adversary rely on single classifier suffer from this issues. In contrast, the proposed method is designed to be less vulnerable, by utilizing the ensemble of independent classifiers where each classifier tries to predict sensitive variables from a different *subset* of the representations. The empirical validations on three user-anonymization tasks show that our proposed method achieves state-of-the-art performance. This is significant because it gives new implications about designing the adversary, which is important to improve the performance of AFL.

1 INTRODUCTION

Since its invention over ten years ago (Hinton et al., 2006), deep neural networks (DNN) have shown significant performance improvements in various fields. When we apply DNN or more general machine learning techniques to real-world data, one of the key challenges is how to systematically incorporate the desired constraints into the learned representations in a controllable manner. For example, when practitioners apply these techniques to the data that contain a lot of user information (such as images with username (Edwards & Storkey, 2016) or data of wearables (Iwasawa et al., 2017)), the desired representations should not contain user-information that may result in privacy issues. Moreover, for legal and ethical reasons, machine learning algorithms have to make fair decisions, which do not rely on sensitive variables such as gender, age, or race (Louizos et al., 2016; Edwards & Storkey, 2016). Such a background requires removal of information related to specific factors (such as user ID, race, etc.) from the representation; this is called *censoring representations* in this paper.

One of the recently proposed approaches for censoring representation is *adversarial feature learning* (AFL) (Edwards & Storkey, 2016; Iwasawa et al., 2017; Xie et al., 2017), which employs the adversarial training framework to constrain the representations (Figure 1-a). Specifically, AFL considers an adversarial classifier who attempts to predict sensitive variables from the representations of a DNN and simultaneously trains the DNN to deceive the classifier. By alternatively or jointly (using gradient reversal layer proposed by Ganin & Lempitsky (2015)) training the adversary and DNN in such a manner, AFL ensures that there is little or no information about the sensitive variables in the representations.

Although some previous studies report significant performance improvements of the AFL in the context of censoring representations, the success of the AFL depends on the choice of the adversarial classifier. For example, if we use a logistic regression as the adversarial classifier, AFL can only eliminate the information that is linearly separated in the representation spaces and cannot remove any non-linear dependency. It is also possible that deceiving a classifier is too easy as suggested

Figure 1: Multiple Adversaries over Random Subspaces (MARS) for censoring representations: (a)AFL with an adversary, (b) AFL with MARS. MARS is designed to have diverse-view and to be less vulnerable to meaningless update of the encoder E.

by adversarial example studies , resulting in poor performance improvements of AFL. As such, the design of adversary is crucial for the performance of AFL; however, existing studies fail to address how to design the adversary for improving the quality of AFL.

In this paper, we propose a novel design of adversary for improving the performance of AFL, *multiple-adversaries over random subspace* (MARS), which consider the *vulnerableness* of the adversary. The term vulnerableness indicates how the target networks (encoder in Figure 1-a) easily fool the adversarial classifier. The proposed design is motivated by the recent report (Iwasawa et al., 2017) that is just increasing the capacity of adversary did not successfully improves the performance of AFL (Iwasawa et al., 2017), and an assumption that deceiving the adversary gives no/wrong information if the adversary is too easy to be fooled. The proposed method, incorporate multiple adversaries where each adversary tries to predict sensitive variables from a different *subset* of the representations. This design makes adversary less vulnerable to the update of the encoder since the encoder need to in a set of diverse adversaries. In this paper, we validate the effectiveness of the proposed design by empirically showing that (1) MARS archives better performance compared to baselines (that uses a single adversary and multiple adversaries over the entire representation spaces), and (2) MARS improve the vulnerableness compared to the baselines.

The primary contributions of this paper are as follows:

- This is the first study verifying the importance of the design of adversary in AFL and proposes the novel design for improving AFL. This is significant because the results suggest that design of adversary is vital for the performance of adversary, and gives new implications about designing the adversary in AFL, which is important to improve the performance of AFL. It is worth mentioning that, except our paper, all existing studies focus only on the *accuracy/capacity* for designing adversaries, which is not enough for improving the performance of AFL as shown in this paper.

- The proposed method achieved state-of-the-art performance in the task of censoring representations, which is essential to extend the applicability of DNN to many real-world applications. The empirical validation using three user-anonymization tasks shows that the proposed method allows the learning of significantly more anonymized representations with negligible performance degradation. Specifically, the probability of correctly predicting the user ID from learned representations is more than 0.07 points better on average than that of a single adversary and multiple adversaries over entire representation spaces.

2 PROBLEM DEFINITION AND RELATED WORKS

2.1 PROBLEM DEFINITION: CENSORING REPRESENTATIONS

Censoring representation means obtaining unbiased features. Here, *unbiased features* are features that are less affected by S, where S is a random variable that we want to remove from the data for some reason. One typical reason is related to fairness or privacy, which requires the output of neural networks not to be affected by unfair information or not contain user information.

It should be noted that poor design of the censoring procedure significantly reduces the utility of data. For example, the output of random mapping f_{rand} apparently has no information about S,

but it also gives no information about target Y. Alternatively, as a more realistic example, a neural network with limited capacity possibly acquires less information about S, but it may also result in poorer performance. Therefore, the primary goal of censoring representation is to obtain an encoder E that reduces information about S, while maintaining information about Y. Formally, the task can be written as a joint optimization problem of the loss:

$$J = L(E(X), Y) - \lambda V(E(X), S),$$

where X indicates the input random variable, E is an encoder that transforms X to representation R, λ is the weighting parameter, and V and L are loss functions that represent how much information about S and Y is present, respectively. Note that S can be any form of variable such as binary variable, categorical variable, or continuous variable. In this paper, we especially consider a special variant of censoring representation tasks, where we learn E with deep neural networks and S is the user ID (anonymization tasks).

2.2 RELATED WORKS: ADVERSARIAL FEATURE LEARNING

A recently proposed approach for the censoring representation task is *adversarial feature learning* (AFL). In AFL, $V(E(X), S)$ is measured by an external neural network D, i.e., if the external networks can accurately predict S from R, AFL regards that R has too much information about S and if it is difficult to accurately predict S, AFL regards that R has little or no information about S. The external network D is called discriminator or adversary in this context. The information is used to update the weights of the encoder E so that the updated representations have less information about S. Formally, AFL solves the joint optimization problems:

$$\min_{E,M} \max_{D} \mathbb{E}[-\log q_M(y|h = E(x)) + \lambda \log q_D(s|h = E(x))],$$

where $M : R \to Y$ is the label classifier, $D : R \to S$ is the adversarial classifier (see Figure 1), and q_M and q_D are conditional distributions parameterized by M and D, respectively. The optimization procedure is called adversarial training because E and D are in an adversarial relationship (E tries to minimize of log-likelihood q_D and D tries to maximize it).

To the best of the authors knowledge, the adversarial training framework was first introduced by (Schmidhuber, 1992), and later re-invented by (Goodfellow et al., 2014) in the context of an image-generation task. In the context of censoring representations, Edwards & Storkey (2016) first proposed the use of adversarial training to remove sensitive information from the representations. They show its efficacy for fair classification tasks (S is binary) compared to an LFR (Learned Fair Representation) proposed by Zemel et al. (2013) that regularizes the l_1 distance between the distributions for data with different S. Iwasawa et al. (2017) first applied the adversarial training to learn anonymized representations on the data of wearables, where S is categorical. More recently, Xie et al. (2017) first introduced the notion of *adversarial feature learning* and showed superior performances compared to variational fair auto-encoder (Louizos et al., 2016).

Although AFL already shows state-of-the-art performance to learn unbiased representations, how to improve its performance is still a challenge, which is tackled in this paper. This work is motivated by previous studies conducted by Iwasawa et al. (2017). They reported that simply using high-capacity networks as an adversary (such as deep neural networks) sometimes *fails* to improve the performance; on the other hand, the leaned representations are still highly biased if the adversary does not have enough capacity. Our work can be regarded as introduction of the novel design consideration (i.e., vulnerableness) of adversary for improving the quality of AFL and validation of it by proposing a method that instantiate the concept, which is not done in the previous works.

It is worth mentioning that the concept of multiple adversaries itself is already proposed and verified in the context of the image generation with adversarial training (Durugkar et al., 2017), and this paper does not insist that using multiple adversaries is the primal novelty. From the methodological perspective, the proposed method (MARS) can be seen as an extension of the concept of multiple adversaries by introducing the concept of diversity, and we verify that this extension is important in the context of censoring representations. Though the primary focus of this paper is limited to the context of adversarial feature learning, we further discuss the applicability of the proposed method on the other application of adversarial training, such as image/text generation (Goodfellow et al., 2014; Zhang et al., 2017) or domain adaptation(Ganin & Lempitsky, 2015); this is done at the end of this paper.

3 MULTIPLE-ADVERSARIES OVER RANDOM SUBSPACES

The proposed method, *multiple-adversaries over random subspaces (MARS)*, considers multiple adversaries where each adversary is in charge of different subsets of features. The development of MARS is motivated by the assumption that the adversary should not be vulnerable and it could be achieved by enforcing the adversary to have diverse view. In the experiment parts, we will empirically validates the importance of the design by showing that (1) MARS gives superior performances compared to the method with single adversary or that of simple ensemble of adversaries without enforcing adversaries to have diverse view, and (2) using ensemble of independent classifiers as adversary actually makes the the adversary robust. Figure 1 shows the comparison of overall architectures of between AFL with an adversary, and with multiple adversaries over random subspaces. Since the primary difference between naive AFL and MARS is how to build the adversary (training adversaries) and how to use the information of adversary (training encoders), the explanation is focused on the part.

3.1 TRAINING ADVERSARIES

There are many possible options to select a subspace; however, this paper specifically considers the case where each subspace is randomly selected. Suppose that n is the number of dimensions of representation $R \in \mathbb{R}^n$, and K is the number of adversaries. In MARS, each adversary D_k is trained to predict S over a randomly selected subset of features R^k, whose dimension is m_k and $m_k < n$. Each adversary is trained to maximize the expected log-likelihood. Formally, the optimization problem for D_k is as follows

$$\max_{\theta_{D_k}} \mathbb{E}[\log q_{D_k}(s|h_k = Sub_k(E(x)))], \tag{1}$$

where Sub_k is a function that return the subset of R, which is fixed before the training. Specifically, each Sub_k determine whether to remove the i-th dimension of R with the probability of α. The θ_{D_k} is the parameter of D_k.

3.2 TRAINING ENCODER

The adversaries are then integrated and a single prediction is made to train the encoder. Formally, the probability distribution of $q_D(s = s_i|h = E(x))$ is parameterized by an ensembled adversary D:

$$q_D(s = s_i|h = E(x)) = \frac{1}{K} \sum_k^K q_{D_k}(s|h_k), \tag{2}$$

which means, the predictions of adversaries D_k are integrated by averaging the predictions. Note that integration operator F is not essential to be the averaging, it may be the max operator or the soften version of the max operator proposed in (Durugkar et al., 2017).

The encoder is trained for minimizing the log-likelihood of Eq.2 and negative log-likelihood $q_M(y|h)$. Formally,

$$\min_{\theta_E, \theta_M} \mathbb{E}[-\log q_M(y|h) + \lambda \log \frac{1}{K} \sum_k^K q_{D_k}(s|h_k)], \tag{3}$$

where θ_E and θ_M are the parameter of E and M respectively. The overall algorithm is shown in Algorithm 1.

4 EXPERIMENTS

4.1 DATASETS

We used two datasets to demonstrate the efficacy of MARS. Both datasets are related to human activity recognition using the data of wearables, where privacy issues have recently been pointed out by (Iwasawa et al., 2017). In both datasets, the task is to learn anonymized representations (R that does not contain user-identifiable information), while maintaining classification performance.

Algorithm 1 Optimization of the proposed model

Require: parameter λ, α
   Initialize Sub_k for all $k \in 1 \cdots K$ based on α
   Initialize neural networks $\{E, M, D_1, \cdots D_K\}$
   while training() **do**
      Update weights of D_k for all $k \in 1 \cdots K$ (eq. 1)
      Update weights of E and M (eq. 3)
   end while

The opportunity recognition dataset (Sagha et al., 2011) consists of sensory data regarding human activity in a breakfast scenario, and the task is to predict the activity performed by a user. A wide variety of body-worn, object-based, and ambient sensors are used (see Figure 1 in Sagha et al. (2011) for more details). Each record consists of 113 real-value sensory readings, excluding time information. We considered two recognition tasks: gesture recognition (Opp-G) and locomotion recognition (Opp-L). Opp-G requires the recognition of 18 class activities [1], while Opp-L requires the recognition of 4 class locomotion-activities, i.e., stand, walk, sit, and lie. Given a sampling frequency of 30 Hz, the sliding window procedure with 30 frames and a 50% overlap produced 57,790 samples. We used data of subjects 2–4 as training/validation sets (90% for training and 10% for validation) and that of subject 1 as test sets.

The USC-HAD dataset (Zhang & Sawchuk, 2012) is a relatively new benchmark dataset, which contains a relatively large number of subjects (14 subjects: 7 males and 7 females). There are 12 activity classes corresponding to the most basic and common activities of people's daily lives [2]. MotionNode, which is a 6-DOF inertial measurement unit specially designed for human motion sensing applications, is used to record the outputs from accelerometers that record 6 real sensory values. The sliding window procedure, using 30 frames and a 50% overlap, produced 172,169 samples. We used data of subjects 1–10 as training/validation sets (90% for training and 10% for validation) and that of subjects 11–14 as test sets.

4.2 EXPERIMENTAL SETTING

In all experiments, we parameterized the encoder E by convolutional neural networks (CNN) with three convolution-ReLU-pooling repeats followed by one fully connected layer and M by a logistic regression, in accordance with a previous study (see Figure 2 in Iwasawa et al. (2017) for more details). Every component of the network was trained with the Adam algorithm (learning rate is set to 0.0001) (Kingma & Ba, 2015) (150 epochs). In the optimization, we used the annealing heuristics to weighting parameter λ in accordance with (Iwasawa et al., 2017); we linearly increased λ during 15 epochs to 135 epochs of training.

Following previous works, we evaluated the level of anonymization by training a classifier f_{eva} that tries to predict S over learned representations. This means that we regarded that a learned representation is anonymized well if we could not build an accurate classifier. Unless mentioned otherwise, we use a multi-layer perceptron with 800 hidden units as f_{eva}. We later discuss how the choice of classifier for f_{eva} and D affects the results by performing empirical evaluations.

To demonstrate the efficacy of the proposed method, we compare the following four methods and its variants: (1) None: w/o adversary (correspond to normal CNN), (2) Adv: w/ a single adversary, (3) MA: w/ multiple adversaries where each adversary tries to predict from the entire space, and (4) MARS: w/ multiple adversaries where each adversary tries to predict from a different subspace of the entire space. Each adversary is parametrized by multi-layer perceptron (MLP) with 800 hidden units. If we need to express the type of adversary, we denote it by a suffix. For example, Adv-LR means an adversary is parametrized by a logistic regression. Without mentioning otherwise, we set the number of adversaries K as 10 for MA and MARS, and α for determine size of the subset as 0.8.

---

[1] open door 1, open door 2, close door 1, close door 2, open fridge, close fridge, open dishwasher, close dishwasher, open drawer 1, close drawer 1, open drawer 2, close drawer 2, open drawer 3, close drawer 3, clean table, drink from cup, toggle switch, and Null

[2] walking forward, walking left, walking right, walking upstairs, walking downstairs, running forward, jumping, sitting, standing, sleeping, elevator up, elevator down

Table 1: Performance comparison against various f_{eva}: (a, b, c) Accuracy on predicting s in Opp-G, Opp-L, and USC-HAD datasets respectively, and (d)Accuracy on predicting y in each datasets.

(a) Opp-G

	LR	MLP$_1$	MLP$_2$	DNN
None	0.806	0.936	0.971	0.968
Adv-LR	0.513	0.934	0.970	0.965
Adv	**0.479**	0.676	0.865	0.960
Adv$_2$	**0.472**	0.672	0.853	0.955
Adv$_5$	0.602	0.842	0.939	0.933
Adv-DNN	0.495	0.689	0.900	0.903
MA	0.571	0.782	0.922	0.942
MA-DNN	0.526	0.755	0.924	0.962
MARS	0.494	**0.589**	**0.777**	**0.817**
MARS-DNN	0.546	**0.636**	**0.835**	**0.820**

(b) Opp-L

	LR	MLP$_1$	MLP$_2$	DNN
None	0.839	0.937	0.970	0.966
Adv-LR	0.583	0.925	0.971	0.964
Adv	**0.481**	**0.615**	0.805	0.932
Adv$_2$	0.593	0.811	0.934	0.928
Adv$_5$	0.610	0.775	0.910	0.910
Adv-DNN	**0.484**	0.712	0.879	0.945
MA	0.527	0.744	0.905	0.949
MA-DNN	0.541	0.726	0.873	0.904
MARS	0.515	0.638	**0.791**	**0.850**
MARS-DNN	0.500	**0.615**	**0.781**	**0.866**

(c) USC-HAD

	LR	MLP$_1$	MLP$_2$	DNN
None	0.655	0.741	0.809	0.808
Adv-LR	**0.275**	0.511	0.721	0.774
Adv	0.325	0.513	0.703	0.762
Adv$_2$	0.538	0.662	0.779	0.801
Adv$_5$	0.377	0.647	0.771	0.792
Adv-DNN	**0.295**	0.499	**0.668**	0.742
MA	0.326	0.603	0.743	0.783
MA-DNN	0.362	**0.497**	0.672	**0.740**
MARS	0.354	**0.482**	0.692	0.751
MARS-DNN	0.364	0.498	**0.655**	**0.680**

(d) Accuracy on predicting y

	Opp-G	Opp-L	USC	Ave
None	0.796	0.828	0.537	0.720
Adv-LR	0.805	0.820	0.535	0.720
Adv	0.805	0.808	0.540	0.718
Adv$_2$	0.803	0.823	0.521	0.716
Adv$_5$	0.805	0.827	0.529	0.721
Adv-DNN	0.804	0.797	0.532	0.711
MA	0.802	0.792	0.528	0.708
MA-DNN	0.776	0.791	0.513	0.694
MARS	0.802	0.824	0.528	0.718
MARS-DNN	0.804	0.815	0.511	0.710

As expected from equation 3, the selection of weighting hyper-parameter λ greatly affects the performances. Without mentioning otherwise, we optimized the λ from $\{0.01, 0.02, 0.05, 0.10, 0.20, 1.0\}$ for each baseline for the fair comparison. Specifically, we select the λ that did *not* significantly harm Y-accuracy (specifically, 5% or less degradation against None) and maxmize the level of anonymization. The selected λ for each baseline is listed in appendix A.

4.3 EXPERIMENTAL RESULTS

The results for the three tasks are shown in Table 1. Table 1-a,b, and c lists the user classification accuracy when different adversarial classifiers D and evaluator f_{eva} are used. In addition to None, Adv, MA, MARS, we compared a logistic repression (Adv-LR), DNNs with 400-200 hidden units, ensemble of DNNs (MA-DNN), and ensemble of DNNs over random subspaces (MARS-DNN) for E. Adv$_2$ and Adv$_5$ correspond to the case where we train an adversary with MLP 2 iterations or 5 iterations against one iteration for training encoder E. For evaluator f_{eva}, we tested LR, multi-layer perceptron with 50 hidden units (MLP$_1$), multi-layer perceptron with 800 hidden units (MLP$_2$), and deep neural networks with 400-200 hidden units. The best performance in each combination of datasets and f_{eva} is highlighted in underline and bold, and the second best performance is highlighted in bold.

We can make the following observations. (1) For small-capacity evaluator (LR), single adversary (Adv and its variants) marks superior performances to MA and MARS. However, the method with single adversary tend to give poor performance for the stronger adversary (MLP$_2$ or DNN). (2) For high-capacity evaluator (MLP$_2$ or DNN), the proposed method clearly outperforms baseline methods. Specifically, in the case when the evaluator is DNN, MARS and MARS-DNN marks 0.806 and 0.789 in average of U-accuracy, which is significantly better than best baseline Adv-DNN (0.863 in average of U-accuracy). (3) Increasing the iterations of training adversary doesn't pay off, as shown in the poor performance improvements of Adv$_2$ or Adv$_5$ against Adv.

In addition to the quantitative evaluation, we also give qualitative evaluation by visualizing the learned representations using t-SNE (Maaten & Hinton, 2008) (Figure 2). Specifically, we randomly sample 1,000 examples from the validation sets, and reduce the dimension of data by using principal component analysis over the output of the E to speed up the computations and suppress some noise. The number of components is selected such that the amount of variance that needs to be explained is greater than 95%. The selected number of components is mentioned on top of each figure. Each colar (and marker) denotes different users ($|S|$=3). The results show that the representations learned

Figure 2: t-SNE visualizations of samples in the Opp-G (original dimension is 400).

(a) Variance of discriminators

(b) Accuracy of D during training

(c) $-\log q_{D_k}$ before updating E

(d) Effect of D to the update of E

Figure 3: Comparison of different representations on three anonymization tasks. Anonymized representation should lead to low accuracy on predicting user ID (a) while keeping accuracy on predicting Y (b). The dotted line of each figure shows the performance of None (w/o adversarial training).

with MARS provide qualitatively more plausive results; we can see that the data for different users lie in almost similar places in the representations of MARS; however, the representations of None, Adv-LR, and Adv, MA are partially clustered based on the users. Moreover, the representation of MARS require significantly small number of components to represent the leaned information, which possibly suggests that MARS eliminates unimportant information to a greater extent.

It is worth mentioning that the proposed method could be benefited from the variance reduction, because ensemble of diverse classifiers typically reduce the variance; however, empirical validations shows that the variance reduction is not main advantage of the proposed method. To be more specific, we calculated the variance of each adversary by training the classifier five times, and compute the variance of the activations before Softmax non-lineality of five trials (in Figure 3-a). The results shows that, MARS and MA the almost same variance, although MARS gives better performance compared to MA as shown in Table 1.

Figure 3-b compares the accuracy of D after updating E, and Figure 3-c shows the $-\log q_{D_k}$ before updating E. The results indicates that MARS and its variants tend to be more robust for update of E, giving more accurate information throughout the training. Note that, the accuracy of each type of adversary start almost same before starting adversarial training (15 epoch). Also, the accuracy of D itself could be controlled by changing λ, but it also reduce the effect of deceiving adversary.

Figure 3-d shows how the update of E affect the $-\log q_{D_k}$. Specifically, each line represent the average effect of the loss by the update E, and the shaded area represents the minimum and maximum loss, which means that larger shaded area indicates the higher variety of the D_k. The result demonstrates that the influences of the update to each adversary is more varied for MARS compared to MA, which implies the adversaries of higher α have more diversity and it make the D less vulnerable against the update.

Figures 4-a and b compares the performance between different K and α. Note that $\alpha = 0.0$ means the method using all feature spaces, which is actually MA. The results shows that (1) although there is no clear winner among the α, using subspaces gives lower accuracy on predicting S, (2)

$(a) - \log q_{D_k}$ $(b) - \log q_{D_k}$

Figure 4: Performance comparisons with different hyper-parameters: (a, b) Predicting accuracy on s and y with different K and α, (c) The performance of overall discriminator D during training, (d) The negative log-likelihood of each discriminator q_{D_k} during training.

the number of discriminator K effect accuracy on S while the accuracy on Y is robust to the K especially if $\alpha \neq 0$, indicating the possibility that the performance of AFL could be improved by incorporating multiple adversaries.

5 DISCUSSION AND CONCLUSION

This study proposed MARS, which incorporates multiple adversaries where each adversary has a different role, and conducted empirical validations on the efficacy of the proposed method for censoring representations, specifically user-anonymization for the data of wearables. Table 1 compares the proposed method and several baselines, and shows the efficacy of the proposed method against various evaluators. Figure 2 qualitatively shows that the proposed method provides well anonymized representations. Figure 3-d shows that the each adversary in MARS have diverse role, resulting MARS more robust to the update of E as a whole. All these results supports that the proposed method is more effective in removing the influence of a specific factor (user in experiments) compared to the previous methods.

One of the reason why MARS works well is that the adversary is designed to have diverse-views by incorporating random subspace methods, resulting the encoder need to be stronger to deceive the adversary. It is worth mentioning that the capacity or accuracy of the adversary is not the only a definitive factor that determine the success of the adversarial feature learning, as shown by the superior performance of MARS over MA that have $\frac{1}{1-\alpha}$ times larger capacity of MARS. Moreover, the final performance of AFL is significantly different even if the accuracy of D is fairly similar during training, as shown in Figure 3-b. As mentioned in the related work section, such knowledge is important to design the adversary in practice, and is not never mentioned in prior studies of adversarial feature learning.

Although this paper focused on the case where the subsets are randomly selected and fixed, this might not be necessary. One of the possible extensions is to determine subsets with more sophisticated ways (e.g., by performing clustering or soft-clustering on the representation spaces after few training iterations), or to learn how to select the subset itself by adding the criterion regarding diversity of adversaries. Also, it might be possible to realize the diversity of adversaries by methods other than subspace selection. One possible way is to constrain weights of two adversaries so that they are orthogonal view, which is used in semi-supervised learning using co-training (Saito et al., 2017), or it might be worth a try to adding different noises for each adversary.

It might be worth mentioning about applicability and implications of MARS for other applications of adversarial training, such as image generation. From the perspective of the applicability, the MARS itself does not rely on any domain-specific settings and is therefore general enough for many applications based on adversarial training. For example, we can build multiple-adversaries upon the subset of feature spaces (maybe not on the image spaces). This makes discriminator have diverse-view, so it might be useful for preventing *mode collapse* that is one of the well-known problems in image-generation with adversarial training. In the context of image-generation, Generative Multi Adversarial Networks proposed by Durugkar et al. (2017), which also use multiple adversaries, shows that multiple adversary is useful for generating better images, and for avoiding mode collapse. It might be interesting to see if enhancing the diversity of discriminators by preparing asymmetric adversaries as with this paper helps to generate better image or to avoid mode collapse better.

REFERENCES

Ishan Durugkar, Ian Gemp, and Sridhar Mahadevan. Generative multi-adversarial networks. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2017.

Harrison Edwards and Amos Storkey. Censoring representations with an adversary. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2016.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2015.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Proceedings of the Annual Conference on Neural Information Processing Systems (NIPS)*, pp. 2672–2680, 2014.

Geoffrey E Hinton, Simon Osindero, and Yee-Whye Teh. A fast learning algorithm for deep belief nets. *Neural computation*, 18(7):1527–1554, 2006.

Yusuke Iwasawa, Kotaro Nakayama, Ikuko Eguchi Yairi, and Yutaka Matsuo. Privacy issues regarding the application of dnns to activity-recognition using wearables and its countermeasures by use of adversarial training. In *Proceedings of the IJCAI*, pp. 1930–1936, 2017.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2015.

Christos Louizos, Kevin Swersky, Yujia Li, Max Welling, and Richard Zemel. The variational fair auto encoder. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2016.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9(Nov):2579–2605, 2008.

Hesam Sagha, Sundara Tejaswi Digumarti, José del R Millán, Ricardo Chavarriaga, Alberto Calatroni, Daniel Roggen, and Gerhard Tröster. Benchmarking classification techniques using the opportunity human activity dataset. In *Proceedings of the INSS*, pp. 36–40. IEEE, 2011.

Kuniaki Saito, Yoshitaka Ushiku, and Tatsuya Harada. Asymmetric tri-training for unsupervised domain adaptation. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2017.

Jürgen Schmidhuber. Learning factorial codes by predictability minimization. *Neural Computation*, 4(6):863–879, 1992.

Qizhe Xie, Zihang Dai, Yulun Du, Eduard Hovy, and Graham Neubig. Controllable invariance through adversarial feature learning. In *Proceedings of the Annual Conference on Neural Information Processing Systems (NIPS)*, 2017.

Rich Zemel, Yu Wu, Kevin Swersky, Toni Pitassi, and Cynthia Dwork. Learning fair representations. In *Proceedings of the 30th International Conference on Machine Learning (ICML)*, pp. 325–333, 2013.

Mi Zhang and Alexander A Sawchuk. USC-HAD: a daily activity dataset for ubiquitous activity recognition using wearable sensors. In *Proceedings of the International Joint Conference on Pervasive and Ubiquitous Computing (UbiComp)*, pp. 1036–1043. ACM, 2012.

Y. Zhang, Z. Gan, K. Fan, Z. Chen, R. Henao, D. Shen, and L. Carin. Adversarial feature matching for text generation. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2017.

A SELECTED HYPER PARAMETER

Table 2 shows the selected λ for each combination of datasets and baselines. Although the best hyper-parameter might be determined by the balance between $\log q_M$ and $\log q_D$, here we cannot see the obvious relationships between the best λ and the easiness of tasks.

Table 2: λ used in Table 1 and Figure 2.

	OppG	OppL	USC
Adv-LR	0.100	0.200	1.000
Adv	0.200	0.050	0.100
Adv$_2$	0.100	0.010	0.010
Adv$_5$	0.010	0.010	0.020
Adv-DNN	0.100	0.050	0.020
MA	0.200	0.200	0.020
MA-DNN	1.000	0.200	0.050
MARS	1.000	1.000	0.050
MARS-DNN	0.200	1.000	0.100