INFORMATION-DIRECTED EXPLORATION FOR DEEP REINFORCEMENT LEARNING

ABSTRACT

Efficient exploration remains a major challenge for reinforcement learning. One reason is that the variability of the returns often depends on the current state and action, and is therefore heteroscedastic. Classical exploration strategies such as upper confidence bound algorithms and Thompson sampling fail to appropriately account for heteroscedasticity, even in the bandit setting. Motivated by recent findings that address this issue in bandits, we propose to use Information-Directed Sampling (IDS) for exploration in reinforcement learning. As our main contribution, we build on recent advances in distributional reinforcement learning and propose a novel, tractable approximation of IDS for deep Q-learning. The resulting exploration strategy explicitly accounts for both parametric uncertainty and heteroscedastic observation noise. We evaluate our method on Atari games and demonstrate a significant improvement over alternative approaches.

1 INTRODUCTION

In Reinforcement Learning (RL), an agent seeks to maximize the cumulative rewards obtained from interactions with an unknown environment. Given only knowledge based on previously observed trajectories, the agent faces the exploration-exploitation dilemma: Should the agent take actions that maximize rewards based on its current knowledge or instead investigate poorly understood states and actions to potentially improve future performance. Thus, in order to find the optimal policy the agent needs to use an appropriate exploration strategy.

Popular exploration strategies, such as ϵ-greedy (Sutton & Barto, 1998), rely on random perturbations of the agent's policy, which leads to undirected exploration. The theoretical RL literature offers a variety of statistically-efficient methods that are based on a measure of uncertainty in the agent's model. Examples include upper confidence bound (UCB) (Auer et al., 2002) and Thompson sampling (TS) (Thompson, 1933). In recent years, these have been extended to practical exploration algorithms for large state-spaces and shown to improve performance (Osband et al., 2016a; Chen et al., 2017; O'Donoghue et al., 2018; Fortunato et al., 2018). However, these methods assume that the observation noise distribution is independent of the evaluation point, while in practice *heteroscedastic observation noise* is omnipresent in RL. This means that the noise depends on the evaluation point, rather than being identically distributed (*homoscedastic*). For instance, the return distribution typically depends on a sequence of interactions and, potentially, on hidden states or inherently heteroscedastic reward observations. Kirschner & Krause (2018) recently demonstrated that, even in the simpler bandit setting, classical approaches such as UCB and TS fail to efficiently account for heteroscedastic noise.

In this work, we propose to use Information-Directed Sampling (IDS) (Russo & Van Roy, 2014; Kirschner & Krause, 2018) for efficient exploration in RL. The IDS framework can be used to design exploration-exploitation strategies that balance the estimated instantaneous regret and the expected information gain. Importantly, through the choice of an appropriate *information-gain function*, IDS is able to account for parametric uncertainty and heteroscedastic observation noise during exploration.

As our main contribution, we propose a novel, tractable RL algorithm based on the IDS principle. We combine recent advances in distributional RL (Bellemare et al., 2017; Dabney et al., 2018b) and approximate parameter uncertainty methods in order to develop both homoscedastic and heteroscedastic variants of an agent that is similar to DQN (Mnih et al., 2015), but uses information-

directed exploration. Our evaluation on Atari 2600 games shows the importance of accounting for heteroscedastic noise and indicates that at our approach can substantially outperform alternative state-of-the-art algorithms that focus on modeling either only epistemic or only aleatoric uncertainty. To the best of our knowledge, we are the first to develop a tractable IDS algorithm for RL in large state spaces.

2 RELATED WORK

Exploration algorithms are well understood in bandits and have inspired successful extensions to RL (Bubeck & Cesa-Bianchi, 2012; Lattimore & Szepesvári, 2018). Many strategies rely on the "optimism in the face of uncertainty" (Lai & Robbins, 1985) principle. These algorithms act greedily w.r.t. an augmented reward function that incorporates an exploration bonus. One prominent example is the upper confidence bound (UCB) algorithm (Auer et al., 2002), which uses a bonus based on confidence intervals. A related strategy is Thompson sampling (TS) (Thompson, 1933), which samples actions according to their posterior probability of being optimal in a Bayesian model. This approach often provides better empirical results than optimistic strategies (Chapelle & Li, 2011).

In order to extend TS to RL, one needs to maintain a distribution over Markov Decision Processes (MDPs), which is difficult in general. Similar to TS, Osband et al. (2016b) propose randomized linear value functions to maintain a Bayesian posterior distribution over value functions. Bootstrapped DQN (Osband et al., 2016a) extends this idea to deep neural networks by using an ensemble of Q-functions. To explore, Bootstrapped DQN randomly samples a Q-function from the ensemble and acts greedily w.r.t. the sample. Fortunato et al. (2018) and Plappert et al. (2018) investigate a similar idea and propose to adaptively perturb the parameter-space, which can also be thought of as tracking an approximate parameter posterior. O'Donoghue et al. (2018) propose TS in combination with an uncertainty Bellman equation, which propagates agent's uncertainty in the Q-values over multiple time steps. Additionally, Chen et al. (2017) propose to use the Q-ensemble of Bootstrapped DQN to obtain approximate confidence intervals for a UCB policy. There are also multiple other ways to approximate parametric posterior in neural networks, including Neural Bayesian Linear Regression (Snoek et al., 2015; Azizzadenesheli et al., 2018), Variational Inference (Blundell et al., 2015), Monte Carlo methods (Neal, 1995; Mandt et al., 2016; Welling & Teh, 2011), and Bayesian Dropout (Gal & Ghahramani, 2016). For an empirical comparison of these, we refer the reader to Riquelme et al. (2018).

A shortcoming of all approaches mentioned above is that, while they consider parametric uncertainty, they do not account for heteroscedastic noise during exploration. In contrast, distributional RL algorithms, such as Categorical DQN (C51) (Bellemare et al., 2017) and Quantile Regression DQN (QR-DQN) (Dabney et al., 2018b), approximate the distribution over the Q-values directly. However, both methods do not take advantage of the return distribution for exploration and use ϵ-greedy exploration. Implicit Quantile Networks (IQN) (Dabney et al., 2018a) instead use a risk-sensitive policy based on a return distribution learned via quantile regression and outperform both C51 and QR-DQN on Atari-57. Similarly, Moerland et al. (2018) and Dilokthanakul & Shanahan (2018) act optimistically w.r.t. the return distribution in deterministic MDPs. However, these approaches to not consider parametric uncertainty.

Return and parametric uncertainty have previously been combined for exploration by Tang & Agrawal (2018) and Moerland et al. (2017). Both methods account for parametric uncertainty by sampling parameters that define a distribution over Q-values. The former then act greedily with respect to the expectation of this distribution, while the latter additionally samples a return for each action and then acts greedily with respect to it. However, like Thompson sampling, these approaches do not appropriately exploit the heteroscedastic nature of the return. In particular, noisier actions are more likely to be chosen, which can slow down learning.

Our method is based on Information-Directed Sampling (IDS), which can explicitly account for parametric uncertainty and heteroscedasticity in the return distribution. IDS has been primarily studied in the bandit setting (Russo & Van Roy, 2014; Kirschner & Krause, 2018). Zanette & Sarkar (2017) extend it to finite MDPs, but their approach remains impractical for large state spaces, since it requires to find the optimal policies for a set of MDPs at the beginning of each episode.

3 BACKGROUND

We model the agent-environment interaction with a MDP $(\mathcal{S}, \mathcal{A}, R, P, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ are the state and action spaces, $R(\mathbf{s}, \mathbf{a})$ is the stochastic reward function, $P(\mathbf{s}'|\mathbf{s}, \mathbf{a})$ is the probability of transitioning from state $\mathbf{s}$ to state $\mathbf{s}'$ after taking action $\mathbf{a}$, and $\gamma \in [0, 1)$ is the discount factor. A policy $\pi(\cdot|\mathbf{s}) \in \mathcal{P}(\mathcal{A})$ maps a state $\mathbf{s} \in \mathcal{S}$ to a distribution over actions. For a fixed policy π, the discounted return of action $\mathbf{a}$ in state $\mathbf{s}$ is a random variable $Z^\pi(\mathbf{s}, \mathbf{a}) = \sum_{t=0}^\infty \gamma^t R(\mathbf{s}_t, \mathbf{a}_t)$, with initial state $\mathbf{s} = \mathbf{s}_0$ and action $\mathbf{a} = \mathbf{a}_0$ and transition probabilities $\mathbf{s}_t \sim P(\cdot|\mathbf{s}_{t-1}, \mathbf{a}_{t-1}), \mathbf{a}_t \sim \pi(\cdot|\mathbf{s}_t)$. The return distribution Z statisfied the Bellman equation,

$$Z^\pi(\mathbf{s}, \mathbf{a}) \stackrel{D}{=} R(\mathbf{s}, \mathbf{a}) + \gamma Z^\pi(\mathbf{s}', \mathbf{a}'), \tag{1}$$

where $\stackrel{D}{=}$ denotes distributional equality. If we take the expectation of (1), the usual Bellman equation (Bellman, 1957) for the Q-function, $Q^\pi(\mathbf{s}, \mathbf{a}) = \mathbb{E}[Z^\pi(\mathbf{s}, \mathbf{a})]$, follows as

$$Q^\pi(\mathbf{s}, \mathbf{a}) = \mathbb{E}[R(\mathbf{s}, \mathbf{a})] + \gamma \mathbb{E}_{P,\pi}[Q^\pi(\mathbf{s}', \mathbf{a}')]. \tag{2}$$

The objective is to find an optimal policy π^* that maximizes the expected total discounted return $\mathbb{E}[Z^\pi(\mathbf{s}, \mathbf{a})] = Q^\pi(\mathbf{s}, \mathbf{a})$ for all $\mathbf{s} \in \mathcal{S}, \mathbf{a} \in \mathcal{A}$.

3.1 UNCERTAINTY IN REINFORCEMENT LEARNING

To find such an optimal policy, the majority of RL algorithms use a point estimate of the Q-function, $Q(\mathbf{s}, \mathbf{a})$. However, such methods can be inefficient, because they can be overconfident about the performance of suboptimal actions if the optimal ones have not been evaluated before. A natural solution for more efficient exploration is to use uncertainty information. In this context, there are two source of uncertainty. Parametric (*epistemic*) uncertainty is a result of ambiguity over the class of models that explain that data seen so far, while intrinsic (*aleatoric*) uncertainty is caused by stochasticity in the environment or policy, and is captured by the distribution over returns (Moerland et al., 2017).

Osband et al. (2016a) estimate *parametric uncertainty* with a Bootstrapped DQN. They maintain an ensemble of K Q-functions, $\{Q_k\}_{k=1}^K$, which is represented by a multi-headed deep neural network. To train the network, the standard bootstrap method (Efron, 1979; Hastie et al., 2001) constructs K different datasets by sampling with replacement from the global data pool. Instead, Osband et al. (2016a) trains all network heads on the exact same data and diversifies the Q-ensemble via two other mechanisms. First, each head $Q_k(\mathbf{s}, \mathbf{a}; \theta)$ is trained on its own independent target head $Q_k(\mathbf{s}, \mathbf{a}; \theta^-)$, which is periodically updated (Mnih et al., 2015). Further, each head is randomly initialized, which, combined with the nonlinear parameterization and the independently targets, provides sufficient diversification.

Intrinsic uncertainty is captured by the return distribution Z^π. While Q-learning (Watkins, 1989) aims to estimate the expected discounted return $Q^\pi(\mathbf{s}, \mathbf{a}) = \mathbb{E}[Z^\pi(\mathbf{s}, \mathbf{a})]$, distributional RL approximates the random return $Z^\pi(\mathbf{s}, \mathbf{a})$ directly. As in standard Q-learning (Watkins, 1989), one can define a distributional Bellman optimality operator based on (1),

$$\mathcal{T}Z(\mathbf{s}, \mathbf{a}) := R(\mathbf{s}, \mathbf{a}) + \gamma Z(\mathbf{s}', \arg\max_{\mathbf{a}' \in \mathcal{A}} \mathbb{E}[Z(\mathbf{s}', \mathbf{a}')]). \tag{3}$$

To estimate the distribution of Z, we use the approach of C51 (Bellemare et al., 2017) in the following. It parameterizes the return as a categorical distribution over a set of equidistant atoms in a fixed interval $[V_{\min}, V_{\max}]$. The atom probabilities are parameterized by a softmax distribution over the outputs of a parametric model. Since the parameterization Z_θ and the Bellman update $\mathcal{T}Z_\theta$ have disjoint supports, the algorithm requires an additional step Φ that projects the shifted support of $\mathcal{T}Z_\theta$ onto $[V_{\min}, V_{\max}]$. Then it minimizes the Kullback-Leibler divergence $D_{\mathrm{KL}}(\Phi\mathcal{T}Z_\theta||Z_\theta)$.

3.2 HETEROSCEDASTICITY IN REINFORCEMENT LEARNING

In RL, heteroscedasticity means that the variance of the return distribution Z depends on the state and action. This can occur in a number of ways. The variance $\mathrm{Var}(R|\mathbf{s}, \mathbf{a})$ of the reward function itself may depend on $\mathbf{s}$ or $\mathbf{a}$. Even with deterministic or homoscedastic rewards, in stochastic environments the variance of the observed return is a function of the stochasticity in the transitions

Figure 1: Gaussian Process setting. R: the true function, ρ^2: true observation noise variance, blue: confidence region with μ indicating the mean, blue dots: sampled evaluation points. (a): prior, (b), (c), (d): UCB, TS, IDS posteriors respectively after 20 samples.

over a sequence of steps. Furthermore, partially Observable MDPs (Monahan, 1982) are also heteroscedastic due to the possibility of different states aliasing to the same observation.

Interestingly, heteroscedasticity also occurs in value-based RL *regardless of the environment*. This is due to Bellman targets being generated based on an evolving policy π. To demonstrate this, consider a standard observation model used in supervised learning $y_t = f(\mathbf{x}_t) + \epsilon_t(\mathbf{x}_t)$, with true function f and Gaussian noise $\epsilon_t(\mathbf{x}_t)$. In Temporal Difference (TD) algorithms (Sutton & Barto, 1998), given a sample transition $(\mathbf{s}_t, \mathbf{a}_t, r_t, \mathbf{s}_{t+1})$, the learning target is generated as $y_t = r_t + \gamma Q^\pi(\mathbf{s}_{t+1}, \mathbf{a}')$, for some action $\mathbf{a}'$. Similarly to the observation model above, we can describe TD-targets for learning Q^* being generated as $y_t = f(\mathbf{s}_t, \mathbf{a}_t) + \epsilon_t^\pi(\mathbf{s}_t, \mathbf{a}_t)$, with f and ϵ_t^π given by

$$f(\mathbf{s}_t, \mathbf{a}_t) = Q^*(\mathbf{s}_t, \mathbf{a}_t) = \mathbb{E}[R(\mathbf{s}_t, \mathbf{a}_t)] + \gamma \mathbb{E}_{\mathbf{s}' \sim p(\mathbf{s}'|\mathbf{s}_t, \mathbf{a}_t)}[\max_{\mathbf{a}'} Q^*(\mathbf{s}', \mathbf{a}')]$$

$$\epsilon_t^\pi(\mathbf{s}_t, \mathbf{a}_t) = r_t + \gamma Q^\pi(\mathbf{s}_{t+1}, \mathbf{a}') - f(\mathbf{s}_t, \mathbf{a}_t) \tag{4}$$

$$= (r_t - \mathbb{E}[R(\mathbf{s}_t, \mathbf{a}_t)]) + \gamma \left(Q^\pi(\mathbf{s}_{t+1}, \mathbf{a}') - \mathbb{E}_{\mathbf{s}' \sim p(\mathbf{s}'|\mathbf{s}_t, \mathbf{a}_t)}[\max_{\mathbf{a}'} Q^*(\mathbf{s}', \mathbf{a}')] \right)$$

The last term clearly shows the dependence of the noise function $\epsilon_t^\pi(\mathbf{s}, \mathbf{a})$ on the policy π, used to generate the Bellman target. Note additionally that heteroscedastic targets are not limited to TD-learning methods, but also occur in TD(λ) and Monte-Carlo learning (Sutton & Barto, 1998), no matter if the environment is stochastic or not.

3.3 INFORMATION-DIRECTED SAMPLING

Information-Directed Sampling (IDS) is a bandit algorithm, which was first introduced in the Bayesian setting by Russo & Van Roy (2014), and later adapted to the frequentist framework by Kirschner & Krause (2018). Here, we concentrate on the latter formulation in order to avoid keeping track of a posterior distribution over the environment, which itself is a difficult problem in RL. The bandit problem is equivalent to a single state MDP with stochastic reward function $R(\mathbf{a}, \mathbf{s}) = R(\mathbf{a})$ and optimal action $\mathbf{a}^* = \arg\max_{\mathbf{a} \in \mathcal{A}} \mathbb{E}[R(\mathbf{a})]$. We define the (expected) regret $\Delta(\mathbf{a}) := \mathbb{E}[R(\mathbf{a}^*) - R(\mathbf{a})]$, which is the loss in reward for choosing an suboptimal action $\mathbf{a}$. Note, however, that we cannot directly compute $\Delta(\mathbf{a})$, since it depends on R and the unknown optimal action $\mathbf{a}^*$. Instead, IDS uses a conservative regret estimate $\hat{\Delta}_t(\mathbf{a}) = \max_{\mathbf{a}' \in \mathcal{A}} u_t(\mathbf{a}') - l_t(\mathbf{a})$, where $[l_t(\mathbf{a}), u_t(\mathbf{a})]$ is a confidence interval which contains the true expected reward $\mathbb{E}[R(\mathbf{a})]$ with high probability.

In addition, assume for now that we are given an *information gain function* $I_t(\mathbf{a})$. Then, at any time step t, the IDS policy is defined by

$$\mathbf{a}_t^{\text{IDS}} \in \arg\min_{\mathbf{a} \in \mathcal{A}} \frac{\hat{\Delta}_t(\mathbf{a})^2}{I_t(\mathbf{a})}. \tag{5}$$

Technically, this is known as *deterministic* IDS which, for simplicity, we refer to as IDS throughout this work. Intuitively, IDS chooses actions with small regret information ratio $\hat{\Psi}_t(\mathbf{a}) := \frac{\hat{\Delta}_t(\mathbf{a})^2}{I_t(\mathbf{a})}$ to balance between incurring regret and acquiring new information at each step. Kirschner & Krause (2018) introduce several information-gain functions and derive regret bounds for the resulting IDS policies.

One particular choice of the information gain function, that works well empirically and we focus on in the following, is $I_t(\mathbf{a}) = \log\left(1 + \sigma_t(\mathbf{a})^2/\rho(\mathbf{a})^2\right)$ (Kirschner & Krause, 2018). Here $\sigma_t(a)^2$ is the variance in the parametric estimate of $\mathbb{E}[R(\mathbf{a})]$ and $\rho(\mathbf{a})^2 = \mathrm{Var}[R(\mathbf{a})]$ is the variance of the observed reward. In particular, the information gain $I_t(\mathbf{a})$ is small for actions with little uncertainty in the true expected reward or with reward that is subject to high observation noise. Importantly, note that $\rho(\mathbf{a})^2$ may explicitly depend on the selected action $\mathbf{a}$, which allows the policy to account for heteroscedastic noise.

We demonstrate the advantage of such a strategy in the Gaussian Process setting (Murphy, 2012). In particular, for an arbitrary set of actions $\mathbf{a}_1, \ldots, \mathbf{a}_N$, we model the distribution of $R(\mathbf{a}_1), \ldots, R(\mathbf{a}_N)$ by a multivariate Gaussian, with covariance $\mathrm{Cov}[R(\mathbf{a}_i), R(\mathbf{a}_j)] = \kappa(\mathbf{x}_i, \mathbf{x}_j)$, where κ is a positive definite kernel. In our toy example, the goal is to maximize $R(\mathbf{x})$ under heteroscedastic observation noise with variance $\rho(\mathbf{x})^2$ (Figure 1). As UCB and TS do not consider observation noise in the acquisition function, they may sample at points where $\rho(\mathbf{x})^2$ is large. Instead, due to kernel correlation, IDS is able to shrink the uncertainty in the high-noise region with fewer samples, by selecting a nearby point with potentially higher regret but small noise.

4 INFORMATION-DIRECTED SAMPLING FOR REINFORCEMENT LEARNING

In this section, we use the IDS strategy from the previous section in the context of deep RL. In order to do so, we have to define a tractable notion of regret Δ_t and information gain I_t.

4.1 ESTIMATING REGRET AND INFORMATION GAIN

In the context of RL, it is natural to extend the definition of instantaneous regret of action $\mathbf{a}$ in state $\mathbf{s}$ using the Q-function

$$\Delta_t^\pi(\mathbf{s}, \mathbf{a}) := \mathbb{E}_P\left[\max_{\mathbf{a}'} Q^\pi(\mathbf{s}, \mathbf{a}') - Q_t^\pi(\mathbf{s}, \mathbf{a})|\mathcal{F}_{t-1}\right], \tag{6}$$

where $\mathcal{F}_t = \{\mathbf{s}_1, \mathbf{a}_1, r_1, \ldots \mathbf{s}_t, \mathbf{a}_t, r_t\}$ is the history of observations at time t. The regret definition in eq. (6) captures the loss in return when selecting action $\mathbf{a}$ in state $\mathbf{s}$ rather than the optimal action. This is similar to the notion of the advantage function. Since $\Delta_t^\pi(\mathbf{s}, \mathbf{a})$ depends on the true Q-function Q^π, which is not available in practice and can only be estimated based on finite data, the IDS framework instead uses a conservative estimate.

To do so, we must characterize the parameteric uncertainty in the Q-function. Since we use neural network as function approximators, we can obtain approximate confidence bounds using a Bootstrapped DQN (Osband et al., 2016a). In particular, given an ensemble of K action-value functions, we compute the empirical mean and variance of the estimated Q-values,

$$\mu(\mathbf{s}, \mathbf{a}) = \frac{1}{K}\sum_{k=1}^{K} Q_k(\mathbf{s}, \mathbf{a}), \qquad \sigma(\mathbf{s}, \mathbf{a})^2 = \frac{1}{K}\sum_{k=1}^{K}(Q_k(\mathbf{s}, \mathbf{a}) - \mu(\mathbf{s}, \mathbf{a}))^2. \tag{7}$$

Based on the mean and variance estimate in the Q-values, we can define a surrogate for the regret using confidence intervals,

$$\hat{\Delta}_t^\pi(\mathbf{s}, \mathbf{a}) = \max_{\mathbf{a}' \in \mathcal{A}}\left(\mu_t(\mathbf{s}, \mathbf{a}') + \lambda_t\sigma_t(\mathbf{s}, \mathbf{a}')\right) - \left(\mu_t(\mathbf{s}, \mathbf{a}) - \lambda_t\sigma_t(\mathbf{s}, \mathbf{a})\right). \tag{8}$$

The first term corresponds to the maximum plausible value that the Q-function could take at a given state, while the right term lower-bounds the Q-value given the chosen action. As a result, eq. (8) provides a conservative estimate of the regret in eq. (6).

Given the regret surrogate, the only missing component to use the IDS strategy in eq. (5) is to compute the information gain function I_t. In particular, we use $I_t(\mathbf{a}) = \log\left(1 + \sigma_t(\mathbf{a})^2/\rho(\mathbf{a})^2\right)$ based on the discussion in (Kirschner & Krause, 2018). In addition to the previously defined predictive parameteric variance estimates for the regret, it depends on the variance of the noise distribution, ρ. While in the bandit setting we track one-step rewards, in RL we focus on learning from returns from complete trajectories. Therefore, instantaneous reward observation noise variance $\rho(\mathbf{a})^2$ in the bandit setting transfers to the variance of the return distribution $\mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)$ in RL. We point out that the scale of $\mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)$ can substantially vary depending on the stochasticity of the policy

---

Algorithm 1 Deterministic Information-Directed Q-learning

Input: λ, action-value function Q with K outputs $\{Q_k\}_{k=1}^K$, action-value distribution Z
for episode $i = 1 : M$ **do**
    Get initial state $\mathbf{s}_0$
    for step $t = 0 : T$ **do**
        $\mu(\mathbf{s}_t, \mathbf{a}) = \frac{1}{K} \sum_{k=1}^K Q_k(\mathbf{s}_t, \mathbf{a})$
        $\sigma(\mathbf{s}_t, \mathbf{a})^2 = \frac{1}{K} \sum_{k=1}^K [Q_k(\mathbf{s}_t, \mathbf{a}) - \mu(\mathbf{s}_t, \mathbf{a})]^2$
        $\hat{\Delta}(\mathbf{s}_t, \mathbf{a}) = \max_{\mathbf{a}' \in \mathcal{A}} [\mu(\mathbf{s}_t, \mathbf{a}') + \lambda\sigma(\mathbf{s}_t, \mathbf{a}')] - [\mu(\mathbf{s}_t, \mathbf{a}) - \lambda\sigma(\mathbf{s}_t, \mathbf{a})]$
        $\rho(\mathbf{s}_t, \mathbf{a})^2 = \mathrm{Var}\left(Z(\mathbf{s}_t, \mathbf{a})\right) / \left(\epsilon_1 + \frac{1}{|\mathcal{A}|} \sum_{\mathbf{a}} \mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)\right)$
        $I(\mathbf{s}_t, \mathbf{a}) = \log\left(1 + \frac{\sigma(\mathbf{s}_t, \mathbf{a})^2}{\rho(\mathbf{s}_t, \mathbf{a})^2}\right) + \epsilon_2$
        Compute regret-information ratio: $\hat{\Psi}(\mathbf{s}_t, \mathbf{a}) = \frac{\hat{\Delta}(\mathbf{s}_t, \mathbf{a})^2}{I(\mathbf{s}_t, \mathbf{a})}$
        Execute action $\mathbf{a}_t = \arg\min_{\mathbf{a} \in \mathcal{A}} \hat{\Psi}(\mathbf{s}_t, \mathbf{a})$, observe r_t and state $\mathbf{s}_{t+1}$
    end for
end for

---

and the environment. This directly affects the scale of the information gain and the degree to which the agent chooses to explore. For stable performance across a range of environments, we propose computing the information gain $I(\mathbf{s}, \mathbf{a}) = \log\left(1 + \frac{\sigma(\mathbf{s}, \mathbf{a})^2}{\rho(\mathbf{s}, \mathbf{a})^2}\right) + \epsilon_2$ using the normalized variance

$$\rho(\mathbf{s}, \mathbf{a})^2 = \frac{\mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)}{\epsilon_1 + \frac{1}{|\mathcal{A}|} \sum_{\mathbf{a}} \mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)}, \tag{9}$$

where ϵ_1, ϵ_2 are small constants that prevent division by 0. This normalization step brings the mean of all variances to 1, while keeping their values positive. We also experimentally found this version to give better results compared to the unnormalized variance $\rho(\mathbf{s}, \mathbf{a})^2 = \mathrm{Var}\left(Z(\mathbf{s}, \mathbf{a})\right)$.

4.2 INFORMATION-DIRECTED REINFORCEMENT LEARNING

Using the estimates for regret and information gain, we provide the complete control algorithm in Algorithm 1. At each step, we compute the parametric uncertainty over $Q(\mathbf{s}, \mathbf{a})$ as well as the distribution over returns $Z(\mathbf{s}, \mathbf{a})$. We then follow the steps from Section 4.1 to compute the regret and the information gain of each action, and select the one that minimizes the regret-information ratio $\hat{\Psi}(\mathbf{s}, \mathbf{a})$.

To estimate parametric uncertainty, we use the exact same training procedure and architecture as Bootstrapped DQN (Osband et al., 2016a): we split the DQN architecture (Mnih et al., 2015) into K bootstrap heads after the convolutional layers. Each head $Q_k(\mathbf{s}, \mathbf{a}; \theta)$ is trained against its own target head $Q_k(\mathbf{s}, \mathbf{a}; \theta^-)$ and all heads are trained on the exact same data. We use Double DQN targets (van Hasselt et al., 2016) and normalize gradients propagated by each head by $1/K$.

To estimate $Z(\mathbf{s}, \mathbf{a})$, it makes sense to share some of the weights θ from the Bootstrapped DQN. We propose to use the output of the last convolutional layer $\phi(\mathbf{s})$ as input to a separate head that estimates $Z(\mathbf{s}, \mathbf{a})$. The output of this head is only used for computing $\rho(\mathbf{s}, \mathbf{a})^2 = \mathrm{Var}(Z_k(\mathbf{s}, \mathbf{a}))$ and is *not* included in the bootstrap estimate. For instance, this head can be trained using C51 or QR-DQN. We note that the bootstrap and the distributional losses might not be on the same scale, which might lead to unsynchronized training of the convolutional layers. For this reason, we do not propagate distributional loss gradients in the convolutional layers and use the representation $\phi(\mathbf{s})$ learned only from the bootstrap branch.

Importantly, our method can account for deep exploration, since both the parametric uncertainty $\sigma(\mathbf{s}, \mathbf{a})^2$ and the intrinsic uncertainty $\rho(\mathbf{s}, \mathbf{a})^2$ estimates in the information gain are extended beyond a single time step and propagate information over sequences of states. We note the difference with intrinsic motivation methods, which augment the reward function by adding an exploration bonus to the step reward (Houthooft et al., 2016; Stadie et al., 2015; Schmidhuber, 2010; Bellemare et al., 2016; Tang et al., 2017). While the bonus is sometimes based on an information-gain measure, it is

Table 1: Mean and median of best scores computed across the Atari 2600 games from Table 3 and 4 in the appendix, measured as human-normalized percentages (Nair et al., 2015).

	Mean	Median
DQN	94%	53%
NoisyNet-DQN	132%	119%
DDQN	144%	108%
Bootstrapped DQN	163%	126%
Prior.	196%	130%
Dueling	252%	140%
NoisyNet-Dueling	439%	204%
DQN-IDS	480%	188%
Prior. Dueling	634%	176%
C51	641%	156%
IQN	733%	224%
QR-DQN	927%	241%
C51-IDS	**1068%**	**253%**

often difficult to account for deep, structured exploration and, without additional care, the estimated optimal policy is affected by the augmentation of the rewards. Instead of myopically focusing on the immediate time step, our approach directly computes an information gain measurement based on the whole expected trajectory.

5 EXPERIMENTS

We now provide experimental results on a the Atari 2600 games from the Arcade Learning Environment (ALE) (Bellemare et al., 2013), simulated via the OpenAI gym interface (Brockman et al., 2016). Due to computational constraints we only evaluate our method on a subset of 12 games. Our method builds on the standard DQN architecture and we expect it to benefit from recent improvements such as Dueling DQN (Wang et al., 2016) and prioritized replay (Schaul et al., 2016). However, in order to separately study the effect of changing the exploration strategy, we compare our method without these additions. We will release our code after the final decision.

We evaluate two versions of our method: a homoscedastic one, called DQN-IDS, for which we do not estimate $Z(\mathbf{s}, \mathbf{a})$ and set $\rho(\mathbf{s}, \mathbf{a})^2$ to a constant, and a heteroscedastic one, C51-IDS, for which we estimate $Z(\mathbf{s}, \mathbf{a})$ using C51 as previously described. DQN-IDS uses the exact same network architecture as Bootstrapped DQN. For C51-IDS, we add the fully-connected part of the C51 network (Bellemare et al., 2017) on top of the last convolutional layer of the DQN-IDS architecture, but we do not propagate distributional loss gradients into the convolutional layers. We use a target network to compute Bellman updates, with double DQN targets only for the bootstrap heads, but not for the distributional update. Weights are updated using the Adam optimizer (Kingma & Ba, 2015). We evaluate the performance of our method using a mean greedy policy that is computed on the bootstrap heads

$$\arg \max_{\mathbf{a} \in \mathcal{A}} \frac{1}{K} \sum_{k=1}^{K} Q_k(\mathbf{s}, \mathbf{a}). \qquad (10)$$

Due to computational limitations, we did *not* perform an extensive hyperparameter search. Our final algorithm uses $\lambda = 0.1$, $\rho(\mathbf{s}, \mathbf{a})^2 = 1.0$ (for DQN-IDS) and target update frequency of 40000 agent steps, based on a parameter search over $\lambda \in \{0.1, 1.0\}$, $\rho^2 \in \{0.5, 1.0\}$, and target update in $\{10000, 40000\}$. For C51-IDS, we put a heuristically chosen lower bound of 0.25 on $\rho(\mathbf{s}, \mathbf{a})^2$ to prevent the agent from fixating on "noiseless" actions. We also use the suggested hyperparameters from C51 and Bootstrapped DQN, and set learning rate $\alpha = 0.00005$, $\epsilon_{\mathrm{ADAM}} = 0.01/32$, number of heads $K = 10$, number of atoms $N = 51$. The rest of our training procedure is identical to that of Mnih et al. (2015), with the difference that we do not use ϵ-greedy exploration. All episodes begin with up to 30 random no-ops (Mnih et al., 2015) and the horizon is capped at 108K frames (van Hasselt et al., 2016). Complete details are provided in Appendix A.

To provide comparable results with existing work we report evaluation results under the best agent protocol. Every 1M training frames, learning is frozen, the agent is evaluated for 500K frames and performance is computed as the average episode return from this latest evaluation run. Table 1 shows the mean and median human-normalized scores (van Hasselt et al., 2016) of the best agent performance after 200M training frames.

We first point out the results of DQN-IDS and Bootstrapped DQN. While both methods use the exact same architecture and training procedure, DQN-IDS outperforms Bootstrapped DQN by almost 300%. This indicates that simply changing the exploration strategy from TS to IDS, even without accounting for heteroscedastic noise, can substantially improve performance. Additionally, while DQN-IDS does not outperform Prioritized Dueling in mean score and NoisyNet-Dueling (Fortunato et al., 2018) in median score, as previously mentioned, it is likely to benefit from the addition of dueling architecture and prioritized replay. We also see that C51-IDS outperforms all previous agents, including the state-of-the-art method IQN (Dabney et al., 2018a). C51-IDS also demonstrates a significant improvement over its counterpart C51. We also experimented with a QRDQN-IDS version, which uses QR-DQN instead of C51 to estimate $Z(\mathbf{s}, \mathbf{a})$. We noticed that our method can benefit from better approximation of the return distribution. However, we do not include QRDQN-IDS scores since we were unable to reproduce the reported QR-DQN results on all games from the subset. Importantly, the fact that C51-IDS substantially outperforms DQN-IDS, highlights the significance of accounting for heteroscedastic noise.

6 CONCLUSION

We extended the idea of frequentist Information-Directed Sampling to a practical RL exploration algorithm that can account for heteroscedastic noise. To the best of our knowledge, we are the first to propose a tractable IDS algorithm for RL in large state spaces. Our method suggests a new way to use the return distribution in combination with parametric uncertainty for efficient deep exploration and demonstrates substantial gains on Atari games. We also identified several sources of heteroscedasticity in RL and demonstrated the importance of accounting for heteroscedastic noise for efficient exploration. Additionally, our evaluation results demonstrated that similarly to the bandit setting, IDS has the potential to outperform alternative strategies such as TS in RL.

There remain promising directions for future work. Our preliminary results show that similar improvements can be observed when IDS is combined with continuous control RL methods such as the Deep Deterministic Policy Gradient (DDPG) (Lillicrap et al., 2016). Developing a computationally efficient approximation of the randomized IDS version, which minimizes the regret-information ratio over the set of stochastic policies, is another idea to investigate. Additionally, as indicated by Russo & Van Roy (2014), IDS should be seen as a design principle rather than a specific algorithm, and thus alternative information gain functions are an important direction for future research.

REFERENCES

Peter Auer, Nicolò Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine Learning*, 47(2):235–256, 2002.

Kamyar Azizzadenesheli, Emma Brunskill, and Animashree Anandkumar. Efficient exploration through bayesian deep q-networks. *arXiv*, abs/1802.04412, 2018.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems 29*, pp. 1471–1479. 2016.

Marc G. Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *Proc. of the International Conference on Machine Learning*, volume 70, pp. 449–458, 2017.

Richard Bellman. *Dynamic Programming*. Princeton University Press, 1st edition, 1957.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *Proc. of the International Conference on Machine Learning*, volume 37, pp. 1613–1622, 2015.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv*, abs/1606.01540, 2016.

Sébastien Bubeck and Nicolò Cesa-Bianchi. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends in Machine Learning*, 5(1):1–122, 2012.

Olivier Chapelle and Lihong Li. An empirical evaluation of thompson sampling. In *Advances in Neural Information Processing Systems 24*, pp. 2249–2257. 2011.

Richard Y. Chen, Szymon Sidor, Pieter Abbeel, and John Schulman. UCB and infogain exploration via q-ensembles. *arXiv*, abs/1706.01502, 2017.

Will Dabney, Georg Ostrovski, David Silver, and Remi Munos. Implicit quantile networks for distributional reinforcement learning. In *Proc. of the International Conference on Machine Learning*, volume 80, pp. 1096–1105, 2018a.

Will Dabney, Mark Rowland, Marc Bellemare, and Remi Munos. Distributional reinforcement learning with quantile regression, 2018b.

Nat Dilokthanakul and Murray Shanahan. Deep reinforcement learning with risk-seeking exploration. In *From Animals to Animats 15*, pp. 201–211. Springer International Publishing, 2018.

Bradley Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1): 1–26, 1979.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Matteo Hessel, Ian Osband, Alex Graves, Volodymyr Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, Charles Blundell, and Shane Legg. Noisy networks for exploration. In *Proc. of the International Conference on Learning Representations*, 2018.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *Proc. of the International Conference on Machine Learning*, volume 48, pp. 1050–1059, 2016.

Trevor Hastie, Robert Tibshirani, and Jerome Friedman. *The Elements of Statistical Learning*. Springer New York Inc., 2001.

Rein Houthooft, Xi Chen, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. In *Advances In Neural Information Processing Systems 29*, pp. 1109–1117. 2016.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2015.

Johannes Kirschner and Andreas Krause. Information directed sampling and bandits with heteroscedastic noise. In *Proc. International Conference on Learning Theory (COLT)*, 2018.

Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in Applied Mathematics*, 6(1):4 – 22, 1985.

Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, draft edition, 2018.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *Proc. of the International Conference on Learning Representations*, 2016.

Stephan Mandt, Matthew Hoffman, and David Blei. A variational analysis of stochastic gradient algorithms. In *Proc. of the International Conference on Machine Learning*, volume 48, pp. 354–363, 2016.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Belle-
mare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen,
Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wier-
stra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning.
Nature, 518(7540):529–533, 2015.

Thomas M. Moerland, Joost Broekens, and Catholijn M. Jonker. Efficient exploration with double
uncertain value networks. *Symposium on Deep Reinforcement Learning, NIPS*, 2017.

Thomas M. Moerland, Joost Broekens, and Catholijn M. Jonker. The potential of the return distri-
bution for exploration in rl. *arXiv*, abs/1806.04242, 2018.

George E. Monahan. A survey of partially observable markov decision processes: Theory, models,
and algorithms. *Management Science*, 28(1):1–16, 1982.

Kevin P. Murphy. *Machine Learning: A Probabilistic Perspective*. The MIT Press, 2012.

Arun Nair, Praveen Srinivasan, Sam Blackwell, Cagdas Alcicek, Rory Fearon, Alessandro De
Maria, Vedavyas Panneershelvam, Mustafa Suleyman, Charles Beattie, Stig Petersen, Shane
Legg, Volodymyr Mnih, Koray Kavukcuoglu, and David Silver. Massively parallel methods for
deep reinforcement learning. *ICML Workshop on Deep Learning*, 2015.

Radford M. Neal. *Bayesian Learning for Neural Networks*. PhD thesis, University of Toronto, 1995.

Brendan O'Donoghue, Ian Osband, Remi Munos, and Vlad Mnih. The uncertainty Bellman equation
and exploration. In *Proc. of the International Conference on Machine Learning*, volume 80, pp.
3839–3848, 2018.

Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via
bootstrapped dqn. In *Advances in Neural Information Processing Systems 29*, pp. 4026–4034.
2016a.

Ian Osband, Benjamin Van Roy, and Zheng Wen. Generalization and exploration via randomized
value functions. In *Proc. of the International Conference on Machine Learning*, volume 48, pp.
2377–2386, 2016b.

Matthias Plappert, Rein Houthooft, Prafulla Dhariwal, Szymon Sidor, Richard Y. Chen, Xi Chen,
Tamim Asfour, Pieter Abbeel, and Marcin Andrychowicz. Parameter space noise for exploration.
In *Proc. of the International Conference on Learning Representations*, 2018.

Carlos Riquelme, George Tucker, and Jasper Snoek. Deep bayesian bandits showdown: An empir-
ical comparison of bayesian deep networks for thompson sampling. In *Proc. of the International
Conference on Learning Representations*, 2018.

Daniel Russo and Benjamin Van Roy. Learning to optimize via information-directed sampling. In
Advances in Neural Information Processing Systems 27, pp. 1583–1591. 2014.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In
Proc. of the International Conference on Learning Representations, 2016.

Jürgen Schmidhuber. Formal theory of creativity, fun, and intrinsic motivation (1990–2010). *IEEE
Transactions on Autonomous Mental Development*, 2(3):230–247, 2010.

Jasper Snoek, Oren Rippel, Kevin Swersky, Ryan Kiros, Nadathur Satish, Narayanan Sundaram,
Md. Mostofa Ali Patwary, Prabhat, and Ryan P. Adams. Scalable bayesian optimization using
deep neural networks. In *Proc. of the International Conference on Machine Learning*, volume 37,
pp. 2171–2180, 2015.

Bradly C. Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement
learning with deep predictive models. *arXiv*, abs/1507.00814, 2015.

Richard S. Sutton and Andrew G. Barto. *Introduction to Reinforcement Learning*. MIT Press, 1st
edition, 1998.

Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, OpenAI Xi Chen, Yan Duan, John Schulman, Filip DeTurck, and Pieter Abbeel. #exploration: A study of count-based exploration for deep reinforcement learning. In *Advances in Neural Information Processing Systems 30*, pp. 2753–2762. 2017.

Yunhao Tang and Shipra Agrawal. Exploration by distributional reinforcement learning. In *Proc. of the International Joint Conference on Artificial Intelligence*, pp. 2710–2716, 2018.

William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.

Hado van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *Proc. of the AAAI Conference on Artificial Intelligence*, pp. 2094–2100, 2016.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Hasselt, Marc Lanctot, and Nando Freitas. Dueling network architectures for deep reinforcement learning. In *Proc. of the International Conference on Machine Learning*, volume 48, pp. 1995–2003, 2016.

Christopher J. C. H. Watkins. *Learning from Delayed Rewards*. PhD thesis, King's College, 1989.

Max Welling and Yee Whye Teh. Bayesian learning via stochastic gradient langevin dynamics. In *Proc. of the International Conference on Machine Learning*, pp. 681–688, 2011.

Andrea Zanette and Rahul Sarkar. Information directed reinforcement learning. Technical report, 2017.

A HYPERPARAMETERS

Table 2: ALE hyperparameters

Hyperparameter	Value	Description
λ	0.1	Scale factor for computing regret surrogate
ρ^2	1.0	Observation noise variance for DQN-IDS
ϵ_1, ϵ_2	0.00001	Information-ratio constants; prevent division by 0
mini-batch size	32	Size of mini-batch samples for gradient descent step
replay buffer size	1M	The number of most recent observations stored in the replay buffer
agent history length	4	The number of most recent frames concatenated as input to the network
action repeat	4	Repeat each action selected by the agent this many times
γ	0.99	Discount factor
training frequency	4	The number of times an action is selected by the agent between successive gradient descent steps
K	10	Number of bootstrap heads
β_1	0.9	Adam optimizer parameter
β_2	0.99	Adam optimizer parameter
ϵ_{ADAM}	0.01/32	Adam optimizer parameter
α	0.00005	learning rate
learning starts	50000	Agent step at which learning starts. Random policy beforehand
number of bins	51	Number of bins for Categorical DQN (C51)
$[V_{\text{MIN}}, V_{\text{MAX}}]$	[-10, 10]	C51 distribution range
number of quantiles	200	Number of quantiles for QR-DQN
target network update frequency	40000	Number of *agent* steps between consecutive target updates
evaluation length	125K	Number of *agent* steps each evaluation window lasts for. Equivalent to 500K frames
evaluation frequency	250K	The number of steps the agent takes in training mode between two evaluation runs. Equivalent to 1M frames
eval episode length	27K	Number of maximum *agent* steps during an evaluation episode. Equivalent to 108K frames
max no-ops	30	Maximum number no-op actions before the episode starts

B SUPPLEMENTAL RESULTS

Human-normalized scores are computed as (van Hasselt et al., 2016),

$$score = \frac{agent - random}{human - random} \times 100 \tag{11}$$

where $agent$, $human$ and $random$ represent the per-game raw scores.

Table 3: Raw evaluation scores. Episodes starting with 30 no-op actions. Reference values from Wang et al. (2016) and Osband et al. (2016a). DQN-IDS averaged over 3 seeds.

	DQN	DDQN	Duel.	Bootstrap	Prior. Duel.	DQN-IDS
Alien	1,620	3,747	4,461	2,436	3,941	**9,780**
Amidar	978	1,793	2,354	1,272	2,296	**2,457**
Asterix	4,359	17,356	28,188	19,713	**375,080**	50,167
BeamRider	8,627	13,772	12,164	23,429	30,276	**30,426**
Enduro	729	1,211	2,258	1,591	2,306	**2,358**
Frostbite	797	1,683	4,672	2,181	**7,413**	5,884
MsPacman	3,085	2,711	6,283	2,983	3,327	**7,273**
Qbert	13,117	15,088	19,220	15,092	18,760	**26,098**
RoadRunner	39,544	44,127	69,524	51,500	**62,151**	59,546
Seaquest	5,860	16,452	50,254	9,083	931	**58,909**
SpaceInvaders	1,692	2,525	6,427	2,893	15,311	**35,422**
UpNDown	9,989	22,972	44,939	26,231	33,879	**85,903**

Table 4: Raw evaluation scores. Episodes starting with 30 no-op actions. C51, QR-DQN and IQN scores given for a single seed, C51-IDS averaged over 3 seeds. Reference values from Dabney et al. (2018b) and Dabney et al. (2018a).

	Random	Human	C51	QR-DQN	IQN	C51-IDS
Alien	227.8	7127.7	3,166	4,871	7,022	**11,473**
Amidar	5.8	1719.5	1,735	1,641	**2,946**	1,757
Asterix	210	8503.3	406,211	261,025	342,016	**536,273**
BeamRider	363.9	16926.5	14,074	34,821	**42,776**	42,196
Enduro	0	860.5	**3,454**	2,355	2,359	2,370
Frostbite	65.2	4334.7	3,965	4,384	4,324	**10,924**
MsPacman	307.3	6951.6	3,415	5,821	6,349	**6,616**
Qbert	163.9	13455	23,784	**572,510**	25,750	27,844
RoadRunner	11.5	7845	55,839	**64,262**	57,900	61,550
Seaquest	68.4	42054.7	**266,434**	8,268	30,140	86,989
SpaceInvaders	148	1668.7	5,747	20,972	28,888	**46,244**
UpNDown	533.4	11693.2	15,612	71,260	88,148	**109,045**

Figure 2: Training curves for DQN-IDS and C51-IDS averaged over 3 seeds

Figure 3: The return distributions learned by C51-IDS and C51. Plots obtained by sampling a random batch of 32 states from the replay buffer every 50000 steps and computing the estimates for $\rho^2(\mathbf{s}, \mathbf{a})$ based on eq. (9). A histogram over the resulting values is then computed and displayed as a distribution (by interpolation). From top to bottom, the lines on each plot correspond to standard deviation boundaries of a normal distribution $[\max, \mu + 1.5\sigma, \mu + \sigma, \mu + 0.5\sigma, \mu, \mu - 0.5\sigma, \mu - \sigma, \mu - 1.5\sigma, \min]$. The x-axis indicates number of training frames.