From Deep Learning to Deep Deducing: Automatically Tracking Down Nash Equilibrium through Autonomous Neural Agent, a Possible Step toward General A.I.

Abstract

Contrary to most reinforcement learning studies, which emphasize on training a deep neural network to approximate its output layer to certain strategies, this paper proposes a reversed method for reinforcement learning. We call this "Deep Deducing". In short, after adequately training a deep neural network according to a strategy-environment-to-payoff table, then we initialize randomized strategy input and propagate the error between the actual output and the desired output back to the initially-randomized strategy input in the "input layer" of the trained deep neural network gradually to perform a task similar to "human deduction". And we view the final strategy input in the "input layer" as the fittest strategy for a neural network when confronting the observed environment input from the world outside.

1 Introduction

Contrary to most reinforcement learning studies (as in "Playing Atari with Deep Reinforcement Learning (Mnih et al., 2013).", which emphasize on training a deep neural network to approximate its output layer to certain strategies and view the output layer of a deep neural network as its strategy in a certain natural environment, this paper provides a revolutionary way for reinforcement learning and a possible road toward general A.I..

Also, contrary to most Game Theory studies, which emphasize on the role of human experts to device smart mathematics algorithm (as in "When Machine Learning Meets AI and Game Theory (Agrawal & Jaiswal, 2012).", this paper emphasizes on the role of machine and tends to show a bridge between A.I. territory and Game Theory.

The method is simple. In short, after training a deep neural network according to a strategy-environment-to-payoff (input-to-output) table that records possible strategies and the environments along with the consequential payoffs, then we randomize the strategy input in the "input layer" and propagate the error between the actual output and the desired output back to the strategy input in the "input layer" of the same trained deep neural network recurrently to perform a task similar to "human deduction". And we view the final strategy input in the "input layer" as the fittest strategy for a neural network confronting the observed environment input from the world outside.

Since the information is sent back to the input layer in a reversed way like deduction in logic, we can call this "Deep Deducing".

By using the same trick, we can force a neural network to automatically track down the Nash Equilibrium in a Simultaneous Discrete Game (which will be explained later). Since Nash Equilibrium is the optimal combination of strategies from which no player will be willing to deviate, and, for any player who deviates from NE, the player will be punished, the ability to find the Nash Equilibrium in advance in a randomized complex system indicates certain intelligence in an autonomous agent.

2 ALGORITHM: DEEP DEDUCING

To grasp the intuition behind Deep Deducing, we will first take a mosquito for example as shown in Figure 1.

Figure 1: example of a simplified brain of a mosquito

Imagine the brain of a mosquito consists of a canonical deep feedforward neural network with only one input layer, one hidden layer, and one output layer. The input layer consists of strategy input and environment input. And the output layer consists of payoff out. A list of neurons in the strategy input records the strategies (denoted $\mathbf{i}^s$) that the mosquito has adopted in response to certain environment information (denoted $\mathbf{i}^n$), which environment information is also simultaneously recorded by the other list of the neurons in the environment input as well. Meanwhile the neurons in the payoff output also instantaneously record the payoff (denoted $\mathbf{o}$) to the mosquito when it adopts a certain strategy $\mathbf{i}^s$ under a certain environment $\mathbf{i}^n$. The concatenation of $\mathbf{i}^s$ and $\mathbf{i}^n$ is denoted as $\mathbf{i}$.

The brain of the mosquito is trained to memorize the set of concatenations of strategy and environment (denoted $\mathbb{I}$) as well as the set of their payoffs (denoted $\mathbb{O}$). That is the set of the weights of the synapse (denoted $\mathbb{W}$) are adjusted through (Stochastic Gradient Descent and Back Propagation):

$$\mathbb{W}_{t+1} \leftarrow \mathbb{W}_t - \alpha \frac{\partial}{\partial \mathbb{W}_t} E(\mathbf{o} - \mathbf{o}') \tag{1}$$

where t is the current epoch, α is the learning rate, E is the error function (the loss or cost function, here we use squared error), and $\mathbf{o}'$ is the estimated payoff generated by current $\mathbf{i}$ and $\mathbf{W}_t$. This is Deep Learning.

For illustration, the consequence of seeing human's hand and choosing not to fly away is recorded. Of course the consequence is death, in which case the payoff to the mosquito is [0]. A cloud (of IoT) records the consequence (payoff) of every combination and trains the brain (the neural network) of the mosquito according to Figure 2 as below.

	Strategy	Environment		Payoff	
fly away	$[1, 0, 0]$	$[1, 0, 0]$	human hand exists	$[1]$	alive
stay	$[0, 0, 1]$	$[1, 0, 0]$	human hand exists	$[0]$	death
fly away	$[1, 0, 0]$	$[0, 0, 1]$	human hand not exist	$[1]$	alive
stay	$[0, 0, 1]$	$[0, 0, 1]$	human hand not exist	$[1]$	alive

Figure 2: example of the learning process in a mosquito's brain

When the brain (the neural network) of the mosquito is adequately trained (by using Stochastic Gradient Descent) according to the table in Figure 2, upon seeing a human's hand at presence, the brain (the neural network) of the mosquito must figure out and make deduction about what strategy it shall adopt in order to stay alive. ***In another word, how could the neural network figure out a strategy that, when put into the neural network along with environment input [1, 0, 0], can generate the payoff [1]?***

The answer that Deep Deducing gives is rather simple – Just randomize the strategy input in the input layer of the trained neural network and let the neurons that represent the strategy input to adjust itself gradually to render the neural network to reach output [1] by propagating the error between the generated output and the desired output [1] back to the neurons in the strategy input itself for fixed epochs or as long as the generated output (of the adjusted strategy input obtained in the last epoch) does not adhere to [1] in a reasonable deviation.

That is, for a given $\mathbf{i}^n$ where $\mathbf{0} \leq \mathbf{i}^n \leq \mathbf{1}$, a set of trained $\mathbb{W}_{trained}$ and a pre-fixed desired payoff $\mathbf{o}^d$, $\mathbf{0} \leq \mathbf{o}^d \leq \mathbf{1}$, we first initialize a randomized strategy input $\mathbf{i}_0^s$ at time zero where $\mathbf{0} \leq sigmoid(\mathbf{i}_0^s) \leq \mathbf{1}$. Then, by using Back Propagation, we let:

$$\mathbf{i}_{t+1}^{strategy} \leftarrow \mathbf{i}_t^{strategy} - \alpha \frac{\partial}{\partial \mathbf{i}_t^{strategy}} E(\mathbf{o}^d - \mathbf{o}_t') \tag{2}$$

where t is the current epoch, α is the deducing rate (like learning rate), E is the error function, and $\mathbf{o}_t'$ is the estimated payoff generated by current $sigmoid(\mathbf{i}_t^s)$, $\mathbf{i}^n$ and $\mathbb{W}_{trained}$. This is "Deep Deducing". Please notice that, $\mathbf{i}^n$, $\mathbb{W}_{trained}$ and $\mathbf{o}^d$ are fixed, and the only thing that is changing is $\mathbf{i}_t^s$ and $\mathbf{o}_t'$. And there is no Stochastic Gradient Descent since the desired payoff $\mathbf{o}^d$ is pre-fixed. ***By exploiting the existing trained neural network and the trick of Back Propagation, Deep Deducing forms a single, compounded and self-completed optimization problem for i_t^s to reach the global minimum error, and therefore any kind of optimization skill, such as gradient-based particle swarm optimization, can be applied here as well***. For simplicity, we will only use the most plain and modest gradient descent with only one starting point for $\mathbf{i}_t^s$ to force the machine to track down Nash Equilibrium.

The whole process is illustrated in Figure 3.

1. Generate output from current strategy input obtained from step 0 or step 2 in the last epoch

2. Propagate the error between [1] and the generated output back to the strategy input and adjust the current strategy input by one epoch. And then repeat from step 1.

0. Initially randomize neurons that represent strategy input

*** The desired output, the neurons that represent the environment input and the weight of the synapse are all intact and left unchanged during all the epochs ***

times	strategy	environment	actual payoff	desired payoff
0	$[0.4, 0.5, 0.6]$	$[1, 0, 0]$	$[0.3]$	$[1]$
100	$[0.5, 0.5, 0.5]$	$[1, 0, 0]$	$[0.3]$	$[1]$
200	$[0.6, 0.5, 0.3]$	$[1, 0, 0]$	$[0.4]$	$[1]$
300	$[0.8, 0.6, 0.2]$	$[1, 0, 0]$	$[0.5]$	$[1]$
...	...	...	...	...
N	$[0.9, 0.6, 0.1]$	$[1, 0, 0]$	$[0.99]$	$[1]$

Figure 3: example of the deduction process in a mosquito's brain

Finally, after fixed epochs, according to the preliminary experimental result shown in Figure 3, the mosquito will obtain a strategy input that approximate [1, 0, 0] when argmaxed and one-hotted, which means the mosquito better just flies away. This final strategy information will later be sent to other parts of the mosquito to initiate the procedure of flying such as twitching wing tensors. We speculate that this simple three-layered deep neural network constitutes the very core of the mosquito's decision-making mechanism.

Therefore, the Deep Deducing algorithm can be dissected into two phases. The first is the training or learning phase, and the second is the deduction phase. In the training or learning phase, the mosquito learns about the consequence in response to the combination of strategy and environment. In the deduction phase, the mosquito must figure out a strategy that can make it stay alive when human is at presence. The pseudo code of Deep Deducing for the learning phase is shown in Algorithm 1.

Algorithm 1 : training phase for the mosquito example

1: $\mathbb{I} \leftarrow set\ of\ strategies\ and\ environments$
2: $\mathbb{O} \leftarrow set\ of\ corresponding\ payoffs$
3: $\mathbb{W}_0 \leftarrow initialize\ set\ of\ randomized\ weights\ at\ time\ zero$
4: $\alpha \leftarrow learning\ rate$
5: $N_{epochs} \leftarrow number\ of\ epochs$
6: $N_{samples} \leftarrow number\ of\ training\ samples$
7: **for** t **in** $[N_{epochs}]$ **do**
8: $\quad index \leftarrow randomint(N_{samples})$
9: $\quad \mathbf{i} \leftarrow \mathbb{I}[index]$
10: $\quad \mathbf{o} \leftarrow \mathbb{O}[index]$
11: $\quad \mathbf{o}' \leftarrow feedforward(\mathbf{i}, \mathbb{W}_t)$
12: $\quad \mathbb{W}_{t+1} \leftarrow \mathbb{W}_t - \alpha \frac{\partial}{\partial \mathbb{W}_t} E(\mathbf{o} - \mathbf{o}')$
13: **end for**
14: $\mathbb{W}_{trained} \leftarrow \mathbb{W}_{N_{epochs}}$

As for the deduction phase, the pseudo code can be shown in Algorithm 2.

Algorithm 2 : deduction phase for the mosquito example

1: $\mathbf{i}_0^{strategy} \leftarrow initialize\ random\ strategy\ input\ at\ time\ zero$
2: $\mathbf{i}^{nature} \leftarrow environment\ input$
3: $\mathbf{o}^d \leftarrow initialize\ desired\ payoff\ output$
4: $\alpha \leftarrow deducing\ rate$
5: $N_{epochs} \leftarrow number\ of\ epochs$
6: **for** t **in** $[N_{epochs}]$ **do**
7: $\quad \mathbf{o}'_t \leftarrow feedforward(concatenate(sigmoid(\mathbf{i}_t^{strategy}), \mathbf{i}^{nature}), \mathbb{W}_{trained})$
8: $\quad \mathbf{i}_{t+1}^{strategy} \leftarrow \mathbf{i}_t^{strategy} - \alpha \frac{\partial}{\partial \mathbf{i}_t^{strategy}} E(\mathbf{o}^d - \mathbf{o}'_t)$
9: **end for**
10: $optimal\ strategy \leftarrow onehot(argmax(sigmoid(\mathbf{i}_{N_{epochs}}^{strategy})))$

For the sake of simplicity, we will summarize the deduction phase in just one single sentence - ***Tuning the neurons in the strategy input to generate the desired output***.

3   EXPERIMENT: TRACKING DOWN THE NASH EQUILIBRIUM IN A SIMULTANEOUS DISCRETE GAME

The first experiment here we will examine is simply the extension of the notion of the mosquito example stated above.

If we take the mosquito and the hand of human as the two players A and B in a Simultaneous Discrete Game in Game Theory. We can train a neural network according to the strategies-to-payoff

table for player A and B, then we can tune the neurons in the strategy input for player A to generate the desired output for player A, and vice versa. After we interchangeably and iteratively tune these two sets of neurons each represents the strategy input for player A and B, these two sets of neurons will converge to the Nash Equilibrium.

For example, in Simultaneous Discrete Game, we often see the strategies-to-payoff table for player A and B as shown in Table 1.

		B Strategies	
		$[1, 0, 0]$	$[0, 0, 1]$
A Strategies	$[1, 0, 0]$	$[5, 5]$	$[10, 0]$
	$[0, 0, 1]$	$[0, 10]$	$[7, 7]$

Table 1: table of prisoner's dilemma

In the same manner, we first train a neural network according to the strategies-to-payoff table for player A and B as illustrated in Figure 4 below.

A strategy	B strategy	Payoff for A and B
$[1, 0, 0]$	$[1, 0, 0]$	$[0.5, 0.5]$
$[0, 0, 1]$	$[1, 0, 0]$	$[0.0, 1.0]$
$[1, 0, 0]$	$[0, 0, 1]$	$[1.0, 0.0]$
$[0, 0, 1]$	$[0, 0, 1]$	$[0.7, 0.7]$

Figure 4: example of the learning process for prisoners

Second, since it is not a zero-sum game, we will tune (by one epoch) the neurons which represent the strategy input for player A to generate the desired payoff output for player A, namely [1, *] (where "*" stands for whatever the payoff for player B already is), and then we will tune (by one epoch) the neurons which represent the strategy input for player B to generate the desired output for player B, namely [*, 1] (where "*" stands for whatever the payoff for player A already is). We will keep this procedure for fair epochs as shown in Figure 5.

After fair epochs, as the preliminary experimental result in Figure 5, the neurons which represent the strategy input for player A will converge to [1, 0, 0] when argmaxed and one-hotted. And the neurons which represent the strategy of player B will also converge to [1, 0, 0] when argmaxed and one-hotted. This means that player A and player B will both adopt strategy [1, 0, 0], which is exactly the Nash Equilibrium in the strategies-to-payoff table in Table 1. The more formal experiment result is shown in Figure 9.

In Game Theory, this strategies-to-payoff table is Prisoner's Dilemma, and strategy input [1, 0, 0] is the "betrayal" strategy. Deep Deducing automatically tracks down the Nash Equilibrium in Prisoner's Dilemma which is that both players will betray each other (as in "Primer in Game Theory (Gibbons, 1994).").

Since Nash Equilibrium is the combination of strategies that no player is willing to deviate from , and, for any player who does not choose the NE strategy, he or she will be punished for his or her deviation (as in "Games of Strategy, Second Edition (Dixit & Skeath, 2004)."), the ability to track down NEs in a complex system in advance shows certain intelligence in a autonomous system. By this logic, since Deep Deducing, in the preliminary result, tracks down NE in the prisoner's dilemma,

0. Initially randomize neurons that represent strategy input for player A and B
1. Generate output from current strategy input for player A and B obtained in step 0 or step 4 in the last epoch
2. Propagation the error between [1, *] and the generated output back to strategy input for player A. Keep strategy input for player A and B
3. Generate output from current strategy input for player B and A obtained in step 2
4. Propagation the error between [*, 1] and the generated output back to strategy input for player B. Keep strategy input for player A and B and then repeat from step 1

*** The desired payoff for player A and B and the weight of the synapse are all intact and left unchanged during all the epochs ***

times	A strategy	B strategy	actual payoff for a round	desired payoff
0	[0.4, 0.5, 0.5]	[0.4, 0.5, 0.5]	[0.7, 0.5]	[1, *] and [*, 1]
100	[0.5, 0.5, 0.5]	[0.5, 0.5, 0.5]	[0.6, 0.5]	[1, *] and [*, 1]
200	[0.6, 0.5, 0.3]	[0.6, 0.5, 0.3]	[0.6, 0.5]	[1, *] and [*, 1]
300	[0.8, 0.6, 0.1]	[0.8, 0.6, 0.2]	[0.6, 0.5]	[1, *] and [*, 1]
…	…	…	…	…
N	[0.9, 0.7, 0.1]	[0.9, 0.7, 0.1]	[0.5, 0.5]	[1, *] and [*, 1]

Figure 5: example of the deduction process for prisoners

there is certain intelligence in Deep Deducing. The pseudo code here can also be dissected into two phases, namely the training or learning phase and the deduction phase. For the training phase, we simply duplicate the training phase in the mosquito example except that this time the environment input was replace by strategy input for player B, and the original strategy by strategy input for player A as shown in Algorithm 3.

Algorithm 3 : training phase for the prisoners' dilemma

1: $\mathbb{I}^{AB} \leftarrow set\,of\,player\,A's\,and\,B's\,strategies$
2: $\mathbb{O}^{AB} \leftarrow set\,of\,player\,A's\,and\,B's\,payoffs$
3: $\mathbb{W}_0 \leftarrow initialize\,set\,of\,randomized\,weights\,at\,time\,zero$
4: $\alpha \leftarrow learning\,rate$
5: $N_{epochs} \leftarrow number\,of\,epochs$
6: $N_{samples} \leftarrow number\,of\,training\,samples$
7: **for** t **in** $[N_{epochs}]$ **do**
8:      $index \leftarrow randomint(N_{samples})$
9:      $\mathbf{i} \leftarrow \mathbb{I}^{AB}[index]$
10:      $\mathbf{o} \leftarrow \mathbb{O}^{AB}[index]$
11:      $\mathbf{o}' \leftarrow feedforward(\mathbf{i}, \mathbb{W}_t)$
12:      $\mathbb{W}_{t+1} \leftarrow \mathbb{W}_t - \alpha \frac{\partial}{\partial \mathbb{W}_t} E(\mathbf{o} - \mathbf{o}')$
13: **end for**
14: $\mathbb{W}_{trained} \leftarrow \mathbb{W}_{N_{epochs}}$

For pseudo code in deduction phase, see Algorithm 4.

Algorithm 4 : deduction phase for the prisoners' dilemma

1: $\mathbf{i}_0^A \leftarrow initialize\,random\,input\,strategy\,for\,player\,A\,at\,time\,zero$
2: $\mathbf{i}_0^B \leftarrow initialize\,random\,input\,strategy\,for\,player\,B\,at\,time\,zero$
3: $p^{dA} \leftarrow initialize\,desired\,payoff\,for\,player\,A$
4: $p^{dB} \leftarrow initialize\,desired\,payoff\,for\,player\,B$
5: $\alpha \leftarrow deducing\,rate$
6: $N_{epochs} \leftarrow number\,of\,epochs$
7: **for** t **in** $[N_{epochs}]$ **do**
8: $\quad \mathbf{o}_t^{'A} \leftarrow feedforward(concatenate(sigmoid(\mathbf{i}_t^A), sigmoid(\mathbf{i}_t^B)), \mathbb{W}_{trained})$
9: $\quad \mathbf{o}^{dA} \leftarrow \mathbf{o}_t^{'A}$
10: $\quad \mathbf{o}^{dA}[0] \leftarrow p^{dA}$
11: $\quad \mathbf{i}_{t+1}^A \leftarrow \mathbf{i}_t^A - \alpha \frac{\partial}{\partial \mathbf{i}_t^A} E(\mathbf{o}^{dA} - \mathbf{o}_t^{'A})$
12: $\quad \mathbf{o}_t^{'B} \leftarrow feedforward(concatenate(sigmoid(\mathbf{i}_{t+1}^A), sigmoid(\mathbf{i}_t^B)), \mathbb{W}_{trained})$
13: $\quad \mathbf{o}^{dB} \leftarrow \mathbf{o}_t^{'B}$
14: $\quad \mathbf{o}^{dB}[1] \leftarrow p^{dB}$
15: $\quad \mathbf{i}_{t+1}^B \leftarrow \mathbf{i}_t^B - \alpha \frac{\partial}{\partial \mathbf{i}_t^B} E(\mathbf{o}^{dB} - \mathbf{o}_t^{'B})$
16: **end for**
17: $optimal\,strategy\,for\,player\,A \leftarrow onehot(argmax(sigmoid(\mathbf{i}_{N_{epochs}}^A)))$
18: $optimal\,strategy\,for\,player\,B \leftarrow onehot(argmax(sigmoid(\mathbf{i}_{N_{epochs}}^B)))$

---

4 EXPERIMENT RESULTS

To thoroughly testify the functionality of Deep Deducing, we will first permute the payoffs in the prisoner dilemma in Table 1 to check if Deep Deducing with a set of trained synapses can track down Nash Equilibriums (NEs) in different locations with arbitrarily randomized starting points for strategy inputs for player A and B in each permuted table. Then we will generate 50 game tables with the size of 2x2 and 4x4, with randomly generated payoffs, to check if Deep Deducing with a set of trained synapses can track down the sole and the only NE in each table with different size. The program we set up guarantees there is only one NE in each table. Therefore, at a random guess, the chance to spot NE is 25 % in table 2x2 and 6.25 % in table 4x4.

Preliminary result shows that Deep Deducing can track down NE in different locations with arbitrarily randomized starting points for strategy inputs for player A and B. Also the result shows that Deep Deducing can track down NEs at the precision of nearly 100 % in tables 2x2, and 70 % in tables 4x4, which is obviously higher than random guess. The whole source code corresponding to each Figure can be seen at: `https://github.com/AnonymousDeepDeducingCode/DeepDeducing/tree/master`, open for inspection.

The model here we will use is simply the traditional canonical 3-layered deep feedforward neural network with no modification. The squared error is used for error function (loss or cost function). To avoid noise in Back Propagation in Deep Deducing, the strategies are represented in digits. For example, strategies in table 2x2 can be represented by 1 digit, [0] or [1], since 1 digit is sufficient to represent all possible strategies for a player. Strategies in table 4x4 can be represented by 2 digits, [0, 0], [1, 0], [0, 1] and [1, 1], for each player. Also, the payoff for each player in each table is represented by digits as well. For example, payoff 3 is represented by [1, 1, 1, 0, 0, 0, 0, 0, 0, 0] with possible maximum payoff 10. The sequence is irrelevant and can be changed at user's will because the volume of error sent back to the input layer is all that matters. Here, we set maximum payoff as well as the optimal desired payoffs to 10 for each player. The final strategy adopted by a player depends on the closest range of its final strategy input to [0] or [1]. For example, if the strategy input for player A arrives at [0.13] in the end, player A will adopt strategy [0]. If the strategy input for player B arrives at [0.653] in the end, player B will adopt strategy [1].

The size of the 3-layered neural network is set to be n*h*m, where n is the sum of the size of the strategy inputs for A and B in each table, h is the size of hidden layer, and m is the sum of the size of

the neurons that represent possible maximum payoffs for player A and B in each table. Therefore, n*h*m = (1+1)*h*(10+10) in table 2x2, and n*h*m = (2+2)*h*(10+10) in table 4x4.

For the first test, the prisoner's dilemma in Table 1 is permuted into 4 different tables as below in Table 2.

Table 2: permuted tables of prisoner's dilemma (with NE underline)

With a 3-layered deep feedforward neural network with size (1+1)*30*(10+10) with learning and deducing rate at 0.01 and learning and deducing epochs at 10000, the trajectories of arbitrarily randomized starting points for strategy inputs for player A and B in each corresponding table in Table 2 can be shown in the left part of Figure 6.

Figure 6: trajectories of strategy inputs for player A and B corresponding to Table 2 (left) trajectories of strategy inputs for player B under fixed strategy corresponding to Table 2 (right)

As we can see in the left part of Figure 6, for a simple and canonical deep neural network, after respectively learning each table in Table 2, regardless of the initially randomized starting points (denoted red dots) for the strategy inputs, the strategy inputs for player A and B converge to NE (denoted blue dots) in each table under Deep Deducing.

If We further fix the strategy input for player A to [0], and tune only the strategy input for player B, we will obtain the right part of Figure 6. As we can see in the right part of Figure 6, the strategy inputs of player B still converge to the optimal (and conditional) strategies for player B in Table 2 (denoted blue dots), regardless of its initially randomized starting positions (denoted red dots). Since the strategy inputs for player A is fixed, this situation is much like the mosquito case where the environment input is fixed as well.

Since the strategies are discrete, the trained synapses $\mathbb{W}_{trained}$ and the pre-fixed desired output $\mathbf{o}^d$ for either player A or B in a deep neural network in Table 2 might form a rugged optimization geometry for the strategy inputs for player A and B, and it might not be possible for strategy inputs to escape these local minimums under Hill-Climbing Algorithms like Back Propagation. ***However, since a canonical deep neural network use sigmoid as activation function, when the training of the neural network is sufficient, a little deviation in the input layer does not generally affect***

the output of the neural network as a whole, which renders the optimization geometry for the strategy inputs rather smooth and further lessens the chance of getting stuck at local minimum for gradient descent and other types of optimization skills. If we take sum of the squared errors $\left(\mathbf{o}^{dB} - \mathbf{o}'^{B}\right)^2$ as axis z, we can obtain Figure 7.

Figure 7: the learning or training process to smooth the optimization geometry for player B under lower left table in Table 2

We can see the smoothness of geometry for the strategy inputs increases as the neural network learns more about a game table and further lessens the chance of getting stuck at local minimum for gradient descent and other types of optimization skills (see Figure 9). This explains why Deep Deducing can be attached to Deep Learning, why the learning phase (Deep Learning) is crucial for Deep Deducing, and why player B can find the optimal (and conditional) strategy under the right part of Figure 6.

However, how did the strategy inputs for player A and B automatically track down NE in the left part of Figure 6? This paper proposes two possible explanations. The first possible and more vivid explanation is that, imagine strategy inputs for A and B are two small ants in two different mountain sides, they both want to climb to the lowest points of their own mountains, however they overlap each other (phantom space) and wherever ant A moves, ant B will be carried to the same direction due to the this phantom effect, and vice versa. ***If ant A moves first and then ant B moves afterwards repeatedly, in the end, ant A and B will pull each other to a certain point (as the blue rectangles in Figure 8), and this point is never the lowest point of their own mountain side***. This can be shown in Figure 8.

Figure 8: the trajectories of strategy inputs under different error surface for player A and B under lower left table in Table 2

The second possible explanation is that, In Kakutani's fixed point theorem, a topology space kept mapped into itself (if closed, continuous) will converge to a point. This point is the fixed point under every mapping. By Nash theorem, if the mapping is the pursuit of the best interest of each player, this point will be the Nash Equilibrium (as in "Introduction to Topology: Pure and Applied (Adams & Franzosa, 2008).)". In Figure 6, we can observe that the trajectory of strategy inputs for player A and B under Deep Deducing algorithm converge to a certain point regardless of their initial different

position. Therefore, the topology space formed by all possible strategy inputs for player A and B is kept mapped into itself under Deep Deducing, and, by Kakutani's fixed point theorem, there is a fixed point under every mapping. Further by Nash theorem, the fixed point shall also be the Nash Equilibrium since Deep Deducing mimics the rationale of human player in the pursuit of their own interest. Therefore, Deep Deducing tracks down the fixed point, and, therefore tracks down the Nash Equilibrium.

For the second test to track down NEs in 50 randomly generated game tables, to save time, we instead use a 3-layered deep feedforward neural network with size (1+1)*15*(10+10) for table 2x2 and (2+2)*15*(10+10) for table 4x4 with learning and deducing rate at 0.1 and deducing epochs at 5000. The success rate to track down NEs in each table type (2x2 and 4x4) varies with learning or training epochs. The final result is shown in Figure 9.

Figure 9: accuracy for tracking down NEs in different learning epochs

The result shows that Deep Deducing can track down NEs at the precision of nearly 100 % in tables 2x2, and 70 % in tables 4x4, which is obviously higher than random guess. We can conclude that there is certain intelligence in Deep Deducing as it can track down NEs at a successful rate higher than the success rate with random guess (as shown in the red dotted line in Figure 9 in table 2x2 or 4x4 when the epochs in the learning or training phase increase. Deep Deducing also tracked down NEs in randomly generated game tables despite the fact that there is only one uncoupled algorithm. For more interesting result, please consult Appendix.

5 CONCLUSIONS

The experiments shown here are not all inclusive, but the preliminary experiments indicate that Deep Deducing can perform the similar task to human deduction by simply propagating error further back to the input layer. In this sense, the input layer of a neural network does not only serve as an information receiver (as we always envisage) but also an information sender, which information is further sent to other parts of the body such as muscles or even other neural networks to enhance further usage of the sent information.

The whole traditional deep neural network can be viewed as a gigantic memory or knowledge reservoir of strategy, environment and payoff. In a word, a simple traditional deep neural network itself is already a memory pool, ready to have its information be extracted for later usage, and Recurrent Neural Network just augmented this function by allowing variable inputs to be considered. This finding might implement the notion of "memory" as we envisaged (as in "Deep Learning (LeCun et al., 2015).").

By back-propagating error back to the input layer, a traditional deep neural network forms an internal information exchange route similar to the internal information exchange in Hopfield Neural Network. The only difference is that the former uses Back Propagation algorithm while the latter exploits the notion of thermodynamics (Hopfield Neural Network can be viewed as a Restricted Boltzmann Machine with visible layers mapping to itself in supervised learning, while a Boltzmann Machine can be viewed as a Hopfield Neural Network with hidden layers and simulated annealing, the latter see "Connectionist architectures for Artificial Intelligence (Fahlman & Hinton, 1987)."). This internal information from other pathways does not only train the synapses itself as we always

envisage (as in "How neural networks learn from experience (Hinton, 1992)."), but also the source (neurons in the input layer) as well.

There are pros and cons to Deep Deducing. First, Deep Deducing is highly intuitive (since it resembles the deductive reasoning in human mind) and can be easily coded (all we need to do is just to copy and replace the weights update with the inputs update). Second, Deep Deducing can be seamlessly combined with other types of neural networks as long as the back-propagation algorithm or back-propagation-like algorithm is compatible with the latter (such as Deep Deducing combined with Neural Turing Machine or LSTM). Third, Deep Deducing can not only deal with discrete strategy but also continuous strategy (digit between 0 and 1).

However, the downside is that, just as the nascent problem encountered by the Deep Learning in 1980s, Deep Deducing requires heavy epochs as well as training time on the training or learning phase in order to achieve high precision in the deduction phase in some application.

There is still an abundant discovery that we have made, and we are still making progress. For simplicity, we will only focus on the application of Deep Deducing on Simultaneous Discrete Game in Game Theory for now.

REFERENCES

Colin Adams and Robert Franzosa. *Introduction to Topology: Pure and Applied*. Prentice Hall Books, 2008.

Anurag Agrawal and Deepak Jaiswal. When machine learning meets ai and game theory. *cs229.stanford.edu*, 2012.

Avinash K. Dixit and Susan Skeath. *Games of Strategy, Second Edition*. W.W. Norton, 2004.

S. E. Fahlman and G. E Hinton. Connectionist architectures for artificial intelligence. *IEEE Computer*, pp. 100–109, 1987.

Robert Gibbons. *Primer in Game Theory*. Prentice Hall Books, 1994.

G.E. Hinton. How neural networks learn from experience. *Scientific American*, pp. 145–151, 1992.

VYann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521:436–444, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *NIPS Deep Learning Workshop*, 2013.

APPENDIX: EXPERIMENT II: DEEP DEDUCING PLAYING TIC-TAC-TOE GAME IN A SEQUENTIAL DISCRETE GAME

The experiment so far touches upon only the combination of Deep Deducing and Deep Feedforward Neural Network in Simultaneous Discrete Game.

However, there are still Recurrent Neural Network in A.I. and Sequential Discrete Game in Game Theory, and we can still combine Deep Deducing and Recurrent Neural Network to play with Sequential Game.

Imagine a simple recurrent neural network with one fully connected input layer, hidden layer and output layer, and the interconnection between the hidden layers is still fully connected. Each layer is represented by a set of neurons marked in the shape of rectangle.

First, in the training or learning phase, we will train the RNN according to a game tree (shown in Figure 10) in Sequential Discrete Game in Game Theory. The whole training or learning phase is shown in Figure 11. This game tree may be generated by fixed program in a chess game or by trail-and-err in the real world like the case of mosquito.

Figure 10: game tree for sequential game

Figure 11: training or learning phase in Sequential Discrete Game

In the deduction phase, we first randomize strategy input for A and B. Then, by using the notion of "Back Induction" in Game Theory (as in "Games of Strategy, Second Edition (Dixit & Skeath, 2004).""), we tune the neurons in the strategy input for player B in layer 2 to meet the desired output [*,1] for player B, and then we tune the strategy input for player A in layer 1 to meet the desired output [1,*] for player A. At last we repeat the process again, and the strategy inputs obtained in the last epoch will be kept to the next epoch. The whole procedure can be shown in Figure 12.

0. Initially randomize neurons that represent strategy input for player A and B
1. Generate output from current strategy input for player A and B obtained in step 0 or step 4 in the last epoch
2. Propagation the error between [*, 1] and the generated output back to strategy input for player B. Keep strategy input for player A and B
3. Generate output from current strategy input for player A and B obtained in step 2
4. Propagation the error between [1, *] and the generated output back to strategy input for player A. Keep strategy input for player A and B and then repeat from step 1

*** The desired payoff for player A and B and the weight of the synapse are all intact and left unchanged during all the epochs ***

Figure 12: deduction phase in Sequential Discrete Game

Finally, the final strategy input for player A in layer 1 in figure Figure 12 is the optimal strategy for player A in layer 1 in the real world. After player A chooses its strategy, in the next layer of the game in the real world, player B can exploit the same technic to obtain the optimal strategy for himself or herself in layer 2. Both players will converge to the Nash Equilibrium (route) in Sequential Discrete Game in Game theory in the end. The same methodology also applies to Sequential Discrete Game with arbitrary numbers of layers.

By this method, we can teach a RNN to learn to play Tic-Tac-Toe game. The experiment result shows that Deep Deducing can handle Tic-Tac-Toe Game. The whole source code can be seen at: `https://github.com/AnonymousDeepDeducingCode/DeepDeducing/tree/master`, open for inspection.

The model here we will use is simply the traditional canonical 3-layered (with one hidden layer fully interconnected) recurrent neural network with no modification. The size of the neural network is (9+9)*40*2. The squared error is used for error function (loss or cost function).

The program we set up will record historic strategies of the players and automatically generate the future legal strategies of the players to the end of the game as well as their final payoffs. The strategy of a player is represented by 9 digit corresponding to its position in the game board when flattened. The payoff for a player is simple, [1] or [0], meaning winning or not winning (might be draw).

When the recurrent neural network is trained according to Figure 11, the recurrent neural network will take history into consideration and deep-deduce the current optimal strategy according to Figure 12 in a pre-fixed future (here we set it to be the steps toward the end of the game). The final current strategy is the argmax of the deduced current legal strategy corresponding to its position in the game board when flattened.

The order of the game is that player A will move first.

We will let Deep Deducing RNN play with the human player and let the readers judge its intelligence by its states of the play. The states are recorded as the rows in Figure 13 (where "O" represents player A assumed by human and "X" represents player B assumed by Deep Deducing):

Figure 13: the states of the play in experiment with Deep Deducing

As we can see, if adequately tuned, in some tricky first-hand advantages, Deep Deducing can avoid bad moves in order to survive.

However, the curious thing is that if we set the number of steps foreseen in the future to be odds, Deep Deducing will take the aggressive stance. In a sense, it will not defence. In some cases, it leads to its defeat because it does not defend. If we set the number to be evens, Deep Deducing will take a defensive stance. In some cases, it misses its chance to win, although it won't be defeated. Therefore further improvement is required.

Nonetheless, the goal of the preliminary experiment is to indicate that Deep Deducing can perform the similar task to human deduction by simply propagating error further back to the input layer.