Bayesian Clustering of Neural Spiking Activity Using a Mixture of Dynamic Poisson Factor Analyzers

Abstract

Modern neural recording techniques allow neuroscientists to observe the spiking activity of many neurons simultaneously. Although previous work has illustrated how activity within and between known populations of neurons can be summarized by low-dimensional latent vectors, in many cases what determines a unique population may be unclear. Neurons differ in their anatomical location, but also, in their cell types and response properties. Moreover, multiple distinct populations may not be well described by a single low-dimensional, linear representation. To tackle these challenges, we develop a clustering method based on a mixture of dynamic Poisson factor analyzers (mixDPFA) model, with the number of clusters treated as an unknown parameter. To do the analysis of DPFA model, we propose a novel Markov chain Monte Carlo (MCMC) algorithm to efficiently sample its posterior distribution. Validating our proposed MCMC algorithm with simulations, we find that it can accurately recover the true clustering and latent states and is insensitive to the initial cluster assignments. We then apply the proposed mixDPFA model to multi-region experimental recordings, where we find that the proposed method can identify novel, reliable clusters of neurons based on their activity, and may, thus, be a useful tool for neural data analysis.

1 Introduction

With modern high-density probes [Jun et al., 2017], neuroscientists can observe the spiking activity of many neurons from many different anatomical regions simultaneously. With these expanding capabilities, new methods to analyze neural data at the population-level and at the level of multiple populations become necessary. Several recent models have been developed to extract shared latent structures from simultaneous neural recordings, assuming that neural activity can be described through low-dimensional latent states. Many existing approaches are extensions of two basic models: the linear dynamical system (LDS) model [Macke et al., 2011] and a Gaussian process factor analysis (GPFA) model [Yu et al., 2009]. The LDS model is built on the state-space model and assumes latent factors evolve with linear dynamics. On the other hand, GPFA models the latent vectors by non-parametric Gaussian processes. However, in both cases, the observation model is generalized linear. Several variants of these models have been implemented to analyze multiple neural populations and their interactions [Semedo et al., 2019, Glaser et al., 2020]. However, in many cases, the total number of distinct populations and which neurons belong to a population is unclear.

Neurons in different anatomical locations may interact with each other or receive common input from unobserved brain areas, sharing the same latent structure. On the other hand, neurons of different cell-types within the same brain area may be better described by distinct latent structures. From a functional point of view, neither the anatomical location nor cell type (Fig. 1A) indicates which neurons should be grouped into the same populations. The incorrect population assignments can

lead to biased and inconsistent inference on the latent structure [Ventura, 2009]. If we instead ignore multi-population structure and treat all neurons as a single population, then using linear model based methods may not describe their activity well, especially when the input is non-homogeneous. Besides, nonlinear models such as deep learning [Pandarinath et al., 2018, Whiteway et al., 2019] and Gaussian processes [Wu et al., 2017] have been developed, but these models do not explicitly distinguish among distinct populations of neurons.

Motivated by the mixture of (Gaussian) factor analyzers (MFA, Arminger et al. 1999, Ghahramani and Hinton 1996, Fokoué and Titterington 2003), which describes globally nonlinear data by combining a number of local factor analyzers, here we group neurons based on the latent factors (Fig. 1B). A similar idea was previously implemented using a mixture of Poisson linear dynamical system (PLDS) model (mixPLDS, Buesing et al. 2014). The mixPLDS model infers the subpopulations and latent factors using deterministic variational inference Wainwright and Jordan [2008], Jordan et al. [1999], Emtiyaz Khan et al. [2013] and the model parameters are estimated by Expectation Maximization (EM). Unlike MFA, the mixPLDS can capture temporal dependencies of neural activity as well as interactions between clusters over time. However, there are several limitations for mixPLDS: 1) it requires we predetermine the number of clusters, and 2) the clustering results are often sensitive to the initial cluster assignment.

Here we cluster the neurons by a mixture of dynamic Poisson factor analyzers (mixDPFA). The DPFA model takes the advantages of both Poisson factor analysis (FA) and PLDS and includes both a population baseline and baselines for individual neurons. The number of clusters is treated as an unknown parameter in the mixDPFA, and the posteriors are sampled using Markov Chain Monte Carlo (MCMC). To sample high dimensional latent factors, we approximate the full conditional distribution of the latent state by a Gaussian, which is similar to results by sampling from exact full conditional distribution. To improve mixing in the cluster assignments, we marginalize the loading out for clustering by Poisson-Gamma conjugacy. We also discuss the constraints necessity for successful sampling of the proposed models. After validating the proposed model with simulated data, we apply it to analyze multi-region experimental recordings from behaving mice: the Visual Coding - Neuropixels Dataset from the Allen Institute for Brain Science. Overall, the proposed method provides a way to efficiently cluster neurons into populations based on their activity.

2 Methods

Here we introduce a mixture of dynamic Poisson factor analyzers (mixDPFA) to cluster neurons based on multi-population latent structure. The number of mixture components is treated as an unknown parameter and the posteriors are sampled by MCMC. In this section, we first provide the single population DPFA for a given cluster. Then, we introduce a prior on the number of clusters and describe how we use the mixture of finite mixture model (MFM) to efficiently sample the posterior of the mixDPFA.

2.1 Dynamic Poisson Factor Analyzer

Denote the observed spike count of neuron $i \in \{1, \ldots, N\}$ at time bin $t \in \{1, \ldots, T\}$ as y_{it} (a non-negative integer), and let $\boldsymbol{y}_i = (y_{i1}, \ldots, y_{iT})'$. Further, let z_i be the cluster indicator of neuron i. Motivated by the nature of neural activity and the former PLDS model [Macke et al., 2011], we propose a new Poisson FA model by adding individual baselines δ_i. The proposed model is a combination of PLDS and Poisson FA, which includes both population baseline and individual baseline. Assume neuron i belongs to the j-th cluster (i.e., $z_i = j$), and its spiking activity is independently Poisson distributed, conditional on the low-dimensional latent state $\boldsymbol{x}_t^{(j)} \in \mathbb{R}^{p_j}$ and population baseline $\mu_t^{(j)}$ as follows:

$$y_{it} \sim Poi(\lambda_{it}),$$
$$\log \lambda_{it} = \delta_i + \mu_t^{(j)} + \boldsymbol{c}_i' \boldsymbol{x}_t^{(j)},$$

with $\boldsymbol{c}_i \sim \mathcal{N}_{p_j}(\boldsymbol{0}, \boldsymbol{I}_{p_j})$. The neuron-specific baseline δ_i is a constant across time for the ith neuron and unrelated to the cluster assignment. For simplicity, we assume the dimension of latent factors (states) is the same for all clusters, s.t. $p_j = p$, however, our method easily extends to the situation when p_js differs across clusters (see Discussion). Further, we assume the population baseline $\mu_t^{(j)}$

Figure 1: **Model overview. A.** There are multiple potential ways to define neural populations. For instance, populations could be defined by anatomical regions (left) or by cell types (right). Since the same latent structure could be shared across anatomical sites and cell types, a useful alternative may be define populations based on neural activity directly. **B.** The main goal for the proposed method is to cluster neurons according to their activity and extract functional grouping structure, based on spike train observations. The activity of each neuron is determined by a low dimensional latent state, specific to that neuron's cluster assignment (e.g. yellow, red, blue). **C.** Graphical representation of the mixture of finite mixtures (MFM) of dynamic Poisson factor analyzers (DPFA) generative model. Here the cluster number is treated as a random variable. The population baseline ($\mu_t^{(j)}$) and the latent factor ($\boldsymbol{x}_t^{(j)}$) for each cluster is generated by linear dynamics, with a Gaussian noise.

86 and the latent state $\boldsymbol{x}_t^{(j)}$ evolve linearly over time with Gaussian noise as following

$$\mu_{t+1}^{(j)} = g^{(j)} + h^{(j)}\mu_t^{(j)} + \epsilon_t^{(j)},$$
$$\boldsymbol{x}_{t+1}^{(j)} = \boldsymbol{b}^{(j)} + \boldsymbol{A}^{(j)}\boldsymbol{x}_t^{(j)} + \boldsymbol{\eta}_t^{(j)},$$

87 where $\epsilon_t^{(j)} \sim \mathcal{N}(0, \sigma^{2(j)})$ and $\boldsymbol{\eta}_t^{(j)} \sim \mathcal{N}_p(\boldsymbol{0}, \boldsymbol{Q}^{(j)})$.

88 If we denote $\boldsymbol{\lambda}_i = (\lambda_{i1}, \dots, \lambda_{iT})'$, $\boldsymbol{\mu}^{(j)} = (\mu_1^{(j)}, \dots, \mu_T^{(j)})'$ and $\boldsymbol{X}^{(j)} = (\boldsymbol{x}_1^{(j)}, \dots, \boldsymbol{x}_T^{(j)})'$, the
89 proposed model can be rewritten as

$$\boldsymbol{y}_i \sim Poi(\boldsymbol{\lambda}_i),$$
$$\log \boldsymbol{\lambda}_i = \delta_i \boldsymbol{1}_T + \boldsymbol{\mu}^{(j)} + \boldsymbol{X}^{(j)}\boldsymbol{c}_i. \tag{1}$$

90 Generally, a factor model is consistent only when $T/N \to 0$ [Johnstone and Lu, 2009], but this is
91 often not the case for most neural spike data. However, when we assume linear dynamics on $\boldsymbol{\mu}^{(j)}$
92 and $\boldsymbol{X}^{(j)}$, it resolves the consistency issue. As known in a FA model, when $p > 1$, the model is only
93 identifiable up to orthogonal rotation on $\boldsymbol{X}^{(j)}$, with $\boldsymbol{c}_i \sim N(\boldsymbol{0}, \boldsymbol{I}_p)$. With including an individual
94 baseline $\delta_i \boldsymbol{1}_T$ in our proposed DPFA model (1), it further makes the model invariant to translation of
95 $\boldsymbol{\mu}^{(j)}$ and $\boldsymbol{X}^{(j)}$. That means if $\boldsymbol{\mu}^{(j)}$ and $\boldsymbol{X}^{(j)}$ is a set solution, then $\boldsymbol{\mu}^{(j)} + a\boldsymbol{1}_T$ and $\boldsymbol{X}^{(j)}\boldsymbol{U} + \boldsymbol{1}_T \otimes \boldsymbol{m}'$
96 also satisfy the model, for any a, $\boldsymbol{m}$ and orthogonal matrix $\boldsymbol{U}$. Thus, to make the model identifiable,
97 we need to add several constraints. Although the clustering is invariant to orthogonal rotation, how
98 we put constraints on translation will influence the cluster assignments. Here we assume $\boldsymbol{A}^{(j)}$ and
99 $\boldsymbol{Q}^{(j)}$ are diagonal [Peña and Poncela, 2004, Lopes et al., 2008], and, to encourage clustering based
100 on the trajectories of latent factors, we set $\sum_{t=1}^{T} \mu_t^{(j)} = 0$ and $\sum_{t=1}^{T} \boldsymbol{x}_t^{(j)} = \boldsymbol{0}$. See Section 5 for
101 more discussions about the choice of these constraints.

102 Given the parameters of the j-th cluster $\boldsymbol{\theta}^{(j)} = \{\boldsymbol{\mu}^{(j)}, \boldsymbol{X}^{(j)}, h^{(j)}, g^{(j)}, \sigma^{2(j)}, \boldsymbol{A}^{(j)}, \boldsymbol{b}^{(j)}, \boldsymbol{Q}^{(j)}\}$, the
103 spike counts of neuron i are generated by the dynamic Poisson factor analyzer (DPFA) model as

104 $[\boldsymbol{y}_i \mid z_i = j] \sim DPFA(\delta_i, \boldsymbol{c}_i, \boldsymbol{\theta}^{(z_i)})$. To faciliate the Bayesian computation, we have to impose
105 priors $\boldsymbol{H}$ on $\boldsymbol{\theta}^{(j)}$, see more details of prior settings in Appendix A.1.

2.2 Clustering by Mixture of Finite Mixtures Model

107 When the population labels z_is are unknown, we cluster the neurons by a mixture of DPFA (mixDPFA).
108 Since the number of neural populations is finite but unknown, we need to put priors on it. To make the
109 Bayesian computation more efficient, we utilize the idea from the mixture of finite mixtures (MFM,
110 Miller and Harrison 2018) model, by assigning the priors for the clusters in the following way:

$$
\begin{aligned}
k &\sim f_k, & f_k \text{ is a p.m.f. on} \{1, 2, \ldots\}, \\
\boldsymbol{\pi} = (\pi_1, \ldots, \pi_k) &\sim Dir_k(\gamma, \ldots, \gamma) & \text{given } k, \\
z_1, \ldots, z_N &\overset{i.i.d.}{\sim} \boldsymbol{\pi} & \text{given } \boldsymbol{\pi}, \\
\boldsymbol{\theta}^{(1)}, \ldots, \boldsymbol{\theta}^{(k)} &\overset{i.i.d.}{\sim} \boldsymbol{H} & \text{given } k, \\
\boldsymbol{y}_i = (y_{i1}, \ldots, y_{iT})' &\sim \mathrm{DPFA}(\delta_i, \boldsymbol{c}_i, \boldsymbol{\theta}^{(z_i)}) & \text{given } \delta_i, \boldsymbol{c}_i, \boldsymbol{\theta}^{(z_i)}, z_i, \forall i = 1, \ldots, N,
\end{aligned}
\tag{2}
$$

111 where p.m.f denotes the probability mass function. By using the MFM, we can integrate the field
112 knowledge about the number of neural populations into our analysis. In the analysis of this paper,
113 we assume k follows a geometric distribution, i.e., $k \sim Geometric(\alpha)$ with its density defined
114 as $f_k(k|\alpha) = (1-\alpha)^{k-1}\alpha$ for $k = 1, 2, \ldots$, and let $\gamma = 1$. The complete generative model is
115 summarized in a graphical form shown in Fig. 1C.

2.3 Inference

117 Here the posteriors of the proposed mixDPFA model are sampled by an MCMC algorithm (see
118 Appendix A.1). In each iteration, we sample the model parameters assuming the known cluster
119 indices at first, and then sample the cluster indices given the model parameters. When sampling the
120 (labeled) model parameters, the latent state $\boldsymbol{X}^{(j)}$ and population baseline $\boldsymbol{\mu}^{(j)}$ have no closed-form
121 full conditional distributions. Although we could sample the posterior by particle MCMC directly,
122 convergence may be too slow for clustering. Here, we approximate the full conditional distribution for
123 $\boldsymbol{X}^{(j)}$ and $\boldsymbol{\mu}^{(j)}$ by a Gaussian distribution (a Laplace approximation) and generate samples according
124 to this approximation. This Laplace approximation is widely used for EM [Macke et al., 2011]
125 and variational inference [Glaser et al., 2020] with PLDS models and their variants, and Gaussian
126 approximation of the intractable full conditional distribution of latent effects has also been used in
127 Bayesian mixed effects binomial regression, where Berman et al. 2022 found that the approximation
128 provided reasonable estimation accuracy with substantial computational speedups. We, thus, use a
129 global Laplace approximation that can be efficiently computed in $\mathcal{O}(T)$ [Paninski et al., 2010]. To
130 help convergence, sampling on (labeled) model parameters is repeated several times before updating
131 the cluster indices. Approximating the intractable full conditional with a Laplace approximation
132 also makes computation of the proposed mixDPFA more efficient. However, to assess the accuracy
133 of the approximation we also compare our approach to directly sampling from the exact posterior
134 of the model. We develop a Pólya-Gamma (PG) data augmentation approach [Windle et al., 2013,
135 Linderman et al., 2017, 2016, Polson et al., 2013] with an additional Metropolis-Hastings (MH) step
136 [Metropolis et al., 1953, Hastings, 1970] to sample exactly from the full conditional of $\boldsymbol{X}^{(j)}$ and
137 $\boldsymbol{\mu}^{(j)}$. We find that the proposed method using a Laplace apprixmation is faster but performs similarly
138 as sampling from the exact joint posterior (Fig. 2, Fig. 5, Appendix A.2, and Table 1)).

139 Once we update the latent state $\boldsymbol{X}^{(j)}$ and population baseline $\boldsymbol{\mu}^{(j)}$, the cluster index is then sampled
140 by the analogy of partition-based algorithm in Dirichlet process mixtures (DPM, Neal 2000). See
141 details in Miller and Harrison 2018 and the Appendix (A.1). When doing the clustering, we need
142 to evaluate the likelihood for neurons under each cluster. Although we can sample $\boldsymbol{c}_i$ directly and
143 evaluate the full likelihood as in MCMC for Gaussian MFA (data-augmentation/ imputation-posterior
144 algorithm, Fokoué and Titterington 2003), the chain has poor mixing and stops after a few iterations,
145 because of the high dimensionality. The heavy dependency on the starting point when fitting the
146 mixture of PLDS (mixPLDS, Buesing et al. 2014) model may suggest a similar problem. To resolve
147 this, we evaluate the marginal likelihood by integrating out the neuron-specific $\boldsymbol{c}_i$, i.e., the marginal

likelihood of neuron i in cluster j is computed by

$$M_{\boldsymbol{\theta}^{(j)}}(\boldsymbol{y}_i) = P(\boldsymbol{y}_i|\boldsymbol{\theta}^{(j)}, \delta_i) = \int P(\boldsymbol{y}_i|\boldsymbol{\theta}^{(j)}, \delta_i, \boldsymbol{c}_i)P(\boldsymbol{c}_i)\, d\boldsymbol{c}_i. \tag{3}$$

However, this marginal likelihood has no closed form. Though we may evaluate it by a Laplace approximation, but iterating over all potential clusters for each neuron is computationally intensive. To make faster clustering, we approximate the marginal likelihood by utilizing a Poisson-Gamma conjugacy. This approach has been previously utilized to approximate posteriors [El-Sayyad, 1973] and predictive distributions [Chan and Vasconcelos, 2009]. In our situation, since $\boldsymbol{c}_i \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{I}_p)$, we have $\lambda_{it} = \exp(\delta_i + \mu_t^{(j)} + \boldsymbol{c}_i'\boldsymbol{x}_t^{(j)}) \sim lognormal(\delta_i + \mu_t^{(j)}, \boldsymbol{x}_t'^{(j)}\boldsymbol{x}_t^{(j)})$, and then we can approximate this lognormal distribution by a gamma distribution, i.e., assume λ_{it} follows $Gamma(a_{it}, b_{it})$ with $a_{it} = (\boldsymbol{x}_t'^{(j)}\boldsymbol{x}_t^{(j)})^{-1}$ and $b_{it} = \boldsymbol{x}_t'^{(j)}\boldsymbol{x}_t^{(j)} \cdot e^{\delta_i + \mu_t^{(j)}}$. Then, by the conjugate property with Poisson and Gamma random variables, we have

$$P(y_{it}|\boldsymbol{\theta}^{(j)}, \delta_i) = \int P(y_{it}|\lambda_{it})P(\lambda_{it})\, d\lambda_{it} \approx NB(y_{it}|\nu_{it}, p_{it}),$$

with $\nu_{it} = a_{it}$ and $p_{it} = 1/(1 + b_{it})$. Further, noticing that we have the conditional independence assumption for $P(\boldsymbol{y}_i|\boldsymbol{\theta}^{(j)}, \delta_i)$, that is $P(\boldsymbol{y}_i|\boldsymbol{\theta}^{(j)}, \delta_i) = \prod_{t=1}^{T} P(y_{it}|\boldsymbol{\theta}^{(j)}, \delta_i)$, we then have a closed-form for Equation (3).

Another possible idea is to approximate the log-likelihood by second-order polynomials, with coefficients determined by Chebyshev polynomial approximation [Keeley et al., 2019]. However, we find that this approximation doesn't work well in practice when spike counts have a wide range.

3   Simulations

To validate and illustrate the proposed clustering method, we simulate neural data directly from the generative model (1) . The labels for each neuron are assumed known and fixed at first to check convergence and model identifiability. We then infer the labels to evaluate clustering performance. All experiments in this paper were performed using a 3.40 GHz processor with 16 GB of RAM.

3.1   Labeled data

We first simulate 10 clusters with 5 neurons in each, with recording length $T = 1000$ and $p = 2$ dimensional latent factors for each cluster. Individual baselines are generated by $\delta_i \sim N(0, 0.5^2)$, and the loading for the latent states are generated by $\boldsymbol{c}_i \sim N(\boldsymbol{0}, \boldsymbol{I}_2)$. The population baseline $\boldsymbol{\mu}^{(j)}$ and latent vector $\boldsymbol{X}^{(j)}$ are generated by the spline interpolation on 10 to 30 evenly spaced knots. The simulations are conducted 50 times with different seeds. Here we show results for one simulation, and the performance for the rest is similar.

Since the labels are known, each whole simulation is equivalent to 10 independent simulations, with 5 neurons in each. Running MCMC for 10,000 iterations, we find that the log-likelihood per spike converges rapidly for individual clusters and overall (Fig.2A). Trace plots (Fig.2B) of the (Frobenius) norms for linear dynamics samples $(h^{(j)}, g^{(j)}, \sigma^{2(j)}, \boldsymbol{A}^{(j)}, \boldsymbol{b}^{(j)}, \boldsymbol{Q}^{(j)})$ show rapid mixing and convergence for each DPFA. The fitted mean firing rate (mean response) (Fig. 2C), $\boldsymbol{\mu}^{(j)}$ and $\boldsymbol{X}^{(j)}$ (Fig. 2D) match the ground truth well. The convergence is fast, especially in terms of mean response and population baseline $\boldsymbol{\mu}^{(j)}$. Together, these results demonstrate the identifiability of the DPFA with appropriate constraints.

We then compare the 10-cluster model with the simplified model ignoring the clustering structure (1-cluster model). The p for 1-cluster model is 14, chosen by 5-fold speckled cross-validation described in [Williams et al., 2020]. To evaluate the fitting performance of these two models, we hold out 1/2 of the data and compare the held-out log-likelihood per spike. The distribution training log-likelihood is evaluated by averaging over the samples in short chains (e.g. iteration 50 to 100), which is justified by the observed fast convergence. The same procedure is replicated for 50 times. In this case, ignoring the clustering structure leads to a worse performance (Fig 2E), and the single population analysis cannot describe the data as accurately, since the input is non-homogeneous and the data is global nonlinear.

Figure 2: **Bayesian inference with labeled data** Here we simulate 10 clusters and assess convergence and mixing of for the DPFA. **A.** Traceplot of the log-likelihood per spike for all neurons and the first 3 clusters. **B.** The traceplot of (Frobenius) norms of linear dynamics of $\boldsymbol{\mu}^{(j)}$ and $\boldsymbol{X}^{(j)}$ for each cluster (showing the first 3). **C.** The true and the fitted mean firing rate, showing the averages over samples from iteration 5000 to 10000. **D.** The true (black) and the fitted (colored) population baseline and latent factor. The $\boldsymbol{X}_{*l}$ denotes the l-th latent factor (i.e. the l-th column of $\boldsymbol{X}$). The dashed lines show the 95% highest posterior density (HPD) interval. The cosine (the "overlap") between true values and posterior means shown besides. **E.** Comparison of the held-out likelihood per spike when fitting to 1/2 of the data: 1) 10-cluster model where each cluster has $p = 2$ (true value), and 2) 1-cluster model where a single DPFA describes all neurons, with $p = 14$ selected by 5-fold speckled cross-validation. Dots denote results from individual short (iterations 50-100), independent chains.

3.2   Clustering

Using the same simulation, we now infer the cluster labels. The latent factor dimension was first optimized with $p = 2$ selected by 5-fold speckled CV on small chains (100 iterations). We then compare three chains fitting with all data: two unique chains initialized using a single cluster and one chain initialized with $N = 50$ clusters (i.e. all clusters are singletons). Traceplots (Fig. 3A) of training log-likelihood and number of clusters show that all chains converge. When fit to the full data or only half, the number of clusters converges to 10, although the prior over the number of clusters is $K \sim Geometric(0.2)$. When the recording length is sufficiently long, the likelihood will dominate, and the number of clusters will not be much affected by the prior setting. The true mean firing rate for each neuron (Fig. 3B) can be well recovered, even with half data held out. To evaluate cluster membership, here we show a similarity matrix where the entry (i, l) is the posterior probability that data points i and l belong to the same cluster. The clustering results for all 4 chains recover the true clusters, no matter what the the starting assignment is (Fig. 3C), which suggest the convergence of MCMC. The overall performance of the full model, where cluster membership is inferred alongside the latent states, is similar to the case when cluster labels are known and substantially higher than the 1-cluster model (Fig. 3D and E).

4   Multi-region neural spike recordings

We then apply the proposed clustering method to the Allen Institute Visual Coding Neuropixels dataset. The dataset contains spiking activity from hundreds of neurons from multiple brain regions of an awake mouse. See detailed data description in [Siegle et al., 2021]. Here we investigate the clustering structure of neurons from four anatomical sites (83 neurons): 1) hippocampal CA1 (24 neurons), 2) dorsal part of the lateral geniculate complex (LGd, 36 neurons), 3) lateral posterior

Figure 3: **Bayesian clustering** The same simulation setting as in Fig. 2, but inferring cluster labels from spike observations alone. **A.** The trace plots of training log-likelihood per spike and the number of clusters. The model is fitted by using all and half data as training with three chains shown for full data (initialized with a single cluster, C1 or $N = 50$ clusters, CN). **B.** The true and fitted mean firing rate, averaging from iteration 500 to 1000. **C.** The posterior similarity matrix for all chains (rows and columns ordered according to the ground truth). **D.** Traceplot of the held-out (1/2) log-likelihood for 1) the 10-cluster model with labels known, 2) the full model estimating labels and optimizing p, and 3) the 1-cluster, single population model with $p = 14$ chosen by CV. **E.** Held-out log-likelihood per spike for each model (samples for iteration 500 to 1000).

nucleus of the thalamus (LP, 12 neurons) and 4) primary visual cortex (VISp, 11 neurons). And we analyze responses to 20s epochs during three visual stimuli: drifting gratings, spontaneous activity, and natural movies. Only neurons with rates > 1Hz within the selected epochs are included (72.17% of 115 neurons) and we analyze data with 40ms bins. We use a $Geometric(0.33)$ prior over the number of clusters, such that $p(k \leq 4) = 0.8$.

In responses to drifting gratings, the 5-fold speckled CV log-likelihood is optimized with $p = 2$, and, as in the simulations, the log-likelihood and number of clusters show rapid convergence and mixing (Fig 4A and B). Low firing rates and short recording lengths tend to cause confusions in clustering, reflecting uncertainty in cluster membership for neurons with little information. Here the average number of clusters is 16. To summarize the clustering results stored as posterior samples in MCMC, we give the single estimate for cluster indices $\hat{z}_i$ by maximizing the posterior expected adjusted Rand index (maxPEAR, Fritsch and Ickstadt 2009). The maxPEAR-sorted neural activity and posterior similarity matrix are shown in Fig. 4C and D. Results sorted by Maximum a posteriori (MAP) estimate are similar and are shown in the Appendix (Fig. 5). To examine the relationship between the clustering results and anatomy, we additionally sort the neurons according anatomical labels (upper left panel in Fig. 4E). Although many identified clusters are neurons from the same anatomical area, clusters also include neurons from different regions and neurons within a region are often clustered into separate populations ($\hat{P}(\text{neuron } i, l \text{ in the same region}|z_i = z_l, \{\boldsymbol{y}_i\}_{i=1}^N) = 0.57$). Together, these results suggest that a simple assignment of populations based on anatomy many not accurately represent the latent structure.

We then evaluate the clustering patterns for different visual stimuli. We run 2 independent chains for each epoch (results from the second chain in Fig. 6D). The similarity matrices show that the pattern is consistent for the same epoch, but will change along the time even under the same experimental

settings (D1 vs. D2 and S1 vs. S2). The changes in the clustering patterns may suggest long-term drift for neuron interactions. To quantify the observations, we evaluate the adjusted Rand index (ARI) of maxPEAR estimates (bottom right panel in Fig. 4E). Between-epoch comparisons tend to have lower similarity (average ARI from comparing 2 chains for each epoch) than within-epoch comparisons (different chains) for both maxPEAR and MAP (Fig. 6C).

The MAP number of clusters is largest (18) for the natural movie, suggesting this epoch has the most severe global non-linearity issue. Here we compare three models: 1) clustering model with $p = 2$, 2) single cluster model, with $p = 8$ selected by 5-fold speckled CV and 3) anatomical cluster model. The anatomical cluster model fits a single DPFA for each region, using the anatomical labels to define the clusters explicitly. Using cross-validation, we find that the optimized dimension for each region is $p = (1, 11, 5, 3)$, respectively. We find that the single cluster model tends to underfit the data, while the anatomical cluster model tends to overfit the data (Fig. 4F).

Figure 4: **Application in Neuropixels data. A. and B.** The trace plots of log-likelihood per spike and number of clusters for drifting grating responses. All results are averages from iteration 500 to 1000. **C.** The observed spikes and fitted mean firing rate, sorted by the maxPEAR label. **D.** The posterior similarity matrix, sorted by the maxPEAR label. **E.** The posterior similarity matrices for 4 adjacent epochs and 1 further epoch with different visual stimuli, sorted sorted according to maxPEAR estimate and anatomical label in the first drifting grating epoch. The last panel shows the adjusted Rand index of the maxPEAR estimates. The diagonal is the ARI between two chains for the same data, while off-diagonal values show the mean ARI of maxPEAR for the four comparisons between two chains from two different epochs. **F.** For the natural epoch, we hold out 1/2 data as the training, and show the histograms of training and held-out log-likelihood per spike, from iteration 500 to 1000 for three models: 1) clustering model, 2) single cluster model, and 3) anatomical cluster model.

5   Discussion

Here we introduce a Bayesian approach to cluster neural spike trains by MCMC. Previous approaches to multi-population latent variable modeling have used anatomical information to label distinct groups of neurons, but this choice is somewhat arbitrary. Brain region and cell-type, for instance, can give contradictory population labels. The proposed method groups neurons by common latent factors, which may be useful for identifying "functional populations" of neurons. Here we use a mixDPFA model and infer the number of clusters by MFM with a partition-based algorithm similar to DPM. MFM may be more conceptually appropriate than DPM, since the number of neural "populations" is unknown but finite. Additionally, MFM produces more concentrated, evenly dispersed clusters (see Miller and Harrison 2018 for detailed discussion). The mixture modeling approach may also be appropriate in cases where neurons share non-homogeneous inputs, since it can approximate global

nonlinearity with a mixture of locally linear models. Here we find that the mixture model outperforms globally linear (1-cluster) models in simulations and with experimental data.

Although the proposed method can describe data and cluster neural spiking activity successfully, there are some potential improvements. Firstly, as mentioned above, the unconstrained model does not have unique solutions. To ensure model identifiable, we put diagonal constraints on $A^{(j)}$ and $Q^{(j)}$ and constrain $\mu^{(j)}$ and $X^{(j)}$ to have mean zero. The assumption that $A^{(j)}$ and $Q^{(j)}$ are diagonal does not allow interaction between latent factors. However, these interactions could be allowed by instead constraining $X'^{(j)}X^{(j)}$ to be diagonal [Krzanowski and Marriott, 1994a,b, Fokoué and Titterington, 2003]. Such a constraint could allow unique solutions for the (P)LDS and GPFA. A second potential improvement would be to automatically infer the dimension of the latent factors (states). In this paper, we assume p_j is the same for all clusters, for convenience. p is a pre-selected value or can be selected by cross-validation (CV). This may limit the accuracy of the model, since populations of neurons in experimental data are likely to have different latent dimensionalities. In future work, it would also be possible to treat p_j as a parameter and sample the posterior by a reversible-jump (RJ)MCMC [Lopes and West, 2004], birth-death (BD)MCMC [Stephens, 2000, Fokoué and Titterington, 2003], or adaptive Gibbs sampling with shrinkage prior on $X^{(j)}$ [Bhattacharya and Dunson, 2011]. Although RJMCMC and BDMCMC can be easily implemented, they perform poorly for high dimensional data and may be sensitive to priors. Adaptive Gibbs sampling with shrinkage, on the other hand, has been implemented with the infinite mixture of infinite factor analyzers (IMIFA, Murphy et al. 2020). The same idea may be useful here with an additional prior on linear dynamics ($A^{(j)}$, $b^{(j)}$ and $Q^{(j)}$) to encourage shrinkage in $X^{(j)}$. Finally, a deterministic approximation of MCMC, such as variational inference may be more computationally efficient. Standard methods for fitting the PLDS could be used directly in the VI updates, and if we further use a stick-breaking representation for the MFM model, it would be straightforward to use VI for clustering as well, similar to [Blei and Jordan, 2006].

As the number of neurons and brain regions that neuroscientists are able to record simultaneously continues to grow, understanding the latent structure of multiple populations will be a major statistical challenge. The Bayesian approach to clustering neural spike trains introduced here converges fast and is insensitive to the initial cluster assignments, and may, thus, be a useful tool for identifying "functional populations" of neurons.

References

G. Arminger, P. Stein, and J. Wittenberg. Mixtures of conditional mean-and covariance-structure models. *Psychometrika*, 64(4):475–494, 1999. ISSN 00333123. doi: 10.1007/BF02294568. URL /record/ 2000-13246-005.

B. Berman, W. O. Johnson, and W. Shen. Normal Approximation for Bayesian Mixed Effects Binomial Regression Models. *Bayesian Analysis*, pages 1 – 21, 2022. doi: 10.1214/22-BA1312. URL https://doi.org/10.1214/22-BA1312.

A. Bhattacharya and D. B. Dunson. Sparse Bayesian infinite factor models. *Biometrika*, 98(2):291, jun 2011. ISSN 00063444. doi: 10.1093/BIOMET/ASR013.

D. M. Blei and M. I. Jordan. Variational Inference for Dirichlet Process Mixtures. *Bayesian Analysis*, 1(1): 121–144, 2006. URL http://www.cs.berkeley.edu/$\sim$blei/.

L. Buesing, T. A. Machado, J. P. Cunningham, and L. Paninski. Clustered factor analysis of multineuronal spike data. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/e8dfff4676a47048d6f0c4ef899593dd-Paper.pdf.

C. K. Carter and R. Kohn. On Gibbs sampling for state space models. *Biometrika*, 81(3):541–553, 09 1994. ISSN 0006-3444. doi: 10.1093/biomet/81.3.541. URL https://doi.org/10.1093/biomet/81.3.541.

A. B. Chan and N. Vasconcelos. Bayesian poisson regression for crowd counting. *Proceedings of the IEEE International Conference on Computer Vision*, pages 545–551, 2009. doi: 10.1109/ICCV.2009.5459191.

U. T. Eden, L. M. Frank, R. Barbieri, V. Solo, and E. N. Brown. Dynamic Analysis of Neural Encoding by Point Process Adaptive Filtering. *Neural Computation*, 16(5):971–998, may 2004. ISSN 0899-7667. doi: 10.1162/089976604773135069. URL https://doi.org/10.1162/089976604773135069.

G. M. El-Sayyad. Bayesian and Classical Analysis of Poisson Regression. *Journal of the Royal Statistical Society: Series B (Methodological)*, 35(3):445–451, jul 1973. ISSN 2517-6161. doi: 10.1111/J.2517-6161. 1973.TB00972.X.

M. Emtiyaz Khan, A. Aravkin, M. Friedlander, and M. Seeger. Fast dual variational inference for non-conjugate latent gaussian models. In S. Dasgupta and D. McAllester, editors, *Proceedings of the 30th International Conference on Machine Learning*, volume 28 of *Proceedings of Machine Learning Research*, pages 951– 959, Atlanta, Georgia, USA, 17–19 Jun 2013. PMLR. URL https://proceedings.mlr.press/v28/emtiyazkhan13.html.

E. Fokoué and D. M. Titterington. Mixtures of factor analysers. Bayesian estimation and inference by stochastic simulation. *Machine Learning*, 50(1-2):73–94, jan 2003. ISSN 08856125. doi: 10.1023/A:1020297828025.

A. Fritsch and K. Ickstadt. Improved criteria for clustering based on the posterior similarity matrix. *Bayesian Analysis*, 4(2):367–391, 2009. doi: 10.1214/09-BA414. URL https://doi.org/10.1214/09-BA414.

S. Frühwirth-Schnatter. Data augmentation and dynamic linear models. *Journal of Time Series Analysis*, 15: 183–202, 1994.

Z. Ghahramani and G. E. Hinton. The EM Algorithm for Mixtures of Factor Analyzers. 1996.

J. Glaser, M. Whiteway, J. P. Cunningham, L. Paninski, and S. Linderman. Recurrent Switching Dynamical Systems Models for Multiple Interacting Neural Populations. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 14867–14878. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/aa1f5f73327ba40d47ebce155e785aaf-Paper.pdf.

W. K. Hastings. Monte Carlo sampling methods using Markov chains and their applications. *Biometrika*, 57 (1):97–109, 04 1970. ISSN 0006-3444. doi: 10.1093/biomet/57.1.97. URL https://doi.org/10.1093/biomet/57.1.97.

M. D. Hoffman and A. Gelman. The No-U-Turn Sampler: Adaptively Setting Path Lengths in Hamiltonian Monte Carlo. *Journal of Machine Learning Research*, 15:1593–1623, nov 2011. ISSN 15337928. URL https://arxiv.org/abs/1111.4246v1.

S. Jain and R. M. Neal. A split-merge markov chain monte carlo procedure for the dirichlet process mixture model. *Journal of Computational and Graphical Statistics*, 13(1):158–182, 2004. doi: 10.1198/1061860043001. URL https://doi.org/10.1198/1061860043001.

S. Jain and R. M. Neal. Splitting and merging components of a nonconjugate Dirichlet process mixture model. *Bayesian Analysis*, 2(3):445 – 472, 2007. doi: 10.1214/07-BA219. URL `https://doi.org/10.1214/07-BA219`.

I. M. Johnstone and A. Y. Lu. On Consistency and Sparsity for Principal Components Analysis in High Dimensions. *Journal of the American Statistical Association*, 104(486):682, jun 2009. ISSN 01621459. doi: 10.1198/JASA.2009.0121.

M. I. Jordan, Z. Ghahramani, T. S. Jaakkola, and L. K. Saul. An Introduction to Variational Methods for Graphical Models. *Machine Learning 1999 37:2*, 37(2):183–233, nov 1999. ISSN 1573-0565. doi: 10.1023/A:1007665907178. URL `https://link.springer.com/article/10.1023/A:1007665907178`.

J. J. Jun, N. A. Steinmetz, J. H. Siegle, et al. Fully integrated silicon probes for high-density recording of neural activity. *Nature 2017 551:7679*, 551(7679):232–236, nov 2017. ISSN 1476-4687. doi: 10.1038/nature24636. URL `https://www.nature.com/articles/nature24636`.

S. L. Keeley, D. M. Zoltowski, Y. Yu, J. L. Yates, S. L. Smith, and J. W. Pillow. Efficient non-conjugate Gaussian process factor models for spike count data using polynomial approximations. *37th International Conference on Machine Learning, ICML 2020*, PartF16814:5133–5142, jun 2019.

W. J. Krzanowski and F. H. C. Marriott. Multivariate analysis. Part I. Distributions, ordination and inference. 1994a.

W. J. Krzanowski and F. H. C. Marriott. Multivariate analysis. Part 2: Classification, covariance structures and repeated measurements. 1994b.

S. Linderman, R. P. Adams, and J. W. Pillow. Bayesian latent structure discovery from multi-neuron recordings. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL `https://proceedings.neurips.cc/paper/2016/file/708f3cf8100d5e71834b1db77dfa15d6-Paper.pdf`.

S. Linderman, M. Johnson, A. Miller, R. Adams, D. Blei, and L. Paninski. Bayesian Learning and Inference in Recurrent Switching Linear Dynamical Systems. In A. Singh and J. Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pages 914–922. PMLR, 20–22 Apr 2017. URL `https://proceedings.mlr.press/v54/linderman17a.html`.

H. F. Lopes and M. West. Bayesian Model Assessment in Factor Analysis. *Statistica Sinica*, 14:41–67, 2004.

H. F. Lopes, E. Salazar, and D. Gamerman. Spatial dynamic factor analysis. *Bayesian Analysis*, 3(4):759–792, 2008. ISSN 19360975. doi: 10.1214/08-BA329.

J. H. Macke, L. Buesing, J. P. Cunningham, B. M. Yu, K. V. Shenoy, and M. Sahani. Empirical models of spiking in neural populations. *Advances in Neural Information Processing Systems*, 24, 2011.

N. Metropolis, A. W. Rosenbluth, M. N. Rosenbluth, A. H. Teller, and E. Teller. Equation of state calculations by fast computing machines. *The Journal of Chemical Physics*, 21(6):1087–1092, 1953. doi: 10.1063/1.1699114. URL `https://doi.org/10.1063/1.1699114`.

J. W. Miller and M. T. Harrison. Mixture models with a prior on the number of components. *Journal of the American Statistical Association*, 113(521):340, jan 2018. doi: 10.1080/01621459.2016.1255636.

K. Murphy, C. Viroli, and I. C. Gormley. Infinite Mixtures of Infinite Factor Analysers. *Bayesian Analysis*, 15 (3):937–963, 2020. doi: 10.1214/19-BA1179. URL `https://doi.org/10.1214/19-BA1179`.

R. M. Neal. Markov Chain Sampling Methods for Dirichlet Process Mixture Models. *Journal of Computational and Graphical Statistics*, 9(2):249–265, 2000.

C. Pandarinath, D. J. O'Shea, J. Collins, R. Jozefowicz, S. D. Stavisky, J. C. Kao, E. M. Trautmann, M. T. Kaufman, S. I. Ryu, L. R. Hochberg, J. M. Henderson, K. V. Shenoy, L. F. Abbott, and D. Sussillo. Inferring single-trial neural population dynamics using sequential auto-encoders. *Nature Methods 2018 15:10*, 15(10): 805–815, sep 2018. ISSN 1548-7105. doi: 10.1038/s41592-018-0109-9. URL `https://www.nature.com/articles/s41592-018-0109-9`.

L. Paninski, Y. Ahmadian, D. G. Ferreira, S. Koyama, K. Rahnama Rad, M. Vidne, J. Vogelstein, and W. Wu. A new look at state-space models for neural data, aug 2010. ISSN 09295313. URL `https://link.springer.com/article/10.1007/s10827-009-0179-x`.

D. Peña and P. Poncela. Forecasting with nonstationary dynamic factor models. *Journal of Econometrics*, 119 (2):291–321, apr 2004. ISSN 03044076. doi: 10.1016/S0304-4076(03)00198-2.

N. G. Polson, J. G. Scott, and J. Windle. Bayesian inference for logistic models using pólya–gamma latent variables. *Journal of the American Statistical Association*, 108(504):1339–1349, 2013. doi: 10.1080/01621459.2013.829001. URL https://doi.org/10.1080/01621459.2013.829001.

H. E. Rauch, F. Tung, and C. T. Striebel. Maximum likelihood estimates of linear dynamic systems. *AIAA Journal*, 3(8):1445–1450, aug 1965. ISSN 0001-1452. doi: 10.2514/3.3166. URL https://doi.org/10.2514/3.3166.

J. D. Semedo, A. Zandvakili, C. K. Machens, B. M. Yu, and A. Kohn. Cortical areas interact through a communication subspace. *Neuron*, 102(1):249–259.e4, 2019. ISSN 0896-6273. doi: https://doi.org/10.1016/j.neuron.2019.01.026. URL https://www.sciencedirect.com/science/article/pii/S0896627319300534.

D. Sen, S. Patra, and D. Dunson. Constrained inference through posterior projections, 2018. URL https://arxiv.org/abs/1812.05741.

J. H. Siegle, X. Jia, S. Durand, et al. Survey of spiking in the mouse visual system reveals functional hierarchy. *Nature 2021 592:7852*, 592(7852):86–92, jan 2021. ISSN 1476-4687. doi: 10.1038/s41586-020-03171-x. URL https://www.nature.com/articles/s41586-020-03171-x.

M. Stephens. Bayesian analysis of mixture models with an unknown number of components—an alternative to reversible jump methods. *The Annals of Statistics*, 28(1):40 – 74, 2000. doi: 10.1214/aos/1016120364. URL https://doi.org/10.1214/aos/1016120364.

V. Ventura. Traditional waveform based spike sorting yields biased rate code estimates. *Proceedings of the National Academy of Sciences of the United States of America*, 106(17):6921–6926, apr 2009. ISSN 00278424. doi: 10.1073/PNAS.0901771106/SUPPL_FILE/SI_APPENDIX.PDF. URL www.pnas.org/cgi/content/full/.

M. J. Wainwright and M. I. Jordan. Graphical models, exponential families, and variational inference. *Foundations and Trends® in Machine Learning*, 1(1–2):1–305, 2008. ISSN 1935-8237. doi: 10.1561/2200000001. URL http://dx.doi.org/10.1561/2200000001.

M. R. Whiteway, K. Socha, V. Bonin, and D. A. Butts. Characterizing the nonlinear structure of shared variability in cortical neuron populations using latent variable models. *Neurons, behavior, data analysis and theory*, 3 (1), 2019. doi: 10.6080/K0NC5Z4X. URL /pmc/articles/PMC6779168//pmc/articles/PMC6779168/?report=abstracthttps://www.ncbi.nlm.nih.gov/pmc/articles/PMC6779168/.

A. H. Williams, A. Degleris, Y. Wang, and S. W. Linderman. Point process models for sequence detection in high-dimensional neural spike trains. *Advances in Neural Information Processing Systems*, 2020-Decem, oct 2020. ISSN 10495258.

J. Windle, C. M. Carvalho, J. G. Scott, and L. Sun. Efficient Data Augmentation in Dynamic Models for Binary and Count Data. aug 2013. URL http://arxiv.org/abs/1308.0774.

A. Wu, N. A. Roy, S. Keeley, and J. W. Pillow. Gaussian process based nonlinear latent structure discovery in multivariate spike train data. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/b3b4d2dbedc99fe843fd3dedb02f086f-Paper.pdf.

B. M. Yu, J. P. Cunningham, G. Santhanam, S. I. Ryu, K. V. Shenoy, and M. Sahani. Gaussian-process factor analysis for low-dimensional single-trial analysis of neural population activity. *Journal of Neurophysiology*, 102(1):614–635, 2009. ISSN 15221598. doi: 10.1152/JN.90941.2008/ASSET/IMAGES/LARGE/Z9K007099508A002.JPEG. URL https://journals.physiology.org/doi/abs/10.1152/jn.90941.2008.

A   Appendix

A.1   MCMC updates

The posteriors are sampled by a Gibbs sampler. In each iteration, the sampling scheme has two main stages: 1) to sample the model parameters assuming known labels and 2) to sample the cluster indices given model parameters. Before moving into the second stage, the first stage is repeated several times. The sampling in the first stage is conducted without considering constraints for $\mu_t^{(j)}$ and $\boldsymbol{x}_t^{(j)}$ at first, and then we project the samples onto the constraint space for $\sum_{t=1}^{T} \mu_t^{(j)} = 0$ and $\sum_{t=1}^{T} \boldsymbol{x}_t^{(j)} = \mathbf{0}$ as used in [Sen et al., 2018].

Update $\boldsymbol{x}_t^{(j)}$ and $\mu_t^{(j)}$ The priors for initial population baseline and latent factor are:

$$\mu_1^{(j)} \sim \mathcal{N}(0, 1),$$
$$\boldsymbol{x}_1^{(j)} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I}_p).$$

Assume there are $n_j = \#\{i : z_i = j\}$ neurons belong to the j-th cluster, and denote the spike counts and firing rates of these neurons at time t as $\widetilde{\boldsymbol{y}}_t^{(j)} = vec\left(\{y_{it}|z_i = j\}\right) \in \mathbb{Z}_{\geq 0}^{n_j}$ and $\widetilde{\boldsymbol{\lambda}}_t^{(j)} = vec\left(\{\lambda_{it}|z_i = j\}\right) \in \mathbb{R}^{n_j}$, where $\mathbb{Z}_{\geq 0}^{n_j}$ denotes a n_j-dimensional vector with each element being non-negative integers. The corresponding loading and baseline for these n_j neurons is $\boldsymbol{C}^{(j)} \in \mathbb{R}^{n_j \times p}$ and $\boldsymbol{\Delta}_j = vec(\{\delta_i|z_i = j\}) \in \mathbb{R}^{n_j}$, such that $\log \widetilde{\boldsymbol{\lambda}}_t^{(j)} = \boldsymbol{\Delta}_j + \mu_t^{(j)} \mathbf{1}_{n_j} + \boldsymbol{C}^{(j)} \boldsymbol{x}_t^{(j)} =$

485    $\Delta_j + \left(\mathbf{1}_{n_j}, \boldsymbol{C}^{(j)}\right)\left(\mu_t^{(j)}, \boldsymbol{x}_t^{\prime(j)}\right)'$. Denote $\widetilde{\boldsymbol{C}}^{(j)} = \left(\mathbf{1}_{n_j}, \boldsymbol{C}^{(j)}\right)$, $\widetilde{\boldsymbol{x}}_t^{(j)} = \left(\mu_t^{(j)}, \boldsymbol{x}_t^{\prime(j)}\right)'$, $\widetilde{\boldsymbol{x}}^{(j)} =$

486    $\left(\widetilde{\boldsymbol{x}}_1^{\prime(j)}, \dots, \widetilde{\boldsymbol{x}}_T^{\prime(j)}\right)'$, $\widetilde{\boldsymbol{A}}^{(j)} = diag(h^{(j)}, \boldsymbol{A}^{(j)})$, $\widetilde{\boldsymbol{b}}^{(j)} = \left(g^{(j)}, \boldsymbol{b}^{\prime(j)}\right)'$ and $\widetilde{\boldsymbol{Q}}^{(j)} = diag(\sigma^{2(j)}, \boldsymbol{Q}^{(j)})$.

487   The full conditional distribution $P(\widetilde{\boldsymbol{x}}^{(j)}|\dots) = P(\widetilde{\boldsymbol{x}}^{(j)}|\{\widetilde{\boldsymbol{y}}_t^{(j)}\}_{t=1}^T, \Delta_j, \widetilde{\boldsymbol{C}}^{(j)}, \widetilde{\boldsymbol{A}}^{(j)}, \widetilde{\boldsymbol{b}}^{(j)}, \widetilde{\boldsymbol{Q}}^{(j)})$ is

488   approximated by a global Laplace approximation, i.e.,

$$P(\widetilde{\boldsymbol{x}}^{(j)}|\dots) \approx \mathcal{N}_{(p+1)T}(\widetilde{\boldsymbol{x}}^{(j)}|\boldsymbol{\mu}_{\widetilde{\boldsymbol{x}}^{(j)}}, \boldsymbol{\Sigma}_{\widetilde{\boldsymbol{x}}^{(j)}}),$$

$$\boldsymbol{\mu}_{\widetilde{\boldsymbol{x}}^{(j)}} = \arg\max_{\widetilde{\boldsymbol{x}}^{(j)}} P(\widetilde{\boldsymbol{x}}^{(j)}|\dots),$$

$$\boldsymbol{\Sigma}_{\widetilde{\boldsymbol{x}}^{(j)}}) = -(\nabla\nabla \log P(\widetilde{\boldsymbol{x}}^{(j)}|\dots)|_{\widetilde{\boldsymbol{x}}^{(j)}=\boldsymbol{\mu}_{\widetilde{\boldsymbol{x}}^{(j)}}})^{-1}.$$

489   Then, taking the logarithm of the full conditional distribution, i.e., $\ell = \ell(\widetilde{\boldsymbol{x}}^{(j)}) = \log P(\widetilde{\boldsymbol{x}}^{(j)}|\dots)$,

490   we have

$$\ell = \text{const} + \sum_{t=1}^T \left(\widetilde{\boldsymbol{y}}_t^{\prime(j)}(\Delta_j + \widetilde{\boldsymbol{C}}^{(j)}\widetilde{\boldsymbol{x}}_t^{(j)}) - \mathbf{1}_{n_j}'\widetilde{\boldsymbol{\lambda}}_t\right) - \frac{1}{2}(\widetilde{\boldsymbol{x}}_1^{(j)} - \widetilde{\boldsymbol{x}}_0^{\prime(j)})[\widetilde{\boldsymbol{Q}}_0^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_1^{(j)} - \widetilde{\boldsymbol{x}}_0^{(j)})$$

$$- \sum_{t=2}^T \frac{1}{2}(\widetilde{\boldsymbol{x}}_t^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_{t-1}^{(j)} - \widetilde{\boldsymbol{b}}^{\prime(j)})[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_t^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_{t-1}^{(j)} - \widetilde{\boldsymbol{b}}^{(j)}).$$

491   Here, $\ell(\widetilde{\boldsymbol{x}}^{(j)})$ is concave and unimodal. By the Markovian assumption for latent state vectors, the

492   Hessian matrix is tri-block diagonal. We can thus compute Newton updates to get $\boldsymbol{\mu}_{\widetilde{\boldsymbol{x}}^{(j)}}$ for the

493   Laplace approximation in $\mathcal{O}(T)$ [Paninski et al., 2010], similar to the E-step for the PLDS [Macke

494   et al., 2011].

495   The gradient $\nabla\ell$ and the Hessian $\nabla\nabla\ell$ are provided as follows. For $t = 2, \dots, T-1$, the gradient of

496    $\ell(\widetilde{\boldsymbol{x}}^{(j)})$ is:

$$\nabla\ell = \left[\left(\frac{\partial\ell}{\partial\widetilde{\boldsymbol{x}}_1^{(j)}}\right)', \dots, \left(\frac{\partial\ell}{\partial\widetilde{\boldsymbol{x}}_T^{(j)}}\right)'\right]',$$

$$\frac{\partial\ell}{\partial\widetilde{\boldsymbol{x}}_1^{(j)}} = \widetilde{\boldsymbol{C}}^{\prime(j)}(\widetilde{\boldsymbol{y}}_1^{(j)} - \widetilde{\boldsymbol{\lambda}}_1) - [\widetilde{\boldsymbol{Q}}_0^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_1^{(j)} - \widetilde{\boldsymbol{x}}_0^{(j)}) + \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_2^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_1^{(j)} - \widetilde{\boldsymbol{b}}^{(j)}),$$

$$\frac{\partial\ell}{\partial\widetilde{\boldsymbol{x}}_t^{(j)}} = \widetilde{\boldsymbol{C}}^{\prime(j)}(\widetilde{\boldsymbol{y}}_t^{(j)} - \widetilde{\boldsymbol{\lambda}}_t) - [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_t^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_{t-1}^{(j)} - \widetilde{\boldsymbol{b}}^{(j)})$$

$$+ \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_{t+1}^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_t^{(j)} - \widetilde{\boldsymbol{b}}^{(j)}),$$

$$\frac{\partial\ell}{\partial\widetilde{\boldsymbol{x}}_T^{(j)}} = \widetilde{\boldsymbol{C}}^{\prime(j)}(\widetilde{\boldsymbol{y}}_t^{(j)} - \widetilde{\boldsymbol{\lambda}}_T) - [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}(\widetilde{\boldsymbol{x}}_T^{(j)} - \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_{T-1}^{(j)} - \widetilde{\boldsymbol{b}}^{(j)}).$$

497   And the Hessian matrix is:

$$\nabla\nabla\ell = \begin{pmatrix} \frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_1^{(j)}\partial\widetilde{\boldsymbol{x}}_1^{\prime(j)}} & \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1} & \mathbf{0} & \cdots & \mathbf{0} \\ [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}\widetilde{\boldsymbol{A}}^{(j)} & \frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_2^{(j)}\partial\widetilde{\boldsymbol{x}}_2^{\prime(j)}} & \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1} & \cdots & \vdots \\ \mathbf{0} & [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}\widetilde{\boldsymbol{A}}^{(j)} & \frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_3^{(j)}\partial\widetilde{\boldsymbol{x}}_3^{\prime(j)}} & \cdots & \vdots \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ \mathbf{0} & \cdots & \cdots & \cdots & \frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_T^{(j)}\partial\widetilde{\boldsymbol{x}}_T^{\prime(j)}} \end{pmatrix},$$

$$\frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_1^{(j)}\partial\widetilde{\boldsymbol{x}}_1^{\prime(j)}} = -\widetilde{\boldsymbol{C}}^{\prime(j)}diag(\widetilde{\boldsymbol{\lambda}}_1)\widetilde{\boldsymbol{C}}^{(j)} - [\widetilde{\boldsymbol{Q}}_0^{(j)}]^{-1} - \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}\widetilde{\boldsymbol{A}}^{(j)},$$

$$\frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_t^{(j)}\partial\widetilde{\boldsymbol{x}}_t^{\prime(j)}} = -\widetilde{\boldsymbol{C}}^{\prime(j)}diag(\widetilde{\boldsymbol{\lambda}}_t)\widetilde{\boldsymbol{C}}^{(j)} - [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1} - \widetilde{\boldsymbol{A}}^{\prime(j)}[\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}\widetilde{\boldsymbol{A}}^{(j)},$$

$$\frac{\partial^2\ell}{\partial\widetilde{\boldsymbol{x}}_T^{(j)}\partial\widetilde{\boldsymbol{x}}_T^{\prime(j)}} = -\widetilde{\boldsymbol{C}}^{\prime(j)}diag(\widetilde{\boldsymbol{\lambda}}_T)\widetilde{\boldsymbol{C}}^{(j)} - [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}.$$

498 Although we can conduct the Newton update efficiently in $\mathcal{O}(T)$, bad initial values may slow down
499 the convergence. To facilitate convergence, we initialize the Newton update with a smoothing
500 estimate by local Gaussian approximation. The forward filtering for a dynamic Poisson model has
501 been previously described [Eden et al., 2004], and we use an additional backward pass to smooth
502 [Rauch et al., 1965].

503 Let $\widetilde{\boldsymbol{x}}_{t|t-1}^{(j)} = E(\widetilde{\boldsymbol{x}}_t^{(j)}|\widetilde{\boldsymbol{y}}_1^{(j)},\ldots,\widetilde{\boldsymbol{y}}_{t-1}^{(j)})$ and $V_{t|t-1}^{(j)} = Var(\widetilde{\boldsymbol{x}}_t^{(j)}|\widetilde{\boldsymbol{y}}_1^{(j)},\ldots,\widetilde{\boldsymbol{y}}_{t-1}^{(j)})$ be the mean and
504 variance for the one-step prediction density, where $\widetilde{\boldsymbol{x}}_{t|t-1}^{(j)} = \widetilde{\boldsymbol{A}}^{(j)}\widetilde{\boldsymbol{x}}_{t-1|t-1}^{(j)} + \widetilde{\boldsymbol{b}}^{(j)}$ and $V_{t|t-1}^{(j)} =$
505 $\widetilde{\boldsymbol{A}}^{(j)}V_{t-1|t-1}^{(j)}\widetilde{\boldsymbol{A}}'^{(j)} + \widetilde{\boldsymbol{Q}}^{(j)}$. Then, after we observe the data at time t, we can do a forward filtering
506 step for the mean $\widetilde{\boldsymbol{x}}_{t|t}^{(j)} = E(\widetilde{\boldsymbol{x}}_t^{(j)}|\widetilde{\boldsymbol{y}}_1^{(j)},\ldots,\widetilde{\boldsymbol{y}}_t^{(j)})$ and the variance $V_{t|t}^{(j)} = Var(\widetilde{\boldsymbol{x}}_t^{(j)}|\widetilde{\boldsymbol{y}}_1^{(j)},\ldots,\widetilde{\boldsymbol{y}}_t^{(j)})$,
507 which are given by

$$\widetilde{\boldsymbol{x}}_{t|t}^{(j)} = \widetilde{\boldsymbol{x}}_{t|t-1}^{(j)} + V_{t|t-1}^{(j)}[\widetilde{\boldsymbol{C}}'^{(j)}(\widetilde{\boldsymbol{y}}_t^{(j)} - \widetilde{\boldsymbol{\lambda}}_t)]_{\widetilde{\boldsymbol{x}}_t^{(j)}=\widetilde{\boldsymbol{x}}_{t|t-1}^{(j)}},$$

$$[V_{t|t}^{(j)}]^{-1} = [V_{t|t-1}^{(j)}]^{-1} + [\widetilde{\boldsymbol{C}}'^{(j)}diag(\widetilde{\boldsymbol{\lambda}}_t)\widetilde{\boldsymbol{C}}^{(j)} - [\widetilde{\boldsymbol{Q}}^{(j)}]^{-1}]_{\widetilde{\boldsymbol{x}}_t^{(j)}=\widetilde{\boldsymbol{x}}_{t|t-1}^{(j)}}.$$

508 Derivation of the filtering estimates can be found in [Eden et al., 2004], and we can further get the
509 smoothing estimates directly by standard Rauch-Tung-Striebel smoother [Rauch et al., 1965].

510 The smoother estimates $\widetilde{\boldsymbol{x}}_{t|T}^{(j)}$ and $V_{t|T}^{(j)}$ are updated as follows:

$$\widetilde{\boldsymbol{x}}_{t-1|T}^{(j)} = \widetilde{\boldsymbol{x}}_{t-1|t-1}^{(j)} + \boldsymbol{J}_{t-1}(\widetilde{\boldsymbol{x}}_{t|T}^{(j)} - \widetilde{\boldsymbol{x}}_{t|t-1}^{(j)}),$$

$$V_{t-1|T}^{(j)} = V_{t-1|t-1}^{(j)} + \boldsymbol{J}_{t-1}(V_{t|T}^{(j)} - V_{t|t-1}^{(j)})\boldsymbol{J}_{t-1}',$$

511 where $\boldsymbol{J}_{t-1} = V_{t-1|t-1}^{(j)}\widetilde{\boldsymbol{A}}'^{(j)}[V_{t|t-1}^{(j)}]^{-1}$.

512 **Update δ_i and $\boldsymbol{c}_i$** We specify the prior for neuron-specific baseline δ_i as $\delta_i \sim \mathcal{N}(0,1)$ and we
513 have assumed the loading $\boldsymbol{c}_i \sim \mathcal{N}(\boldsymbol{0},\boldsymbol{I}_p)$. Then, from the matrix representation of DPFA in (1), i.e.,
514 $\log \boldsymbol{\lambda}_i = \delta_i\boldsymbol{1}_T + \boldsymbol{\mu}^{(j)} + \boldsymbol{X}^{(j)}\boldsymbol{c}_i$, it is easy to see that given $\boldsymbol{\mu}^{(j)}$ and $\boldsymbol{X}^{(j)}$ are known, the update
515 of δ_i and $\boldsymbol{c}_i$ is just a regular Bayesian Poisson regression problem. Thus, we can sample the full
516 conditional distribution of δ_i and $\boldsymbol{c}_i$ by a No U-Turn Sampler (NUTS, Hoffman and Gelman 2011),
517 within the Gibbs sampler. .

518 **Update parameters of latent state** The parameters for linear dynamics are $h^{(j)}, g^{(j)}, \sigma^{2(j)}, \boldsymbol{A}^{(j)}$,
519 $\boldsymbol{b}^{(j)}$ and $\boldsymbol{Q}^{(j)}$. To make the model identifiable, we simply assume $\boldsymbol{A}^{(j)} = diag(a_1^{(j)},\ldots,a_p^{(j)})$
520 and $\boldsymbol{Q}^{(j)} = diag(q_1^{(j)},\ldots,q_p^{(j)})$. Therefore, we can update $\boldsymbol{A}^{(j)}, \boldsymbol{b}^{(j)}$ and $\boldsymbol{Q}^{(j)}$ for each diagonal
521 element separately, as the update in $h^{(j)}, g^{(j)}$ and $\sigma^{2(j)}$. Here, we update $h^{(j)}, g^{(j)}$ and $\sigma^{2(j)}$ as
522 follows.

523 First, we specify the priors for $\sigma^{2(j)}$ following $IG\left(\nu_0/2,\nu_0\sigma_0^2/2\right)$ and $\left(g^{(j)},h^{(j)}\right)' \sim$
524 $\mathcal{N}(\boldsymbol{\tau}_0,\sigma^{2(j)}\boldsymbol{\Lambda}_0^{-1})$, with $\nu_0 = 1, \sigma_0 = 0.01, \boldsymbol{\tau}_0 = (0,1)'$ and $\boldsymbol{\Lambda}_0 = \boldsymbol{I}_2$. Here, the "IG" denotes the
525 inverse-gamma distribution.

526 Denote $\boldsymbol{\mu}_{2:T}^{(j)} = \left(\mu_2^{(j)},\ldots,\mu_T^{(j)}\right)'$ and $\widetilde{\boldsymbol{\mu}}_{1:(T-1)}^{(j)} = \left(\boldsymbol{1}_{T-1},\boldsymbol{\mu}_{1:(T-1)}^{(j)}\right)$, with $\boldsymbol{\mu}_{1:(T-1)}^{(j)} =$
527 $\left(\mu_1^{(j)},\ldots,\mu_{T-1}^{(j)}\right)'$. The full conditional distributions for $\sigma^{2(j)}$ and $\left(g^{(j)},h^{(j)}\right)'$ are:

$$\sigma^{2(j)}|\{\mu_t^{(j)}\}_{t=1}^T \sim IG\left(\frac{\nu_0 + T - 1}{2}, \frac{\nu_0\sigma_0^2 + \boldsymbol{\mu}_{2:T}'^{(j)}\boldsymbol{\mu}_{2:T}^{(j)} + \boldsymbol{\tau}_0'\boldsymbol{\Lambda}_0\boldsymbol{\tau}_0 - \boldsymbol{\tau}_n'\boldsymbol{\Lambda}_n\boldsymbol{\tau}_n}{2}\right),$$

$$\left(g^{(j)},h^{(j)}\right)'|\{\mu_t^{(j)}\}_{t=1}^T \sim \mathcal{N}(\boldsymbol{\tau}_n,\sigma^{2(j)}\boldsymbol{\Lambda}_n^{-1}),$$

528 with $\boldsymbol{\Lambda}_n = \widetilde{\boldsymbol{\mu}}_{1:(T-1)}'^{(j)}\widetilde{\boldsymbol{\mu}}_{1:(T-1)}^{(j)} + \boldsymbol{\Lambda}_0$, and $\boldsymbol{\tau}_n = \boldsymbol{\Lambda}_n^{-1}\left(\widetilde{\boldsymbol{\mu}}_{1:(T-1)}'^{(j)}\boldsymbol{\mu}_{2:T}^{(j)} + \boldsymbol{\Lambda}_0\boldsymbol{\tau}_0\right)$.

529 For completeness, we also provide the update of latent state parameters when using the more
530 parsimonious constraint, i.e. diagonal $\boldsymbol{X}'^{(j)}\boldsymbol{X}^{(j)}$. According to results from previous research

531 [Krzanowski and Marriott, 1994a,b, Fokoué and Titterington, 2003], this constraint is one of the most
532 parsimonious one, which only put constraints on $p(p-1)/2$ parameters. The constraint can also be
533 implemented in MCMC by "unconstrained sampling-projection" procedure [Sen et al., 2018].

534 Without constraints, the sampling of $h^{(j)}$, $g^{(j)}$ and $\sigma^{2(j)}$ is the same as shown previously. The
535 update of $\boldsymbol{A}^{(j)}$, $\boldsymbol{b}^{(j)}$ and $\boldsymbol{Q}^{(j)}$ is the standard multivariate Bayesian linear regression. Denote
536 $\boldsymbol{X}^{(j)}_{2:T} = (\boldsymbol{x}^{(j)}_2, \ldots, \boldsymbol{x}^{(j)}_T)'$ and $\widetilde{\boldsymbol{X}}^{(j)}_{1:(T-1)} = (\mathbf{1}_{T-1}, \boldsymbol{X}^{(j)}_{1:(T-1)})$, with $\boldsymbol{X}^{(j)}_{1:(T-1)} = (\boldsymbol{x}^{(j)}_1, \ldots, \boldsymbol{x}^{(j)}_{T-1})'$.
537 Let us use the conjugate priors as following for $\boldsymbol{Q}^{(j)}$, $\boldsymbol{b}^{(j)}$ and $\boldsymbol{A}^{(j)}$:

$$\boldsymbol{Q}^{(j)} \sim \mathcal{W}^{-1}(\boldsymbol{\Psi}_0, \gamma_0),$$

$$vec((\boldsymbol{b}^{(j)}, \boldsymbol{A}'^{(j)})) \sim N(vec(\boldsymbol{T}_0), \boldsymbol{Q}^{(j)} \otimes \boldsymbol{\Gamma}_0^{-1}).$$

538 Here, the $\mathcal{W}^{-1}$ denotes the inverse-Wishart distribution. We can set the priors as $\boldsymbol{\Psi}_0 = 0.01\boldsymbol{I}_p$,
539 $\gamma_0 = p+2$ and $\boldsymbol{T}_0 = (\boldsymbol{0}_p, \boldsymbol{I}_p)'$. Then, the full conditional distributions for $\boldsymbol{Q}^{(j)}$ and $vec((\boldsymbol{b}^{(j)}, \boldsymbol{A}^{(j)})')$
540 are:

$$\boldsymbol{Q}^{(j)} | \boldsymbol{X}^{(j)} \sim \mathcal{W}^{-1}(\boldsymbol{\Psi}_n, \gamma_n),$$

$$vec((\boldsymbol{b}^{(j)}, \boldsymbol{A}^{(j)})') | \boldsymbol{X}^{(j)} \sim N(vec(\boldsymbol{T}_n), \boldsymbol{Q}^{(j)} \otimes \boldsymbol{\Gamma}_n^{-1}),$$

541 with

$$\boldsymbol{\Psi}_n = \boldsymbol{\Psi}_0 + (\boldsymbol{X}^{(j)}_{2:T} - \widetilde{\boldsymbol{X}}^{(j)}_{1:(T-1)}\boldsymbol{T}_n)'(\boldsymbol{X}^{(j)}_{2:T} - \widetilde{\boldsymbol{X}}^{(j)}_{1:(T-1)}\boldsymbol{T}_n),$$

$$+ (\boldsymbol{T}_n - \boldsymbol{T}_0)'\boldsymbol{\Gamma}_0(\boldsymbol{T}_n - \boldsymbol{T}_0),$$

$$\gamma_n = \gamma_0 + T - 1,$$

$$\boldsymbol{T}_n = \boldsymbol{\Gamma}_n^{-1}(\widetilde{\boldsymbol{X}}'^{(j)}_{1:(T-1)}\boldsymbol{X}^{(j)}_{2:T} + \boldsymbol{\Gamma}_0\boldsymbol{T}_0),$$

$$\boldsymbol{\Gamma}_n = \widetilde{\boldsymbol{X}}'^{(j)}_{1:(T-1)}\widetilde{\boldsymbol{X}}^{(j)}_{1:(T-1)} + \boldsymbol{\Gamma}_0.$$

542 Before updating the cluster indices z_i, the sampling of $\{\boldsymbol{x}^{(j)}_t, \mu^{(j)}_t, \delta_i, \boldsymbol{c}_i, \boldsymbol{\theta}^{(j)}\}$ is repeated several
543 times (5 times in both simulation and application for this paper). To save time, we can further allow
544 the repetitions to be pre-stopped, when the training log-likelihood converges roughly.

545 **Update z_i**   To update the cluster assignments for each neuron i, we use a partition based algorithm
546 for MFM, similarly as described in Miller and Harrison 2018.

547 Let $\mathcal{C}$ denote a partition of neurons, and $\mathcal{C}\backslash i$ denote the partition obtained by removing neuron i from
548 $\mathcal{C}$.

549   1. Initialize $\mathcal{C}$ and $\{\boldsymbol{\theta}^{(c)} : c \in \mathcal{C}\}$ (e.g. one cluster).
550   2. Repeat the following steps G times to obtain G samples. For $i = 1, \ldots, N$: remove neuron
551   i from $\mathcal{C}$ and place it:
552   (a) in $c \in \mathcal{C}\backslash i$ with probability $\propto (|c| + \gamma)M_{\boldsymbol{\theta}^{(c)}}(\boldsymbol{y}_i)$, where γ is defined in the MFM
553   model in the main text (Equation 2) and $M_{\boldsymbol{\theta}^{(c)}}(\boldsymbol{y}_i)$ denotes the marginal likelihood of
554   neuron i in cluster c, when integrating the loading $\boldsymbol{c}_i$ out (Equation (3)). The marginal
555   likelihood is approximated by using Poisson-Gamma conjugacy.
556   (b) in a new cluster c^* with probability $\propto \gamma\frac{V_n(t+1)}{V_n(t)}M_{\boldsymbol{\theta}^{(c^*)}}(\boldsymbol{y}_i)$, where t is the number of
557   partitions obtained by removing the neuron i and $V_n(t) = \sum_{j=1}^{\infty} \frac{j_{(t)}}{(\gamma j)^{(n)}} f_k(j)$, with
558            $x^{(m)} = x(x+1)\cdots(x+m-1)$, $x_{(m)} = x(x-1)\cdots(x-m+1)$, $x^{(0)} = 1$ and
559            $x_{(0)} = 1$.

560 The update is an adaptation of partition-based algorithm for DPM [Neal, 2000], but with two
561 substitutions: 1) replace $|c_i|$ by $|c_i| + \gamma$ and 2) replace α by $\gamma V_n(t+1)/V_n(t)$. See more details
562 and discussions in [Miller and Harrison, 2018]. When evaluating the likelihood, we marginalize the
563 cluster-independent loading $\boldsymbol{c}_i$ out. This is necessary for the high dimensional situation, otherwise
564 the chain will stop moving.

565 One issue with incremental Gibbs samplers such as Algorithm 3 and 8 in Neal [2000], when applied
566 to DPM, is that mixing can be somewhat slow. To further improve the mixing, we may intersperse
567 the "split-merge" Metropolis-Hasting updates [Jain and Neal, 2007, 2004] between Gibbs sweeps, as
568 in [Miller and Harrison, 2018].

A.2 Sample Latent Vectors Using Pólya-Gamma Augmentation and Metropolis-Hastings Algorithm

In this section, we provide details of sampling algorithms to draw the latent states $X^{(j)}$ and population baseline $\mu^{(j)}$ from the exact posterior of the model. In order to explain the algorithm much clearer, we just focus on a given cluster index, and thus in this section we suspend the superscript (j) as the cluster index in our notations. We present the sampling idea with two major parts as described below.

Pólya-Gamma Augmentation Although the mixDPFA model does not directly follow the PG augmentation scheme [Polson et al., 2013], we can approximate the Poisson distribution by a negative binomial (NB) distribution, i.e., $\lim_{r\to\infty} \text{NB}(r, \sigma(\psi - \log r)) = \text{Poisson}(e^\psi)$, where $\sigma(\psi) = e^\psi/(1 + e^\psi)$ and $\text{NB}(r, p)$ denotes the NB distribution with $rp/(1 - p)$ as its expectation. We approximate the proposed DPFA model using a NB, then we can instead sample a mixture of NB factor analyzers using the PG scheme [Windle et al., 2013]. Further, we use the forward-filtering-backward-sampling (FFBS) algorithm [Carter and Kohn, 1994, Frühwirth-Schnatter, 1994] to update the latent states X and population baseline μ. These two steps are summarized in the step 1 and step 2 of Algorithm 1 for updating $\widetilde{X} = (\mu, X)$.

Metropolis-Hastings Step Next, we use the samples of $\widetilde{X}$ yielded from FFBS algorithm as a proposal, where we employ a Metropolis-Hastings (MH) step to reject or accept the proposal. In this step, the dispersion parameter r in NB distribution becomes a tuning parameter, to balance acceptance rate and autocorrelation in MH. When r is large, the approximation to Poisson observation is accurate and the MH performs similar to the Gibbs sampler. Here, we allow neurons at different time points to have unique tuning parameters r_{it}. The MH step is summarized in step 3 of Algorithm 1.

We have further implemented Algorithm 1 to fit DPFA model for cluster 1 data in Fig. 2 and the results have been presented in Fig. 5. We set the tuning parameters for each neuron at all time points as $r_{it} = 10$, to tune the acceptance rate around 0.4. When implementing the PG-MH algorithm in DPFA, the ω_{it} (i.e., PG random variable) was sampled using `pgdraw` function in R package `pgdraw`, which is called from our MATLAB code. Although we can program Algorithm 1 without calling `pgdraw` function from R to save some time, to sample the PG random variable is often much computationally expensive in comparison to sample from the Gaussian random variable. When fitting the simulated data with $N = 5$, $T = 1000$ and $p = 2$ (cluster 1 data in Fig. 2) using a 3.40 GHz processor with 16 GB of RAM, it takes 131.64s for PG-MH to draw 1000 posterior samples, while the proposed approximation method in the main context of the paper takes 83.86s. Although the proposed method takes the approximation to the full conditional of the latent state X and population baseline μ, the results are similar as to sample directly from the exact full conditional. Table 1 shows the similarities, defined by cosine function, of fitted μ and $X = (X_{*1}, X_{*2})$ between the PG-MH and the Gaussian approximation for full conditional, where X_{*l} denotes the l-th latent vectors (i.e. the l-th column of X). Here, $\hat{\xi}_{\text{PGMH}}$ denotes the average from iteration 5000 to 10,000 for chain 1 of PG-MH (Fig. 5), $\hat{\xi}_{\mathcal{N}}$ denotes the average from iteration 5000 to 10,000 for the chain in Fig. 2 of the Gaussian approximation, and ξ_{true} denotes the ground truth. In each column, ξ is replaced by μ, X_{*1} and X_{*2} respectively. The posterior means for these two method are close to each other, i.e. $\cos(\hat{\xi}_{\text{PGMH}}, \hat{\xi}_{\mathcal{N}}) \approx 1$.

A.3 Supplementary Results for Neuropixels Application

This section shows supplementary results when applying the proposed model to the Neuropixels dataset (4 Multi-region neural spike recordings). Here, we show 1) results sorted by maximum a posteriori probability (MAP) estimates and 2) clustering results in another independent chain (Fig. 6).

Algorithm 1: Pólya-Gamma-Metropolis-Hastings Algorithm (PG-MH) for Poisson Dynamic Model

Recall the DPFA model using the notations defined in A.1:

$$y_{it} \sim Poi(\lambda_{it}),$$
$$\log \lambda_{it} = \delta_i + \widetilde{c}_i' \widetilde{x}_t,$$

for $i = 1, \ldots, n$ and $t = 1, \ldots, T$. Here, $\widetilde{c}_i = (1, c_i')'$ and $\widetilde{x}_t = (\mu_t, x_t')'$. $\widetilde{x}_t$ follows linear dynamics $\widetilde{x}_{t+1} | \widetilde{x}_t \sim \mathcal{N}(\widetilde{A}\widetilde{x}_t + \widetilde{b}, \widetilde{Q})$. Denote the prior as $\widetilde{x}_1 \sim \mathcal{N}(m_0, V_0)$. Given the sample from the $(G-1)$-th iteration $\widetilde{x}_t^{(G-1)}$ and $U = \{\widetilde{c}_i, \delta_i, \widetilde{A}, \widetilde{b}, \widetilde{Q}\}$.

1. sample ω_{it} from PG distribution and calculate $\hat{y}_{it}$, which follows $\mathcal{N}(\widetilde{c}_i' \widetilde{x}_t^{(G-1)}, \omega_{it}^{-1})$
for $t = 1, \ldots, T$ **do**
    for $i = 1, \ldots, n$ **do**
        sample $\omega_{it} \sim P_{PG}(r_{it} + y_{it}, \delta_i + \widetilde{c}_i' \widetilde{x}_t^{(G-1)} - \log r_{it})$
        $\kappa_{it} = (y_{it} - r_{it})/2 + \omega_{it}(\log r_{it} - \delta_i)$
        $\hat{y}_{it} = \omega_{it}^{-1} \kappa_{it}$
    end
end

2. Forward-filtering-backward-sampling (FFBS) for $\widetilde{X}$
Denote $\hat{y}_t = (\hat{y}_{1t}, \ldots, \hat{y}_{Nt})'$, $\Omega_t = Diag([\omega_{1t}, \ldots, \omega_{Nt}])$ and $\widetilde{C} = (\widetilde{c}_1, \ldots, \widetilde{c}_N)'$
for $t = 1, \ldots, T$ **do**
    $m_{t|t-1} = \widetilde{A}m_{t-1} + \widetilde{b}$
    $V_{t|t-1} = \widetilde{A}V_{t-1}\widetilde{A}' + \widetilde{Q}$
    $K_t = V_{t|t-1}\widetilde{C}'(\widetilde{C}V_{t|t-1}\widetilde{C}' + \Omega_t^{-1})^{-1}$
    $m_t = m_{t|t-1} + K_t(\hat{y}_t - \widetilde{C}m_{t|t-1})$
    $V_t = (I - K_t\widetilde{C})V_{t|t-1}$
end
sample $\widetilde{x}_T^* \sim \mathcal{N}(m_T, V_T)$
for $t = T-1, \ldots, 1$ **do**
    $J_t = V_t\widetilde{A}'(\widetilde{A}V_t\widetilde{A}' + \widetilde{Q})^{-1}$
    $m_t^* = m_t + J_t(x_{t+1}^* - \widetilde{A}m_t - \widetilde{b})$
    $V_t^* = (I - J_t\widetilde{A})V_t$
    sample $x_t^* \sim \mathcal{N}(m_t^*, V_t^*)$
end

3. Accept or reject the proposal $\widetilde{X}^*$
compute the acceptance ratio

$$\zeta = \frac{\pi(\widetilde{X}^* | \{y_i\}_{i=1}^n, U)}{\pi(\widetilde{X}^{(G-1)} | \{y_i\}_{i=1}^n, U)} \frac{q(\widetilde{X}^{(G-1)} | \widetilde{X}^*, U)}{q(\widetilde{X}^* | \widetilde{X}^{(G-1)}, U)}$$
$$= \frac{P(\{y_i\}_{i=1}^n | \widetilde{X}^*)}{P(\{y_i\}_{i=1}^n | \widetilde{X}^{(G-1)})} \frac{NB(\{y_i\}_{i=1}^n | \widetilde{X}^{(G-1)}, R)}{NB(\{y_i\}_{i=1}^n | \widetilde{X}^*, R)},$$

where $R = \{r_{it}\}$ is matrix for dispersion parameters for each neuron at all time points. $P(\cdot)$ denotes the Poisson likelihood, and $NB(\cdot)$ denotes the negative binomial likelihood. Accept the proposal $\widetilde{X}^*$ with probability $\min(1, \zeta)$.

Table 1: PG-MH vs. Gaussian approximation for μ and X

	μ	X_{*1}	X_{*2}
$\cos{(\hat{\xi}_{\text{PGMH}}, \xi_{\text{true}})}$	0.9724	0.7663	0.9728
$\cos{(\hat{\xi}_{\mathcal{N}}, \xi_{\text{true}})}$	0.9680	0.7443	0.9699
$\cos{(\hat{\xi}_{\text{PGMH}}, \hat{\xi}_{\mathcal{N}})}$	0.9435	0.9664	0.9959

Figure 5: **PG-MH for DPFA** Two independent chains (10,000 iterations) for cluster 1 data in Figure 2. The full conditional distributions of μ and X are sampled by PG-MH algorithm (Algorithm 1).**A.** Traceplot of Frobenius norms of linear dynamics. The acceptance rates in subtitle are for sampling μ and X (PG-MH step). **B.** The true (black) and fitted (colored) population baseline and latent factor. Use samples from iteration 5000 to 10,000 in chain 1, the solid orange lines show averages and the dashed lines show 95% HPD intervals.

Figure 6: **Supplementary Results for Neuropixels Application A.** The first row shows the spike counts and fitted mean firing rate, sorted according to the MAP label estimates. The second row sort the spikes further according the anatomical sites, which shows clustering structure within each region. **B.** The posterior similarity matrix sorted by MAP estimates. **C.** The ARI of MAP estimates. The diagonal is ARI between 2 chains, and the off-diagonal is mean ARI of MAP for 4 combinations. **D.** Posterior similarity matrices for the second chains. Neurons are sorted as in the first panel of Fig. 4E