From Unverifiable Domain Text to Cross-Lingual RLVR via Code-Switched Task Synthesis

Abstract

Reinforcement Learning with Verifiable Rewards (RLVR) can improve reasoning in large language models, but specialized non-English domains expose a data mismatch. Raw English domain text is often available, while target-language RLVR tasks with verifiable rewards are scarce. We introduce **code-switched task synthesis for cross-lingual RLVR**, a data-centric approach that derives target-language and code-switched RLVR task variants from otherwise unverifiable English domain text. Using fill-in-the-middle multiple-choice QA (FIM-MCQA) as a seed task format, we synthesize automatically verifiable tasks from domain passages and reshape them into cross-lingual variants. These variants preserve the same evidence-answer relation but change how English and target-language evidence are presented during RLVR. On Korean medical and cybersecurity benchmarks and in a Swahili cybersecurity setting, our synthesized code-switched data improves target-language performance over English-only, target-language-only, and bilingual-mixture training. English performance remains comparable. Analyses of answer consistency, input understanding, representation alignment, and generated reasoning consistency suggest that code-switched training helps models leverage English-dominant domain reasoning for target-language inputs beyond translated supervision alone.

1 Introduction

Reinforcement Learning with Verifiable Rewards (RLVR) has become a powerful post-training method for improving the reasoning ability of large language models (Shao et al., 2024; DeepSeek-AI et al., 2025). Its effectiveness depends on tasks whose outcomes can be automatically verified and converted into reward signals. Mathematics and programming naturally provide such tasks through exact answers, symbolic checks, or execution, but the same assumption does not generally hold for knowledge-intensive domains. Although raw text is abundant, scaling the creation of high-quality verifiable problems is difficult and time-consuming. We study this setting using cybersecurity and medicine as controlled domain testbeds (Zhang et al., 2025a; Su et al., 2025b). This limitation is more severe outside English, where domain-specific multilingual corpora are scarce and rewardable reasoning data is even scarcer (Dobler et al., 2026; Wang et al., 2026). Thus, a central obstacle for cross-lingual domain RLVR is not only how to obtain multilingual data, but how to turn that data into verifiable training signals.

A practical way to construct verifiable supervision from domain text is fill-in-the-middle multiple-choice question answering (FIM-MCQA) synthesis (Lu et al., 2026; Ren et al., 2025). FIM-MCQA masks a span from a domain passage, treats the removed span as the correct answer, and rewards the model for selecting it. This turns otherwise unverifiable raw text into an automatically verifiable task. In multilingual settings, the verified seed task can be translated into a target language to construct target-language training data.

Yet translation alone may not provide the most effective transfer signal. Multilingual reasoning gaps often stem from input understanding or cross-lingual alignment failures (Kang et al., 2025; Son et al., 2026), and specialized domains may require target-language inputs to access stronger English-side domain knowledge. Code-switching offers such a bridge by placing English and target-language evidence in the same context, but it has mainly been studied in pretraining, supervised fine-tuning, or inference-time settings (Chen et al., 2024; Zhu et al., 2024; Etxaniz et al., 2024; Yoo et al., 2025a; Wang et al., 2025b; Yoo et al., 2025b). We instead ask how to make code-switching part of the verifiable RLVR training signal itself.

We introduce **code-switched task synthesis for cross-lingual RLVR** as a data-construction ap-

proach for specialized domains where English text is available but target-language RLVR data with verifiable rewards is scarce. We synthesize FIM-MCQA seed tasks from cybersecurity and medical corpora and derive target-language and code-switched training variants that preserve the same evidence-answer relation. This design keeps the training signal compatible with standard answer-based RLVR while changing how the domain evidence is presented across languages. We evaluate the resulting data on Korean medical and cybersecurity benchmarks and in a Swahili cybersecurity transfer setting. The code-switched data improves target-language performance over monolingual and bilingual-mixture baselines, with comparable English performance. Input-level, representation-level, and reasoning-trace analyses suggest that code-switched training helps models leverage English-dominant domain reasoning for target-language beyond translated and bilingual variants.

Contributions. We introduce code-switched task synthesis for cross-lingual RLVR as a data-construction approach for domains where English text is available but target-language RLVR data with verifiable rewards is scarce. Starting from English FIM-MCQA seed tasks, we derive target-language and code-switched training variants that preserve the same evidence-answer relation and remain compatible with standard answer-based RLVR. Under matched supervision, code-switched data improves target-language performance over English-only, target-language-only, and bilingual-mixture training while maintaining comparable English performance. Analyses of answer consistency, input understanding, representations, and generated reasoning suggest that code-switched training helps target-language inputs access English-side domain reasoning beyond translated and bilingual variants.

2 Related Work

2.1 Verifiable Data Construction for RLVR

Reinforcement learning with verifiable rewards (RLVR) has become an effective post-training paradigm for improving reasoning (DeepSeek-AI et al., 2025; Shao et al., 2024). Math and programming tasks naturally support RLVR because their answers can often be checked directly, for example by exact matching or execution. In specialized, data-scarce domains, the available data often consists of raw documents rather than rewardable MCQA examples. Building verifiable MCQA

datasets by hand is costly and time-consuming.

Recent work addresses this challenge by constructing automatically verifiable tasks from text. General-Reasoner mines and re-verifies web QA pairs (Ma et al., 2025), Nemotron-CrossThink aggregates multi-domain reasoning corpora (Akter et al., 2026), and Golden Goose synthesizes fill-in-the-middle multiple-choice QA (FIM-MCQA) tasks from otherwise unverifiable text (Lu et al., 2026; Guo et al., 2026). Domain-specific resources also exist in cybersecurity or biomedical corpora mainly designed for supervised training (Yu et al., 2025b; Touchent et al., 2025a). However, prior work does not directly address how to construct verifiable domain tasks into cross-lingual training signals when target-language data is scarce from the raw text.

Our work follows the FIM-MCQA direction but uses it for a different purpose. A translated FIM-MCQA task gives target-language exposure, but it still keeps English and the target language as separate versions of the same content. We instead construct code-switched FIM-MCQA tasks, where both languages appear within a single rewardable instance. This lets the model learn the cross-lingual bridge through the same answer reward.

2.2 Multilingual Reasoning Gaps and Code-Switched Transfer

Large language reasoning models exhibits substantial gaps between English and other languages, especially in low-resource settings (Wang et al., 2026; Dobler et al., 2026; Luo et al., 2025b; Ko et al., 2025; Shi et al., 2022). Recent analyses attribute much of this gap to input understanding, where the model fails to map non-English inputs into its dominant reasoning language (Kang et al., 2025). This view is consistent with work showing that hub-language reasoning often remains more accurate than forced target-language reasoning (Tam et al., 2025; Qi et al., 2025), and with mechanistic analyses identifying dominant languages as privileged reasoning channels in multilingual LLMs (Schut et al., 2025a; Zhong et al., 2024; Wang et al., 2025a). Taken together, these findings suggest that a central bottleneck is how target-language inputs can access English-side domain knowledge and reasoning behavior.

Prior work has addressed this bottleneck through both algorithmic and data-centric routes. Algorithmic approaches modify the training framework, reasoning language, or reward design, especially

in math reasoning and machine translation settings where automatic rewards are easier to define (Zhang et al., 2025b; Feng et al., 2025a). Data-centric approaches instead change the supervision or prompting interface used for transfer, including translated or question-aligned SFT (Chen et al., 2024; Zhu et al., 2024), cross-lingual alignment or bridging methods (She et al., 2024; Yoon et al., 2024), and inference-time translation (Etxaniz et al., 2024). These methods show that language form can strongly affect cross-lingual reasoning, but they do not study how mixed-language data should be synthesized for RLVR training.

Code-switching, alternating between languages within a single context (Auer, 1998), provides a natural data-centric interface for this problem because it places source-language and target-language evidence in the same instance. Prior work uses code-switching as a cross-lingual transfer signal in pre-training with synthetic data (Wang et al., 2025b), supervised fine-tuning with curriculum learning or chain-of-thought supervision (Yoo et al., 2025b; Son et al., 2026), and inference-time demonstrations (Yoo et al., 2025a). We extend this line to multilingual RLVR by synthesizing code-switched FIM-MCQA tasks from English domain corpora. The resulting tasks expose the model to English and target-language evidence within the same rewardable instance, so cross-lingual transfer is learned from verifiable multilingual training data rather than from translation-only supervision. To our knowledge, this is the first data-centric approach that uses code-switched RLVR tasks to induce cross-lingual transfer in multilingual settings.

3 Method

3.1 Overview

We convert raw English domain corpora into cross-lingual RLVR training tasks for a resource-mismatch setting in which English domain text is available but target-language verifier-ready RLVR data is scarce. We build a source pool from cybersecurity (Yu et al., 2025c) and medical corpora (Touchent et al., 2025b). We remove boilerplate, non-educational pages, and low-quality documents. Appendix A reports the filtering rules.

Figure 1 illustrates the pipeline. First, we synthesize English FIM-MCQA seed tasks from the filtered documents. Each task masks a verbatim span in a self-contained passage and uses the removed span as the answer. Second, we derive target-language and code-switched variants from each seed task. The variants keep the same domain content but change its language form, allowing us to compare translation-only exposure, option-side code-switching, and passage-level code-switching under matched supervision.

3.2 Verifiable FIM-MCQA Synthesis

For each retained source document S, we synthesize an English FIM-MCQA seed task $q^{\text{en}} = (p^{\text{en}}_{\text{mask}}, \mathcal{A}^{\text{en}}, y)$, where $p^{\text{en}}_{\text{mask}}$ is a passage with one span replaced by [MASK], $\mathcal{A}^{\text{en}}$ is the answer-option set, and y is the correct option index. The central constraint is that the correct answer must originate from a verbatim span in the passage. This keeps the task compatible with an automatic answer-option verifier during RLVR.

Rather than asking an LLM to generate the full task in one call, we decompose synthesis into extraction, span verification, and distractor generation. The synthesizer first extracts a self-contained educational passage S' from the filtered source document. It then selects a consecutive answer span $a^\star$ from S' and is instructed to copy the span verbatim. A deterministic verifier checks that $a^\star$ appears in S' and replaces that occurrence with [MASK] to form $p^{\text{en}}_{\text{mask}}$. Examples that fail this substring check are retried or discarded.

Finally, the model generates plausible distractors conditioned on (S_{mask}, S', t). The distractors are required to match the length, format, and semantic type of the answer while avoiding direct answer leakage. The correct span and distractors are shuffled to form $\mathcal{A}^{\text{en}}$, with the correct index recorded as y. This decomposition prevents paraphrased or non-substring answers from entering the pool while keeping the reward function simple and fully automatic. The complete multi-stage extraction pipeline, and prompt templates are provided in Appendix B.

3.3 Cross-Lingual Task Variant Synthesis

Given an English FIM-MCQA seed task, we construct target-language and code-switched variants by changing how the same domain content is presented across languages. We first translate the masked passage and answer options into the target language, yielding $q^{\text{tgt}} = (p^{\text{tgt}}, \mathcal{A}^{\text{tgt}}, y)$, with the [MASK] marker preserved.

Translation gives target-language exposure, but it keeps English and the target language in separate examples. We therefore construct code-switched

Figure 1: Data construction pipeline for cross-lingual RLVR from raw English domain corpora. (a) We first extract educational passages from domain raw corpora, identify answer spans, and generate distractors to synthesize English FIM-MCQA seed tasks. We then translate each seed task into the target language and construct code-switched variants: option-side code-switching, which pairs passages and answer options across languages, and passage-level code-switching, which mixes English and target-language evidence within the passage in both directions. (b) The resulting training variants used for controlled RLVR comparisons.

variants that bring English and target-language evidence into the training task, making language form the main intervention.

Let $\mathcal{L} = \{\text{en}, \text{tgt}\}$, and write p^L for the masked passage in language L. For $u, v \in \mathcal{L}$ and $u \neq v$, we use two code-switched variants that differ in where the language boundary is placed.

Option-side code-switching. We pair a passage in one language with answer options in the other:

$$q_{\text{opt}}^{u,v} = (p^u, \mathcal{A}^v, y).$$

This trains cross-lingual matching between passage evidence and answer choices.

Passage-level code-switching. We mix languages inside the passage while keeping the options in the base language:

$$q_{\text{pass}}^{u \to v} = (c_{u \to v}(p^u), \mathcal{A}^u, y).$$

Here, $c_{u \to v}$ replaces selected content-bearing spans in p^u with fluent translations in language v.

We generate both directions, en $\to$ tgt and tgt $\to$ en. The first introduces target-language spans into English domain passages, while the second starts from target-language passages and inserts English spans. This design targets cross-lingual transfer: it trains target-language inputs to connect with English-dominant domain evidence.

Generated passages are filtered for [MASK] preservation, target-language coverage, script validity, and malformed switching patterns. The exact prompt templates, generation configurations, and detailed filtering rules are reported in Appendix D.

4 Experiments

4.1 Experimental Setting

Experimental design. We design the experiments to test whether code-switched RLVR improves cross-lingual transfer in specialized domains where English resources are abundant but target-language verifier-ready RLVR data is scarce..

We use medicine and cybersecurity as two specialized domains. Korean is our main target language because it has native domain benchmarks while remaining linguistically distant from English; we also include Swahili cybersecurity as a lower-resource transfer setting. English serves as the source language for FIM-MCQA synthesis and for constructing target-language and code-switched views.

Base models. We use three 3B-scale open-source language models: Llama 3.2-3B-Instruct (Grattafiori et al., 2024), Qwen2.5-3B-Instruct (Team, 2024), and SmolLM3-3B (Bakouch et al., 2025). These models provide a suitable base model for studying cross-lingual RLVR. These models can process target-language inputs, but their domain-level reasoning behavior is still largely English-dominant. This setting allows us to test whether target-language inputs can be better leverage reasoning behavior learned most strongly in English through various settings.

Training variants and RL setup. We compare the original checkpoint (BASE) with several RL-trained variants. RLVR-BASE is trained only on an auxiliary general-reasoning RLVR mixture, while the domain variants additionally use the synthesized domain FIM-MCQA pool from Appendix C. These domain variants differ only in how each domain example is realized across languages: EN-ONLY uses English examples, TGT-ONLY uses target-language examples, BI-MONO mixes English and target-language monolingual views, and OURS combines monolingual, Opition-side, and passage-level code-switched datasets while preserving the same answer index and verifier.

We mix domain FIM-MCQA data with the auxiliary RLVR mixture to prevent the model from overfitting to the fill-in-the-middle MCQA format and to mitigate format collapse during RLVR training. The auxiliary mixture contains general reasoning data, such as scientific reasoning, math, coding, and instruction-following prompts (Akter et al., 2026; Luo et al., 2025a; Bercovich et al., 2025), which acts as a regularizer for retaining broad free-form reasoning ability while the model acquires cross-lingual, domain-specific reasoning skills. Empirically, we found this mixing strategy to yield more stable RLVR training than using the domain-specific FIM-MCQA pool alone.

All RL variants are trained with DAPO (Yu et al., 2025a). We sample 16 rollouts per prompt, use a learning rate of 1×10^{-6}, with two epochs. Each domain variant uses the same auxiliary sampling ratio. Additional details on the variants and training configurations are provided in Appendix E.

Evaluation. We evaluate target-language and English performance in both domains. For medicine, we use MedQA (Jin et al., 2020), MedMCQA (Pal et al., 2022), KorMedMCQA-Doctor (Kweon et al., 2024), and KMMLU-Pro-Medical (Hong et al., 2025). For cybersecurity, we use CTI-MCQ, CyberMetric, and SecEval (Yu et al., 2025c; Li et al., 2023). Because this task primarily targets non-English performance, we select the best checkpoint based on target-language validation scores. The translation process and subsequent quality evaluations of translated benchmarks are described in Appendices F and G, respectively.

4.2 Experimental Results

Table 1 shows the medical results for Qwen2.5-3B-Instruct and Llama-3.2-3B-Instruct. RLVR improves performance across languages, regardless of whether the domain examples are presented in English, Korean, or mixed-language form. The gains are particularly clear when the training mixture includes in-domain medical FIM-MCQA data. EN-ONLY and KO-ONLY often outperform the RLVR-BASE, showing that the improvement comes not only from additional RL optimization but also from rewardable examples in the target domain.

We next compare different language realizations of the same domain data. Bilingual exposes the model to both English and Korean, but they do not consistently outperform the monolingual domain baselines. This suggests that simply adding translated views or mixing languages at the instance level is not enough to reliably improve target-language reasoning.

The main improvement appears when code-switched examples are added. Across both medical model families, OURS gives more consistent gains on Korean benchmarks than the monolingual and bilingual baselines. On Korean-native benchmarks such as KMMLU-Pro-Medical and KorMedMCQA-Doctor, it improves over all non-code-switched baselines by more than one point. It also improves translated medical QA performance over both EN-ONLY and KO-ONLY, indicating that code-switching helps not only on native Korean benchmarks but also on Korean versions of English medical reasoning tasks.

A similar pattern appears beyond this Ko-

Bench.	Qwen2.5-3B-Instruct					Llama-3.2-3B-Instruct				
	RLVR-Base	+En	+Tgt	+BiMono	+Ours	RLVR-Base	+En	+Tgt	+BiMono	+Ours
Target Language										
KorMedMQ-D	35.06	35.34	35.29	35.34	**36.67**	21.10	27.93	27.47	28.79	**29.31**
MedMCQA*	34.52	33.96	34.03	33.72	**34.86**	24.26	27.12	27.36	**29.65**	29.22
KMMLU-Pro-M	35.45	35.76	36.21	36.06	**36.29**	22.84	24.77	24.09	25.08	**26.36**
Tgt Lang Avg	35.01	35.02	35.18	35.04	**35.94**	22.73	26.61	26.31	27.84	**28.30**
English										
KorMedMQ-D*	57.74	58.05	**61.03**	60.06	58.74	50.01	56.72	57.30	57.53	**57.93**
MedMCQA	**47.88**	47.60	47.42	47.34	47.01	52.57	55.00	55.00	**55.17**	55.04
MedQA	48.65	50.92	50.47	**51.47**	50.65	52.38	58.19	58.37	**58.92**	58.82
En Avg	51.42	52.19	**52.97**	52.96	52.13	51.65	56.64	56.89	57.21	**57.26**

Table 1: Comprehensive performance on medical benchmarks across RLVR data configurations. RLVR-BASE denotes RLVR training using only the auxiliary data pool. The remaining variants include the same auxiliary pool and additionally use English data (+EN), target-language data (+TGT), bilingual monolingual data (+BIMONO), or our proposed code-switched data (+OURS). English rows are shown in gray to indicate source-language evaluation, which is reported as a retention check rather than the primary target-language transfer metric. The asterisk (*) indicates that the benchmark is translated into the respective language.

rean medical setting. As presented in Table 1, results from the cybersecurity and additional target-language experiments show that code-switched RLVR again yields stronger average target-language performance than monolingual or bilingual-only training. Overall, these results suggest that code-switched examples act as an effective cross-lingual bridge, helping target-language inputs access the model's English-dominant domain reasoning behavior. Additionally, full results includes base model performance in Appendix M.

4.3 Cross-lingual Consistency

To test whether code-switched RLVR reduces the language barrier between English and Korean inputs, we measure accuracy-preserving cross-lingual consistency on parallel cybersecurity questions. For each English–Korean question pair, we partition model predictions into four mutually exclusive cases: both languages correct, English-only correct and Korean-only correct. The both-correct rate captures language-invariant correct decisions, whereas the English-only and Korean-only gap captures directional answer asymmetry.

As shown in Table 3, OURS achieves the strongest accuracy-preserving consistency and reduces asymmetry. This suggests that the code-switched data does more than add translated supervision: it helps Korean input elicit the same answer decisions as their English counterparts, providing empirical evidence for the cross-lingual bridge.

5 Analysis

Table 3 shows that Code-switched RLVR improves cross-lingual consistency, but the source of this gain is not obvious from answer accuracy alone. Following the view that multilingual reasoning gaps arise when target-language inputs fail to reach the model's dominant, often English-proximal, reasoning pathway, we test whether OURS reduces this gap at three levels: input understanding, internal representation, and generated reasoning behavior.

5.1 In-domain Translation Quality

We first test whether the OURS gain begins at the input-understanding stage. Prior work argues that multilingual reasoning gaps often arise because the model fails to map non-English inputs into the dominant language of its reasoning trace, typically English (Kang et al., 2025). We therefore use in-domain Korean-to-English translation quality as a diagnostic proxy for how well a model recovers the English-side semantic content of Korean questions. We compare this score with the reasoning performance ratio, defined as Korean accuracy divided by accuracy on the matched English benchmark. Details of the translation prompt, GEMBA-DA scoring, and metrics are provided in Appendix I.

Figure 2 shows that in-domain translation quality closely tracks retained Korean reasoning performance. The correlation is near-perfect on Cyber-Metric ($r = 0.998$) and remains high on KMMLU-Pro-Medical ($r = 0.967$). In both domains, the

Bench.	SmolLM3-3B									
	Korean					Swahili				
	RLVR-Base	+En	+Tgt	+BiMono	+Ours	RLVR-Base	+En	+Tgt	+BiMono	+Ours
Target Language										
SecEval*	44.3	50.1	49.8	51.1	**57.3**	25.8	26.8	**28.6**	25.9	28.3
CyberMetric*	65.8	70.6	**80.2**	72.4	80.0	54.0	53.9	54.2	54.5	**55.0**
CTI-MCQ*	40.6	43.2	45.5	43.8	**47.1**	41.9	42.1	43.2	43.4	**45.0**
Tgt Lang Avg	50.23	54.63	58.50	55.77	**61.47**	40.57	40.93	42.00	41.27	**42.77**
English										
SecEval	56.7	59.9	61.7	58.9	**62.7**	56.7	59.9	65.6	65.3	**66.6**
CyberMetric	83.0	83.6	**85.6**	84.4	**85.6**	83.0	83.6	86.3	86.0	**86.6**
CTI-MCQ	54.9	**57.5**	56.2	57.1	56.5	54.9	57.5	**61.1**	60.9	60.3
En Avg	64.87	67.00	67.83	66.80	**68.27**	64.87	67.00	71.00	70.73	**71.17**

Table 2: Comprehensive performance on cybersecurity benchmarks across RLVR data configurations. **Target Language** indicates Korean for the left and Swahili for the right. All other notations and formatting follow Table 1.

(English, Korean)	(✓,✓)↑	(✓,✗)↓	(✗,✓)↓
Base	15.1	28.2	13.0
En-only	28.1	30.0	7.3
Bi-Mono	29.2	29.8	7.1
Ours	**34.8**	**27.1**	**6.7**

Table 3: Cross-lingual consistency comparison on cybersecurity benchmarks. This table aggregates the outcomes of English and Korean question pairs across cybersecurity domain benchmarks. ✓ denotes a correct answer, and × denotes an incorrect answer. **Bold** indicates the most consistent results.

Figure 2: Reasoning performance ratio vs. in-domain Korean-to-English translation quality for (a) Cyber-Metric (SmolLM3-3B) and (b) KMMLU-Pro-Medical (Llama-3.2-3B-Instruct). Dashed lines show linear trends; r denotes Pearson correlation.

code-switched model lies toward the upper-right region, indicating that it both recovers the English-side meaning of Korean inputs more accurately and preserves a larger fraction of its English reasoning performance. This supports the view that code-switched RLVR reduces the target-language understanding bottleneck before reasoning begins.

5.2 Latent Reasoning State Alignment

The translation analysis suggests that part of the OURS gain comes from better semantic recovery of Korean inputs. We next ask whether this gain is visible at the point where the model begins to reason. We analyze the SmolLM3-3B ablation models on a fixed parallel English–Korean subset of CyberMetric. For each question pair, we append the same opening reasoning token, <think>, and extract the hidden state at that token before any reasoning chaint-of-thoughts(CoTs) are generated. We measure English–Korean alignment across layers

with Mean-Centered Cosine and Average Neuron-wise Correlation (ANC) (Del and Fishel, 2022a). Details of experiment settings and metric definitions are provided in Appendix J.

Figure 3 shows a common depth pattern across models: English–Korean similarity rises in the middle layers, where cross-lingual semantic representations are expected to become more comparable. The important difference is the magnitude of this convergence. In the highlighted layer band, OURS consistently achieves higher similarity than the non-code-switched variants across all three measures. Thus, the baselines do show some middle-layer alignment, but their English and Korean reasoning-entry states remain less tightly matched than those of OURS. This is especially informative because BI-MONO already includes bilingual supervision; exposure to both languages alone does not pro-

Figure 3: Layer-wise English–Korean representation alignment on CyberMetric, measured at the opening `<think>` marker. Our method shows stronger middle-to-upper layer alignment than the non-code-switched baselines. The gray area marks middle layers 12–24.

Win Rate(%)	vs. EN-ONLY		vs. TGT-ONLY	
	Ours	En-only	Ours	Tgt-only
Medical				
Qwen2.5	**50.0**	36.0	**44.0**	43.0
Llama3.2	**46.0**	38.5	**42.5**	41.0
Cyber				
SmolLM3	**42.5**	31.3	**60.7**	18.7

Table 4: Pairwise judge win rates to measure cross-lingual reasoning consistency using GPT-5.5. The target language is Korean. The reported results are aggregated across benchmarks within each domain (evaluating 50 samples per benchmark). Our method demonstrates consistent improvement across all models and baselines.

duce the same level of alignment as adding code-switched training dataset.

This depth profile is consistent with prior findings that multilingual models often form their most comparable cross-lingual semantic states in the middle layers (Muller et al., 2021; Liu and Niehues, 2025), and with the view that non-English inputs may pass through an English-proximal reasoning space before target-language realization (Schut et al., 2025b). Under this interpretation, code-switched RLVR does not create cross-lingual alignment from scratch. Instead, it amplifies the natural middle-layer convergence and narrows the English–Korean gap at the reasoning-entry state.

5.3 Generated Reasoning Trace Alignment

The representation analysis above suggests that code-switched RLVR better aligns English and target-language inputs. We further examine whether this alignment is reflected in the model's generated reasoning CoTs. To this end, we conduct a pairwise LLM-as-a-judge evaluation that compares OURS with monolingual RLVR baselines. For each example, the judge is given English and target-language outputs from two systems and selects the system whose two outputs are more semantically consistent in high-level reasoning, problem decomposition, and solution strategy. We use GPT-5.5 as the judge model and swap the order to mitigate position bias. The full evaluation details are provided in Appendix K.

Table 4 shows that our consistently outperforms EN-ONLY across all evaluated model-domain settings, with gains of +14.0, +7.5, and +4.7 points for Qwen2.5-3B-Instruct, Llama-3.2-3B-Instruct, and SmolLM3-3B, respectively. Compared with

TGT-ONLY, OURS is comparable in the medical domain and substantially better in cybersecurity. These results suggest that code-switched RLVR helps the model leverage English-side domain reasoning when solving target-language problems.

6 Conclusion

This work proposes cross-lingual RLVR in specialized domains as a data construction problem to alleviate data scarcity issue in the RLVR framework. We build on FIM-MCQA synthesis to obtain rewardable seed tasks from English cybersecurity and medical documents, then reshape those tasks into target-language and code-switched training data. This lets us study how the language form of the same domain evidence affects transfer under a standard RLVR training. The results show that our synthesized code-switched data provides stronger target-language transfer than translation-only or bilingual-mixture training, while English performance remains comparable. The analyses give a consistent explanation. Code-switched training improves answer agreement across languages, supports better recovery of target-language input meaning, strengthens English–target representation alignment, and produces more consistent reasoning traces. These findings suggest that code-switched task synthesis is a practical way to help models leverage English-dominant domain reasoning for target-language inputs in data-scarce multilingual domains.

Limitations

Our study uses a controlled but computationally demanding RLVR setup. We train multiple domain–language–model variants with the same RL algo-

rithm and data mixture, and each training variant requires approximately 2,500 H100 GPU hours. This cost prevents exhaustive search over training schedules, data mixtures, rollout budgets, and model scale. Prior work suggests that longer or more carefully staged RL training (Liu et al., 2026), as well as larger rollout budgets (Hu et al., 2025), can further affect reasoning performance. We therefore interpret our results as evidence for the effectiveness of code-switched task synthesis under a practical compute budget, rather than as a fully optimized upper bound. For the same reason, we focus on 3B-scale open-source models, which make controlled comparisons feasible across domains, languages, and training variants.

A second limitation is evaluation coverage. While English domain benchmarks are widely available, comparable target-language benchmarks are scarce, especially outside high-resource languages. As a result, our cybersecurity evaluation relies partly on translated benchmarks. These translations may introduce artifacts or differ from naturally written target-language questions. We mitigate this issue with domain-aware translation prompts and translation quality checks in Appendix G. We also include native Korean medical benchmarks, which provide a complementary test beyond translated evaluation.

Finally, our language and domain coverage is limited. We use Korean as the main target language and add Swahili cybersecurity experiments as a lower-resource setting, but many multilingual scenarios remain unexplored. Extending code-switched task synthesis to extremely low-resource languages and broader domain settings is left for future work.

References

Sandhini Agarwal, Lama Ahmad, Jason Ai, Sam Altman, Andy Applebaum, Edwin Arbus, Rahul K Arora, Yu Bai, Bowen Baker, Haiming Bao, and 1 others. 2025. gpt-oss-120b & gpt-oss-20b model card. *arXiv preprint arXiv:2508.10925*.

Syeda Nahida Akter, Shrimai Prabhumoye, Matvei Novikov, Seungju Han, Ying Lin, Evelina Bakhturina, Eric Nyberg, Yejin Choi, Mostofa Patwary, Mohammad Shoeybi, and Bryan Catanzaro. 2026. Nemotron-CrossThink: Scaling self-learning beyond math reasoning. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 984–1002, Rabat, Morocco. Association for Computational Linguistics.

Md Tanvirul Alam, Dipkamal Bhusal, Le Nguyen, and Nidhi Rastogi. 2024. Ctibench: A benchmark for evaluating llms in cyber threat intelligence. *Advances in Neural Information Processing Systems*, 37:50805–50825.

Peter Auer. 1998. *Code-Switching in Conversation: Language, Interaction and Identity*. Routledge, London.

Elie Bakouch, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Lewis Tunstall, Carlos Miguel Patiño, Edward Beeching, Aymeric Roucher, Aksel Joonas Reedi, Quentin Gallouédec, Kashif Rasul, Nathan Habib, Clémentine Fourrier, Hynek Kydlicek, Guilherme Penedo, Hugo Larcher, Mathieu Morlon, Vaibhav Srivastav, Joshua Lochner, and 4 others. 2025. SmolLM3: smol, multilingual, long-context reasoner. https://huggingface.co/blog/smollm3.

Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, Ido Shahaf, Oren Tropp, Ehud Karpas, Ran Zilberstein, Jiaqi Zeng, Soumye Singhal, Alexander Bukharin, Yian Zhang, Tugrul Konuk, and 114 others. 2025. Llama-nemotron: Efficient reasoning models. *Preprint*, arXiv:2505.00949.

Marianne Busch, Nora Koch, and Martin Wirsing. 2014. Seceval: an evaluation framework for engineering secure systems. In *Modellierung 2014*, pages 337–352. Gesellschaft für Informatik eV.

Nuo Chen, Zinan Zheng, Ning Wu, Ming Gong, Dongmei Zhang, and Jia Li. 2024. Breaking language barriers in multilingual mathematical reasoning: Insights and observations. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 7001–7016, Miami, Florida, USA. Association for Computational Linguistics.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, and 1 others. 2025. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Maksym Del and Mark Fishel. 2022a. Cross-lingual similarity of multilingual representations revisited. In *Proceedings of the 2nd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 12th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 185–195, Online only. Association for Computational Linguistics.

Maksym Del and Mark Fishel. 2022b. Cross-lingual similarity of multilingual representations revisited. In *Proceedings of the 2nd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 12th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 185–195.

Konstantin Dobler, Simon Lehnerer, Federico Scozzafava, Jonathan Janke, and Mohamed Ali. 2026. macereason-math: A dataset of high-quality multilingual math problems ready for rlvr. *arXiv preprint arXiv:2603.10767*.

Kawin Ethayarajh. 2019. How contextual are contextualized word representations? Comparing the geometry of BERT, ELMo, and GPT-2 embeddings. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 55–65, Hong Kong, China. Association for Computational Linguistics.

Julen Etxaniz, Gorka Azkune, Aitor Soroa, Oier Lopez de Lacalle, and Mikel Artetxe. 2024. Do multilingual language models think better in English? In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pages 550–564, Mexico City, Mexico. Association for Computational Linguistics.

Zhaopeng Feng, Shaosheng Cao, Jiahan Ren, Jiayuan Su, Ruizhe Chen, Yan Zhang, Jian Wu, and Zuozhu Liu. 2025a. MT-R1-Zero: Advancing LLM-based machine translation via R1-Zero-like reinforcement learning. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 18685–18702, Suzhou, China. Association for Computational Linguistics.

Zhaopeng Feng, Jiayuan Su, Jiamei Zheng, Jiahan Ren, Yan Zhang, Jian Wu, Hongwei Wang, and Zuozhu Liu. 2025b. M-mad: Multidimensional multi-agent debate for advanced machine translation evaluation. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7084–7107.

Gemma Team and Google DeepMind. 2026. Gemma 4 model card. https://ai.google.dev/gemma/docs/core/model_card_4. Accessed: 2026-05-26.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Xu Guo, Qiming Ge, Jian Tong, Kedi Chen, Jin Zhang, Xiaogui Yang, Xuan Gao, Haijun Lv, Zhihui Lu, Yicheng Zou, and Qipeng Guo. 2026. Rethinking multiple-choice questions for RLVR: Unlocking potential via distractor design. *arXiv preprint arXiv:2603.12826*.

Seokhee Hong, Sunkyoung Kim, Guijin Son, Soyeon Kim, Yeonjung Hong, and Jinsik Lee. 2025. From kmmlu-redux to kmmlu-pro: A professional korean benchmark suite for llm evaluation. *Preprint*, arXiv:2507.08924.

Jian Hu, Mingjie Liu, Ximing Lu, Fang Wu, Zaid Harchaoui, Shizhe Diao, Yejin Choi, Pavlo Molchanov, Jun Yang, Jan Kautz, and 1 others. 2025. Brorl: Scaling reinforcement learning via broadened exploration. *arXiv preprint arXiv:2510.01180*.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. 2020. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *arXiv preprint arXiv:2009.13081*.

Deokhyung Kang, Seonjeong Hwang, Daehui Kim, Hyounghun Kim, and Gary Geunbae Lee. 2025. Why do multilingual reasoning gaps emerge in reasoning language models? *arXiv preprint arXiv:2510.27269*.

Hyunwoo Ko, Guijin Son, and Dasol Choi. 2025. Understand, solve and translate: Bridging the multilingual mathematical reasoning gap. In *Proceedings of the 5th Workshop on Multilingual Representation Learning (MRL 2025)*, pages 78–95, Suzhuo, China. Association for Computational Linguistics.

Sunjun Kweon, Byungjin Choi, Gyouk Chu, Junyeong Song, Daeun Hyeon, Sujin Gan, Jueon Kim, Minkyu Kim, Rae Woong Park, and Edward Choi. 2024. Kormedmcqa: Multi-choice question answering benchmark for korean healthcare professional licensing examinations. *arXiv preprint arXiv:2403.01469*.

Guancheng Li, Yifeng Li, Wang Guannan, Haoyu Yang, and Yang Yu. 2023. Seceval: A comprehensive benchmark for evaluating cybersecurity knowledge of foundation models. https://github.com/XuanwuAI/SecEval.

Danni Liu and Jan Niehues. 2025. Middle-layer representation alignment for cross-lingual transfer in finetuned llms. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15979–15996.

Mingjie Liu, Shizhe Diao, Ximing Lu, Jian Hu, Xin Dong, Yejin Choi, Jan Kautz, and Yi Dong. 2026. ProRL: Prolonged reinforcement learning expands reasoning boundaries in large language models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Ximing Lu, David Acuna, Jaehun Jung, Jian Hu, Di Zhang, Shizhe Diao, Yunheng Zou, Shaokun Zhang, Brandon Cui, Mingjie Liu, Hyunwoo Kim, Prithviraj Ammanabrolu, Jan Kautz, Yi Dong, and Yejin Choi. 2026. Golden goose: A simple trick to synthesize unlimited RLVR tasks from unverifiable internet text. *arXiv preprint arXiv:2601.22975*.

Michael Luo, Sijun Tan, Justin Wong, Xiaoxiang Shi, William Tang, Manan Roongta, Colin Cai, Jeffrey Luo, Tianjun Zhang, Erran Li, Raluca Ada Popa, and Ion Stoica. 2025a. Deepscaler: Surpassing o1-preview with a 1.5b model by scaling rl. Notion Blog.

Wenyang Luo, Wayne Xin Zhao, Jing Sha, Shijin Wang, and Ji-Rong Wen. 2025b. MMATH: A multilingual benchmark for mathematical reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 11187–11202, Suzhou, China. Association for Computational Linguistics.

Xueguang Ma, Qian Liu, Dongfu Jiang, Ge Zhang, Zejun Ma, and Wenhu Chen. 2025. General-Reasoner: Advancing LLM reasoning across all domains. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Benjamin Muller, Yanai Elazar, Benoît Sagot, and Djamé Seddah. 2021. First align, then predict: Understanding the cross-lingual ability of multilingual bert. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2214–2231.

OpenAI. 2025. Introducing GPT-4.1 in the API. https://openai.com/index/gpt-4-1/. Accessed: 2026-05-26.

OpenAI. 2026a. GPT-5.5 system card. Technical report, OpenAI. Accessed: 2026-05-26.

OpenAI. 2026b. Introducing GPT-5.4 mini and nano. https://openai.com/index/introducing-gpt-5-4-mini-and-nano/. Accessed: 2026-05-26.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. 2022. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. In *Proceedings of the Conference on Health, Inference, and Learning*, volume 174 of *Proceedings of Machine Learning Research*, pages 248–260. PMLR.

Jirui Qi, Shan Chen, Zidi Xiong, Raquel Fernández, Danielle Bitterman, and Arianna Bisazza. 2025. When models reason in your language: Controlling thinking language comes at the cost of accuracy. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 20279–20296, Suzhou, China. Association for Computational Linguistics.

Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. 2020. Comet: A neural framework for mt evaluation. In *Proceedings of the 2020 conference on empirical methods in natural language processing (emnlp)*, pages 2685–2702.

Houxing Ren, Zimu Lu, Weikang Shi, Haotian Hou, Yunqiao Yang, Ke Wang, Aojun Zhou, Junting Pan, Mingjie Zhan, and Hongsheng Li. 2025. Alignment with fill-in-the-middle for enhancing code generation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 8304–8320, Suzhou, China. Association for Computational Linguistics.

Lisa Schut, Yarin Gal, and Sebastian Farquhar. 2025a. Do multilingual llms think in english? *CoRR*, abs/2502.15603.

Lisa Schut, Yarin Gal, and Sebastian Farquhar. 2025b. Do multilingual llms think in english? *arXiv preprint arXiv:2502.15603*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Shuaijie She, Wei Zou, Shujian Huang, Wenhao Zhu, Xiang Liu, Xiang Geng, and Jiajun Chen. 2024. MAPO: Advancing multilingual reasoning through multilingual-alignment-as-preference optimization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10015–10027, Bangkok, Thailand. Association for Computational Linguistics.

Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2022. Language models are multilingual chain-of-thought reasoners. *Preprint*, arXiv:2210.03057.

Guijin Son, Donghun Yang, Hitesh Laxmichand Patel, Amit Agarwal, Hyunwoo Ko, Chanuk lim, Srikant Panda, Minhyuk Kim, Nikunj drolia, Dasol Choi, Kyong-Ha Lee, and Youngjae Yu. 2026. Pushing on multilingual reasoning models with language-mixed chain-of-thought. In *The Fourteenth International Conference on Learning Representations*.

Dan Su, Kezhi Kong, Ying Lin, Joseph Jennings, Brandon Norick, Markus Kliegl, Mostofa Patwary, Mohammad Shoeybi, and Bryan Catanzaro. 2025a. Nemotron-cc: Transforming common crawl into a refined long-horizon pretraining dataset. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2459–2475.

Yi Su, Dian Yu, Linfeng Song, Juntao Li, Haitao Mi, Zhaopeng Tu, Min Zhang, and Dong Yu. 2025b. Crossing the reward bridge: Expanding rl with verifiable rewards across diverse domains. *arXiv preprint arXiv:2503.23829*.

Zhi Rui Tam, Cheng-Kuang Wu, Yu Ying Chiu, Chieh-Yen Lin, Yun-Nung Chen, and Hung-yi Lee. 2025. Language matters: How do multilingual input and reasoning paths affect large reasoning models? *arXiv preprint arXiv:2505.17407*.

Qwen Team. 2024. Qwen2.5: A party of foundation models.

Norbert Tihanyi, Mohamed Amine Ferrag, Ridhi Jain, Tamas Bisztray, and Merouane Debbah. 2024. Cybermetric: A benchmark dataset based on retrieval-augmented generation for evaluating llms in cybersecurity knowledge. In *2024 IEEE International Conference on Cyber Security and Resilience (CSR)*, pages 296–302. IEEE.

William Timkey and Marten van Schijndel. 2021. All bark and no bite: Rogue dimensions in transformer language models obscure representational quality. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4527–4546, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Rian Touchent, Nathan Godey, and Eric de la Clergerie. 2025a. Biomed-Enriched: A biomedical dataset enriched with LLMs for pretraining and extracting rare and hidden content. *arXiv preprint arXiv:2506.20331*.

Rian Touchent, Nathan Godey, and Eric de la Clergerie. 2025b. Biomed-enriched: A biomedical dataset enriched with llms for pretraining and extracting rare and hidden content. *Preprint*, arXiv:2506.20331.

Mingyang Wang, Lukas Lange, Heike Adel, Yunpu Ma, Jannik Strötgen, and Hinrich Schuetze. 2025a. Language mixing in reasoning language models: Patterns, impact, and internal causes. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 2637–2665, Suzhou, China. Association for Computational Linguistics.

Yiming Wang, Pei Zhang, Jialong Tang, Hao-Ran Wei, Baosong Yang, Rui Wang, Chenshu Sun, Feitong Sun, Jiran Zhang, Junxuan Wu, and 1 others. 2026. Polymath: Evaluating mathematical reasoning in multilingual contexts. *Advances in Neural Information Processing Systems*, 38.

Zhijun Wang, Jiahuan Li, Hao Zhou, Rongxiang Weng, Jingang Wang, Xin Huang, Xue Han, Junlan Feng, Chao Deng, and Shujian Huang. 2025b. Investigating and scaling up code-switching for multilingual language model pre-training. In *Findings of the Association for Computational Linguistics: ACL 2025*. Association for Computational Linguistics. ArXiv:2504.01801.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Haneul Yoo, Jiho Jin, Kyunghyun Cho, and Alice Oh. 2025a. Code-switching in-context learning for cross-lingual transfer of large language models. *arXiv preprint arXiv:2510.05678*.

Haneul Yoo, Cheonbok Park, Sangdoo Yun, Alice Oh, and Hwaran Lee. 2025b. Code-switching curriculum learning for multilingual transfer in LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 7816–7836, Vienna, Austria. Association for Computational Linguistics.

Dongkeun Yoon, Joel Jang, Sungdong Kim, Seungone Kim, Sheikh Shafayat, and Minjoon Seo. 2024. LangBridge: Multilingual reasoning without multilingual supervision. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7502–7522, Bangkok, Thailand. Association for Computational Linguistics.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Tiantian Fan, Gaohong Liu, Lingjun Liu, Xin Liu, and 1 others. 2025a. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*.

Yao-Ching Yu, Tsun-Han Chiang, Cheng-Wei Tsai, Chien-Ming Huang, and Wen-Kwang Tsao. 2025b. Primus: A pioneering collection of open-source datasets for cybersecurity LLM training. *arXiv preprint arXiv:2502.11191*.

Yao-Ching Yu, Tsun-Han Chiang, Cheng-Wei Tsai, Chien-Ming Huang, and Wen-Kwang Tsao. 2025c. Primus: A pioneering collection of open-source datasets for cybersecurity LLM training. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 10391–10413, Suzhou, China. Association for Computational Linguistics.

Sheng Zhang, Qianchu Liu, Guanghui Qin, Tristan Naumann, and Hoifung Poon. 2025a. Med-RLVR: Emerging medical reasoning from a 3B base model via reinforcement learning. *arXiv preprint arXiv:2502.19655*.

Xue Zhang, Yunlong Liang, Fandong Meng, Songming Zhang, Kaiyu Huang, Yufeng Chen, Jinan Xu, and Jie Zhou. 2025b. Think natively: Unlocking multilingual reasoning with consistency-enhanced reinforcement learning. *arXiv preprint arXiv:2510.07300*.

Chengzhi Zhong, Fei Cheng, Qianying Liu, Junfeng Jiang, Zhen Wan, Chenhui Chu, Yugo Murawaki, and Sadao Kurohashi. 2024. Beyond english-centric llms: What language do multilingual language models think in? *CoRR*, abs/2408.10811.

Wenhao Zhu, Shujian Huang, Fei Yuan, Shuaijie She, Jiajun Chen, and Alexandra Birch. 2024. Question translation training for better multilingual reasoning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 8411–8423, Bangkok, Thailand. Association for Computational Linguistics.

Appendix

We provide detailed supplementary materials organized as follows:

A Source Corpora and Pre-filtering Details

Cybersecurity For the cybersecurity domain, we use the Primus dataset (Yu et al., 2025b), an open-source corpus released by Trend Micro for training cybersecurity large language models. It consists of two sub-corpora: *Primus-Seed*, a manually curated, high-quality collection of documents gathered from MITRE, Wikipedia, major security vendor websites, and expert-collected Cyber Threat Intelligence (CTI); and *Primus-FineWeb*, which filters cybersecurity-related texts from FineWeb using a TinyBERT classifier trained with Primus-Seed as positive samples.

We combine these two sub-corpora into Primus-Pretraining and apply an additional educational quality filter. We include only documents that score ≥ 2.2 (on a scale of 0 to 5) using nemocurator-fineweb-nemotron-4-edu-classifier[1] (Su et al., 2025a). Although the default high-quality threshold for this classifier is 2.5, cybersecurity domain texts tend to receive slightly lower average scores compared to general-purpose educational texts. Therefore, we adopt a slightly more permissive threshold of 2.2. Combining these two sources yields a total of 500k seed documents.

Medical For the medical domain, we utilize the Biomed-Enriched dataset (Touchent et al., 2025a), which annotates the PubMed Open Access (PMC-OA) corpus with document types, domains, and educational quality scores. We use the commercial split of this dataset and filter the seed documents based on the following criteria: an educational score of 4 or higher, domains categorized as either clinical or biomedical, and document types restricted to reviews and clinical cases. Furthermore, we exclude the "reference" sections and require all texts to have a minimum length of 200 characters. This filtering process results in a total of 450k seed documents.

B Details of FIM-MCQA synthesis

Our data construction pipeline converts raw documents into verifiable training tasks through a multi-stage process.

In the first phase, we utilize the gpt-oss-120b (Agarwal et al., 2025), configured with a medium reasoning effort, to simultaneously extract an educational passage and identify the target span for masking. If the document lacks educational content, the model is instructed to generate an empty response, ensuring this data is filtered out and does not proceed to the next phase.

Next, a deterministic programmatic verifier processes the passage and the identified span (S', t) to construct the masked text. This programmatic layer applies a 4-tier matching protocol, consisting of exact, strip, NFKC, and fuzzy matching, to locate the

---

[1]https://huggingface.co/nvidia/nemocurator-fineweb-nemotron-4-edu-classifier

Domain	n	Source
Cybersecurity	207,048	Primus-Seed, Primus-FineWeb
Medical	158,714	Biomed-Enriched
Total	**365,762**	

Table 5: Synthesized FIM-MCQA data pool per domain. Note that for each domain-target language pair, an identical number of samples is constructed across all training variants, matching the exact counts reported in the table. The subsample used for training is described in Appendix E.

Domain	Model	Pool	Filtered
Medical	Qwen2.5-3B-Instruct	158,714	**50,476**
Medical	Llama-3.2-3B-Instruct	158,714	**44,294**
Cybersecurity	SmolLM3-3B	207,048	**43,705**

Table 6: Number of Effective Samples after the difficulty filtering stage.

span within the passage. It then replaces the verified substring with a [MASK] marker to produce the masked passage S_{mask}. If the substring check fails across all formatting tiers, the instance is rejected.

Finally, the gpt-oss-120b (Agarwal et al., 2025) (again with medium reasoning effort) generates the multiple-choice distractors. The model is prompted to create distractors such that each question contains a total of nine options, including the correct answer.

To ensure the quality of the constructed dataset, we apply a difficulty filtering step using the Qwen3-4b-Instruct-2507 (Yang et al., 2025). Specifically, for each question, we sample the model's responses 8 times, setting the temperature to 0.7 and the maximum token length to 6000. The statistics of the final filtered dataset are detailed in Appendix C.

For the exact instructions, please refer to the detailed prompt templates provided in Figure 8, 9, 10, 11.

C   Final data statistics

Table 5 summarizes the synthesized data pool by domain. We refer to this as a synthesized pool rather than the final training set, because our training runs use controlled subsamples and mix them with Auxilary data as described in §4.

D   Details of Cross-lingual Task Variant Synthesis

D.1   Details of Translation

We synthesize the TGT-ONLY data by fully translating the EN-ONLY dataset. For the translation process, we utilize the Gemma-4-26B-A4B-it (Gemma Team and Google DeepMind, 2026) model configured with thinking=off. We translate the passages and multiple-choice options separately. This separate processing ensures the strict preservation of the [MASK] tokens and addresses the empiri-

cal tendency of large language models to undertranslate or truncate long contexts. To mitigate this generation issue, passages are segmented and translated on a sentence-by-sentence basis, and the options are similarly split and translated individually. Furthermore, we provide few-shot exemplars within the prompt to enhance overall translation quality. Domain-specific terminology that must remain untranslated is managed separately via literal passthrough rules. The exact translation prompts are provided in Figure 12 and Figure 13.

D.2   Details of Code-switching Process

We construct the option-side code-switching data by cross-matching the passages and multiple-choice options from the TGT-ONLY and EN-ONLY datasets. For the passage-level code-switched data, we utilize the Gemma-4-26B-A4B-it (Gemma Team and Google DeepMind, 2026) model configured with thinking=off. The code-switching pipeline operates by prompting the model to replace selected segments of a source passage with their target language counterparts. The model is strictly constrained to ensure contextual fluency, uniform span dispersion, and the exact preservation of [MASK] markers. The full prompt template is described at Figure 14.

Following the generation, we enforce a post-hoc filtering step: if the cumulative character length of the switched spans constitutes less than 15% of the total passage length, the generation is retried up to three times, with the decoding temperature increased by 0.3 for each sequential attempt.

E   Additional Training Details

Model-specific effective sample filtering. To isolate effective training instances without compromising response lengths, we apply a model-specific filtering procedure to the synthesized FIM-MCQA data pool for each domain–target-language pair. Specifically, for all training variants, we evaluate the respective models on the EN-ONLY data by sampling responses eight times per instance. We

discard instances where the model answers correctly across all eight trials, as well as those with response lengths falling into the bottom 25th percentile. After applying this filtering process, we retain only the intersection of the surviving instances across all models to construct the final base dataset. The filtered data counts per model and domain are detailed in Table 6.

Training data mixture. Each single-view variant utilizes the entirety of this filtered data for its corresponding language configuration. For multi-view variants, we sample uniformly across the constituent views so that the total contribution of each view is balanced. Note that the same FIM-MCQA instance preserves its answer index across its monolingual, bilingual, and code-switched realizations, enabling all variants to share the identical exact-match verifier.

Auxiliary General-Reasoning dataset. The auxiliary RLVR pool is shared across all RL-trained variants and consists of 25K scientific reasoning problems (Akter et al., 2026), 15K math problems (Luo et al., 2025a), and 10K instruction-following prompts (Bercovich et al., 2025). For domain-RLVR variants, each batch samples prompts from the synthesized domain FIM-MCQA pool with probability 0.6 and from the auxiliary pool with probability 0.4. The RLVR-BASE baseline is trained only on the auxiliary pool. We use the same auxiliary pool and sampling rule across all domain variants so that differences among EN-ONLY, TGT-ONLY, BI-MONO, and OURS reflect the language realization of the domain examples rather than changes in generic RLVR data.

DAPO hyperparameters. We post-train all RL variants with DAPO (Yu et al., 2025a). For each prompt, we sample $N = 16$ rollouts and apply accuracy-based group filtering, keeping a group only when it contains at least one correct and one incorrect answer. We disable the KL penalty and the overlong-buffer component. Rollouts are sampled with temperature 0.6 and top-$p = 0.95$, using a maximum prompt length of $4{,}200$ tokens and a maximum response length of $8{,}192$ tokens. We train for two epoch with a batch size of 256 prompts and a PPO mini-batch size of 64. Each variant requires approximately $2{,}500$ H100 GPU hours.

Validation and Evaluation. For cybersecurity, we reserve 10% of CyberMetric for validation. For medicine, we reserve an exclusive 10% split of translated MedQA for validation. These validation sets are used only for hyperparameter selection and are excluded from final evaluation. The primary metric is pass@1 with $n = 1$, temperature $T = 0.6$, and top-$p = 0.95$.

F Details of Evaluation Dataset Translation

We utilize the GPT-5.4-mini (OpenAI, 2026b)[2] model to perform the translation. The prompt template for translating the evaluation data is provided in Figure 15.

G Translation Quality Assessment of the Evaluation Dataset

To ensure the reliability of our cross-lingual evaluation, we assess the translation quality of the three cybersecurity benchmarks: SecEval (Busch et al., 2014), CyberMetric (Tihanyi et al., 2024), and CTI-MCQ (Alam et al., 2024). The evaluation process incorporates an LLM-as-a-judge approach, qualitative human assessment, and quantitative automated metrics.

To evaluate the translations comprehensively, we employ GPT-5.5 as an LLM judge to score the translated texts on a scale of 1 to 5 across three criteria: Accuracy, Fluency, and Terminology. Drawing inspiration from Feng et al. (2025b), we specifically adjusted our prompt to elicit explicit numerical scores (on a scale of 1 to 5) in a strict JSON format. This design choice enables a direct quantitative comparison to calculate the agreement between the LLM and human judgments. To validate the reliability of this LLM-based evaluation, we measure its alignment with human judgments. We randomly subsampled 20 instances from each benchmark, and three independent evaluators with Computer Science backgrounds assessed them. To ensure a fair and consistent comparison between the machine and human assessments, both GPT-5.5 (OpenAI, 2026a) and the human experts were provided with the exact same instructions. The prompt utilized for this evaluation is illustrated in Figure 19. It asks the evaluator to output a strict JSON format scoring the translation on Accuracy, Fluency, and Terminology.

As shown in Table 7, GPT-5.5 yielded high scores across all benchmarks. When compared to

---

[2]Specifically, we used the `gpt-5.4-mini-2026-03-17` version.

the human evaluation, we observed a strong positive correlation, with Pearson r values ranging from 0.79 to 0.81 across the datasets. This significant alignment demonstrates that our LLM-based evaluation pipeline reliably mirrors human judgment, effectively verifying the translation quality.

In addition to the prompt-based evaluation, we perform a comprehensive automated evaluation using the COMET score (Rei et al., 2020) to measure the semantic alignment between the original English texts and their translated counterparts. Specifically, we utilize the `Unbabel/wmt22-cometkiwi-da` model and compute the scores for the full evaluation sets across both target languages, Korean and Swahili, to ensure broad quantitative validation.

The detailed results of the LLM evaluation, human assessment, and the COMET automated metric are summarized in Table 7.

Benchmark	Korean (Acc/Flu/Term)			COMET	
	GPT-5.5	Human	r	KO	SW
SecEval	4.94/4.82/4.70	4.25/4.18/4.12	0.81	0.852	0.803
CyberMetric	4.92/4.75/4.67	4.21/4.14/4.08	0.83	0.864	0.810
CTI-MCQ	4.88/4.74/4.66	4.16/4.10/4.02	0.79	0.851	0.808

Table 7: Translation quality evaluation across cybersecurity benchmarks. GPT-5.5 and human scores represent assessments on a 20-instance subsample for Korean (evaluated on a 1-5 scale). r denotes the Pearson correlation between LLM and human judgments. COMET scores are reported for the full evaluation sets in Korean and Swahili.

H Details of Cross-lingual Consistency Comparison

In this section, we present a detailed breakdown of the results from Table 3 across individual benchmarks. These results are provided in Table 8.

I Details of In-domain Translation Experiment

The performance ratio of variant v on benchmark b is $\rho^{v,b} = \mathrm{acc}^{v,b}_{\mathrm{tgt}}/\mathrm{acc}^{v,b}_{\mathrm{EN}}$, where $\mathrm{acc}^{v,b}_\ell$ is the variant's accuracy on the N_b items of b rendered in language $\ell \in \{\mathrm{EN}, \mathrm{tgt}\}$, evaluated on the same stem-key paired item set. The translation prompts used by each model are provided in Figure 16. Figure 17 shows the exact prompt template used for the LLM-based direct assessment (GEMBA-DA) with GPT-4.1 (OpenAI, 2025) to evaluate translation quality from the target language to English.

(English, Korean)	($\checkmark$,$\checkmark$)↑	($\checkmark$,$\times$)↓	($\times$,$\checkmark$)↓
SecEval			
Base	8.3	39.2	5.4
En-only	15.3	41.8	3.4
Bi-Mono	16.3	41.1	3.7
Ours	**23.8**	**38.8**	**2.5**
CyberMetric			
Base	31.4	13.8	32.0
En-only	62.0	15.6	9.6
Bi-Mono	64.0	17.6	7.2
Ours	**74.4**	**11.2**	**5.4**
CTI-MCQ			
Base	17.7	21.4	15.8
En-only	32.6	22.6	10.4
Bi-Mono	33.5	22.4	**10.0**
Ours	**36.5**	**20.0**	10.6

Table 8: Detailed cross-lingual consistency comparison for each benchmark. **Bold** indicates the highest consistency.

J Details of Representation Alignment Analysis

We use a fixed subset of $N = 500$ semantically matched source–target question pairs from CyberMetric. The source side is the original English question, and the target side is the Korean translation used in our evaluation. For each item, we render the same multiple-choice prompt in both languages and append the same opening reasoning marker, `<think>`.

We run a single forward pass over the prompt plus the opening reasoning marker and extract the hidden state at the marker position from every layer. If the marker is split into multiple tokenizer tokens, we use the hidden state of the final token of the marker. This position is immediately before the first reasoning token would be predicted. Since the marker is identical across the source and target prompts, differences in its contextualized hidden state mainly reflect how the preceding question is represented before reasoning begins, rather than variation from generated chain-of-thought continuations.

For each item i and layer ℓ, let s_i^ℓ and t_i^ℓ denote the hidden states extracted from the source and target prompts. Stacking them over all paired items gives layer-wise matrices $S^\ell, T^\ell \in \mathbb{R}^{N \times d}$. We mean-center each language separately over the item dimension:

$$S_c^\ell = S^\ell - \bar{S}^\ell, \qquad T_c^\ell = T^\ell - \bar{T}^\ell.$$

We compute two alignment metrics. First, Mean-

Centered Cosine measures paired item-level similarity after removing the per-language mean, which reduces the effect of anisotropy in contextual LM representations (Ethayarajh, 2019; Timkey and van Schijndel, 2021):

$$\text{MCC}^{\ell} = \frac{1}{N} \sum_{i=1}^{N} \frac{\langle S_{c,i}^{\ell}, T_{c,i}^{\ell} \rangle}{\|S_{c,i}^{\ell}\| \|T_{c,i}^{\ell}\|}.$$

Second, ANC measures feature-level activation correspondence by averaging the Pearson correlation of each hidden dimension over the aligned items (Del and Fishel, 2022b):

$$\text{ANC}^{\ell} = \frac{1}{d} \sum_{j=1}^{d} \text{corr}\left(S_{c,:,j}^{\ell}, T_{c,:,j}^{\ell}\right).$$

We report the full layer-wise curves and summarize the results over a fixed middle-layer band, layers 12–24 of the 36-layer model. The main text focuses on this band because intermediate representations are commonly used to study cross-lingual alignment, and because this range captures the largest separation between the code-switched model and the non-code-switched baselines in our analysis.

K Details of Generated Reasoning Trace Alignment

For each benchmark item, we construct an English–target-language pair and collect outputs from each evaluated model under both language conditions. We compare OURS against EN-ONLY and KO-ONLY using GPT-5.5 as a blind pairwise judge with reasoning effort set to `medium`. The judge receives anonymized outputs from two systems and selects the system whose English and target-language outputs are more semantically consistent in high-level logical progression, problem decomposition, intermediate conclusions, and solution strategy. The judge is instructed to ignore surface-level differences such as wording, formatting, verbosity, fluency, and language-specific phrasing.

To reduce position bias, we evaluate each comparison twice with the A/B order reversed. We aggregate the two judgments into a single outcome per example. If both orders prefer the same underlying system, we count it as a win for that system; otherwise, we treat the example as a tie. Unless otherwise specified, n denotes the number of examples before A/B order swapping.

For the medical domain, we evaluate Qwen2.5-3B-Instruct and Llama-3.2-3B-Instruct on four benchmarks with 50 randomly sampled examples per benchmark, resulting in $n = 200$ examples per model family. For cybersecurity, we evaluate SmolLM3-3B on three benchmarks with 50 examples per benchmark, resulting in $n = 150$. The judge prompt is shown in Figure 18, and the per-benchmark results are reported in Table 9.

L Qualitative Examples

In this section, we present qualitative examples from our dataset. The examples for the medical domain are detailed in Figure 4, 5, and those for the cybersecurity domain are provided in Figure 6, and 7.

M Full Evaluation Results

IIn this section, we report the full evaluation results, including the no-RLVR settings. The results for the medical domain are presented in Tables 10 and 11.

		vs. EN-ONLY			vs. TGT-ONLY		
	Benchmark	Ours%	En-only%	tie%	Ours%	Tgt-only%	tie%
Medical							
Qwen2.5-3B	MedQA	**56.0**	26.0	2.0	38.0	48.0	0.0
	MedMCQA	**60.0**	32.0	2.0	**50.0**	36.0	2.0
	KMMLU-Pro-Medical	40.0	38.0	0.0	32.0	54.0	2.0
	KorMedMCQA-Doctor	44.0	48.0	0.0	**56.0**	34.0	2.0
	Average	*50.0*	*36.0*	*1.0*	*44.0*	*43.0*	*1.5*
Llama-3.2-3B	MedQA	36.0	46.0	6.0	46.0	44.0	0.0
	MedMCQA	**48.0**	28.0	4.0	34.0	42.0	4.0
	KMMLU-Pro-Medical	**48.0**	42.0	2.0	**52.0**	36.0	0.0
	KorMedMCQA-Doctor	**52.0**	38.0	0.0	38.0	42.0	0.0
	Average	*46.0*	*38.5*	*3.0*	*42.5*	*41.0*	*1.0*
Cyber							
SmolLM3-3B	CTI-MCQ	**48.0**	30.0	6.0	**76.0**	18.0	0.0
	CyberMetric	**34.0**	24.0	16.0	26.0	22.0	20.0
	SecEval	26.0	40.0	18.0	**80.0**	16.0	0.0
	Average	*36.0*	*31.3*	*13.3*	*60.7*	*18.7*	*6.7*

Table 9: Detailed pairwise judge win rate results using GPT-5.5. The target language is Korean. 50 samples are evaluated per benchmark. **Bold** indicates a higher win rate.

N Prompts

In this section, we present the full prompt templates used in our experiments. To facilitate navigation, we group these prompts according to their specific tasks: extraction synthesis, translation, code-switching, and evaluation.

Bench.	Qwen2.5-3B-Instruct						Llama-3.2-3B-Instruct					
	Base	RLVR-Base	+En	+Tgt	+BiMono	+Ours	Base	RLVR-Base	+En	+Tgt	+BiMono	+Ours
Target Language												
KorMedMQ-D	34.50	35.06	35.34	35.29	35.34	**36.67**	19.02	21.10	27.93	27.47	28.79	**29.31**
MedMCQA*	33.24	34.52	33.96	34.03	33.72	**34.86**	19.85	24.26	27.12	27.36	**29.65**	29.22
KMMLU-Pro-M	35.20	35.45	35.76	36.21	36.06	**36.29**	20.45	22.84	24.77	24.09	25.08	**26.36**
Tgt Lang Avg	34.31	35.01	35.02	35.18	35.04	**35.94**	19.77	22.73	26.61	26.31	27.84	**28.30**
English												
KorMedMQ-D*	57.53	57.74	58.05	**61.03**	60.06	58.74	48.85	50.01	56.72	57.30	57.53	**57.93**
MedMCQA	47.36	**47.88**	47.60	47.42	47.34	47.01	52.28	52.57	55.00	55.00	**55.17**	55.04
MedQA	50.29	48.65	50.92	50.47	**51.47**	50.65	50.63	52.38	58.19	58.37	**58.92**	58.82
En Avg	51.73	51.42	52.19	**52.97**	52.96	52.13	50.59	51.65	56.64	56.89	57.21	**57.26**

Table 10: Comprehensive performance on medical benchmarks across RLVR data configurations. BASE denotes the original instruction-tuned model without RLVR. RLVR-BASE denotes RLVR training using only the auxiliary data pool. The remaining variants include the same auxiliary pool and additionally use English data (+EN), target-language data (+TGT), bilingual monolingual data (+BIMONO), or our proposed code-switched data (+OURS). English rows are shown in gray to indicate source-language evaluation, which is reported as a retention check rather than the primary target-language transfer metric. The asterisk (*) indicates that the benchmark is translated into the respective language. The best performance within each model is highlighted in **bold**.

Bench.	SmolLM3-3B											
	Korean						Swahili					
	Base	RLVR-Base	+En	+Tgt	+BiMono	+Ours	Base	RLVR-Base	+En	+Tgt	+BiMono	+Ours
Target Language												
SecEval*	40.9	44.3	50.1	49.8	51.1	**57.3**	26.9	25.8	26.8	**28.6**	25.9	28.3
CyberMetric*	63.6	65.8	70.6	**80.2**	72.4	80.0	53.0	54.0	53.9	54.2	54.5	**55.0**
CTI-MCQ*	33.7	40.6	43.2	45.5	43.8	**47.1**	41.4	41.9	42.1	43.2	43.4	**45.0**
Tgt Lang Avg	46.07	50.23	54.63	58.50	55.77	**61.47**	40.43	40.57	40.93	42.00	41.27	**42.77**
English												
SecEval	55.6	56.7	59.9	61.7	58.9	**62.7**	55.6	56.7	59.9	65.6	65.3	**66.6**
CyberMetric	77.0	83.0	83.6	**85.6**	84.4	**85.6**	77.0	83.0	83.6	86.3	86.0	**86.6**
CTI-MCQ	50.7	54.9	**57.5**	56.2	57.1	56.5	50.7	54.9	57.5	**61.1**	60.9	60.3
En Avg	61.10	64.87	67.00	67.83	66.80	**68.27**	61.10	64.87	67.00	71.00	70.73	**71.17**

Table 11: Comprehensive performance on cybersecurity benchmarks across RLVR data configurations. **Target Language** indicates Korean for the left section and Swahili for the right section. BASE denotes the original instruction-tuned model without RLVR. RLVR-BASE denotes RLVR training using only the auxiliary data pool. The remaining variants include the same auxiliary pool and additionally use English data (+EN), target-language data (+TGT), bilingual monolingual data (+BIMONO), or our proposed code-switched data (+OURS). English rows are shown in gray to indicate source-language evaluation, which is reported as a retention check rather than the primary target-language transfer metric. The asterisk (*) indicates that the benchmark is translated into the respective language. The best performance within each model is highlighted in **bold**.

Variant: En-only

Passage:

Anti-programmed death-1 (anti-PD-1) and programmed death-ligand 1 (anti-PD-L1) monoclonal antibodies are approved treatments for several malignancies, including nivolumab and pembrolizumab for melanoma and non-small-cell lung cancer (NSCLC), nivolumab for renal cell carcinoma and Hodgkin's lymphoma, atezolizumab for bladder cancer, and the combination of nivolumab plus ipilimumab for melanoma. While these agents are generally associated with mild toxicity, they can provoke serious immune-related adverse events. [MASK]. Drug-induced pneumonia may also arise from conventional chemotherapy agents such as docetaxel, gemcitabine, and bleomycin, from targeted therapies like epidermal growth factor receptor inhibitors and mammalian target of rapamycin inhibitors, as well as from radiotherapy.

Options:

A) Pneumonia—defined as focal or diffuse inflammation of the lung parenchyma—is one such adverse event; its reported incidence in clinical trials of anti-PD-1/PD-L1 antibodies ranges from 0 % to 10 % ✓

B) Colitis — characterized by ulcerative lesions of the intestinal mucosa — another potential toxicity ; its observed frequency in phase III studies of PD-1/PD-L1 blockers varies between 2 % and 12 % in treated patients

C) Pancreatitis involving inflammatory swelling of the exocrine gland is a rare metabolic side effect ; its noted proportion within large anti-PD-1/PD-L treatment groups hovers around three percent through eight percent across cycles

D) Hypothyroidism — characterized by reduced thyroid hormone production and fatigue — a common endocrine immune-related adverse effect ; its occurrence rate across anti-PD-1/PD-L1 studies lies near 15 % to 30 % globally in adult populations

E) Myocarditis — manifested as inflammatory infiltration of cardiac muscle — an infrequent yet severe checkpoint inhibitor toxicity ; its prevalence reported in extensive PD-1/PD-L1 cohorts fluctuates between 1 % and 5 % overall in patients

F) Hepatitis — identified by elevated transaminases and hepatic inflammation — a documented immune-related complication ; its cumulative incidence across pivotal PD-1/PD-L1 trials spans roughly from 3 % up to 9 % among study participants

G) Dermatitis — described as erythematous rash covering variable body surface area — a frequent cutaneous manifestation ; its incidence reported in major anti-PD-01/PD-L1 investigations spans roughly from 20 % to 45 %, depending on regimen

H) Nephritis — presenting with proteinuria haematuria and impaired renal function — another recognized renal toxicity ; its documented frequency among PD-1/PD-L1 recipients ranges approximately from 2 % up to 8 % during therapy in clinical trials

I) Encephalitis — defined as brain parenchymal inflammation with neurological symptoms — an uncommon neurotoxic event ; its estimated rate among pooled PD-1/PD-L1 patient data sets runs from five per cent up to fifteen per cent during follow up

Figure 4: Qualitative example — Medical (Part 1/2). Same source passage shown across 3 variants. [MASK] marks the masked answer span; the ground-truth option (✓) is what fills it.

Variant: Ko-only

Passage:

Anti-programmed death-1 (anti-PD-1) 및 programmed death-ligand 1 (anti-PD-L1) 단클론 항체는 흑색종 및 비소세포폐암(NSCLC)에 대한 nivolumab 및 pembrolizumab, 신세포암 및 호지킨 림프종에 대한 nivolumab, 방광암에 대한 atezolizumab, 그리고 흑색종에 대한 nivolumab과 ipilimumab 병용 요법을 포함하여 여러 악성 종양에 대해 승인된 치료제입니다. 이러한 약제들은 일반적으로 경미한 독성과 관련이 있지만, 심각한 면역 관련 이상 반응을 유발할 수 있습니다. **[MASK]**. 약물 유발 폐렴은 docetaxel, gemcitabine, bleomycin과 같은 전통적인 화학요법제, epidermal growth factor receptor inhibitors 및 mammalian target of rapamycin inhibitors와 같은 표적 치료제, 그리고 방사선 치료로 인해 발생할 수도 있습니다.

Options:

A) 폐렴—폐 실질의 국소적 또는 미만성 염증으로 정의됨—은 그러한 이상 반응 중 하나입니다; anti-PD-1/PD-L1 항체의 임상 시험에서 보고된 발생률은 0%에서 10% 사이입니다. ✓

B) 장 점막의 궤양성 병변을 특징으로 하는 결장염은 또 다른 잠재적 독성입니다. PD-1/PD-L1 차단제의 임상 3상 연구에서 관찰된 치료 환자에서의 발생 빈도는 2%에서 12% 사이로 다양합니다.

C) 외분비선의 염증성 부종을 동반하는 췌장염은 드문 대사성 부작용입니다; 대규모 anti-PD-1/PD-L1 치료군 내에서 관찰되는 비율은 사이클 전반에 걸쳐 3%에서 8% 사이를 오갑니다.

D) 갑상선 기능 저하증 — 갑상선 호르몬 생성 감소와 피로를 특징으로 함 — 흔한 내분비 면역 관련 이상 반응 ; 전 세계 성인 인구 대상 anti-PD-1/PD-L1 연구에서의 발생률은 15%에서 30% 사이입니다.

E) 심근염 — 심근의 염증성 침윤으로 나타나는 — 드물지만 심각한 checkpoint inhibitor 독성; 광범위한 PD-1/PD-L1 코호트에서 보고된 유병률은 환자 전체에서 1%에서 5% 사이에서 변동합니다.

F) 간염 — 상승된 트랜스아미나제와 간 염증으로 식별됨 — 기록된 면역 관련 합병증; 주요 PD-1/PD-L1 임상 시험 전반에 걸친 연구 참여자들의 누적 발생률은 대략 3%에서 9%에 이릅니다.

G) 피부염 — 다양한 체표면적을 덮는 홍반성 발진으로 설명됨 — 빈번한 피부 증상; 주요 anti-PD-1/PD-L1 연구에서 보고된 발생률은 요법에 따라 대략 20%에서 45%에 이릅니다.

H) 신염 — 단백뇨, 혈뇨 및 신기능 저하를 동반함 — 또 다른 알려진 신독성; 임상 시험 중 PD-1/PD-L1 투여군에서 보고된 빈도는 치료 기간 동안 약 2%에서 최대 8%에 이릅니다.

I) 뇌염 — 신경학적 증상을 동반한 뇌 실질의 염증으로 정의됨 — 은 흔하지 않은 신경독성 사건입니다; 통합된 PD-1/PD-L1 환자 데이터 세트에서 추정되는 발생률은 추적 관찰 기간 동안 5%에서 15% 사이입니다.

Variant: Ko→En (Passage-level Code-switching)

Passage:

Anti-programmed death-1 (anti-PD-1) 및 programmed death-ligand 1 (anti-PD-L1) monoclonal antibodies는 melanoma 및 non-small cell lung cancer(NSCLC)에 대한 nivolumab 및 pembrolizumab, renal cell carcinoma 및 Hodgkin lymphoma에 대한 nivolumab, bladder cancer에 대한 atezolizumab, 그리고 melanoma에 대한 nivolumab과 ipilimumab combination therapy를 포함하여 various malignant tumors에 대해 approved therapeutics입니다. 이러한 약제들은 generally mild toxicity와 관련이 있지만, 심각한 immune-related adverse reactions을 유발할 수 있습니다. **[MASK]**. 약물 유발 폐렴은 docetaxel, gemcitabine, bleomycin과 같은 전통적인 화학요법제, epidermal growth factor receptor inhibitors 및 mammalian target of rapamycin inhibitors와 같은 표적 치료제, 그리고 방사선 치료로 인해 발생할 수도 있습니다.

Options:

A) 폐렴—폐 실질의 국소적 또는 미만성 염증으로 정의됨—은 그러한 이상 반응 중 하나입니다; anti-PD-1/PD-L1 항체의 임상 시험에서 보고된 발생률은 0%에서 10% 사이입니다. ✓

B) 장 점막의 궤양성 병변을 특징으로 하는 결장염은 또 다른 잠재적 독성입니다. PD-1/PD-L1 차단제의 임상 3상 연구에서 관찰된 치료 환자에서의 발생 빈도는 2%에서 12% 사이로 다양합니다.

C) 외분비선의 염증성 부종을 동반하는 췌장염은 드문 대사성 부작용입니다; 대규모 anti-PD-1/PD-L1 치료군 내에서 관찰되는 비율은 사이클 전반에 걸쳐 3%에서 8% 사이를 오갑니다.

D) 갑상선 기능 저하증 — 갑상선 호르몬 생성 감소와 피로를 특징으로 함 — 흔한 내분비 면역 관련 이상 반응 ; 전 세계 성인 인구 대상 anti-PD-1/PD-L1 연구에서의 발생률은 15%에서 30% 사이입니다.

E) 심근염 — 심근의 염증성 침윤으로 나타나는 — 드물지만 심각한 checkpoint inhibitor 독성; 광범위한 PD-1/PD-L1 코호트에서 보고된 유병률은 환자 전체에서 1%에서 5% 사이에서 변동합니다.

F) 간염 — 상승된 트랜스아미나제와 간 염증으로 식별됨 — 기록된 면역 관련 합병증; 주요 PD-1/PD-L1 임상 시험 전반에 걸친 연구 참여자들의 누적 발생률은 대략 3%에서 9%에 이릅니다.

G) 피부염 — 다양한 체표면적을 덮는 홍반성 발진으로 설명됨 — 빈번한 피부 증상; 주요 anti-PD-1/PD-L1 연구에서 보고된 발생률은 요법에 따라 대략 20%에서 45%에 이릅니다.

H) 신염 — 단백뇨, 혈뇨 및 신기능 저하를 동반함 — 또 다른 알려진 신독성; 임상 시험 중 PD-1/PD-L1 투여군에서 보고된 빈도는 치료 기간 동안 약 2%에서 최대 8%에 이릅니다.

I) 뇌염 — 신경학적 증상을 동반한 뇌 실질의 염증으로 정의됨 — 은 흔하지 않은 신경독성 사건입니다; 통합된 PD-1/PD-L1 환자 데이터 세트에서 추정되는 발생률은 추적 관찰 기간 동안 5%에서 15% 사이입니다.

Figure 5: Qualitative example — Medical (Part 2/2). Continuation of the 3 variants.

Variant: En-only

Passage:

Sender Policy Framework (SPF) is an email authentication system used to verify that a message originates from an authorized server for the sender's domain. **[MASK]** By enforcing this check, SPF prevents attackers from forging (spoofing) the "From" address of a legitimate domain, which is a common technique for phishing and spam campaigns.

Options:
 A) When configuring SPF, administrators must add a CNAME record pointing to an external validation service, which then returns a list of allowed sending hosts during each SMTP handshake.
 B) Activating SPF requires adding a DNS A record for each permitted mail server, after which receiving systems perform a reverse-DNS lookup to match the connecting IP to the A records.
 C) Deploying SPF for a domain creates a DNS TXT record that lists the IP addresses of mail servers permitted to send mail on behalf of that domain. Once the record propagates to DNS resolvers worldwide, each receiving mail server can query the sender's DNS zone during the SMTP transaction. The receiving server checks whether the connecting IP address appears in the SPF record; if it does, the message is accepted and delivered, otherwise it is rejected or marked as suspicious. ✓
 D) The SPF setup process creates a DNS TXT entry that enumerates permitted sending hosts; receiving mail servers then validate the connecting client's IP against this entry during SMTP.
 E) Setting up SPF entails publishing a DNS TXT record containing the authorized IP blocks, after which each inbound mail server performs an SPF-PASS lookup before delivering the message.
 F) Implementing SPF involves publishing a DNS MX record that enumerates all mail exchangers, and the receiver validates the HELO/EHLO hostname against this list before accepting mail.
 G) Configuring SPF means inserting a DNS TXT entry with a "v=spf1" tag followed by "include" mechanisms, and receivers compare the sender's DKIM signature against this policy.
 H) To set up SPF, you create a DNS SRV record containing the authorized IP ranges, and mail servers query this record on every inbound connection to decide acceptance.
 I) During SPF deployment, a DNS TXT record is published that lists authorized IPs, and receiving servers use this list to compute a hash of the sender's envelope-from domain for verification.

Variant: Ko-only

Passage:

Sender Policy Framework (SPF)는 메시지가 발신자 도메인에 대해 권한이 있는 서버에서 생성되었는지 확인하는 데 사용되는 이메일 인증 시스템입니다. **[MASK]** 이 검사를 강제함으로써, SPF는 공격자가 피싱 및 스팸 캠페인에서 흔히 사용하는 기술인 합법적인 도메인의 "From" 주소를 위조(spoofing)하는 것을 방지합니다.

Options:
 A) SPF를 구성할 때, 관리자는 외부 검증 서비스로 가리키는 CNAME 레코드를 추가해야 하며, 해당 서비스는 각 SMTP 핸드쉐이크 동안 허용된 발신 호스트 목록을 반환합니다.
 B) SPF를 활성화하려면 허용된 각 메일 서버에 대해 DNS A 레코드를 추가해야 하며, 이후 수신 시스템은 연결된 IP 와 A 레코드를 매칭하기 위해 역 DNS 조회를 수행합니다.
 C) 도메인에 SPF를 배포하면 해당 도메인을 대신하여 메일을 보낼 수 있는 메일 서버의 IP 주소를 나열한 DNS TXT 레코드가 생성됩니다. 레코드가 전 세계 DNS 리졸버에 전파되면, 각 수신 메일 서버는 SMTP 트랜잭션 중에 발신자의 DNS 영역을 조회할 수 있습니다. 수신 서버는 연결된 IP 주소가 SPF 레코드에 포함되어 있는지 확인하고, 포함되어 있으면 메시지를 수락하고 전달하며, 그렇지 않으면 거부하거나 의심스러운 것으로 표시합니다. ✓
 D) SPF 설정 과정에서는 허용된 발신 호스트를 열거한 DNS TXT 엔트리를 생성하고, 수신 메일 서버는 SMTP 중에 연결된 클라이언트의 IP를 이 엔트리와 대조하여 검증합니다.
 E) SPF를 설정하려면 허가된 IP 블록을 포함한 DNS TXT 레코드를 게시하고, 이후 각 인바운드 메일 서버는 메시지를 전달하기 전에 SPF-PASS 조회를 수행합니다.
 F) SPF를 구현하려면 모든 메일 교환기를 열거한 DNS MX 레코드를 게시하고, 수신자는 메일을 수락하기 전에 HELO/EHLO 호스트명을 이 목록과 대조하여 검증합니다.
 G) SPF를 구성한다는 것은 "v=spf1" 태그와 뒤에 이어지는 "include" 메커니즘을 포함한 DNS TXT 엔트리를 삽입하는 것을 의미하며, 수신자는 발신자의 DKIM 서명을 이 정책과 비교합니다.
 H) SPF를 설정하려면 허가된 IP 범위를 포함한 DNS SRV 레코드를 생성하고, 메일 서버는 각 인바운드 연결 시 이 레코드를 조회하여 수락 여부를 결정합니다.
 I) SPF 배포 중에 허가된 IP를 나열한 DNS TXT 레코드가 게시되며, 수신 서버는 이 목록을 사용해 발신자의 envelope-from 도메인의 해시를 계산하여 검증합니다.

Figure 6: Qualitative example — Cybersecurity (Part 1/2). Same source passage shown across 4 variants. [MASK] marks the masked answer span; the ground-truth option (✓) is what fills it.

Variant: SW-only

Passage:

Sender Policy Framework (SPF) ni mfumo wa uthibitishaji wa barua pepe unaotumiwa kuhakiki kuwa ujumbe unatokana na seva iliyoidhinishwa kwa ajili ya domain ya mtumaji. **[MASK]** Kwa kusimamia ukaguzi huu, SPF huzuia washambuliaji kutengeneza (spoofing) anwani ya "From" ya domain halali, ambayo ni mbinu ya kawaida kwa kampeni za phishing na spam.

Options:

A) Wakati wa kusanidi SPF, wasimamizi lazima waongeze rekodi ya CNAME inayoelekeza kwenye huduma ya nje ya uhakiki, ambayo kisha hurudisha orodha ya wenyeji wanaoruhusiwa kutuma wakati wa kila SMTP handshake.

B) Kuamsha SPF kunahitaji kuongeza rekodi ya DNS A kwa kila seva ya barua pepe iliyoruhusiwa, baada ya hapo mifumo inayopokea hufanya reverse-DNS lookup ili kuoanisha IP inayojiunganisha na rekodi za A.

C) Kuweka SPF kwa ajili ya domain kunatengeneza rekodi ya DNS TXT inayoorodhesha IP addresses za mail servers zinazoruhusiwa kutuma barua pepe kwa niaba ya domain hiyo. Mara tu rekodi inapoelea kwenye DNS resolvers duniani kote, kila seva ya barua pepe inayopokea inaweza kuulizia DNS zone ya mtumaji wakati wa muamala wa SMTP. Seva inayopokea hukagua ikiwa anwani ya IP inayojiunganisha inaonekana katika rekodi ya SPF; ikiwa inaonekana, ujumbe unakubaliwa na kuwasilishwa, vinginevyo unakataliwa au kuwekwa alama kama wa shaka. ✓

D) Mchakato wa usanidi wa SPF unaunda ingizo la DNS TXT ambalo linaorodhesha host zinazoruhusiwa kutuma; seva za kupokea barua pepe kisha zinathibitisha IP ya mteja anayeunganishwa dhidi ya ingizo hili wakati wa SMTP.

E) Kuandaa SPF kunahusisha kuchapisha rekodi ya DNS TXT inayojumuisha vizuizi vya IP vilivyoidhinishwa, baada ya hapo kila seva ya barua pepe inayopokea inafanya utafutaji wa SPF-PASS kabla ya kuwasilisha ujumbe.

F) Kutekeleza SPF kunahusisha kuchapisha rekodi ya DNS MX inayoorodhesha mail exchangers zote, na mpokeaji huhakiki hostname ya HELO/EHLO dhidi ya orodha hii kabla ya kukubali barua pepe.

G) Kusanidi SPF inamaanisha kuingiza rekodi ya DNS TXT yenye tag ya "v=spf1" ikifuatiwa na mifumo ya "include", na wapokeaji hulinganisha saini ya DKIM ya mtumaji dhidi ya sera hii.

H) Ili kuweka SPF, unatengeneza rekodi ya DNS SRV inayojumuisha masafa ya IP yaliyoidhinishwa, na seva za barua pepe huulizia rekodi hii kwenye kila muunganisho unaoingia ili kuamua kukubalika.

I) Wakati wa utekelezaji wa SPF, rekodi ya DNS TXT huchapishwa ambayo inaorodhesha IP zilizoidhinishwa, na seva zinazopokea hutumia orodha hii kukokotoa hash ya envelope-from domain ya mtumaji kwa ajili ya uhakiki.

Variant: EN→SW (Passage-level Code-switching)

Passage:

Sender Policy Framework (SPF) ni mfumo wa uthibitishaji wa barua pepe used to verify kwamba ujumbe unatoka kutoka kwa server iliyoidhinishwa kwa ajili ya domain ya mtumaji. **[MASK]** Kwa kusimamia ukaguzi huu, SPF inazuia wadukuzi kutoka kughushi (spoofing) anuani ya "From" ya domain halali, ambayo ni mbinu ya kawaida kwa kampeni za phishing na spam.

Options:

A) When configuring SPF, administrators must add a CNAME record pointing to an external validation service, which then returns a list of allowed sending hosts during each SMTP handshake.

B) Activating SPF requires adding a DNS A record for each permitted mail server, after which receiving systems perform a reverse-DNS lookup to match the connecting IP to the A records.

C) Deploying SPF for a domain creates a DNS TXT record that lists the IP addresses of mail servers permitted to send mail on behalf of that domain. Once the record propagates to DNS resolvers worldwide, each receiving mail server can query the sender's DNS zone during the SMTP transaction. The receiving server checks whether the connecting IP address appears in the SPF record; if it does, the message is accepted and delivered, otherwise it is rejected or marked as suspicious. ✓

D) The SPF setup process creates a DNS TXT entry that enumerates permitted sending hosts; receiving mail servers then validate the connecting client's IP against this entry during SMTP.

E) Setting up SPF entails publishing a DNS TXT record containing the authorized IP blocks, after which each inbound mail server performs an SPF-PASS lookup before delivering the message.

F) Implementing SPF involves publishing a DNS MX record that enumerates all mail exchangers, and the receiver validates the HELO/EHLO hostname against this list before accepting mail.

G) Configuring SPF means inserting a DNS TXT entry with a "v=spf1" tag followed by "include" mechanisms, and receivers compare the sender's DKIM signature against this policy.

H) To set up SPF, you create a DNS SRV record containing the authorized IP ranges, and mail servers query this record on every inbound connection to decide acceptance.

I) During SPF deployment, a DNS TXT record is published that lists authorized IPs, and receiving servers use this list to compute a hash of the sender's envelope-from domain for verification.

Figure 7: Qualitative example — Cybersecurity (Part 2/2). Continuation of the 4 variants.

```
Given a source document, perform TWO tasks:

1. **Extract an educational passage**: Extract a coherent, self-contained
   passage (around 200-300 words) from the document that is educationally
   valuable for learning Cybersecurity. The passage should contain reasoning
   - causal explanations, attack mechanism analysis, vulnerability
   consequences, or defensive logic. Remove noise such as ads, navigation
   menus, author bylines, dates, and promotional content. The passage must
   read as a clean, standalone educational text.

2. **Identify the mask span**: Within the extracted passage, identify a
   consecutive multi-sentence span (around 50-100 words) that contains the
   most important reasoning steps. This span will be masked and serve as the
   ground-truth answer.

VERBATIM COPYING RULES - violating these causes a task failure:
1. Both "passage" and "removed_steps" must be copied CHARACTER-FOR-CHARACTER
   from the original document.
2. Do NOT paraphrase, simplify, reorder, or summarize.
3. Do NOT add or remove spaces, line breaks, or punctuation.
4. "removed_steps" must be a substring of "passage" - every character must
   appear in the passage exactly as written.

Return ONLY the following JSON within <answer></answer> tags:

<answer>
{
  "passage": "...",
  "removed_steps": "..."
}
</answer>

If there is no suitable educational passage about Cybersecurity, or if the
   document is not written in English, return an empty string within <answer
   ></answer>.

Document:
SOLUTION_PLACEHOLDER
```

Figure 8: The prompt template used in Stage 1 to simultaneously extract educational passages and identify mask spans for the Cybersecurity domain.

```
Given a source document, perform TWO tasks:

1. **Extract an educational passage**: Extract a coherent, self-contained
   passage (around 200-300 words) from the document that is educationally
   valuable for learning Medicine or Biomedical Science. The passage should
   contain reasoning - clinical reasoning, pathophysiology, mechanism of
   disease, diagnostic logic, treatment rationale, or pharmacological
   mechanisms. Remove noise such as ads, navigation menus, author bylines,
   dates, and promotional content. The passage must read as a clean,
   standalone educational text.

2. **Identify the mask span**: Within the extracted passage, identify a
   consecutive multi-sentence span (around 50-100 words) that contains the
   most important reasoning steps. This span will be masked and serve as the
   ground-truth answer.

VERBATIM COPYING RULES - violating these causes a task failure:
1. Both "passage" and "removed_steps" must be copied CHARACTER-FOR-CHARACTER
   from the original document.
2. Do NOT paraphrase, simplify, reorder, or summarize.
3. Do NOT add or remove spaces, line breaks, or punctuation.
4. "removed_steps" must be a substring of "passage" - every character must
   appear in the passage exactly as written.

Return ONLY the following JSON within <answer></answer> tags:

<answer>
{
  "passage": "...",
  "removed_steps": "..."
}
</answer>

If there is no suitable educational passage about Medicine or Biomedical
   Science, or if the document is not written in English, return an empty
   string within <answer></answer>.

Document:
SOLUTION_PLACEHOLDER
```

Figure 9: The prompt template used in Stage 1 to simultaneously extract educational passages and identify mask spans for the Medical domain.

Figure 10: The prompt template used in Stage 3 to generate plausible, length-matched distractors for the masked spans in the Cybersecurity domain.

Figure 11: The prompt template used in Stage 3 to generate plausible, length-matched distractors for the masked spans in the Medical domain.

```
Using the {domain} document below as context, translate the given text into {language}
↪  ({native}).
Translation rules:
- Translate the **entire text** into {language}. Even if the text is long, translate it all the
↪  way through.
- Do not leave any English sentence and do not break off the translation midway.
- Keep ONLY {keep_in_english} in English. All other English text must be **fully** translated.
- {literal_passthroughs} remain unchanged, but the surrounding sentences must be translated.

- Never modify the markers [MASK].
- Do NOT switch language mid-word (no English suffix glued to a {language} stem, no {language}
↪  character inserted inside an English word). A technical term must appear in exactly one of
↪  these forms: (a) all English, (b) all {language}, or (c) {language} followed by the English
↪  term in parentheses.

- Use consistent {language} technical terminology across the whole text.
- Return only the translated text, with no explanation or extra quotation marks.

Translation example:
Input:  "{ex_in_single}"
Output: "{ex_out_single}"

Document (translation context):
PASSAGE_PLACEHOLDER

Text to translate:
TEXT_PLACEHOLDER
```

Figure 12: The prompt template used for context-aware translation into the target language. The prompt enforces strict constraints to preserve code snippets, system identifiers, and [MASK] markers while preventing unnatural mid-word language mixing.

Figure 13: The prompt template used to translate the multiple-choice options into the target language. Similar to the passage translation, it leverages the source document as context to ensure terminology consistency and requires a strict JSON array output.

```
Span-Level Code-Switching Generation Prompt

You will code-switch a {source} ({source_native}) {domain} text into {target}
↪  ({target_native}) by replacing selected spans with their {target} translations. Choose
↪  spans so that the resulting text READS NATURALLY - the output should feel like a fluent
↪  bilingual {domain} writer's prose, not a mechanical word-by-word substitution.

Rules (STRICT):
1. Pick spans whose {target} translation READS NATURALLY in context. Translate
↪  content-carrying spans - nouns, verbs, adjectives, short noun/verb phrases - whenever
↪  their {target} rendering is smooth. Spans may be single words or short 2-4 token phrases -
↪  phrasal translations often read more naturally than single-word swaps, so prefer them when
↪  they flow better.
2. Domain literals stay in their original form (do NOT translate or transliterate):
↪  {literal_passthroughs}, code blocks, equations.
3. Spread selections EVENLY across the whole passage - the beginning, the middle, and the end
↪  must each contribute some switched spans. Clustering in one region is a failure.
4. If the same word appears several times, you do NOT have to translate every occurrence.
↪  Translating one or two occurrences and leaving the others in {source} is actually preferred
↪  - it looks more natural and avoids the "always the same word" bias.
5. Translate each selected span into natural {target} and substitute it in place of the
↪  {source} original. Keep the surrounding {source} text exactly as it was (same whitespace,
↪  same casing, same punctuation, same paragraph breaks).
6. NEVER modify, translate, remove, or reorder the markers [MASK]. They must appear the same
↪  number of times and in the same order in your output.
7. Do not add, remove, or reorder sentences. Do not paraphrase untouched text.

{example_block}
OUTPUT FORMAT - respond with ONLY the following, nothing else:
<answer>
{
  "code_switched": "<the full passage after code-switching>",
  "switched_tokens": ["<{source} span 1>", "<{source} span 2>", ...]
}
</answer>

Emit exactly ONE opening `{` and ONE matching closing `}`. Do NOT double them.
Escape newlines inside the JSON string as \n and backslashes as \\.

PASSAGE:
<<<
PASSAGE_PLACEHOLDER
>>>
```

Figure 14: The prompt template used for generating span-level code-switched passages.

```
Evaluation Benchmark Translation Prompt

You are a professional {language} translator specializing in {domain}.
Translate the following {domain} multiple-choice question and its options into natural
↪  {language} ({native}).

Rules:
- Translate naturally and fluently into {language} - readers should feel the text was
↪  originally written in {language}.
- Do NOT translate or modify any code blocks, command-line examples, or inline code snippets.
- Keep option labels (A), B), C), D) etc.) exactly as-is at the start of each option.
- Output ONLY the translated question and options, nothing else.

Text to translate:
{text}
```

Figure 15: The prompt template used to translate evaluation benchmark multiple-choice questions and options into the target language.

Direct Translation Prompt

```
Translate the following {src_lang_full}
↪  text to English. Output only the
↪  English translation, no explanation,
↪  no preamble.

{src_lang_full} text:
{source_text}
```

Figure 16: The prompt template used for translating source language text into English.

GEMBA-DA Evaluation Prompt

```
Score the following translation
    from {src_full} to {tgt_full}
    on a
continuous scale from 0 to 100,
    where a score of zero means "no
     meaning
preserved" and score of one
    hundred means "perfect meaning
    and grammar".

{src_full} source: "{src}"
{tgt_full} translation: "{tgt}"

Score (0-100):
```

Figure 17: The prompt template for GEMBA-DA used to measure translation quality. The variables {src_full} and {tgt_full} represent the full names of the source and target languages, while {src} and {tgt} are substituted with the original text and the model's translation, respectively.

Reasoning Trace Alignment Judge Prompt

```
You will see TWO models' reasoning
↪  behavior on the same problem.
Each model produced one English trace (for
↪  the English version
of the problem) and one {target_name}
↪  trace (for the
{target_name} version of the same
↪  problem).

Your task: judge which MODEL shows MORE
↪  CONSISTENT REASONING
between its English and {target_name}
↪  responses.

WHAT "CONSISTENT" MEANS:
- The model decomposes the problem the
↪  same way in both languages
- Uses similar key facts, concepts,
↪  formulas across both traces
- Follows a similar high-level strategy in
↪  both languages
- Arrives at similar intermediate insights

WHAT "CONSISTENT" DOES NOT MEAN:
- Both traces being correct (a model can
↪  be consistently wrong,
  and that still counts as consistent)
- The {target_name} trace using English
↪  words (this is a surface
  feature, not consistency)
- Either trace being more detailed or
↪  longer than the other
- Either model being individually
↪  "smarter" or producing
  higher-quality reasoning

PROBLEM (English):
{Q_en}

PROBLEM ({target_name}):
{Q_tgt}
```

Figure 18: The prompt template used for the reasoning trace alignment experiment.

```
Evaluate the translation on three
    aspects (1=worst, 5=best):
1. Accuracy: Does the translation
    preserve the source meaning?
2. Fluency: Is the translation
    grammatically correct and
    natural?
3. Terminology: Are domain-
    specific terms translated
    correctly?
Domain: {domain}
Source: {src}
Translation: {tgt}
Output JSON only:
{"accuracy": <1-5>, "fluency":
    <1-5>, "terminology": <1-5>}
```

Figure 19: The prompt template used for both the LLM-as-a-judge (GPT-5.5) and the human evaluators to assess translation quality.