MonoDistill: Learning Spatial Features for Monocular 3D Object Detection

Abstract

3D object detection is a fundamental and challenging task for 3D scene understanding, and the monocular-based methods can serve as an economical alternative to the stereo-based or LiDAR-based methods. However, accurately detecting objects in the 3D space from a single image is extremely difficult due to the lack of spatial cues. To mitigate this issue, we propose a simple and effective scheme to introduce the spatial information from LiDAR signals to the monocular 3D detectors, without introducing any extra cost in the inference phase. In particular, we first project the LiDAR signals into the image plane and align them with the RGB images. After that, we use the resulting data to train a 3D detector (LiDAR Net) with the same architecture as the baseline model. Finally, this LiDAR Net can serve as the teacher to transfer the learned knowledge to the baseline model. Experimental results show that the proposed method can significantly boost the performance of the baseline model and ranks the 1^{st} place among all monocular-based methods on the KITTI benchmark. Besides, extensive ablation studies are conducted, which further prove the effectiveness of each part of our designs and illustrate what the baseline model has learned from the LiDAR Net. Our code will be publicly available.

1 Introduction

3D object detection is an indispensable component for 3D scene perception, which has wide applications in the real world, such as autonomous driving and robotic navigation. Although the algorithms with stereo (Li et al., 2019b; Wang et al., 2019; Chen et al., 2020a) or LiDAR sensors (Qi et al., 2018; Shi et al., 2019; 2020) show promising performances, the heavy dependence on the expensive equipment restricts the application of these algorithms. Accordingly, the methods based on the cheaper and more easy-to-deploy monocular cameras (Xu & Chen, 2018; Ma et al., 2019; 2021; Brazil & Liu, 2019; Ding et al., 2020) show great potentials and have attracted lots of attention.

As shown in Figure 1 (a), some prior works (Brazil & Liu, 2019; Simonelli et al., 2019; Chen et al., 2020b) directly estimate the 3D bounding boxes from monocular images. However, because of the lack of depth cues, it is extremely hard to accurately detect the objects in the 3D space, and the localization error is the major issue of these methods (Ma et al., 2021). To mitigate this problem, an intuitive idea is to estimate the depth maps from RGB images, and then use them to augment the input data (Figure 1 (b)) (Xu & Chen, 2018; Ding et al., 2020) or directly use them as the input data (Figure 1 (c)) (Wang et al., 2019; Ma et al., 2019). Although these two strategies have made significant improvement in performance, the drawbacks of them can not be ignored: (1) These methods generally use an off-the-shelf depth estimator to generate the depth maps, which introduce lots of computational cost (*e.g.* the most commonly used depth estimator (Fu et al., 2018) need about 400ms to process a standard KITTI image). (2) The depth estimator and detector are trained separately, which may lead to a sub-optimal optimization. Recently, Reading et al. (2021) propose an end-to-end framework (Figure 1 (d)) for monocular 3D detection, which can also leverage depth estimator to provide depth cues. Specifically, they introduce a sub-network to estimate the depth distribution and use it to enrich the RGB features. Although this model can be trained end-to-end and achieves better performance, it still suffer from the low inference speed (630ms per image), mainly caused by the depth estimator and the complicated network architecture. Note that the well-designed monocular detectors, like Ma et al. (2021); Zhang et al. (2021b); Lu et al. (2021), only take about 40ms per image.

Figure 1: Comparison on the high-level paradigms of monocular 3D detectors.

In this paper, we aim to introduce the depth cues to the monocular 3D detectors without introducing any extra cost in the inference phase. Inspired by the knowledge distillation (Hinton et al.), which can transfer the learned knowledge from a well-trained CNN to another one without any changes in the model design, we propose that the spatial cues may also be transferred by this way from the LiDAR-based models. However, the main problem for this proposal is the difference of the feature representations used in these two kinds of methods (2D images features *v.s.* 3D voxel features). To bridge this gap, we propose to project the LiDAR signals into the image plane and use the 2D CNN, instead of the commonly used 3D CNN or point-wise CNN, to train a 'image-version' LiDAR-based model. After this alignment, the knowledge distillation can be friendly applied to enrich the features of our monocular detector.

Based on the above-mentioned motivation and strategy, we propose the **distill**ation based **mono**cular 3D detector (**MonoDistill**): We first train a teacher net using the projected LiDAR maps (used as the ground truths of the depth estimator in previous works), and then train our monocular 3D detector under the guidance of the teacher net. We argue that, compared with previous works, the proposed method has the following two advantages: First, our method directly learn the spatial cues from the teacher net, instead of the estimated depth maps. This design performs better by avoiding the information loss in the proxy task. Second, our method does not change the network architecture of the baseline model, thus no extra computational cost is introduced.

Experimental results on the most commonly used KITTI benchmark, where we rank the 1^{st} place among all monocular based models by applying the proposed method on a simple baseline, demonstrate the effectiveness of our approach. Besides, we also conduct extensive ablation studies to present each design of our method in detail. More importantly, these experiments clearly illustrate the improvements are achieved by the introduction of spatial cues, instead of other unaccountable factors in CNN.

2 RELATED WORKS

3D Detection from only monocular images. 3D detection from only monocular image data is challenging due to the lack of reliable depth information. To alleviate this problem, lots of scholars propose their solutions in different ways, including but not limited to network design (Roddick et al., 2019; Brazil & Liu, 2019; Zhou et al.; Liu et al., 2020; Luo et al., 2021), loss formulation (Simonelli et al., 2019; Ma et al., 2021), 3D prior (Brazil & Liu, 2019), geometric constrain (Mousavian et al., 2017; Qin et al., 2019; Li et al., 2019a; Chen et al., 2020b), or perspective modeling (Zhang et al., 2021a; Lu et al., 2021; Shi et al., 2021).

Depth augmented monocular 3D detection. To provide the depth information to the 3D detectors, several works choose to estimate the depth maps from RGB images. According to the usage of the estimated depth maps, these methods can be briefly divided into three categories. The first class of these methods use the estimated depth maps to augment the RGB images (Figure 1 (b)). In particular, Xu & Chen (2018) propose three fusion strategies of the RGB images and depth maps, while Ding et al. (2020) and Wang et al. (2021) focus on how to enrich the RGB features with depth maps in the latent feature space. Besides, Wang et al. (2019); Ma et al. (2019) propose another pipeline (Figure 1 (c)): They back-project the depth maps into the 3D space, and then use LiDAR-

Figure 2: Visualization of the sparse LiDAR maps (*left*) and the dense LiDAR maps (*right*).

based model and the resulting data (pseudo-LiDAR signal) to predict the 3D boxes. This framework shows promising performance, and lots works (Weng & Kitani, 2019; Cai et al., 2020; Wang et al., 2020; Chu et al., 2021) are built on this solid foundation. Recently, Reading et al. (2021) propose another way to leverage the depth cues for monocular 3D detection (Figure 1 (d)). Particularly, they first estimate the depth distribution using a sub-network, and then use it to lift the 2D features into 3D features, which is used to generate the final results. Compared with the previous two families, this model can be trained in the end-to-end manner, avoiding the sub-optimal optimization. However, a common disadvantage of these methods is that they inevitably increase the computational cost while introducing depth information. Unlike these methods, our model chooses to learn the feature representation under the guidance of depth maps, instead of integrating them. Accordingly, the proposed model not only introduces rich depth cues but also maintains high efficiency.

Knowledge distillation. Knowledge distillation (KD) is initially proposed by Hinton et al. for model compression, and the main idea of this mechanism is transferring the learned knowledge from large CNN models to the small one. Although the effectiveness of this strategy has been proved in many computer vision tasks, few work explore it in monocular 3D detection. In this work, we design a KD-based paradigm to efficiently introduce depth cues for monocular 3D detectors.

LIGA Stereo. We found a recent work LIGA Stereo (Guo et al., 2021) (submitted to arXiv on 18 Aug. 2021) discusses the application of KD for stereo 3D detection under the guidance of LiDAR signals. Here we discuss the main differences of LIGA Stereo and our work. First, the tasks and underlying data are different (monocular *v.s.* stereo), which leads to different conclusions. For example, Guo et al. (2021) concludes that using the predictions of teacher net as 'soft label' can not bring benefits. However, our experimental results shows the effectiveness of this design. Even more, in our task, supervising the student net in the result space is more effective than feature space. Second, they use an off-the-shelf LiDAR-based model to provide guidance to their model. However, we project the LiDAR signals into image plane and use the resulting data to train the teacher net. Except for the input data, the teacher net and student net are completely aligned, including network architecture, hyper-parameters, and training schedule. Third, to ensure the consistent shape of features, LIGA Stereo need to generate the cost volume from stereo images, which is time-consuming (it need about 350ms to estimate 3D boxes from a KITTI image) and hard to achieve for monocular images. In contrast, our method align the feature representations by adjusting the LiDAR-based model, instead of the target model. This design makes our method more efficient (about 35ms per image) and can generalize to all kinds of image-based models in theory.

3 METHOD

3.1 OVERVIEW

Figure 3 presents the framework of the proposed MonoDistill, which mainly has three components: a monocular 3D detector, an aligned LiDAR-based detector, and several side branches which build the bridge to provide guidance from the LiDAR-based detector to our monocular 3D detector. We will introduce the how to build these parts one by one in the rest of this section.

3.2 BASELINE MODEL

Student model. We use the one-stage monocular 3D detector MonoDLE (Ma et al., 2021) as our baseline model. Particularly, this baseline model adopt DLA-34 (Yu et al., 2017) as the backbone and use several parallel heads to predict the required items for 3D object detection. Due to this

Figure 3: **Illustration of the proposed MonoDistill.** We first generate the 'image-like' LiDAR maps from the LiDAR signals and then train a teacher model using an identical network to the student model. Finally, we propose three distillation schemes to train the student model under the guidance of the well-trained teacher net. In the inference phase, only the student net is used.

clean and compact design, this model achieve good performance with high efficiency. Besides, we further normalize the confidence of each predicted object using the estimated depth uncertainty (see Appendix A.1 for more details), which brings about 1 AP improvement.

Teacher model. Existing LiDAR-based models mainly based on the 3D CNN or point-wise CNN. To align the gap between the feature representations of the monocular detector and the LiDAR-based detector, we project the LiDAR points into the image plane to generate the sparse depth map. Further, we also use the interpolation algorithm (Ku et al., 2018) to generate the dense depth, and see Figure 2 for the visualization of generated data. Then, we use these 'image-like LiDAR maps' to train a LiDAR-based detector using the identical network with our student model.

3.3 MONODISTILL

In order to transfer the spatial cues from the well-trained teacher model to the student model, we design three complementary distillation schemes to provide additional guidance to the baseline model.

Scene-level distillation in the feature space. First, we believe the structured scene information is beneficial to our task. Therefore, we train our student model under the guidance of the high-level semantic features provided by the backbone of the teacher model. To better model the structured cues, we choose to learn the affinity map of high-level features, instead of the features themselves. Specifically, we first generate the affinity map, which encodes the similarity of each feature vector pair, for both the teacher and student network, and each element $A_{i,j}$ in this affinity map can be computed by:

$$A_{i,j} = \frac{f_i^T f_j}{||f_i||_2 \cdot ||f_j||_2},$$ (1)

where f_j and f_j denote the i^{th} and j^{th} feature vector. After that, we use the L1 norm to enforce the student net to learn the structured information from the teacher net:

$$\mathcal{L}_{sf} = \frac{1}{K \times K} \sum_{i=1}^{K} \sum_{j=1}^{K} ||A_{i,j}^t - A_{i,j}^s||_1,$$ (2)

Figure 4: *Left:* Regard the center point as the foreground region. *Right:* Generate foreground region from the center point and the size of bounding box. Besides, the 2D bounding box are used as the foreground region for $\mathcal{L}_{\mathbf{of}}$.

where K is the number of the feature vectors. Note the computational/storage complexity is quadratically related to K. To reduce the cost, we group all features into several local regions and generate the affinity map using the features of local regions. This makes the training of the proposed model more efficient, and we did not observe any performance drop caused by this strategy.

Object-level distillation in the feature space. Second, except for the affinity map, directly using the features from teacher net as guidance may also provide valuable cues to the student. However, there is much noise in feature maps, since the background occupies most of the area and is less informative. Distilling knowledge from these regions may make the network deviate from the right optimization direction. To make the knowledge distillation more focused, limiting the distillation area is necessary. Particularly, the regions in the ground-truth 2D bounding boxes are used for knowledge transfer to mitigate the effects of noise. Specifically, given the feature maps of the teacher model and student model $\{\mathbf{F^t}, \mathbf{F^s}\}$, our second distillation loss can be formulated as.

$$\mathcal{L}_{\mathbf{of}} = \frac{1}{N_{\text{pos}}} ||M_{\mathbf{of}}(F_{\mathbf{s}}^{\mathbf{k}} - F_{\mathbf{t}}^{\mathbf{k}})||_1, \tag{3}$$

where M_{of} is the mask generated from the center point and the size of 2D bounding box and N_{pos} is the number of valid feature vectors.

Object-level distillation in the result space. Third, similar to the traditional KD, we use the predictions from the teacher net as extra 'soft label' for the student net. Note that in this scheme, only the predictions on the foreground region should be used, because the predictions on the background region are usually false detection. As for the definition of the 'foreground regions', inspired by CenterNet (Zhou et al.), a simple baseline is regarding the center point as the foreground region. Furtherly, we find that the quality of the predicted value of the teacher net near the center point is good enough to guide the student net. Therefore, we generate a Gaussian-like mask based on the position of the center point and the size of 2D bounding box (see Figure 4 for the visualization). After that, our third distillation loss can be formulated as:

$$\mathcal{L}_{\mathbf{or}} = \sum_{k=1}^{N} ||M_{\mathbf{or}}(y_{\mathbf{k}}^{\mathbf{s}} - y_{\mathbf{k}}^{\mathbf{t}})||_1, \tag{4}$$

where $M_{\mathbf{or}}$ is the mask which represents positive and negative samples, $y_{\mathbf{k}}$ is the output of the k^{th} detection head and N is the number of detection heads.

Additional strategies. We further propose some strategies for our method. First, for the distillation schemes in the feature space (*i.e.* $\mathcal{L}_{\mathbf{sf}}$ and $\mathcal{L}_{\mathbf{of}}$), we only perform them on the last three blocks of the backbone. The main motivation of this strategy is: The first block usually is rich in the low-level features (such as edges, textures, etc.). The expression forms of the low-level features for LiDAR and image data may be completely different, and enforcing the student net to learn these features in a modality-across manner may mislead it. Second, in order to better guide the student to learn spatial-aware feature representations, we apply the attention based fusion module (FF in Table 1) proposed by Chen et al. (2021b) in our distillation schemes in the feature space (i.e. $\mathcal{L}_{\mathbf{sf}}$ and $\mathcal{L}_{\mathbf{of}}$).

Loss function. We train our model in an end-to-end manner using the following loss function:

$$\mathcal{L} = \mathcal{L}_{\mathbf{src}} + \lambda_1 \cdot \mathcal{L}_{\mathbf{sf}} + \lambda_2 \cdot \mathcal{L}_{\mathbf{of}} + \lambda_3 \cdot \mathcal{L}_{\mathbf{or}}, \tag{5}$$

where $\mathcal{L}_{\mathbf{src}}$ denotes the loss function used in the MonoDLE (Ma et al., 2021). $\lambda_1, \lambda_2, \lambda_3$ are the hyper-parameters to balance each loss. For the teacher net, only $\mathcal{L}_{\mathbf{src}}$ is adopted.

4 EXPERIMENTS

4.1 SETUP

Dataset and metrics. We conduct our experiments on the KITTI (Geiger et al., 2012), which is most commonly used dataset in 3D detection task. Specifically, this dataset provides 7,481 training samples and 7,518 testing samples, and we further divide the training data into a train set (3,712 samples) and a validation set (3,769 samples), following prior works (Chen et al., 2015). Both 3D detection and Bird's Eye View (BEV) detection are evaluated using $AP|_{R_{40}}$ (Simonelli et al., 2019) as metric. We report our final results on the *testing* set, while the ablation studies are conducted on the *validation* set. Besides, we mainly focus on the **Car** category, while also present the performances of **Pedestrian** and **Cyclist** in Appendix A.2 for reference.

Implementation. We provide the implementation details in Appendix A.1. Besides, our code will be open-sourced for the reproducibility.

4.2 MAIN RESULTS

Ablation studies. Table 1 shows the ablation studies of the proposed methods. Specifically, we can found that all three distillation schemes can improve the accuracy of the baseline model, and the improvements of them are complementary. Besides, the feature fusion strategy can also boost the accuracy. Compared with the baseline, our full model improve 3D detection performance by **3.34**, **5.02**, **2.98** and improve BEV performance by **5.16**, **6.62**, **3.87** on the moderate, easy and hard settings respectively.

Table 1: **Ablation studies on the KITTI *validation* set.** SF, OF, and OR denote the scene-level distillation in feature space, the object-level distillation in feature space, and the object-level distillation in result space, respectively. Besides, FF means the attention based feature fusion strategy.

	SF	OF	OR	FF	3D@IOU=0.7			BEV@IOU=0.7		
					Mod.	Easy	Hard	Mod.	Easy	Hard
a.					15.13	19.29	12.78	20.24	26.47	18.29
b.	✓				16.96	21.99	14.42	22.79	29.76	19.78
c.		✓			16.85	21.76	14.36	22.30	28.93	19.31
d.			✓		17.24	21.63	14.71	23.47	30.52	20.33
e.	✓	✓			17.33	22.34	14.63	22.90	30.02	19.84
f.	✓		✓		17.70	22.59	15.17	23.59	31.07	20.46
g.		✓	✓		17.98	22.58	15.26	23.76	30.98	20.52
h.	✓	✓	✓		18.24	23.82	15.49	25.06	32.66	21.88
i.	✓	✓	✓	✓	**18.47**	**24.31**	**15.76**	**25.40**	**33.09**	**22.16**

Detailed design choice. We provide additional experiments in Table 2 for our method. First, as for object-level distillation in the feature space, we investigate the different effects of applying distillation on the whole image and foreground regions. Due to the noise in the background, guiding the foreground regions is more effective than the whole image, which improves the accuracy by 0.7. Second, as for object-level distillation in the result space, we compare the different effects of point label and region label. It can be observed that the generated region can significantly increase performance while guiding only in sparse point label brings limited improvements. Our proposed label diffusion strategy can increase the number of positive samples for supervision, thus improving performance.

Comparison with state-of-the-art methods. Table 3 and Table 4 compare the proposed method with other state-of-the-art methods on the KITTI *test* and *validation* sets. On the *test* set, the proposed method outperforms existing methods in all metrics. We note that, compared with previous best results, we can obtain **1.83, 0.50, 1.53** improvements on the moderate, easy and hard settings in 3D detection. Furthermore, our method achieves more significant improvements in BEV detection, increasing upon the prior work by **2.51, 1.21, 2.46** on the moderate, easy and hard settings. Moreover, compared with the depth-based methods, our method outperforms them in performance by a margin and is superior to theirs in the inference speed. By contrast, our method can only takes

Table 2: **Evaluation on the KITTI *validation* set for detailed design choice.** OF and OR represent the object-level distillation in feature space and the object-level distillation in result space.

Guidance	Choice	3D@IOU=0.7			BEV@IOU=0.7		
		Mod.	Easy	Hard	Mod.	Easy	Hard
OF	full	16.13	21.52	14.18	22.04	27.85	19.04
	foreground	16.85	21.76	14.36	22.30	28.93	19.31
OR	sparse label	15.51	20.58	13.70	21.47	27.16	18.60
	diffused label	17.24	21.63	14.71	23.47	30.52	20.33

25ms to process a KITTI image, tested on a single NVIDIA GTX 1080Ti, while the Fastest of the depth-based methods (Ma et al., 2019; 2020; Ding et al., 2020; Wang et al., 2021; Reading et al., 2021) need 180ms. On the *validation* set, the proposed also performs best, both for the 0.7 IoU threshold and 0.5 IoU threshold. Besides, we also present the performance of the baseline model to better show the effectiveness of the proposed method. Note that we do not report the performances of some depth-based methods (Ma et al., 2019; 2020; Ding et al., 2020; Wang et al., 2021) due to the data leakage problem [1].

.

Table 3: **Comparison of state-of-the-art methods on the KITTI *test* set.** Methods are ranked by moderate setting. We highlight the best results in **bold** and the second place in underlined. Only RGB images are required as input in the inference phase for all listed methods. *: need dense depth maps or LiDAR signals for training. [†]: need CAD models for training.

Method	3D@IOU=0.7			BEV@IOU=0.7			Runtime
	Mod.	Easy	Hard	Mod.	Easy	Hard	
M3D-RPN (Brazil & Liu, 2019)	9.71	14.76	7.42	13.67	21.02	10.23	160 ms
SMOKE (Liu et al., 2020)	9.76	14.03	7.84	14.49	20.83	12.75	30 ms
MonoPair (Chen et al., 2020b)	9.99	13.04	8.65	14.83	19.28	12.89	60 ms
RTM3D (Li et al., 2020)	10.34	14.41	8.77	14.20	19.17	11.99	50 ms
AM3D* (Ma et al., 2019)	10.74	16.50	9.52	17.32	25.03	14.91	400 ms
PatchNet* (Ma et al., 2020)	11.12	15.68	10.17	16.86	22.97	14.97	400 ms
KM3D (Li & Zhao, 2021)	11.45	16.73	9.92	16.20	23.44	14.47	30 ms
D4LCN* (Ding et al., 2020)	11.72	16.65	9.51	16.02	22.51	12.55	200 ms
YOLOMono3D (Liu et al., 2021a)	12.06	18.28	8.42	17.15	26.79	12.56	50 ms
MonoDLE (Ma et al., 2021)	12.26	17.23	10.29	18.89	24.79	16.00	40 ms
MonoRUn* (Chen et al., 2021a)	12.30	19.65	10.58	17.34	27.94	15.24	70 ms
GrooMeD-NMS (Kumar et al., 2021)	12.32	18.10	9.65	18.27	16.19	14.05	120 ms
DDMP-3D* (Wang et al., 2021)	12.78	19.71	9.80	17.89	28.08	13.44	180 ms
Ground-Aware (Liu et al., 2021b)	13.25	21.65	9.91	17.98	29.81	13.08	50 ms
CaDDN* (Reading et al., 2021)	13.41	19.17	11.46	18.91	27.94	17.19	630 ms
MonoEF (Zhou et al., 2021)	13.87	21.29	11.71	19.70	29.03	17.26	30 ms
MonoFlex (Zhang et al., 2021b)	13.89	19.94	12.07	19.75	28.23	16.89	30 ms
Autoshape[†] (Liu et al., 2021c)	14.17	22.47	11.36	20.08	30.66	15.59	50 ms
GUPNet (Lu et al., 2021)	14.20	20.11	11.77	-	-	-	35 ms
Ours	**16.03**	**22.97**	**13.60**	**22.59**	**31.87**	**19.72**	40 ms
Improvements	+1.83	+0.50	+1.53	+2.51	+1.21	+2.46	-

4.3 MORE DISCUSSIONS

What has the student model learned from the teacher model? To locate the source of improvement, we use the items predicted from the baseline model to replace that from our full model, and Table 5 summarizes the results of the cross-model evaluation. From these results, we can see that the teacher model provides effective guidance to the location estimation (b→f), and improvement of

---

[1]these methods use the depth estimator pre-trained on the KITTI Depth, which overlaps with the validation set of the KITTI 3D.

Table 4: **Performance of the Car category on the KITTI *validation* set.** We highlight the best results in **bold** and the second place in underlined.

Method	3D@IOU=0.7			BEV@IOU=0.7			3D@IOU=0.5			BEV@IOU=0.5		
	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard
CenterNet	0.66	0.60	0.77	3.31	3.46	3.21	17.50	20.00	15.57	27.91	34.36	24.65
MonoGRNet	7.56	11.90	5.76	12.81	19.72	10.15	32.28	47.59	25.50	35.94	48.53	28.59
MonoDIS	7.60	11.06	6.37	12.58	18.45	10.66	-	-	-	-	-	-
M3D-RPN	11.07	14.53	8.65	15.62	20.85	11.88	35.94	48.53	28.59	39.60	53.35	31.76
MonoPair	12.30	16.28	10.42	18.17	24.12	15.76	42.39	55.38	37.99	47.63	61.06	41.92
MonoDLE	13.66	17.45	11.68	19.33	24.97	17.01	43.42	55.41	37.81	46.87	60.73	41.89
GrooMeD-NMS	14.32	19.67	11.27	19.75	27.38	15.92	41.07	55.62	32.89	44.98	61.83	36.29
MonoRUn	14.65	20.02	12.61	-	-	-	43.39	59.71	38.44	-	-	-
GUPNet	16.46	22.76	13.72	22.94	31.07	19.75	42.33	57.62	37.59	47.06	61.78	40.88
MonoFlex	17.51	23.64	14.83	-	-	-	-	-	-	-	-	-
Baseline	15.13	19.29	12.78	20.24	26.47	18.29	43.54	57.43	39.22	48.49	63.56	42.81
Ours	**18.47**	**24.31**	**15.76**	**25.40**	**33.09**	**22.16**	**49.35**	**65.69**	**43.49**	**53.11**	**71.45**	**46.94**

dimension part is also considerable (e→f). Relatively, the teacher model provides limited valuable cues to the classification and orientation part. This phenomenon suggests the proposed methods boost the performance of the baseline model mainly by introducing the spatial-related information, which is consistent with our initial motivation. Besides, we also show the errors of depth estimation, see Appendix A.3 for the results.

Table 5: **Cross-model evaluation on the KITTI *validation* set.** We extract each required item (location, dimension, orientation, and confidence) from the baseline model (B) and the full model (O), and evaluate them in a cross-model manner.

	loc.	dim.	ori.	con.	3D@IOU=0.7			BEV@IOU=0.7		
					Mod.	Easy	Hard	Mod.	Easy	Hard
a.	B	B	B	B	15.13	19.29	12.78	20.24	26.47	18.29
b.	B	O	O	O	16.05	20.07	13.47	21.31	27.77	19.14
c.	O	B	O	O	17.91	22.87	15.29	25.09	32.78	21.93
d.	O	O	B	O	18.12	24.02	15.34	25.02	32.85	21.84
e.	O	O	O	B	18.41	24.27	15.55	24.98	32.78	21.81
f.	O	O	O	O	18.47	24.31	15.76	25.40	33.09	22.16

Is the effectiveness of our method related to the performance of the teacher model? An intuitive conjecture is the student can learn more if the teacher network has better performance. To explore this problem, we also use the sparse LiDAR maps to train a teacher net to provide guidance to the student model (see Figure 2 for the comparison of the sparse and dense data). As shown in Table 6, the performance of the teacher model trained from the sparse LiDAR maps is largely behind by that from dense LiDAR maps (drop to 20.80% from 42.45%, moderate setting), while both of them provides comparable benefits to the student model. Therefore, for our task, the performance of the teacher model is not directly related to the performance improvement, while the more critical factor is whether the teacher network contains complementary information to the student network.

Table 6: **Performance of the student model under the guidance of different teacher models.** Metric is the $AP|_{40}$ for the 3D detection task on the KITTI *validation* set. We also show the performance improvements of the student model to the baseline model for better comparison.

	Teacher Model			Student Model			Improvement		
	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard
sparse maps	20.80	28.94	17.82	18.51	24.00	15.68	+3.38	+4.71	+2.90
dense maps	42.57	58.06	37.07	18.47	24.31	15.76	+3.34	+5.02	+2.98

Do we need depth estimation as an intermediate task? As shown in Figure 1, most previous methods choose to estimate the depth maps to provide depth information for monocular 3D detection (information flow: LiDAR data →estimated depth map→3D detector). Compared with this

scheme, our method directly learns the depth cues from LiDAR-based methods (information flow: LiDAR data→3D detector), avoiding the information loss in the depth estimation step. Here we qualitatively show the information loss in depth estimation using a simple experiment. Specifically, we use DORN (Fu et al., 2018) (same as most previous depth augmented methods) to generate the depth maps, and then use them to train the teacher net. Table 7 show the results of this experiment. Note that, compared with setting c, setting b's teacher net is trained from a larger training set (23,488 *v.s.* 3,712) with ground-truth depth maps (ground truth depth maps v.s. noisy depth maps). Nevertheless, this scheme still lags behind our original method, which means that there is serious information loss in monocular depth estimation (stereo image performs better, which is discussed in Appendix A.4).

Table 7: **Comparison of using depth estimation as intermediate task or not**. Setting a. and c. denote the baseline model and our full model. Setting b. uses the depth maps generated from DORN (Fu et al., 2018) to train the teacher model. Experiments are conducted on the KITTI *validation* set.

	3D@IOU=0.7			BEV@IOU=0.7			AOS@IOU=0.7			2D@IOU=0.7		
	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard
a.	15.13	19.29	12.78	20.24	26.47	18.29	90.95	97.46	83.02	92.18	98.37	85.05
b.	17.70	23.21	15.02	23.34	31.20	20.40	91.50	97.77	83.49	92.51	98.54	85.38
c.	18.47	24.31	15.76	25.40	33.09	22.16	91.67	97.88	83.59	92.71	98.58	85.56

4.4 QUALITATIVE RESULTS

In Figure 5, we show the qualitative comparison of detection results. We can see that the proposed method shows better localization accuracy than the baseline model. See Appendix A.5 for the multi-class and more detailed qualitative results.

Figure 5: **Qualitative results**. We use green, blue and red bounding boxes to denote the results from baseline, our method, and ground truth. Besides, we use red circle to highlight the main differences of these results.

5 CONCLUSION

In this work, we propose the MonoDistill, which introduces spatial cues to the monocular 3D detector based on the knowledge distillation mechanism. Compared with previous schemes, which share the same motivation, our method avoids any modifications on the target model and directly learns the spatial features from the model rich in these features. This design makes the proposed methods perform well both in performance and efficiency. To show an all-around display of our model, extensive experiments are conducted on the KITTI dataset, where the proposed method ranks 1^{st} at 25 FPS among all monocular 3D detectors.

REFERENCES

Garrick Brazil and Xiaoming Liu. M3d-rpn: Monocular 3d region proposal network for object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9287–9296, 2019.

Yingjie Cai, Buyu Li, Zeyu Jiao, Hongsheng Li, Xingyu Zeng, and Xiaogang Wang. Monocular 3d object detection with decoupled structured polygon estimation and height-guided depth estimation. In *AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pp. 10478–10485, 2020.

Hansheng Chen, Yuyao Huang, Wei Tian, Zhong Gao, and Lu Xiong. Monorun: Monocular 3d object detection by reconstruction and uncertainty propagation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10379–10388, 2021a.

Pengguang Chen, Shu Liu, Hengshuang Zhao, and Jiaya Jia. Distilling knowledge via knowledge review. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*. Computer Vision Foundation / IEEE, 2021b.

Xiaozhi Chen, Kaustav Kundu, Yukun Zhu, Andrew G. Berneshawi, Huimin Ma, Sanja Fidler, and Raquel Urtasun. 3d object proposals for accurate object class detection. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, 2015.

Yilun Chen, Shu Liu, Xiaoyong Shen, and Jiaya Jia. DSGN: deep stereo geometry network for 3d object detection. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, pp. 12533–12542. Computer Vision Foundation / IEEE, 2020a.

Yongjian Chen, Lei Tai, Kai Sun, and Mingyang Li. Monopair: Monocular 3d object detection using pairwise spatial relationships. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020b.

Xiaomeng Chu, Jiajun Deng, Yao Li, Zhenxun Yuan, Yanyong Zhang, Jianmin Ji, and Yu Zhang. Neighbor-vote: Improving monocular 3d object detection through neighbor distance voting. In *ACM International Conference on Multimedia (MM)*, 2021.

Mingyu Ding, Yuqi Huo, Hongwei Yi, Zhe Wang, Jianping Shi, Zhiwu Lu, and Ping Luo. Learning depth-guided convolutions for monocular 3d object detection. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020.

Huan Fu, Mingming Gong, Chaohui Wang, Kayhan Batmanghelich, and Dacheng Tao. Deep ordinal regression network for monocular depth estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2002–2011, 2018.

Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the KITTI vision benchmark suite. In *2012 IEEE Conference on Computer Vision and Pattern Recognition, Providence, RI, USA, June 16-21, 2012*, pp. 3354–3361. IEEE Computer Society, 2012.

Xiaoyang Guo, Shaoshuai Shi, Xiaogang Wang, and Hongsheng Li. Liga-stereo: Learning lidar geometry aware representations for stereo-based 3d detector. *arXiv preprint arXiv:2108.08258*, 2021.

Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. *CoRR*, abs/1503.02531.

Jason Ku, Ali Harakeh, and Steven L Waslander. In defense of classical image processing: Fast depth completion on the cpu. In *2018 15th Conference on Computer and Robot Vision (CRV)*, pp. 16–22. IEEE, 2018.

Abhinav Kumar, Garrick Brazil, and Xiaoming Liu. Groomed-nms: Grouped mathematically differentiable nms for monocular 3d object detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8973–8983, 2021.

Buyu Li, Wanli Ouyang, Lu Sheng, Xingyu Zeng, and Xiaogang Wang. Gs3d: An efficient 3d object detection framework for autonomous driving. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1019–1028, 2019a.

Peiliang Li, Xiaozhi Chen, and Shaojie Shen. Stereo r-cnn based 3d object detection for autonomous driving. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7644–7652, 2019b.

Peixuan Li and Huaici Zhao. Monocular 3d detection with geometric constraint embedding and semi-supervised training. *IEEE Robotics Autom. Lett.*, 6(3):5565–5572, 2021.

Peixuan Li, Huaici Zhao, Pengfei Liu, and Feidao Cao. RTM3D: real-time monocular 3d detection from object keypoints for autonomous driving. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm (eds.), *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part III*, 2020.

Yuxuan Liu, Lujia Wang, and Ming Liu. Yolostereo3d: A step back to 2d for efficient stereo 3d detection. *CoRR*, abs/2103.09422, 2021a.

Yuxuan Liu, Yixuan Yuan, and Ming Liu. Ground-aware monocular 3d object detection for autonomous driving. *IEEE Robotics Autom. Lett.*, 6(2):919–926, 2021b.

Zechen Liu, Zizhang Wu, and Roland Tóth. Smoke: single-stage monocular 3d object detection via keypoint estimation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pp. 996–997, 2020.

Zongdai Liu, Dingfu Zhou, Feixiang Lu, Jin Fang, and Liangjun Zhang. Autoshape: Real-time shape-aware monocular 3d object detection. *CoRR*, abs/2108.11127, 2021c.

Yan Lu, Xinzhu Ma, Lei Yang, Tianzhu Zhang, Yating Liu, Qi Chu, Junjie Yan, and Wanli Ouyang. Geometry uncertainty projection network for monocular 3d object detection. *CoRR*, abs/2107.13774, 2021.

Shujie Luo, Hang Dai, Ling Shao, and Yong Ding. M3dssd: Monocular 3d single stage object detector. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2021.

Xinzhu Ma, Zhihui Wang, Haojie Li, Pengbo Zhang, Wanli Ouyang, and Xin Fan. Accurate monocular 3d object detection via color-embedded 3d reconstruction for autonomous driving. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, 2019.

Xinzhu Ma, Shinan Liu, Zhiyi Xia, Hongwen Zhang, Xingyu Zeng, and Wanli Ouyang. Rethinking pseudo-lidar representation. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm (eds.), *Computer Vision - ECCV 2020 - 16th European Conference, Glasgow, UK, August 23-28, 2020, Proceedings, Part XIII*, Lecture Notes in Computer Science, 2020.

Xinzhu Ma, Yinmin Zhang, Dan Xu, Dongzhan Zhou, Shuai Yi, Haojie Li, and Wanli Ouyang. Delving into localization errors for monocular 3d object detection. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, pp. 4721–4730, 2021.

Arsalan Mousavian, Dragomir Anguelov, John Flynn, and Jana Kosecka. 3d bounding box estimation using deep learning and geometry. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7074–7082, 2017.

Charles R Qi, Wei Liu, Chenxia Wu, Hao Su, and Leonidas J Guibas. Frustum pointnets for 3d object detection from rgb-d data. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 918–927, 2018.

Zengyi Qin, Jinglu Wang, and Yan Lu. Monogrnet: A geometric reasoning network for monocular 3d object localization. In *AAAI Conference on Artificial Intelligence (AAAI)*, volume 33, pp. 8851–8858, 2019.

Cody Reading, Ali Harakeh, Julia Chae, and Steven L. Waslander. Categorical depth distribution network for monocular 3d object detection. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021.

Thomas Roddick, Alex Kendall, and Roberto Cipolla. Orthographic feature transform for monocular 3d object detection. 2019.

Shaoshuai Shi, Xiaogang Wang, and Hongsheng Li. Pointrcnn: 3d object proposal generation and detection from point cloud. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, 2019.

Shaoshuai Shi, Chaoxu Guo, Li Jiang, Zhe Wang, Jianping Shi, Xiaogang Wang, and Hongsheng Li. PV-RCNN: point-voxel feature set abstraction for 3d object detection. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*, 2020.

Xuepeng Shi, Qi Ye, Xiaozhi Chen, Chuangrong Chen, Zhixiang Chen, and Tae-Kyun Kim. Geometry-based distance decomposition for monocular 3d object detection. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

Andrea Simonelli, Samuel Rota Bulò, Lorenzo Porzi, Manuel Lopez-Antequera, and Peter Kontschieder. Disentangling monocular 3d object detection. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*. IEEE, 2019.

Li Wang, Liang Du, Xiaoqing Ye, Yanwei Fu, Guodong Guo, Xiangyang Xue, Jianfeng Feng, and Li Zhang. Depth-conditioned dynamic message propagation for monocular 3d object detection. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021.

Xinlong Wang, Wei Yin, Tao Kong, Yuning Jiang, Lei Li, and Chunhua Shen. Task-aware monocular depth estimation for 3d object detection. In *AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pp. 12257–12264, 2020.

Yan Wang, Wei-Lun Chao, Divyansh Garg, Bharath Hariharan, Mark E. Campbell, and Kilian Q. Weinberger. Pseudo-lidar from visual depth estimation: Bridging the gap in 3d object detection for autonomous driving. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, 2019.

Xinshuo Weng and Kris Kitani. Monocular 3d object detection with pseudo-lidar point cloud. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*, pp. 0–0, 2019.

Bin Xu and Zhenzhong Chen. Multi-level fusion based 3d object detection from monocular images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2345–2353, 2018.

Fisher Yu, Dequan Wang, and Trevor Darrell. Deep layer aggregation. *CoRR*, abs/1707.06484, 2017.

Yinmin Zhang, Xinzhu Ma, Shuai Yi, Jun Hou, Zhihui Wang, Wanli Ouyang, and Dan Xu. Learning geometry-guided depth via projective modeling for monocular 3d object detection. *arXiv preprint arXiv:2107.13931*, 2021a.

Yunpeng Zhang, Jiwen Lu, and Jie Zhou. Objects are different: Flexible monocular 3d object detection. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, 2021b.

Xingyi Zhou, Dequan Wang, and Philipp Krähenbühl. Objects as points. *CoRR*.

Yunsong Zhou, Yuan He, Hongzi Zhu, Cheng Wang, Hongyang Li, and Qinhong Jiang. Monocular 3d object detection: An extrinsic parameter free approach. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7556–7566, June 2021.

A APPENDIX

A.1 MORE DETAILS OF THE BASELINE MODEL

Network architecture. The baseline network is extended from the anchor-free 2D object detection framework, which consists of a feature extraction network and seven detection subheads. We employ DLA34 (Yu et al., 2017) without deformable convolutions as our backbone. The feature maps are downsampled by 4 times and then we take the image features as input and use 3x3 convolution, ReLU, and 1x1 convolution to output predictions for each detection head. Detection head branchs include three for 2D components and four for 3D components. Specifically, 2D detection heads include heatmap, offset between the 2D key-point and the 2D box center and size of 2D box. 3D components include offset between the 2D key-point and the projected 3D object center, depth, dimensions and orientations. As for objective functions, we train the heatmap with focal loss. The other loss items adopt L1 losses except for depth and orientation. Depth branch employs a modified L1 loss with the assist of heteroscedastic aleatoric uncertainty. Common multiBin loss is used for orientation branch. Besides, we propose a strategy to improve the accuracy of baseline. Inspire by (Lu et al., 2021), estimated depth uncertainty can provide confidence for each projection depth. Therefore, we normalize the confidence of each predicted box using depth uncertainty. In this way, score has capability of indicating the uncertainty of depth.

Training details. Our model is trained on 2 NVIDIA 1080Ti (12G) GPUS in an end-to-end manner for 150 epochs. We employ the common Adam optimizer with initial learning rate 1.25e–4, and decay it by ten times at 90 and 120 epochs. To stabilize the training process, we also used the warm-up strategy. As for data augmentations, in addition to random flip, we also use random crop. Note that, because our distillation mechanism needs to process data for both RGB map and depth map in the same type to ensure alignment, some data augmentations will bring about the change of labels. Therefore, we did not employ random scale due to its complexity in 3D space. And we use the common knowledge distillation scheme, first train teacher network in advance, and then fix the teacher network. As for student network, we simply train the detection model to give a suitable initialization. We implemented our method using PyTorch. And our code is based on Ma et al. (2021).

A.2 PEDESTRIAN/CYCLIST DETECTION ON THE KITTI TEST SET.

Due to the small sizes, non-rigid structures, the pedestrian and cyclist categories are much more challenging. We report the detection results in table 8. It can be seen that our proposed method is also competitive with current state-of-the-art methods on the KITTI *test* set, which increases 0.69 AP on hard difficulty level of pedestrian category. Note that, the accuracy of these difficult categories fluctuates greatly compared with Car detection due to insufficient training samples.

Table 8: **Performance of Pedestrian/Cyclist detection on the KITTI *test* set.** We highlight the best results in **bold** and the second place in underlined.

Method	Pedestrian			Cyclist		
	Easy	Mod.	Hard	Easy	Mod.	Hard
M3D-RPN	4.92	3.48	2.94	0.94	0.65	0.47
D4LCN	4.55	3.42	2.83	2.45	1.67	1.36
MonoPair	10.02	6.68	5.53	3.79	2.21	1.83
MonoFlex	9.43	6.31	5.26	4.17	2.35	2.04
MonoDLE	9.64	6.55	5.44	4.59	2.66	2.45
CaDDN	**12.87**	8.14	6.76	**7.00**	**3.14**	**3.30**
DDMP-3D	4.93	3.55	3.01	4.18	2.50	2.32
Autoshape	5.46	3.74	3.03	5.99	3.06	2.70
Ours	12.79	**8.17**	**7.45**	5.53	2.81	2.40

Figure 6: **Depth Error Analysis.** We show the depth error distributions and fit it into a linear function. *Left:* Baseline model. *Right:* Our Full Model.

A.3 DEPTH ERROR ANALYSIS

As shown in Fig 6, we compare the depth error between baseline and our method. Specifically, for each car sample, we obtain the predicted depth and then calculate the difference with the label. Further, we fit depth errors as a linear function by Least square method. Our proposed method shows a significant reduction in depth errors at different distances.

A.4 THE EFFECTS OF STEREO DEPTH

We explore the changes in performance under the guidance of stereo depth estimation. The results are shown in table 9. Stereo depth estimation exploits geometric constraints in stereo images to obtain the absolute depth value through pixel-wise matching, which is accurate enough compared with monocular depth estimation. Therefore, under the guidance of stereo depth, it achieves almost the same accuracy as LiDAR signals guidance at 0.5 IoU threshold. There is only a small performance degradation at 0.7 IoU threshold.

Table 9: **Effects of Stereo Depth Estimation.** Baseline denotes the baseline model without guidance of teacher network. Stereo Depth and LiDAR Depth denote under the guidance of stereo depth maps and LiDAR signals. Experiments are conducted on the KITTI *validation* set.

	3D@IOU=0.7			BEV@IOU=0.7			3D@IOU=0.5			BEV@IOU=0.5		
	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard	Mod.	Easy	Hard
Baseline	15.13	19.29	12.78	20.24	26.47	18.29	43.54	57.43	39.22	48.49	63.56	42.81
Stereo Depth	18.18	23.54	15.42	24.89	32.26	21.64	49.13	65.18	43.29	52.88	69.47	46.72
LiDAR Depth	18.47	24.31	15.76	25.40	33.09	22.16	49.35	65.69	43.49	53.11	71.45	46.94

A.5 MORE QUALITATIVE RESULTS

In Figure 7, we show more qualitative results on the KITTI dataset. We use orange box, green box, and purple box for car, pedestrian, and cyclist, respectively. In Figure 8, we show comparison of detection results in 3D scene. It can be found that our method can significantly improve the accuracy of depth estimation compared with baseline.

Figure 7: Qualitative results for multi-class 3D object detection. The boxes' color of cars, pedestrian, and cyclist are in orange, green, and purple, respectively.

Figure 8: Qualitative results of our method for 3D space. The boxes' color of ground truth, baseline, and ours are in red, green, and blue, respectively.