DYNAMICS-AWARE COMPARISON OF LEARNED REWARD FUNCTIONS

ABSTRACT

The ability to learn reward functions plays an important role in enabling the deployment of intelligent agents in the real world. However, *comparing* reward functions, for example as a means of evaluating reward learning methods, presents a challenge. Reward functions are typically compared by considering the behavior of optimized policies, but this approach conflates deficiencies in the reward function with those of the policy search algorithm used to optimize it. To address this challenge, Gleave et al. (2020) propose the Equivalent-Policy Invariant Comparison (EPIC) distance. EPIC avoids policy optimization, but in doing so requires computing reward values at transitions that may be impossible under the system dynamics. This is problematic for learned reward functions because it entails evaluating them outside of their training distribution, resulting in inaccurate reward values that we show can render EPIC ineffective at comparing rewards. To address this problem, we propose the Dynamics-Aware Reward Distance (DARD), a new reward pseudometric. DARD uses an approximate transition model of the environment to transform reward functions into a form that allows for comparisons that are invariant to reward shaping while only evaluating reward functions on transitions close to their training distribution. Experiments in simulated physical domains demonstrate that DARD enables reliable reward comparisons without policy optimization and is significantly more predictive than baseline methods of downstream policy performance when dealing with learned reward functions.

1 INTRODUCTION

Reward functions provide a general way to specify objectives for reinforcement learning. Tasks such as game playing have simple, natural reward functions that enable learning of effective policies (Tesauro, 1995; Mnih et al., 2013; Silver et al., 2017); however, many tasks, such as those involving human interaction, multiple competing objectives, or high-dimensional state spaces, do not have easy to define reward functions (Knox et al., 2021; Holland et al., 2013; Cabi et al., 2019). In these cases, reward functions can be learned from demonstrations, explicit preferences, or other forms of reward supervision (Abbeel & Ng, 2004; Christiano et al., 2017; Cabi et al., 2019). However, evaluating the quality of learned reward functions, which may be too complicated to manually inspect, remains an open challenge.

Prior work on comparing reward functions typically involves a computationally expensive and indirect process of (i) learning a reward function, (ii) learning a policy on that reward function, and (iii) evaluating that policy on a known, ground-truth reward function. Gleave et al. (2020) refer to this as the "rollout method" for evaluating methods for learning reward functions. Furthermore, the rollout method can be potentially dangerous in safety critical environments because (i) it cannot distinguish deficiencies between the reward function and the policy optimization procedure, and (ii) rewards are evaluated on the distribution of transitions induced by an optimized policy, which may not capture all the transitions required to accurately quantify reward differences.

To address these challenges, Gleave et al. (2020) introduce Equivalent-Policy Invariant Comparison (EPIC). EPIC quantifies differences in reward functions directly, without learning policies. EPIC uses an offline dataset of transitions, and consists of two stages. First, transitions from this dataset are used to convert reward functions to a canonical form that is invariant to reward transformations that do not affect the optimal policy. Second, the correlation between reward values is computed on

transition samples, yielding a pseudometric capturing reward function similarity. However, when computing this canonical form, EPIC evaluates rewards on transitions between all state-state combinations, regardless of whether those state-state transitions are possible or not. While this makes it possible for EPIC to quantify reward distances that are robust to arbitrary changes in transition dynamics, in practice evaluating learned reward functions on physically impossible transitions leads to unreliable reward values, as these are outside the distribution of the transitions on which the reward functions are learned. We show empirically in Section 5 that these out-of-distribution reward evaluations can render EPIC an ineffective reward comparison metric.

To address this issue, we propose a new method for quantifying differences in reward functions, Dynamics-Aware Reward Distance (DARD), that transforms reward functions into a form allowing for reward-shaping-invariant comparisons while ensuring that learned reward functions are only evaluated on transitions that are physically realizable. We achieve this by assuming access to a transition model for the environment of interest, and evaluate reward functions on transitions sampled from this transition model. This ensures that reward functions are not evaluated on impossible transitions, which will necessarily be out-of-distribution, and is well motivated in a variety of physical environments in which transition models are unlikely to change significantly between learning and deployment. Experiments suggest that DARD better reflects reward function similarity than does EPIC in comparing learned reward functions in two simulated, physics-based environments: the first involving multi-agent navigation, and the second involving manipulating a robotic arm. Videos available at https://sites.google.com/view/dard-paper.

2 RELATED WORK

2.1 LEARNING REWARD FUNCTIONS

A variety of methods exist for learning reward functions, which can be categorized based on the form of supervision used. Rewards can be learned from supervision provided by explicit labels. For example, human-labeled preferences between demonstrations can be used to learn reward functions (Christiano et al., 2017). Rewards can also be labeled on a per-timestep basis, allowing for learning via supervised regression (Cabi et al., 2019).

Alternatively, inverse reinforcement learning (IRL) methods typically assume access to expert demonstrations, and attempt to find a reward function under which the expert is uniquely optimal (Ziebart et al., 2008; Abbeel & Ng, 2004). IRL is underconstrained in that many reward functions can make the expert policy appear optimal. This problem is often addressed by favoring reward functions that induce high-entropy optimal policies (Ziebart et al., 2008). Recent work in IRL focuses on learning reward functions with expressive function approximators such as neural networks, particularly in an adversarial formulation (Fu et al., 2017). There has also been recent interest in offline IRL methods (Lee et al., 2019). In this work, we study how these various reward learning methods can be evaluated efficiently and accurately in practice.

2.2 EVALUATING METHODS OF LEARNING REWARD FUNCTIONS

Reward functions are typically evaluated by first learning an optimal policy under the reward function. The value of the induced policy is found by aggregating the returns from online trajectory rollouts under the known, ground-truth reward function. This requirement of online rollouts from experimental policies is often prohibitive in safety-critical domains such as autonomous driving or decision making in healthcare (Thapa et al., 2005).

Off-policy evaluation (OPE) methods attempt to address these issues by estimating the value of a policy in a purely offline setting by using previously collected data. Traditional OPE methods address policy mismatch by using a form of importance sampling (Precup et al., 2000). While this approach can be effective, it is unbiased only if the underlying expert policy is known, and can often be subject to large variance. Direct OPE methods (Dudik et al. (2011); Voloshin et al. (2020)), apply regression-based techniques in either a model-based (Paduraru, 2013) or model-free setting (Le et al., 2019). Contemporary works combine these two methods using Doubly Robust Estimation, which originated in a contextual bandits setting (Dudik et al., 2011), and was later extended to reinforcement learning by Jiang & Li (2016). More recent works seek to forego models

and importance sampling entirely, such as Irpan et al. (2019), which recasts OPE as a positive-unlabeled classification problem with the Q-function as the decision function. An overview of all of these methods and empirical analysis of their performance can be found in Voloshin et al. (2020).

All OPE methods indirectly evaluate the reward by estimating the value of the induced optimal policy. This introduces additional complexity into the evaluation procedure and can obfuscate sources of error as resulting either from aspects of policy learning or due to the underlying reward function. EPIC (Gleave et al., 2020) seeks to circumvent these shortcomings by comparing reward functions directly. Our work builds on EPIC as covered in Section 4, but uses a transition model of the environment to significantly improve the accuracy of comparisons involving learned reward functions.

3 PRELIMINARIES

3.1 MARKOV DECISION PROCESSES

A Markov decision process (MDP) is a tuple $(\mathcal{S}, \mathcal{A}, T, R, \gamma, d_0)$ where $\mathcal{S}$ and $\mathcal{A}$ are the state and action spaces. The transition model $T : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow [0, 1]$ maps a state and action to a probability distribution over next states, the reward $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow \mathbb{R}$ measures the quality of a transition. Finally, $\gamma \in [0, 1]$ and d_0 are respectively the discount factor and initial state distribution. A trajectory τ consists of a sequence of state-action pairs: $\tau = \{(s_0, a_0), (s_1, a_1), ...\}$, and the return g of a trajectory is defined as the sum of discounted rewards along that trajectory: $g(\tau) = \sum_{t=0}^{\infty} \gamma^t R(s_t, a_t, s_{t+1})$. The goal in an MDP is to find a policy $\pi : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$ that maximizes the expected return, $\mathbb{E}[g(\tau)]$, where $s_0 \sim d_0$, $a_t \sim \pi(a_t|s_t)$, and $s_{t+1} \sim T(s_{t+1}|s_t, a_t)$.

We denote a distribution over a space $\mathcal{S}$ as $\mathcal{D}_{\mathcal{S}}$, and the set of distributions over a space $\mathcal{S}$ as $\Delta(\mathcal{S})$.

3.2 REWARD FUNCTION EQUIVALENCE

Our goal is to define a metric for comparing reward functions without learning policies. Nevertheless, the measure of similarity we are interested in is the extent to which the optimal policies induced by two reward functions are the same. Because different reward functions can induce the same set of optimal policies, we in fact seek a *pseudometric* as formalized in the following definition.

Definition 3.1 (Pseudometric (Definition 3.5 from Gleave et al. (2020))). *Let $\mathcal{X}$ be a set and $d : \mathcal{X} \times \mathcal{X} \rightarrow [0, \infty]$ a function. d is a premetric if $d(x, x) = 0$ for all $x \in \mathcal{X}$. d is a pseudometric if, furthermore, it is symmetric, $d(x, y) = d(y, x)$ for all $x, y \in \mathcal{X}$; and satisfies the triangle inequality, $d(x, z) \leq d(x, y) + d(y, z)$ for all $x, y, z \in \mathcal{X}$. d is a metric if, furthermore, for all $x, y \in \mathcal{X}$, $d(x, y) = 0 \implies x = y$.*

Which rewards induce the same set of optimal policies? Ng et al. (1999) showed that without additional prior knowledge about the MDP only reward functions that are related through a difference in state potentials are equivalent. This "reward shaping" refers to an additive transformation F applied to an initial reward function R to compute a shaped reward R': $R'(s, a, s') = R(s, a, s') + F(s, a, s')$. Reward shaping is typically applied in a reward design setting to produce denser reward functions that make policy optimization easier in practice (Ng et al., 2003; Schulman et al., 2015). Ng et al. (1999) showed that if F is of the form $F(s, a, s') = \gamma\Phi(s') - \Phi(s)$ for arbitrary state potential function $\Phi(s)$, the set of optimal policies under R and R' are the same. This provides a definition for reward equivalence:

Definition 3.2 (Reward Equivalence, Definition 3.3 from Gleave et al. (2020)). *Bounded rewards R_A and R_B, are equivalent if and only if*

$$\exists \lambda > 0, \text{ and } \Phi : \mathcal{S} \rightarrow \mathbb{R} \text{ bounded s.t.}$$
$$R_B(s, a, s') = \lambda R_A(s, a, s') + \gamma\Phi(s') - \Phi(s) \ \forall s, s' \in \mathcal{S}, \ a \in \mathcal{A}.$$

This form of equivalence is only possible in reward functions that depend on (s, a, s'), which motivates our focus on these types of rewards in this paper. This choice is further motivated by the fact that there are cases where conditioning on the next state s' can make reward learning simpler, for example in highly stochastic MDPs, or in cases where rewards are a simple function of (s, a, s'), but not of (s, a). We next describe an existing pseudometric that in theory is capable of identifying these reward equivalence classes.

3.3 EQUIVALENT-POLICY INVARIANT COMPARISON (EPIC)

EPIC is a pseudometric for comparing reward functions and involves two stages. The first stage converts reward functions into a canonical form that removes the effect of reward shaping, and the second stage computes the correlation between the canonicalized rewards.

The following definition describes the canonicalization stage.

Definition 3.3 (Canonically Shaped Reward (Definition 4.1 from Gleave et al. (2020))). *Let R : $\mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ be a reward function. Given distributions $\mathcal{D}_\mathcal{S} \in \Delta(\mathcal{S})$ and $\mathcal{D}_\mathcal{A} \in \Delta(\mathcal{A})$ over states and actions, let S and S' be independent random variables distributed as $\mathcal{D}_\mathcal{S}$ and A distributed as $\mathcal{D}_\mathcal{A}$. Define the canonically shaped R to be:*

$$C_{\mathcal{D}_\mathcal{S}, \mathcal{D}_\mathcal{A}}(R)(s, a, s') = R(s, a, s') + \mathbb{E}[\gamma R(s', A, S') - R(s, A, S') - \gamma R(S, A, S')]. \quad (1)$$

Fig. 1 visualizes this process. Informally, this operation computes the mean of the potentials of s and s' with respect to S' using only evaluations of the reward R, and subtracts/adds those averages from/to the original, shaped reward, thereby canceling out their effects. This cancellation behavior is formalized in the following proposition.

Proposition 1 (The Canonically Shaped Reward is Invariant to Shaping (Proposition 4.2 from Gleave et al. (2020))). *Let $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ be a reward function, and $\Phi : \mathcal{S} \to \mathbb{R}$ a potential function. Let $\gamma \in [0, 1]$ be a discount rate, and $\mathcal{D}_\mathcal{S} \in \Delta(\mathcal{S})$ and $\mathcal{D}_\mathcal{A} \in \Delta(\mathcal{A})$ be distributions over states and actions. Let R' denote R shaped by $\Phi : R'(s, a, s') = R(s, a, s') + \gamma\Phi(s') - \Phi(s)$. Then the canonically shaped R' and R are equal: $C_{\mathcal{D}_\mathcal{S}, \mathcal{D}_\mathcal{A}}(R') = C_{\mathcal{D}_\mathcal{S}, \mathcal{D}_\mathcal{A}}(R)$.*

This invariance means that canonicalized rewards can be compared without reward shaping impacting the comparison. In practice, canonicalization is performed over an offline dataset of transitions. The rewards for (s, a, s') transitions are computed, and then canonicalized using (1). The distributions $\mathcal{D}_\mathcal{S}$ and $\mathcal{D}_\mathcal{A}$ are the marginal distributions of states and actions in the dataset on which evaluation proceeds. As we will discuss in the next section, this results in evaluating learned reward functions outside their training distribution, leading to inaccurate reward values.

EPIC's second stage computes the Pearson distance between two canonicalized reward functions.

Definition 3.4 (Pearson Distance (Definition 4.4 from Gleave et al. (2020))). *The Pearson distance between random variables X and Y is defined by the expression $D_\rho(X, Y) = \sqrt{1 - \rho(X, Y)}/\sqrt{(2)}$, where $\rho(X, Y)$ is the Pearson correlation between X and Y.*

In combining these two steps, EPIC is capable of quantifying the similarity of two reward functions while being invariant to shaping (due to canonicalization), and invariant to changes in shift and scale (due to the use of the Pearson distance).

Definition 3.5 (EPIC pseudometric (Definition 4.6 from Gleave et al. (2020))). *Let S, A, S' be random variables jointly following some coverage transition distribution. Let $\mathcal{D}_\mathcal{S}$, and $\mathcal{D}_\mathcal{A}$ respectively be the state and action distributions. The EPIC pseudometric between rewards R_A and R_B is:*

$$D_{EPIC}(R_A, R_B) = D_\rho\Big(C_{\mathcal{D}_\mathcal{S}, \mathcal{D}_\mathcal{A}}(R_A)(S, A, S'), C_{\mathcal{D}_\mathcal{S}, \mathcal{D}_\mathcal{A}}(R_B)(S, A, S')\Big). \quad (2)$$

Note that during the canonicalization stage, S, A, S' are independent while in the stage computing the Pearson correlation between canonical rewards, the joint distribution of S, A, S' is used.

4 DARD: DYNAMICS-AWARE REWARD DISTANCE

Here we present DARD, a new distance measure between learned reward functions that leverages information about system dynamics to prevent errors due to out-of-distribution queries of learned rewards. As described in 3.3, the EPIC distance measure first transforms reward functions as shown in equation (1). This transformation procedure involves computing expectations $\mathbb{E}[R(s', A, S')]$, $\mathbb{E}[R(s, A, S')]$, and $\mathbb{E}[R(S, A, S')]$ with *independent* random variables S and S' distributed as $\mathcal{D}_\mathcal{S}$, which in practice is the marginal distribution of states in the dataset. Thus, the resulting transitions may not actually be possible under the transition model of the environment of interest. Computing transformed rewards with these out-of-distribution transitions allows EPIC to be robust to (arbitrary) changes in the transition model. Moreover, without additional information about the transition

Figure 1: These plots depict the canonicalization procedure of EPIC (**left**) and the transformation of DARD (**right**) applied to a single transition from $s = 1$ to $s' = 2$ in a simple MDP. The contours depict a reward function for a 1D, continuous-state environment with a continuous action space of displacements in $[-1, 1]$. The axes show the state S and next state S' (omitting the action because T is deterministic). The reward function is zero everywhere, but shaped by the potential function $\Phi(s)$. The plotted points correspond to different terms in Eq. (1) or Eq. (3) as indicated by the legends. EPIC canonicalizes reward functions by computing reward values for transitions that may not be possible under the transition model of the environment. This is reflected in the visualization by samples comprising the different expectations being dispersed globally over S and/or S'. Our approach in contrast uses a transition model to transform the reward function using approximately in-distribution transitions as illustrated visually by its local sampling in computing the expectations. Both approaches arrive at the unshaped value of zero depicted by the red triangle.

model, two reward functions that behave identically on in-distribution transitions, but differently on out-of-distribution transitions, could justifiably be regarded as different.

However, if these reward functions are learned from data, evaluating them on out-of-distribution transitions can lead to unreliable reward values, introducing errors into the reward distance computed by EPIC. For example, the reward value of a transition in which a home robot teleports across a room is likely to be arbitrarily incorrect, since no similar transition would be observed when the robot interacts with its environment. Because EPIC necessarily evaluates learned reward functions on out-of-distribution data when computing reward distances, these distances can have significant inaccuracies as we show empirically in Section 5.

To address this challenge, we assume access to a transition model of the environment (which may also be learned in practice), and propose Dynamics-Aware Reward Distance (DARD), a new reward distance measure, which builds on EPIC. DARD computes an alternative reward transformation that evaluates reward functions on transitions that are much closer to those observed in the environment. This helps to encourage evaluation of reward functions closer to the distribution of transitions on which they were trained while still providing a distance metric between reward functions that is invariant to potential shaping.

Definition 4.1 (Dynamics-Aware Transformation). *Let $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ be a reward function. Given distributions $\mathcal{D}_\mathcal{S} \in \Delta(\mathcal{S})$ and $\mathcal{D}_\mathcal{A} \in \Delta(\mathcal{A})$ over states and actions, let S be a random variable distributed as $\mathcal{D}_\mathcal{S}$, and A be a random variable distributed as $\mathcal{D}_\mathcal{A}$. Furthermore, given a probabilistic transition model defining a conditional distribution over next states $T(S'|S, A)$, let S' and S'' be random variables distributed as $T(S''|s, A)$ and $T(S''|s', A)$ respectively. Define the dynamics-aware transformation of R as follows:*

$$C_T(R)(s, a, s') = R(s, a, s') + \mathbb{E}[\gamma R(s', A, S'') - R(s, A, S') - \gamma R(S', A, S'')]. \quad (3)$$

By sampling next states from the transition model conditioning on the current state (either s or s'), this transformation is able to evaluate reward models at (s, a, s') transitions that are closer to

their training distribution. In the case of the term $\mathbb{E}[R(S', A, S'')]$, the transitions evaluated are not perfectly in-distribution with respect to T. This is because S'' is distributed conditionally on the original s' as opposed to the random variable S'. These transitions are nevertheless much closer to physically realizable than those sampled in EPIC. In Section 5 we show that learned reward functions are relatively insensitive to these slight errors in practice. We select $\mathcal{D}_{\mathcal{A}}$ to densely cover the space of possible actions. We do this because during policy optimization, policies may select a wide range of possible actions, resulting in evaluating learned reward functions on this same distribution of actions. See Figure 1 for a visualization of our dynamics-aware transformation. Informally, this operation normalizes the reward values of a transition (s, a, s') based on the reward values of nearby transitions sampled from the transition model. This normalization allows for a comparison between reward functions that is invariant to potential shaping.

Proposition 2 (The dynamics-aware transformed reward is invariant to shaping). *Let $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ be a reward function, and $\Phi : \mathcal{S} \to \mathbb{R}$ a state potential function. Let $\gamma \in [0, 1]$ be a discount factor, and $\mathcal{D}_{\mathcal{S}} \in \Delta(\mathcal{S})$ and $\mathcal{D}_{\mathcal{A}} \in \Delta(\mathcal{A})$ be distributions over states and actions, and $T : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ be a conditional distribution over next states. Let R' denote R shaped by $\Phi : R'(s, a, s') = R(s, a, s') + \gamma\Phi(s') - \Phi(s)$. Then the transition-relative transformations of R' and R are equal: $C_T(R') = C_T(R)$.*

Proof: See Section A.3.

Definition 4.2 (DARD Distance Measure). *Let S, A, S' be random variables jointly following some coverage transition distribution, and let T be the transition model of the corresponding environment. We define the DARD pseudometric between rewards R_A and R_B as follows:*

$$D_{DARD}(R_A, R_B) = D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_B)(S, A, S')\Big). \tag{4}$$

We prove that the above distance measure is a pseudometric in Section A.3.

The key insight behind DARD is that we can use knowledge of transition dynamics to define a distance measure between reward functions that only evaluates those functions at realizable transitions. Though, unlike EPIC, DARD assumes knowledge of transition dynamics and that these dynamics will remain similar during deployment, DARD uses these additional assumptions to produce significantly more accurate and predictive distances between learned reward functions in practice.

5 EXPERIMENTS

In experiments we evaluate the following hypotheses: **H1**: EPIC is a poor predictor of policy return for learned reward functions due to its out-of-distribution evaluation of these reward functions. **H2**: DARD is predictive of policy return even for learned reward models, while maintaining EPIC's invariance to reward shaping. **H3**: DARD is predictive of policy performance across diverse coverage distributions. We test these hypotheses by computing each metric across a set of reward models, and then evaluate a policy trained on each reward model against a ground truth reward function through on-policy evaluation. We perform these steps across two environments as described next.

5.1 EXPERIMENTAL SETUP

Environments We evaluate DARD in two environments. We first study the Bouncing Balls environment, which requires an agent to navigate from a random initial position to a random goal position while avoiding a set of balls randomly bouncing around the scene. This environment captures elements of real-world, physical environments with multiple interacting agents, as is the case, for example, in autonomous driving. In these types of environments, EPIC samples transitions in a manner such that agents teleport around the scene, causing issues for learned reward models. The second environment is adapted from the Reacher environment from OpenAI Gym (Brockman et al., 2016). This environment captures aspects of robotic manipulation tasks where arbitrary changes in joint configuration between s and s' can cause issues for learned reward models. Videos illustrating both environments can be found at `https://sites.google.com/view/dard-paper`.

Coverage Distributions In order to compute reward distances for DARD, we must sample transitions from the environments. In the experiments we consider two coverage distributions. The first is

the distribution induced by a policy that takes actions uniformly at random across magnitude bounds (denoted by π_{uni}). The second is the distribution over transitions of an expert policy π^*, which we learn in both environments using Proximal Policy Optimization (PPO) Schulman et al. (2017).

Action Sampling and Transition Models   Both environments have a 2D, continuous action space. DARD samples actions from these spaces (i.e., defines $\mathcal{D}_A$) by defining an uniformly-spaced, 2D grid of action values within magnitude bounds.

The transition model for the Bouncing Balls environment is a constant velocity model that deterministically samples next states conditional on each sampled action. For the Reacher environment, we use the underlying MuJoCo simulator (Todorov et al., 2012) as the transition model, again deterministically sampling next states.

Reward Models   For each environment, we define or learn the following reward models:

GROUND TRUTH: The reward function against which we perform on-policy evaluation. In both environments, this is a goal-based reward given when the agent position is within some range of the goal location. The Reacher environment also contains additive terms penalizing distance from the goal and large action magnitudes.

SHAPED: The ground truth reward function, shaped by a potential function. In both environments, we use a potential shaping based on the distance to the goal location. In the Bouncing Balls environment, we take the difference in the square root of the distance to goal (due to the large distance values). In the Reacher environment we use the difference of distances from the end effector to goal directly.

FEASIBILITY: A manually-defined reward model for the Bouncing Balls environment, which returns the shaped reward function when evaluated with a dynamically-feasible transition, and returns unit Gaussian noise otherwise. This serves as a sanity check to illustrate that EPIC performs poorly on models that exhibit inaccurate reward values on OOD transitions.

REGRESS: A learned model trained via regression to the *shaped* reward model. We regress the shaped reward function because otherwise the metrics do not need to account for shaping (see A.2.1 for an example). Although simple, this method is used in practice in cases where people manually label reward functions (Cabi et al., 2019), and was used as a baseline in Christiano et al. (2017) ("target" method, section 3.3).

REGRESS OUT-OF-DISTRIBUTION: A model trained similarly to REGRESS, except that it is trained "out-of-distribution" in the sense that during training it samples (a, s') pairs randomly from the dataset such that its training distribution matches the evaluation distribution of EPIC.

PREFERENCES: A reward model learned using preference comparisons, similar to the approach from Christiano et al. (2017). We synthesize preference labels based on ground-truth return.

All learned models are fully-connected neural networks. In the Bouncing Balls environment, the input to the network is a specific set of features designed to be susceptible to OOD issues (a squared distance is computed between s and s' as one of the features). For the Reacher environment, we concatenate s, a, and s' as in the learned-reward experiments in Gleave et al. (2020).

Baselines   We compare with two baseline methods. First, we compare with EPIC. Second, we compare with a simple calculation of the Pearson distance (D_p). We include this baseline in order to assess the extent to which reward shaping is an issue that needs to be accounted for in comparing rewards (see section A.2.1 for additional motivation).

5.2   RESULTS AND DISCUSSION

Table 1 summarizes the experimental results, which provide support for **H1** across both environments. We first note as a sanity check that EPIC assigns large distances between GROUND TRUTH and FEASIBILITY. This demonstrates EPIC's tendency to assign large distances to reward functions that are equivalent when assuming a fixed transition model, but different under an arbitrary transition model. This behavior manifests with learned models in practice due to EPIC's OOD evaluation of those models. For example, in both environments EPIC assigns large distances to the REGRESS

Table 1: Results for the Bouncing Balls (**Top**) and Reacher (**Bottom**) environments. **Center**: For each reward model, we compute each distance metric $\times 1000$ from GROUND TRUTH (GT). The coverage distribution is indicated by the policy (π_{uni} corresponding to the distribution resulting from uniformly random actions, π^* to that from expert actions). **Right**: The average episode return and its standard error of the policy trained on the corresponding reward model. Values are averaged over 5 executions of all steps (data collection, reward learning, reward evaluation) across different random seeds (see section A.1.6 for standard errors of distances). Distance values that are inversely correlated with episode return are desirable (i.e., *increasing* distance within a column should correspond with *decreasing* episode return). Additionally, for hand-designed models that are equivalent to GT (SHAPING, FEASIBILITY), and for well-fit learned models (REGRESS), lower is better. Learned models are fit to SHAPED, and may produce higher episode return than those fit to GT as a result.

| Reward Function | 1000 x D_{DARD} | | 1000 x D_{EPIC} | | 1000 x D_p | | Episode Return |
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	10.5 ± 0.50
SHAPING	0.00	0.00	0.00	0.00	640	603	12.2 ± 0.12
FEASIBILITY	0.00	0.00	639	604	640	603	12.0 ± 0.15
REGRESS OOD	13.7	10.7	12.8	7.10	640	604	12.1 ± 0.08
REGRESS	32.3	14.4	692	620	640	604	11.7 ± 0.31
PREF	112	57.3	692	632	665	638	10.9 ± 0.16

| Reward Function | 1000 x D_{DARD} | | 1000 x D_{EPIC} | | 1000 x D_p | | Episode Return |
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	75.3 ± 2.63
SHAPING	0.00	0.00	0.00	0.00	367	81.8	78.6 ± 2.30
REGRESS OOD	27.5	113	24.7	131	368	114	84.3 ± 0.50
REGRESS	49.9	171	184	216	368	120	81.3 ± 2.25
PREF	63.1	241	157	214	367	144	29.1 ± 4.89

model when, based on policy performance, we see that it is quite similar to the ground truth (disregarding shaping). This results from EPIC's evaluation of these reward models with OOD transitions, which is illustrated by the fact that the metric is more much predictive of on-policy performance on the REGRESS OOD model (which does not suffer from OOD evaluation issues). Perhaps most importantly, EPIC fails to be predictive of episode return when comparing learned models. For example, in the Reacher environment, the metric assigns a lower distance to PREF than REGRESS despite the lower episode returns of PREF.

The results from both environments also support **H2**. In the Bouncing Balls environment, DARD gives low distances for the well-fit models (FEASIBILITY, REGRESS, REGRESS OOD) as a result of only evaluating them in their training distribution. In the Reacher environment, DARD exhibits a gap between REGRESS and REGRESS OOD, which indicates that the algorithm's evaluation of the reward model on slightly out-of-distribution transitions does hurt performance. Nevertheless, on the reward models that can be learned in practice (REGRESS, PREF) DARD produces distances that are more predictive of episode return compared to baseline methods.

Finally, the results also demonstrate that DARD is predictive of episode return across coverage distributions (**H3**). DARD is sensitive to the choice of coverage distribution because the transitions the metric samples are tightly grouped around this distribution. This is reflected in the different distance scales between π_{uni} and π^*. Nevertheless, the relative value of DARD within a sampling distribution is still predictive of episode return. For example, the metric maintains a consistent ordering of the models across π_{uni} and π^* in both environments.

In our experiments, we discovered that DARD is poorly suited for reward comparison in environments where nearby transitions exclusively have similar reward values. This is the case, for example, in robotic domains with small timesteps and in which a smooth reward function is used (such as negative distance to the goal). We illustrate this behavior and explain why it occurs in section A.2.1 with

experiments on the Point Maze environment used by Gleave et al. (2020). In short, because DARD performs reward comparisons between transitions relative to a transition model, if all the transitions it considers (across all possible actions) have nearly-identical reward values, it can be sensitive to noise in the reward model. For this reason, DARD should be used in environments for which, at least for some parts of the state-action space, nearby transitions yield well-differentiated reward values.

Overall, these experiments demonstrate that in situations where we have confidence the transition model will not change significantly, as is the case in many physical settings, DARD allows for comparing *learned* reward functions with other reward functions without policy optimization.

6 CONCLUSION

The ability to reliably compare reward functions is a critical tool for ensuring that intelligent systems have objectives that are aligned with human intentions. The typical approach to comparing reward functions, which involves learning policies on them, conflates errors in the reward with errors in policy optimization. We present Dynamics-Aware Reward Distance (DARD), a pseudometric that allows for comparing rewards directly while being invariant to reward shaping. DARD uses knowledge of the transition dynamics to avoid evaluating *learned* reward functions far outside their training distribution. Experiments suggest that for environments where we can assume the transition dynamics will not change significantly between evaluation and deployment time that DARD reliably predicts policy performance associated with a reward function, even learned ones, without learning policies and without requiring online environment interaction.

There are a number of exciting areas for future work. First, DARD could be used to define benchmarks for evaluating reward learning methods (for example in autonomous driving). Second, DARD could also be applied in conjunction with learned transition models, for example in visual domains where OOD evaluation issues are likely particularly challenging to overcome. Last, we are interested in investigating whether the rapid reward evaluation provided by DARD can be used to enable contrastive learning of reward functions.

7 REPRODUCIBILITY STATEMENT

We have attempted to make the experimental results easily reproducible by providing the following: first, source code necessary to reproduce results is available in the supplementary material. Second, the software for this research is designed to allow for reproducing the results in the main body of the text through a single program execution. Third, results are computed over five random seeds and standard error values are reported in section A.1.6 to provide reasonable bounds within which reproduced results should fall. Fourth, we have attempted to provide extensive details regarding the experimental setup in appendix A.1.

8 ETHICS STATEMENT

The ability to reliably and efficiently evaluate reward functions without executing policies in the environment has the potential to ensure that AI systems will exhibit behavior that is aligned with the objective of the system designer before risking deploying these systems for making safety critical decisions. This has the potential to facilitate the application of reinforcement learning algorithms in settings in which this might otherwise be too risky, such as healthcare, finance, and robotics.

REFERENCES

Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *International Conference on Machine Learning*, pp. 1, 2004.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. OpenAI Gym. *arXiv preprint arXiv:1606.01540*, 2016.

Serkan Cabi, Sergio Gómez Colmenarejo, Alexander Novikov, Ksenia Konyushkova, Scott Reed, Rae Jeong, Konrad Zolna, Yusuf Aytar, David Budden, Mel Vecerik, et al. Scaling data-

driven robotics with reward sketching and batch reinforcement learning. *arXiv preprint arXiv:1909.12200*, 2019.

Paul Christiano, Jan Leike, Tom B Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *arXiv preprint arXiv:1706.03741*, 2017.

Miroslav Dudik, John Langford, and Lihong Li. Doubly robust policy evaluation and learning. *arXiv preprint arXiv:1103.4601*, 2011.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adversarial inverse reinforcement learning. *arXiv preprint arXiv:1710.11248*, 2017.

Adam Gleave, Michael Dennis, Shane Legg, Stuart Russell, and Jan Leike. Quantifying differences in reward functions. *arXiv preprint arXiv:2006.13900*, 2020.

Jessica E Holland, Mykel J Kochenderfer, and Wesley A Olson. Optimizing the next generation collision avoidance system for safe, suitable, and acceptable operational performance. *Air Traffic Control Quarterly*, 21(3):275–297, 2013.

Alex Irpan, Kanishka Rao, Konstantinos Bousmalis, Chris Harris, Julian Ibarz, and Sergey Levine. Off-policy evaluation via off-policy classification. *arXiv preprint arXiv:1906.01624*, 2019.

Nan Jiang and Lihong Li. Doubly robust off-policy value evaluation for reinforcement learning. *arXiv preprint arXiv:1511.03722*, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

W Bradley Knox, Alessandro Allievi, Holger Banzhaf, Felix Schmitt, and Peter Stone. Reward (mis)design for autonomous driving. *arXiv preprint arXiv:2104.13906*, 2021.

Hoang M. Le, Cameron Voloshin, and Yisong Yue. Batch policy learning under constraints. *arXiv preprint arXiv:1903.08738*, 2019.

Donghun Lee, Srivatsan Srinivasan, and Finale Doshi-Velez. Truly batch apprenticeship learning with deep successor features. *arXiv preprint arXiv:1903.10077*, 2019.

Eric Liang, Richard Liaw, Robert Nishihara, Philipp Moritz, Roy Fox, Ken Goldberg, Joseph Gonzalez, Michael Jordan, and Ion Stoica. Rllib: Abstractions for distributed reinforcement learning. In *International Conference on Machine Learning*, pp. 3053–3062. PMLR, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing Atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *International Conference on Machine Learning*, volume 99, pp. 278–287, 1999.

Andrew Y Ng, H Jin Kim, Michael I Jordan, Shankar Sastry, and Shiv Ballianda. Autonomous helicopter flight via reinforcement learning. In *Neural Information Processing Systems*, volume 16. Citeseer, 2003.

Cosmin Paduraru. *Off-policy evaluation in Markov decision processes*. PhD thesis, McGill University, 2013.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Neural Information Processing Systems*, 32:8026–8037, 2019.

Doina Precup, Richard S. Sutton, and Satinder P. Singh. Eligibility traces for off-policy policy evaluation. In *International Conference on Machine Learning*, pp. 759–766, San Francisco, CA, USA, 2000. Morgan Kaufmann Publishers Inc.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of Go without human knowledge. *nature*, 550(7676):354–359, 2017.

Gerald Tesauro. Temporal difference learning and TD-Gammon. *Communications of the ACM*, 38 (3):58–68, 1995.

Devinder Thapa, In-Sung Jung, and Gi-Nam Wang. *Agent Based Decision Support System Using Reinforcement Learning Under Emergency Circumstances*, volume 3610. 2005.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Cameron Voloshin, Hoang M. Le, Nan Jiang, and Yisong Yue. Empirical study of off-policy policy evaluation for reinforcement learning. *arXiv preprint arXiv:1911.06854*, 2020.

Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, Anind K Dey, et al. Maximum entropy inverse reinforcement learning. In *AAAI Conference on Artificial Intelligence*, volume 8, pp. 1433–1438. Chicago, IL, USA, 2008.

A   SUPPLEMENTARY MATERIAL

A.1   EXPERIMENTAL DETAILS

The following sub-sections provide details on the different components involved in the experiments.

A.1.1   ENVIRONMENTS

Bouncing Balls Environment   This is a custom environment with traits of multi-agent navigation environments such as autonomous driving. The agent attempts to navigate to a random goal location while avoiding a set of balls (other agents) bouncing around the scene. The state consists of the position and velocity of the balls (the agent included), as well as the goal location. The action space is a 2D continuous space of accelerations between $[-5, 5]$ to apply to the agent state. The transition function applies the agent accelerations to its state, while the other agents apply random accelerations sampled from a zero-mean, low variance Gaussian distribution. The reward function gives a positive value once the agent is within some distance of the goal, which results in the agent and goal position being randomly moved. This environment executes for a fixed horizon of 400 timesteps to approximate a continuing, infinite horizon MDP. We make the environment approximately continuing in order to ensure that S and S' are distributed identically as is required by EPIC. Sampling S and S' from their marginal distributions in the dataset results in transitions where the agents in s have completely different positions and velocities as in s', an issue that would be encountered in real-world multi-agent settings.

Reacher Environment   This environment is adapted from the Reacher environment from OpenAI gym (Brockman et al., 2016). We adapt the environment in two ways. First, we add a goal-based reward component. Second, we increase the timesteps between states to 5 from an original 2. We make both these changes so that the rewards of nearby transitions are sufficiently differentiated (see A.2.1 for detailed motivation).

A.1.2   POLICY LEARNING

We used the RLlib (Liang et al., 2018) implementation of Proximal Policy Optimization (PPO) for learning control policies (Schulman et al., 2017). Parameters are provided in table 2.

Parameter	Value
Discount γ	0.95
GAE λ	0.95
# Timesteps Per Rollout	64
Train Epochs Per Rollout	2
# Minibatches Per Epoch	10
Entropy Coefficient	0.01
PPO Clip Range	0.2
Learning Rate	5×10^{-4}
Hidden Layer Sizes.	[256,256]
# Workers	8
# Environments Per Worker	40
Total Timesteps	8M$^{\text{BB}}$, 10M$^{\text{R}}$

Table 2: PPO parameters. Superscripts indicate Bouncing Balls (BB) or Reacher (R) environments.

A.1.3   DATA COLLECTION

We collect *sets* of datasets for use in reward learning and evaluation. Each set contains three sub-datasets for (i) reward model training, (ii) reward model validation, and (iii) reward evaluation. We collect these dataset sets using two policies. The first policy (π_{uni}) yields a uniform distribution on the action space. The second policy is an expert (π^*) trained as described in A.1.2. Table 3 gives the sizes of these datasets, which were set such that the validation and train losses were similar during reward learning.

Environment	Reward Learning Train	Reward Learning Validation	Reward Evaluation
Bouncing Balls	2,000,000	500,000	500,000
Reacher	4,000,000	1,000,000	1,000,000

Table 3: The sizes of the datasets used for reward learning and evaluation for each environment.

A.1.4 REWARD LEARNING

Three methods of learning reward functions were considered in this research: (i) direct regression of per-timestep rewards (REGRESS), (ii) regression on a shuffled dataset matching the evaluation distribution of EPIC (REGRESS OOD), and (iii) preference-based learning of rewards. These methods each fit a fully-connected neural network, and their model and training hyperparameters are provided in table 4. We used early stopping based on validation loss for all models to determine the number of training epochs.

For the Bouncing Balls environment we input into the model a set of manually extracted features including distance of the agent to the goal in the current and next state, the difference in distances between states, an indicator of whether the goal has been reached, squared differences in position of other agents, and others. Features involving squared distances are what make these model susceptible to OOD issues. For the Reacher environment we concatenate the state, action, and next state, and pass that directly into the model. In either case, these features are normalized by subtracting their mean and dividing by their standard deviation.

Parameter	Value
Batch Size	2048
Hidden Layer Sizes	[256, 256]
Activation Function	tanh
Learning Rate	2×10^{-4}
Gradient Clip	1.0
Discount γ	0.95
Optimizer	Adam (Kingma & Ba (2014))
Reward Regularization[p]	0.01^{BB}, 0.001^{R}
Trajectory Length[p]	25^{BB}, 15^{R}
# Random Pairs[OOD]	10^{BB}, 5^{R}

Table 4: Parameters for reward learning algorithms. For information on datasets used for training see section A.1.3. Superscripts indicate parameters specific to preference learning (p), OOD regression (OOD), Bouncing Balls environment (BB), Reacher environment (R).

A.1.5 REWARD EVALUATION

EPIC   We compute the sample-based approximation of EPIC described in section A.1.1 of Gleave et al. (2020). Table 5 gives the parameters we use in computing EPIC. We use the same values of N_V and N_M as Gleave et al. (2020), though use fewer seeds. In our case each seed represents a full execution of the pipeline (data collection, reward model training, reward evaluation), whereas in Gleave et al. (2020) it represents different sub-samplings of a single dataset. We take this approach in order to assess sensitivity to randomness in the data collection and reward learning processes.

Parameter	Value
State Distribution $\mathcal{D}_{\mathcal{S}}$	Marginalized from $\mathcal{D}$
State Distribution $\mathcal{D}_{\mathcal{A}}$	Marginalized from $\mathcal{D}$
# Seeds	5
Samples N_V	32768
Mean Samples N_M	32768
Discount γ	0.95

Table 5: EPIC parameters.

DARD Similarly to EPIC, we compute a sample-based approximation of DARD in the experiments. We sample a batch B_V of N_V (s, a, s') transitions. For computing the expectations $\mathbb{E}[R(s, A, S')]$ and $\mathbb{E}[R(s', A, S'')]$ we sample N_A actions u using a sampling policy (described in Appendix A.1.3). We then sample N_T samples of S' or S'', x' and x'', conditional on s or s' and u. For the last expectation, $\mathbb{E}[R(S', A, S'')]$, we sample actions and next states similarly for S', but repeat the process for S'', overall computing the mean over $O((N_A N_T)^2)$ transitions. We compute the dynamics-aware transformation (definition 3) for each transition by averaging over these sampled actions and next states:

$$C_T(R)(s, a, s') = R(s, a, s') + \mathbb{E}[\gamma R(s', A, S'') - R(s, A, S') - \gamma R(S', A, S'')] \quad (5)$$

$$\approx R(s, a, s') + \frac{\gamma}{N_A N_T} \sum_{i=0}^{N_A} \sum_{j=0}^{N_T} R(s', u_i, x''_j)$$

$$- \frac{1}{N_A N_T} \sum_{i=0}^{N_A} \sum_{j=0}^{N_T} R(s, u_i, x'_j) \quad (6)$$

$$- \frac{\gamma}{N_A^2 N_T^2} \sum_{i=0}^{N_A} \sum_{j=0}^{N_T} \sum_{k=0}^{N_A} \sum_{l=0}^{N_T} R(x'_{ij}, u_{kl}, x''_{kl}).$$

Overall this yields an $O(N_V N_A^2 N_T^2)$ algorithm. In our experiments the transition model is assumed to be deterministic, making $N_T = 1$. The actions are sampled from the N-dimensional action space by taking the cross product of linearly-sampled values for each dimension. For example, in the Bouncing Balls environment, we sample 8 actions linearly between $[-5, 5]$ for each of the two dimensions, overall yielding $N_A = 64$. The complexity of computing $\mathbb{E}[R(S', A, S'')]$ could be reduced by instead sampling N_A actions and N_T transitions for each of x' and x''.

For the Bouncing Balls environment, we approximate the transition function with a constant velocity model for all agents, implemented in Pytorch and executed on the GPU (Paszke et al., 2019). For the Reacher environment, we use the ground truth simulator, which we execute in parallel across 8 cores. See table 6 for a summary of the DARD parameters used in the experiments.

Parameter	Value
# Seeds	5
Samples N_V	100,000
Action Samples N_A	64^{BB}, 16^{R}
Transition Samples N_T	1
Discount γ	0.95

Table 6: DARD parameters. Superscripts indicate parameters specific to the Bouncing Balls (BB) or Reacher (R) environments.

Policy Evaluation We compute average episode returns of policies trained on both manually-defined and learned reward models. Training parameters are the same as those used for learning the

expert policy (see Table 2). We evaluate policies for 1 million steps in the respective environment, and report the average, undiscounted episode return. Similarly to the other reward evaluation steps, we train one policy for each random seed (of which there are 5).

A.1.6 STANDARD ERROR OF RESULTS

Tables 7 and 8 provide the standard errors in the estimates of the mean distances and episode returns, computed over 5 random seeds.

Reward Function	1000 x D_{DARD}		1000 x D_{EPIC}		1000 x D_p		Episode Return
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	0.50
SHAPING	0.00	0.00	0.00	0.00	1.51	0.80	0.12
FEASIBILITY	0.00	0.00	0.56	1.11	1.51	0.80	0.15
REGRESS OOD	1.16	1.19	0.72	0.32	1.53	0.90	0.08
REGRESS	3.14	1.59	1.53	10.9	1.54	0.90	0.31
PREF	9.66	5.08	1.16	7.55	1.39	1.91	0.16

Table 7: Standard error values for bouncing balls environment.

Reward Function	1000 x D_{DARD}		1000 x D_{EPIC}		1000 x D_p		Episode Return
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	2.63
SHAPING	0.00	0.00	0.00	0.00	0.76	1.88	2.30
REGRESS OOD	0.96	15.6	1.16	56.8	0.77	18.6	0.50
REGRESS	4.25	15.2	17.8	43.9	0.73	18.0	2.25
PREF	3.14	13.8	10.7	41.7	0.69	14.5	4.89

Table 8: Standard error values for Reacher environment.

A.2 ADDITIONAL EXPERIMENTS

A.2.1 POINT MAZE EXPERIMENTS

In this section we present results for the Point Maze environment considered in Gleave et al. (2020). These results illustrate a disadvantage of DARD. As discussed in section 5, because DARD performs reward comparisons between transitions relative to a transition model, if all the transitions it considers (across all possible actions) have near-identical reward values, it can be sensitive to noise in the reward model. The Point Maze environment fits this description, and DARD performs poorly on it as a result (see table 9). We provide evidence for the hypothesis that the lack of reward-differentiated transitions causes this poor performance by also providing results for an adapted Point Maze environment, which is identical to the original except that we increase the time difference between timesteps by a factor of 5 (such that nearby transitions yield different reward values). In this adapted case, DARD and EPIC distances are significantly closer than in the original environment.

Two additional traits of the environment are relevant. First, the ground truth reward is only a function of the current state and action, but not the next state. As a result, learned reward models tend to ignore the next state, which minimizes the effect of the OOD reward evaluations performed by EPIC. Second, in these experiments (unlike those in section 5) we train reward models to fit the ground truth reward model (as opposed to a shaped version of it). We do this to be consistent with the experiments provided in Gleave et al. (2020); however, this results in the learned reward models exhibiting little shaping (as illustrated by the low distance values of $\mathcal{D}_p$). This is a property of the reward learning algorithm and specific environment in which it is applied, but learned reward models may exhibit significant shaping in general (Fu et al., 2017).

Reward Function	1000 x D_{DARD}		1000 x D_{EPIC}		1000 x D_p		Episode Return
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	-4.73 ± 0.48
REGRESS	195	480	14.8	34.2	6.59	32.1	-8.02 ± 0.95

Reward Function	1000 x D_{DARD}		1000 x D_{EPIC}		1000 x D_p		Episode Return
	π_{uni}	π^*	π_{uni}	π^*	π_{uni}	π^*	
GT	0.00	0.00	0.00	0.00	0.00	0.00	-2.1 ± 0.06
REGRESS	16.3	47.5	6.34	25.4	6.19	20.2	-2.59 ± 0.10

Table 9: **Top**: Results for the original Point Maze environment. **Bottom**: Results for the Point Maze environment when using a larger timestep. See the caption of table 1 for how to interpret these results. DARD distances are much closer to those of EPIC in the large-timestep case, indicating that the differences in rewards assigned to nearby transitions has a significant impact on DARD performance. Parameters used for reward learning match those of Gleave et al. (2020). We were unable to exactly reproduce the episode returns of the policies trained on learned reward models. Note that in the larger-timestep case the episode returns will differ due to the change in timestep.

A.3 PROOFS

A.3.1 COMPARING LEARNED REWARD FUNCTIONS

Proposition 3 (The dynamics-aware transformed reward is invariant to shaping). *Let $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ be a reward function, and $\Phi : \mathcal{S} \to \mathbb{R}$ a potential function. Let $\gamma \in [0, 1]$ be a discount rate, and $\mathcal{D}_{\mathcal{S}} \in \Delta(\mathcal{S})$ and $\mathcal{D}_{\mathcal{A}} \in \Delta(\mathcal{A})$ be distributions over states and actions, and $T : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ be a conditional distribution over next states. Let R' denote R shaped by $\Phi : R'(s, a, s') = R(s, a, s') + \gamma\Phi(s') - \Phi(s)$. Then the dynamics-aware transformations of R' and R are equal: $C_T(R') = C_T(R)$.*

Proof. Let $s, a, s' \in \mathcal{S} \times \mathcal{A} \times \mathcal{S}$. Then by substituting in the definition of R' and using linearity of expectation:

$$C_T(R')(s, a, s') \triangleq R'(s, a, s') + \mathbb{E}[\gamma R'(s', A, S'') - R'(s, A, S') - \gamma R'(S', A, S'')] \quad (7)$$

$$= (R(s, a, s') + \gamma\Phi(s') - \Phi) \quad (8)$$
$$+ \mathbb{E}[\gamma R(s', A, S'') + \gamma^2\Phi(S'') - \gamma\Phi(s')]$$
$$- \mathbb{E}[R(s, A, S') + \gamma\Phi(S') - \Phi(s)]$$
$$- \mathbb{E}[\gamma R(S', A, S'') + \gamma^2\Phi(S'') - \gamma\Phi(S')]$$

$$= R(s, a, s') + \mathbb{E}[\gamma R(s', A, S'') - R(s, A, S') - \gamma R'(S', A, S'')] \quad (9)$$
$$+ (\gamma\Phi(s') - \Phi(s)) - \mathbb{E}[\gamma\Phi(s') - \Phi(s)]$$
$$+ \mathbb{E}[\gamma^2\Phi(S'') - \gamma\Phi(S')] - \mathbb{E}[\gamma^2\Phi(S'') - \gamma\Phi(S')]$$

$$= R(s, a, s') + \mathbb{E}[\gamma R(s', A, S'') - R(s, A, S') - \gamma R'(S', A, S'')] \quad (10)$$

$$= C_T(R)(s, a, s'). \quad (11)$$

$\square$

Lemma A.1 (The Pearson distance $\mathcal{D}_\rho$ is a pseudometric). *(Lemma 4.5 from Gleave et al. (2020)) Namely, for $\mathcal{X}$ a set of random variables, $\mathcal{D}_\rho$ satisfies the following properties:*
   Identity: *$\mathcal{D}_\rho(X, X) = 0 \, \forall X \in \mathcal{X}$,*
   Symmetry: *$\mathcal{D}_\rho(X, Y)\mathcal{D}_\rho(Y, X) \, \forall X, Y \in \mathcal{X}$, and*
   Triangle Inequality: *$\mathcal{D}_\rho(X, Z) \leq \mathcal{D}_\rho(X, Y) + \mathcal{D}_\rho(Y, Z) \, \forall X, Y, Z \in \mathcal{X}$.*

Proof: See Gleave et al. (2020)

Proposition 4 (The DARD distance metric is a pseudometric). *Let S, A, S' be random variables jointly following some coverage transition distribution, and let T be the transition model of the corresponding environment. We define the DARD pseudometric between rewards R_A and R_B as follows:*

$$D_{DARD}(R_A, R_B) = D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_B)(S, A, S')\Big) \tag{12}$$

Proof. This proof closely follows the proof of Theorem 4.7 from Gleave et al. (2020). Namely, the result follows from direct application of Lemma A.1.

Let R_A, R_B, and R_C be reward functions mapping from transitions $\mathcal{S} \times \mathcal{A} \times \mathcal{S}$ to real numbers $\mathbb{R}$.

Identity: It immediately follows that
$D_{\text{DARD}}(R_A, R_A) = D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_A)(S, A, S')\Big) = 0$ since D_ρ is a pseudometric, $D_\rho(X, X) = 0 \,\forall X \in \mathcal{X}$.

Symmetry: This again immediately follows from the fact that D_ρ is a pseudometric. We have that:

$$D_{\text{DARD}}(R_A, R_B) = D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_B)(S, A, S')\Big) \tag{13}$$

$$= D_\rho\Big(C_T(R_B)(S, A, S'), C_T(R_A)(S, A, S')\Big) \tag{14}$$

$$= D_{\text{DARD}}(R_B, R_A) \tag{15}$$

since $D_\rho(X, Y) = D_\rho(Y, X)$ because D_ρ is a pseudometric.

Triangle Inequality: This again immediately follows from the fact that D_ρ is a pseudometric. We have that:

$$D_{\text{DARD}}(R_A, R_C) = D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_C)(S, A, S')\Big) \tag{16}$$

$$\leq D_\rho\Big(C_T(R_A)(S, A, S'), C_T(R_B)(S, A, S')\Big) \tag{17}$$

$$+ D_\rho\Big(C_T(R_B)(S, A, S'), C_T(R_C)(S, A, S')\Big) \tag{18}$$

$$= D_{\text{DARD}}(R_A, R_B) + D_{\text{DARD}}(R_B, R_C) \tag{19}$$

since $D_\rho(X, Z) \leq D_\rho(X, Y) + D_\rho(Y, Z)$ because D_ρ is a pseudometric. $\qquad\square$