Dataset Inference for Self-Supervised Models

Abstract

Self-supervised models are increasingly prevalent in machine learning (ML) since they reduce the need for expensively labeled data. Because of their versatility in downstream applications, they are increasingly used as a service exposed via public APIs. At the same time, these encoder models are particularly vulnerable to model stealing attacks due to the high dimensionality of vector representations they output. Yet, encoders remain undefended: existing mitigation strategies for stealing attacks focus on supervised learning. We introduce a new dataset inference defense, which uses the private training set of the victim encoder model to attribute its ownership in the event of stealing. The intuition is that the log-likelihood of an encoder's output representations is higher on the victim's training data than on test data if it is stolen from the victim, but not if it is independently trained. We compute this log-likelihood using density estimation models. As part of our evaluation, we also propose to measure the fidelity of stolen encoders without involving downstream tasks and to quantify the effectiveness of the theft detection; instead, we leverage mutual information and distance measurements. Our extensive empirical results in the vision domain demonstrate that dataset inference is a promising direction for defending self-supervised models against model stealing.

1 Introduction

The self-supervised learning (SSL) paradigm enables pre-training models with unlabeled data to learn generally useful domain knowledge and then transfer the knowledge to solve specific downstream tasks. The ability to learn from unlabeled data alleviates the high costs of labeling large datasets [23], and the transfer learning setup reduces the computational costs of retraining. These advantages have made SSL increasingly popular [20] in domains like vision [5], language [12], and bioinformatics [27].

Recently, commercial service providers like Cohere [1] and OpenAI [2]began offering paid query access to trained SSL encoders over public APIs. This exposes the encoders to black-box extraction attacks, *i.e.,* model stealing. In a model stealing attack, an attacker aims to train an approximate copy of a victim model by submitting carefully chosen queries and observing the victim's outputs. The high costs of data collection, preprocessing and model training make encoders valuable targets for stealing. For example, the training data of CLIP includes 400 million image and text pairs [36], while computation costs of training a large language model can exceed one million USD [40]. The threat of model stealing in SSL is real: researchers have demonstrated that encoders can be stolen at a fraction of the victim's training cost [14, 38]. Yet, most current defenses are designed for supervised models [15, 22, 34] and cannot be directly applied to encoders [14].

Dataset inference [29] is a state-of-the-art defense against model stealing in the supervised learning setting. The defense provides ownership resolution: it enables the model owner to make a strong statistical claim that a given model is a stolen copy of their own model by showing that this model is derivative of their own private training data. Dataset inference does not require retraining or overfitting the model to any form of explicit watermark [4] and has been shown to resist attacks from

Figure 1: **Dataset Inference on Encoders.** ❶ Victim trains encoder f_v using private training data D_P.
❷ Adversary steals f_v: submit queries from dataset D_S and obtain representations (denoted by h_{D_S}) to train
the stolen encoder f_s. ❸ Arbitrator trains density estimators: divide D_P into non-overlapping partitions D_{P1}
and D_{P2}, and train density estimators $\mathcal{E}_v$, $\mathcal{E}_s$ and $\mathcal{E}_i$ using the representations of f_v, f_s, f_i on D_{P2}, respectively.
❹ Arbitrator performs dataset inference: apply $\mathcal{E}_v$, $\mathcal{E}_s$ and $\mathcal{E}_i$ on the representations of D_{P1} and D_N of each
encoder. For the victim and stolen encoders, the log-likelihood of the representations of D_{P1} is significantly
higher than D_N.

adaptive adversaries [29]. These properties make the defense particularly attractive for SSL, as large
encoders can be expensive to retrain, and performance is paramount because it carries over to all
downstream tasks. However, the original dataset inference algorithm from [29] cannot be applied
to encoders, because it relies on computing distances between data points and decision boundaries.
These decision boundaries do not exist in encoders since they are trained on unlabeled data.

We introduce a new dataset inference algorithm (Figure 1) to defend against model stealing for
encoders. Our algorithm is suitable for the high-dimensional outputs of SSL encoders and does not
rely on labeled data or decision boundaries. Instead, it relies solely on the private training data of the
victim encoder as a signature. Moreover, our algorithm retains the advantages of dataset inference for
supervised models [29], namely, it does not require retraining or overfitting the model.

Our key intuition is to identify stolen encoders by characterizing differences between an encoder's
representations on its training data vs on unseen test data. The victim encoder and its derivatives,
such as stolen copies, exhibit different behavior on the victim's private training data than on test
data; independently trained encoders do not. These differences exist because encoders overfit to
training data [18, 28]. Although for well-trained encoders the effect is minimal on any given data
point, we show that when aggregated over many training points it provides a statistically strong
signal. To identify the differences, we train a Gaussian Mixture Model (GMM), as an efficient general
approximator, to model the distribution of an encoder's representations of data from its training
domain. We then use the GMMs to predict the log-likelihood of the encoders' representations of the
victim's training set and a test set; derivatives of the victim encoder will have a higher log-likelihood
on the training set than on the test set. We perform experiments on five datasets from the vision
domain and show that we are able to distinguish between stolen and independent encoders even in
cases when adversaries obfuscate the representations from the stolen encoders to hide the theft (*e.g.*,
by shuffling the elements in the representation vectors).

As part of our evaluation, we also introduce new metrics to measure the fidelity of stolen encoders
without involving downstream tasks and to quantify the effectiveness of theft detection. We compute
scores directly on the representations using tools from information theory and distance metrics. These
methods work well because losses used for stealing encoders directly minimize distances between
representations of victim and stolen encoders. Our mutual information score to assess the quality of
the stolen encoders is robust against obfuscations that an adversary might apply to the representations
returned by a stolen encoder. Without any obfuscation, our cosine similarity score shows a clearer
distinction between stolen and independent encoders. Finally, using these metrics, we observe that the
higher the quality of the stolen encoders, the more confident our dataset inference defense becomes.

Our main contributions are as follows:

- We propose a new defense against model stealing attacks on encoders, by combining dataset inference with density estimation models for ownership resolution on unlabeled data.

- We are the first to design new metrics that quantify the quality of stolen encoders, which are derived from the mutual information and distances between representations.

- We evaluate our defense using five datasets from the computer vision domain and show that our defense can successfully identify stolen encoders with a strong statistical significance.

2 Related Work

In model stealing, an adversary queries the victim model, obtains outputs, and uses them to recreate a copy of the victim [42]. This is most commonly performed with black-box access, *e.g.,* via a public API. When stealing encoders in SSL, the goal of an adversary is to extract high-quality embeddings either to train a stolen copy that achieves high performance on downstream tasks, or to obtain faithful replicas of the victim's embeddings on the same inputs. Stolen encoders might be further used for model reselling, backdoor attacks, or membership inference [9].

While most past research on model stealing and defenses focuses on classifiers trained via supervised learning, recent work constructed new attacks that target encoders [14, 38]. The main differences between the attacks in these settings are that the outputs of encoders leak more information due to their higher dimensionalities [38], and the attacks require different loss functions. Inspired by contrastive learning, *Cont-Steal* [38] provides a method of stealing encoders using a loss function based on InfoNCE [5]. SSL extraction [14]—a general Siamese-network-based framework for stealing encoders—leverages losses including mean squared error, InfoNCE, Soft Nearest Neighbor, and Wasserstein distance. The authors empirically show that an adversary can steal an ImageNet victim encoder in less than a fifth of the queries required for training.

Unfortunately, current defenses against model stealing for supervised learning are inadequate for defending encoders, and adjusting them to the specificities of encoders is non-trivial [14]. One line of approach is watermarking [9, 14], where the defender embeds a secret trigger into the victim encoder during training to determine ownership at test time. However, watermarking-based defenses have two significant disadvantages. First, researchers have repeatedly shown that adaptive attackers can remove watermarks without severely affecting model performance [7, 21, 39, 44], *e.g.,* through pruning, fine-tuning, rounding or performing backdoor removal [4]. Second, the watermark must be embedded during training; if a model is already trained, or if a watermark defense needs to be updated, the model must be retrained. This is not practical for large encoders.

Another state-of-the-art defense against model stealing in the supervised setting is dataset inference [29] which addresses these disadvantages. However, the adaptation of dataset inference to encoders is difficult, because (1) the algorithm [29] relies on decision boundaries, which do not exist for encoders; and (2) encoders are less prone to overfitting, which provides the signal for dataset inference [14, 29]. Therefore, naive approaches like computing the loss of representations or distances between train and test sets are ineffective [14]. To overcome these issues, we extract more signals from the representations by estimating their densities for train and test sets, as described in Section 3.

When it comes to comparing signals within representations, prior work has considered measuring the similarity between different representations. This has led to the proposal of various similarity metrics including canonical correlation analysis (CCA) [31], centered kernel alignment (CKA) [24], and the orthogonal Procrustes distance [13], which use methods from linear regression, principal component analysis (PCA), and singular value decomposition (SVD). However, these metrics are very general and complex. They have also been shown to disagree in some cases [13]. Since we can only access the final embeddings from encoders, we design metrics more closely related to our setting.

3 Defense Method

Dataset inference serves as a defense against model stealing. It enables the model owner or a third-party arbitrator to attribute the ownership of a model in the event that it is stolen. The idea is to take advantage of the effects of knowledge from the victim's training set and

to use that as a signature for attributing ownership. Given a well-trained encoder, the effects are small on any single data point; however, when aggregated over many points in the training set, they collectively provide a strong statistical signal for dataset inference. As depicted in Figure 2, for a victim that leverages the private data D_P during training or a stolen copy, we can identify a difference between distributions of the train data's representations h_{D_P} and the test data's representations h_{D_N} while the distributions of these representations from an independent encoder cannot be distinguished. We use this signal to determine whether a model is derivative of the victim's training data, *i.e.,* either directly trained on the data or stolen from the victim.

Figure 2: **Dataset Inference - Intuition.** D_P and D_N come from the same distribution. For independent encoders, their representations h_{D_N} and h_{D_P} are i.i.d. while for victim/stolen encoders, h_{D_N} and h_{D_P} induce different distributions.

To capture the signal, we first partition the victim encoder's training data into two subsets and use one to train Gaussian Mixture Models (GMMs) with the aim of modeling the distribution of representations of data from the encoder's domain. Then, we apply the GMMs to perform dataset inference by measuring the log-likelihood of the encoder's representations of the remaining training data vs some test data (see Figure 1). For the victim encoder or its stolen copies, the log-likelihood of training data representations is significantly higher than the one of test data. We use this to construct statistical t-tests to determine whether a model is stolen, and present our empirical results in Section 5.

3.1 Threat Model

As described in Figure 1, we consider a victim encoder f_v trained on a private training dataset D_P. An adversary with black-box access to f_v trains a stolen encoder f_s by querying the victim with data points from a dataset D_S to obtain representations. These representations are then used as part of the training objective for the stolen encoder. During the dataset inference, we assume the presence of a third-party arbitrator, such as law enforcement, with white-box access to the victim's training data, as well as all encoders. Additionally, the arbitrator requires the test dataset D_N from the same distribution as D_P to perform dataset inference. An independent encoder f_i is trained with no access to the victim's private training set D_P and without any queries to the victim's encoder. It is used as a baseline for the ownership resolution in the dataset inference.

3.2 Density Estimation of Representations

Representations from encoders contain rich features for given inputs. We analyze the inputs that come from the training and test sets through their representations. For the training inputs, we compute their representations and model their densities [16]. To this end, we leverage GMMs as universal approximators of densities. We give representations a probabilistic interpretation such that they have a smooth enough density which can be approximated by any specific nonzero amount of error using a GMM with enough components. Each component has a separately parameterized mean μ and covariance Σ. We observe that GMMs can overfit to their training data when no constraints are applied to the covariance matrix, hence we limit the covariance matrix for each component to be diagonal. Components with diagonal covariance matrices act together to model feature density even when features are in fact correlated [37]. Moreover, this constraint makes training more computationally efficient since it avoids storing and inverting full high-dimensional covariance matrices.

3.3 Data Flow

The full flow of our dataset inference for encoders consists of the following four main steps which are also visualized in Figure 1:

1. **Victim Training.** The victim's encoder f_v is trained using the whole private training dataset D_P.

2. **Encoder Stealing.** To steal the victim encoder f_v, an adversary queries f_v with data points from D_S to obtain representations $h_{D_S} \in \mathcal{R}^n : h_{D_S} = f_v(D_S)$. With these representations, the adversary trains the stolen encoder f_s in a contrastive manner.

3. **Training Estimators.** To perform ownership resolution, an arbitrator trains three density estimators $\mathcal{E}_v$, $\mathcal{E}_s$ and $\mathcal{E}_i$ for the victim f_v, stolen f_s, and independent encoder f_i as follows:

   a) D_P is divided into two non-overlapping subsets D_{P1} and D_{P2}. While D_{P2} serves as the base for training the density estimators, D_{P1} is used to evaluate density estimates of the private training data vs the test data D_N.

   b) For a given encoder $f \in \{f_v, f_s, f_i\}$, the arbitrator generates representations $h \in \mathcal{R}^n$: $h_{D_{P2}} = f(D_{P2})$ on dataset D_{P2}. Training the density estimators on the respective representations yields the final density estimators $\mathcal{E}_v, \mathcal{E}_s$, and $\mathcal{E}_i$.

4. **Estimating Densities.** The arbitrator generates representations of D_{P1} and D_N with each encoder $f \in \{f_v, f_s, f_i\}$. Applying the respective density estimator $\mathcal{E} \in \{\mathcal{E}_v, \mathcal{E}_s, \mathcal{E}_i\}$ on the representations yields the log-likelihood of each data point x in the respective dataset: $\forall x \in D : p(x) = \mathcal{E}(f(x))$.

3.4 Ownership Resolution

For an encoder f, we compute the log-likelihood on D_{P1} and D_N as: $u_P := \frac{1}{|D_{P1}|} \sum_{x \in D_{P1}} \mathcal{E}(f(x))$ and $u_N := \frac{1}{|D_N|} \sum_{x \in D_N} \mathcal{E}(f(x))$. The density estimator $\mathcal{E}$ measures the similarity between the distributions over the victim's representations of the training D_P vs test data D_N. The intuition behind the setup is that if an encoder was trained on D_P, representations of D_{P1} are much more similar to representations of D_{P2}, because the whole dataset D_P was used for training the encoder, however, representations of D_N differ from representation of D_{P2} since D_N was not used to train the encoder. For a victim f_v and a stolen encoder f_s, u_P is significantly larger than u_N, whereas, for an independent encoder f_i, the values do not differ significantly. Finally, we carry out a hypothesis test with the null hypothesis being: $H_0 := u_P \leq u_N$. If the null-hypothesis can be rejected (p-value < 0.05), *i.e.,* when the log-likelihood for the training set D_{P1} is higher than that for the test set D_N, we can conclude that the tested model was stolen. On the other hand, if the null hypothesis cannot be rejected then the test is inconclusive and we cannot determine if a tested encoder was stolen or not.

4 Encoder Similarity Scores

Measuring the quality of stolen encoders allows us to assess attacks and defenses. In standard supervised learning, the quality of a stolen model is evaluated using two main objectives, namely task accuracy, which is the model's performance on the test set, and fidelity, which is the agreement in the predictions for a given task between the stolen and the victim model [19]. One of the approaches to measure the quality of an extracted encoder is to use its outputs to train a downstream task and compute the accuracy on that task or fidelity (with respect to the outputs of the downstream task trained on the victim encoder). However, a single downstream task cannot adequately reflect the degree of similarity between encoders since it reduces their high dimensional embeddings to single label representations, which are confounded by choices of downstream data and training protocol. Instead, we propose two new metrics. Our first metric is an information-theoretic score based on mutual information [10, 25]. This metric corresponds to the *accuracy* in supervised learning. Our second metric is a cosine similarity score based on the representations returned by different encoders. This corresponds to the *fidelity* metric in supervised learning. The behavior of the two metrics differs in certain cases, for example, when used on obfuscated representations (*e.g.,* with shuffled elements) or with independent models, however, we find that the overall trend is similar. Moreover, the mutual information score is based on an approximation while the cosine similarity score is calculated exactly given representation vectors. Often the effectiveness of defenses may be underestimated against low-quality stolen copies that haven't successfully stolen victim behavior. Our metrics help disentangle such effects and enable faithful evaluation of defenses.

4.1 Mutual Information Score

Our first approach to assessing the quality of a stolen encoder uses a score based on mutual information. We sample N data points from the victim's private training dataset D_P and pass them through the encoders f_v, f_s, and f_i to generate the respective representations. Per standard practice, we recenter and normalize the representations [13]. We denote the entropy by H and compute it according to Algorithm 2 which takes f_v, D_P, and N as input. For the joint entropy $H(f_v, f_s|D)$, we generate representations from the two encoders (in this case victim f_v and stolen f_s) and concatenate

them, which increases the dimensionality of the final representation to $2d$, while other steps remain unchanged. A detailed algorithm for computing the joint entropy can be found in the Appendix as Algorithm 3. We compute an **approximate score** that is based on the definition of mutual information $I(f_v, f_s|D_P)$ between the victim encoder f_v and the stolen copy f_s as well as the analogous mutual information $I(f_v, f_i|D_P)$ between the victim encoder f_v and the independently trained encoder f_i. We rely on approximations since we measure mutual information using finite data. Yet, in practice, such approximations have proven useful [30]. We define our mutual information score as follows:

$$I(f_v, f_s|D_P) = H(f_v|D_P) + H(f_s|D_P) - H(f_v, f_s|D_P). \tag{1}$$

A higher value of the mutual information $I(f_v, f_s|D_P)$ indicates a higher information leakage incurred by the stolen encoder. Expectedly, mutual information is higher between the victim and the stolen encoder than between the victim and independent encoders $I(f_v, f_s|D_P) >> I(f_v, f_i|D_P)$. We can normalize mutual information into a score (between 0 and 1) by setting the lower bound as the mutual information between the victim f_v and a randomly initialized model f_r: $I_{min} = I(f_v, f_r|D_P)$ and the upper bound as the mutual information between the victim and itself: $I_{max} = I(f_v, f_v|D_P)$ For the current mutual information score I_c, the normalized score is defined as $S := \frac{I_c - I_{min}}{I_{max} - I_{min}}$.

4.2 Cosine Similarity Score

The second score we use to assess the quality of a stolen encoder is based on the cosine similarity between its representations and the victim's representations. More specifically, we first compute representations for the two encoders on a set of N randomly selected data points from the dataset D_P. Again as per standard practice [13], we recenter and normalize these representations. For each of the N inputs, we then compute the cosine similarity between the corresponding representations from both encoders where the cosine similarity $\text{sim}(a, b) = \frac{a^T b}{||a||_2 ||b||_2}$ for representation vectors a and b.

We show (in Section 4.3) that the loss functions, which are used for stealing encoders, directly maximize the cosine similarity between representations from victim and stolen encoders. We thus propose to use the cosine similarity score C as a metric, which we define as:

$$C = |\text{sim}(a, b)| \tag{2}$$

The score yields values in the range $[0, 1]$, with a higher score indicating closer representations. To calculate a per-encoder cosine similarity score, we average the cosine similarity scores over all inputs.

We find that the cosine similarity score is well-calibrated across encoders. Namely, an independent encoder, expected to have representations unrelated to the victim encoder, has an average cosine similarity concentrated around 0 [9], while a stolen encoder exhibits significantly higher scores. The cosine similarity score is also easy to compute since it only requires the corresponding representations of the two models and their dot product.

4.3 Analysis

There are various ways in which an attacker may steal an encoder. To simplify our analysis of the cosine similarity score, we consider two best performing loss functions used for stealing [14]: the first where the attacker minimizes the non-contrastive MSE (Mean Squared Error) loss between its representations and the victim encoder's representations to train the stolen encoder, and the second where the attacker uses a contrastive loss function, such as the InfoNCE loss [43] which is applied in SimCLR [5].

Stealing with MSE loss. In the case where the MSE loss is used, let x_i be a query made by an attacker and let $f_v(x_i) = h_{v_i}, f_s(x_i) = h_{s_i} \in \mathcal{R}^n$ be the corresponding representations of the victim and stolen encoders respectively. The MSE loss between these two representations is $\frac{1}{n} \sum_{j=1}^{n} (h_{v_{ij}} - h_{s_{ij}})^2 = \frac{1}{n} ||h_{v_i} - h_{s_i}||_2^2$. It follows directly that minimizing the MSE loss also minimizes the ℓ_2 distance between representations and equivalently maximizes the cosine similarity between representations (see Theorem I.1).

Stealing with InfoNCE loss. When an attacker uses the InfoNCE loss for stealing , minimizing the loss corresponds to maximizing the sum of the cosine similarities between positive pairs, *i.e.,* $\sum_{c=1}^{m} (\text{sim}(h_{s_c}, h_{v_c})/\tau)$. The InfoNCE loss, or contrastive losses in general, also increase the mutual

information score [3, 43]. We, therefore, expect that stolen encoders will have larger similarity scores w.r.t. the victim encoder than independent encoders. We refer the reader to Appendix I.1 for a more detailed discussion of the loss functions and their relationship with the similarity scores.

5 Empirical Evaluation

We evaluate our defense against encoder extraction attacks using five different vision datasets (CIFAR10, CIFAR100 [26], SVHN [32], STL10 [8], and ImageNet [11]). Table 1 shows that our dataset inference method is able to differentiate between the stolen copies of the victim encoder and independently trained encoders by using the victim's private training data as the signature. We also show that our defense works in the scenario where the adversary modifies the representations to render them inconspicuous, *e.g.,* by shuffling the order of elements in the representation vectors. To assess the quality of the stolen encoders and performance of our defense, we measure the mutual information and cosine similarity scores between encoders and present our results in Tables 2 and 3.

5.1 Training Victim, Stolen and Independent Encoders

Victim. We use victim encoders trained on the ImageNet, CIFAR10, and SVHN datatsets. For the ImageNet victim encoder , we use a model released by the authors of SimSiam [6]. To train CIFAR10 and SVHN victim encoders, we use an open-source PyTorch implementation of SimCLR [5]. The ImageNet victim has an output representation dimension of 2048, while the CIFAR10 and SVHN victim encoders have 512-dimensional representations.

Stolen. When stealing from the victim encoders, we evaluate different numbers of queries from various datasets, including CIFAR10, SVHN, ImageNet, and STL10. Stolen encoders are trained in a similar contrastive way as the victim and use the InfoNCE loss, where the positive pairs consist of representations from the victim and stolen encoder for a given input. Algorithm 1 summarizes the stealing approach used by the stolen encoder.

Independent. For each victim encoder, we train independent encoders using datasets different from the victim's private training dataset D_P. The encoders are trained with the SimCLR approach, similar to the way the victim encoders were trained. In the case where the dataset used to train the independent model had different image dimensions from the victim's training dataset, the dataset was resized to be of the same size.

More details on training and stealing encoders can be found in Section D.4 of the Appendix.

5.2 Dataset Inference on Encoders

Setup. We train GMMs with 10 components for CIFAR10 and SVHN, and GMMs with 20 components for ImageNet. For all cases, we restrict the covariance matrix to be diagonal (as stated in Section 3.2). For CIFAR10 and SVHN, we use 80% of the training set to train GMMs, and the remaining 20% to evaluate the training log-likelihood. For ImageNet, we use $100K$ images from the training set to train GMMs and $50K$ as an evaluation set. The whole test sets are used to evaluate test log-likelihood in all datasets. For each setting, we tune the hyperparameters on the victim model and a randomly-initialized model.

Evaluation of our Defense. The empirical results in Table 1 demonstrate that we are able to differentiate between stolen and independent encoders from the difference of log-likelihoods. We observe that the stolen encoders have significantly larger $\Delta\mu$ than the independent encoders. The p-values further show that for stolen encoders the null-hypothesis is rejected while for independent encoders, the test is inconclusive. Similar to dataset inference for supervised learning [29], the victim model typically has the largest $\Delta\mu$ and the smallest p-values. Also, we observe that our method is better at detecting encoders that are stolen using the victim's train set to extract queries.

Number of Stolen Queries. Table 3 shows that as the attacker steals more queries, the p-value from our defense becomes lower. This is consistent with the finding in [29] that dataset inference works better with stronger stolen encoders. We also find that our defense is able to detect stolen encoders even if the attacker only steals from a small number of queries. For example, in Table 3, we are able to claim ownership when only 10K queries are used for stealing the SVHN victim encoder (less than 15% of its training set) and around 50K queries for ImageNet (less than 4% of its training set).

Table 1: **Dataset inference via density estimation of representations.** We detect if a given encoder was stolen. f_v denotes the victim encoder trained on data D, f_s is the stolen encoder extracted using queries from a given stealing dataset D, and f_i is an independent encoder trained on data D (different than victim's private training data). Each value is an average of 3 trials. $\Delta\mu$ is the effect size from the statistical t-test. Obfuscations: the representation can be modified by an attacker in the following ways: (1) *Shuffle* the elements in the representation vectors, (2) *Pad* with zeros or add zeros at random positions, and (3) apply a linear *Transform*. The first row below denotes the victim's private data D_P.

Victim's private data:			*CIFAR10*			*SVHN*			*ImageNet*	
Encoder	Obfuscate	D	p-value	$\Delta\mu$	D	p-value	$\Delta\mu$	D	p-value	$\Delta\mu$
f_v	N/A	CIFAR10	1.37e-16	9.34	SVHN	9.69e-227	19.93	ImageNet	4.18e-36	28.39
f_s	N/A	SVHN	9.82e-2	2.23	SVHN	1.05e-75	11.75	SVHN	3.33e-4	14.79
		CIFAR10	3.56e-6	4.64	CIFAR10	1.19e-17	6.22	CIFAR10	1.47e-4	10.19
		STL10	2.12e-2	3.16	STL10	1.65e-11	4.32	ImageNet	3.14e-5	16.53
f_s	*Shuffle*	CIFAR10	7.81e-6	4.53	CIFAR10	4.79e-16	5.38	CIFAR10	6.72e-4	10.21
	Pad	CIFAR10	5.61e-4	3.09	CIFAR10	7.81e-18	7.98	CIFAR10	2.31e-3	7.23
	Transform	CIFAR10	1.37e-6	4.72	CIFAR10	5.32e-15	5.21	CIFAR10	8.45e-3	8.98
f_i	N/A	CIFAR100	8.39e-1	-0.93	CIFAR100	2.13e-1	0.68	CIFAR100	7.89e-2	4.56
		SVHN	6.90e-1	-0.75	CIFAR10	3.56e-1	0.84	SVHN	5.42e-1	0.69

Robustness of Dataset Inference to Obfuscations. The attacker can obfuscate the stolen encoder representations by, for instance, applying shuffling (changing the order of elements), padding (adding zeros), or linear transformations (*e.g.,* scaling or adding a constant). These obfuscations have little impact on the downstream performance [17] but may pose challenges to the defenses of the victim. The results in Table 1 show that the p-values for the stolen encoders after attackers' obfuscations remain low, which implies that our method is robust to these types of obfuscations.

5.3 Measuring Quality of Stolen Encoders

Setup. To measure the quality of stolen encoders, we select a random subset of $N = 20K$ unaugmented images from the private training dataset D_P and compute their representations from stolen and victim encoders. We then centralize (subtract the mean for each dimension) and normalize the representations (divide by the ℓ_2 norm). For the mutual information score, we first estimate the entropies $H(f_v), H(f_s), H(f_v, f_s)$, which are then added and normalized as in Section 4.1. The score is capped to be in the range $[0, 1]$. To compute the cosine similarity score, we find the absolute value of the dot product of corresponding representations for the two encoders (Equation 2). These dot products are then averaged over all representations.

Figure 3: Distribution of **cosine similarity scores**.

Evaluation of Metrics. To evaluate the mutual information and the cosine similarity scores, we conduct two sets of experiments to verify if: (1) the scores are higher for stolen than independent encoders, and (2) the scores increase as more queries are used to steal encoders, which implies a higher quality of the stolen copies [14]. In Table 2, we observe that both our scores assign higher values to the stolen encoders than the independent encoders. Table 3 shows that our mutual information and cosine similarity scores increase while the p-values from our dataset inference decrease with respect to the number of queries used to steal an encoder. This implies that the performance of our defense is consistent with the similarity metrics and becomes more effective as the quality of the stolen encoder improves. We also plot a histogram of the cosine similarity scores for the stolen and independent encoders in Figure 3 for an SVHN victim encoder, a stolen encoder from it (using CIFAR10 training data as the stealing dataset), and an independent encoder (trained on CIFAR100). There is a pronounced difference between the two distributions with the scores for the independent encoder being close to 0 and the scores for the stolen encoder being much higher than 0.

Robustness of Metrics to Obfuscations. We also consider the effect of obfuscations on these metrics. Without any obfuscation of the representations from stolen encoders, the cosine similarity score shows a clearer distinction between stolen and independent encoders than the mutual information

Table 2: **Encoder similarity scores.** We compare encoders via the encoder quality metrics using the same setting as in Table 1. We compute the score $S(\cdot, f_v)$ based on the mutual information between a given encoder (in a row) and the victim encoder f_v. Analogously, we compute the cosine similarity score $C(\cdot, f_v)$.

Victim's private data:			CIFAR10			SVHN			ImageNet	
Encoder	Obfuscate	D	$S(\cdot, f_v)$	$C(\cdot, f_v)$	D	$S(\cdot, f_v)$	$C(\cdot, f_v)$	D	$S(\cdot, f_v)$	$C(\cdot, f_v)$
f_v	N/A	CIFAR10	1.0	1.0	SVHN	1.0	1.0	ImageNet	1.0	1.0
	N/A	SVHN	0.73	0.504	SVHN	0.96	0.91	SVHN	0.86	0.39
f_s	N/A	CIFAR10	0.84	0.95	CIFAR10	0.94	0.69	CIFAR10	0.88	0.43
	N/A	STL10	0.89	0.92	STL10	0.95	0.89	ImageNet	0.96	0.78
	Shuffle	SVHN	0.74	0.002	CIFAR10	0.94	0.003	SVHN	0.86	0.005
f_s	*Pad*	SVHN	0.74	0.007	CIFAR10	0.93	0.013	SVHN	0.85	0.003
	Transform	SVHN	0.75	0.504	CIFAR10	0.93	0.69	SVHN	0.86	0.39
f_i	N/A	CIFAR100	0.63	0.0007	CIFAR100	0.90	0.007	CIFAR100	0.81	0.0018
	N/A	SVHN	0.12	0.0001	CIFAR10	0.90	0.009	SVHN	0.75	0.002

Table 3: **Encoder similarity scores and p-values from dataset inference vs the number of queries.** The quality of the stolen encoders increases with more stealing queries, which is reflected by the rise in the mutual information and cosine similarity scores as well as the better performance of our defense as indicated by the decreasing p-values. D_P is the private dataset used to train the victim and D_S is the dataset used for stealing.

D_P	D_S	Score	Number of Queries								
			500	5K	7K	8K	9K	10K	20K	30K	50K
		$S(\cdot, f_v)$	0.00	0.11	0.14	0.53	0.57	0.69	0.92	0.93	0.94
SVHN	CIFAR10	$C(\cdot, f_v)$	0.24	0.40	0.46	0.47	0.49	0.52	0.58	0.63	0.69
		p-values	6.89e-1	3.51e-1	4.72e-1	9.87e-2	6.23e-2	5.82e-3	2.31e-7	2.11e-10	1.19e-17
			5K	10K	50K	100K	200K	250K			
		$S(\cdot, f_v)$	0.62	0.79	0.84	0.85	0.85	0.86			
ImageNet	SVHN	$C(\cdot, f_v)$	0.25	0.32	0.38	0.38	0.40	0.39			
		p-values	1.23e-1	7.91e-2	1.1e-2	2.11e-3	1.11e-3	3.33e-4			

score: in Table 2, the cosine similarity scores for all independent encoders are close to zero, but the mutual information scores can be quite high (such as, 0.9 for the independent encoders of SVHN). However, the mutual information score is robust to the obfuscations of the attackers while cosine similarity is not: in Table 2, the cosine similarity score for the stolen encoders after shuffling and padding drops close to zero. Mutual information, as a more general metric based on the information measurement instead of the brittle structure of the representation vectors, performs better and is oblivious to the obfuscations that attackers might introduce.

6 Conclusions

New public APIs expose self-supervised encoder models which return high-dimensional embeddings for provided inputs. Adversaries can use these embeddings to steal the encoders. We present a novel method based on dataset inference for defending against such stealing attacks along with metrics to assess the quality of the stolen encoders and to quantify the effectiveness of our defense. We observe that knowledge contained in the private training set is transferred from the victim encoder to its stolen copy. Thus, the private data acts as a signature of the victim encoder. By leveraging density estimation on the respective encoders' representations, we obtain a signal allowing us to differentiate between the encoder's training and test data. This difference is detectable in both the victim encoder and its stolen copy but not in independent encoders which are legitimately trained on different data than the victim's private training data. Thus, we are able to flag the stolen copy of the victim encoder while not accusing creators of legitimately trained encoders of theft. We show the high effectiveness of our defense on vision encoders. Future work may explore additional applications of our proposed defense and metrics beyond model stealing and ownership verification, as well as their use in other domains such as natural language processing (NLP). In particular, our method may help enforce the ethical usage of sensitive online data, such as images on social media, in accordance with privacy regulations by auditing if a given providers' encoder contains knowledge of these sensitive data.

References

[1] Cohere, https://cohere.ai. URL https://cohere.ai/.

[2] Openai, https://openai.com. URL https://openai.com/.

[3] Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views, 2019. URL https://arxiv.org/abs/1906.00910.

[4] Franziska Boenisch. A systematic review on model watermarking for neural networks. *Frontiers in Big Data*, 4, nov 2021. doi: 10.3389/fdata.2021.729663.

[5] Ting Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. *International Conference on Machine Learning*, 2020.

[6] Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. 2020.

[7] Xinyun Chen, Wenxiao Wang, Chris Bender, Yiming Ding, Ruoxi Jia, Bo Li, and Dawn Song. Refit: a unified watermark removal framework for deep learning systems with limited data. In *Proceedings of the 2021 ACM Asia Conference on Computer and Communications Security*, pages 321–335, 2021.

[8] Adam Coates, Andrew Ng, and Honglak Lee. An Analysis of Single Layer Networks in Unsupervised Feature Learning. In *AISTATS*, 2011. https://cs.stanford.edu/~acoates/papers/coatesleeng_aistats_2011.pdf.

[9] Tianshuo Cong, Xinlei He, and Yang Zhang. Sslguard: A watermarking scheme for self-supervised learning pre-trained encoders. *CoRR*, abs/2201.11692, 2022. URL https://arxiv.org/abs/2201.11692.

[10] Thomas M. Cover and Joy A. Thomas. *Elements of Information Theory (Wiley Series in Telecommunications and Signal Processing)*. Wiley-Interscience, USA, 2006. ISBN 0471241954.

[11] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[12] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[13] Frances Ding, Jean-Stanislas Denain, and Jacob Steinhardt. Grounding representation similarity through statistical testing. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=_kwj6V53ZqB.

[14] Adam Dziedzic, Nikita Dhawan, Muhammad Ahmad Kaleem, Jonas Guan, and Nicolas Papernot. On the difficulty of defending self-supervised learning against model extraction, 2022. URL https://arxiv.org/abs/2205.07890.

[15] Adam Dziedzic, Muhammad Ahmad Kaleem, Yu Shen Lu, and Nicolas Papernot. Increasing the cost of model extraction with calibrated proof of work. In *International Conference on Learning Representations*, 2022. URL https://arxiv.org/abs/2201.09243.

[16] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. http://www.deeplearningbook.org.

[17] Jeff Z HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. *Advances in Neural Information Processing Systems*, 34, 2021.

[18] Xinlei He and Yang Zhang. Quantifying and mitigating privacy risks of contrastive learning. In *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, CCS '21, page 845–863, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450384544. doi: 10.1145/3460120.3484571. URL https://doi.org/10.1145/3460120.3484571.

[19] Matthew Jagielski, N. Carlini, D. Berthelot, A. Kurakin, and N. Papernot. High accuracy and high fidelity extraction of neural networks. *USENIX Security Symposium*, 2020.

[20] Ashish Jaiswal, Ashwin Ramesh Babu, Mohammad Zaki Zadeh, Debapriya Banerjee, and Fillia Makedon. A survey on contrastive self-supervised learning. *Technologies*, 9(1), 2021. ISSN 2227-7080. doi: 10.3390/technologies9010002. URL https://www.mdpi.com/2227-7080/9/1/2.

[21] Hengrui Jia, C. A. Choquette-Choo, V. Chandrasekaran, and N. Papernot. Entangled watermarks as a defense against model extraction. *USENIX Security Symposium*, 2021.

[22] Mika Juuti, Sebastian Szyller, Samuel Marchal, and N Asokan. Prada: protecting against dnn model stealing attacks. In *2019 IEEE European Symposium on Security and Privacy (EuroS&P)*, pages 512–527. IEEE, 2019.

[23] Ashish Kapoor, Eric Horvitz, and Sumit Basu. Selective supervision: Guiding supervised learning with decision-theoretic active learning. In *IJCAI*, volume 7, pages 877–882, 2007.

[24] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited, 2019. URL https://arxiv.org/abs/1905.00414.

[25] L. F. Kozachenko and N. N. Leonenko. Sample estimate of the entropy of a random vector. *Probl. Peredachi Inf.*, 23:9–16, 1987. URL http://www.mathnet.ru/links/5e0609d41b53e39bccea1f8711152ecd/ppi797.pdf.

[26] Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

[27] Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. BioBERT: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240, 09 2019. ISSN 1367-4803. doi: 10.1093/bioinformatics/btz682. URL https://doi.org/10.1093/bioinformatics/btz682.

[28] Hongbin Liu, Jinyuan Jia, Wenjie Qu, and Neil Zhenqiang Gong. Encodermi: Membership inference against pre-trained encoders in contrastive learning. In *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, CCS '21, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450384544. URL https://doi.org/10.1145/3460120.3484749.

[29] Pratyush Maini, Mohammad Yaghini, and Nicolas Papernot. Dataset inference: Ownership resolution in machine learning. In *Proceedings of ICLR 2021: 9th International Conference on Learning Representationsn*, 2021.

[30] David McAllester and Karl Stratos. Formal limitations on the measurement of mutual information. In Silvia Chiappa and Roberto Calandra, editors, *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 875–884. PMLR, 26–28 Aug 2020. URL https://proceedings.mlr.press/v108/mcallester20a.html.

[31] Ari S. Morcos, Maithra Raghu, and Samy Bengio. Insights on representational similarity in neural networks with canonical correlation, 2018.

[32] Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf.

[33] Tribhuvanesh Orekondy, Bernt Schiele, and Mario Fritz. Knockoff nets: Stealing functionality of black-box models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4954–4963, 2019.

[34] Tribhuvanesh Orekondy, Bernt Schiele, and Mario Fritz. Prediction poisoning: Towards defenses against dnn model stealing attacks. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=SyevYxHtDB.

[35] Ben Poole, Sherjil Ozair, Aaron van den Oord, Alexander A. Alemi, and George Tucker. On variational bounds of mutual information, 2019.

[36] Alec Radford, Jong Wook Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever. Learning transferable visual models from natural language supervision. *Arxiv*, abs/2103.00020, 2021.

[37] Douglas Reynolds. *Gaussian Mixture Models*, pages 659–663. Springer US, Boston, MA, 2009. ISBN 978-0-387-73003-5. doi: 10.1007/978-0-387-73003-5_196. URL https://doi.org/10.1007/978-0-387-73003-5_196.

[38] Zeyang Sha, Xinlei He, Ning Yu, Michael Backes, and Yang Zhang. Can't steal? cont-steal! contrastive stealing attacks against image encoders. 2022. URL https://arxiv.org/abs/2201.07513.

[39] Masoumeh Shafieinejad, Nils Lukas, Jiaqi Wang, Xinda Li, and Florian Kerschbaum. On the robustness of backdoor-based watermarking in deep neural networks. In *Proceedings of the 2021 ACM Workshop on Information Hiding and Multimedia Security*, pages 177–188, 2021.

[40] Or Sharir, Barak Peleg, and Yoav Shoham. The cost of training NLP models: A concise overview. *CoRR*, abs/2004.08900, 2020. URL https://arxiv.org/abs/2004.08900.

[41] Alessandro Sordoni, Nouha Dziri, Hannes Schulz, Geoff Gordon, Phil Bachman, and Remi Tachet. Decomposed mutual information estimation for contrastive representation learning, 2021. URL https://arxiv.org/abs/2106.13401.

[42] Florian Tramèr, F. Zhang, A. Juels, M. Reiter, and T. Ristenpart. Stealing machine learning models via prediction apis. *USENIX Security Symposium*, 2016.

[43] Aäron van den Oord, Y. Li, and O. Vinyals. Representation learning with contrastive predictive coding. *ArXiv*, abs/1807.03748, 2018.

[44] Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y Zhao. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *2019 IEEE Symposium on Security and Privacy (SP)*, pages 707–723. IEEE, 2019.

[45] Lixu Wang, Shichao Xu, Ruiqi Xu, Xiao Wang, and Qi Zhu. Non-transferable learning: A new approach for model ownership verification and applicability authorization. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=tYRrOdSnVUy.