# SINGLE-PHOTON IMAGE CLASSIFICATION

## ABSTRACT

Quantum Computing based Machine Learning mainly focuses on quantum computing hardware that is experimentally challenging to realize due to requiring quantum gates that operate at very low temperature. We demonstrate the existence of a "quantum computing toy model" that illustrates key aspects of quantum information processing while being experimentally accessible with room temperature optics. Pondering the question of the theoretical classification accuracy performance limit for MNIST (respectively "Fashion-MNIST") classifiers, subject to the constraint that a decision has to be made after detection of the very first photon that passed through an image-filter, we show that a machine learning system that is permitted to use quantum interference on the photon's state can substantially outperform any machine learning system that can not. Specifically, we prove that a "classical" MNIST (respectively "Fashion-MNIST") classifier cannot achieve an accuracy of better than $21.28\%$ (respectively $18.28\%$ for "Fashion-MNIST") if it must make a decision after seeing a single photon falling on one of the $28 \times 28$ image pixels of a detector array. We further demonstrate that a classifier that is permitted to employ quantum interference by optically transforming the photon state prior to detection can achieve a classification accuracy of at least $41.27\%$ for MNIST (respectively $36.14\%$ for "Fashion-MNIST"). We show in detail how to train the corresponding quantum state transformation with TensorFlow and also explain how this example can serve as a teaching tool for the measurement process in quantum mechanics.

## 1 INTRODUCTION

Both quantum mechanics and machine learning play a major role in modern technology, and the emerging field of AI applications of quantum computing may well enable major breakthroughs across many scientific disciplines. Yet, as the majority of current machine learning practitioners do not have a thorough understanding of quantum mechanics, while the majority of quantum physicists only have an equally limited understanding of machine learning, it is interesting to look for "Rosetta Stone" problems where simple and widely understood machine learning ideas meet simple and widely understood quantum mechanics ideas. It is the intent of this article to present a setting in which textbook quantum mechanics sheds a new light on a textbook machine learning problem, and vice versa, conceptually somewhat along the lines of Google's TensorFlow Playground (Smilkov et al. (2017),) which was introduced as a teaching device to illustrate key concepts from Deep Learning to a wider audience.

Specifically, we want to consider the question what the maximal achievable accuracy on common one-out-of-many image classification tasks is if one must make a decision after the detection of the very first quantum of light (i.e. photon) that passed a filter showing an example image from the test set. In this setting, we do not have a one-to-one correspondence between example images from the training (respectively test) set and classification problems. Instead, every example image defines a probability distribution for the $(x, y)$ detector pixel location on which the first photon passing an image filter lands, the per-pixel probability being the pixel's brightness relative to the accumulated (across all pixels) image brightness. So, from every ($28 \times 28$ pixels) example image, we can sample arbitrarily many photon-detection-event classifier examples, where the features are a pair of integer pixel coordinates, and the label is the digit class.

On the MNIST handwritten digit dataset (LeCun and Cortes (2010)), any machine learning system that only gets to see a single such "photon detected at coordinates $(x, y)$" event as its input features, of the pixel that flashed up are the only input features, is limited in accuracy

by the maximum likelihood estimate, since we have: $P(\text{Image class C}|\text{Photon detected at } (x, y)) = \sum_{\text{E}} P(\text{Image class C}|\text{Example E}) P(\text{Example E}|\text{Photon detected at } (x, y))$.

On photon detection events generated each by first randomly picking a training set image, and then randomly picking a brightness-weighted pixel from that, we cannot do any better than predicting the most likely digit class given these input features – the two pixel coordinates. Evaluating the performance of this proven-optimal-on-examples-generated-from-training-set MLE classifier on examples generated from the test set, we find an accuracy of $21.27\%$ (rounded - so, $21.28\%$ is an upper bound), for the MNIST dataset – substantially higher than random guessing ($10\%$). The most likely digit class per pixel is shown in figure 2(b).

This accuracy is, by construction, the best we can hope to achieve for a classifier whose input is the address of a single pixel: We cannot, for example, outperform it by redistributing light intensity between pixels, since any such redistribution could only destroy some of the available useful information, not magically create extra useful information.

An entirely different situation arises when we allow quantum mechanics to enter the stage: For a single photon passing through a coherently illuminated image filter, with all pixels at the same optical phase on the incoming wave, we can imagine putting some precision optical device between the image filter and the detector array that redistributes not the *probabilities* (which correspond to light intensity when aggregating over many photons), but the *amplitudes* that make up the spatial part of the photon wave-function. Illuminating such a set-up with many photons would show a hologram-like interference pattern on the detector array. This transformation of the (single-)photon wave function by linear optical elements then has tuneable parameters which we can adjust to improve classifier accuracy. Quantum mechanics tells us that every (lossless) linear optical device can be represented by a linear unitary transform on the photon state: The action of any complex optical device consisting of (potentially very many) components which transforms a $N$-component photon state (in our case, $N = 28^2$ amplitudes in the spatial part of the photon wavefunction) can be described by an element of the $N^2$-dimensional unitary matrix Lie group $U(N)$. Vice versa, Reck et al. (1994) describes a constructive algorithm by which any $U(N)$ transformation matrix can be translated back to a network of optical beam splitters and phase shifters.

Conceptually, exploiting interference to enhance the probability of a quantum experiment producing the sought outcome is the essential idea underlying all quantum computing. The main difference between this problem and modern quantum computing is that the latter tries to perform calculations by manipulating quantum states of multiple "entangled" constituents, typically coupled two-state quantum systems called "qubits," via "quantum gates" that are controlled by parts of the total quantum system's quantum state. Building a many-qubit quantum computer hence requires delicate control over the interactions between constituent qubits. This usually requires eliminating thermal noise by going to millikelvin temperatures. For the problem studied here, the quantum state can be transformed with conventional optics at room temperature: the energy of a green photon is 2.5 eV, way above the typical room temperature thermal radiation energy of $kT \simeq 25$ meV. The price to pay is that it is challenging to build a device that allows multiple photons to interact in the way needed to build a many-qubit quantum computer. Nevertheless, Knill, Laflamme, and Milburn (Knill et al. (2001)) devised a protocol to make this feasible in principle, avoiding the need for coherency-preserving nonlinear optics (which may well be impossible to realize experimentally) by clever exploitation of ancillary photon qubits, boson statistics, and the measurement process. In all such applications, the basic idea is to employ coherent multiphoton quantum states to do computations with multiple qubits. In the problem studied here, there is only a single photon, the only relevant information that gets processed is encoded in the spatial part of its wave function (i.e. polarization is irrelevant), so the current work resembles the "optical simulation of quantum logic" proposed by Cerf et al. (1998) where a N-qubit system is represented by $2^N$ spatial modes of a single photon. Related work studied similar "optical simulations of quantum computing" for implementing various algorithms, in particular (small) integer factorization (Clauser and Dowling (1996); Summhammer (1997)), but to the best of the present authors' knowledge did not consider machine learning problems.

This work can be described as belonging to the category of machine learning methods on quantum non-scalable architectures. Alternatively, one can regard it as a quantum analogue of recent work that demonstrated digital circuit free MNIST digit classification via classical nonlinear optics, for instance via saturable absorbers (Khoram et al. (2019).) Apart from providing an accessible and commonly understandable toy problem for both quantum and ML research communities, this simple-

quantum/simple-ML corner also may be of interest for teaching the physics of the measurement process ("the collapse of the wave function") in a more accessible setting. Whereas explanations of the measurement process are forced to remain vague where they try to model "the quantum states of the observer" (typically unfathomably many states that one would never hope to be able to model in terms of actual numbers), using machine learning as a sort-of cartoon substitute for high level mental processes actually allows us to come up with fully concrete toy models of the measurement process on low-dimensional (such as: $D < 1000$) Hilbert spaces that nevertheless capture many of the essential aspects – to the extent that "ML classifies the measurement as showing the image of a shoe" can be regarded as a crude approximation to "observer sees a shoe".

## 2 THE MEASUREMENT PROCESS

How well one can one solve a mental processing task, such as identifying a handwritten digit, if one is permitted to only measure a single quantum? This question leads to a Hilbert space basis factorization that parallels the factorization needed to study the quantum mechanical measurement process. Let us consider a gedankenexperiment where our quantum system (see Feynman et al. (2010); Landau and Lifshitz (1981) for an introduction to quantum mechanics) is a single atom that has two experiment-relevant quantum states, 'spin-up' and 'spin-down',

$$|\psi_{\text{Atom}}\rangle = c_0|\psi_{\text{Atom}=\uparrow}\rangle + c_1|\psi_{\text{Atom}=\downarrow}\rangle. \tag{1}$$

This atom undergoes a measurement by interacting, over a limited time period, with an apparatus. The measurement process may involve for instance an atom emitting a photon that is detected by a camera, and it may include a human observing the result. We describe a quantum state in the potentially enormous Hilbert space of apparatus states with the vector $|\psi_{\text{Apparatus}}\rangle$. If, in this gedankenexperiment, we actually assume that we have maximal information about the (quantum) state of the measurement apparatus (which, however, in practical terms would be unfathomably complicated) at the beginning of the experiment, then the full quantum state of the initial system is the tensor product

$$|\psi_{\text{System, initial}}\rangle = |\psi_{\text{Atom, initial}}\rangle \otimes |\psi_{\text{Apparatus, initial}}\rangle. \tag{2}$$

This factorization implies that atom and apparatus states are independent before the interaction.

Without interaction between the apparatus and the atom, the time-evolution of the total system factorizes. A measurement requires an interaction between the apparatus and the atom, the solution of the Schrödinger equation is equivalent to the application of a unitary operator $U$ to the state $|\psi_{\text{System, initial}}\rangle$. This has the effect of combining the state components of the atom and the apparatus and, as a consequence, the joint time evolution no longer can be factorized. The overall state is $|\psi_{\text{System, final}}\rangle = U|\psi_{\text{System, initial}}\rangle$ and can be always decomposed in the sum:

$$|\psi_{\text{System, final}}\rangle = \alpha|\psi_{\text{Atom}=\uparrow}\rangle \otimes |\psi_{\text{Apparatus, final}=\uparrow}\rangle + \beta|\psi_{\text{Atom}=\downarrow}\rangle \otimes |\psi_{\text{Apparatus, final}=\downarrow}\rangle, \tag{3}$$

where the apparatus states $|\psi_{\text{Apparatus, final}=\uparrow}\rangle$ and $|\psi_{\text{Apparatus, final}=\downarrow}\rangle$ represent the state of the apparatus after the measurement for the two basis states of the atom. Therefore, the apparatus is in a different state for the two cases, which leads to the apparent "collapse" of the wave function. The apparatus in the state $|\psi_{\text{Apparatus, final}=\uparrow}\rangle$ perceives the "collapse" because the atom seems to have taken the state $|\psi_{\text{Atom}=\uparrow}\rangle$. The state of the apparatus includes also the representation of the thought process of a possible human observer, for instance asking herself at what instant the atom took a well determined state. This thought process disregards the superposed state $|\psi_{\text{Apparatus, final}=\downarrow}\rangle$ which represents the alternative reality, where the apparatus observed a different outcome.

Considering that a mental process could be seen as a measurement on the environment, one would naturally be inclined to think that high level mental concepts never would naturally lend themselves to a description in terms of some Hilbert space basis that has tensor product structure $|\psi_{\text{general concept}}\rangle \otimes |\psi_{\text{details}}\rangle$. Machine learning is now making the question to what extent this may nevertheless work quantitatively testable for some simple cases, if we consider it as providing reasonably good (for this purpose) models for mental concepts.

Let us consider the spatial part of a single photon's quantum state as it traveled through a mask that has the shape of a complicated object. For instance, let's assume that the mask is obtained from a random sample of the "Fashion-MNIST" dataset, Xiao et al. (2017), where each sample represents an

object such as a shirt, a trouser, etc. One would generally expect that any sort of transformation that connects a highly regular and mathematically simple description of such a quantum system, such as in terms of per-picture-cell ("pixel") amplitudes, with a description in human-interpretable terms, such as "the overall intensity pattern resembles a shirt," would unavoidably involve very complicated entanglement, and one should not even remotely hope to be able to even only approximately express such photon states in terms of some factorization

$$|\psi_{\text{photon}}\rangle \approx \sum_{\text{shape class } C \in \{shirt, trouser, ...\}} \sum_{\text{style } S} c_{CS}|\psi_{\text{shape class } C}\rangle \otimes |\psi_{\text{style } S}\rangle, \qquad (4)$$

since one would not expect the existence of a basis of orthonormal quantum states that can be (approximately) labeled $|\psi_{\text{shirt}}\rangle, |\psi_{\text{shoe}}\rangle$, etc. Using machine learning, we can quantitatively demonstrate that, at least for some simple examples, *precisely such a factorization does indeed work remarkably well*, at least if we content ourselves with the concept of a "shirt shape" being that of a one-out-of-many machine learning classifier, so not quite that of a human. In any case, it is reassuring to see that even near-future few-qbits quantum computers might be able to model high level concepts rather well.

## 3   SINGLE-QUANTUM OBJECT CLASSIFICATION

Our gedankenexperiment starts with a single photon passing from faraway through a programmable LCD screen, which we here consider to consist of $N \times N$ pixels and show an image, where for both the MNIST handwritten digit dataset of LeCun and Cortes (2010) and the "Fashion-MNIST" dataset of Xiao et al. (2017), we have $N = 28$.

The size of the screen shall be sufficiently small for the photon's quantum state to be at the same phase as it reaches each individual pixel. This does not mean that the screen has to be small in comparison to the wavelength. Rather, the light source must provide highly collimated illumination.

The relevant spatial part of the photon's quantum state is described by an element of a $N \times N$-dimensional complex vector space. We can choose a basis for this Hilbert space such that the quantum state of a photon that managed to pass through the screen (rather than getting absorbed) has the form

$$|\psi_{\text{Photon}}\rangle = \sum_{\text{row } j, \text{ column } k} c_{jk}|\psi_{jk}\rangle \qquad (5)$$

where the $|\psi_{jk}\rangle$ basis functions correspond to a photon that went through pixel $(j, k)$, and the coefficients $c_{jk}$ are real, non-negative, proportional to the square roots of the image's pixel-brightnesses, and are normalized according to $\sum_{j,k} |c_{j,k}|^2 = 1$.

As we want to perform a rotation on this Hilbert space that maximizes alignment with a tensor product Hilbert space where one factor describes an image class, we pad this $N^2$-dimensional Hilbert space into a larger Hilbert space with dimensionality $M$ divisible by the number of object classes $C$, i.e. $M = C \cdot S$. This amounts to adding always-dark pixels (that may not form a complete row) to the image. The problem then amounts to engineering, for a problem $P$ such as handwritten digit recognition, a single problem-specific unitary transform $U_P$ of the photon state, $|\psi_{\text{Photon}}\rangle \to U_P|\psi_{\text{Photon}}\rangle$, such that we can meaningfully claim:

$$U_P|\psi_{\text{Photon}}\rangle = |\psi_{\text{Photon}^*}\rangle \approx \sum_{\text{example class } c} \sum_{\text{style } s} c_{cs}|\psi_{\text{class is } c}\rangle \otimes |\psi_{\text{style variant is } s}\rangle \qquad (6)$$

Specifically, for each individual example image $E$, we would like to have

$$U_P|\psi_{\text{Photon},E}\rangle \approx |\psi_{C(E)}\rangle \otimes \sum_{\text{style } s} c_s|\psi_{\text{style variant is } s}(E)\rangle, \qquad (7)$$

where $C(E)$ is the ground truth label of the example in a supervised learning setting.

Using the method described in Reck et al. (1994), this trained matrix then can be translated to an optical network blueprint. The transformed quantum state at the output side of the network of beam splitters and phase shifters then gets measured by a detector array that can discriminate $M = C \cdot S$ quantum states which are labeled $|\psi_{\text{digit is a } 0}\rangle \otimes |\psi_{\text{style variant } 1}\rangle, |\psi_{\text{digit is a } 0}\rangle \otimes |\psi_{\text{style variant } 2}\rangle, \ldots,$

$$c = 0 \qquad c = 1 \qquad\qquad c = 0 \qquad c = 1$$

(a) (b)

Figure 1: (a) The two shapes of the toy example. The four gray pixels correspond to a photon arrival probability of $1/4$, i.e. a probability amplitude of $1/2$. (b) The per-pixel photon arrival probability after the orthogonal transformation is applied. The dark gray pixels correspond to a probability of $1/8$ and the light gray pixels to $1/2$.

$|\psi_{\text{digit is a }3}\rangle \otimes |\psi_{\text{style variant }57}\rangle, \ldots, |\psi_{\text{digit is a }9}\rangle \otimes |\psi_{\text{style variant }S_{\max}}\rangle$. If we detect the photon in any of the $|\psi_{\text{digit is a }7}\rangle \otimes \ldots$ cells, the classifier output is a "7", and likewise for the other digits.

From a machine learning perspective, the trainable parameters hence are the complex entries of the matrix $U_P$, which according to quantum mechanics have to satisfy an unitarity constraint, $U_P U_P^\dagger = I$, and this search space automatically covers all experimentally realizable linear optical devices. For MNIST, where examples have $28 \times 28$ pixels, the most obvious choice is padding to a $M = 790$-dimensional input vector. While one could implement the unitarity constraint in terms of a (regularizer) loss-function contribution that measures the degree of violation of unitarity, it here makes more sense to instead use a parametrization of $U_P$ that automatically guarantees unitarity, using Lie group theory. If $W_P$ is a $790 \times 790$ matrix of trainable (real) weights, then the hermitean matrix $H_P = -i(W_P - W_P^T) + (W_P + W_P^T)$ parametrizes the Lie algebra $\mathfrak{u}(790)$, and $U_P = \exp(iH_P)$ covers all of the (compact) unitary group $U(790)$. This approach slightly over-parametrizes the problem, since, in the tensor-product basis that we are transforming to, we can freely re-define the basis on each of the ten $790/10 = 79$-dimensional style subspaces. This means that $10\%$ of the parameters are redundant.

Model accuracy has to be evaluated with caution: as we need to make a prediction after detection of a single photon, accuracy is the quantum probability of the correct label, averaged over all examples. Naturally, we can not determine which of the $C$ output classes would receive the most photons (= has highest probability) if all we have is a single photon detection event. This accuracy, about $40\%$ for the problems considered here, differs substantially from the accuracy that would be obtainable by looking at many photons coming from the same example image, which here typically exceeds $90\%$. In other words, probabilities are uncalibrated, and the (non-linear "deep learning") transformation that would be required to calibrate them cannot be expressed as a unitary operator.

Let us consider a radically simplified example that illustrates why this method works. We want to discriminate between only two different shapes (with no further shape variation) on a $2 \times 4$ pixel screen where each pixel is either "on" or "off", using only one photon. Specifically, let us consider the two Tetris "T" shapes represented in figure 1(a).

For both shapes, the probability that the single photon arrives on one of the "on" pixels is $1/4$; therefore, taking into account that for two pixels the correct shape is identified exactly and for two with $50\%$ probability, we conclude that the baseline accuracy is $1/2 + 1/4 = 75\%$. Instead, we can apply a unitary transformation to reshape the probability amplitudes.

Let us consider the simple but not optimal transformation of the photon amplitude that replaces the pair of amplitudes $(a, b)$ in each 2-pixel column with $((a - b)/\sqrt{2}, (a + b)/\sqrt{2})$, i.e. creates destructive interference in the top row and constructive interference in the bottom row. This gives the detection probability patterns shown in figure 1 (b). Maximum likelihood estimation here gives an accuracy of $1/2 + 3/8 = 87.5\%$.

Obtaining the maximum achievable accuracy will here require a more complicated all-pixel amplitude transformation, obtained as follows: The quantum amplitude transformation is angle-preserving, and the angle $\alpha$ between the two amplitude quantum states $q_1$, $q_2$ is given by $\cos \alpha = \langle q_1 | q_2 \rangle = 0.5$. Hence, we can rotate these two states to lie in the plane of the first two Cartesian coordinate axes of

Table 1: Results for the Fashion-MNIST and MNIST datasets. The "classic" accuracy and information refer to the observation of a single photon, while the "quantum" quantities are obtained after applying the quantum transformation.

| Dataset | Entropy [bits] | Accuracy (classic) | Information (classic) [bits] | Accuracy (quantum) | Information (quantum) [bits] |
|---|---|---|---|---|---|
| Fashion-MNIST | 3.32 | 18.27% | 0.8694 | **36.14%** | **1.85** |
| MNIST | 3.32 | 21.27% | 1.09 | **41.27%** | **2.04** |

the Hilbert space, and at the same angle from their bisector. Identifying these coordinate axes with the correct labels, the accuracy is the cosine-squared of the angle between the transformed state and the corresponding axis, i.e. $\cos^2(\pi/4 - \alpha/2) = (\sqrt{3} + 2)/4 \approx 93.30\%$.

While the performance measure that we care about here is the probability for a correct classification, one observes that model training is nevertheless more effective when one instead minimizes cross-entropy, as one would when training a conventional machine learning model. Intuitively, this seems to make sense, as a gradient computed on cross-entropy loss is expected to transport more information about the particular way in which a classification is off than a gradient that is based only on maximizing the correct classification probability.

Overall, this task is somewhat unusual as a machine learning problem for three reasons: First, it involves complex intermediate quantities, and gradient backpropagation has to correctly handle the transitioning from real to complex derivatives where the loss function is the magnitude-squared of a complex quantity. TensorFlow is at the time of this writing the only widely used machine learning framework that can handle this aspect nicely. Second, (as explained above), we cannot simply pick the class for which the predicted probability is highest as the predicted class. Rather, the probability for the single-photon measurement to produce the ground truth label sets the accuracy. Third, while most machine learning architectures roughly follow a logistic regression architecture and accumulate per-class evidence which gets mapped to a vector of per-class probabilities, we here have the probabilities as the more readily available data, so the computation of cross-entropy loss will have to infer logits from probabilities. Due to this need to compute logarithms of probabilities, it is very important that the training process does not intermediately see invalid probabilities outside the range $(0 \ldots 1)$, and this is ensured by parametrizing unitary transforms as matrix exponentials of anti-hermitean matrices.

TensorFlow code to both train such a model and also evaluate its performance is included in the supplementary material.

## 4 RESULTS

Figure 2 shows the most probable image class for each pixel, for the "Fashion-MNIST" and MNIST datasets. A classifier that looks up and predicts the most likely class in this table achieves maximal accuracy among all single photon classifiers that do not employ quantum interference. This accuracy is reported in the third column of table 1. (We note that, as pointed out by Sun et al. (2007), the "Fashion-MNIST" dataset contains many mislabeled instances, which affects both classical and quantum results.) We can compute the amount of information provided by the photon by computing the difference between the class entropy, i.e. $-\log_2(0.1) = 3.32$, since there are 10 classes, and the entropy associated to the classification errors, i.e. the accuracy. The mutual information for the classical classifier is given in the fourth column of table 1.

Training a unitary $U(790)$ quantum transformation that gets applied after the photon passed the image filter and before it hits a bank of 790 detectors allows boosting accuracy for both the "Fashion-MNIST" and MNIST datasets, as reported in the fifth column of table 1. The observation of the photon after the transformation provides a higher amount of mutual information with respect to the classical case. The values of mutual information in this case are given in the last column of table 1. Explicit matrices to perform the transformation for the two data sets have been made available with the supplementary material.

(a)                        (b)

Figure 2: (a) Fashion-MNIST most likely class given detection of a single photon at the corresponding pixel coordinates. Here, the classes are: 0=T-shirt/top, 1=Trouser, 2=Pullover, 3=Dress, 4=Coat, 5=Sandal, 6=Shirt, 7=Sneaker, 8=Bag, 9=Ankle Boot. (b) Most likely digit-class given detection of a single photon for MNIST.

Figure 3: The confusion matrices for the "Fashion-MNIST" and MNIST datasets when classic and quantum classifiers are used: (a) "Fashion-MNIST"/classic, (b) MNIST/classic, (c) "Fashion-MNIST"/quantum, (d) MNIST/quantum.

The quantum transformation $U_P$ allows us to define the pixel-space projection operators:

$$P_{\text{class } C} := U_P^{-1} \left( |\psi_C\rangle\langle\psi_C| \otimes I_{\text{style}} \right) U_P \tag{8}$$

with which we can decompose any example into contributions that are attributable to the different classes. Here, one must keep in mind that such separation is done at the level of probability amplitudes, so while we can compute intensities/probabilities from these components, which are mutually orthogonal as quantum states, summing these per-component per-pixel intensities will not reproduce the example's per-pixel intensities. This shows most clearly when considering the decomposition of an example "Trouser" from the "Fashion-MNIST" dataset's test set with the model we trained for this task, as shown in figure 4(a). The dark vertical line between the legs in the original image mostly comes from *destructive interference* between a bright line from the "Trousers" component and a matching bright line from the "Dress" component.

Due to the intrinsic quantum nature of this set-up, care must be taken when interpreting confusion matrices. Naturally, we never can claim of any single-photon classifier that it would 'classify a

Figure 4: Projection of probability amplitudes for some samples of the "Fashion-MNIST" (a) and the MNIST (b) datasets. The first image shows the original sample probability and the following images show the probability amplitudes for each class. We visualize the complex amplitude by using brightness to represent magnitude and hue for phase (the colormap for the phase is shown on the right of each row.)

particular image example correctly', since re-running the experiment on the same example will not see the photon always being counted by the same detector! So, strictly speaking, for any single-photon classifier realized as a device, the "confusion matrix" could be determined experimentally only in the statistical sense, leaving uncertainty in the entries that decreases with the number of passes over the test set. Confusion matrices are shown in figure 3.

Our factorization ansatz appears to contain a hidden constraint: we are forcing each image class to use the same number of style-states. One could imagine, for instance, that a classifier might achieve even higher accuracy by treating image classes unevenly. Any such model that allows more style-space dimesions for some classes can always be embedded into a model that allows more style-space dimensions for all classes, so this question can be answered by padding to a larger Hilbert space. Numerical experiments, e.g. padding to 1000 rather than 790 dimensions, suggest that this has no appreciable impact on classification accuracy.

## 5 DISCUSSION

In summary, we demonstrated that, at least for the considered datasets, the space of the single observed photon state can be factorized remarkably well by a product of the example class space and a space collecting the remaining variables, such as the style. This factorization can be obtained easily by the proposed method and is experimentally realizable with optical elements placed in front of the sensor. The supplementary material contains a blueprint for an example circuit outperforming the classical limit (at 36.05% accuracy) on $10 \times 10$ downsampled MNIST.

An experimental implementation of the proposed system would be a demonstration of a high-temperature and low- effective-qubit quantum ML device. With respect to other experimental approaches to quantum computing, such a device would have the limitation that it is built for the specific classification problem and cannot be reconfigured easily. It would be interesting to see whether an advanced quantum protocol along the lines of Knill et al. (2001) might enable the realization of more sophisticated intermediate-scale high temperature quantum machine learning in a way that mostly (like here) bypasses the need for quantum logic built from common quantum gates.

## 6 TENSORFLOW CODE

TensorFlow2 code to reproduce the experiments of this work and all the figures is provided in the ancillary files together with the computed unitary tranformations for MNIST and "Fashion-MNIST".

REFERENCES

Daniel Smilkov, Shan Carter, D. Sculley, Fernanda B. Viégas, and Martin Wattenberg. Direct-manipulation visualization of deep networks. *CoRR*, abs/1708.03788, 2017. URL http://arxiv.org/abs/1708.03788.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010. URL http://yann.lecun.com/exdb/mnist/.

Michael Reck, Anton Zeilinger, Herbert J. Bernstein, and Philip Bertani. Experimental realization of any discrete unitary operator. *Phys. Rev. Lett.*, 73:58–61, Jul 1994. doi: 10.1103/PhysRevLett.73.58. URL https://link.aps.org/doi/10.1103/PhysRevLett.73.58.

E. Knill, Laflamme, R., and G. Milburn. A scheme for efficient quantum computation with linear optics. *Nature*, 409:46–52, 2001. URL https://doi.org/10.1038/35051009.

N. J. Cerf, C. Adami, and P. G. Kwiat. Optical simulation of quantum logic. *Phys. Rev. A*, 57:R1477–R1480, Mar 1998. doi: 10.1103/PhysRevA.57.R1477. URL https://link.aps.org/doi/10.1103/PhysRevA.57.R1477.

John F. Clauser and Jonathan P. Dowling. Factoring integers with young's n-slit interferometer. *Phys. Rev. A*, 53:4587–4590, Jun 1996. doi: 10.1103/PhysRevA.53.4587. URL https://link.aps.org/doi/10.1103/PhysRevA.53.4587.

Johann Summhammer. Factoring and fourier transformation with a mach-zehnder interferometer. *Phys. Rev. A*, 56:4324–4326, Nov 1997. doi: 10.1103/PhysRevA.56.4324. URL https://link.aps.org/doi/10.1103/PhysRevA.56.4324.

Erfan Khoram, Ang Chen, Dianjing Liu, Lei Ying, Qiqi Wang, Ming Yuan, and Zongfu Yu. Nanophotonic media for artificial neural inference. *Photon. Res.*, 7(8):823–827, Aug 2019. doi: 10.1364/PRJ.7.000823. URL http://www.osapublishing.org/prj/abstract.cfm?URI=prj-7-8-823.

Richard Phillips Feynman, Robert Benjamin Leighton, and Matthew Sands. *The Feynman lectures on physics; New millennium ed.* Basic Books, New York, NY, 2010. URL https://cds.cern.ch/record/1494701. Originally published 1963-1965.

L. D. Landau and L. M. Lifshitz. *Quantum Mechanics Non-Relativistic Theory, Third Edition: Volume 3*. Butterworth-Heinemann, 3 edition, January 1981. ISBN 0750635398. URL http://www.worldcat.org/isbn/0750635398.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv*, 2017.

J. Sun, F. Zhao, C. Wang, and S. Chen. Identifying and correcting mislabeled training instances. In *Future Generation Communication and Networking (FGCN 2007)*, volume 1, pages 244–250, 2007.