On the Decision Boundaries of Neural Networks. A Tropical Geometry Perspective

Abstract

This work tackles the problem of characterizing and understanding the decision boundaries of neural networks with piecewise linear non-linearity activations. We use tropical geometry, a new development in the area of algebraic geometry, to characterize the decision boundaries of a simple network of the form (Affine, ReLU, Affine). Our main finding is that the decision boundaries are a subset of a tropical hypersurface, which is intimately related to a polytope formed by the convex hull of two zonotopes. The generators of these zonotopes are functions of the network parameters. This geometric characterization provides new perspectives to three tasks. Specifically, we propose a new tropical perspective to the lottery ticket hypothesis, where we view the effect of different initializations on the tropical geometric representation of a network's decision boundaries. Moreover, we propose new tropical based optimization problems that directly influence the decision boundaries of the network for the tasks of network pruning (removing network parameters not contributing to the tropical geometric representation of the decision boundaries) and the generation of adversarial attacks.[1]

1 Introduction

Deep Neural Networks (DNNs) have demonstrated outstanding performance across a variety of research domains, including computer vision (Krizhevsky et al., 2012), speech recognition (Hinton et al., 2012), natural language processing (Bahdanau et al., 2015; Devlin et al., 2018), quantum chemistry Schütt et al. (2017), and healthcare (Ardila et al., 2019; Zhou et al., 2019) to name a few (LeCun et al., 2015). Nevertheless, a rigorous interpretation of their success remains elusive (Shalev-Shwartz & Ben-David, 2014). For instance, and in an attempt to uncover the expressive power of DNNs, the work of Montufar et al. (2014) studied the complexity of functions computable by DNNs that have piecewise linear activations. They derived a lower bound on the maximum number of linear regions. Several other works have followed to improve such estimates under certain assumptions (Arora et al., 2018). In addition, and in attempt to understand some of the subtle behaviours DNNs exhibit, *e.g.* the sensitive reaction of DNNs to small input perturbations, several works directly investigated the decision boundaries induced by a DNN for classification. The work of Moosavi-Dezfooli et al. (2019) showed that the smoothness of these decision boundaries and their curvature can play a vital role in network robustness. Moreover, the expressiveness of these decision boundaries at perturbed inputs was studied in He et al. (2018a), where it was shown that these boundaries do not resemble the boundaries around benign inputs. The work of Li et al. (2018) showed that under certain assumptions, the decision boundaries of the last fully connected layer of DNNs will converge to a linear SVM. Also, Beise et al. (2018) showed that the decision regions of DNNs with width smaller than the input dimension are unbounded.

More recently, and due to the popularity of the piecewise linear ReLU as an activation function, there has been a surge in the number of works that study this class of DNNs in particular. As a result, this has incited significant interest in new mathematical tools that help analyze piecewise linear functions, such as tropical geometry. While tropical geometry has shown its potential in many applications such as dynamic programming (Joswig & Schröter, 2019), linear programming (Allamigeon et al., 2015), multi-objective discrete optimization (Joswig & Loho, 2019), enumerative geometry (Mikhalkin, 2004), and economics (Akian et al., 2009; Mai Tran & Yu, 2015), it has only been recently used

---

[1]Code regenerating all our experiments is attached in the supplementary material.

to analyze DNNs. For instance, the work of Zhang et al. (2018) showed an equivalency between the family of DNNs with piecewise linear activations and integer weight matrices and the family of tropical rational maps, *i.e.* ratio between two multi-variate polynomials in tropical algebra. This study was mostly concerned about characterizing the complexity of a DNN by counting the number of linear regions, into which the function represented by the DNN can divide the input space. This was done by counting the number of vertices of a polytope representation recovering the results of Montufar et al. (2014) with a simpler analysis. More recently, Smyrnis & Maragos (2019) leveraged this equivalency to propose a heuristic for neural network minimization through approximating the tropical rational map.

Contributions. In this paper, we take the results of Zhang et al. (2018) several steps further and present a novel perspective on the decision boundaries of DNNs using tropical geometry. To that end, our contributions are three-fold. **(i)** We derive a geometric representation (convex hull between two zonotopes) for a super set to the decision boundaries of a DNN in the form (Affine, ReLU, Affine). **(ii)** We demonstrate a support for the lottery ticket hypothesis (Frankle & Carbin, 2019) from a geometric perspective. **(iii)** We leverage the geometric representation of the decision boundaries, referred to as the decision boundaries polytope, in two interesting applications: network pruning and adversarial attacks. For *tropical pruning*, we design a geometrically inspired optimization to prune the parameters of a given network such that the decision boundaries polytope of the pruned network does not deviate too much from its original network counterpart. We conduct extensive experiments with AlexNet (Krizhevsky et al., 2012) and VGG16 (Simonyan & Zisserman, 2014) on SVHN (Netzer et al., 2011), CIFAR10, and CIFAR 100 (Krizhevsky & Hinton, 2009) datasets, in which 90% pruning rate is achieved with a marginal drop in testing accuracy. For *tropical adversarial attacks*, we show that one can construct input adversaries that can change network predictions by perturbing the decision boundaries polytope.

2 PRELIMINARIES TO TROPICAL GEOMETRY

For completeness, we first provide preliminaries to tropical geometry (Itenberg et al., 2009; Maclagan & Sturmfels, 2015).

Definition 1. *(Tropical Semiring[2]) The tropical semiring $\mathbb{T}$ is the triplet $\{\mathbb{R} \cup \{-\infty\}, \oplus, \odot\}$, where $\oplus$ and $\odot$ define tropical addition and tropical multiplication, respectively. They are denoted as:*

$$x \oplus y = \max\{x, y\}, \qquad x \odot y = x + y, \qquad \forall x, y \in \mathbb{T}.$$

It can be readily shown that $-\infty$ is the additive identity and 0 is the multiplicative identity.

Given the previous definition, a tropical power can be formulated as $x^{\odot a} = x \odot x \cdots \odot x = a.x$, for $x \in \mathbb{T}$, $a \in \mathbb{N}$, where $a.x$ is standard multiplication. Moreover, a tropical quotient can be defined as: $x \oslash y = x - y$, where $x - y$ is standard subtraction. For ease of notation, we write $x^{\odot a}$ as x^a.

Definition 2. *(Tropical Polynomials) For $\mathbf{x} \in \mathbb{T}^d$, $c_i \in \mathbb{R}$ and $\mathbf{a}_i \in \mathbb{N}^d$, a d-variable tropical polynomial with n monomials $f : \mathbb{T}^d \to \mathbb{T}^d$ can be expressed as:*

$$f(\mathbf{x}) = (c_1 \odot \mathbf{x}^{\mathbf{a}_1}) \oplus (c_2 \odot \mathbf{x}^{\mathbf{a}_2}) \oplus \cdots \oplus (c_n \odot \mathbf{x}^{\mathbf{a}_n}), \qquad \forall \ \mathbf{a}_i \neq \mathbf{a}_j \ \text{when} \ i \neq j.$$

We use the more compact vector notation $\mathbf{x}^{\mathbf{a}} = x_1^{a_1} \odot x_2^{a_2} \cdots \odot x_d^{a_d}$. Moreover and for ease of notation, we will denote $c_i \odot \mathbf{x}^{\mathbf{a}_i}$ as $c_i \mathbf{x}^{\mathbf{a}_i}$ throughout the paper.

Definition 3. *(Tropical Rational Functions) A tropical rational is a standard difference or a tropical quotient of two tropical polynomials: $f(\mathbf{x}) - g(\mathbf{x}) = f(\mathbf{x}) \oslash g(\mathbf{x})$.*

Algebraic curves or hypersurfaces in algebraic geometry, which are the solution sets to polynomials, can be analogously extended to tropical polynomials too.

Definition 4. *(Tropical Hypersurfaces) A tropical hypersurface of a tropical polynomial $f(\mathbf{x}) = c_1 \mathbf{x}^{\mathbf{a}_1} \oplus \cdots \oplus c_n \mathbf{x}^{\mathbf{a}_n}$ is the set of points $\mathbf{x}$ where f is attained by two or more monomials in f, i.e.*

$$\mathcal{T}(f) := \{\mathbf{x} \in \mathbb{R}^d : c_i \mathbf{x}^{\mathbf{a}_i} = c_j \mathbf{x}^{\mathbf{a}_j} = f(\mathbf{x}), \ \text{for some} \ \mathbf{a}_i \neq \mathbf{a}_j\}.$$

Tropical hypersurfaces divide the domain of f into convex regions, where f is linear in each region. Also, every tropical polynomial can be associated with a Newton polytope.

---

[2]A semiring is a ring that lacks an additive inverse.

Figure 1: **Tropical Hypersurfaces and their Corresponding Dual Subdivisions.** We show three tropical polynomials, where the solid red and black lines are the tropical hypersurfaces $\mathcal{T}(f)$ and dual subdivisions $\delta(f)$ to the corresponding tropical polynomials, respectively. $\mathcal{T}(f)$ divides The domain of f into convex regions where f is linear. Moreover, each region is in one-to-one correspondence with each node of $\delta(f)$. Lastly, the tropical hypersurfaces are parallel to the normals of the edges of $\delta(f)$ shown by dashed red lines.

Definition 5. *(Newton Polytopes) The Newton polytope of a tropical polynomial $f(\mathbf{x}) = c_1\mathbf{x}^{\mathbf{a}_1} \oplus \cdots \oplus c_n\mathbf{x}^{\mathbf{a}_n}$ is the convex hull of the exponents $\mathbf{a}_i \in \mathbb{N}^d$ regarded as points in $\mathbb{R}^d$, i.e.*

$$\Delta(f) := ConvHull\{\mathbf{a}_i \in \mathbb{R}^d : i = 1, \ldots, n \text{ and } c_i \neq -\infty\}.$$

A tropical polynomial determines a dual subdivision, which can be constructed by projecting the collection of upper faces (UF) in $\mathcal{P}(f) := \text{ConvHull}\{(\mathbf{a}_i, c_i) \in \mathbb{R}^d \times \mathbb{R} : i = 1, \ldots, n\}$ onto $\mathbb{R}^d$. That is to say, the dual subdivision determined by f is given as $\delta(f) := \{\pi(p) \subset \mathbb{R}^d : p \in \text{UF}(\mathcal{P}(f))\}$, where $\pi : \mathbb{R}^d \times \mathbb{R} \to \mathbb{R}^d$ is the projection that drops the last coordinate. It has been shown by Maclagan & Sturmfels (2015) that the tropical hypersurface $\mathcal{T}(f)$ is the $(d-1)$-skeleton of the polyhedral complex dual to $\delta(f)$. This implies that each node of the dual subdivision $\delta(f)$ corresponds to one region in $\mathbb{R}^d$ where f is linear. This is exemplified in Figure 1 with three tropical polynomials, and to see this clearly, we will elaborate on the first tropical polynomial example $f(x, y) = x \oplus y \oplus 0$. Note that as per Definition 4, the tropical hypersurface is the set of points (x, y) where $x = y, y = 0$, and $x = 0$. This indeed gives rise to the three solid red lines indicating the tropical hypersurfaces. As for the dual subdivision $\delta(f)$, we observe that $x \oplus y \oplus 0$ can be written as $(x^1 \odot y^0) \oplus (x^0 \odot y^1) \oplus (x^0 \odot y^0)$. Thus, and since the monomials are bias free ($c_i = 0$), then $\mathcal{P}(f) = \text{ConvHull}\{(1, 0, 0), (0, 1, 0), (0, 0, 0)\}$. It is then easy to see that $\delta(f) = \text{ConvHull}\{(1, 0), (0, 1), (0, 0)\}$, since $\text{UP}(\mathcal{P}(f)) = \mathcal{P}(f)$, which is the black triangle in solid lines in Figure 1. One key observation in all three examples in Figure 1 is that the number of regions where f is linear (that is 3, 6 and 10, respectively) is equal to the number of nodes in the corresponding dual subdivisions. Second, the tropical hypersurfaces are parallel to the normals to the edges of the dual subdivision polytope. This observation will be essential for the remaining part of the paper. Several other observations are summarized by Brugallé & Shaw (2014). Moreover, Zhang et al. (2018) showed an equivalency between tropical rational maps and a family of neural network $f : \mathbb{R}^n \to \mathbb{R}^k$ with piecewise linear activations through the following theorem.

Theorem 1. *(Tropical Characterization of Neural Networks, (Zhang et al., 2018)). A feedforward neural network with integer weights and real biases with piecewise linear activation functions is a function $f : \mathbb{R}^n \to \mathbb{R}^k$, whose coordinates are tropical rational functions of the input, i.e., $f(\mathbf{x}) = H(\mathbf{x}) \oslash Q(\mathbf{x}) = H(\mathbf{x}) - Q(\mathbf{x})$, where H and Q are tropical polynomials.*

While this is new in the context of tropical geometry, it is not surprising, since any piecewise linear function can be written as a difference of two max functions over a set of hyperplanes (Melzer, 1986).

3 DECISION BOUNDARIES OF NEURAL NETWORKS AS POLYTOPES[3]

In this section, we analyze the decision boundaries of a network in the form (Affine, ReLU, Affine) using tropical geometry. For ease, we use ReLUs as the non-linear activation, but any other piecewise linear function can also be used. The functional form of this network is: $f(\mathbf{x}) = \mathbf{B}\max(\mathbf{A}\mathbf{x} + \mathbf{c}_1, \mathbf{0}) + \mathbf{c}_2$, where $\max(.)$ is an element-wise operator. The outputs of the network f are the logit scores. Throughout this section, we assume[4] that $\mathbf{A} \in \mathbb{Z}^{p \times n}$, $\mathbf{B} \in \mathbb{Z}^{2 \times p}$, $\mathbf{c}_1 \in \mathbb{R}^p$ and $\mathbf{c}_2 \in \mathbb{R}^2$. For ease of notation, we only consider networks with two outputs, *i.e.* $\mathbf{B}^{2 \times p}$, where the extension to a multi-class output follows naturally and is discussed in the **appendix**. Now,

---

[3]All proofs are left for the **appendix**.

[4]Without loss of generality, as one can very well approximate real weights as fractions and multiply by the least common multiple of the denominators as discussed in Zhang et al. (2018).

Figure 2: Decision Boundaries as Geometric Structures. The decision boundaries $\mathcal{B}$ (in red) comprise two linear pieces separating classes $\mathcal{C}_1$ and $\mathcal{C}_2$. As per Theorem 2, the dual subdivision of this single hidden neural network is the convex hull between the zonotopes $\mathcal{Z}_{\mathbf{G}_1}$ and $\mathcal{Z}_{\mathbf{G}_2}$. The normals to the dual subdivison $\delta(R(\mathbf{x}))$ are in one-to-one correspondence to the tropical hypersurface $\mathcal{T}(R(\mathbf{x}))$, which is a superset to the decision boundaries $\mathcal{B}$. Note that some of the normals to $\delta(R(\mathbf{x}))$ (in red) are parallel to the decision boundaries.

since f is a piecewise linear function, each output can be expressed as a tropical rational as per Theorem 1. If f_1 and f_2 refer to the first and second outputs respectively, we have $f_1(\mathbf{x}) = H_1(\mathbf{x}) \oslash Q_1(\mathbf{x})$ and $f_2(\mathbf{x}) = H_2(\mathbf{x}) \oslash Q_2(\mathbf{x})$, where H_1, H_2, Q_1 and Q_2 are tropical polynomials. In what follows and for ease of presentation, we present our main results where the network f has no biases, *i.e.* $\mathbf{c}_1 = \mathbf{0}$ and $\mathbf{c}_2 = \mathbf{0}$, and we leave the generalization to the **appendix**.

Theorem 2. *For a bias-free neural network in the form $f(\mathbf{x}) : \mathbb{R}^n \to \mathbb{R}^2$, where $\mathbf{A} \in \mathbb{Z}^{p \times n}$ and $\mathbf{B} \in \mathbb{Z}^{2 \times p}$, let $R(\mathbf{x}) = H_1(\mathbf{x}) \odot Q_2(\mathbf{x}) \oplus H_2(\mathbf{x}) \odot Q_1(\mathbf{x})$ be a tropical polynomial. Then:*

- *Let $\mathcal{B} = \{\mathbf{x} \in \mathbb{R}^n : f_1(\mathbf{x}) = f_2(\mathbf{x})\}$ define the decision boundaries of f, then $\mathcal{B} \subseteq \mathcal{T}(R(\mathbf{x}))$.*

- *$\delta(R(\mathbf{x})) = \text{ConvHull}(\mathcal{Z}_{\mathbf{G}_1}, \mathcal{Z}_{\mathbf{G}_2})$. $\mathcal{Z}_{\mathbf{G}_1}$ is a zonotope in $\mathbb{R}^n$ with line segments $\{(\mathbf{B}^+(1,j) + \mathbf{B}^-(2,j))[\mathbf{A}^+(j,:), \mathbf{A}^-(j,:)]\}_{j=1}^p$ and shift $(\mathbf{B}^-(1,:) + \mathbf{B}^+(2,:))\mathbf{A}^-$, where $\mathbf{A}^+ = \max(\mathbf{A}, 0)$ and $\mathbf{A}^- = \max(-\mathbf{A}, 0)$. $\mathcal{Z}_{\mathbf{G}_2}$ is a zonotope in $\mathbb{R}^n$ with line segments $\{(\mathbf{B}^-(1,j) + \mathbf{B}^+(2,j))[\mathbf{A}^+(j,:), \mathbf{A}^-(j,:)]\}_{j=1}^p$ and shift $(\mathbf{B}^+(1,:) + \mathbf{B}^-(2,:))\mathbf{A}^-$.*

Before any further discussion, we first recap the definition of zonotopes.

Definition 6. *Let $\mathbf{u}^1, \ldots, \mathbf{u}^p \in \mathbb{R}^n$. The zonotope formed by $\mathbf{u}^1, \ldots, \mathbf{u}^p$ is defined as $\mathcal{Z}(\mathbf{u}^1, \ldots, \mathbf{u}^p) := \{\sum_{i=1}^p x_i \mathbf{u}^i : 0 \leq x_i \leq 1\}$. Equivalently, $\mathcal{Z}$ can be expressed with respect to the generator matrix $\mathbf{U} \in \mathbb{R}^{p \times n}$, where $\mathbf{U}(i,:) = \mathbf{u}^{i^\top}$ as $\mathcal{Z}_{\mathbf{U}} := \{\mathbf{U}^\top \mathbf{x} : \forall \mathbf{x} \in [0,1]^p\}$.*

Another common definition for a zonotope is the Minkowski sum of the set of line segments $\{\mathbf{u}^1, \ldots, \mathbf{u}^p\}$ (refer to **appendix**), where a line segment of the vector $\mathbf{u}^i$ in $\mathbb{R}^n$ is defined as $\{\alpha \mathbf{u}^i : \forall \alpha \in [0,1]\}$. It is well-known that the number of vertices of a zonotope is polynomial in the number of line segments, *i.e.* $|\text{vert}(\mathcal{Z}_{\mathbf{U}})| \leq 2\sum_{i=0}^{n-1}\binom{p-1}{i} = \mathcal{O}(p^{n-1})$ (Gritzmann & Sturmfels, 1993).

Digesting Theorem 2. This theorem aims at characterizing the decision boundaries (where $f_1(\mathbf{x}) = f_2(\mathbf{x})$) of a bias-free neural network of the form (Affine, ReLU, Affine) through the lens of tropical geometry. In particular, the first result of Theorem 2 states that the tropical hypersurface $\mathcal{T}(R(\mathbf{x}))$ of the tropical polynomial $R(\mathbf{x})$ is a superset to the set of points forming the decision boundaries, *i.e.* $\mathcal{B}$. Just as discussed earlier and exemplified in Figure 1, tropical hypersurfaces are associated with a corresponding dual subdivision polytope $\delta(R(\mathbf{x}))$. Based on this, the second result of Theorem 2 states that this dual subdivision is precisely the convex hull of two zonotopes denoted as $\mathcal{Z}_{G_1}$ and $\mathcal{Z}_{G_2}$, where each zonotope is only a function of the network parameters $\mathbf{A}$ and $\mathbf{B}$.

Theorem 2 bridges the gap between the behaviour of the decision boundaries $\mathcal{B}$, through the superset $\mathcal{T}(R(\mathbf{x}))$, and the polytope $\delta(R(\mathbf{x}))$, which is the convex hull of two zonotopes. It is worthwhile to mention that Zhang et al. (2018) discussed a special case of the first part of Theorem 2 for a neural network with a single output and a score function $s(\mathbf{x})$ to classify the output. To the best of our knowledge, this work is the first to propose a tropical geometric formulation of a superset containing the decision boundaries of a multi-class classification neural network. In particular, the first result of Theorem 2 states that one can perhaps study the decision boundaries, $\mathcal{B}$, directly by studying their superset $\mathcal{T}(R(\mathbf{x}))$. While studying $\mathcal{T}(R(\mathbf{x}))$ can be equally difficult, the second result of Theorem 2 comes in handy. First, note that, since the network is bias-free, π becomes an identity mapping with $\delta(R(\mathbf{x})) = \Delta(R(\mathbf{x}))$, and thus the dual subdivision $\delta(R(\mathbf{x}))$, which is the Newton polytope $\Delta(R(\mathbf{x}))$ in this case, becomes a well-structured geometric object that can be exploited to preserve decision boundaries as per the second part of Theorem 2. Now, based on the results of Maclagan & Sturmfels (2015) (Proposition 3.1.6) and as discussed in Figure 1, the normals to the edges of the polytope $\delta(R(\mathbf{x}))$ (convex hull of two zonotopes) are in one-to-one correspondence with the tropical

Figure 3: **Effect of Different Initializations on the Decision Boundaries Polytope.** From left to right: training dataset, decision boundaries polytope of original network (before pruning), followed by the decision boundaries polytope for networks pruned at different pruning percentages using different initializations. Note that in the original polytope there are many more vertices than just 4, but they are very close to each other forming many small edges that are not visible in the figure.

hypersurface $\mathcal{T}(R(\mathbf{x}))$. Therefore, one can study the decision boundaries, or at least their superset $\mathcal{T}(R(\mathbf{x}))$, by studying the orientation of the dual subdivision $\delta(R(\mathbf{x}))$.

While Theorem 2 presents a strong relation between a polytope (convex hull of two zonotopes) and the decision boundaries, it remains unclear how such a polytope can be efficiently constructed. Although the number of vertices of a zonotope is polynomial in the number of its generating line segments, fast algorithms for enumerating these vertices are still restricted to zonotopes with line segments starting at the origin Stinson et al. (2016). Since the line segments generating the zonotopes in Theorem 2 have arbitrary end points, we present the next result that transforms these line segments into a generator matrix of line segments starting from the origin as in Definition 6. This result is essential for an efficient computation of the zonotopes in Theorem 2.

Proposition 1. *The zonotope formed by p line segments in $\mathbb{R}^n$ with arbitrary end points $\{[\mathbf{u}_1^i, \mathbf{u}_2^i]\}_{i=1}^p$ is equivalent to the zonotope formed by the line segments $\{[\mathbf{u}_1^i - \mathbf{u}_2^i, \mathbf{0}]\}_{i=1}^p$ with a shift of $\sum_{i=1}^p \mathbf{u}_2^i$.*

We can now represent with the following corollary the arbitrary end point line segments forming the zonotopes in Theorem 2 with generator matrices, which allow us to leverage existing algorithms that enumerate zonotope vertices Stinson et al. (2016).

Corollary 1. *The generators of $\mathcal{Z}_{\mathbf{G}_1}, \mathcal{Z}_{\mathbf{G}_2}$ in Theorem 2 can be defined as $\mathbf{G}_1 = Diag[(\mathbf{B}^+(1,:)) + (\mathbf{B}^-(2,:))]\mathbf{A}$ and $\mathbf{G}_2 = Diag[(\mathbf{B}^+(2,:)) + (\mathbf{B}^-(1,:))]\mathbf{A}$, both with shift $(\mathbf{B}^-(1,:) + \mathbf{B}^+(2,:) + \mathbf{B}^+(1,:) + \mathbf{B}^-(2,:)) \mathbf{A}^-$, where $Diag(\mathbf{v})$ arranges $\mathbf{v}$ in a diagonal matrix.*

Next, we show several applications for Theorem 2 by leveraging the tropical geometric structure.

4 TROPICAL PERSPECTIVE TO THE LOTTERY TICKET HYPOTHESIS

The lottery ticket hypothesis was recently proposed by Frankle & Carbin (2019), in which the authors surmise the existence of sparse trainable sub-networks of dense, randomly-initialized, feed-forward networks that when trained in isolation perform as well as the original network in a similar number of iterations. To find such sub-networks, Frankle & Carbin (2019) propose the following simple algorithm: perform standard network pruning, initialize the pruned network with the same initialization that was used in the original training setting, and train with the same number of epochs. They hypothesize that this results in a smaller network with a similar accuracy. In other words, a sub-network can have decision boundaries similar to those of the original larger network. While we do not provide a theoretical reason why this pruning algorithm performs favorably, we utilize the geometric structure that arises from Theorem 2 to reaffirm such behaviour. In particular, we show that the orientation of the dual subdivision $\delta(R(\mathbf{x}))$ (referred to as decision boundaries polytope), where the normals to its edges are parallel to $\mathcal{T}(R(\mathbf{x}))$ that is a superset to the decision boundaries, is preserved after pruning with the proposed initialization algorithm of Frankle & Carbin (2019). Conversely, pruning with a different initialization at each iteration results in a significant variation in the orientation of the decision boundaries polytope and ultimately in reduced accuracy.

To this end, we train a neural network with 2 inputs ($n = 2$), 2 outputs, and a single hidden layer with 40 nodes ($p = 40$). We then prune the network by removing the smallest $x\%$ of the weights. The pruned network is then trained using different initializations: (i) the same initialization as the original network (Frankle & Carbin, 2019), (ii) Xavier (Glorot & Bengio, 2010), (iii) standard Gaussian, and (iv) zero mean Gaussian with variance 0.1. Figure 3 shows the decision boundaries polytope, *i.e.* $\delta(R(\mathbf{x}))$, as we perform more pruning (increasing the $x\%$) with different initializations. First, we show the decision boundaries by sampling and classifying points in a grid with the trained network

(first subfigure). We then plot the decision boundaries polytope $\delta(R(\mathbf{x}))$ as per the second part of Theorem 2 denoted as original polytope (second subfigure). While there are many overlapping vertices in the original polytope, the normals to some of the edges (the major visible edges) are parallel to the decision boundaries shown in the first subfigure of Figure 3. We later show the decision boundaries polytope for the same network under different levels of pruning. One can observe that the orientation of $\delta(R(\mathbf{x}))$ for all different initialization schemes deviates much more from the original polytope as compared to the lottery ticket initialization. This gives an indication that lottery ticket initialization indeed preserves the decision boundaries, since it preserves the orientation of the decision boundaries polytope throughout the evolution of pruning. An alternative means to study the lottery ticket could be to directly observe the polytopes representing the functional form of the network, *i.e.* $\delta(H_{\{1,2\}}(\mathbf{x}))$ and $\delta(Q_{\{1,2\}}(\mathbf{x}))$, in lieu of the decision boundaries polytopes. However, this strategy may fail to provide a conclusive analysis of the lottery ticket, since there can exist multiple polytopes $\delta(H_{\{1,2\}}(\mathbf{x}))$ and $\delta(Q_{\{1,2\}}(\mathbf{x}))$ for networks with the same decision boundaries. This highlights the importance of studying the decision boundaries directly. Additional discussions and experiments are left for the **appendix**.

5 TROPICAL NETWORK PRUNING

Network pruning has been identified as an effective approach to reduce the computational cost and memory usage during network inference. While it dates back to the work of LeCun et al. (1990) and Hassibi & Stork (1993), network pruning has recently gained more attention. This is due to the fact that most neural networks over-parameterize commonly used datasets. In network pruning, the task is to find a smaller subset of the network parameters, such that the resulting smaller network has similar decision boundaries (and thus supposedly similar accuracy) to the original over-parameterized network. In this section, we show a new geometric approach towards network pruning. In particular and as indicated by Theorem 2, preserving the polytope $\delta(R(\mathbf{x}))$ preserves a superset to the decision boundaries, $\mathcal{T}(R(\mathbf{x}))$, and thus the decision boundaries themselves.

Motivational Insight. For a single hidden layer neural network, the dual subdivision to the decision boundaries is the polytope that is the convex hull of two zonotopes, where each is formed by taking the Minkowski sum of line segments (Theorem 2). Figure 4 shows an example, where pruning a neuron in the network has no effect on the dual subdivision polytope and hence no effect on performance. This occurs, since the tropical hypersurface $\mathcal{T}(R(\mathbf{x}))$ before and after pruning is preserved, thus, keeping the decision boundaries the same.

Problem Formulation. In light of the motivational insight, a natural question arises: *Given an over-parameterized binary output neural network $f(\mathbf{x}) = \mathbf{B} \max(\mathbf{A}\mathbf{x}, \mathbf{0})$, can one construct a new neural network, parameterized by sparser weight matrices $\tilde{\mathbf{A}}$ and $\tilde{\mathbf{B}}$, such that this smaller network has a dual subdivision $\delta(\tilde{R}(\mathbf{x}))$ that preserves the decision boundaries of the original network?*

To address this question, we propose the following optimization problem to compute $\tilde{\mathbf{A}}$ and $\tilde{\mathbf{B}}$:

$$\min_{\tilde{\mathbf{A}}, \tilde{\mathbf{B}}} d\Big(\delta(\tilde{R}(\mathbf{x})), \delta(R(\mathbf{x}))\Big) = \min_{\tilde{\mathbf{A}}, \tilde{\mathbf{B}}} d\Big(\text{ConvHull}\left(\mathcal{Z}_{\tilde{\mathbf{G}}_1}, \mathcal{Z}_{\tilde{\mathbf{G}}_2}\right), \text{ConvHull}\left(\mathcal{Z}_{\mathbf{G}_1}, \mathcal{Z}_{\mathbf{G}_2}\right)\Big). \quad (1)$$

The function $d(.)$ defines a distance between two geometric objects. Since the generators $\tilde{\mathbf{G}}_1$ and $\tilde{\mathbf{G}}_2$ are functions of $\tilde{\mathbf{A}}$ and $\tilde{\mathbf{B}}$ (as per Theorem 2), this optimization problem can be challenging to solve. However, for pruning purposes, one can observe from Theorem 2 that if the generators $\tilde{\mathbf{G}}_1$ and $\tilde{\mathbf{G}}_2$ had fewer number of line segments (rows), this corresponds to a fewer number of rows in the weight matrix $\tilde{\mathbf{A}}$ (sparser weights). So, we observe that if $\tilde{\mathbf{G}}_1 \approx \mathbf{G}_1$ and $\tilde{\mathbf{G}}_2 \approx \mathbf{G}_2$, then $\delta(\tilde{R}(\mathbf{x})) \approx \delta(R(\mathbf{x}))$, and thus the decision boundaries tend to be preserved as a consequence. Therefore, we propose the following optimization problem as a surrogate to the one in Problem (1):

$$\min_{\tilde{\mathbf{A}}, \tilde{\mathbf{B}}} \frac{1}{2}\Big(\left\|\tilde{\mathbf{G}}_1 - \mathbf{G}_1\right\|_F^2 + \left\|\tilde{\mathbf{G}}_2 - \mathbf{G}_2\right\|_F^2\Big) + \lambda_1 \left\|\tilde{\mathbf{G}}_1\right\|_{2,1} + \lambda_2 \left\|\tilde{\mathbf{G}}_2\right\|_{2,1}. \quad (2)$$

The matrix mixed norm for $\mathbf{C} \in \mathbb{R}^{n \times k}$ is defined as $\|\mathbf{C}\|_{2,1} = \sum_{i=1}^{n} \|\mathbf{C}(i,:)\|_2$, which encourages the matrix $\mathbf{C}$ to be row sparse, *i.e.* complete rows of $\mathbf{C}$ are zero. The first two terms in Problem (2) aim at approximating the original dual subdivision $\delta(R(\mathbf{x}))$ by approximating the underlying generator matrices, $\mathbf{G}_1$ and $\mathbf{G}_2$. This aims to preserve the orientation of the decision boundaries of the newly constructed network. On the other hand, the second two terms in Problem (2) act

Figure 4: **Tropical Pruning Pipeline.** Pruning the 4^{th} node, or equivalently removing the two yellow vertices of zonotope $\mathcal{Z}_{G_2}$ does not affect the decision boundaries polytope, which will lead to no change in accuracy.

as regularizers to control the sparsity of the constructed network by controlling the sparsity in the number of line segments. We observe that Problem (2) is not quadratic in its variables, since as per Corollary, 1 $\tilde{\mathbf{G}}_1 = \text{Diag}[\text{ReLU}(\tilde{\mathbf{B}}(1,:)) + \text{ReLU}(-\tilde{\mathbf{B}}(2,:))]\tilde{\mathbf{A}}$ and $\tilde{\mathbf{G}}_2 = \text{Diag}[\text{ReLU}(\tilde{\mathbf{B}}(2,:)) + \text{ReLU}(-\tilde{\mathbf{B}}(1,:))]\tilde{\mathbf{A}}$. However, since Problem (2) is separable in the rows of $\tilde{\mathbf{A}}$ and $\tilde{\mathbf{B}}$, we solve Problem (2) via alternating optimization over these rows, where each sub-problem can be shown to be convex and exhibits a closed-form solution leading to a very efficient solver. For ease of notation, we refer to $\text{ReLU}(\tilde{\mathbf{B}}(i,:))$ and $\text{ReLU}(-\tilde{\mathbf{B}}(i,:))$ as $\tilde{\mathbf{B}}^+(i,:)$ and $\tilde{\mathbf{B}}^-(i,:)$, respectively. As such, the per row update for $\tilde{\mathbf{A}}$ (first linear layer) is given as follows:

$$\tilde{\mathbf{A}}(i,:) = \max\left(1 - \frac{1}{2}\frac{\lambda_1\sqrt{\mathbf{c}_1^i} + \lambda_2\sqrt{\mathbf{c}_2^i}}{\frac{1}{2}(\mathbf{c}_1^i + \mathbf{c}_2^i)}\frac{1}{\left\|\frac{\mathbf{c}_1^i\mathbf{G}_1(i,:)+\mathbf{c}_2^i\mathbf{G}_2(i,:)}{\frac{1}{2}(\mathbf{c}_1^i+\mathbf{c}_2^i)}\right\|_2}, 0\right)\left(\frac{\mathbf{c}_1^i\mathbf{G}_1(i,:) + \mathbf{c}_2^i\mathbf{G}_2(i,:)}{\frac{1}{2}(\mathbf{c}_1^i + \mathbf{c}_2^i)}\right),$$

where $\mathbf{c}_1^i$ is the i^{th} element of $\mathbf{c}_1 = \text{ReLU}(\mathbf{B}(1,:)) + \text{ReLU}(-\mathbf{B}(2,:))$ and $\mathbf{c}_2 = \text{ReLU}(\mathbf{B}(2,:)) + \text{ReLU}(-\mathbf{B}(1,:))$. Similarly, the closed form update for the j^{th} element of the second linear layer is as follows:

$$\tilde{\mathbf{B}}^+(1,j) = \max\left(0, \frac{\tilde{\mathbf{A}}(j,:)^\top\tilde{\mathbf{G}}_{1+}(j,:) - \lambda\|\tilde{\mathbf{A}}(j,:)\|_2}{\|\tilde{\mathbf{A}}(j,:)\|_2^2}\right),$$

where $\mathbf{G}_{1+} = \text{Diag}(\mathbf{B}^+(1,:))\mathbf{A}$. A similar argument can be used to update the variables $\tilde{\mathbf{B}}^+(2,:)$, $\tilde{\mathbf{B}}^-(1,:)$, and $\tilde{\mathbf{B}}^-(2,:)$. The details of deriving the aforementioned update steps and the extension to the multi-class case are left to the **appendix**. Note that all updates are cheap, as they are expressed in a closed form single step. In all subsequent experiments, we find that running the alternating optimization for a single iteration is sufficient to converge to a reasonable solution, thus, leading to a very efficient overall solver.

Extension to Deeper Networks. While the theoretical results in Theorem 2 and Corollary 1 only hold for a shallow network in the form of (Affine, ReLU, Affine), we propose a greedy heuristic to prune much deeper networks by applying the aforementioned optimization for consecutive blocks of (Affine, ReLU, Affine) starting from the input and ending at the output of the network. This extension from a theoretical study of 2 layer network was observed in several works such as (Bibi et al., 2018).

Experiments on Tropical Pruning. Here, we evaluate the performance of the proposed pruning approach as compared to several classical approaches on several architectures and datasets. In particular, we compare our tropical pruning approach against Class Blind (CB), Class Uniform (CU) and Class Distribution (CD) (Han et al., 2015; See et al., 2016). In Class Blind, all the parameters across all nodes of a layer are sorted by magnitude where the $x\%$ with smallest magnitude are pruned. In contrast, Class Uniform prunes the parameters with smallest $x\%$ magnitudes per node in a layer. Lastly, Class Distribution performs pruning of all parameters for each node in the layer, just as in Class Uniform, but the parameters are pruned based on the standard deviation σ_c of the magnitude of the parameters per node. Since fully connected layers in deep neural networks tend to have much higher memory complexity than convolutional layers, we restrict our focus to pruning fully connected layers. We train AlexNet and VGG16 on SVHN, CIFAR10, and CIFAR100 datasets. We observe that we can prune more than 90% of the classifier parameters for both networks without affecting the accuracy. Moreover, we demonstrate experimentally that our approach can outperform all other methods even when all parameters or when only the biases are fine-tuned after pruning. These experiments in addition to many others are left for the **appendix**.

Setup. To account for the discrepancy in input resolution, we adapt the architectures of AlexNet and VGG16, since they were originally trained on ImageNet (Deng et al., 2009). The fully connected

Figure 5: **Results of Tropical Pruning.** Pruning-accuracy plots for AlexNet (top) and VGG16 (bottom) trained on SVHN, CIFAR10, and CIFAR100, pruned with our tropical method and three other pruning methods.

layers of AlexNet and VGG16 have sizes (256,512,10) and (512,512,10) for SVHN and CIFAR10, respectively, and with the last dimension increased to 100 for CIFAR100. All networks were trained to baseline test accuracy of (92%,74%,43%) for AlexNet on SVHN, CIFAR10, and CIFAR100, respectively and (92%,92%,70%) for VGG16. To evaluate the performance of pruning and following previous work Han et al. (2015), we report the area under the curve (AUC) of the pruning-accuracy plot. The higher the AUC is, the better the trade-off is between pruning rate and accuracy. For efficiency purposes, we run the optimization in Problem 2 for a single alternating iteration to identify the rows in $\tilde{\mathbf{A}}$ and elements of $\tilde{\mathbf{B}}$ that will be pruned.

Results. Figure 4 shows the comparison between our tropical approach and the three popular pruning schemes on both AlexNet and VGG16 over the different datasets. Our proposed approach can indeed prune out as much as 90% of the parameters of the classifier without sacrificing much of the accuracy. For AlexNet, we achieve much better performance in pruning as compared to other methods. In particular, we are better in AUC by 3%, 3%, and 2% over other pruning methods on SVHN, CIFAR10 and CIFAR100, respectively. This indicates that the decision boundaries can indeed be preserved by preserving the dual subdivision polytope. For VGG16, we perform similarly well on both SVHN and CIFAR10 and slightly worse on CIFAR100. While the performance achieved here is comparable to the other pruning schemes, if not better, we emphasize that our contribution does not lie in outperforming state-of-the-art pruning methods, but in giving a new geometry-based perspective to network pruning. More experiments were conducted where only network biases or only the classifier are fine-tuned after pruning. Retraining only biases can be sufficient, as they do not contribute to the orientation of the decision boundaries polytope (and effectively the decision boundaries), but only to its translation. Discussions on biases and more results are left for the **appendix**.

Comparison Against Tropical Geometry Approaches. A recent tropical geometry inspired approach was proposed to address the problem of network pruning. In particular, Smyrnis & Maragos (2019; 2020) (SM) proposed an interesting yet heuristic algorithm to directly approximate the tropical rational by approximating the Newton polytope. For fair comparison and following the setup of SM, we train LeNet on MNIST and monitor the test accuracy as we prune its neurons. We report (neurons kept, SM, ours) triplets in (%) as follows: (100, 98.60, 98.84), (90, 95.71, 98.82), (75, 95.05, 98.8), (50, 95.52, 98.71), (25, 91.04, 98.36), (10, 92.79, 97.99), and (5, 92.93, 94.91). It is clear that tropical pruning outperforms SM by a margin that reaches 7%. This demonstrates that our theoretically motivated approach is still superior to more recent pruning approaches.

6 TROPICAL ADVERSARIAL ATTACKS

DNNs are notorious for being sensitive to imperceptible noise at their inputs referred to as adversarial attacks. Several works investigated DNNs' decision boundaries in the presence of such adversaries. For instance, Khoury & Hadfield-Menell (2018) analyzed the high dimensional geometry of adversarial examples by means of manifold reconstruction while He et al. (2018b) crafted adversarial attacks by estimating the distance to the decision boundaries using random search directions. In this work, we show how Theorem 2 can be leveraged to construct a tropical geometric adversarial attack. Due to the space limitation, we leave the extensive formulation, the algorithm to find the adversary, and the experimental results on synthetic and real datasets to the **appendix**.

REFERENCES

Marianne Akian, Stphane Gaubert, and Alexander Guterman. Tropical polyhedra are equivalent to mean payoff games. *International Journal of Algebra and Computation*, 2009.

Xavier Allamigeon, Pascal Benchimol, Stphane Gaubert, and Michael Joswig. Tropicalizing the simplex algorithm. *SIAM J. Discrete Math. 29:2*, 2015.

Diego Ardila, Atilla P. Kiraly, Sujeeth Bharadwaj, Bokyung Choi, Joshua J. Reicher, Lily Peng, Daniel Tse, Mozziyar Etemadi, Wenxing Ye, Greg Corrado, David P. Naidich, and Shravya Shetty. End-to-end lung cancer screening with three-dimensional deep learning on low-dose chest computed tomography. *Nature Medicine*, 2019.

Raman Arora, Amitabh Basu, Poorya Mianjy, and Anirbit Mukherjee. Understanding deep neural networks with rectified linear units. In *International Conference on Learning Representations*, 2018.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. In *International Conference on Learning Representations*, 2015.

Hans-Peter Beise, Steve Dias Da Cruz, and Udo Schröder. On decision regions of narrow deep neural networks. *arXiv preprint arXiv:1807.01194*, 2018.

Adel Bibi, Modar Alfadly, and Bernard Ghanem. Analytic expressions for probabilistic moments of pl-dnn with gaussian input. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9099–9107, 2018.

Erwan Brugallé and Kristin Shaw. A bit of tropical geometry. *The American Mathematical Monthly*, 2014.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Computer Vision and Patter Recognition Conference (CVPR)*, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *ICLR*. OpenReview.net, 2019.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of 13th International Conference on Artificial Intelligence and Statistics*, 2010.

Peter Gritzmann and Bernd Sturmfels. Minkowski addition of polytopes: computational complexity and applications to gröbner bases. *SIAM Journal on Discrete Mathematics*, 1993.

Song Han, Jeff Pool, John Tran, and William J. Dally. Learning both weights and connections for efficient neural networks. *CoRR*, 2015.

Babak Hassibi and David G Stork. Second order derivatives for network pruning: Optimal brain surgeon. In *Advances in neural information processing systems*, 1993.

Warren He, Bo Li, and Dawn Song. Decision boundary analysis of adversarial examples. In *International Conference on Learning Representations (ICLR)*, 2018a.

Warren He, Bo Li, and Dawn Song. Decision boundary analysis of adversarial examples. In *International Conference on Learning Representations*, 2018b.

G. Hinton, L. Deng, D. Yu, G. E. Dahl, A. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. N. Sainath, and B. Kingsbury. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 2012.

Ilia Itenberg, Grigory Mikhalkin, and Eugenii I Shustin. *Tropical algebraic geometry*. Springer Science & Business Media, 2009.

Michael Joswig and Georg Loho. Monomial tropical cones for multicriteria optimization. *AIP Conference Proceedings*, 2019.

Michael Joswig and Benjamin Schröter. The tropical geometry of shortest paths. *arXiv preprint arXiv:1904.01082*, 2019.

Marc Khoury and Dylan Hadfield-Menell. On the geometry of adversarial examples. *arXiv preprint arXiv:1811.00525*, 2018.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2012.

Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, 1990.

Yann LeCun, Y Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 2015.

Yu Li, Peter Richtarik, Lizhong Ding, and Xin Gao. On the decision boundary of deep neural networks. *arXiv preprint arXiv:1808.05385*, 2018.

D. Maclagan and B. Sturmfels. *Introduction to Tropical Geometry*. Graduate Studies in Mathematics. American Mathematical Society, 2015.

Ngoc Mai Tran and Josephine Yu. Product-mix auctions and tropical geometry. *Mathematics of Operations Research*, 2015.

D Melzer. On the expressibility of piecewise-linear continuous functions as the difference of two piecewise-linear convex functions. In *Quasidifferential Calculus*. Springer, 1986.

Grigory Mikhalkin. Enumerative tropical algebraic geometry in r2. *Journal of the American Mathematical Society*, 2004.

Guido Montufar, Razvan Pascanu, Kyunghyun Cho, and Y Bengio. On the number of linear regions of deep neural networks. *Advances in Neural Information Processing Systems (NeurIPS)*, 2014.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Jonathan Uesato, and Pascal Frossard. Robustness via curvature regularization, and vice versa. *CVPR*, 2019.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. *Advances in Neural Information Processing Systems (NeurIPS)*, 2011.

Kristof Schütt, Farhad Arbabzadah, Stefan Chmiela, Klaus-Robert Müller, and Alexandre Tkatchenko. Quantum-chemical insights from deep tensor neural networks. *Nature Communications*, 2017.

Abigail See, Minh-Thang Luong, and Christopher D. Manning. Compression of neural machine translation models via pruning. *CoRR*, 2016.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Georgios Smyrnis and Petros Maragos. Tropical polynomial division and neural networks. *arXiv preprint arXiv:1911.12922*, 2019.

Georgios Smyrnis and Petros Maragos. Multiclass neural network minimization via tropical newton polytope approximation. 2020.

Kerrek Stinson, David F Gleich, and Paul G Constantine. A randomized algorithm for enumerating zonotope vertices. *arXiv preprint arXiv:1602.06620*, 2016.

Liwen Zhang, Gregory Naitzat, and Lek-Heng Lim. Tropical geometry of deep neural networks. In *International Conference on Machine Learning, ICML 2018*, 2018.

Jian Zhou, Christopher Y. Park, Chandra L. Theesfeld, Aaron Wong, Yuan Yuan, Claudia Scheckel, John Fak, Julien Funk, Kevin Yao, Yoko Tajima, Alan Packer, Robert Darnell, and Olga G. Troyanskaya. Whole-genome deep-learning analysis identifies contribution of noncoding mutations to autism risk. *Nature Genetics*, 2019.