# Celebrating Diversity in Shared Multi-Agent Reinforcement Learning

## Abstract

Recently, deep multi-agent reinforcement learning (MARL) has shown the promise to solve complex cooperative tasks. Its success is partly because of parameter sharing among agents. However, such sharing may lead agents to behave similarly and limit their coordination capacity. In this paper, we aim to introduce diversity in both optimization and representation of shared multi-agent reinforcement learning. Specifically, we propose an information-theoretical regularization to maximize the mutual information between agents' identities and their trajectories, encouraging extensive exploration and diverse individualized behaviors. In representation, we incorporate agent-specific modules in the shared neural network architecture, which are regularized by L1-norm to promote learning sharing among agents while keeping necessary diversity. Empirical results show that our method achieves state-of-the-art performance on Google Research Football[1] and super hard StarCraft II micromanagement tasks.

## 1 Introduction

Cooperative multi-agent reinforcement learning (MARL) has drawn increasing interest in recent years, which provides a promise for solving many real-world challenging problems, such as sensor networks [1], traffic management [2], and coordination of robot swarms [3]. However, learning effective policies for such complex multi-agent systems remains challenging. One central problem is that the joint action-observation space grows exponentially with the number of agents, which imposes high demand on the scalability of learning algorithms.

To address this scalability challenge, *policy decentralization with shared parameters* (PDSP) is widely used, where agents share their neural network weights. Parameter sharing significantly improves learning efficiency because it dramatically reduces the total number of policy parameters, while experiences and gradients of one agent can be used to train others. Enjoying these advantages, many advanced deep MARL approaches adopt the PDSP paradigm, including value-based methods [4–6], policy gradients [7, 8] and communication learning algorithms [9, 10]. These approaches achieve state-of-the-art performance on tasks such as StarCraft II micromanagement [11].

(a) Parameter sharing: similar behaviors (competing for ball).

(b) Our approach: each agent has its responsibility to score.

Agents' history location — The goal's passing, dribbling and shooting — Off-the-ball moving

Figure 1: Shared parameters induce behaviors (**left**) and can hardly learn successful policies on the challenging Google Research Football task. Our method learns sophisticated cooperative strategies by **trading off diversity and sharing (right)**.

---

[1] `https://sites.google.com/view/celebrate-diversity-shared`

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

While parameter sharing has been proven to accelerate training [12], its drawbacks are also apparent in complex tasks. These tasks typically require substantial exploration and diversified strategies among agents. When parameters are shared, agents tend to acquire homogeneous behaviors because they typically adopt similar actions under similar observations, preventing efficient exploration and the emergence of sophisticated cooperative policies. This tendency becomes particularly problematic for many challenging multi-agent coordination tasks, hindering deep MARL from broader applications. For example, the unsatisfactory performance of state-of-the-art MARL algorithms on Google Research Football (Fig. 1, and [13]) highlights an urgent demand for diverse behaviors.

Notably, sacrificing the merits of parameter sharing for diversity is also unfavorable. Like humans, sharing necessary experience or understanding of tasks can broadly accelerate cooperation learning. Without parameter sharing, agents search in a much larger parameter space, which may be wasteful because they do not need to behave differently all the time. Therefore, the question is how to adaptively trade-off diversity and sharing. In this paper, we solve this dilemma by proposing several structural and learning novelties.

To encourage diversity, we propose a novel information-theoretical objective to maximize the mutual information between agents' identities and trajectories. This objective enables each agent to distinguish themselves from others and thus involves the contribution of all agents. Accordingly, we derive an intrinsic reward for motivating diversity and optimize it with the global environmental reward by learning the total Q-function as a combination of individual Q-functions. Structurally, we further decompose individual Q-functions as the sum of shared and non-shared local Q-functions for sharing experiences while maintaining representation diversity. We hope agents can use and expand shared knowledge whenever possible. Thus we introduce L1 regularization on each non-shared Q-function, encouraging agents to share and be diverse when necessary on several critical actions. Combining these novelties achieves a dynamic balance between diversity and homogeneity, efficiently catalyzing adaptive and sophisticated cooperation.

We benchmark our approach on Google Research Football (GRF) [13], and StarCraft II micromanagement tasks (SMAC) [11]. The extraordinary performance of our approach on challenging benchmarking tasks shows that our approach achieve significantly higher coordination capacity than baselines while using diversity as a catalyst for more robust and talent policies. To our best knowledge, our approach achieves state-of-the-art performance on SMAC super hard maps and challenging GRF multi-agent tasks like `academy_3_vs_1_with_keeper`, `academy_counterattack_hard`, and a full-field scenario `3_vs_1_with_keeper` (`full field`).

## 2  Background

A fully cooperative multi-agent task can be formulated as a Dec-POMDP [14], which is defined as a tuple $\mathcal{G} = \langle N, S, A, P, R, O, \Omega, n, \gamma \rangle$, where $N$ is a finite set of $n$ agents, $s \in S$ is the true state of the environment, $A$ is the set of actions, and $\gamma \in [0, 1)$ is a discount factor. At each time step, each agent $i \in N$ receives his own observation $o_i \in \Omega$ according to the observation function $O(s, i)$, and selects an action $a_i \in A$, which results in a joint action vector $\boldsymbol{a}$. The environment then transitions to a new state $s'$ based on the transition function $P(s'|s, \boldsymbol{a})$, and inducing a global reward $r = R(s, \boldsymbol{a})$ shared by all the agents. Each agent has its own action-observation history $\tau_i \in \mathcal{T}_i \doteq (\Omega_i \times A)^*$. Due to partial observability, each agent conditions its policy $\pi_i(a_i|\tau_i)$ on $\tau_i$. The joint policy $\boldsymbol{\pi}$ induces the joint action-value function $Q_{tot}^{\boldsymbol{\pi}}(s, \boldsymbol{a}) = \mathbb{E}_{s_{0:\infty}, \boldsymbol{a}_{0:\infty}} [\sum_{t=0}^{\infty} \gamma^t r_t \mid s_0 = s, \boldsymbol{a}_0 = \boldsymbol{a}, \boldsymbol{\pi}]$.

### 2.1  Centralized Training with Decentralized Execution

Our method adopts the framework of centralized training with decentralized execution (CTDE) [7, 15, 4, 5, 16, 17, 6]. This framework tackles the exponentially growing joint action space by decentralizing the control policies while adopting centralized training to learn cooperation. Agents learn in a centralized manner with access to global information but execute based on their local action-observation history. One promising approach to implement the CTDE framework is value function factorization. The IGM (individual-global-max) principle [16] guarantees the consistency between the local and global greedy actions. When IGM is satisfied, agents can obtain the optimal global action by simply choosing the local greedy action that maximizes each agent's individual utility function $Q_i$. Some algorithms have successfully used the IGM principle [5, 6, 18] to push forward the progress of MARL.

# 3 Method

In this section, we present a novel diversity-driven MARL framework (Fig. 2) that balances each agent's individuality with group coordination, which is a general approach that can be combined with existing CDTE value factorization methods.

## 3.1 Identity-Aware Diversity

We first introduce how to encourage behavioral diversity by designing intrinsic motivations. Intuitively, to encourage the specialty of individual trajectories, agents need to behave differently to highlight themselves from others, taking different actions and visiting different local observations. To achieve this goal, we use an information-theoretic objective for maximizing the mutual information between individual trajectory and agents' identity:

Figure 2: Schematics of our approach.

$$I^{\boldsymbol{\pi}}(\tau_T; id) = H(\tau_T) - H(\tau_T|id) = E_{id, \tau_T \sim \boldsymbol{\pi}} \left[ \log \frac{p(\tau_T|id)}{p(\tau_T)} \right], \tag{1}$$

where $\tau_T$ and $id$ is the random variable for agent's local trajectory and identity, respectively. $\boldsymbol{\pi}$ is the joint policy. To optimize Eq. 1, we expand $p(\tau_T)$ as $p(o_0) \prod_{t=0}^{T-1} p(a_t|\tau_t)p(o_{t+1}|\tau_t, a_t)$, and $p(\tau_T|id)$ as $p(o_0|id) \prod_{t=0}^{T-1} p(a_t|\tau_t, id)p(o_{t+1}|\tau_t, a_t, id)$. Therefore, the mutual information can be written as:

$$I^{\boldsymbol{\pi}}(\tau_T; id) = E_{id, \tau} \left[ \underbrace{\log \frac{p(o_0|id)}{p(o_0)}}_{①} + \underbrace{\sum_{t=0}^{T-1} \log \frac{p(a_t|\tau_t, id)}{p(a_t|\tau_t)}}_{②} + \underbrace{\sum_{t=0}^{T-1} \log \frac{p(o_{t+1}|\tau_t, a_t, id)}{p(o_{t+1}|\tau_t, a_t)}}_{③} \right]. \tag{2}$$

Term ① is determined by the environment, and we can ignore it when optimizing the mutual information. The second term quantifies the information gain about agent's action selection when the identity is given, which measures **action-aware diversity** as $I(a; id|\tau)$. However, $p(a_t|\tau_t, id)$ is typically the distribution induced by $\epsilon$-greedy, which only distinguishes the action with the highest possibility. Therefore, directly optimizing this term conceals most information about the local Q-functions. To solve this problem, we use the Boltzmann softmax distribution of local Q values to replace $p(a_t|\tau_t, id)$, which forms a lower bound of term ②:

$$E_{id, \tau} \left[ \log \frac{p(a_t|\tau_t, id)}{p(a_t|\tau_t)} \right] \geq E_{id, \tau} \left[ \log \frac{\text{SoftMax}(\frac{1}{\alpha}Q(a_t|\tau_t, id))}{p(a_t|\tau_t)} \right]. \tag{3}$$

The inequity holds because the KL divergence $D_{\text{KL}}(p(\cdot|\tau_t, id) \| \text{SoftMax}(\frac{1}{\alpha}Q(\cdot|\tau_t, id)))$ is non-negative. We maximize this lower bound to optimize Term ②. Direct optimization of Term ③ is intractable because it involves integrals over a continuous observation space. Inspired by variational inference approaches [19], we derive and optimize a tractable lower bound for this term at each timestep by introducing a variational posterior estimator $q_\phi$ parameterized by $\phi$:

$$E_{id, \tau} \left[ \log \frac{p(o_{t+1}|\tau_t, a_t, id)}{p(o_{t+1}|\tau_t, a_t)} \right] \geq E_{id, \tau} \left[ \log \frac{q_\phi(o_{t+1}|\tau_t, a_t, id)}{p(o_{t+1}|\tau_t, a_t)} \right], \tag{4}$$

Similar to the second term, the inequality holds because for any $q_\phi$, the KL divergence $D_{\text{KL}}(p(\cdot|\tau_t, a_t, id) \| q_\phi(\cdot|\tau_t, a_t, id))$ is non-negative. Intuitively, optimizing Eq. 4 encourages agents to have diverse observations that are distinguishable by agents' identification and thus measures **observation-aware diversity** as $I(o'; id|\tau, a)$. To tighten the this lower bound, we minimize the KL

divergence with respect to the parameters $\phi$. The gradient for updating $\phi$ is:

$$\nabla_\phi \mathcal{L}(\phi) = \nabla_\phi \mathbb{E}_{\tau, a, id} \left[ D_{\mathrm{KL}} \left( p \left( \cdot | \tau, a, id \right) \| q_\phi \left( \cdot | \tau, a, id \right) \right) \right] = \nabla_\phi \mathbb{E}_{\tau, a, id, o'} \left[ \log \frac{p \left( o' | \tau, a, id \right)}{q_\phi \left( o' | \tau, a, id \right)} \right]$$
$$= -\mathbb{E}_{\tau, a, id, o'} \left[ \nabla_\phi \log q_\phi \left( o' | \tau, a, id \right) \right].$$
(5)

Based on the lower bounds shown in Eq. 3 and Eq. 4, we introduce intrinsic rewards to optimise the information-theoretic objective (Eq. 1) for encouraging diverse behaviors:

$$r^I = E_{id} [\beta_2 D_{\mathrm{KL}}(\mathrm{SoftMax}(\beta_1 Q(\cdot | \tau_t, id)) \| p(\cdot | \tau_t))$$
$$+ \beta_1 \log q_\phi(o_{t+1} | \tau_t, a_t, id) - \log p(o_{t+1} | \tau_t, a_t)].$$
(6)

We introduce two scaling factors $\beta_1, \beta_2 \geq 0$ when calculating intrinsic rewards. When $\beta_1$ is 0, we only optimize the entropy term $H(\tau_T)$ in the mutual information objective (Eq. 1). $\beta_2$ is used to adjust the importance of policy diversity compared with transition diversity. In Appendix A, we discuss and compare two different approaches for estimating $p(a_t | \tau_t)$ and $p(o_{t+1} | \tau_t, a_t)$.

## 3.2 Action-Value Learning for Balancing Diversity and Sharing

In the previous section, we introduce an information-theoretic objective for encouraging each agent to behave differently from general trajectories. However, the shared local Q-function does not have enough capacity to present different policies for each agent. For solving this problem, we additionally equip each agent $i$ with an individual local Q-function $Q_i^I$. Defining experiences need to be shared or exclusively learned is inefficient and usually can not generalize. Therefore, we let agents adaptively decide whether to share experiences by decomposing $Q_i$ as:

$$Q_i(a_i | \tau_i) = Q^S(a_i | \tau_i) + Q_i^I(a_i | \tau_i),$$
(7)

where $Q^S$ is the shared Q-function among agents. In its current form, agents may learn to decompose its local Q-function arbitrarily. On the contrary, we expect that agents can share as much knowledge as possible so that we apply an L1 regularization on individual local Q-function $Q^I$ as shown in Fig.2. Such a regularization can also prevent agents from being too diverse and ignore cooperating to finish the task. In our experiments, we show that the L1 regularization is critical to achieving a balance between diversity and cooperation.

## 3.3 Overall Learning Objective

In this section, we discuss how to use the diversity-encouraging reward to train the proposed learning framework. Since the intrinsic rewards $r^I$ inevitably involves the influence from all agents, we add $r^I$ to environment rewards $r^e$ and use the following TD loss:

$$\mathcal{L}_{TD}(\theta) = \left[ r^e + \beta r^I + \gamma \max_{\boldsymbol{a}'} Q_{tot} \left( s', \boldsymbol{a}'; \theta^- \right) - Q_{tot}(s, \boldsymbol{a}; \theta) \right]^2,$$
(8)

where $\theta$ is the parameters in the whole framework, $\theta^-$ is periodically frozen parameters copied from $\theta$ for a stable update, and $\beta$ is a hyper-parameter adjusting the weight of intrinsic rewards compared with environment rewards. We use QPLEX to decompose $Q_{tot}$ as a mixing of local Q-functions $Q_i$ and train the framework end-to-end by minimizing the loss:

$$\mathcal{L}(\theta) = \mathcal{L}_{TD}(\theta) + \lambda \sum_i \mathcal{L}_{L_1}(Q_i^I(\theta_i^I)),$$
(9)

where $\theta_i^I$ is the parameters of $Q_i^I$, $\mathcal{L}_{L_1}(Q_i^I)$ is the L1 regularization term for independent Q-functions, and $\lambda$ is a scaling factor.

# 4 Case study: outperforming by being diverse only when necessary

We design `Pac-Men` shown in Fig. 3 to demonstrate how our approach works. In this task, four agents are initialized at the center room and can only observe a $5 \times 5$ grid around them. Three dots are initialized randomly in each edge room. To make this environment more challenging, paths to

different rooms have different lengths, which are down : left : up : right = 4 : 8 : 12 : 8. Three out of four rooms are outside agents' observation scope, which brings about the difficulty of exploration. Dots will refresh randomly after all rooms are empty. An ineffective competition between agents occurs when they come together in one room. The total environmental reward is the number of dots eaten in one step or -0.1 if no one eats dots. The time limit of this environment is set to 100 steps.

(a) Comparison against baselines  (b) Visitation heatmap  (c) Behavior diversity heatmap

Figure 3: Why does our method work? The balance between identity-aware diversity and experience sharing encourages sophisticated strategies.

Fig. 3-middle demonstrates the learned strategies of our approach, with a heatmap showing the visitation number. Driven by the objective of mutual information between individual trajectory and identity, agents achieve diversity and scatter in different rooms to eat dots. We further analyze the role of independent and shared Q-functions during different stages in Fig. 3 right. We visualize the value of $SD(Q_i^I(\cdot))/SD(Q^S(\cdot))$, where SD denotes the standard deviation (SD) of Q values for different actions. A higher SD ratio indicates the independent Q-functions play a leading role, while a lower SD ratio indicates the shared Q function's domination.

We notice that the SD ratio is considerably larger in the central room and four paths than in four edge rooms. This observation means that agents use independent Q networks to reach different rooms while use the shared Q network to search for dots in them. The result shows that our method achieves a good balance between diversity and knowledge sharing. Taking this advantage, our approach significantly outperforms baselines (Fig. 3 left, baselines are introduced in Sec. 6). Other methods, such as influence-based exploration (EITI & EDTI [20]), variational exploration (MAVEN [21]), and individuality emergence (EOI [22]) methods, are slower to learn optimal strategies.

# 5 Related Work

Deep multi-agent reinforcement learning algorithms have witnessed significant advances in recent years. COMA [15], MADDPG [7], PR2 [23], and DOP [8] study the problem of policy-based multi-agent reinforcement learning. They use a (decomposed) centralized critic to calculate gradients for decentralized actors. Value-based algorithms decompose the joint value function into individual utility functions in order to enable efficient optimization and decentralized execution. VDN [4], QMIX [5], and QTRAN [16] progressively expand the representation capabilities of the mixing network. QPLEX [6] implements the full IGM class [16] by encoding the IGM principle into a duplex dueling network architecture. Weighted QMIX [18] proposes weighted projection to decompose any joint action-value functions. There are other works that investigate into MARL from the perspective of coordination graphs [24–26], communication [27, 28, 10], and role-based learning [12, 29].

**Knowledge sharing in MARL** From IQL [30] to QPLEX, many works focus on designing mixing network structures and have provided promising empirical and theoretical results. For these works, experience sharing among agents has been an important component. Learning from others is one essential skill engraved in humans' genes to survive in society. Based on the relationship between teachers and students in human society, a series of research work hopes each agent can learn from others or selectively share its knowledge with others [31–34]. But it is challenging to specify knowledge in practice, let alone deciding what to share or learn. SEAC [35] partially solves this

problem by sharing trajectories only for off-policy training. NCC [28] maintains cognition consistency
by representation alignment between neighbors. Roy et al. [36] force each agent to predict others'
local policies and adds a coach for group experience alignment. In this paper, we do not try to let
agents choose whether to learn or share experiences. Our neural network structure shown in Fig. 2
can balance group coordination and diversity by gradient backpropagation.

**Diversity** In single-agent settings, diversity emerges for exploration or solving sparse reward prob-
lems. Existing methods such as curiosity-driven algorithms [37–40] or maximising mutual infor-
mation [41–43] have shown great promise. When encouraging diversity in MARL settings, agents'
coordination must be considered. Several recent works study this problem, such as MAVEN [21],
EITI & EDTI [20], and EOI [22]. MAVEN learns a diverse ensemble of monotonic approximations
with the help of a latent space to explore. EITI and EDTI consider pairwise mutual influence to
encourage the interdependence between agents. EOI [22] combines the gradient from the intrinsic
value function (IVF) and the total Q-function to train each agent's local Q-function. In this paper, we
encourage agents to explore unique trajectories by optimizing the mutual information between agent's
identity and trajectory. Moreover, we propose a novel network structure to enable experience sharing
or consensus, which combines all agents' rare ideas, while still maintain independent action-value
functions for each agent to behave differently when necessary. The combination of these novelties
balances diversity and homogeneity for learning sophisticated cooperation.

## 6 Experiments

In Sec. 4, we use a toy game to illustrate how our approach adaptively balances experience sharing and
identity-aware diversity. In this section, we use challenging tasks from GRF and SMAC benchmark
to further demonstrate and illustrate the outperformance of our approach. We compare our approach
against multi-agent value-based methods (QMIX [5], QPLEX [6]), influence-based exploration
(EITI & EDTI [20]), variational exploration (MAVEN [21]), and individuality emergence (EOI [22])
methods. Different from baselines, we do not include agents' identification in inputs when calculating
local Q-functions. We show the average and variance of the performance for our method, baselines,
and ablations tested with five random seeds.

### 6.1 Performance on Google Research Football (GRF)

We first benchmark our approach on three challenging Google Research Football (GRF) offensive sce-
narios `academy_3_vs_1_with_keeper`, `academy_counterattack_hard`, and our own designed
full-field scenario `3_vs_1_with_keeper` (full field). Agents' initial locations for each scenario
are shown in Appendix B.3. In GRF tasks, agents need to coordinate timing and positions for orga-
nizing offense to seize fleeting opportunities, and only scoring leads to rewards. In our experiments,
we control left-side players (in yellow) except the goalkeeper. The right-side players are rule-based
bots controlled by the game engine. Agents have a discrete action space of 19, including moving in
eight directions, sliding, shooting, and passing. The observation contains the positions and moving
directions of the ego-agent, other agents, and the ball. The $z$-coordinate of the ball is also included.
We make a small and reasonable change to the half-court offensive scenarios: our players will lose if
they or the ball returns to our half-court. All baselines and ablations are tested with this modification.
Environmental reward only occurs at the end of the game. They will get +100 if they win, else get -1.

Figure 4: Comparison of our approach against baseline algorithms on Google Research Football.

We show the performance comparison against baselines in Fig. 4. Our approach significantly outperforms on all the scenarios. The win rate of a multi-agent exploration method, MAVEN, needs more time to solve the task, demonstrating that CDS incentives more efficient exploration. Influence-based approaches EITI and EDTI can learn effective strategies. However, these two methods use the sum of all pairwise interaction values between agents, which brings more computational complexity, causing less efficient learning than our approach. EOI lets each agent consider individuality and cooperation by setting local learning objectives but without exclusive Q networks, making cooperation and individuality hard to be persistently coordinated. In comparison, taking advantage of the partially shared network structure, CDS agents learn diverse but coordinated strategies. For example, as shown in Fig. 1, three agents have different behaviors, with the first agent passing the ball, the second scoring, while the third running to threaten. These diverse behaviors closely coordinate with each other, forming a perfect scoring strategy and leading to significant outperformance against EOI.

Figure 5: Why does our approach work? The balance between identity-aware diversity and homogeneity encourages sophisticated strategies.

**How does CDS work?** We further visualize the development of team performance, accompanied by the balancing process between identity-aware diversity and homogeneity, to show why our method works (Fig. 5). We pinpoint three critical points during the training process. In the first training stage $(0 \sim 1.2\text{M})$, CDS players attempt to be as diverse as possible due to the sparsity of environmental rewards. Agents behave differently, such as sliding randomly (Fig. 5a) or running aimlessly (Fig. 5b). These behaviors essentially promote distributed exploration. After $T = 1.2\text{M}$, agents realize they need to organize an offense to score a goal. They aggregate near the goal and prepare to attack while dribbling. However, in this second training phase, agents focus on the ball rather than cooperation, leading to unnecessary competition. For example, as highlighted by the circle in Fig. 5c and Fig. 5d, our players try to compete for the ball. They lose their individuality after obtaining huge benefits brought by scoring. We believe this is also why some baseline algorithms, such QMIX and QPLEX, encounter a performance bottleneck in GRF scenarios. After $T = 3\text{M}$, our approach gradually achieves the balance of diversity and cooperation and again enables players to make diverse decisions when handling the ball for better collaboration. The whole training process shows our approach can coordinate the relationship between agents while keeping a good balance between individuality and group tasks.

## 6.2 Performance on StarCraft II

In this section, we test our approach on the StarCraft II micromanagement (SMAC) benchmarks [11]. This benchmark consists of various maps classified as easy, hard, and super hard. Here we test our method on four **super hard** maps: `corridor`, `MMM2`, `6h_vs_8z`, and `3s5z_vs_3s6z`. Fig. 6 demonstrates that our approach outperforms all baselines with acceptable variance across random

Figure 6: Comparison of our approach against baseline algorithms on four **super hard** SMAC maps: `corridor`, `MMM2`, `6h_vs_8z`, and `3s5z_vs_3s6z`.

seeds. Comparing our approach with MAVEN shows that our approach is much more efficient in completing complex tasks. The baselines QPLEX and QMIX can achieve satisfactory performance on some challenging benchmarks, such as `3s5z_vs_3s6z`. But on other maps, they need the proposed diversity-celebrating method to get better results. EOI behaves worse than QPLEX, and the cooperation even collapses on `3s5z_vs_3s6z`. This observation shows that, compared to EOI, CDS incentivizes diverse behaviors which are more cooperative in terms of task solving. EITI behaves worse than QPLEX, while EDTI achieves outstanding performance on `3s5z_vs_3s6z`, where our approach achieves similar performance at the end of training. Taking the value of interaction into consideration lets EDTI better facilitate exploration. But the same as EITI, EDTI needs to sum up all the pairwise influence between agents, which is complex to calculate. Our approach simplifies the computational complexity by encouraging agents to highlight themselves from other agents, bypassing calculating pairwise influence. In this way, our approach can be adapted to multi-agent problems of larger scales.

### 6.3    Ablations and Visualization

To understand the contribution of each component in the proposed CDS framework, we carry out ablation studies to test the contribution of its three main components: Identity-aware *diversity* (A) encouragement and *partially shared* (B) neural network structure with *L1 regularization* (C) on non-shared Q-functions. To test component A, we ablate our intrinsic rewards to four different levels. (1) CDS-Raw ablates all intrinsic rewards by setting $\beta$ in Eq. 8 to zero. (2) CDS-No-Identity ablates $H\left(\tau_T|id\right)$ and only optimize $H\left(\tau_T\right)$ in Eq. 1 by setting $\beta_1$ in Eq. 6 to zero. (3) CDS-No-Action ablates item ② in Eq. 2 by setting $\beta_2$ in Eq. 6 to zero. (4) CDS-No-Obs ablates item ③ in Eq. 2 by ablating $\beta_1 \log q_\phi\left(o_{t+1}|\tau_t, a_t, id\right) - \log p\left(o_{t+1}|\tau_t, a_t\right)$ in Eq. 6. To test component B, we design CDS-All-Shared, which ablates independent action-value functions together with the L1 loss and, like baselines, adds agents' identification to the input. To test component C, we design CDS-No-L1, which ablates L1 regularization terms by setting $\lambda$ in Eq. 9 to zero.

Figure 7: **Left.** Ablation studies on `academy_counterattack_hard`. **Right.** Visualization of trained policies, which achieve complex cooperation with impressive off-the-ball moving strategies.

We first carry out ablation studies on `academy_counterattack_hard` to analyze which part of our novelties lead to the outstanding performance. As shown on the left side of Fig. 7, CDS-No-Identity performs the best among all ablations. However, compared with CDS, CDS-No-Identity is slower to explore winning strategy and performs noticeably worse at the end of training. Thus for

the intrinsic reward component in this environment, the superior performance of CDS is primarily due to optimizing group diversity. Still, the specialization of agents' behavior given identification noticeably improves learning. Moreover, the performance of CDS-No-Obs and CDS-Raw perform poorly. CDS-No-Action performs a little better but is similar to QPLEX. Therefore, action- and observation-aware diversity are both crucial. CDS-No-L1 performs similarly to MAVEN, which indicates that unlimited diversity is harmful to cooperation. CDS-All-Shared performs even worse than QPLEX, demonstrating that identity-aware diversity is difficult to emerge without our specially designed network structure.

We further visualize the final trained strategies on the right side of Fig. 7, which shows complex cooperation between agents. Our players first attack down the wing by dribbling and passing the ball. Then one of them draws the attention of the enemy defenders and the goalkeeper, while the ball being passed across the penalty area. Another player catches the ball and completes the shot. The most impressive part of our sophisticated strategies is off-the-ball moving strategies. All agents without the ball try to use their unique and valuable moves to create more scoring opportunities, which shows behavior and position diversity for finishing the goal.

Figure 8: **Left.** Ablation studies in super hard map `corridor`. **Right.** Visualization of the final trained strategies, which achieves a hard-earned victory brought by the sacrifice of a warrior.

We also carry out ablation studies on the super hard map `corridor` as shown in Fig. 8 left. The combination of our novelties still performs the best. We notice considerable differences against the GRF scenario. For instance, CDS-No-Identity performs the worst on `corridor` but the best on `academy_counterattack_hard` among all ablations. This phenomenon indicates the different importance of group diversity and specialization of agents' behavior given identification between GRF and SMAC. For SMAC, the most important intrinsic reward component is optimizing the conditional entropy. Unlimited identity-aware diversity without L1 regularization, CDS-No-L1, has worse performances than QPLEX. Therefore, excessive diversity is harmful to the emerge of complex cooperation, which is the same in both GRF and SMAC.

To better explain why our approach performs well. On `corridor`, we also visualize the final strategies in Fig. 8 right. In this super hard map, six friendly Zealots are facing 24 enemy Zerglings. The disparity in quantity means our agents are doomed to lose if they attack together. One Zealot, whose route is highlighted blue, becomes a warrior leaving the team to attract the attention of most enemies in the blue oval. Although doomed to sacrifice, he brings enough time for the team to eliminate a small part of the enemies in the green oval. After that, another Zealot stands out to attract some enemies and enables teammates to eradicate them. These sophisticated strategies reflect the leverage between diversity and homogeneity by encouraging agents to be diverse only when necessary.

# 7   Closing Remarks

Observing that behavioral diversity among agents is essential for many challenging and complex multi-agent tasks, in this paper, we introduce a novel mechanism of *being diverse when necessary* into shared multi-agent reinforcement learning. The balance between individual diversity and group coordination induced by our CDS approach pushes forward state-of-the-art of deep MARL on challenging benchmark tasks while keeping parameter sharing benefits. We hope that our method can shed light on future works to motivate agents to cooperate with diversity to further explore complex multi-agent coordination problems.

## References

[1] Chongjie Zhang and Victor Lesser. Coordinated multi-agent reinforcement learning in networked distributed pomdps. In *Twenty-Fifth AAAI Conference on Artificial Intelligence*, 2011.

[2] Arambam James Singh, Akshat Kumar, and Hoong Chuin Lau. Hierarchical multiagent reinforcement learning for maritime traffic management. In *Proceedings of the 19th International Conference on Autonomous Agents and MultiAgent Systems*, pages 1278–1286, 2020.

[3] Maximilian Hüttenrauch, Adrian Šošić, and Gerhard Neumann. Guided deep reinforcement learning for swarm systems. *arXiv preprint arXiv:1709.06011*, 2017.

[4] Peter Sunehag, Guy Lever, Audrunas Gruslys, Wojciech Marian Czarnecki, Vinicius Zambaldi, Max Jaderberg, Marc Lanctot, Nicolas Sonnerat, Joel Z Leibo, Karl Tuyls, et al. Value-decomposition networks for cooperative multi-agent learning based on team reward. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, pages 2085–2087. International Foundation for Autonomous Agents and Multiagent Systems, 2018.

[5] Tabish Rashid, Mikayel Samvelyan, Christian Schroeder Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 4292–4301, 2018.

[6] Jianhao Wang, Zhizhou Ren, Terry Liu, Yang Yu, and Chongjie Zhang. Qplex: Duplex dueling multi-agent q-learning. *International Conference on Learning Representations (ICLR)*, 2021.

[7] Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in Neural Information Processing Systems*, pages 6379–6390, 2017.

[8] Yihan Wang, Beining Han, Tonghan Wang, Heng Dong, and Chongjie Zhang. Dop: Off-policy multi-agent decomposed policy gradients. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

[9] Jakob Foerster, Ioannis Alexandros Assael, Nando de Freitas, and Shimon Whiteson. Learning to communicate with deep multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2137–2145, 2016.

[10] Tonghan Wang, Jianhao Wang, Chongyi Zheng, and Chongjie Zhang. Learning nearly decomposable value functions with communication minimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020.

[11] Mikayel Samvelyan, Tabish Rashid, Christian Schroeder de Witt, Gregory Farquhar, Nantas Nardelli, Tim GJ Rudner, Chia-Man Hung, Philip HS Torr, Jakob Foerster, and Shimon Whiteson. The starcraft multi-agent challenge. *arXiv preprint arXiv:1902.04043*, 2019.

[12] Tonghan Wang, Heng Dong, Victor Lesser, and Chongjie Zhang. Roma: Multi-agent reinforcement learning with emergent roles. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

[13] Karol Kurach, Anton Raichuk, Piotr Stańczyk, Michał Zając, Olivier Bachem, Lasse Espeholt, Carlos Riquelme, Damien Vincent, Marcin Michalski, Olivier Bousquet, et al. Google research football: A novel reinforcement learning environment. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 4501–4510, 2020.

[14] Frans A Oliehoek, Christopher Amato, et al. *A concise introduction to decentralized POMDPs*, volume 1. Springer, 2016.

[15] Jakob N Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[16] Kyunghwan Son, Daewoo Kim, Wan Ju Kang, David Earl Hostallero, and Yung Yi. Qtran: Learning to factorize with transformation for cooperative multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 5887–5896, 2019.

[17] Kyunghwan Son, Sungsoo Ahn, Roben Delos Reyes, Jinwoo Shin, and Yung Yi. Qtran++: Improved value transformation for cooperative multi-agent reinforcement learning, 2020.

[18] Tabish Rashid, Gregory Farquhar, Bei Peng, and Shimon Whiteson. Weighted qmix: Expanding monotonic value function factorisation for deep multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[19] Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends® in Machine Learning*, 1(1–2):1–305, 2008.

[20] Tonghan Wang, Jianhao Wang, Wu Yi, and Chongjie Zhang. Influence-based multi-agent exploration. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020.

[21] Anuj Mahajan, Tabish Rashid, Mikayel Samvelyan, and Shimon Whiteson. Maven: Multi-agent variational exploration. In *Advances in Neural Information Processing Systems*, pages 7611–7622, 2019.

[22] Jiechuan Jiang and Zongqing Lu. The emergence of individuality in multi-agent reinforcement learning. *arXiv preprint arXiv:2006.05842*, 2020.

[23] Ying Wen, Yaodong Yang, Rui Luo, Jun Wang, and Wei Pan. Probabilistic recursive reasoning for multi-agent reinforcement learning. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2019.

[24] Carlos Guestrin, Michail Lagoudakis, and Ronald Parr. Coordinated reinforcement learning. In *ICML*, volume 2, pages 227–234. Citeseer, 2002.

[25] Carlos Guestrin, Daphne Koller, and Ronald Parr. Multiagent planning with factored mdps. In *Advances in neural information processing systems*, pages 1523–1530, 2002.

[26] Wendelin Böhmer, Vitaly Kurin, and Shimon Whiteson. Deep coordination graphs. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

[27] Amanpreet Singh, Tushar Jain, and Sainbayar Sukhbaatar. Learning when to communicate at scale in multiagent cooperative and competitive tasks. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2019.

[28] Hangyu Mao, Wulong Liu, Jianye Hao, Jun Luo, Dong Li, Zhengchao Zhang, Jun Wang, and Zhen Xiao. Neighborhood cognition consistent multi-agent reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 7219–7226, 2020.

[29] Tonghan Wang, Tarun Gupta, Anuj Mahajan, Bei Peng, Shimon Whiteson, and Chongjie Zhang. Rode: Learning roles to decompose multi-agent tasks. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

[30] Ming Tan. Multi-agent reinforcement learning: Independent vs. cooperative agents. In *Proceedings of the tenth international conference on machine learning*, pages 330–337, 1993.

[31] Changxi Zhu, Ho-fung Leung, Shuyue Hu, and Yi Cai. A q-values sharing framework for multiple independent q-learners. In *Proceedings of the 18th International Conference on Autonomous Agents and MultiAgent Systems*, pages 2324–2326, 2019.

[32] Yongyuan Liang and Bangwei Li. Parallel knowledge transfer in multi-agent reinforcement learning. *arXiv preprint arXiv:2003.13085*, 2020.

[33] Changxi Zhu, Ho-fung Leung, Shuyue Hu, and Yi Cai. A q-values sharing framework for multiagent reinforcement learning under budget constraint. *arXiv preprint arXiv:2011.14281*, 2020.

[34] Yonggan Fu, Zhongzhi Yu, Yongan Zhang, and Yingyan Lin. Auto-agent-distiller: Towards efficient deep reinforcement learning agents via neural architecture search. *arXiv preprint arXiv:2012.13091*, 2020.

[35] Filippos Christianos, Lukas Schäfer, and Stefano Albrecht. Shared experience actor-critic for multi-agent reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[36] Julien Roy, Paul Barde, Félix Harvey, Derek Nowrouzezahrai, and Chris Pal. Promoting coordination through policy regularization in multi-agent deep reinforcement learning. *Advances in Neural Information Processing Systems*, 33, 2020.

[37] Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pages 2778–2787, 2017.

[38] Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018.

[39] Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martín Arjovsky, Alexander Pritzel, Andew Bolt, et al. Never give up: Learning directed exploration strategies. *arXiv preprint arXiv:2002.06038*, 2020.

[40] Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Zhaohan Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. In *International Conference on Machine Learning*, pages 507–517. PMLR, 2020.

[41] Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2018.

[42] Archit Sharma, Shixiang Gu, Sergey Levine, Vikash Kumar, and Karol Hausman. Dynamics-aware unsupervised discovery of skills. In *International Conference on Learning Representations*, 2020.

[43] Víctor Campos, Alexander Trott, Caiming Xiong, Richard Socher, Xavier Giro-i Nieto, and Jordi Torres. Explore, discover and learn: Unsupervised discovery of state-covering skills. In *International Conference on Machine Learning*, pages 1317–1327. PMLR, 2020.