MESSAGE FUNCTION SEARCH FOR HYPER-RELATIONAL KNOWLEDGE GRAPH

ABSTRACT

Recently, the hyper-relational knowledge graph (HKG) has attracted much attention due to its widespread existence and potential applications. The pioneer works have adapted powerful graph neural networks (GNNs) to embed HKGs by proposing domain-specific message functions. These message functions for HKG embedding are utilized to learn relational representations and capture the correlation between entities and relations of HKGs. However, these works often manually design and fix structures and operators of message functions, which makes them difficult to handle complex and diverse relational patterns in various HKGs (i.e., data patterns). To overcome these shortcomings, we plan to develop a method to dynamically search suitable message functions that can adapt to patterns of the given HKG. Unfortunately, it is not trivial to design an expressive search space and an efficient search algorithm to make the search effective and efficient. In this paper, we first unify a search space of message functions that enables both structures and operators to be searchable. Especially, the classic KG/HKG models and message functions of existing GNNs can be instantiated as special cases in the proposed search space. Then, we design an efficient search algorithm to search the message function and other GNN components for any given HKGs. Through empirical study, we show that the searched message functions are data-dependent, and can achieve leading performance in link/relation prediction tasks on benchmark data sets.

1 INTRODUCTION

Knowledge base (KB) (Auer et al., 2007) is an important tool to organize and explore human knowledge, thereby promoting a series of applications, e.g., question answering (Lukovnikov et al., 2017) and recommendation system (Cao et al., 2019). Generally, the KB stores the n-ary fact $r(e_1, \cdots, e_n)$ (n is arity) that represents the relation $r \in R$ between real-world entities $e_i \in E$. To manipulate large scale KBs, KB embedding (Nickel et al., 2015; Wang et al., 2017) proposes to encode the set of relations R and entities E into a d-dimensional vector space $\boldsymbol{R} \in \mathbb{R}^{|R| \times d}$, $\boldsymbol{E} \in \mathbb{R}^{|E| \times d}$. In last decades, the research community mainly focuses on embedding knowledge graphs (KGs) that only contain binary facts $\{r(e_1, e_2)\}$, e.g., `isCaptialOf(Beijing,China)`. Among kinds of KG embedding models (Rossi et al., 2021), tensor models (Lacroix et al., 2018; Balazevic et al., 2019) propose to represent a KG into a 3-order tensor and decompose tensors into entity/relation embeddings, which achieve outstanding empirical performance and theoretical guarantees (Lacroix et al., 2018). Recent studies start to learn embeddings from n-ary facts ($n \geq 2$) because n-ary facts are widespread in KBs, e.g., `playedCharacterIn(LeonardNimoy,Spock,StarTrek1)`. For example, more than 30% of entities in Freebase (Bollacker et al., 2008) involve facts with higher arity (Wen et al., 2016). Therefore, it is necessary to investigate the more general case of KGs, facts with mixed arities $S = \{r(e_1, \ldots, e_n) : n \in \{2, \ldots, N\}\}$ named as hyper-relational KGs (HKGs).

Unfortunately, it is hard to extend powerful tensor models from the case of fixed arity (e.g., KG) to the case of mixed arities (i.e., HKG). That is because a tensor can only model a set of facts under the same arity. Instead, some pioneer works (Yadati, 2020; Galkin et al., 2020) demonstrate that the multi-relational hypergraph (MRHG) could be a more natural way to model HKGs (check Appx. A for more details about modeling). Let entities E and relations R be nodes and edge types in the MRHG $\mathcal{G}(E, R, S)$, respectively. The length of MRHG's edge $(e_1, \ldots, e_n)$ (hyperedge) could be variant, which can represent facts with various arities n. And hyperedges can be labeled by multiple edge types $r \in R$ like $r(e_1, \ldots, e_n) \in S$. Under the MRHG modeling, these works adapt powerful

graph neural networks (GNNs) (Kipf & Welling, 2016; Hamilton et al., 2017) to embed HKGs (Yadati, 2020; Galkin et al., 2020). Generally, GNNs learn node embeddings by passing messages (e.g., the node features) from adjacent nodes to the center node. But in scenarios of HKGs, it is important to know which relation (edge type) makes entities (nodes) adjacent. Therefore, existing GNNs for HKG embedding design several domain-specific message functions to learn relational representations $\boldsymbol{R}$ by capturing the interaction between entities E and relations R.

Existing works manually design and fix the structures and operators of message functions. However, such rigid message function designs are not conducive to pursuing high empirical performance, as relations usually have distinct patterns in various KGs/HKGs (e.g., symmetry (Yang et al., 2015), anti-symmetry (Trouillon et al., 2017)). For example, the message function of G-MPNN (Yadati, 2020) adopts the inner product way like DistMult (Yang et al., 2015) to compute the correlation between entities and relations, which has been proven to only cover symmetric relations (Kazemi & Poole, 2018). Thus, its performance may not be good if there are many non-symmetric relations existed in the given HKG (check Appx. B.1 for more details). Excepts for existing designs, it may be a potential solution to design a universal message function to cover as many relational patterns as possible. But both Meilicke et al. (2018) and Rossi et al. (2021) report that covering a certain pattern does not mean that the model can reach good performance on it. Moreover, one pioneer work AutoSF (Zhang et al., 2020) shows that designing data-aware models can consistently achieve high performance on any given KGs. Thus, dynamically searching message functions could be a more effective way to capture the data patterns of the given HKG and pursue high performance.

Unfortunately, the searching method AutoSF is strictly restricted to bilinear KG models (Yang et al., 2015; Kazemi & Poole, 2018), which is not applicable to message function design and the HKG scenario. Besides, although neural architecture search (NAS) (Elsken et al., 2019) has been introduced to search GNN architectures, current GNN search spaces (Zhang et al., 2021) are not well regularized to tasks on HKGs. Specifically, the existing search spaces of message function follow the classic way to simply aggregate node neighbors to learn node embeddings, while ignoring edge embeddings to represent relations. Thus, they cannot capture the correlation between entities and relations of HKGs.

In summary, rigid message function designs for HKGs are not conducive to consistently pursuing high performance on different data sets, while existing searching methods are not applicable for HKGs. To bridge this research gap, we propose the *M*essage function *SEA*rch for any given *HKG*s, named as MSeaHKG. However, it is non-trivial to make the message function search effective and efficient. First, we propose a search space of message functions that enables the expressive message function to be searched for capturing the relational patterns of the given HKG. Moreover, except for the message function search, we also incorporate other GNN components (e.g., aggregation function) in the MSeaHKG search space for more performance improvements. Then, to make search more efficient, we formulate the discrete HKG models with probabilistic modelings to enable a stochastic differentiable algorithm working on our scenario. The main contributions are listed as:

- Previous GNN searching methods generally ignore the edge representations, which fails to handle semantic meaningful relations on HKGs. Besides, their message functions cannot capture complex interactions between entities with relations. In this paper, we propose a searching method to dynamically design a suitable GNN that can achieve high performance on the given HKG.

- Inspired by rigid message function designs, we define a novel search space of message functions for HKGs, which enables the message function to be flexibly searched on the given HKG. Especially, many classic KG/HKG models and existing message function designs for HKGs can be instantiated as special cases of the proposed space.

- We conduct experiments on benchmark HKGs for the link prediction and relation prediction tasks. Experimental results demonstrate that MSeaHKG can consistently achieve state-of-the-art performance by designing data-aware message functions.

2 RELATED WORK

2.1 ONE-SHOT NEURAL ARCHITECTURE SEARCH IN GRAPH NEURAL NETWORK

To avoid manual efforts on neural architecture designs, NAS (Hutter et al., 2018; Yao & Wang, 2018) aims to automatically search suitable neural architectures for the given data and task. Generally, search

Table 1: Overview of Existing Works. NC, GC, LP, RP denote node classification, graph classification, link prediction, relation prediction, respectively. $DP(\cdot)$ is dropout; $BN(\cdot)$ is batch normalization; $\bar{o}(\cdot)$ outputs the hidden representation after summarizing mixed operations (Zhao et al., 2021); $\boldsymbol{h}_i^K$ denotes the output from i-th operator of $\mathcal{O}$ in K-th layer of message function (see Sec. 3.1).

Type	Model	Scenarios		Message Function
		Task	# Type/Length of edge	
NAS for GNNs	You et al. (2020)	NC/GC/LP		$DP(BN(\boldsymbol{W}\boldsymbol{e}_j + \boldsymbol{b}))$
	GraphNAS	NC	$= 1/ = 2$	$a_{ij}concat(\boldsymbol{e}_i, \boldsymbol{e}_j)$
	AGNN			$a_{ij}\boldsymbol{W}\boldsymbol{e}_j$
	SANE		$\geq 1/ = 2$	$\boldsymbol{W}\bar{o}(\{\boldsymbol{e}_j\}_{e_j \in N(e_i)})$
	NAS-GCN	GC		$a_{ij}MLP(\boldsymbol{h}_{ij})\boldsymbol{e}_j$
GNNs for KGs/HKGs	R-GCN	LP/RP	$\geq 1/ = 2$	$\boldsymbol{W}_r\boldsymbol{e}_j$
	CompGCN			$\boldsymbol{W}_{\lambda(r)}\phi(\boldsymbol{e}_j, \boldsymbol{r})$
	StarE		$\geq 1/ \geq 2$	$\boldsymbol{W}_{\lambda(r)}\phi_r(\boldsymbol{e}_o, \gamma(\boldsymbol{r}, \boldsymbol{h}_r))$
	G-MPNN			$\boldsymbol{r}_{P(e)} * \prod_i \boldsymbol{p}_{e_i} * \boldsymbol{e}_i$
Ours	MSeaHKG	LR/RP	$\geq 1/ \geq 2$	$MLP\&concat(\{\boldsymbol{h}_i^K\}_{i=1}^{|\mathcal{O}|})$

space, search algorithm, and evaluation measurement are three important components in NAS (Elsken et al., 2019). Search space defines what network architectures in principle should be searched. The search algorithm performs an efficient search over the search space and finds architectures that achieve good performance. Evaluation measurement decides how to evaluate the searched architectures during the search. Classical NAS methods are computationally consuming because candidate architectures are evaluated by the stand-alone way, i.e., evaluating the performance of architecture after training it to convergence. More recently, one-shot NAS (Pham et al., 2018) proposes the weight sharing mechanism to share network weights across different candidate architectures and evaluate them on the shared weights, which can extremely reduce the search cost.

Some pioneer works have explored NAS for GNNs, such as You et al. (2020), GraphNAS (Gao et al., 2020), AGNN (Zhou et al., 2019), NAS-GCN (Jiang & Balaprakash, 2020). And the advanced one-shot NAS also has been introduced to search GNN architectures recently, e.g., SANE (Zhao et al., 2021). As shown in the left part of Fig. 1, most GNN searching methods follow the message passing neural networks (MPNNs) (Gilmer et al., 2017) to unify two steps of the GNN framework in one layer:

$$step1 : \boldsymbol{m}_i \leftarrow agg(\{mg_c(\boldsymbol{e}_i, \boldsymbol{e}_j)\}_{e_j \in N(e_i)}), \; step2 : \boldsymbol{e}_i \leftarrow act(comb(\boldsymbol{e}_i, \boldsymbol{m}_i)), \quad (1)$$

where $\boldsymbol{e}_i \in \mathbb{R}^d$ represents the embedding of node e_i, $\boldsymbol{m}_i$ is the intermediate embeddings of e_i gathered from its neighborhood $N(e_i)$. The search space of operators in Eq. 1 are summarized into:

- **Message Function** $mg_c(\cdot)$: The message function decides the way to gather information from a neighborhood e_j of the center node e_i. Zhang et al. (2021) summarizes the typical message in existing GNN searching methods as $mg_c(\boldsymbol{e}_i, \boldsymbol{e}_j) = a_{ij}\boldsymbol{W}\boldsymbol{e}_j$, where a_{ij} denotes the attention scores between nodes e_i with e_j. Besides, we present more message function designs in Tab. 1.

- **Aggregation Function** $agg(\cdot)$: It controls the way to aggregate message from nodes' neighborhood. Usually $agg \in \{sum, mean, max\}$, where $sum(\cdot) = \sum_{e_j \in N(e_i)} mg_c(\boldsymbol{e}_i, \boldsymbol{e}_j)$, $mean(\cdot) = \sum_{e_j \in N(e_i)} mg_c(\boldsymbol{e}_i, \boldsymbol{e}_j)/|N(v)|$, and $max(\cdot)$ denotes channel-wise maximum.

- **Combination Function** $comb(\cdot)$: It determines the way to merge messages between neighborhood and node itself. In literature, $comb$ is selected from $\{concat, add, mlp\}$, where $concat(\cdot) = [\mathbf{e}_i, \mathbf{m}_i]$, $add(\cdot) = \mathbf{e}_i + \boldsymbol{m}_i$, and $mlp(\cdot) = MLP(\boldsymbol{e}_i + \boldsymbol{m}_i)$ (MLP is Multi-layer Perceptron).

- **Activation Function** $act(\cdot)$: $[identity, sigmoid, tanh, relu, elu]$ are some of the most commonly used activation functions (Gao et al., 2020).

Overall, $mg_c(\cdot)$ in Eq. 1 only learns node embeddings, which cannot encode the semantic meaningful edge types (i.e., relations in HKGs). Note that NAS-GCN (Jiang & Balaprakash, 2020) takes the edge feature $\boldsymbol{h}_{ij}$ between e_i and e_j as input without learning edge embeddings, and recent AutoGEL (Zhili et al., 2021) simply extends the message function $mg_c(\cdot)$ to learn edge embeddings without studying the interactions between entities and relations as works in Sec. 2.2, thereby failing to handle the LP/RP tasks on HKGs.

Figure 1: The framework of several GNN frameworks. The green box refers to the message function. Note that CompGCN and StarE select $sum(\cdot)$ as $agg(\cdot)$ and omit $comb(\cdot)$, while G-MPNN uses $concat(\cdot)$ as $comb(\cdot)$.

2.2 GRAPH NEURAL NETWORKS FOR KG/HKG EMBEDDING

As introduced in Sec. 1 and Sec. 2.1, message functions in classic GNNs simply aggregate messages from adjacent nodes (see Tab. 1 and Eq. 1). But it is important to know what relations make entities adjacent in KGs/HKGs. To capture relations, R-GCN (Schlichtkrull et al., 2018) proposes to model relations R in KGs through relation-specific weight matrix $\mathbf{W}_r \in \mathbb{R}^{d \times d}$ for $r \in R$ in message functions, which is instantiated as:

$$e_i = act(sum(\{\boldsymbol{W}_r \boldsymbol{e}_j\}_{r(e_i, e_j) \in I(e_i)})), \tag{2}$$

where $I(e_i) = \{r(e_i, e_j) \in S : r \in R, e_j \in E\}$ is the set of relational edges incident on e_i. But such relation modeling may lead to the over-parameterization issue because there are many relations in KGs. Therefore, CompGCN (Vashishth et al., 2020) utilizes the embedding vector $\boldsymbol{r}$ to represent the relation instead of weigh matrix:

$$e_i = act(sum(\{\boldsymbol{W}_{\lambda(r)} \phi(\boldsymbol{e}_j, \boldsymbol{r})\}_{r(e_i, e_j) \in I(e_i)})), \ \boldsymbol{r} = \boldsymbol{W} \boldsymbol{r} \tag{3}$$

where $\lambda(r)$ records the directional information of edges. The entity-relation composition operator set $\{sub, mult, corr\}$ is inspired by classical scoring function design in existing KG embedding models, such as element-wise subtraction $sub(\cdot) = \boldsymbol{e}_j - \boldsymbol{r}$ (Bordes et al., 2013), inner product $mult(\cdot) = \boldsymbol{e}_j * \boldsymbol{r}$ (Yang et al., 2015), circular correlation $corr(\cdot) = \boldsymbol{e}_j \circ \boldsymbol{r}$ (Nickel et al., 2016).

Subsequently, StarE and G-MPNN extend the applications of GNNs from KGs to HKGs. StarE (Galkin et al., 2020) requires the role information r_{o_j} of entity e_j and assumes a hyper-relational fact $r(e_1, \ldots, e_n)$ is composed by a base triplet $r(e_s, e_o)$ with a set of role-value pairs $\{(r_{o_j}, e_j)\}$ such that $r(e_s, e_o, \{(r_{o_j}, e_j)\})$. Then StarE takes base relation with the role-value pairs as a hyper-relation and performs the composition operator $\phi_r(\cdot)$ on the hyper-relation with base entity:

$$e_s = act(sum(\{\boldsymbol{W}_{\lambda(r)} \phi_r(\boldsymbol{e}_o, \gamma(\boldsymbol{r}, \boldsymbol{h}_r))\}_{r(e_s, e_o, \{(r_{o_j}, e_j)\}) \in I(e_s)})), \ \boldsymbol{h}_r = \boldsymbol{W} sum(\{\phi_o(\boldsymbol{r}_{o_j}, \boldsymbol{e}_j)\}_j),$$

where $\boldsymbol{h}_r$ is the hidden representation aggregated from the role-value pairs, $\gamma(\cdot)$ is a concatenate operator to output the representation of hyper-relation. The update of $\boldsymbol{r}$ in StarE is similar to CompGCN. Instead of requiring role information, G-MPNN (Yadati, 2020) proposes to model positional information in GNNs:

$$e_i = act([\boldsymbol{e}_i, agg(\{\boldsymbol{r}_{s, P(s)} * \prod_{j \in \{1, \ldots, n\}} \boldsymbol{p}_{e_j, s} * \boldsymbol{e}_j\}_{r(e_1, \ldots, e_n) \in I(e_i)})]), \tag{4}$$

where s represents $r(e_1, \ldots, e_n) \in S$, $P(s) : s \to \{1, \ldots, n_p\}$ is a positional mapping ($n_p \leq |E|$), and $\boldsymbol{p}_{e_j, s}$ is the positional embedding vector of e_j on fact s. To intuitively check the difference of message functions, we plot the framework of general MPPNs and GNNs for KGs/HKGs in Fig. 1.

3 MSEAHKG

In this section, we first propose a GNN search space, especially the space of message functions, which enables the powerful GNNs to be searched for HKG embedding. Then, we formulate our search problem on the proposed space and solve it with an efficient search algorithm.

3.1 GNN SEARCH SPACE DESIGN FOR HKG EMBEDDING

As discussed in Sec. 1, designing the proper message function is more conducive to capturing relational patterns of given HKGs and pursuing high empirical performance. Therefore, the first task is to design an expressive search space so that message functions covering various relational patterns can be searched. However, the space of existing GNN searching methods (see Eq. 1 and Fig. 1) does not apply to HKGs and cannot cover the message functions of GNNs for KGs/HKGs (see Sec. 2.2). Thus, we focus on the search space design of message functions in this paper.

Recently, various message functions have been proposed for KGs/HKGs as presented in Sec. 2.2. From Fig. 1, we can observe that those message functions are mainly different in these two aspects: 1) the operators (e.g., $\boldsymbol{W}, \phi, \gamma$) for computing hidden representations, 2) the structure of message functions that decides how computational operators are connected. For the operator selection, existing works manually tune them on different data sets, such as ϕ in CompGCN, ϕ_o, ϕ_r, γ in StarE, $agg(\cdot)$ in G-MPNN. Moreover, the structure of message functions for HKGs (StarE and G-MPNN) tends to be deeper and more complex than those for KGs (e.g., CompGCN). This is because the message function needs to process more information (e.g., more entities/roles) when facing the facts with higher arity. These observations motivate us to build space of operators and structures for message function search. Furthermore, we investigate more about the relationship between operators and relational patterns. Generally, the relational pattern can be represented as a certain correlation among $r(pemu(e_1, \ldots, e_n))$ (check more in Appx. B.2), where $pemu$ denotes the permutation. For example, r is symmetry if $r(e_j, e_i)$ must be true when $r(e_i, e_j)$ is true. Therefore, the message function in the search space must be able to handle such correlation in the form of $r(pemu(e_1, \ldots, e_n))$. In the next, we first introduce the space of operators, and then discuss how they deal with $r(pemu(e_1, \ldots, e_n))$.

- **Positional Transformation Matrix $\boldsymbol{W}_{P(e)}$:** The position of entity in a fact can largely determines the plausibility of the fact. For example, `isCaptialOf(Beijing,China)` is true while `isCaptialOf(China,Beijing)` is false. G-MPNN utilizes the positional embedding $\boldsymbol{p}_{e,s}$ and $\boldsymbol{r}_{e,P(e)}$ to encode the position of entity e and relation r in different facts, which requires the model complexity $O(d|S|(|E| + N))$. However, the training data set is very sparse in KBs. Such over-parameterization may make the training insufficient. Instead, we adopt the way to transform one entity e to N possible positions. Let the positional mapping be $P(e) : e \rightarrow \{1, \ldots, N\}$, then the positional matrix is able to transform $\boldsymbol{e}$ to the permutation position in $pemu(\cdot)$ by $\boldsymbol{W}_{P(e)}\boldsymbol{e}$, where $\boldsymbol{W}_{P(e)}$ consumes $O(Nd^2)$ ($|S| \gg d$ in practice).

- **Concatenate Operator $\gamma(\cdot)$:** It mainly determines the concatenation way between embedding vectors. In this paper, we set $\mathcal{O}_\gamma = \{concat, mult, wsum\}$ (Galkin et al., 2020), where $wsum$ is the weighted sum. In general, $\gamma(\cdot)$ can concatenate embeddings after the positional transform matrix $\boldsymbol{W}_{P(e)}$, i.e., encoding $pemu(\boldsymbol{e}_1, \ldots, \boldsymbol{e}_n)$.

- **Role Embedding $\boldsymbol{r}_o$:** The role of entities can provide rich semantic information in the fact (Liu et al., 2021). For example, the entity roles involved in the relation `playedCharacterIn` are an actor, a character, and a movie. Then the model only needs to verify whether the candidate entities belonging to these roles. Given a fact to be verified, the fact is probably false if one or more entities in the fact do not belong to these roles. Note that some pioneer works take the role as the secondary relation (Galkin et al., 2020).

- **Composition Operator $\phi(\cdot)$:** Following CompGCN, we utilize composition operator $\phi(\cdot)$ to capture message between the node and edge embeddings before aggregation step. Note that ϕ actually encodes the interaction between $\boldsymbol{r}$ and $pemu(\boldsymbol{e}_1, \ldots, \boldsymbol{e}_n)$. While CompGCN and StarE empirically selects the most proper $\phi(\cdot)$, we include this operator into the space $\mathcal{X}$. Thus, MSeaHKG is able to automatically search for the most suitable $\phi(\cdot)$ in a more efficient way. We combine the settings of CompGCN and StarE to set $\mathcal{O}_\phi = \{sub, mult, corr, rotat\}$ ($rotat$ (Sun et al., 2019), see others in Sec 2.2). Besides, ϕ not only occurs between primary relations with entities, but also captures the correlation between roles with entities.

(a) Framework.   (b) One-layer MPNN.   (c) Message Function Space.

Figure 2: The framework of MSeaHKG. Fig. (b) represents concrete framework of MPNN layer in Fig. (a), and Fig. (c) is detailed formulation of $mg(\cdot; \boldsymbol{\theta})$ in Fig. (b). The operator $layer\ cnt$ enables the connectivity of different layers (Jiang & Balaprakash, 2020).

- **Others:** (1) The idt operation: To enable more flexible search, we allow inputs (embeddings) to skip one layer in the message function, i.e., $idt(\boldsymbol{h}) = \boldsymbol{h}$. (2) The transform matrix $\boldsymbol{W}$: Differ from $\boldsymbol{W}_{P(e)}$, $\boldsymbol{W}$ processes the hidden representations.

Among above components, we fix the role embedding and positional transform matrix $\boldsymbol{W}_{P(e)}$ in the message function (see Fig. 2 (c)) at the initial layer. And we include others into the space of message function $\mathcal{O} = \{\boldsymbol{W}, \phi, \gamma, idt\}$ for searching. As shown in Fig. 2 (c), the search space of message function is a directed acyclic graph consisting $|\mathcal{O}|$ nodes in every layer. We denote the node o_i^k as i-th operator of $\mathcal{O}$ in k-th layer and $\boldsymbol{h}_i^k$ be the hidden representation outputted by o_i^k. Then we have:

$$\{\boldsymbol{h}_i^0\}_{i=1}^{2n+1} = \{\boldsymbol{W}_{P(e_1)}\boldsymbol{e}_1, \ldots, \boldsymbol{W}_{P(e_n)}\boldsymbol{e}_n, \boldsymbol{r}_{o_1}, \ldots, \boldsymbol{r}_{o_n}, \boldsymbol{r}\}, \quad (5)$$

$$\boldsymbol{h}_i^k = o_i^k\big(\{\theta_{ij}^k \boldsymbol{h}_j^{k-1}\}_{j=1}^{|\mathcal{O}|}\big), \text{ for } k \in \{1, \ldots, K\} \text{ and } i \in \{1, \ldots, |\mathcal{O}|\}, \quad (6)$$

where $\theta_{ij}^k \in \{0, 1\}$ controls the connection between o_i^k with o_j^{k-1}. Note that $\{\boldsymbol{h}_i^0\}_{i=1}^{n+1} = \{\boldsymbol{W}_{P(e_1)}\boldsymbol{e}_1, \ldots, \boldsymbol{W}_{P(e_n)}\boldsymbol{e}_n, \boldsymbol{r}\}$ if role information is not available in the given HKG. From Fig. 2 (c), we can observe that the structure of message functions is controlled by $\{\theta_{ij}^k\}$. To avoid manual operation selection, we also search for concrete operations of two operators ϕ and γ. Given the operator set $\mathcal{O}_\phi$ and $\mathcal{O}_\gamma$, let $\theta_i^{\phi_k}, \theta_i^{\gamma_k} \in \{0, 1\}$ records the selection i-th operation $o_i \in \mathcal{O}_\phi, \mathcal{O}_\gamma$ at k-layer respectively. Then, ϕ and γ perform the computation in Eq. 6 could be $\phi^k(\boldsymbol{h}) = \sum \theta_i^{\phi_k} o_i(\boldsymbol{h})$ and $\gamma^k(\boldsymbol{h}) = \sum \theta_i^{\gamma_k} o_i(\boldsymbol{h})$. Note that $\sum_i \theta_i^{\phi_k} = 1$ and $\sum_i \theta_i^{\gamma_k} = 1$. Let $\boldsymbol{\theta}^{mg} = \{\theta_{ij}^k\} \cup \{\theta_i^{\phi_k}\} \cup \{\theta_i^{\gamma_k}\}$. The message function parameterized by $\boldsymbol{\theta}^{mg}$ is defined as:

$$mg\big(\boldsymbol{r}(\boldsymbol{e}_1, \ldots, \boldsymbol{e}_n); \boldsymbol{\theta}^{mg}\big) = MLP\&concat(\{\boldsymbol{h}_i^K\}_{i=1}^{|\mathcal{O}|}), \quad (7)$$

where we simplify role embedding $\boldsymbol{r}_o$ for simplicity and $\boldsymbol{h}_i^K$ is outputted by the last layer of Eq. 6. Intuitively, existing GNNs for KGs/HKGs are contained in the MSeaHKG space (compare Fig. 1 and Fig. 2). Moreover, we include more discussions about the instantiations of other KG/HKGs models in the MSeaHKG space and the capability of handling relational patterns in Appx. B.2.

In addition to message function search, we also search for other operators (e.g., $agg, comb, act$) like existing GNN search methods as shown in Fig. 2 (a) and (b). Let $\boldsymbol{\Theta} = \{\boldsymbol{\theta}^{mg}, \boldsymbol{\theta}^{agg}, \ldots\}$ be parameter set for all operators selection in our MPNN framework. Then, a GNN architecture for HKG embedding can be represented as $X_{\boldsymbol{\Theta}} = \{mg(\cdot; \boldsymbol{\theta}^{mg}), agg(\cdot; \boldsymbol{\theta}^{agg}), \cdots\}$. And existing GNNs for KG/HKG embeddings actually can be represented by different instantiations of $\boldsymbol{\Theta}$. Overall, a GNN model $X_{\boldsymbol{\Theta}}$ encodes the given HKG $\mathcal{G}$ into embedding space $\boldsymbol{\omega} = \{\boldsymbol{E}, \boldsymbol{R}\}$, i.e., $\boldsymbol{\omega} = X_{\boldsymbol{\Theta}}(\mathcal{G})$.

3.2 SEARCH ALGORITHM DESIGN

In this subsection, we introduce how to select the GNN X_{Θ} that can achieve high performance on the given $\mathcal{G}$. First, we evaluate performance of X_{Θ} based on the HKG embedding $\boldsymbol{\omega} = \{\boldsymbol{E}, \boldsymbol{R}\}$ since X_{Θ} is utilized to encode $\mathcal{G}(E, R, S)$ into $\boldsymbol{\omega}$, i.e., $\boldsymbol{\omega} = X_{\Theta}(\mathcal{G})$. In the KG/HKG embedding, the scoring function $f(s; \boldsymbol{\omega})$ is to verify the plausibility of fact $s = r(e_1, \ldots, e_n)$ by decoding $\boldsymbol{\omega}$ (check more about scoring functions in Appx. C.1). Generally, the good embedding $\boldsymbol{\omega}$ can make $f(s; \boldsymbol{\omega})$ to distinguish true or false for a given fact s. Thus, we build evaluation of X_{Θ} on $f(s; \boldsymbol{\omega})$. Taking link prediction task (predict the missing entity in a fact, e.g., $r(?, e_2, \ldots, e_n)$) as example, let a scoring function $f(s; \boldsymbol{\omega})$ decode $\boldsymbol{\omega}$ and output a score matrix $\boldsymbol{p}^s \in [0, 1]^{|E|}$, where $\boldsymbol{p}_e^s$ is the probability score of $e \in E$ may be the ground truth of the missing entity. Then, we follow Dettmers et al. (2018) to construct the cross entropy loss $\ell(f(s; \boldsymbol{\omega})) = \sum_{e \in E} \boldsymbol{y}_e^s \log \boldsymbol{p}_e^s$, where $\boldsymbol{y}_e^s = 1$ if e is the ground truth otherwise 0. Subsequently, we denote $\mathcal{L}(X_{\Theta}, \boldsymbol{\omega}; \mathcal{G}) = \sum_{s \in S} \ell(f(s; \boldsymbol{\omega}))$ to calculate the overall loss of a GNN model X_{Θ} with the HKG embedding $\boldsymbol{\omega}$ on $\mathcal{G}(E, R, S)$. Formally the GNN search problem for a given HKG $\mathcal{G}$ is formulated as:

$$\min_{\Theta, \boldsymbol{\omega}} \mathcal{L}(X_{\Theta}, \boldsymbol{\omega}; \mathcal{G}). \tag{8}$$

Solving Eq. 8 is a non-trivial task because X_{Θ} (e.g., $X_{\Theta} = \{agg : sum, act : relu, \ldots\}$) is from a large space. For example, only the structure space size $\{\theta_{ij}^k\}$ of message function reaches to $O(2^{K|\mathcal{O}|^2 + (2N+1)|\mathcal{O}|})$. And X_{Θ} is discrete, indicating the gradient-based optimization cannot be employed since $\nabla_{X_{\Theta}} \mathcal{L}(\cdot)$ does not exist. To enable an efficient search, we firs relax the parameters of GNN model Θ from a discrete space into a continuous and probabilistic space $\bar{\Theta}$. More specifically, $\theta_{ij}^k \in \{0, 1\}$ restrictively controls the connectivity between o_i^k with o_j^{k-1}, while $\bar{\theta}_{ij}^k \in [0, 1]$ is the probability that o_i^k is connected with o_j^{k-1}. Then, let $X \sim p_{\bar{\Theta}}(X)$ represent a GNN model X being sampled from the distribution $p_{\bar{\Theta}}(X)$. We reformulate the problem in Eq. 8 into:

$$\min_{\bar{\Theta}, \boldsymbol{\omega}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})], \tag{9}$$

where $E[\cdot]$ is the expectation. To compute the gradient w.r.t. $\bar{\Theta}$, we first utilize the reparameterization trick $X = g_{\bar{\Theta}}(U)$ (Maddison et al., 2016), where U is sampled from a uniform distribution $p(U)$. Then the gradient w.r.t. $\bar{\Theta}$ and $\boldsymbol{\omega}$ is computed as (check full derivation in Appx. C.3):

$$\nabla_{\bar{\Theta}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})] = E_{U \sim p(U)}[\mathcal{L}'(g_{\bar{\Theta}}(U), \omega; D) \nabla_{\bar{\Theta}} g_{\bar{\Theta}}(U)], \tag{10}$$

$$\nabla_{\boldsymbol{\omega}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})] = E_{X \sim p_{\bar{\Theta}}(X)}[\nabla_{\boldsymbol{\omega}} \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})]. \tag{11}$$

Note that $\nabla_{\bar{\Theta}} g_{\bar{\Theta}}(U)$ can be computed if $g_{\bar{\Theta}}(U)$ is differentiable. Inspired by SNAS (Xie et al., 2018), we leverage Maddison et al. (2016); Jang et al. (2016) to instantiate $g_{\bar{\Theta}}(U)$ (see Appx. C.3).

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

In this paper, we implement the proposed method on top of PyTorch (Paszke et al., 2019). The experiments are performed on one single RTX 2080 Ti GPU. More details about hyper-parameters are introduced in Appendix D.1.1.

Data Sets. The details of data sets are summarized into Tab. 7 in Appendix D.1.2. For experiments on HKGs (facts with mixed arities), we employ 2 benchmark data sets: (1) Wiki-People (Guan et al., 2019) is extracted from wiki-data, which mainly concerns the entities that belong to the human type. (2) JF17K (Zhang et al., 2018) is extracted from Freebase (Bollacker et al., 2008). For experiments on facts with fixed arities, we utilize several data sets with fixed arities and $n > 2$: WikiPeople-3, JF17k-3, WikiPeople-4, and JF17k-4. Note that GETD (Liu et al., 2020) filters out the 3-ary and 4-ary facts from WikiPeople and JF17K to construct WikiPeople-n and JF17k-n, respectively.

Tasks and Evaluation Metrics. In this paper, we mainly compare HKG embedding models on the link prediction task and relation prediction task in the transductive setting. The link prediction task is to predict the missing entity in the given fact at n possible positions, e.g., predicting the first missing entity $r(?, e_2, \cdots, e_n)$. The relation classification task needs to predict the missing relation

Table 2: The model comparison of the link prediction task on HKGs.

type	model	WikiPeople				JF17K			
		MRR	Hit@1	Hit@3	Hit@10	MRR	Hit@1	Hit@3	Hit@10
Geo	RAE	0.172	0.102	0.182	0.320	0.310	0.219	0.334	0.504
NNs	NaLP	0.338	0.272	0.364	0.466	0.366	0.290	0.391	0.516
	HINGE	0.333	0.259	0.361	0.477	0.473	0.397	0.490	0.618
	NeuInfer	0.350	0.282	0.381	0.467	0.517	0.436	0.553	0.675
Multi-linear	HypE	0.292	0.162	0.375	0.502	0.507	0.421	0.550	0.669
	RAM	0.380	0.279	0.445	0.539	0.539	0.463	0.573	0.690
GNNs	StarE	0.378	0.265	0.452	0.542	0.542	0.454	0.580	0.685
	G-MPNN	0.367	0.258	0.439	0.526	0.530	0.459	0.572	0.688
Search	S2S	0.372	0.277	0.439	0.533	0.528	0.457	0.570	0.690
	MSeaHKG	**0.395**	**0.291**	**0.470**	**0.554**	**0.577**	**0.481**	**0.599**	**0.711**

Table 3: The model comparison of the relation prediction task on HKGs.

type	model	WikiPeople				JF17K			
		MRR	Hit@1	Hit@3	Hit@10	MRR	Hit@1	Hit@3	Hit@10
NNs	NaLP	0.735	0.595	0.852	0.938	0.825	0.762	0.873	0.927
	NeuInfer	0.765	0.686	0.877	0.900	0.861	0.832	0.885	0.910
GNNs	StarE	0.800	0.753	0.936	0.951	0.901	0.884	0.929	0.963
	G-MPNN	0.777	0.694	0.905	0.912	0.864	0.842	0.883	0.917
Search	S2S	0.813	0.744	0.928	0.960	0.912	0.877	0.932	0.951
	MSeaHKG	**0.831**	**0.787**	**0.955**	**0.972**	**0.933**	**0.894**	**0.950**	**0.972**

in a fact when all entities are known, i.e., $?(e_1, \cdots, e_n)$. We employ Mean Reciprocal Ranking (MRR) (Voorhees, 1999) and Hits@$\{1, 3, 10\}$. All reports are in the "filtered" setting (see more in Appendix D.1.3).

Baselines. Except for GNNs baselines in Sec. 2.2, we present key functions of most adopted baselines in Tab. 5. For tasks on HKGs, we mainly compare the proposed method with advanced HKG embedding models: (1) Geometric model: RAE (Zhang et al., 2018), which is upgrade version of m-TransH (Wen et al., 2016) that extended by KG embedding model TransH (Wang et al., 2014); (2) GNN-based models: G-MPNN (Yadati, 2020) and StarE (Galkin et al., 2020) (we re-implement G-MPNN and StarE because their initial task scenarios are not exactly match tasks in Sec. 4.1); (3) Other NN-based models: NaLP (Guan et al., 2019), HINGE (Rosso et al., 2020), and NeuInfer (Guan et al., 2020); (4) Multi-linear models: The final score of HypE (Fatemi et al., 2020) and RAM (Liu et al., 2021) is computed by multi-way inner product which is extended from bilinear KG embedding models (Yang et al., 2015). (5) Search method: S2S (Di et al., 2021) proposes a search space for tensor decomposition models and searches for sparse core tensors. It shares embeddings to jointly learn from facts with mixed arities to alleviate the issue of tensor modeling.

Except for the above methods on HKGs, we also include the tensor decomposition models (n-CP, n-TuckER, GETD) that work well on the scenario of facts with fixed arity. n-CP (Lacroix et al., 2018) leverages CANDECOMP/PARAFAC decomposition (Hitchcock, 1927), while n-TuckER (Balazevic et al., 2019) is based on Tucker decomposition (Tucker, 1966). GETD (Liu et al., 2020) proposes to reduce the model complexity by tensor ring decomposition.

4.2 MAIN EXPERIMENTAL RESULTS

The main results on HKGs (i.e., WikiPeople and JF17K) have been summarized into Tab. 2 and Tab. 3. Compared with Geometric and classic NN-based methods (e.g., NaLP), GNNs methods (e.g., StarE) achieve outstanding performance, which demonstrates the power of GNNs on the graph tasks. And StarE generally is better than G-MPNN in GNNs methods because the inner product way in G-MPNN cannot handle several relational patterns as mentioned in Sec. 1. Besides, although the multi-linear method RAM utilizes the simple inner product as its scoring function, it carefully models the role semantic information and interaction patterns, thus achieving good performance. Another searching method S2S alleviates the extension issue of tensor decomposition models from the fixed to the mixed scenario. It is still slightly inferior compared with other state-of-the-art methods. Overall,

Table 4: The model comparison of the link prediction task on facts with fixed arity.

type	model	WikiPeople-3		JF17K-3		WikiPeople-4		JF17K-4	
		MRR	H@10	MRR	H@10	MRR	H@10	MRR	H@10
Geo	RAE	0.239	0.379	0.505	0.644	0.150	0.273	0.707	0.835
NNs	NaLP	0.301	0.508	0.515	0.679	0.342	0.540	0.719	0.805
	HINGE	0.338	0.508	0.587	0.738	0.352	0.557	0.745	0.842
	NeuInfer	0.355	0.521	0.622	0.770	0.361	0.566	0.765	0.871
Tensor	n-CP	0.330	0.496	0.700	0.827	0.265	0.445	0.787	0.890
	n-TuckER	0.365	0.548	0.727	0.852	0.362	0.570	0.804	0.902
	GETD	0.373	0.558	0.732	0.856	0.386	0.596	0.810	0.913
Search	S2S	0.386	0.559	0.740	0.860	0.391	0.600	0.822	0.924
	MSeaHKG	**0.405**	**0.583**	**0.757**	**0.892**	**0.412**	**0.628**	**0.834**	**0.940**

all existing methods cannot consistently achieve the leading performance on different tasks and data sets. In this paper, we propose MSeaHKG to dynamically design the most suitable message function for the given data set and task by the pursuit of model performance. And the searched message functions can capture data-level properties (see case study in Appx. D.2), thereby showing the leading performance. Especially, the search space of another search method S2S is based on the tensor modeling. As discussed in Sec. 1 and Appx. A, the MRHG could be a more natural way to represent HKGs, thereby MSeaHKG benefits from building a message function search space in GNNs under the MRHG modeling.

We show experiments on facts with fixed arity in Tab. 4. As discussed in Sec. 1, we can indeed observe that classic tensor decomposition models (n-CP, n-TuckER, GETD) perform better than Geometric and NN-based methods on the scenario of fixed arity. Then, S2S proposes to dynamically sparsify the core tensor of tensor decomposition models for the given data and further improve the performance of tensor models. Moreover, we note that MSeaHKG still performs better than S2S even in the scenario of fixed arity. That is because S2S simply assumes 3 relationships between entities and relations in the search space: positive, irrelevant, and negative. But the message function space in Sec. 3.1 could characterize more complex interactions between entities and relations, thereby achieving improvements.

4.3 MORE INSIGHTS VIA EMPIRICAL STUDY

Due to the space limitation, we include more experimental results in Appx. D to provide more insights and verify several claims in this paper. First, we demonstrate several cases studies in Appx. D.2 that the searched message functions are data-dependent and can adapt to the given data set. Second, we conduct several ablation studies to analyze the components of the proposed method in Appx. D.3. Specifically, we show several variants of the proposed search space to demonstrate: (1) the GNN searching method cannot work well on HKGs (e.g., AutoGEL mentioned in Sec. 2.2) with a simple extension of message function, (2) automatic operation selection can improve the performance built on the manual operation tuning, (3) the structure design of message functions is important to improve performance on HKGs. Then, we implement two more popular NAS algorithms (Liu et al., 2018; Akimoto et al., 2019) to compare the searching effectiveness and efficiency of different one-shot NAS search algorithms in our scenarios.

5 CONCLUSION

In this paper, we propose a new message function searching method for HKGs, named MSeaHKG. First, we present a novel search space of message functions in MPNNs, which enables both structure search and operation selection in message functions. With our expressive message function design, some classic KGs/HKGs models and existing message functions for HKGs could be instantiated as special cases of the proposed space. Then, we develop an efficient one-shot NAS algorithm to search the message function and other GNN components for the given HKG. The empirical study demonstrates that the searched message functions are data-dependent and can adapt to the data patterns of the given HKGs. Overall, MSeaHKG has shown its effectiveness and efficiency on benchmark data sets.

REFERENCES

Youhei Akimoto, Shinichi Shirakawa, Nozomu Yoshinari, Kento Uchida, Shota Saito, and Kouhei Nishida. Adaptive stochastic natural gradient method for one-shot neural architecture search. In ICML, 2019.

Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. Dbpedia: A nucleus for a web of open data. In The Semantic Web, pp. 722–735. Springer, 2007.

I. Balazevic, C. Allen, and T. Hospedales. Tucker: Tensor factorization for knowledge graph completion. In EMNLP, pp. 5188–5197, 2019.

J. Bergstra, D. Yamins, and D. D. Cox. Making a science of model search: Hyperparameter optimization in hundreds of dimensions for vision architectures. 2013.

Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collabo-ratively created graph database for structuring human knowledge. In SIGMOD, pp. 1247–1250, 2008.

A. Bordes, N. Usunier, A. Garcia-Duran, J. Weston, and O. Yakhnenko. Translating embeddings for modeling multi-relational data. In NIPS, pp. 2787–2795, 2013.

Yixin Cao, Xiang Wang, Xiangnan He, Zikun Hu, and Tat-Seng Chua. Unifying knowledge graph learning and recommendation: Towards a better understanding of user preferences. In WWW, pp. 151–161, 2019.

Xiangxiang Chu, Tianbao Zhou, Bo Zhang, and Jixiang Li. Fair darts: Eliminating unfair advantages in differentiable architecture search. In ECCV, pp. 465–480. Springer, 2020.

Tim Dettmers, Pasquale Minervini, Pontus Stenetorp, and Sebastian Riedel. Convolutional 2D knowledge graph embeddings. In AAAI, 2018.

Shimin Di, Quanming Yao, and Lei Chen. Searching to sparsify tensor decomposition for n-ary relational data. In WebConf, pp. 4043–4054, 2021.

Thomas Elsken, Jan Hendrik Metzen, Frank Hutter, et al. Neural architecture search: A survey. J. Mach. Learn. Res., 20(55):1–21, 2019.

Stefan Falkner, Aaron Klein, and Frank Hutter. Bohb: Robust and efficient hyperparameter optimiza-tion at scale. In ICML, pp. 1437–1446. PMLR, 2018.

Bahare Fatemi, Perouz Taslakian, David Vazquez, and David Poole. Knowledge hypergraphs: Prediction beyond binary relations. 2020.

Mikhail Galkin, Priyansh Trivedi, Gaurav Maheshwari, Ricardo Usbeck, and Jens Lehmann. Message passing for hyper-relational knowledge graphs. In EMNLP, 2020.

Yang Gao, Hong Yang, Peng Zhang, Chuan Zhou, and Yue Hu. Graph neural architecture search. In IJCAI, volume 20, pp. 1403–1409, 2020.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In ICML, pp. 1263–1272. PMLR, 2017.

Saiping Guan, Xiaolong Jin, Yuanzhuo Wang, and Xueqi Cheng. Link prediction on n-ary relational data. In WWW, pp. 583–593, 2019.

Saiping Guan, Xiaolong Jin, Jiafeng Guo, Yuanzhuo Wang, and Xueqi Cheng. Neuinfer: Knowledge inference on n-ary facts. In ACL, pp. 6141–6151, 2020.

William L Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In NeurIPS, pp. 1025–1035, 2017.

W Keith Hastings. Monte carlo sampling methods using markov chains and their applications. 1970.

Frank L Hitchcock. The expression of a tensor or a polyadic as a sum of products. Journal of Mathematics and Physics, 6(1-4):164–189, 1927.

F. Hutter, L. Kotthoff, and J. Vanschoren. Automated Machine Learning: Methods, Systems, Challenges. Springer, 2018.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. arXiv preprint arXiv:1611.01144, 2016.

Shengli Jiang and Prasanna Balaprakash. Graph neural network architecture search for molecular property prediction. In IEEE Big Data, pp. 1346–1353. IEEE, 2020.

S. Kazemi and D. Poole. Simple embedding for link prediction in knowledge graphs. In NeurIPS, pp. 4284–4295, 2018.

D.P. Kingma and J. Ba. Adam: A method for stochastic optimization. In ICLR, 2014.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In ICLR, 2016.

T. Lacroix, N. Usunier, and G. Obozinski. Canonical tensor decomposition for knowledge base completion. In ICML, pp. 2863–2872, 2018.

H. Liu, K. Simonyan, and Y. Yang. DARTS: Differentiable architecture search. In ICLR, 2018.

Yu Liu, Quanming Yao, and Yong Li. Generalizing tensor decomposition for n-ary relational knowledge bases. In WebConf, pp. 1104–1114, 2020.

Yu Liu, Quanming Yao, and Yong Li. Role-aware modeling for n-ary relational knowledge bases. In WebConf, pp. 2660–2671, 2021.

Denis Lukovnikov, Asja Fischer, Jens Lehmann, and Sören Auer. Neural network-based question answering over knowledge graphs on word and character level. In WWW, pp. 1211–1220, 2017.

Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. arXiv preprint arXiv:1611.00712, 2016.

Christian Meilicke, Manuel Fink, Yanjie Wang, Daniel Ruffinelli, Rainer Gemulla, and Heiner Stuckenschmidt. Fine-grained evaluation of rule-and embedding-based systems for knowledge graph completion. In ISWC, pp. 3–20, 2018.

Maximilian Nickel, Kevin Murphy, Volker Tresp, and Evgeniy Gabrilovich. A review of relational machine learning for knowledge graphs. Proceedings of the IEEE, 104(1):11–33, 2015.

Maximilian Nickel, Lorenzo Rosasco, and Tomaso Poggio. Holographic embeddings of knowledge graphs. In AAAI, 2016.

A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In NeurIPS, pp. 8024–8035, 2019.

H. Pham, M. Guan, B. Zoph, Q. Le, and J. Dean. Efficient neural architecture search via parameter sharing. In ICML, pp. 4092–4101, 2018.

Andrea Rossi, Denilson Barbosa, Donatella Firmani, Antonio Matinata, and Paolo Merialdo. Knowledge graph embedding for link prediction: A comparative analysis. TKDD, 15(2):1–49, 2021.

Paolo Rosso, Dingqi Yang, and Philippe Cudré-Mauroux. Beyond triplets: hyper-relational knowledge graph embedding for link prediction. In WebConf, pp. 1885–1896, 2020.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In ESWC, pp. 593–607. Springer, 2018.

DI Shimin, YAO Quanming, Yongqi ZHANG, and CHEN Lei. Efficient relation-aware scoring function search for knowledge graph embedding. In ICDE, pp. 1104–1115. IEEE, 2021.

Z. Sun, Z. Deng, J. Nie, and J. Tang. RotatE: Knowledge graph embedding by relational rotation in complex space. In ICLR, 2019.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. Rotate: Knowledge graph embedding by relational rotation in complex space. In ICLR, 2018.

K. Toutanova and D. Chen. Observed versus latent features for knowledge base and text inference. In Workshop on CVSMC, pp. 57–66, 2015.

T. Trouillon, Christopher R., É. Gaussier, J. Welbl, S. Riedel, and G. Bouchard. Knowledge graph completion via complex tensor factorization. JMLR, 18(1):4735–4772, 2017.

Ledyard R Tucker. Some mathematical notes on three-mode factor analysis. Psychometrika, 31(3): 279–311, 1966.

Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. Composition-based multi-relational graph convolutional networks. In ICLR, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In NeurIPS, pp. 5998–6008, 2017.

Ellen Voorhees. The trec-8 question answering track report. In TREC, volume 99, pp. 77–82, 1999.

Q. Wang, Z. Mao, B. Wang, and L. Guo. Knowledge graph embedding: A survey of approaches and applications. TKDE, 29(12):2724–2743, 2017.

Zhen Wang, Jianwen Zhang, Jianlin Feng, and Zheng Chen. Knowledge graph embedding by translating on hyperplanes. In AAAI, 2014.

Jianfeng Wen, Jianxin Li, Yongyi Mao, Shini Chen, and Richong Zhang. On the representation and embedding of knowledge bases beyond binary relations. In IJCAI, 2016.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. ML, 8(3-4):229–256, 1992.

Sirui Xie, Hehui Zheng, Chunxiao Liu, and Liang Lin. SNAS: stochastic neural architecture search. arXiv preprint arXiv:1812.09926, 2018.

Naganand Yadati. Neural message passing for multi-relational ordered and recursive hypergraphs. Advances in Neural Information Processing Systems, 33, 2020.

B. Yang, W. Yih, X. He, J. Gao, and L. Deng. Embedding entities and relations for learning and inference in knowledge bases. In ICLR, 2015.

Quanming Yao and Mengshuo Wang. Taking human out of learning applications: A survey on automated machine learning. Technical report, arXiv:1810.13306, 2018.

Jiaxuan You, Zhitao Ying, and Jure Leskovec. Design space for graph neural networks. Advances in Neural Information Processing Systems, 33, 2020.

Arber Zela, Thomas Elsken, Tonmoy Saikia, Yassine Marrakchi, Thomas Brox, and Frank Hutter. Understanding and robustifying differentiable architecture search. arXiv preprint arXiv:1909.09656, 2019.

Richong Zhang, Junpeng Li, Jiajie Mei, and Yongyi Mao. Scalable instance reconstruction in knowledge bases via relatedness affiliated embedding. In WWW, pp. 1185–1194, 2018.

Yongqi Zhang, Quanming Yao, Wenyuan Dai, and Lei Chen. AutoSF: Searching scoring functions for knowledge graph embedding. In ICDE, pp. 433–444, 2020.

Ziwei Zhang, Xin Wang, and Wenwu Zhu. Automated machine learning on graphs: A survey. arXiv preprint arXiv:2103.00742, 2021.

Huan Zhao, Quanming Yao, and Weiwei Tu. Search to aggregate neighborhood for graph neural network. arXiv preprint arXiv:2104.06608, 2021.

Wang Zhili, Di Shimin, and Chen Lei. Autogel: An automated graph neural network with explicit link information. In NeurIPS, 2021.

Kaixiong Zhou, Qingquan Song, Xiao Huang, and Xia Hu. Auto-gnn: Neural architecture search of graph neural networks. arXiv preprint arXiv:1909.03184, 2019.

(a) KG with Multi-relational Graph Modeling.

(b) HKG with Multi-relational Hypergraph Modeling.

Figure 3: The illustration to KGs and HKGs. The binary facts are simplified in (b) to make the 3-ary facts look more prominent.

A DISCUSSION ON THE MODELING OF HKG

Given a set of facts with the fixed arity $\{r(e_1, \ldots, e_n)\}$, tensor models (e.g., CP (Lacroix et al., 2018) and TuckER (Balazevic et al., 2019)) use a $(n+1)$-dimensional tensor $\boldsymbol{G}^{n+1} \in \{0,1\}^{|R| \times |E| \times \cdots \times |E|}$ to represent facts, where $\boldsymbol{G}^{n+1}_{r,1,\ldots,n} = 1$ represents the fact $r(e_1, \ldots, e_n)$ existed otherwise $\boldsymbol{G}^{n+1}_{r,1,\ldots,n} = 0$. Then, tensor models leverage the tensor decomposition techniques to decompose $\boldsymbol{G}^{n+1}$ into embeddings $\boldsymbol{R}$ and $\boldsymbol{E}$ with a core tensor $\boldsymbol{\mathcal{Z}}^{n+1} \in \mathbb{R}^{d \times \cdots \times d}$:

$$\boldsymbol{G}^{n+1} = \boldsymbol{\mathcal{Z}}^{n+1} \times_1 \boldsymbol{R} \times_2 \boldsymbol{E} \times_3 \cdots \times_{n+1} \boldsymbol{E}.$$

Obviously, a tensor $\boldsymbol{G}^{n+1}$ can only model facts with the fixed arity n. Thus, we have to build $\{\boldsymbol{G}^2, \ldots, \boldsymbol{G}^{N+1}\}$ to model the facts with mixed arities $S = \{r(e_1, \ldots, e_n) : n \in \{2, \ldots, N\}\}$ and decompose them into $N-1$ sets of entity and relation embeddings, such as $\{\boldsymbol{E}^n, \boldsymbol{R}^n\}_{n=2}^N$. But KBs are known to have the data sparse issue, thus learning multiple set of embeddings could lead to severe problems.

As mentioned in Sec. 1, multi-relational hypergraphs (MRHGs) $\mathcal{G}(E, R, S)$ could be a more natural way to represent HKGs. We illustrate examples of KGs and HKGs in Fig. 3 (a) and (b), respectively. Given a fact with high arity (e.g., `playCharacterIn`(e_1, e_3, e_5)), MRHG can first store the correspondence between multiple entities by a hyperedge (e_1, e_3, e_5), then label this hyperedge with the relation `playCharacterIn`. Moreover, Fig. 3 (b) demonstrates that the facts with mixed arities ($n \in \{2, 3\}$ in this example) can be represented by a MRHG. Thus, MRHG allows us to directly encode a given HKG into entity and relation embeddings, where every embedding vector is jointly learned from low and high arities. However, tensor modeling leads the model to learn multiple sets of embeddings.

Besides, HKGs generally contain more complete information compared with KGs. For example, it is hard to answer "who plays Spock in StarTrek-1?" with the KG example (Fig. 3 (a)). That is because KGs suffer from the information loss of correspondence among multiple entities. Generally, the constructing procedure of KG, named Star-to-Clique Conversion, has been verified to be irreversible and caused the information loss in the facts with high arities (Wen et al., 2016). Therefore, we believe that HKG could be a potential solution to solve complex Q&A scenarios.

(a) HolE (Nickel et al., 2016).   (b) RotatE (Sun et al., 2019).   (c) n-CP (Lacroix et al., 2018).   (d) n-DistMult (Yang et al., 2015).

Figure 4: Several instantiation cases of MSeaHKG message function space. $\circ$ denotes circular correlation $corr(\cdot)$ (Nickel et al., 2016), $*$ denotes inner product $mult(\cdot)$ (Yang et al., 2015), $-$ denotes the substraction $sub(\cdot)$ (Bordes et al., 2013), $\star$ is from RotatE (Sun et al., 2018).

B   DISCUSSION ON DATA-LEVEL PROPERTIES OF KGS/HKGS AND MESSAGE FUNCTION DESIGN

B.1   DATA-LEVEL PROPERTIES IN KGS: RELATIONAL PATTERNS

In the past decades, the research community has found that the relations of KGs exhibit different patterns. For example, we can infer that `neighborOf(location2,location1)` must be true as long as `neighborOf(location1,location2)` is true, like `neighborOf(ShenZhen,HongKong)`. But for other relations (e.g., `largerThan`), we know `largerThan(value2,value1)` must be false if `largerThan(value1,value2)` is true. Many relational patterns in KGs have been found and discussed (Kazemi & Poole, 2018; Rossi et al., 2021), such as symmetry, anti-symmetry, asymmetry, inversion, composition, hierarchy, intersection. However, various KGs usually contain different relational patterns with different proportions of facts. To handle diverse relational patterns on different KGs (i.e., data-level properties), kinds of scoring functions have been proposed to cover as many relational patterns as possible, i.e., pursuing expressiveness. Given the learned embeddings $\boldsymbol{\omega} = \{\boldsymbol{E}, \boldsymbol{R}\}$, the scoring function $f(\cdot)$ is proposed to evaluate whether the fact is true or false (check Appx. C.1 and Tab. 5 for more details about scoring function). For the sake of understanding, we here present the requirements of several relational patterns on scoring functions:

- Symmetry: r is symmetry if $r(e_j, e_i)$ must be true when $r(e_i, e_j)$ is true, i.e., $f(\boldsymbol{r}(\boldsymbol{e}_i, \boldsymbol{e}_j)) = f(\boldsymbol{r}(\boldsymbol{e}_j, \boldsymbol{e}_i))$

- Anti-symmetry: r is anti-symmetric if $r(e_j, e_i)$ must be false when $r(e_i, e_j)$ is true, i.e., $f(\boldsymbol{r}(\boldsymbol{e}_i, \boldsymbol{e}_j)) = -f(\boldsymbol{r}(\boldsymbol{e}_j, \boldsymbol{e}_i))$.

- Asymmetry: The plausibility of $r(e_j, e_i)$ is unknown when $r(e_i, e_j)$ is true, $f(\boldsymbol{r}(\boldsymbol{e}_i, \boldsymbol{e}_j)) \neq f(\boldsymbol{r}(\boldsymbol{e}_j, \boldsymbol{e}_i))$.

- Inverse: r_1 and r_2 are inverse relations if $r_1(e_i, e_j)$ is true and $r_2(e_j, e_i)$ is true. Then, $f(\boldsymbol{r}_1(\boldsymbol{e}_i, \boldsymbol{e}_j)) = f(\boldsymbol{r}_2(\boldsymbol{e}_j, \boldsymbol{e}_i))$

As mentioned in Sec. 1, the message function of G-MPNN may not be able to infer the non-symmetric relations. Suppose that $s_1 = r(e_1, e_2)$ is true and r is one of any non-symmetric relations (e.g., anti-symmetry $s_2 = r(e_2, e_1)$ must be false). Let $\boldsymbol{h}_i$ be the entity feature and $\boldsymbol{h}_r$ be the relation feature. According to the message function of G-MPNN in Eq. 4, we can learn the hidden embeddings of $\boldsymbol{m}_i$: $\boldsymbol{m}_1 = \boldsymbol{m}_2 = \boldsymbol{h}_r * \boldsymbol{h}_1 * \boldsymbol{p}_{e_1,s} * \boldsymbol{h}_2 * \boldsymbol{p}_{e_2,s}$ Then e_i are updated with $\boldsymbol{m}_i$. With the scoring function of G-MPNN (multiple inner product), we can compute $f(\boldsymbol{r}(\boldsymbol{e}_1, \boldsymbol{e}_2)) = \boldsymbol{h}_r * \boldsymbol{p}_{e_1,s} * \boldsymbol{e}_1 * \boldsymbol{p}_{e_2,s} * \boldsymbol{e}_2$. Because e_1, e_2 are seen in s_1, G-MPNN will assign the positional embeddings e_1, e_2 in s_1 when computing the score of s_2, thereby leading $f(\boldsymbol{r}(\boldsymbol{e}_1, \boldsymbol{e}_2)) = f(\boldsymbol{r}(\boldsymbol{e}_2, \boldsymbol{e}_1))$. Thus, we argue that the fixed message function is not flexible enough to capture the relational patterns of the given HKGs, especially its performance may not be good if some uncovered relational patterns exist in the given data set.

Table 5: Scoring Functions for Facts with High-order Arities.

Type	Model	Scoring Function Design $f(s; \boldsymbol{\omega})$	Notes
Geo	m-TransH	$\left\| \sum_{i=1}^{n} a_j (\boldsymbol{e}_i - \boldsymbol{v}_r^\top \boldsymbol{e}_i \boldsymbol{v}_r) + \boldsymbol{r} \right\|^2$	$\boldsymbol{v}_r$ is relation dependent. $FC(\cdot)$ is fully connected layer.
	RAE	$\left\| \sum_{i=1}^{n} a_j (\boldsymbol{e}_i - \boldsymbol{v}_r^\top \boldsymbol{e}_i \boldsymbol{v}_r) + \boldsymbol{r} \right\|^2 + \sum_{ij} FC([\boldsymbol{e}_i, \boldsymbol{e}_j])$	
Tensor	n-CP	$\boldsymbol{r} * \boldsymbol{e}_1^{(1)} * \boldsymbol{e}_2^{(2)} * \cdots * \boldsymbol{e}_n^{(n)}$	$\boldsymbol{e}_i^{(j)}$ is for e_i in j-th position. $\boldsymbol{\mathcal{Z}} \in \mathbb{R}^{d \times \cdots \times d}$, $\times_i$ is tensor product in i-th mode. $TR(\cdot)$ is tensor ring decomposition $\boldsymbol{\mathcal{W}}_i$ is a 3-order tensor.
	n-TuckER	$\boldsymbol{\mathcal{Z}} \times_1 \boldsymbol{r} \times_2 \boldsymbol{e}_1 \times_3 \cdots \times_{n+1} \boldsymbol{e}_n$	
	GETD	$TR(\boldsymbol{\mathcal{W}}_1, \ldots, \boldsymbol{\mathcal{W}}_k) \times_1 \boldsymbol{e}_1 \times_2 \boldsymbol{e}_2 \times_3 \cdots \times_{n+1} \boldsymbol{e}_n$	
GNNs	G-MPNN	$\boldsymbol{r}_{s,P(s)} * \prod_{e_j \in Seen(s)} \boldsymbol{p}_{e_j,s} * \boldsymbol{e}_j$	$Seen(s)$ returns the seen entities e_j in s
Multi-linear	HypE	$\boldsymbol{r} * Conv(\boldsymbol{e}_1) * Conv(\boldsymbol{e}_2) * \cdots * Conv(\boldsymbol{e}_n)$	$Conv(\cdot)$ is the convolutional filter. $\boldsymbol{r}_i$ is embedding for i-th role of r, $\bar{\boldsymbol{e}}_j \in \mathbb{R}^{m \times d}$ is embedding matrix of e
	RAM	$\sum_{i=1}^{n} \boldsymbol{r}_i * \boldsymbol{p}_i^r(1,:) \bar{\boldsymbol{e}}_1 * \cdots * \boldsymbol{p}_i^r(n,:) \bar{\boldsymbol{e}}_n$	
Search	S2S	$\sum_{j_r, j_1, \ldots, j_s} \boldsymbol{\mathcal{Z}}_i^n \times_1 \boldsymbol{r}^{j_r} \times_2 \boldsymbol{e}_1^{j_1} \times_3 \cdots \times_{n+1} \boldsymbol{e}_n^{j_n}$	$\boldsymbol{\mathcal{Z}}_i^n$ is the searched sparse core tensor, i denotes $(j_r, j_1, \ldots, j_s)$.

B.2 DISCUSSION ON THE CAPABILITY OF MESSAGE FUNCTIONS TO COVER RELATIONAL PATTERNS ON HKGS

As mentioned in Appx. B.1, pursuing expressiveness is one way to cover relational patterns on KGs. Such potential solution is also discussed in Sec. 1. However, Meilicke et al. (2018); Rossi et al. (2021) report that being expressive does not mean achieving good performance even the model can cover those relational patterns. Thus, AutoSF (Zhang et al., 2020) proposes to search bilinear-based scoring functions for KGs and consistently achieve good performance. Inspired by literature, MSeaHKG proposes to search proper message functions for the pursuit of high model performance on any given HKGs.

Generally, the relational patterns on HKGs have not been explored before. Inspired by literature on KGs, we roughly summarize a high level representations of relational patterns in the scenario of high arity as:

$$f(r_1(pemu(e_1, \ldots, e_n)); \boldsymbol{\omega}) ? f(r_2(pemu(e_1, \ldots, e_n)); \boldsymbol{\omega}),$$

where r_1, r_2 may be same relation or different, $pemu(\cdot)$ represents the permutation of n entities $\{e_i\}_{i=1}^n$, and $? \in \{=, >, \neq, \neg\}$. For example, $f(r_1(pemu(e_1, \ldots, e_n)); \boldsymbol{\omega}) = f(r_1(pemu(e_1, \ldots, e_n)); \boldsymbol{\omega})$ indicates r_1 is a symmetry. In this paper, since our scoring function design is a linear transformation (see Appx. C.1), the design of message function in MPNNs (i.e., $\boldsymbol{\omega} = X_{\boldsymbol{\Theta}}(\mathcal{G})$) will be the crucial component to capture relational patterns. To capture the permutation information $pemu(\cdot)$, we first utilize $\boldsymbol{W}_{P(e)}$ to encode the positional information, which transforms entity embeddings into corresponding positions. Then, the operator $\gamma(\cdot)$ concatenates the entity embeddings after encoding positional information. Lastly, the operator $\phi(\cdot)$ computes the interaction between $\boldsymbol{r}$ with $\boldsymbol{e}_i$. In other words, $\boldsymbol{W}_{P(e)}$ and $\gamma(\cdot)$ are employed to represent $pemu(\cdot)$, and $\phi(\cdot)$ is utilized to represent the correlation between r and $pemu(\cdot)$. Within such design, most classic scoring function designs (including Geometric models (Bordes et al., 2013; Nickel et al., 2016; Sun et al., 2019), Bilinear models (Yang et al., 2015) and Tensor models (Lacroix et al., 2018)) and GNNs for KGs/HKGs can be instantiated as special cases in the MSeaHKG space. We have demonstrated several examples of classic scoring function designs in Fig. 4. Note that the expressiveness of these models has been fully investigated in literature. Every model can cover one or multiple relational patterns, which can make our message function space expressive enough to handle most HKGs. In other words, the search space of MSeaHKG has the potential to return a GNN model that can adapt to the relational patterns of the given HKG.

C   SUPPLEMENTARY OF SEARCH ALGORITHM

C.1   SCORING FUNCTION FORMULATION

As mentioned in Sec. 3.2, the GNN model X embeds the HKG $\mathcal{G}(E, R, S)$ into the low-dimensional vector space $\boldsymbol{\omega} = \{\boldsymbol{E}, \boldsymbol{R}\}$, i.e., $\boldsymbol{\omega} = X(\mathcal{G})$. Besides, it is also important to design a scoring function $f(s; \boldsymbol{\omega})$ to interprets the plausibility of the fact s based on the learned $\boldsymbol{\omega}$ (Rossi et al., 2021; Zhang et al., 2020; Shimin et al., 2021). Many promising scoring functions have been proposed in the past decades, including geometric models (e.g., TransE (Bordes et al., 2013) and RotatE (Sun et al., 2018)), neural network models (e.g., ConvE (Dettmers et al., 2018)), tensor decomposition models (e.g., CP (Lacroix et al., 2018), TuckER (Balazevic et al., 2019)). Inspired by the success of literature, we regard the scoring function design as a component of implementations. In this paper, we focus on those scoring functions for facts with high arity ($n > 2$) and summarize the popular ones in Tab. 5. Note that StarE (Galkin et al., 2020) employs the Transformer (Vaswani et al., 2017) as its scoring function, thus it is not included in Tab. 5.

In principle, MSeaHKG can implement most of existing scoring functions as its decoder. But we argue that the power of the searched message function could well model the interaction between entities and relations in the encoding step. Within a powerful encoder, it may be unnecessary to introduce a complex scoring function like CompGCN (Vashishth et al., 2020) and StarE (Galkin et al., 2020) to decode embeddings. In this paper, we simply concatenate the embeddings of known entities and relations in a fact and feed it into the linear transformation with a softmax operator.

C.2   LOSS FUNCTION W.R.T. RELATION PREDICTION

Note that the loss function $\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})$ introduced in Sec. 3.2 is under the scenario of link prediction task. In the relation classification task, the probability score is formed to $\boldsymbol{p}^s \in [0, 1]^{|R|}$, i.e., predicting the ground truth $r \in R$ when the relation is missing in $?(e_1, \ldots, e_2)$. The loss function is defined as:

$$\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) = \sum_{s \in S} \sum_{r \in R} \boldsymbol{y}_r^s \log \boldsymbol{p}_r^s,$$

where $\boldsymbol{y}_r^s = 1$ if r is the ground truth relation in s.

C.3   FULL DERIVATION INVOLVED IN SEC. 3.2

First, we present the full derivation of Eq. 10 and Eq. 11, and their approximation based on Monte-Carlo sampling:

$$\nabla_{\bar{\Theta}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})] = \nabla_{\bar{\Theta}} E_{U \sim p(U)}[\mathcal{L}(g_{\bar{\Theta}}(U), \boldsymbol{\omega}; \mathcal{G})] = \nabla_{\bar{\Theta}} \int p(U) \mathcal{L}(g_{\bar{\Theta}}(U), \boldsymbol{\omega}; \mathcal{G}) dU$$

$$= \int p(U) \nabla_{\bar{\Theta}} \mathcal{L}(g_{\bar{\Theta}}(U), \boldsymbol{\omega}; \mathcal{G}) dU = E_{U \sim p(U)}[\nabla_{\bar{\Theta}} \mathcal{L}(g_{\bar{\Theta}}(U), \boldsymbol{\omega}; \mathcal{G})]$$

$$= E_{U \sim p(U)}[\mathcal{L}'(g_{\bar{\Theta}}(U), \boldsymbol{\omega}; \mathcal{G}) \nabla_{\bar{\Theta}} g_{\bar{\Theta}}(U)],$$

$$\nabla_{\boldsymbol{\omega}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})] = \nabla_{\boldsymbol{\omega}} \int p_{\bar{\Theta}}(X) \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) dX = \int p_{\bar{\Theta}}(X) \nabla_{\boldsymbol{\omega}} \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) dX$$

$$= E_{X \sim p_{\bar{\Theta}}(X)}[\nabla_{\boldsymbol{\omega}} \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})].$$

Second, we build the reparameterization trick $X = g_{\bar{\Theta}}(U)$ (mentioned in Sec. 3.2) based on Gumbel-Softmax (Jang et al., 2016) or Concrete distribution (Maddison et al., 2016). For simplicity, we simplify $\bar{\Theta}$ to the parameter $\bar{\boldsymbol{\theta}}$ for a specific operator space $\mathcal{O}$:

$$X_o = g_{\bar{\boldsymbol{\theta}}}(U) = \frac{\exp((\log \bar{\boldsymbol{\theta}}_o - \log(-\log(U_o)))/\tau)}{\sum_{o' \in \mathcal{O}} \exp((\log \bar{\boldsymbol{\theta}}_{o'} - \log(-\log(U_{o'})))/\tau)}, \tag{12}$$

where τ is the temperature of softmax, and $U_o \sim Uniform(0, 1)$. It has been proven that $p(\lim_{\tau \to 0} X_o = 1) = \bar{\boldsymbol{\theta}}_o / \sum_{o' \in \mathcal{O}} \bar{\boldsymbol{\theta}}_{o'}$ making the stochastic differentiable relaxation unbiased once converged (Xie et al., 2018). And the details of $\nabla_{\bar{\Theta}} g_{\bar{\Theta}}(U)$ can refer to Xie et al. (2018).

D MORE EXPERIMENTS

D.1 EXPERIMENTAL SETUP

D.1.1 HYPER-PARAMETER SETTINGS

We have summarized the hyper-parameters of this paper in Tab. 6. The hyper-parameter set includes Adam optimizer (Kingma & Ba, 2014), learning rate $\in \{0.1, 0.01, 0.001, 0.0001, 0.00001\}$, # MPNN layers $\in \{1, 2, 3, 4\}$ (see left part of Fig. 2), # layers in message functions $K \in \{1, 2, 3, 4, 5\}$ (see right part of Fig. 2), batch size $\in \{64, 128, 256, 512\}$, embedding dimension $d \in \{64, 128, 256, 512\}$, dropout ratio $\in \{0, 0.05, 0.1, 0.15, \ldots, 0.5\}$, label smoothing ratio $\tau \in \{0, 0.1, 0.2, \ldots, 0.9\}$. Note that the label smoothing ratio τ is employed to relax the one-hot label vector $\boldsymbol{y}$. In practical, we set $\boldsymbol{y}_i = 1 - \tau$ for the ground truth entity/relation, while $\boldsymbol{y}_i = \tau/|E|-1$ for link prediction and $\boldsymbol{y}_i = \tau/|R|-1$ for relation prediction. That is because there are usually a large candidate space for relations and entities, while Using one-hot vector is quite restrictive. All hyper-parameters are tuned with the help of `optuna.samplers.TPESampler` (Bergstra et al., 2013; Falkner et al., 2018)[1].

Table 6: List of hyper-parameters in main experiments. W and J are abbreviations of WikiPeople and JF17K, respectively.

Hyperparameters	Link Prediction						Relation Prediction	
	WikiPeople	JF17K	W-3	J-3	W-4	J-4	WikiPeople	JF17K
Learning rate	0.0001	0.001	0.0001	0.001	0.0001	0.0001	0.0001	0.001
# MPNN layers	2	2	1	1	1	1	2	2
# Layers in $mg(\cdot)$ K	4	4	3	2	2	3	4	4
Batch size	256	128	128	128	256	128	256	128
Embedding dim d	256	256	128	128	256	128	128	128
Dropout ratio	0.15	0.2	0.1	0.1	0.05	0.15	0.2	0.15
Label smoothing ratio τ	0.3	0.8	0.7	0.5	0.8	0.7	0.1	0.1

D.1.2 DATA STATISTICS

Here we present the statistic summary of the benchmark data sets in this paper. And the links for download them.

Table 7: The statistical summary on data sets.

type	data set	# all facts	# facts ($n > 2$)	max arity N	# ent	# rel	train	valid	test
Mixed	JF17K	100,947	46,320	6	28,645	322	76,379	-	24,568
	WikiPeople	382,229	44,315	9	47,765	707	305,725	38,223	38,281
Fixed	WN18RR	93,003	0	2	40,943	11	86,835	3,034	3,134
	FB15k237	310,116	0	2	14,541	237	272,115	17,535	20,466
	JF17K-3	34,544	34,544	3	11,541	104	27,635	3,454	3,455
	JF17K-4	9,509	9,509	4	6,536	23	7,607	951	951
	WikiPeople-3	25,820	25,820	3	12,270	66	20,656	2,582	2,582
	WikiPeople-4	15,188	15,188	4	9,528	50	12,150	1,519	1,519

D.1.3 EVALUATION MEASUREMENT

Let $\text{rank}_{i,n}$ denote the rank of ground truth entity at position n of i-th fact $s = (r, e_1, \ldots, e_N)$, defined as:
$$\text{rank}_{i,n} = |\{e' \in E \setminus \{e_n\} : f(s'; \boldsymbol{\omega}) > f(s; \boldsymbol{\omega})\}| + 1,$$
where $s' = (r, e_1, \ldots, e_{n-1}, e', \ldots, e_N)$. As in (Bordes et al., 2013; Wang et al., 2014), we report performance under the "filtered" setting, i.e., evaluating the rank of test fact after removing all corrupted facts that exist in the train, valid, and test data set. That is because true facts in data set

---

[1]`https://optuna.readthedocs.io/en/stable/reference/generated/optuna.samplers.TPESampler.html`

(a) WN18RR.   (b) FB15k237.   (c) JF17K-3.

Figure 5: Several message functions searched by MSeaHKG on different data sets.

should be not considered as faults when evaluating a test fact. Correspondingly, $\text{rank}_{i,n}$ under filtered setting is formed as:

$$\text{rank}_{i,n} = |\{e' \in E \setminus \{e_n\} : f(s'; \boldsymbol{\omega}) > f(s; \boldsymbol{\omega}) \cap s' \notin S\}| + 1.$$

Then we adopt the classical metrics (Bordes et al., 2013; Wang et al., 2014):

- Mean Reciprocal Ranking (MRR): $1/N|S| \sum_{i=1}^{|S|} \sum_{n=1}^{N} 1/\text{rank}_{i,n}$;

- Hit@1, Hit@3, and Hit@10, where Hit@k is given by $1/|S| \sum_{i=1}^{|S|} \sum_{n=1}^{N} \mathbb{I}(\text{rank}_{i,n} \le k)$ and $\mathbb{I}(\cdot)$ is the indicator function.

Note that the higher MRR and Hit@n values mean better embedding quality.

D.2 CASE STUDY

The relational patterns on KGs (see Appx. B) have been fully investigated (Kazemi & Poole, 2018; Rossi et al., 2021) in existing works. Thus, we first show the case studies on two benchmark KGs WN18RR (Dettmers et al., 2018) and FB15k237 (Toutanova & Chen, 2015) (see Tab. 7 for data statistics), which have removed the duplicate and inverse relations of WN18 and FB15k (Bordes et al., 2013; Dettmers et al., 2018). As presented in Rossi et al. (2021), the irreflexive, anti-symmetric, and symmetric relations account for a major proportion of these two data sets, especially facts with the symmetric relations reach 37% in WN18RR. We found that the message function searched on WN18RR (Fig. 5 (a)) is the exact RotatE model (Sun et al., 2019), which has been proven to cover symmetric relations. As for the message function searched on FB15k237 (Fig. 5 (b)), it first feeds the relation embedding into a transformation matrix $\boldsymbol{W}$. We infer that is mainly because FB15k237 has 237 relations, which is more than 11 relations on WN18RR. For the message function searched on facts with high arity, we show an example on JF17K-3 in Fig. 5 (c). It demonstrates that the message function tends to be deeper and complex in the high arity case. Note that the full version of message functions searched on WikiPeople ($N = 9$) and JF17K ($N = 6$) is too large to put it on paper. Overall, we can observe that the message functions are data-dependent from Fig. 5.

D.3 ABLATION STUDY

Except for main experimental results, here we report the performance of several variants of MSeaHKG (see Tab. 8) to investigate some key designs in this paper, including MSeaHKG^{W_r}, MSeaHKG^{op}, MSeaHKG^{st} for the search space, MSeaHKG^{darts} and MSeaHKG^{rl} for the search algorithm.

D.3.1 SEARCH SPACE

We first present the configuration of variants:

Table 8: The comparison of variants of MSeaHKG in the link prediction task on HKGs.

Type	Model	WikiPeople				JF17K			
		MRR	Hit@1	Hit@3	Hit@10	MRR	Hit@1	Hit@3	Hit@10
GNNs	StarE	0.378	0.265	0.452	0.542	0.542	0.454	0.580	0.685
	G-MPNN	0.367	0.258	0.439	0.526	0.530	0.459	0.572	0.688
Search	S2S	0.372	0.277	0.439	0.533	0.528	0.457	0.570	0.690
	MSeaHKG	**0.395**	**0.291**	**0.470**	**0.554**	**0.577**	**0.481**	**0.599**	**0.711**
Variants of space	MSeaHKG^{W_r}	0.354	0.233	0.431	0.520	0.512	0.445	0.553	0.671
	MSeaHKG^{op}	0.385	0.274	0.460	0.548	0.554	0.468	0.591	0.699
	MSeaHKGst	0.391	0.278	0.465	0.552	0.563	0.475	0.602	0.706
Variants of algorithm	MSeaHKG^{darts}	0.373	0.275	0.445	0.535	0.554	0.460	0.588	0.697
	MSeaHKG^{rl}	0.380	0.281	0.457	0.542	0.563	0.472	0.593	0.701

- MSeaHKG^{W_r} basically enables current GNN searching methods working on HKGs. Inspired by R-GCN (see Eq. 2), we first replace the transform matrix $\boldsymbol{W}$ in $mg_c(\cdot)$ (see Eq. 1) to $\boldsymbol{W}_r$. Then, we concatenate the entity embeddings as $\boldsymbol{h} = concat(\boldsymbol{e}_1, \ldots, \boldsymbol{e}_n, \boldsymbol{0}, \ldots, \boldsymbol{0})$. Note that the number of zero embeddings $\boldsymbol{0}$ is equal to $n_{max} - n$. We utilize the message function $mg_c(\boldsymbol{r}(\boldsymbol{e}_1, \ldots, \boldsymbol{e}_n)) = \boldsymbol{W}_r \boldsymbol{h}$ to replace Eq. 7. Other steps are same with original version.

- MSeaHKG^{op} only searches operations of operators ϕ and γ in $mg(\cdot; \boldsymbol{\theta})$ (i.e., $\boldsymbol{\theta} = \{\theta_i^{\phi_k}\} \cup \{\theta_i^{\gamma_k}\}$), while keeping the structure of StarE's message functions. Other steps are same with original version.

- MSeaHKGst only searches structures of the proposed message function $mg(\cdot; \boldsymbol{\theta})$, and sets ϕ, γ to $corr, wsum$ respectively (i.e., $\boldsymbol{\theta} = \{\theta_{ij}^k\}$). The fixed operations are selected based on better empirical performance. Other steps are same with original version.

From Tab. 8, we observe that the simple extension version MSeaHKG^{W_r} even cannot achieve as good performance as existing GNNs (e.g., StarE and G-MPNN). This verifies the claim that the simple message function in the existing GNN searching method (e.g., AutoGEL (Zhili et al., 2021) discussed in Sec. 2.2) may not be able to handle the complex correlations between relations and entities on HKGs. Moreover, MSeaHKG^{op} keeps the same message function structure with StarE but searches suitable operations. Differ from manually tuning operations in StarE, the automatic way is more powerful so that MSeaHKG^{op} achieves a minor improvement compared with StarE. As for MSeaHKGst, it can search for more flexible structures of message functions for the given HKG and achieve the best performance among several variants. It can illustrate that the message function design is important to HKG embedding. However, MSeaHKGst is still slightly inferior compared with the original version of MSeaHKG. This shows that the best structure and operations are dependent. Simply fixing operations to search the structure may lead to the sub-optimum.

D.3.2 SEARCH ALGORITHM

In this paper, we mainly focus on one-shot NAS search algorithms due to their searching efficiency (see more discussion in Sec. 2.1). Existing one-shot NAS algorithms can be roughly categorized into: stochastic differentiable method (e.g., SNAS (Xie et al., 2018)), deterministic differentiable method (e.g., DARTS (Liu et al., 2018)), and policy gradient-based method (e.g., ENAS (Pham et al., 2018), ASNG (Akimoto et al., 2019)). Here, we implement two more variants of MSeaHKG, MSeaHKG^{darts} based on DARTS and MSeaHKG^{rl} based on ASNG, to investigate the performance of other two kinds of NAS search algorithms in our application scenario.

- MSeaHKG^{darts} follows DARTS to directly relax $\boldsymbol{\Theta}$ to learnable parameters. Then, the computation in DAG (see Eq. 6) will be reformed to:

$$\boldsymbol{h}_i^k = \sum_{j=1}^{|\mathcal{O}|} \alpha_{ij}^k \cdot o_i^k(\boldsymbol{h}_j^{k-1}), \; \alpha_{ij}^k = \frac{\theta_{ij}^k}{\sum_{j'=1}^{|\mathcal{O}|} \theta_{ij'}^k}. \tag{13}$$

Then, we are able to minimize the loss $\mathcal{L}(\boldsymbol{\Theta}, \boldsymbol{\omega}; \mathcal{G})$ through the gradient $\nabla_{\boldsymbol{\Theta}} \mathcal{L}(\cdot)$.

Table 9: The training time comparison (in hours) of GNN-based models in the link prediction task on HKGs.

Type	Model	HKGs		Arity=3		Arity=4	
		WikiPeople	JF17K	W-3	J-3	W-4	J-4
GNNs	G-MPNN	15.4 ± 2.6	4.1 ± 0.3	1.2 ± 0.1	0.6 ± 0.1	0.5 ± 0.1	0.6 ± 0.1
	StarE	137.5 ± 6.3	16.7 ± 2.2	2.6 ± 0.4	4.7 ± 0.8	2.3 ± 0.4	1.9 ± 0.2
Search	MSeaHKG	30.9 ± 4.7	7.7 ± 1.8	1.8 ± 0.4	1.4 ± 0.2	0.9 ± 0.1	1.1 ± 0.2
Variants of	MSeaHKG^{darts}	40.2 ± 2.5	11.5 ± 2.2	2.5 ± 0.5	2.1 ± 0.3	1.5 ± 0.2	1.3 ± 0.1
algorithm	MSeaHKG^{rl}	35.1 ± 3.0	10.3 ± 1.7	2.3 ± 0.3	1.5 ± 0.2	1.4 ± 0.2	1.1 ± 0.1

- MSeaHKG^{rl} follows the policy gradient-based NAS search algorithm to derive:

$$\nabla_{\bar{\Theta}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G})] = \nabla_{\bar{\Theta}} \int p_{\bar{\Theta}}(X) \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) dX = \int \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) \nabla_{\bar{\Theta}} p_{\bar{\Theta}}(X) dX$$

$$= \int \mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) \nabla_{\bar{\Theta}} \log p_{\bar{\Theta}}(X) \cdot p_{\bar{\Theta}}(X) dX \qquad (14)$$

$$= \nabla_{\bar{\Theta}} E_{X \sim p_{\bar{\Theta}}(X)}[\mathcal{L}(X, \boldsymbol{\omega}; \mathcal{G}) \nabla_{\bar{\Theta}} \log p_{\bar{\Theta}}(X)],$$

where $\nabla_{\bar{\Theta}} p_{\bar{\Theta}}(X) = \log p_{\bar{\Theta}}(X) p_{\bar{\Theta}}(X)$ is the policy gradient trick (Williams, 1992). In practical, we utilize ASNG (Akimoto et al., 2019) to instantiate Eq. 14, which implements the fisher information matrix for fast convergence and adaptive learning rate for robustness.

We here analyze the model comparison between original MSeaHKG with its variants MSeaHKG^{rl} and MSeaHKG^{darts}. From Tab. 8 and Tab. 9, we observe that MSeaHKG and MSeaHKG^{rl} have better performance than MSeaHKG^{darts} in both effectiveness and efficiency comparisons. First, DARTS aims to train a supernet by mixing all candidate operations during the searching phase, then it will derive a discrete architecture after finishing the search. But the weights $\boldsymbol{\alpha}_i^k$ in Eq. 13 cannot cannot converge to a one-hot vector, which lead to performance collapse after removing $|\mathcal{O} - 1|$ operations in $\mathcal{O}$ (Zela et al., 2019; Chu et al., 2020). Second, it will consume more computational resources when maintaining all operations during the search. Instead, MSeaHKG and MSeaHKG^{rl} are to train discrete architectures in searching (the bounded discreteness of MSeaHKG is discussed in Appx. C.3), which avoids performance collapse and large computational overhead. As for the comparison between MSeaHKG with MSeaHKG^{rl}, MSeaHKG achieves slight improvements. That is mainly because MSeaHKG directly calculates the gradient w.r.t. $\bar{\Theta}$ from the loss $\mathcal{L}(\cdot)$, while MSeaHKG^{rl} takes the loss $\mathcal{L}(\cdot)$ as a reward to feed it to a RL controller.

From Tab. 9, we also can observe the efficiency comparison between GNN-based models (G-MPNN, StarE, and MSeaHKG). Like other NAS methods, MSeaHKG requires two training phases, searching architecture and training the searched architecture from the scratch. Thus, it needs more running time compared with G-MPNN. Moreover, both G-MPNN and MSeaHKG utilizes the simple decoders (i.e., scoring function discussed in Appx. C.1), while StarE adopts the complex transformer as its decoder. Thus, StarE is less efficient.