GEOMETRIC TRANSFORMERS FOR PROTEIN INTERFACE CONTACT PREDICTION

ABSTRACT

Computational methods for predicting the interface contacts between proteins come highly sought after for drug discovery as they can significantly advance the accuracy of alternative approaches, such as protein-protein docking, protein function analysis tools, and other computational methods for protein bioinformatics. In this work, we present the Geometric Transformer, a novel geometry-evolving graph transformer for rotation and translation-invariant protein interface contact prediction, packaged within DeepInteract, an end-to-end prediction pipeline. DeepInteract predicts *partner-specific* protein interface contacts (i.e., inter-protein residue-residue contacts) given the 3D tertiary structures of two proteins as input. In rigorous benchmarks, DeepInteract, on challenging protein complex targets from the new Enhanced Database of Interacting Protein Structures (DIPS-Plus) and the 13th and 14th CASP-CAPRI experiments, achieves 17% and 13% top L/5 precision (L: length of a protein unit in a complex), respectively. In doing so, DeepInteract, with the Geometric Transformer as its graph-based backbone, outperforms existing methods for interface contact prediction in addition to other graph-based neural network backbones compatible with DeepInteract, thereby validating the effectiveness of the Geometric Transformer for learning rich relational-geometric features for downstream tasks on 3D protein structures.[1]

1 INTRODUCTION

Interactions of proteins often reflect and directly influence their functions in molecular processes, so understanding the relationship between protein interaction and protein function is of utmost importance to biologists and other life scientists. Here, we study the residue-residue interaction between two protein structures that bind together to form a binary protein complex (i.e., dimer), to better understand how these coupled proteins will function *in vivo*. Predicting where two proteins will interface *in silico* has become an appealing method for measuring the interactions between proteins since a computational approach saves time, energy, and resources compared to traditional methods for experimentally measuring such interfaces (Wells & McClendon (2007)). A key motivation for determining these interface contacts is to decrease the time required to discover new drugs and to advance the study of newly designed proteins (Murakami et al. (2017)).

Existing approaches to interface contact prediction include classical machine learning and deep learning-based methods. These methods traditionally use hand-crafted features to predict which inter-chain pairs of amino acid residues will interact with one another upon the binding of the two protein chains, treating each of their residue pairs as being independent of one another. Recent work on interface prediction (Liu et al. (2020)), however, considers the biological insight that the interaction between two inter-chain residue pairs depends not only on the pairs' features themselves but also on other residue pairs ordinally nearby in terms of the protein complex's sequence. As such, the problem of interface contact prediction became framed as one akin to image segmentation or object detection, opening the door to innovations in interface contact prediction by incorporating the latest techniques from computer vision.

Nonetheless, up to now, no works on *partner-specific* protein interface contact prediction have leveraged two recent innovations to better capture geometric shapes of protein structures and long-range

---

[1]Training and inference code as well as pre-trained models are available at `https://github.com/xxxxx/DeepInteract`

Figure 1: A Mol* (Sehnal et al. (2021)) visualization of interacting protein chains (PDB ID: 3H11).

interactions between amino acids important for accurate prediction of protein-protein interface contacts: (1) geometric deep learning for *evolving* proteins' geometric representations and (2) graph-based self-attention similar to that of Vaswani et al. (2017). Towards this end, we introduce Deep-Interact, an end-to-end deep learning pipeline for protein interface prediction. DeepInteract houses the Geometric Transformer, a new graph transformer designed to exploit protein structure-specific geometric properties, as well as a dilated convolution-based interaction module adapted from Chen et al. (2021) to predict which inter-chain residue pairs comprise the interface between the two protein chains. In response to the exponential rate of progress being made in predicting protein structures *in silico*, we trained DeepInteract end-to-end using DIPS-Plus (Morehead et al. (2021)), to date the largest feature-rich dataset of protein complex structures for machine learning of protein interfaces, to close the gap on a proper solution to this fundamental problem in structural biology.

2 RELATED WORK

Over the past several years, geometric deep learning has become an effective means of automatically learning useful feature representations from structured data (Bronstein et al. (2021)). Previously, geometric learning algorithms like convolutional neural networks (CNNs) and graph neural networks (GNNs) have been used to predict protein interface contacts. Fout et al. (2017) designed a siamese GNN architecture to learn weight-tied feature representations of residue pairs. This approach, in essence, processes subgraphs for each residue in each complex and aggregates node-level features locally using a nearest-neighbors approach. Since this *partner-specific* method derives its training dataset from Docking Benchmark 5 (DB5) Vreven et al. (2015), it is ultimately data-limited. Townshend et al. (2019) represent interacting protein complexes by voxelizing each residue into a 3D grid and encoding in each grid entry the presence and type of the residue's underlying atoms. This *partner-specific* encoding scheme captures static geometric features of interacting complexes, but it is not able to scale well due to its requiring a computationally-expensive spatial resolution of the residue voxels to achieve good results.

Continuing the trend of applying geometric learning to protein structures, Gainza et al. (2020) developed MaSIF to perform *partner-independent* interface region prediction. Likewise, Dai & Bailey-Kellogg (2021) do so with an attention-based GNN. These methods learn to perform binary classification of the residues in both complex structures to identify regions where residues from both complexes are likely to interact with one another. However, because these approaches predict *partner-independent* interface regions, they are less likely to be useful in helping solve related tasks such as drug-protein interaction prediction and protein-protein docking (Ahmad & Mizuguchi (2011)). To date, one of the best result sets obtained by any model for protein interface contact prediction comes from Liu et al. (2020) where high-order (i.e. sequential and coevolution-based) interactions between residues are learned and preserved throughout the network in addition to static geometric features initially embedded in the protein complexes. However, this work, like many of those preceding it, undesirably maintains the trend of reporting model performance in terms of the median area under the receiver operating characteristic which is not robust to extreme class imbal-

ances as often occur in interface contact prediction. In addition, this approach is data-limited as it uses the DB5 dataset and its predecessors to derive both its training data and makes use of only each residue's carbon-alpha ($C\alpha$) atom in deriving its geometric features, ignoring important geometric details provided by an all-atom view of protein structures.

Our work builds on top of prior works by making the following contributions:

- We provide the *first* example of graph self-attention applied to protein interface contact prediction, showcasing its effective use in learning representations of protein geometries to be exploited in downstream tasks.

- We propose the new *Geometric Transformer* which can be used for tasks on 3D protein structures and other 3D graphs. For the problem of interface contact prediction, we train the Geometric Transformer to evolve a geometric representation of protein structures simultaneously with protein sequence and coevolutionary features for the prediction of inter-chain residue-residue contacts. In doing so, we also demonstrate the merit of the recently-released Enhanced Database of Interacting Protein Structures (DIPS-Plus) for interface prediction (Morehead et al. (2021)).

- Our experiments on challenging protein complex targets demonstrate that our proposed method, DeepInteract, achieves state-of-the-art results for interface contact prediction. Through these experiments, we also highlight the need for *more transparent and problem-appropriate metrics* as well as more stringent sequence-based filtering on dataset cross-validation partitions to assess the real-world performance of machine learning models for proteins.

3 DATASETS

The current opinion in the bioinformatics community is that protein sequence features still carry important higher-order information concerning residue-residue interactions (Liu et al. (2020)). In particular, the residue-residue coevolution and residue conservation information obtained through multiple sequence alignments (MSAs) has been shown to contain powerful information concerning intra-chain and even inter-chain residue-residue interactions as they yield a compact representation of residues' coevolutionary relationships (Jumper et al. (2021)).

Keeping this in mind, for our training and validation datasets, we chose to use DIPS-Plus (Morehead et al. (2021)), which is to our knowledge the largest feature-rich dataset of protein complexes for protein interface contact prediction to date. In total, DIPS-Plus contains 42,112 binary protein complexes with positive labels (i.e., 1) for each inter-chain residue pair that are found within 6 Å of each other in the complex's bound (i.e., structurally-conformed) state. The dataset contains a variety of rich residue-level features: (1) an 8-state one-hot encoding of the secondary structure in which the residue is found; (2) a scalar solvent accessibility; (3) a scalar residue depth; (4) a 1×6 vector detailing each residue's protrusion concerning its side chain; (5) a 1×42 vector describing the composition of amino acids towards and away from each residue's side chain; (6) each residue's coordinate number conveying how many residues to which the residue meets a significance threshold, (7) a 1×27 vector giving residues' emission and transition probabilities derived from HH-suite3 (Steinegger et al. (2019)) profile hidden Markov models constructed using MSAs; and (8) amide plane normal vectors for downstream calculation of the angle between each intra-chain residue pair's amide planes.

To compare the performance of DeepInteract with that of state-of-the-art methods, we select 32 challenging and well-diversified homodimers and heterodimers from the test partition of DIPS-Plus to benchmark each method for its competency in predicting interface contacts. In addition, we evaluate each method on 14 homodimers and 5 heterodimers with PDB structures readily and publicly available from the 13th and 14th sessions of CASP-CAPRI (Lensink et al. (2019), Lensink et al. (2021)) since these targets are considered by the bioinformatics community to be challenging for existing interface predictors. For any test complexes derived from multimers (i.e., protein complexes that can contain more than two chains), to represent the complex we chose the pair of chains with the largest number of interface contacts.

Figure 2: DeepInteract overview. Our proposed pipeline separates interface contact prediction into two tasks: (1) learning new node representations from pairs of residue protein graphs inductively and (2) convolving over the new node representations interleaved together to predict pairwise contact probabilities.

To expedite training and validation and to constrain memory usage, beginning with all remaining complexes not chosen for testing, we filtered out all complexes where either chain contains fewer than 20 residues and where the number of possible interface contacts is more than 256^2, leaving us with an intermediate total of 26,504 complexes for training and validation. In DIPS-Plus, binary protein complexes are grouped into shared directories according to whether they are derived from the same parent complex. As such, using a *per-directory* strategy, we randomly designate 80% of these complexes for training and 20% for validation to restrict overlap between our cross-validation datasets. After choosing these targets for testing, we then filter out complexes from our training and validation partitions of DIPS-Plus that contain any chain with over 30% sequence identity to any chain in any complex in our test datasets. This threshold of 30% sequence identity is commonly used in the bioinformatics literature (Jordan et al. (2012), Yang et al. (2013)) to prevent large evolutionary overlap between a dataset's cross-validation partitions. However, most existing works for interface contact prediction do not employ such filtering criteria, so the results reported in these works may be over-optimistic by nature. In performing such sequence-based filtering, we are left with 15,618 and 3,548 binary complexes for training and validation, respectively.

4 METHODS

4.1 PROBLEM FORMULATION

Summarized in Figure 2, we designed DeepInteract, our proposed pipeline for interface contact prediction, to frame the problem of predicting interface contacts *in silico* as a two-part task: The first part is to use attentive graph representation learning to inductively learn new node-level representations from a pair of graphs representing two protein structures. The second part is to interleave the new node representations for each graph into a single interaction tensor, an $\mathbb{M} \times \mathbb{N}$ tensor where $\mathbb{M}$ and $\mathbb{N}$ are the numbers of amino acid residues in the first and second input protein chains, respectively. We use such interaction tensors as input to an interaction module, a convolution-based dense predictor of node-node (i.e., residue-residue) interactions. We denote each protein chain in the complexes as a graph, with nodes corresponding to the chain's amino acid residues represented by their $C\alpha$ atoms and edges corresponding to the residues' k-nearest neighbors. In this setting, we let $k = 20$ as we observed favorable cross entropy loss on our validation dataset with this level of connectivity. We note that this level of connectivity has also proven to be advantageous for prior works developing deep learning approaches for graph-based protein representations (Fout et al. (2017); Ingraham et al. (2019)).

4.2 GEOMETRIC TRANSFORMER ARCHITECTURE

Hypothesizing that a self-attention mechanism that evolves proteins' physical geometries is a key component missing from existing interface contact predictors, we propose the Geometric Trans-

Figure 3: Geometric Transformer overview. The Geometric Transformer uses the Graph Transformer as its foundational architecture. Notably, our final layer of the Geometric Transformer removes the edge update path in the above figure since, in our formulation of the interface prediction problem, only node representations are directly used for the final interface contact prediction.

former, a graph neural network explicitly designed for capturing and iteratively *evolving* protein geometric features. As seen in Figure 3, the Geometric Transformer builds upon the existing Graph Transformer architecture (Dwivedi & Bresson (2021)) to include an edge initialization module and geometry-evolving conformation module as well as subtler architectural enhancements such as moving the network's first normalization layer to precede any affinity score computations for improved training stability (Hussain et al. (2021)). To our knowledge, the Geometric Transformer is the *first* deep learning model that applies multi-head attention to the task of *partner-specific* protein interface contact prediction. The new modules proposed with the Geometric Transformer are described in detail in the following sections.

4.2.1 EDGE REPRESENTATION INITIALIZATION

The Geometric Transformer first creates an initial embedding for each edge given a set of learnable vectors and precomputed features derived from each protein chain's 3D tertiary structure. Formally, we embed each edge e's source and destination nodes n_i and n_j as trainable one-hot vectors indexed by P_i and P_j, the position of node i and j in the chain's underlying amino acid sequence. In the spirit of Ingraham et al. (2019), we then concatenate an edge-wise sinusoidal positional encoding $sin(P_i - P_j)$ for e with an edge weight (i.e., the normalized Euclidean distance between node i and j) to serve as e's original message, providing the network with a directional notion of residue-to-residue distances in protein chains' underlying sequences.

For the edge initializer module's remaining four features, we sought to include enough geometric information for the network to be able to uniquely determine the Euclidean positions of each node's neighboring nodes. For this reason, we adopt similar distance, direction, and orientation descriptors as Ingraham et al. (2019). Finally, we complement the protein backbone-geometric features provided by inter-residue distances, directions, and orientations with the angles between each residue pair's amide plane normal vectors. Once all seven edge initial features are constructed, we then concatenate them together and feed them through a multilayer perceptron (MLP). After doing so, we apply gating to the edges' messages, distances, directions, orientations, and amide angles separately to encourage the network to learn the importance of specific channels in each of these input features.

Geometric Transformer
Conformation Module

Figure 4: Conformation module overview. The Geometric Transformer uses a conformation module in each layer for evolving protein structure information via repeated gating and finally a series of residual connection blocks.

4.2.2 CONFORMATION MODULE

The role of the Geometric Transformer's conformation module, as illustrated in Figure 4, is for it to learn how to iteratively evolve a geometric representation of protein structures by applying repeated gating to our initial geometric edge features. Gating is a technique that has previously been shown to encourage neural networks to not become over-reliant on any particular input feature (Gu et al. (2020)) and, as such, in the Geometric Transformer can be seen as a form of channel-wise dropout for single feature sets. By also employing residual connections from original edge representations to gating-learned edge representations, the conformation module can operate more stably in the presence of multiple neural network layers (He et al. (2016)).

In locating edges with which to update e_{ij}, the Geometric Transformer introduces the notion of a *geometric neighborhood* for edge e_{ij}, treating each edge as a pseudo-node. Precisely, an edge geometric neighborhood, with $n \in \mathbb{Z}^+$, is defined as the $2n$ incoming edges e_{ni}, e_{nj} for e_{ij}'s source and destination nodes, respectively. The intuition behind updating each edge according to its $2n$ nearest edge neighbors is that the geometric relationship between a residue pair, described by their mutual edge's features, can be influenced by the physical constraints imposed by proximal residue-residue geometries. As such, we use these nearby edges during geometric feature updates.

The conformation module's design was inspired by SphereNet (Liu et al. (2021)) and similar graph neural network architectures designed for learning on 3D graphs. What distinguishes the conformation module from the works of others is its incorporation of geometric insights specific to large biomolecules such as proteins. Namely, by including the residue-residue distances, residue-residue local reference frame directions and (quaternion) orientations, and amide plane-amide plane angles, the network is provided with enough information to ascertain the relative coordinates of each neighboring residue from a given residue's local reference frame (Liu et al. (2021)), thereby ensuring the network's capability of adequately learning from 3D structures.

By way of their construction, as described in Section A.2, each of our selected geometric edge features is invariant to rotations and translations of the network's input space. Further, since each node and edge-wise operation we apply to such features is also geometrically invariant, we observe that the Geometric Transformer operates invariantly with respect to translations and rotations in $\mathbb{R}^3$, a desirable property to have when using deep learning architectures to process 3D objects such as proteins.

4.2.3 NODE REPRESENTATION INITIALIZATION

For the node features we used with the Geometric Transformer, we chose to use each of the residue-level features contained in DIPS-Plus that are described succinctly in Section 3. In addition to these node-level features in our protein chain graphs, we include node-wise positional encodings to initialize the Geometric Transformer with information concerning the residue ordering of the chain's underlying sequence as such ordering is important to understanding downstream protein structural,

interactional, and functional properties of each residue. This positional encoding is calculated for each node by applying a min-max normalization of each chain sequence's residue indices P_i.

4.3 INTERACTION MODULE

Upon applying multiple layers of the Geometric Transformer to each pair of input protein chains, we then feed the Geometric Transformer's learned node representations after channel-wise interleaving into our interaction module, consisting of a dilated ResNet module adapted from the intra-chain contact predictor of Chen et al. (2021). The core residual network component in this interaction module consists of four residual blocks differing in the number of internal layers. Each residual block is comprised of several consecutive instance normalization layers and convolutional layers with 64 kernels of size 3×3. The number of layers in each block represents the number of 2D convolution layers in the corresponding component. The final values of the last convolutional layer are added to the output of a shortcut block, which is a convolutional layer with 64 kernels of size 1×1. A squeeze-and-excitation (SE) block (Hu et al. (2018)) is added at the end of each residual block. The SE operation weights each of its channels differently by a trainable 2-layer dense network when creating the output feature maps, so that channel-wise feature responses can be adaptively recalibrated. Ultimately, the output of the interaction module is a probability-valued $\mathbb{M}$ x $\mathbb{N}$ matrix that can be viewed as a heatmap describing which inter-chain residue pairs are likely to be in contact with one another upon binding of the two chains.

5 EXPERIMENTS

5.1 SETUP

For all experiments conducted with DeepInteract, we used 2 layers of the graph neural network chosen for the experiment and 128 intermediate GNN and CNN channels to restrict the time required to train each model. For the Geometric Transformer, we used an edge geometric neighborhood of size $n = 2$ for each edge such that each edge's geometric features are updated by their 4-nearest incoming edges. In addition, we used the Adam optimizer (Kingma & Ba (2014)), a learning rate of $1e^{-3}$, a weight decay rate of $1e^{-2}$, a dropout (i.e., forget) rate of 0.2, and a batch size of 1. We also employed 0.5-threshold gradient value clipping and stochastic weight averaging (Izmailov et al. (2018)). With an early-stopping patience period of 5 epochs, we observed most models converging after approximately 30 training epochs on DIPS-Plus. For our loss function, we used weighted cross entropy with a positive class weight of 5 to help the network overcome the large class imbalance present in interface prediction. All DeepInteract models employed 14 layers of our dilated ResNet architecture described in Section 4.3 and had their top-k precisions averaged over three separate runs, each with a different random seed (standard deviation of top-k precisions in parentheses).

5.2 HYPERPARAMETER SEARCH

The identify our optimal set of model hyperparameters, we performed a manual hyperparameter search over the ranges of $[1e^{-1}, 1e^{-2}, 1e^{-3}, 1e^{-4}, 1e^{-5}, 1e^{-6}]$ and $[1e^{-1}, 1e^{-2}, 1e^{-3}, 1e^{-4}]$ for the learning rate and weight decay rate, respectively. In doing so, we found a learning rate of $1e^{-3}$ and a weight decay rate of $1e^{-2}$ to provide the lowest loss and the highest metric values on our validation dataset. We restricted our hyperparameter search to the learning rate and weight decay rate of our models due to the large computational and environmental costs associated with training each model, however, this suggests that further improvements to our models could be found with a more extensive hyperparameter search such as a grid search over, for example, the models' dropout rate and number of intermediate GNN and CNN channels.

5.3 SELECTION OF BASELINES

In choosing the baseline state-of-the-art methods against which we would compare DeepInteract with various graph-based backbones, we considered the reproducibility and accessibility of the method as the most important factor for its inclusion in our benchmarks to encourage adoption of accessible and transparent benchmarks for future works. That is, we only selected baseline methods that are easy to reproduce or instead simple for the general public to use to make predictions.

Table 1: The average interface prediction precision on two types of DIPS-Plus test targets.

Method	16 (Homo)			16 (Hetero)		
	10	$L/10$	$L/5$	10	$L/10$	$L/5$
BI	0	0	0	0.02	0.02	0.02
DH	0.13	0.12	0.09			
CC				0.18	0.16	0.16
DI (GCN)	0.23 (0.03)	0.21 (0.03)	0.21 (0.01)	0.1 (0.03)	0.1 (0.02)	0.1 (0.02)
DI (GraphTran)	0.25 (0.06)	**0.25** (**0.04**)	0.21 (0.05)	0.12 (0.03)	0.11 (0.03)	0.09 (0.02)
DI (GeoTran)	**0.25** (**0.03**)	0.24 (0.03)	**0.21** (**0.01**)	**0.19** (**0.04**)	**0.17** (**0.04**)	**0.16** (**0.03**)

Table 2: The average interface prediction precision on DIPS-Plus test targets of both types.

Method	32 (Both Types)		
	10	$L/10$	$L/5$
BI	0.01	0.01	0.01
DI (GCN)	0.18 (0.005)	0.17 (0.004)	0.16 (0.01)
DI (GraphTran)	0.2 (0.02)	0.18 (0.02)	0.15 (0.02)
DI (GeoTran)	**0.22** (**0.02**)	**0.2** (**0.02**)	**0.17** (**0.02**)

Since two of the three baseline methods we chose to include, DeepHomo and ComplexContact, do not make both their feature generation and model training source code publicly available, we were restricted to using the version of their public web servers available on 9/20/2021 to make inter-chain interface contact predictions. As such, our selection criterion for each baseline method consequently determined the number of complexes against which we could feasibly test each method, thereby restricting the size of our test datasets to 51 complexes in total. In addition, not all baselines chosen were originally trained for both types of protein complexes (i.e., homodimers and heterodimers), so for these baselines we do not include their results for the type of complex for which they are not respectively designed. To assess models' ability to accurately select residue pairs likely to be in interaction upon binding of two given chains, all methods are scored using the top-k precision metric commonly used for intra-chain contact prediction (Chen et al. (2021)), where $k \in \{10, L/10, L/5\}$ with L being the length of the shortest chain in a given complex. Formally, our definition of a model's top-k precision $prec_k$, where T_{pos_k} represents the number of true positive residue pairs selected from the top-k most probable pairs, is

$$prec_k = \frac{T_{pos_k}}{k}.$$

5.4 DISCUSSION

For brevity, in all experiments, we refer to BIPSPI (Sanchez-Garcia et al. (2018)), DeepHomo (Yan & Huang (2021)), ComplexContact (Zeng et al. (2018)), and DeepInteract as BI, DH, CC, and DI, respectively. In addition, we refer to the Graph Convolutional Network of Kipf & Welling (2016), the Graph Transformer of Dwivedi & Bresson (2021), and the Geometric Transformer as GCN, GraphTran, and GeoTran, respectively. Each method predicts interfacing residue pairs subject to the (on average) 1:1000 positive-negative class imbalance imposed by the biological sparsity of true interface contacts.

Table 1 demonstrates that DeepInteract outperforms existing state-of-the-art methods for interface contact prediction on DIPS-Plus with both types of protein complexes, homodimers (homo) where the two chains are of the same protein and heterodimers (hetero) where the two chains are from different proteins. Table 2 shows the average precision of DeepInteract across both complex types. Since future users of DeepInteract may want to predict interface contacts for either type of complex, we consider a method's type-averaged top-k precision as an important metric for which to optimize.

Likewise, Tables 3 and 4 present the average top-k precision of DeepInteract on 19 challenging protein complexes (14 homodimers and 5 heterodimers) from the 13th and 14th rounds of the joint CASP-CAPRI meeting. In them, we once again see DeepInteract exceed the precision of state-

Table 3: The average interface prediction precision on dimers from CASP-CAPRI 13 & 14.

	14 (Homo)			5 (Hetero)		
Method	10	$L/10$	$L/5$	10	$L/10$	$L/5$
BI	0	0	0	0.04	0	0.03
DH	0.02	0.02	0.02			
CC				0.06	0.08	0.05
DI (GCN)	0.12 (0.01)	0.1 (0.02)	0.09 (0.03)	0.1 (0.04)	0.1 (0.03)	0.09 (0.01)
DI (GraphTran)	0.07 (0.04)	0.07 (0.04)	0.07 (0.03)	0.2 (0.02)	0.2 (0.02)	0.17 (0.02)
DI (GeoTran)	**0.14** (**0.03**)	**0.13** (**0.01**)	**0.11** (**0.02**)	**0.23** (**0.04**)	**0.23** (**0.03**)	**0.20** (**0.04**)

Table 4: The average interface prediction precision across all targets from CASP-CAPRI 13 & 14.

	19 (Both Types)		
Method	10	$L/10$	$L/5$
BI	0.01	0	0.01
DI (GCN)	0.11 (0.02)	0.1 (0.03)	0.09 (0.02)
DI (GraphTran)	0.11 (0.04)	0.1 (0.04)	0.1 (0.03)
DI (GeoTran)	**0.17** (0.03)	**0.16** (0.02)	**0.13** (0.01)

of-the-art interface contact predictors for both complex types. In addition, we see that combining DeepInteract with the Geometric Transformer offers improvements to top-k precision for both homodimers and heterodimers compared to using either a GCN or a Graph Transformer-based GNN backbone. Such a result confirms our hypothesis that the Geometric Transformer's geometric self-attention mechanism can enable enhanced prediction performance for downstream tasks on 3D protein structures, using interface contact prediction as a case study.

An interesting future experiment to run involves using the structures of chains generated by AlphaFold2 (Jumper et al. (2021)) as the inputs to our DeepInteract models while benchmarking on publicly available CASP-CAPRI 13-14 targets. Doing so, however, would require extensive fine-tuning of AlphaFold2's input feature generation to ensure that no CASP-CAPRI target overlaps widely with a target included in AlphaFold2's training dataset. As such, we defer an exploration of this idea to future works.

6 CONCLUSION

In this work, we presented a DeepInteract which introduces the geometry-evolving Geometric Transformer for protein structures and showcases its use in predicting inter-chain residue-residue interactions in protein complexes. We foresee several other uses of the Geometric Transformer in geometric deep learning of protein structures such as protein tertiary and quaternary structure quality assessment and refinement as well as residue disorder prediction, simply to name a few. One limitation of the existing design for the Geometric Transformer is the $O(n^2)$ computational complexity associated with its dot product self-attention mechanism. With the advent of more efficient alternatives to self-attention, we hope to overcome this limitation with sparse attention variants like those of the Nyströmformer (Xiong et al. (2021)) in future works. In addition, for future work, we plan to investigate how to integrate the Geometric Transformer's conformation module for evolving geometric representations into equivariant machine learning architectures such as the Equivariant Graph Neural Network (EGNN) by Satorras et al. (2021). Equivariant updates to rich geometric features is an interesting avenue for future research that we hope to explore further.

ACKNOWLEDGMENTS

The project is partially supported by two NSF grants (DBI 1759934 and IIS 1763246), one NIH grant (GM093123), three DOE grants (DE-SC0020400, DE-AR0001213, and DE-SC0021303), and the computing allocation on the Summit compute cluster provided by Oak Ridge Leadership Computing Facility (Contract No. DE-AC05-00OR22725).

ETHICS STATEMENT

DeepInteract is designed to be used for machine learning of protein molecular data. It makes use of only publicly available information concerning biomolecular structures and their interactions. Consequently, all data used to create DeepInteract models do not contain any personally identifiable information or offensive content. As such, we do not foresee negative societal impacts as a consequence of DeepInteract or the Geometric Transformer being made publicly available. Furthermore, future adaptions or enhancements to DeepInteract may benefit the machine learning community and, more broadly, the scientific community by providing meaningful refinements to a transparent and extensible pipeline for geometric deep learning of protein-protein interactions.

REPRODUCIBILITY STATEMENT

To enable this work to be reproducible by others, we have thoroughly documented two methods for running predictions with DeepInteract using a provided PyTorch Lightning model checkpoint (Falcon (2019)) and one method for training DeepInteract models in an associated GitHub repository. The most convenient prediction method describes how to run DeepInteract as a platform-agnostic Docker container. The second method, for both training and prediction, details how users can piece-wise install DeepInteract and its data and software dependencies on a Linux-based operating system. An anonymized version of this GitHub repository, with version history and personally identifiable artifacts removed, has been uploaded alongside this manuscript at the time of submission.

REFERENCES

Shandar Ahmad and Kenji Mizuguchi. Partner-aware prediction of interacting residues in protein-protein complexes from sequence data. *PloS one*, 6(12):e29104, 2011.

Michael M. Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges, 2021.

Chen Chen, Tianqi Wu, Zhiye Guo, and Jianlin Cheng. Combination of deep neural network with attention mechanism enhances the explainability of protein contact prediction. *Proteins: Structure, Function, and Bioinformatics*, 89(6):697–707, 2021. doi: https://doi.org/10.1002/prot.26052. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/prot.26052.

Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 801–818, 2018.

Bowen Dai and Chris Bailey-Kellogg. Protein Interaction Interface Region Prediction by Geometric Deep Learning. *Bioinformatics*, 03 2021. ISSN 1367-4803. doi: 10.1093/bioinformatics/btab154. URL https://doi.org/10.1093/bioinformatics/btab154. btab154.

Vijay Prakash Dwivedi and Xavier Bresson. A generalization of transformer networks to graphs, 2021.

et al. Falcon, WA. Pytorch lightning. *GitHub. Note: https://github.com/PyTorchLightning/pytorch-lightning*, 3, 2019.

Alex Fout, Jonathon Byrd, Basir Shariat, and Asa Ben-Hur. Protein interface prediction using graph convolutional networks. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30, pp. 6530–6539. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/f507783927f2ec2737ba40afbd17efb5-Paper.pdf.

Pablo Gainza, Freyr Sverrisson, Frederico Monti, Emanuele Rodola, D Boscaini, MM Bronstein, and BE Correia. Deciphering interaction fingerprints from protein molecular surfaces using geometric deep learning. *Nature Methods*, 17(2):184–192, 2020.

Albert Gu, Caglar Gulcehre, Thomas Paine, Matt Hoffman, and Razvan Pascanu. Improving the gating mechanism of recurrent neural networks. In *International Conference on Machine Learning*, pp. 3800–3809. PMLR, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7132–7141, 2018.

Md Shamim Hussain, Mohammed J Zaki, and Dharmashankar Subramanian. Edge-augmented graph transformers: Global self-attention is enough for graphs. *arXiv preprint arXiv:2108.03348*, 2021.

John Ingraham, Vikas Garg, Regina Barzilay, and Tommi Jaakkola. Generative models for graph-based protein design. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/f3a4ff4839c56a5f460c88cce3666a2b-Paper.pdf.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Rafael A Jordan, EL-Manzalawy Yasser, Drena Dobbs, and Vasant Honavar. Predicting protein-protein interface residues using local surface structural similarity. *BMC bioinformatics*, 13(1): 1–14, 2012.

John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *Nature*, pp. 1–11, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Marc F Lensink, Guillaume Brysbaert, Nurul Nadzirin, Sameer Velankar, Raphaël AG Chaleil, Tereza Gerguri, Paul A Bates, Elodie Laine, Alessandra Carbone, Sergei Grudinin, et al. Blind prediction of homo-and hetero-protein complexes: The casp13-capri experiment. *Proteins: Structure, Function, and Bioinformatics*, 87(12):1200–1221, 2019.

Marc F Lensink, Guillaume Brysbaert, Théo Mauri, Nurul Nadzirin, Sameer Velankar, Raphael AG Chaleil, Tereza Clarence, Paul A Bates, Ren Kong, Bin Liu, et al. Prediction of protein assemblies, the next frontier: The casp14-capri experiment. *Proteins: Structure, Function, and Bioinformatics*, 2021.

Yi Liu, Hao Yuan, Lei Cai, and Shuiwang Ji. Deep learning of high-order interactions for protein interface prediction. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 679–687, 2020.

Yi Liu, Limei Wang, Meng Liu, Xuan Zhang, Bora Oztekin, and Shuiwang Ji. Spherical message passing for 3d graph networks. *arXiv preprint arXiv:2102.05013*, 2021.

Alex Morehead, Chen Chen, Ada Sedova, and Jianlin Cheng. Dips-plus: The enhanced database of interacting protein structures for interface prediction, 2021.

Yoichi Murakami, Lokesh P Tripathi, Philip Prathipati, and Kenji Mizuguchi. Network analysis and in silico prediction of protein–protein interactions with applications in drug discovery. *Current opinion in structural biology*, 44:134–142, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Ruben Sanchez-Garcia, C O S Sorzano, J M Carazo, and Joan Segura. BIPSPI: a method for the prediction of partner-specific protein–protein interfaces. *Bioinformatics*, 35(3):470–477, 07 2018. ISSN 1367-4803. doi: 10.1093/bioinformatics/bty647. URL `https://doi.org/10.1093/bioinformatics/bty647`.

Víctor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E(n) equivariant graph neural networks. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 9323–9332. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/satorras21a.html`.

David Sehnal, Sebastian Bittrich, Mandar Deshpande, Radka Svobodová, Karel Berka, Václav Bazgier, Sameer Velankar, Stephen K Burley, Jaroslav Koča, and Alexander S Rose. Mol* Viewer: modern web app for 3D visualization and analysis of large biomolecular structures. *Nucleic Acids Research*, 49(W1):W431–W437, 05 2021. ISSN 0305-1048. doi: 10.1093/nar/gkab314. URL `https://doi.org/10.1093/nar/gkab314`.

Martin Steinegger, Markus Meier, Milot Mirdita, Harald Vöhringer, Stephan J Haunsberger, and Johannes Söding. Hh-suite3 for fast remote homology detection and deep protein annotation. *BMC bioinformatics*, 20(1):1–15, 2019.

Raphael Townshend, Rishi Bedi, Patricia Suriana, and Ron Dror. End-to-end learning on 3d protein structure for interface prediction. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32, pp. 15642–15651. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/6c7de1f27f7de61a6daddfffbe05c058-Paper.pdf`.

Guido Van Rossum and Fred L. Drake. *Python 3 Reference Manual*. CreateSpace, Scotts Valley, CA, 2009. ISBN 1441412697.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.

Thom Vreven, Iain H Moal, Anna Vangone, Brian G Pierce, Panagiotis L Kastritis, Mieczyslaw Torchala, Raphael Chaleil, Brian Jiménez-García, Paul A Bates, Juan Fernandez-Recio, et al. Updates to the integrated protein–protein interaction benchmarks: docking benchmark version 5 and affinity benchmark version 2. *Journal of molecular biology*, 427(19):3031–3041, 2015.

James A Wells and Christopher L McClendon. Reaching for high-hanging fruit in drug discovery at protein–protein interfaces. *Nature*, 450(7172):1001–1009, 2007.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn Fung, Yin Li, and Vikas Singh. Nystr\" omformer: A nystr\" om-based algorithm for approximating self-attention. *arXiv preprint arXiv:2102.03902*, 2021.

Yumeng Yan and Sheng-You Huang. Accurate prediction of inter-protein residue–residue contacts for homo-oligomeric protein complexes. *Briefings in Bioinformatics*, 2021.

Jianyi Yang, Ambrish Roy, and Yang Zhang. Protein–ligand binding site recognition using complementary binding-specific substructure comparison and sequence profile alignment. *Bioinformatics*, 29(20):2588–2595, 2013.

Hong Zeng, Sheng Wang, Tianming Zhou, Feifeng Zhao, Xiufeng Li, Qing Wu, and Jinbo Xu. Complexcontact: a web server for inter-protein contact prediction using deep learning. *Nucleic acids research*, 46(W1):W432–W437, 2018.

Figure 5: The network's softmax contact probabilities (leftmost column), 0.5 positive probability-thresholded predictions (middle column), and ground-truth labels (rightmost column), respectively, for PDB ID: 4HEQ (first row) and 6TRI (second row), two of the complexes in our test datasets.

A APPENDIX

A.1 SAMPLE INTERFACE CONTACT PREDICTIONS

In the first row of Figure 5, we see predictions made by DeepInteract for a homodimer complex from our test partition of DIPS-Plus (i.e., PDB ID: 4HEQ). The leftmost image represents the softmax contact probability map. The center image corresponds to the same contact map after having a 0.5 probability threshold applied to it such that residue pairs with at least a 50% probability of being in interaction with each other have their interaction probabilities rounded up to 1.0. The rightmost image is the ground-truth contact map. Similarly, in the second row of Figure 5, we are shown the cropped predictions made by DeepInteract for a CASP-CAPRI test heterodimer (i.e., PDB ID: 6TRI).

A.2 DEFINITION OF EDGE GEOMETRIC FEATURES

Similar to Ingraham et al. (2019), we construct a local reference frame (i.e., an orientation $\boldsymbol{O}_i$) for each protein chain graph's residues. Representing each residue by its Cartesian coordinates $\boldsymbol{x}_i$, we formally define

$$\boldsymbol{u}_i = \frac{\boldsymbol{x}_i - \boldsymbol{x}_{i-1}}{\|\boldsymbol{x}_i - \boldsymbol{x}_{i-1}\|}, \quad \boldsymbol{n}_i = \frac{\boldsymbol{u}_i \times \boldsymbol{u}_{i+1}}{\|\boldsymbol{u}_i \times \boldsymbol{u}_{i+1}\|}, \quad \boldsymbol{b}_i = \frac{\boldsymbol{u}_i - \boldsymbol{u}_{i+1}}{\|\boldsymbol{u}_i - \boldsymbol{u}_{i+1}\|}.$$

with $\boldsymbol{n}_i$ being the unit vector normal to the plane formed by the rays $(\boldsymbol{x}_{i-1} - \boldsymbol{x}_i)$ and $(\boldsymbol{x}_{i+1} - \boldsymbol{x}_i)$ and $\boldsymbol{b}_i$ being the negative bisector of this plane. We then define $\boldsymbol{O}_i$ as

$$\boldsymbol{O}_i = [\boldsymbol{b}_i \ \ \boldsymbol{n}_i \ \ \boldsymbol{b}_i \times \boldsymbol{n}_i].$$

Having defined the orientation $\boldsymbol{O}_i$ for each residue that describes the local reference frame $(\boldsymbol{x}_i, \boldsymbol{O}_i)$. To provide the Geometric Transformer with an alternative notion of residue-residue orientations, we define the unit vector normal to the amide plane for residue i as

$$\boldsymbol{U}_i = (\boldsymbol{x}_{C\alpha_i} - \boldsymbol{x}_{C\beta i}) \times (\boldsymbol{x}_{C\beta_i} - \boldsymbol{x}_{N_i})$$

where $\boldsymbol{x}_{C\alpha_i}$, $\boldsymbol{x}_{C\beta i}$, and $\boldsymbol{x}_{Ni}$ are the Cartesian coordinates of the residue's carbon-alpha ($C\alpha$), carbon-beta ($C\beta$), and nitrogen (N) atoms, respectively.

Table 5: The protein complexes selected from DIPS-Plus for testing interface contact predictors.

PDB ID	Chain 1	Chain 2	Type	PDB ID	Chain 1	Chain 2	Type
1BHN	B	D	Homo	1AON	R	S	Hetero
1KPT	A	B	Homo	1BE3	D	E	Hetero
1SDU	A	B	Homo	1GK8	K	M	Hetero
1UZN	A	B	Homo	1OCZ	R	V	Hetero
2B4H	A	B	Homo	1UWA	A	I	Hetero
2G30	C	E	Homo	3A6N	A	E	Hetero
2GLM	E	F	Homo	3ABM	D	K	Hetero
2IUO	D	J	Homo	3JRM	H	I	Hetero
3BXS	A	B	Homo	3MG6	D	E	Hetero
3CT7	B	E	Homo	3MNN	C	F	Hetero
3NUT	A	D	Homo	3T1Y	E	H	Hetero
3RE3	B	C	Homo	3TUY	D	E	Hetero
4HEQ	A	B	Homo	3VYG	G	H	Hetero
4LIW	A	B	Homo	4A3D	C	L	Hetero
4OTA	D	F	Homo	4CW7	G	H	Hetero
4TO9	B	D	Homo	4DR5	G	I	Hetero

Finally, we relate the reference frames for residues i and j by describing their edge geometric features as

$$\left(\boldsymbol{r}(\|\boldsymbol{x}_j - \boldsymbol{x}_i\|), \ \ \boldsymbol{O}_i^T \frac{\boldsymbol{x}_j - \boldsymbol{x}_i}{\|\boldsymbol{x}_j - \boldsymbol{x}_i\|}, \ \ \boldsymbol{q}(\boldsymbol{O}_i^T \boldsymbol{O}_j), \ \ \boldsymbol{a}(\boldsymbol{U}_i, \boldsymbol{U}_j) \right)$$

with the first term $\boldsymbol{r}()$ being a distance encoding of 16 Gaussian RBFs spaced isotropically from 0 to 20 Å, the second term describing the relative direction of $\boldsymbol{x}_j$ with respect to reference frame $(\boldsymbol{x}_i, \boldsymbol{O}_i)$, the third term detailing an orientation encoding $\boldsymbol{q}()$ of the quaternion representation of the rotation matrix $\boldsymbol{O}_i^T \boldsymbol{O}_j$, representing each quaternion with respect to its vector of real coefficients, and the fourth term $\boldsymbol{a}()$ representing the angle between the amide plane normal vectors $\boldsymbol{U}_i$ and $\boldsymbol{U}_j$.

Our definition of these edge geometric features makes use of the backbone atoms for each residue. As such, the graph representation of protein chains we use with the Geometric Transformer encodes not only residue-level geometric features but also those derived from an atomic view of protein structures. We hypothesized this hybrid approach to modeling protein structure geometries would have a noticeable downstream effect on interface contact prediction precision via the node and edge representations learned by the Geometric Transformer. This hypothesis is confirmed in Section 5.4.

A.3 PROTEIN COMPLEXES SELECTED FOR TESTING

Table 5 displays the PDB and chain IDs of DIPS-Plus protein complexes chosen for testing. Likewise, in Table 6, we see the PDB and chain IDs of CASP-CAPRI 13-14 targets chosen for testing.

A.4 ALTERNATIVE NETWORKS FOR THE INTERACTION MODULE

We, like Liu et al. (2020), note that the task of interface prediction bears striking similarities to dense prediction tasks in computer vision (e.g., semantic segmentation). In this train of thought, we experimented with several semantic segmentation models as replacements for our interaction module's dilated ResNet, one namely being DeepLabV3Plus (Chen et al. (2018)). We observed a strong propensity of such semantic segmentation models to identify interaction regions well but to do so with low *pixel-wise* precision. We hypothesize this is due to the downsampling and upsampling methods often employed within such architectures that invariably degrade the original input tensor's representation resolution. We also experimented with several state-of-the-art Vision Transformer and MLP-based models for computer vision but ultimately found their algorithmic complexity, memory usage, or input shape requirements to be prohibitive for this task, since our test datasets' input protein complexes can vary greatly in size to contain between 20 residues and over

Table 6: The CASP-CAPRI 13-14 protein complexes selected for testing interface contact predictors.

PDB ID	Chain 1	Chain 2	Type
5W6L	A	B	Homo
6D2V	A	B	Homo
6E4B	A	B	Homo
6FXA	C	D	Homo
6HRH	A	B	Homo
6MXV	A	B	Homo
6N64	A	B	Homo
6N91	A	B	Homo
6NQ1	A	B	Homo
6QEK	A	B	Homo
6UBL	A	B	Homo
6UK5	A	B	Homo
6YA2	A	B	Homo
7CWP	C	D	Homo
6CP8	A	C	Hetero
6D7Y	A	B	Hetero
6TRI	A	B	Hetero
6XOD	A	B	Hetero
7M5F	A	C	Hetero

2,000 residues in length. As such, for the design of DeepInteract's interaction module, we experimented primarily with convolution-based architectures that do not employ such sampling techniques or pose limited input size constraints.

A.5 HARDWARE USED

The Oak Ridge Leadership Facility (OLCF) at the Oak Ridge National Laboratory (ORNL) is an open science computing facility that supports HPC research. The OLCF houses the Summit compute cluster. Summit, launched in 2018, delivers 8 times the computational performance of Titan's 18,688 nodes, using only 4,608 nodes. Like Titan, Summit has a hybrid architecture, and each node contains multiple IBM POWER9 CPUs and NVIDIA Volta GPUs all connected with NVIDIA's high-speed NVLink. Each node has over half a terabyte of coherent memory (high bandwidth memory + DDR4) addressable by all CPUs and GPUs plus 800GB of non-volatile RAM that can be used as a burst buffer or as extended memory. To provide a high rate of I/O throughput, the nodes are connected in a non-blocking fat-tree using a dual-rail Mellanox EDR InfiniBand interconnect. We used the Summit compute cluster to train all our models.

A.6 SOFTWARE USED

In addition, we used Python 3.8 (Van Rossum & Drake (2009)), PyTorch 1.7.1 (Paszke et al. (2019)), and PyTorch Lightning 1.4.8 (Falcon (2019)) to run our deep learning experiments. PyTorch Lightning was used to facilitate model checkpointing, metrics reporting, and distributed data parallelism across 72 Tesla V100 GPUs. A more in-depth description of the software environment used to train and predict with DeepInteract models can be found at https://github.com/xxxxx/DeepInteract.